

ANN'S COPY

SEISMIC FIELD DATA FORM 23432

DFS V SYSTEM


IDENTIFICATION				SHOT				SPREAD				TAPE			GAIN		FILTERS			REPRODUCE/DISPLAY			REMARKS							
PHOFILE	REEL NUMBER	FILE NUMBER	SHOT CAL	PLAY	TIME	SIZE	TOP BOT	NO CAPS	CODE	S.P. OFFSET	NO. 1 DIR	CODE	SPREAD	SPREAD	SET UP	SAMPLE RATE	RECORD LENGTH	PARITY	ERRORS	MODE	GAIN	HIGH CUT FREQ.		LOW CUT FREQ.	NOTCH IN/OUT	MODE	INIT. GAIN	TRIP. GENS.	HIGH CUT	LOW CUT
1	751891	521				50	70% 90%	2			N				45	5	✓	6		AGC	IFP	120	8	out	AGC	18	18	out	out	F-1 - 6+4
2	11	522				50	70% 90%	2							49															F-5 - 7+4
3	11	523				50	70% 90%	2							53															F-9 - 8+4
4	11	524				50	70% 90%	2							57															F-13 - 9+4

Q roots
F-1 - 6+4
F-5 - 7+4
F-9 - 8+4
F-13 - 9+4

SEISMOMETER AND SPREAD INFORMATION

SPST/PP	NO./GP	INT.	GROUP PATTERN	GP INT.	SPREAD PATTERN

SHOT CONFIGURATION



DFS V SYSTEM PARAMETERS:

GAIN CONSTANT 36 dB
 FORMAT TYPE: 0-1024
 P-SEG B SEG C
 PACKING DENSITY: 0.800 1600 PE
 NUMBER DATA FRAMES: 024 48 96
 OTHER:
 MISC:

MISCELLANEOUS INFORMATION:

AGC FUNCTIONS: AGC PGC GAGC
 GALVO: GALVO OTA 5
 AUX: 5
 AGC Option Settings:
 Trip Sens: _____ dB Initial Gain: _____ Final Gain: _____
 Trip: _____ Secs PGC Rate: _____ dB/Sec.
 AGC Speed: _____ Energy Monitor Channel
 Monitor Type:
 RAW NOT RAW
 OTHER:

GENERAL CONSTANTS:

--	--	--	--	--	--	--	--	--	--

11/11

11/11

LAND SEISMIC RECORDING LOG

15.5 Hours

CLIENT: <u>Husky</u> PROSPECT: <u>NPR-A</u> AREA: <u>BARROW</u> LINE NO.: <u>606</u>	
PARTY NO.: <u>1182</u> INST. ENG.: <u>William</u> DATE: <u>606</u>	
INSTRUMENT: <input checked="" type="checkbox"/> 1 SYSTEM <input type="checkbox"/> 2 SYSTEMS <input type="checkbox"/> 1-24 & 25-48 <input checked="" type="checkbox"/> CDS <input type="checkbox"/> 1-48 & 49-96 <input checked="" type="checkbox"/> EVENS	
TYPE: <input type="checkbox"/> DFB <input type="checkbox"/> DFB III <input type="checkbox"/> D-DFB X <input type="checkbox"/> OTHER	
NO. TRACKS: <input checked="" type="checkbox"/> 9 TRACK <input type="checkbox"/> 21 TRACK	
FORMAT: <u>SEL</u> <input type="checkbox"/> GAPPED <input type="checkbox"/> UNGAPPED	
PACKING DENSITY: (10) <input type="checkbox"/> 356 BPI (11) <input type="checkbox"/> 400 BPI (12) <input type="checkbox"/> 712 BPI (13) <input type="checkbox"/> 1000 BPI	
NO. BYTES IN HEADER REC.: _____ NO. BYTES IN RECORD ID.: _____ NO. BYTES PER SCAN: <u>134</u>	
RECORD NUMBERS: <u>B-DEC</u> <input type="checkbox"/> OCT	
GAIN CONSTANT: <u>36</u> INPUT IMPEDANCE: <u>20,000</u> ohms	
CONFIGURATION (MAG TAPE): FIELD TRACE NOS.: <u>1-48</u> DATA CHANNEL NOS.: <u>1-48</u> (ON MAG TAPE)	
AUXILIARY DATA: (1) <u>7B</u> (2) <u>4H</u> (3) _____ (4) _____ (5) _____ (6) _____	
AUXILIARY CHANNEL NOS.: <u>3</u> <u>4</u>	
PARAMETER: RECORD LENGTH: <u>6</u> sec SAMPLE RATE: <input type="checkbox"/> 1 sec <input type="checkbox"/> 2 sec <input type="checkbox"/> 4 sec	
GAIN MODE: <input type="checkbox"/> INITIAL <input type="checkbox"/> MANUAL <input type="checkbox"/> OPERATE	
FILTERS: <u>8</u> Hz LO CUT <u>18</u> Hz HZ SLOPE <u>18</u> HZ CUT <u>70</u> HZ SLOPE <u>70</u> HZ	
DISPLAY: MODE: <input type="checkbox"/> ACC <input type="checkbox"/> FLOAT <input type="checkbox"/> AMPLIFIER <input type="checkbox"/> DIRECT	
INITIAL GAIN: <u>18</u> TRIP SENS.: <u>18</u> POLARITY CONVENTION: <input type="checkbox"/> NEGATIVE <input type="checkbox"/> POSITIVE	
CFS I: TYPE STACK: _____ GATE LENGTH: _____ RECORD REJECTION: _____ NOISE REDUCTION: _____	
SOURCE: TYPE: <input checked="" type="checkbox"/> DYNAMIC <input type="checkbox"/> VIBROSEIS <input type="checkbox"/> OTHER	
PATTERN: <u>Single hole - inline</u> NO. OF POSITIONS: _____ INLINE SPACING: _____	
CHG/ HOLE: <u>50</u> HOLE DEPTH: <u>90</u> SWEEP START: _____ SWEEP END: _____	
RECEIVER: TYPE: <u>GSC-20d</u> PATTERN: <u>inline</u> NO. OF ELEMENTS: <u>18</u>	
CONNECTION: <u>Series - Parallel</u> RESISTANCE: <u>560</u> OHMS STAGGER: _____	
SPREAD: NO. OF GROUPS: <u>48</u> GROUP INTERVAL: <u>330'</u> SHOTPOINT INTERVAL: <u>1320'</u>	
OFFSET GROUP: <u>7755'</u> OFFSET GROUP: <u>24</u> <u>165'</u> OFFSET GROUP: <u>25</u> <u>165'</u>	

DIAGRAMS/MISC. INFORMATION:

SHOTPOINT NO.	TR 1		TR 2		SHOT		DIR	COP SWITCH	SPREAD		REMARKS	CORR STACK			
	REEL NO.	REC.	REEL NO.	REC.	SIZE	DEPTH			NO.	OFFSET		LINE	GROUPS	TR 1	TR 2
5	7511897	535			50	70	1		29	F-17 - 10+4	Recorder @ SP-10				
6		536			50	70	2		33	F-21 - 11+4					
7		537			50	70	3	400' South	37	SP-14 - 12+4	Inline offset				
8		538			50	70	4		41	2H - 13+4					
9		539			50	70	6		45	3+1 - 14+4					
10		540			50	70	6		49	4+1 - 15+4	Recorder @ SP-15				
11		541			50	70	7		33	5+1 - 16+4					
12		542			50	70	8		37	6+1 - 17+4					
13		543			50	70	9		41	7+1 - 18+4					
14		544			50	70	10		45	8+1 - 19+4					
15		545			50	70	11		29	9+1 - 20+4	Recorder @ SP-20				
16		546			50	70	12		33	10+1 - 21+4					
17		547			50	70	13		37	11+1 - 22+4					
18		548			50	70	14		41	12+1 - 23+4					
19		549			50	70	15		45	13+1 - 24+4					
20		550			50	70	16		49	14+1 - 25+4					
21		551			50	70	17		53	15+1 - 26+4					
22		552			50	70	18		57	16+1 - 27+4					
23		553			50	70	18		29	17+1 - 28+4	Recorder @ SP-28				
24		554			50	70	20		33	18+1 - 29+4					

LAND SEISMIC RECORDING LOG

CLIENT: Husky		PROSPECT: NPR-A		AREA: BARROW		LINE NO: 606	
PARTY NO: 1182		INST. ENG: Widdham		DATE: 2 DAY 25 79		MO: 2 DAY: 25 YE: 79	
INSTRUMENT: <input checked="" type="checkbox"/> 1 SYSTEM <input checked="" type="checkbox"/> 1-24 & 25-48 <input checked="" type="checkbox"/> 2 SYSTEMS <input type="checkbox"/> 1-24 & 49-96		MODES: <input checked="" type="checkbox"/> ODDS <input type="checkbox"/> EVENS		TYPE: <input type="checkbox"/> OPS III <input type="checkbox"/> OPS IV <input type="checkbox"/> OTHER		FORMAT: B <input type="checkbox"/> 9 TRACK <input type="checkbox"/> 21 TRACK	
NO. BYTES IN HEADER REC:		NO. BYTES IN RECORD ID:		NO. BYTES PER SCAN: 134		RECORD NUMBERS: 256 <input type="checkbox"/> DCI <input type="checkbox"/> OCF	
CONFIGURATION (MAG TAPE):		FIELD TRACE NOS: 1-48		DATA CHANNEL NOS: 1-48 (ON MAG TAPE)		AUXILIARY DATA: 18 4H	
PARAMETER: RECORD LENGTH: 6		SAMPLE RATE: <input type="checkbox"/> 1 sec <input type="checkbox"/> 4 sec		GAIN MODE: <input type="checkbox"/> INITIAL <input type="checkbox"/> MANUAL <input type="checkbox"/> FINAL		FILTERS: 18 18 128 70	
DISPLAY: <input type="checkbox"/> MODES <input type="checkbox"/> FLOAT <input type="checkbox"/> AMPLIFIER <input type="checkbox"/> DIRECT		INITIAL GAIN: 18 db		STRIP SENS: 18 db		POLARITY CONVENTION: <input type="checkbox"/> POSITIVE <input type="checkbox"/> NEGATIVE	
CFS I: TYPE STACK:		GATE LENGTH:		RECORD REJECTION:		NOISE REDUCTION: <input type="checkbox"/> CORN SCALING: <input type="checkbox"/> C.U. NORM/ALT SW	
SOURCE: TYPE: <input checked="" type="checkbox"/> DYNAMITE <input type="checkbox"/> VIBROSEIS <input type="checkbox"/> OTHER		PATTERN: Single hole - Inline		NO. OF POSITIONS: 18		INLINE SPACING: 18'	
RECEIVER: TYPE: GSC-20d		PATTERN: Inline		NO. OF ELEMENTS: 18		INLINE SPACING: 18'	
CONNECTION: Series - Parallel		RESISTANCE: 560 ohms		STAGGER:		LENGTH: 18'	
SPREAD: NO. OF GROUPS: 48		GROUP INTERVAL: 330'		SHOTPOINT INTERVAL: 1320'		FIELD: 6	
OFFSET GROUP 1: 7755'		OFFSET GROUP 2: 165'		OFFSET GROUP 3: 165'		DIRECTION OF PROGRESSION: N-75	
OFFSET GROUP 4: 165'		OFFSET GROUP 5: 165'		OFFSET GROUP 6: 165'		LEADING GROUP: 48	

DIAGRAMS/MISC. INFORMATION:

SHOTPOINT	TR 1 to 48		TR 49 to 96		SHOT		SPREAD		REMARKS	CORR STACK	
	REEL NO	REC.	REEL NO	REC.	SIZE	DEPTH	NO.	OFFSET		DIR	CDP SWITCH
25	751887	555			50	7021		37	191	- 30+4	
26		556			50	7022		25	201	- 31+4	5 Recorder @ SP-32
27		557			50	7023		29	211	- 32+4	
28		558			50	7024		33	221	- 33+4	
29		559			50	7025		37	231	- 34+4	
30		560			50	7026		41	241	- 35+4	
31		561			50	7027		29	251	- 36+4	6 Recorder @ SP-36 File 561 mixed
32		562-563			50	7028		33	261	- 37+4	
33		564			50	7029		37	271	- 38+4	
34		565			50	7030		41	281	- 39+4	
35		566			50	7031		25	291	- 40+4	7 Recorder @ SP-41
36		567			50	7032		29	301	- 41+4	
37		568			50	7033		33	311	- 42+4	
38		569			50	7034		37	321	- 43+4	
39		570			50	7035		29	331	- 44+4	8 Recorder @ SP-44
40		571			50	7036		33	341	- 45+4	
41		572			50	7037		37	351	- 46+4	
42		573			50	7038		41	361	- 47+4	
43		574			50	7039		45	371	- 48+4	
44		575			50	7040		49	381	- 49+4	

LAND SEISMIC RECORDING LOG

CLIENT: Haskey PARTY NO.: 1182 INST. ENG.: Windham PROSPECT.: NPR-A AREA: Barrow		LINE NO.: 606 DATE: NO 2 DAY 25 1977
INSTRUMENT: <input checked="" type="checkbox"/> 1 SYSTEM <input type="checkbox"/> 2 SYSTEMS NO. BYTES IN HEADER REC: _____ NO. BYTES IN RECORD ID: _____ NO. BYTES PER SCAN: 134		TRACK: <input checked="" type="checkbox"/> 9 TRACK <input type="checkbox"/> 21 TRACK RECORD NUMBERS: 0 DEC <input type="checkbox"/> OCT GAIN CONSTANT: 36
CONFIGURATION (MAG TAPE): FIELD TRACE NOS.: 1-48 DATA CHANNEL NOS.: 1-48		PACKING DENSITY: (L0) <input type="checkbox"/> 350 BPI (M1) <input type="checkbox"/> 712 BPI INPUT IMPEDANCE: 20,000 ohms
PARAMETER: RECORD LENGTH: 6 sec DISPLAY: MODE: <input type="checkbox"/> FLOAT <input type="checkbox"/> AMPLIFIER <input type="checkbox"/> DIRECT <input type="checkbox"/> DEFLOAT <input type="checkbox"/> DIRECT CFS I: TYPE STACK: _____		AUXILIARY DATA: (1) 70 (2) 4H (3) _____ (4) _____ AUXILIARY CHANNEL NOS.: 3 4 FILTERS: MEG 8 LO CUT 18 HZ SLOPE 18
SOURCE: TYPE: <input checked="" type="checkbox"/> DYNAMITE <input type="checkbox"/> VIBROSEIS <input type="checkbox"/> OTHER PATTERN: SINGLE Hole - T-Plane CHG. HOLE: 50 HOLE DEPTH: 90		POLARITY CONVENTION: <input type="checkbox"/> NEGATIVE <input checked="" type="checkbox"/> POSITIVE NOISE REDUCTION: _____ NOISE THRESHOLD: _____ CORR. SCALING: _____ R C U. NORM. ALT SW.
RECEIVER: TYPE: GSC-20d CONNECTION: Series-Parallel RESISTANCE: 560 ohms		LATERAL SPACING: _____ SWEEP START: _____ SWEEP END: _____ STAGGER: _____ SWEEP LENGTH: _____ SWEEP TAPER: _____ WIDTH: _____ PHASE COMP.
SPREAD: NO. OF GROUPS: 48 OFFSET GROUP 1: 7755' GROUP INTERVAL: 330' OFFSET GROUP 24: 165'		STAGGER: _____ NO. OF ELEMENTS: 18 INLINE SPACING: _____ SWEEP START: _____ SWEEP END: _____ LENGTH: 18' INLINE SPACING: _____ WIDTH: _____ PHASE COMP.
DIAGRAMS/MISC. INFORMATION:		KNO: 6 OFFSET GROUP FROM: 7755' DIRECTION OF PROGRESSION: N → S LEADING GROUP: 48

SHOT NO.	TR 1 to 48		TR 10 to 20		SHOT		DIR	COF SWITCH	SPREAD LINE GROUPS	REMARKS	CORR STACK				
	REEL NO.	REC.	REEL NO.	REC.	SIZE	DEPTH					NO.	OFFSET	TR 1-20	TR 21-40	TR 41-60
45	751185	15716			50	70441	33	37	39H - 50H	8	Satz dead				
46		577			50	70442			33 40H - 51H	9	Recorder @ SP-50				
47		578			50	70443			37 41H - 52H						
48		579			50	70444			41 42H - 53H						
49		580			50	70445			45 43H - 54H						
50		581			50	70446			49 44H - 55H						
51		582			50	70447			53 45H - 56H						
52		583			50	70448			57 46H - 57H						
53		584			50	70449			61 47H - 58H						
54		585			50	70450			65 48H - 59H						

LAND SEISMIC RECORDING LOG

15.5 Hours

	CLIENT: Husky	PROSPECT: NPR-1	AREA: Barlow	LINE NO: 606	
PARTY NO: 1187	INST ENG: Windham	DATE: MO. 4 DAY 26 YR 79			

INSTRUMENT (9-TRACK)	<input checked="" type="checkbox"/> 1 SYSTEM <input type="checkbox"/> 2 SYSTEMS	<input type="checkbox"/> 1-24 & 25-48 <input type="checkbox"/> 1-48 & 49-96	TYPE: <input type="checkbox"/> DFS III <input type="checkbox"/> DFS IV <input type="checkbox"/> DFS V <input type="checkbox"/> DFS VI <input type="checkbox"/> OTHER	<input type="checkbox"/> 9 TRACK <input type="checkbox"/> 21 TRACK	FORMAT: B <input type="checkbox"/> SFC <input type="checkbox"/> GAPPED <input type="checkbox"/> UNGAPPED	PACKING DENSITY: (10) <input type="checkbox"/> 356 BPI (11) <input type="checkbox"/> 712 BPI (12) <input type="checkbox"/> 1000 BPI
	NO. BYTES IN HEADER REC.	NO. BYTES IN RECORD ID.	NO. BYTES PER SCAN: 136	RECORD NUMBERS: 6000	GAIN CONSTANT: 36	INPUT IMPEDANCE: 20,000 ohms

CONFIGURATION (MAG TAPE)	FIELD TRACE NOS.: 1-48 DATA CHANNEL NOS.: 1-48 (ON MAG TAPE)	AUXILIARY DATA: 7B 4H AUXILIARY CHANNEL NOS.: 3 4
--------------------------	---	--

PARAMETER	RECORD LENGTH: 6 sec	SAMPLE RATE: <input checked="" type="checkbox"/> 1 sec <input type="checkbox"/> 4 ms	GAIN MODE: <input type="checkbox"/> INITIAL <input type="checkbox"/> MANUAL <input type="checkbox"/> OPERATE	FILTERS: FREQ: 8	LO CUT: 18 Hz	HI CUT: 70 Hz	NOTCH FILTER: <input type="checkbox"/> IN <input type="checkbox"/> OUT
DISPLAY	MODE: <input checked="" type="checkbox"/> AGC <input type="checkbox"/> FLOAT <input type="checkbox"/> DIRECT	AMPLIFIER: <input type="checkbox"/> DIRECT	TRIP SENS: 18 db	POLARITY CONVENTION: <input type="checkbox"/> POSITIVE <input type="checkbox"/> NEGATIVE	PRESSURE INCREASE ON GEOPHONE: <input type="checkbox"/> POSITIVE <input type="checkbox"/> NEGATIVE	NUMBERS ON MAG TAPE: <input type="checkbox"/> DOWNBREAK <input type="checkbox"/> UMBRELL	ON DISPLAY: <input type="checkbox"/> ON DISPLAY
CFS I	TYPE STACK	GATE LENGTH	RECORD REJECTION	NOISE REDUCTION: 3	NOISE THRESHOLD	CORR. SCALING	R.C.U. NORM. ALT SW

SOURCE	TYPE: <input checked="" type="checkbox"/> DYNAMITE <input type="checkbox"/> VIBROSEIS <input type="checkbox"/> OTHER	PATTERN: Single hole - inline	NO. OF POSITIONS: 18	INLINE SPACING: 18'	LATERAL SPACING: 18'	STAGGER: 18'	LENGTH: 18'	WIDTH: 18'	LATERAL OFFSET: 18'
	CHG. HOLE: 50	HOLE DEPTH: 90	SWEEP POSITION	SWEEP START	SWEEP END	SWEEP LENGTH	SWEEP TAPER	PHASE COMP.	

RECEIVER	TYPE: RSC-20d	PATTERN: IN line	NO. OF ELEMENTS: 18	INLINE SPACING: 18'	LATERAL SPACING: 18'	STAGGER: 18'	LENGTH: 18'	WIDTH: 18'	LATERAL OFFSET: 18'
	CONNECTION: Series - Parallel	RESISTANCE: 560 ohms	STAGGER	SWEEP LENGTH	SWEEP TAPER	PHASE COMP.			

SPREAD	NO. OF GROUPS: 48	GROUP INTERVAL: 330'	SHOTPOINT INTERVAL: 1320'	FOLD: 6	DIRECTION OF PROGRESSION: N → S
	OFFSET GROUP: 7755'	OFFSET GROUP 24: 165'	OFFSET GROUP 25: 165'	OFFSET GROUP 48: 7755'	LEADING GROUP: 68

DIAGRAMS/MISC. INFORMATION: **PPPPPP ← TR-24 → CTR-25** **File # 587 → 595 Daily Test** **File # 596 - Test TB**

SHOTPOINT	TR 1 to 48		TR 49 to 96		SHOT		SPREAD		REMARKS	CORR STACK				
	REEL NO	REC.	REEL NO	REC.	SIZE	DEPTH	NO.	DIR		COP SWITCH	LINE GROUPS	HT	NC	HT
551	7511	5917			50	70	1		29	49+1 - 60+4				
556		5918			50	70	2		33	50+1 - 61+4				
561		5919			50	70	3		37	51+1 - 62+4				
566		600			50	70	4		41	52+1 - 63+4				
569		601			50	70	5		45	53+1 - 64+4	2			RECORDER @ SP 65
570		602			50	70	6		29	54+1 - 65+4				
571		603			50	70	7		33	55+1 - 66+4				
572		604			50	70	8		37	56+1 - 67+4				
573		605			50	70	9		41	57+1 - 68+4				
574		606			50	70	10		45	58+1 - 69+4				
575		607			50	70	11		29	59+1 - 70+4	3			RECORDER @ SP 70
576		608			50	70	12		33	60+1 - 71+4				
577		609			50	70	13		37	61+1 - 72+4				
578		610			50	70	14		41	62+1 - 73+4				
579		611			50	70	15		45	63+1 - 74+4				
580		612			50	70	16		49	64+1 - 75+4				
581		613			50	70	17		53	65+1 - 76+4				
582		614			50	70	18		57	66+1 - 77+4				
583		615			50	70	19		29	67+1 - 78+4	4			RECORDER @ SP 78
584		616			50	70	20		33	68+1 - 79+4				

LAND SEISMIC RECORDING LOG

CLIENT: Husky		PROSPECT: NPR-A		AREA: BARROW		LINE NO.: 606							
PARTY NO.: 1182		INST. ENG.: WINDHAM		DATE: NO. 2 DAY 26 TR 79									
INSTRUMENT <input type="checkbox"/> 1 SYSTEM <input checked="" type="checkbox"/> 2 SYSTEMS NO BYTES IN HEADER REC.: _____		ODDS EVENS <input type="checkbox"/> 1-24 & 75-48 <input type="checkbox"/> 1-48 & 49-96		TYPE: <input type="checkbox"/> DFS <input checked="" type="checkbox"/> DFS II <input type="checkbox"/> DFS III <input type="checkbox"/> OTHER		TRACKS: <input type="checkbox"/> 9 TRACK <input checked="" type="checkbox"/> 21 TRACK		TOPRAI: <input type="checkbox"/> SEG <input checked="" type="checkbox"/> B		GAPPED UNGAPPED: <input type="checkbox"/> GAPPED <input checked="" type="checkbox"/> UNGAPPED		FACING DENSITY: (L) <input type="checkbox"/> 250 BPI (M) <input type="checkbox"/> 712 BPI (R) <input type="checkbox"/> 800 BPI (S) <input type="checkbox"/> 1400 BPI	
CONFIGURATION (MAG TAPE) FIELD TRACE NOS.: 1-48 DATA CHANNEL NOS.: 1-48		NO BYTES IN RECORD ID: _____		NO BYTES PER SCAN: 134		RECORD NUMBERS: <input checked="" type="checkbox"/> DEC <input type="checkbox"/> OCT		GAIN CONSTANT: 36 db		INPUT IMPEDANCE: 20,000 ohms		(1) (2) (3) (4) (5) (6) (7)	
PARAMETER RECORD LENGTH: 6 sec		SAMPLE RATE: <input type="checkbox"/> 1 sec <input checked="" type="checkbox"/> 2 sec <input type="checkbox"/> 4 sec		GAIN MODE: <input type="checkbox"/> INITIAL <input checked="" type="checkbox"/> MANUAL <input type="checkbox"/> FINAL		FILTERS: <input type="checkbox"/> 8		LO CUT: 13 Hz		HI CUT: _____ Hz		NOTCH FILTER: <input type="checkbox"/> IN <input checked="" type="checkbox"/> OUT	
DISPLAY MODE: <input checked="" type="checkbox"/> AGC <input type="checkbox"/> FLOAT <input type="checkbox"/> DEFLOAT <input type="checkbox"/> AMPLIFIER <input type="checkbox"/> DIRECT		INITIAL GAIN: 18 db		TRIP SENS: _____ db		POLARITY CONVENTION: <input type="checkbox"/> NEGATIVE <input checked="" type="checkbox"/> POSITIVE		PRESSURE INCREASE ON GEOPHONE: <input type="checkbox"/> NEGATIVE <input checked="" type="checkbox"/> POSITIVE		NUMBERS ON MAG TAPE: <input type="checkbox"/> DOWNBREAK <input checked="" type="checkbox"/> UPBREAK		ON DISPLAY: <input type="checkbox"/> ON DISPLAY	
SOURCE TYPE: <input checked="" type="checkbox"/> DYNAMIC <input type="checkbox"/> VIBROSEIS <input type="checkbox"/> OTHER		PATTERN: INLINE SINGLE HOLE CHG/NOLE: 50 HOLE DEPTH: 90		NO. OF POSITIONS: _____ SWEEP POSITION: _____		INLINE SPACING: _____ SWEEP START: _____		LATERAL SPACING: _____ SWEEP END: _____		STAGGER: _____ SWEEP LENGTH: _____		LENGTH: _____ SWEEP TAPER: _____	
RECEIVER TYPE: GSC 20-D CONNECTION: SERIES / PARALLEL		PATTERN: INLINE RESISTANCE: 560 ohms		NO. OF ELEMENTS: 18 STAGGER: _____		INLINE SPACING: 18' LENGTH: _____		LATERAL SPACING: _____ WIDTH: _____		LATERAL OFFSET: _____ PHASE COMP: _____			
SPREAD NO. OF GROUPS: 48 OFFSET GROUP 1: 775'		GROUP INTERVAL: 330' OFFSET GROUP 24: 165'		SHOTPOINT INTERVAL: 1320' OFFSET GROUP 25: 165'		FOLD: 6		DIRECTION OF PROGRESSION: N→S		LEADING GROUP: 48			

DIAGRAMS/MISC. INFORMATION:

SHOTPOINT	TR 1a		TR 1b		SHOT		SPREAD		REMARKS	CORR STAGE					
	REEL NO	REC.	REEL NO	REC.	SIZE	DEPTH	NO.	OFFSET		DIR.	CDP SWITCH	LINE GROUPS	Y1-Z1	Y2-Z2	Y3-Z3
175	7518197	6117			50	70	21	1		37	69+1 - 80+4				
176		6118			50	70	22	1		41	70+1 - 81+4				
177		6119			50	70	23	1		45	71+1 - 82+4				
178		621			50	70	24	1		49	72+1 - 83+4				
179		622			50	70	25	1		53	73+1 - 84+4				
180		623			50	70	26	1		57	74+1 - 85+4				
181		624			50	70	27	1		29	75+1 - 86+4				
182		625			50	70	28	1		33	76+1 - 87+4				
183		626			50	70	29	1		37	77+1 - 88+4				
184		627			50	70	30	1		29	78+1 - 89+4				
185		628			50	70	31	1		33	79+1 - 90+4				
186		629			50	70	32	1		37	80+1 - 91+4				
187		630			50	70	33	1		41	81+1 - 92+4				
188		631			50	70	34	1		45	82+1 - 93+4				
189		632			50	70	35	1		49	83+1 - 94+4				
190		633			50	70	36	1		53	84+1 - 95+4				
191		634			50	70	37	1		29	85+1 - 96+4				
192	7518198	635			50	70	38	1		37	86+1 - 97+4				
193		638			50	70	39	1		37	87+1 - 98+4				
194		639			50	70	40	1		41	88+1 - 99+4				

FILE # 620 MISFIRE

5 RECORDER @ 86

6 RECORDER @ 89

7 RECORDER @ 96

FILE # 635 DUMMY RECORD

FILE # 636 MISFIRE

LAND SEISMIC RECORDING LOG

CLIENT: Husky		PROSPECT: NPR-A		AREA: BARROCO		LINE NO: 606			
PARTY NO: 1182		INST. ENG: WINDHAM		DATE: 2 DAY 26 YR 79		MO: 2 DAY 26 YR 79			
INSTRUMENT: <input checked="" type="checkbox"/> 1 SYSTEM <input type="checkbox"/> 2 SYSTEMS		GAINS: <input type="checkbox"/> 1-24 & 25-48 <input type="checkbox"/> 000S <input type="checkbox"/> 000S <input type="checkbox"/> 000S		TYPE: <input type="checkbox"/> DFS III <input type="checkbox"/> DFS III <input type="checkbox"/> DFS III <input type="checkbox"/> OTHER		# 9 TRACK <input type="checkbox"/> # 21 TRACK		POPMAT: B	
[P-TRACK] NO BYTES IN HEADER REC:		NO BYTES IN RECORD ID:		NO BYTES PER SCAN: 134		RECORD NUMBERS: <input checked="" type="checkbox"/> DEC <input type="checkbox"/> OCT		GAIN CONSTANT: 36	
CONFIGURATION (MAG TAPE)		FIELD TRACE NOS: 1-48		DATA CHANNEL NOS: 1-48		AUXILIARY DATA:		INPUT IMPEDANCE: 20,000 ohms	
PARAMETER		RECORD LENGTH: 6		SAMPLE RATE: <input type="checkbox"/> 1 ms <input type="checkbox"/> 4 ms		GAIN MODE: <input checked="" type="checkbox"/> INITIAL <input type="checkbox"/> MANUAL <input type="checkbox"/> OPERATE		FILTERS: 8	
DISPLAY		MODE: <input checked="" type="checkbox"/> AGC <input type="checkbox"/> FLOAT <input type="checkbox"/> AMPLIFIER <input type="checkbox"/> DEFOAT <input type="checkbox"/> DIRECT		INITIAL GAIN: 18		TRIP SENS:		LO CUT Hz SLOPE: 18	
CFS I		TYPE:		GATE LENGTH:		RECORD REJECTION:		FREQ 128 Hz SLOPE 70	
SOURCE		TYPE: <input checked="" type="checkbox"/> DYNAMITE <input type="checkbox"/> VIBROSEIS <input type="checkbox"/> OTHER		PATTERN: INLINE SINGLE HOLD		NO OF POSITIONS:		POLARITY CONVENTION: <input type="checkbox"/> NEGATIVE <input type="checkbox"/> POSITIVE	
RECEIVER		TYPE: GSC 20-D		PATTERN: INLINE		INLINE SPACING:		NOISE REDUCTION:	
CONNECTION: SERIES/PARALLEL		RESISTANCE: 560 ohms		SWEEP POSITION:		SWEEP START:		CORR SCALING:	
NO OF GROUPS: 48		GROUP INTERVAL: 330'		SWEEP END:		SWEEP LENGTH:		STAGGER:	
OFFSET GROUP 1: 7755'		OFFSET GROUP 24: 165'		SHOTPOINT INTERVAL: 1320'		SWEEP TAPER:		LENGTH:	
OFFSET GROUP 25: 165'		OFFSET GROUP 48/96: 7755'		FOLD: 6		PHASE COMP:		WIDTH:	
DIAGRAMS/MISC. INFORMATION:		LATERAL SPACING: 18'		DIRECTION OF PROGRESSION: N7S		LATERAL OFFSET:		LEADING GROUP: 48	

SHOTPOINT	TR 1		TR 2		SHOT			SPREAD		REMARKS	CORR STACK	
	REEL NO	REC	REEL NO	REC	SIZE	DEPTH	NO. OFFSET	DIR	COP SWITCH		LINE GROUPS	TR 1
85	761	898	640		50	70	41		45	89+1 - 100+4		
86		641			50	70	42		25 25	90+1 - 101+4		
87		642			50	70	43		29	91+1 - 102+4		
88		643			50	70	44		33	92+1 - 103+4		
89		644			50	70	45		37	93+1 - 104+4		
100		645			50	70	46		41	94+1 - 105+4		
101		646			50	70	47		45	95+1 - 106+4		
102		647			50	70	48		49	96+1 - 107+4		
103		648			50	70	49		63	97+1 - 108+4		
104		649			50	70	50		57	98+1 - 109+4		
105		650			50	70	51		61	99+1 - 110+4		
106		651			50	70	52		65	100+1 - 111+4		

FILE # 652 N.G.

LAND SEISMIC RECORDING LOG

14.5 Hours

	CLIENT: Haskey	PROSPECT: NPR-A	AREA: BARROW	LINE NO: 606	
PARTY NO: 1182	INST. ENG: Windham		DATE: 27-79		

INSTRUMENT	<input type="checkbox"/> 1 SYSTEM <input type="checkbox"/> 2 SYSTEMS	<input type="checkbox"/> 1-24 & 25-48 <input type="checkbox"/> 1-48 & 49-96	TYPE: <input type="checkbox"/> DPS III <input type="checkbox"/> DPS IV <input type="checkbox"/> OTHER	RECORD NUMBERS: <input type="checkbox"/> 9 TRACK <input type="checkbox"/> 21 TRACK	FORMAT: B SEG:	GAPPED: <input type="checkbox"/> GAPPED <input type="checkbox"/> UNGAPPED	PACKING DENSITY:	(10) <input type="checkbox"/> 350 BPI <input type="checkbox"/> 600 BPI	(11) <input type="checkbox"/> 712 BPI <input type="checkbox"/> 1300 BPI
[9-TRACK]	NO. BYTES IN HEADER REC:	NO. BYTES IN RECORD ID:	NO. BYTES PER SCAN: 134			GAIN CONSTANT: 36	INPUT IMPEDANCE: 20,000		

CONFIGURATION (MAG TAPE)	FIELD TRACE NOS: 1-48	AUUXILIARY DATA: PA 4H	RECORD NUMBERS: 3 4
	DATA CHANNEL NOS: 1-48	(ON MAG TAPE)	

PARAMETER	RECORD LENGTH: 6	SAMPLE RATE: <input type="checkbox"/> 1 sec <input type="checkbox"/> 4 sec	GAIN MODE: <input type="checkbox"/> INITIAL <input checked="" type="checkbox"/> TRIP	FILTERS: B	LO CUT: 18	HI CUT: 128	NOTCH FILTER: <input type="checkbox"/> IN <input type="checkbox"/> OUT
DISPLAY	MODE: <input type="checkbox"/> FLOAT <input type="checkbox"/> DEFLOAT	INITIAL GAIN: 18	TRIP SENS: 18	FREQ: 8	PRESSURE INCREASE ON GEOPHONE: <input type="checkbox"/>	NEGATIVE NUMBERS ON MAG TAPE: <input type="checkbox"/>	DOWNBREAK ON DISPLAY: <input type="checkbox"/>

SOURCE	TYPE: <input checked="" type="checkbox"/> DYNAMITE <input type="checkbox"/> VIBROSEIS <input type="checkbox"/> OTHER	PATTERN: Single hole - Tailine	NO. OF POSITIONS: 18	INLINE SPACING: 18'	LATERAL SPACING: 18'	STAGGER: 18'	LENGTH: 18'	WIDTH: 18'	LATERAL OFFSET: 18'
	CHG/ HOLE: 50	HOLE DEPTH: 90	SWEEP POSITION: 25	SWEEP START: 1.65'	SWEEP END: 1.65'	SWEEP LENGTH: 77.55'	SWEEP TAPER: 1.65'	PHASE COMP: 1.65'	

RECEIVER	TYPE: G.S.C-20d	PATTERN: Tailine	NO. OF ELEMENTS: 18	INLINE SPACING: 18'	LATERAL SPACING: 18'	STAGGER: 18'	LENGTH: 18'	WIDTH: 18'	LATERAL OFFSET: 18'
	CONNECTION: Series-Parallel	RESISTANCE: 560	STAGGER: 18'						

SPREAD	NO. OF GROUPS: 48	GROUP INTERVAL: 330'	SHOTPOINT INTERVAL: 13.20'	FOOT: 6	DIRECTION OF PROGRESSION: N→S
	OFFSET GROUP: 77.55'	OFFSET GROUP: 24	OFFSET GROUP: 1.65'	OFFSET GROUP: 77.55'	LEADING GROUP: 48

DIAGRAMS/MISC. INFORMATION:
 101 P P P P P ← → P P P P P P P P P P ← → P P P P P P P P P P
 5A107 TR-24 TR-25
 112 TR-26
 113 TR-27
 File 655 → 661 Daily Test
 File 662 = Test TB

SHOTPOINT	TR 1 to 48		TR 49 to 96		SHOT		SPREAD		REMARKS	CORR STACK	
	REEL NO	REC.	REEL NO	REC.	SIZE	DEPTH	NO.	OFFSET		DIR.	COP SWITCH
1107	7511898	663			50	70	1		29	101+1 - 112+4	1
1108		664			50	70	2		33	102+1 - 113+4	
1109		665			50	70	3		37	103+1 - 114+4	
1110		666			50	70	4		41	104+1 - 115+4	
1111		667			50	70	5		45	105+1 - 116+4	
1112		668			50	70	6		49	106+1 - 117+4	
1113		669			50	70	7		53	107+1 - 118+4	
1114		670			50	70	8		57	108+1 - 119+4	
1115		671			50	70	9		61	109+1 - 120+4	
1116		672			50	70	10		65	110+1 - 121+4	
1117		673			50	70	11		29	111+1 - 122+4	2 Recorder @ SP-122
1118		674			50	70	12		33	112+1 - 123+4	
1119		675			50	70	13		37	113+1 - 124+4	
120		676			50	70	14		41	114+1 - 125+4	
121		677			50	70	15		45	115+1 - 126+4	
122		678			50	70	16		49	116+1 - 127+4	3 Recorder @ SP-123
123		679			50	70	17		49	117+1 - 128+4	
124		680			50	70	18		53	118+1 - 129+4	
125		681			50	70	19		57	119+1 - 130+4	4 Recorder @ SP-124
126		682			50	70	20		57	120+1 - 131+4	

LAND SEISMIC RECORDING LOG

CLIENT: Nasky		PROSPECT: NPR-A		AREA: BARROW		LINE NO.: 606	
PARTY NO.: 1182		INS. ENG.: Windham		DATE: 2 DAY 27 79			
INSTRUMENT (9-TRACK) <input type="checkbox"/> 1 SYSTEM <input checked="" type="checkbox"/> 2 SYSTEMS		NO. BYTES IN HEADER REC: _____		NO. BYTES IN RECORD ID: _____		NO. BYTES PER SCAN: 134	
CONFIGURATION (MAG TAPE) FIELD TRACE NOS.: 1-48 DATA CHANNEL NOS.: 1-48		AUXILIARY DATA: 18 48		AUXILIARY CHANNEL NOS.: 3 4			
PARAMETER RECORD LENGTH: 6		SAMPLE RATE: <input type="checkbox"/> 1 sec <input checked="" type="checkbox"/> 4 sec		GAIN MODE: <input type="checkbox"/> INITIAL <input type="checkbox"/> MANUAL <input type="checkbox"/> FINAL <input checked="" type="checkbox"/> OPERATE		FILTERS: FREQ: 8	
DISPLAY MODE: <input checked="" type="checkbox"/> MAG <input type="checkbox"/> FLOAT <input type="checkbox"/> AMPLIFIER <input type="checkbox"/> DIRECT		INITIAL GAIN: 18		TRIP SENS: 18		POLARITY CONVENTION: <input type="checkbox"/> NEGATIVE <input checked="" type="checkbox"/> POSITIVE	
CFS I TYPE STACK: _____		GATE LENGTH: _____		RECORD REJECTION: _____		NOISE REDUCTION: _____	
SOURCE TYPE: <input checked="" type="checkbox"/> DYNAMITE <input type="checkbox"/> VIBROSEIS <input type="checkbox"/> OTHER		PATTERN: Single hole - ENline		NO. OF POSITIONS: _____		INLINE SPACING: _____	
RECEIVER TYPE: Gsc-20d		PATTERN: ENline		NO. OF ELEMENTS: 18		INLINE SPACING: 18'	
SPREAD NO. OF GROUPS: 48		GROUP INTERVAL: 330'		SHOTPOINT INTERVAL: 1320'		FOLD: 6	
DIAGRAMS/MISC. INFORMATION:		RESISTANCE: 560 ohms		STAGGER: _____		LATERAL SPACING: _____	
		OFFSET GROUP 24: 165'		SWEEP POSITION: _____		SWEEP LENGTH: _____	
		OFFSET GROUP 25: 165'		SWEEP START: _____		SWEEP TAPE: _____	
		OFFSET GROUP 26: 77.55'		SWEEP END: _____		PHASE COMP: _____	

SHOTPOINT	TR 1 to 48		TR 49 to 96		SHOT		SPREAD		REMARKS	CORR STACK		
	REEL NO.	REC.	PEEL NO.	REC.	SIZE	DEPTH	NO.	OFFSET		CDP SWITCH	LINE GROUPS	TR 1-28
127	751698	683			50	7021		61	1211 - 13214	4		
128		684			50	7022		65	12211 - 13314			
129		685			50	7023		69	12311 - 13414			
130		686			50	7024		29	12411 - 13514	5	Recorder @ SP-135	
131		687			50	7025		33	12511 - 13614			
132		688			50	7026		37	12611 - 13714			
133		689			50	7027		41	12711 - 13814			
134		690			50	7028		45	12811 - 13914			
135		691			50	7029	6.5	49	12911 - 14014			
136		692			50	7030		53	13011 - 14114			
137		693			50	7031		57	13111 - 14214			
138		694			50	7032		29	13211 - 14314	6	Recorder @ SP-147	Field 694 mistake
139		695			50	7033		33	13311 - 14414			
140		697			50	7034		37	13411 - 14514			
141		698			50	7035		41	13511 - 14614			
142		699			50	7036		29	13611 - 14714	7	Recorder @ 50-147	
143		700			50	7037		33	13711 - T4			
144		701			50	7038		37	13811 - T8			
145		702			50	7039		41	13911 - T12			
146		703			50	7040		45	14011 - T16			

