

LAND SEISMIC RECORDING LOG



CLIENT: <b>Husky</b>		PROSPECT: <b>Southern Foothills</b>		AREA: <b>NPR-A Alaska</b>		LINE NO: <b>607</b>	
PARTY NO: <b>1186</b>		INST. ENG: <b>DEREDE-PANKO</b>		LEAVE BASE: <b>7:00 AM</b>		DATE: <b>MO 03 DAY 11 YR 79</b>	
ARRIVE FIELD: <b>9:30 AM</b>		ARRIVE FIELD: <b>9:00 AM</b>		ARRIVE FIELD: <b>9:00 AM</b>		ARRIVE FIELD: <b>9:00 AM</b>	
INSTRUMENT: <b>1 SYSTEM</b>		NO. BYTES IN HEADER REC: <b>128</b>		NO. BYTES IN RECORD ID: <b>254</b>		NO. BYTES PER SCAN: <b>254</b>	
CONFIGURATION (MAG TAPE):		FIELD TRACE NOS.: <b>1-96</b>		DATA CHANNEL NOS.: <b>1-96</b>		AUXILIARY DATA:	
PARAMETER: RECORD LENGTH: <b>8</b> sec.		SAMPLE RATE: <b>1 ms</b>		GAIN MODE: <b>INITIAL</b>		FILTERS: <b>FREQ 8</b>	
DISPLAY: MODE: <b>AGC</b>		INITIAL GAIN: <b>db</b>		REC'D CONVENTION: <b>POSITIVE</b>		POLARITY CONVENTION: <b>POSITIVE</b>	
SOURCE: TYPE: <b>DYNAMITE</b>		PATTERN: <b>Int. NE (S/N) 10</b>		NO. OF POSITIONS: <b>18</b>		LATERAL SPACING: <b>15'</b>	
RECEIVER: TYPE: <b>HST 10 1/2</b>		PATTERN: <b>Inline</b>		NO. OF ELEMENTS: <b>18</b>		INLINE SPACING: <b>15'</b>	
SPREAD: NO. OF GROUPS: <b>96</b>		GROUP INTERVAL: <b>220'</b>		SHOTPOINT INTERVAL: <b>880'</b>		FOLD: <b>1200%</b>	
DIAGRAMS/MISC. INFORMATION:		West #96 <b>10,340</b>		→ 49 <b>9</b>		48 <b>10,340</b> → 17 East	


SHOTPOINT	TR. 10		TR. 10		SHOT		SPREAD		REMARKS	CORR. STAGE			
	REEL NO.	REC.	REEL NO.	REC.	SIZE	DEPTH	NO. OFFSET	DIR.		CDP SWITCH	LINE GROUPS	TR. 10	TR. 10
1	1186	113			110	105	1		49	1.1	24.4		
2		14			110	105	2		49	1.1	24.4		
3		15			110	105	3	25'E	49	1.1	24.4		
4		16			110	105	4	125'S	49	1.1	24.4		
5		17			110	105	5		49	1.1	24.4		
6		18			110	105	6		49	1.1	24.4		
7		19			110	105	7	90'E	49	1.1	24.4		75' N.
8		20			110	105	8	65'E	49	1.1	24.4		50' N.
9		21			110	105	9		49	1.1	24.4		
10		22			110	105	10		49	1.1	24.4		
11		23			110	105	11		49	1.1	24.4		
12		24			110	105	12		49	1.1	24.4		
13		25			110	105	13		49	1.1	24.4		
14		26			110	105	14		45	2.1	25.4		
15		27			110	105	15	35'E	41	3.1	26.4		
16		28			110	105	16		37	4.1	27.4		T4 BAD
17		29			110	105	17	55'S	33	5.1	28.4		T8 "
18		30			110	105	18		29	6.1	29.4		#95-196 DEAD
19		31			110	105	19		25	7.1	30.4		
20		32			110	105	20	50'E	21	8.1	31.4		

\* INcomplete (only 4 Ranges Run in FTP) (S/P 1-100)



# LAND SEISMIC RECORDING LOG Page 1 of 2

	CLIENT: <u>Husky</u>	PROSPECT: <u>Southern Foothills</u>	AREA: <u>NPR-A Alaska</u>	LINE NO.: <u>607</u>				
	PARTY NO.: <u>1186</u>	INST. ENG.: <u>Derek De-Panko</u>	<u>Leave Base 7:20 AM</u> <u>ARR. FIELD 8:30</u>	DATE: <u>NO. 03 DAY 13. YR 79</u>				
<b>INSTRUMENT</b> (9-TRACK)	<input type="checkbox"/> 1 SYSTEM <input checked="" type="checkbox"/> 2 SYSTEMS	<input type="checkbox"/> 1-24 & 25-48 <input checked="" type="checkbox"/> 1-48 & 49-96	ODDS EVENTS	TYPE: <input type="checkbox"/> DFS III <input type="checkbox"/> DFS II	<input type="checkbox"/> 9 TRACK <input checked="" type="checkbox"/> 21 TRACK	FORMAT: <input type="checkbox"/> GAPPED <input type="checkbox"/> UNGAPPED	PACKING DENSITY: (L) <input type="checkbox"/> 356 BPI (M) <input type="checkbox"/> 800 BPI	(H) <input type="checkbox"/> 710 BPI (I) <input type="checkbox"/> 1500 BPI
	NO. BYTES IN HEADER REC.: <u>128</u>	NO. BYTES IN RECORD ID: _____	NO. BYTES PER SCAN: <u>254</u>	RECORD NUMBERS: <input type="checkbox"/> DEC. <input type="checkbox"/> OCT.	GAIN CONSTANT: <u>31</u> db	INPUT IMPEDANCE: <u>20,000</u> ohms.	(1) _____ (2) _____ (3) _____ (4) _____ (5) _____ (6) _____ (7) _____	
<b>CONFIGURATION</b> (MAG TAPE)	FIELD TRACE NOS.: <u>1-96</u>	(ON MAG TAPE)			AUXILIARY DATA:			
	DATA CHANNEL NOS.: <u>1-96</u>				AUXILIARY CHANNEL NOS.: _____			
<b>PARAMETER</b>	RECORD LENGTH: <u>8</u> sec.	SAMPLE RATE: <input type="checkbox"/> 1 ml. <input type="checkbox"/> 4 ml.	GAIN MODE: <input type="checkbox"/> INITIAL <input type="checkbox"/> FINAL	<input type="checkbox"/> MANUAL <input type="checkbox"/> OPERATE	FILTERS: _____	LO CUT _____ HZ	H1 CUT _____ HZ	H2 SLOPE _____
<b>DISPLAY</b>	MODE: <input type="checkbox"/> FLOAT <input type="checkbox"/> AMPLIFIER <input checked="" type="checkbox"/> AGC <input type="checkbox"/> DEFOAT <input type="checkbox"/> DIRECT	INITIAL GAIN: _____ db	TRIP SENS: _____ db		POLARITY CONVENTION: _____	PRESSURE INCREASE ON GEOPHONE: <input type="checkbox"/> NEGATIVE <input type="checkbox"/> POSITIVE	NUMBERS ON MAG. TAPE: <input type="checkbox"/> DOWNBREAK <input type="checkbox"/> UPBREAK	NOTCH FILTER: <input type="checkbox"/> IN <input type="checkbox"/> OUT
<b>CFS I</b>	TYPE STACK: _____	GATE LENGTH: _____	RECORD REJECTION: _____		NOISE REDUCTION: _____	NOISE THRESHOLD: _____	CORR. SCALING: _____	P.C.U. NORM./ALT SW. _____
<b>SOURCE</b>	TYPE: <input checked="" type="checkbox"/> DYNAMITE <input type="checkbox"/> VIBROSEIS <input type="checkbox"/> OTHER	PATTERN: <u>Inline (single)</u>	NO. OF POSITIONS: _____	INLINE SPACING: _____	LATERAL SPACING: _____	STAGGER: _____	LENGTH: _____	WIDTH: _____
	CONNECTION: <u>10/1/3</u> <u>SERIES</u>	CHG/ HOLE: <u>110</u>	HOLE DEPTH: <u>105</u>	SWEEP START: _____	SWEEP END: _____	SWEEP LENGTH: _____	SWEEP TAPER: _____	PHASE COMP. _____
<b>RECEIVER</b>	TYPE: <u>10/1/3</u>	PATTERN: <u>Inline</u>	NO. OF ELEMENTS: <u>18</u>	INLINE SPACING: _____	LATERAL SPACING: _____	STAGGER: _____	LENGTH: _____	WIDTH: _____
	RESISTANCE: _____ ohms							LATERAL OFFSET: _____
<b>SPREAD</b>	NO. OF GROUPS: _____	GROUP INTERVAL: <u>220'</u>	SHOTPOINT INTERVAL: <u>880'</u>	FOLD: <u>120%</u>	OFFSET GROUP 48/96: <u>10,450</u>	DIRECTION OF PROGRESSION: <u>East</u>	LEADING GROUP: <u>1</u>	



SHOTPOINT	TR. 10		TR. 10		SHOT				SPREAD		REMARKS	CORR. STAGE					
	REEL NO.	REC.	REEL NO.	REC.	SIZE	DEPTH	NO.	OFFSET	DIR.	CDP SWITCH		#96 LINE GROUPS	TR. 10	TR. 10	TR. 10	TR. 10	
30	222602	57	2223	57	110	105	2	150	E	49	13.1	36.4	1				
31	60				110	105	2	150	S	45	14.1	37.4					
32	61				110	105	3			41	15.1	38.4					
33	62				110	105	4			37	16.1	39.4					
34	63				110	105	5			33	17.1	40.4					
35	64				110	105	6			29	18.1	41.4					
36	65				110	105	7			25	19.1	42.4					
37	66				110	105	8	30	E	21	20.1	43.4					
38	67				110	105	9			17	21.1	44.4					
39	68				110	105	10			13	22.1	45.4					
40	69				110	105	11			9	23.1	46.4					
41	70				110	105	12			5	24.1	47.4					
42	71				110	105	13			49	25.1	48.4	2				
43	72				110	105	14			45	26.1	49.4					
44	73				110	105	15	45	S	41	27.1	50.4					
45	74				110	105	16	55	N	37	28.1	51.4					
46	75				110	105	17	55	E	33	29.1	52.4					
47	76				110	105	18	200	S	29	30.1	53.4					
48	77				110	105	19	25	W	25	31.1	54.4					
49	78				110	105	20	60	N	21	32.1	55.4					



### LAND SEISMIC RECORDING LOG

CLIENT: <b>Husky</b>		PROSPECT: <b>Southern Foothills</b>		AREA: <b>NPR-A ALASKA</b>		LINE NO.: <b>607</b>			
PARTY NO.: <b>1186</b>		INST. ENG.:		LEAVE BASE - 7:00 ARRIVE FIELD - 8:30		LEAVE FIELD 8:50 ARRIVE BASE 10:00		DATE: <b>MO. 03 DAY 15 YR 79</b>	
INSTRUMENT: <input type="checkbox"/> 1 SYSTEM <input type="checkbox"/> 2 SYSTEMS		ODDS: <input type="checkbox"/> 1-24 & 25-48 <input type="checkbox"/> 1-48 & 49-96		TYPE: <input type="checkbox"/> DFS III <input type="checkbox"/> DFS II <input type="checkbox"/> DFS I		TRACK: <input type="checkbox"/> 9 TRACK <input type="checkbox"/> 21 TRACK		FORMAT: <b>SEG B3</b>	
NO. BYTES IN HEADER REC: <b>128</b>		NO. BYTES IN RECORD ID:		NO. BYTES PER SCAN: <b>254</b>		RECORD NUMBERS:		PACKING DENSITY:	
CONFIGURATION (MAG TAPE):		FIELD TRACE NOS.: <b>1-96</b>		DATA CHANNEL NOS.: <b>1-96</b>		AUXILIARY DATA:		AUXILIARY CHANNEL NOS.:	
PARAMETER:		RECORD LENGTH: <b>8</b>		SAMPLE RATE: <input type="checkbox"/> 1 ms <input type="checkbox"/> 4 ms		GAIN MODE: <input type="checkbox"/> INITIAL <input type="checkbox"/> FINAL		FILTERS:	
DISPLAY:		MODE: <input type="checkbox"/> AGC <input type="checkbox"/> FLOAT <input type="checkbox"/> DEFLOAT		INITIAL GAIN:		TRIP SENS:		LO CUT HZ SLOPE: <b>13</b>	
CFS I:		TYPE STACK:		DATE LENGTH:		RECORD REJECTION:		HI CUT HZ SLOPE: <b>22</b>	
SOURCE:		TYPE: <input type="checkbox"/> DYNAMITE <input type="checkbox"/> VIBROSEIS <input type="checkbox"/> OTHER		PATTERN: <b>INLINE</b>		NO. OF POSITIONS:		LATERAL SPACING:	
RECEIVER:		TYPE: <b>110 10 76</b>		CONNECTION: <b>Series</b>		RESISTANCE:		NO. OF ELEMENTS: <b>18</b>	
SPREAD:		NO. OF GROUPS: <b>96</b>		GROUP INTERVAL: <b>220'</b>		SHOTPOINT INTERVAL: <b>880'</b>		FOLD: <b>1700%</b>	
DIAGRAMS/MISC. INFORMATION:		CHG/HOLE: <b>110</b>		HOLE DEPTH: <b>105'</b>		SWEEP START:		SWEEP END:	
NOISE REDUCTION:		NOISE THRESHOLD:		CORR. SCALING:		R.C.U. NORM/ALT SW:		PHASE COMP:	
LATERAL SPACING:		LENGTH:		WIDTH:		LATERAL OFFSET:		DIRECTION OF PROGRESSION: <b>EAST</b>	
OFFSET GROUP 1: <b>10,450</b>		OFFSET GROUP 2: <b>110'</b>		OFFSET GROUP 3: <b>110'</b>		OFFSET GROUP 4: <b>10,450'</b>		LEADING GROUP: <b>1</b>	

East 10,340 — 48 110' A 110' 49 — 10,340 — 96 WEST.

SHOTPOINT	TR 10		TR 20		SHOT		SPREAD			REMARKS	CORR. STACK			
	REEL NO.	REC.	REEL NO.	REC.	SIZE	DEPTH	NO.	OFFSET	DIR.		CDP SWITCH	LINE GROUPS	TR 10	TR 20
49	22R607	95			110	105	1	110	W	49	37.1	60.4		
50		96			110	105	2	30	W	45	38.1	61.4		
51		97			110	105	3	100	W	41	39.1	62.4		
52		98			110	105	4			37	40.1	63.4		
53		99			110	95	5	75	E	33	41.1	64.4		
54		100			110	105	6	85	E	29	42.1	65.4		
55		101			110	105	7			25	43.1	66.4		
56		102			110	105	8	40	W	21	44.1	67.4		
57		103			110	105	9	90	W	17	45.1	68.4		
58		104			110	105	10			13	46.1	69.4		
59		105			110	105	11			9	47.1	70.4		
60		106			110	105	12			5	48.1	71.4		
61		107			110	105	13			49	49.1	72.4		
62		108			110	105	14	30	W	45	50.1	73.4		
63		109			110	105	15			41	51.1	74.4		
64		110			110	105	16	25	W	37	52.1	75.4		
65		111			110	105	17			33	53.1	76.4		
66		112			110	105	18			29	54.1	77.4		
67		113			110	105	19	100	E	25	55.1	78.4		
68		114			110	105	20			21	56.1	79.4		

ELEM 86-94 Daily Tests  
 INST 59.4 & 55.1  
 SUSPECT ONLY PARTIAL CHARGE FIRED  
 T 3+4 NOISY  
 T 7+8 "  
 T 11+12 "  
 60'S T 14+20 NOISY  
 T 23+24 "  
 T 27+28 "  
 T 31+32 NOISY  
 INST 66.4 & 67.1 T 35+36 NOISY  
 49-96 SLASHED  
 T B WEAK  
 TAPE CHANGE

# LAND SEISMIC RECORDING LOG

Page #2 of 3



	CLIENT: <b>Husky</b>	PROSPECT: <b>SOUTHERN FOOTHILLS</b>	AREA: <b>NPR-A ALASKA</b>	LINE NO.: <b>607</b>					
	PARTY NO.: <b>1186</b>	INST. ENG:		DATE: <b>MO. 3 DAY 15 YR 79</b>					
INSTRUMENT (9-TRACK)	<input type="checkbox"/> 1 SYSTEM <input type="checkbox"/> 2 SYSTEMS	<input type="checkbox"/> 1-24 & 25-48 <input type="checkbox"/> 1-48 & 49-96	ODDS EVENS	TYPE: <input type="checkbox"/> DFS III <input type="checkbox"/> DFS IV <input type="checkbox"/> DFS V	<input type="checkbox"/> 9 TRACK <input type="checkbox"/> 21 TRACK	FORMAT: _____ SEG. _____	<input type="checkbox"/> GAPPED <input type="checkbox"/> UNGAPPED	PACKING DENSITY: (L0) <input type="checkbox"/> 356 BPI (H1) <input type="checkbox"/> 712 BPI	<input type="checkbox"/> 800 BPI <input type="checkbox"/> 1600 BPI
	NO. BYTES IN HEADER REC: _____	NO. BYTES IN RECORD ID: _____	NO. BYTES PER SCAN: _____	RECORD NUMBERS: _____	<input type="checkbox"/> DEC. <input type="checkbox"/> OCT.	GAIN CONSTANT: _____ db	INPUT IMPEDANCE: _____ ohms	(1) _____ (2) _____ (3) _____ (4) _____ (5) _____ (6) _____ (7) _____	
CONFIGURATION (MAG TAPE)	FIELD TRACE NOS.: _____				AUXILIARY DATA: _____				
	DATA CHANNEL NOS.: _____				AUXILIARY CHANNEL NOS.: _____				
PARAMETER	RECORD LENGTH: _____ sec.	SAMPLE RATE: <input type="checkbox"/> 1 ms. <input type="checkbox"/> 4 ms. <input type="checkbox"/> 2 ms. <input type="checkbox"/> _____ ms.	GAIN MODE: <input type="checkbox"/> INITIAL <input type="checkbox"/> FINAL	<input type="checkbox"/> MANUAL <input type="checkbox"/> OPERATE	FILTERS: _____	LO CUT _____ HZ SLOPE _____	FREQ. _____	HI CUT _____ HZ SLOPE _____	NOTCH FILTER: <input type="checkbox"/> IN <input type="checkbox"/> OUT
DISPLAY	MODE: <input type="checkbox"/> AGC <input type="checkbox"/> FLOAT <input type="checkbox"/> DEFLOAT <input type="checkbox"/> AMPLIFIER <input type="checkbox"/> DIRECT	INITIAL GAIN: _____ db	TRIP SENS: _____ db	POLARITY CONVENTION: <input type="checkbox"/> NEGATIVE <input type="checkbox"/> POSITIVE	PRESSURE INCREASE ON GEOPHONE: _____	<input type="checkbox"/> NUMBERS ON ON MAG. TAPE	<input type="checkbox"/> DOWNBREAK <input type="checkbox"/> UPBREAK	ON DISPLAY	
CFS I	TYPE STACK: _____	GATE LENGTH: _____	RECORD REJECTION: _____	NOISE REDUCTION: _____	NOISE THRESHOLD: _____	CORR. SCALING: _____	R.C.U. NORM/ALT SW.		
SOURCE	TYPE: <input type="checkbox"/> DYNAMITE <input type="checkbox"/> VIBROSEIS <input type="checkbox"/> OTHER	PATTERN: _____	NO. OF POSITIONS: _____	INLINE SPACING: _____	LATERAL SPACING: _____	STAGGER: _____	LENGTH: _____	WIDTH: _____	LATERAL OFFSET: _____
RECEIVER	CONNECTION: _____	RESISTANCE: _____ ohms	STAGGER: _____	INLINE SPACING: _____	LATERAL SPACING: _____	LENGTH: _____	WIDTH: _____	LATERAL OFFSET: _____	
SPREAD	NO. OF GROUPS: _____	GROUP INTERVAL: _____	SHOFPPOINT INTERVAL: _____	OFFSET GROUP: _____	FOLD: _____	OFFSET GROUP 48/96: _____	DIRECTION OF PROGRESSION: _____		

DIAGRAMS/MISC. INFORMATION:

SHOFPPOINT	TR. _____ TO _____		TR. _____ TO _____		SHOT				SPREAD				REMARKS	CORR. STACK				
	REEL NO.	REC.	REEL NO.	REC.	SIZE	DEPTH	NO.	OFFSET	DIR.	CDP SWITCH	#91	LINE GROUPS		#1	SET UP	TR 1-24	TR 25-48	TR 49-96
69	722698	116			11.0	10521				17	57.1		80.4		REC# 115 TEST SLASHED 1-78 95+96 820			
70		117			11.0	10522			13	58.1		81.9						
71		118			11.0	10523			9	59.1		82.4						
72		119			11.0	10524			5	60.1		83.4						
73		120			11.0	10525			49	61.1		84.4	3	INST 78.4 & 79.1				
74		121			11.0	10526			45	62.1		85.4						
75		122			11.0	10527			41	63.1		86.4						
76		123			11.0	10528			37	64.1		87.4						
77		124			11.0	10529			33	65.1		88.4						
78		125			11.0	10530	25	E	29	66.1		89.4						
79		126			11.0	10531			25	67.1		90.4						
80		127			11.0	10532			21	68.1		91.4						
81		128			11.0	10533			17	69.1		92.4		UP 3dB GALVO LEVEL				
82		129			11.0	10534			13	70.1		93.4						
83		130			11.0	10535			9	71.1		94.4						
84		131			11.0	10536	55	E	5	72.1		95.4						
85		132			11.0	10537	45	E	49	73.1		96.4	4	INST 90.4 & 91.1				
86		133			11.0	10538	55	S	45	74.1		97.4		T 4 NOISY				
87		134			11.0	10539			41	75.1		98.4		T 8 " (REPLANTED)				
88		135			11.0	10540	20	E	37	76.1		99.4						

# LAND SEISMIC RECORDING LOG

Page # 3 of 3

	CLIENT: <b>Husky</b>	PROSPECT: <b>SOUTHERN FOOTHILLS</b>	AREA: <b>N.P.R.-A ALASKA</b>	LINE NO: <b>607</b>						
	PARTY NO: <b>1186</b>	INST. ENG:		DATE: <b>MO 3 DAY 15 YR 79</b>						
INSTRUMENT (9-TRACK)	<input type="checkbox"/> 1 SYSTEM <input type="checkbox"/> 2 SYSTEMS	<input type="checkbox"/> 1-24 & 25-48 <input type="checkbox"/> 1-48 & 49-96	ODS & EVENS	TYPE: <input type="checkbox"/> DFS III <input type="checkbox"/> DFS IV <input type="checkbox"/> DFS V <input type="checkbox"/> OTHER	<input type="checkbox"/> 9 TRACK <input type="checkbox"/> 21 TRACK	FORMAT: _____ SEG. _____	<input type="checkbox"/> GAPPED <input type="checkbox"/> UNGAPPED	PACKING DENSITY: _____	(LO) <input type="checkbox"/> 356 BPI <input type="checkbox"/> 500 BPI	(HI) <input type="checkbox"/> 712 BPI <input type="checkbox"/> 1000 BPI
	NO. BYTES IN HEADER REC:	NO. BYTES IN RECORD ID:	NO. BYTES PER SCAN:	RECORD NUMBERS:	<input type="checkbox"/> DEC. <input type="checkbox"/> OCT.	GAIN CONSTANT: _____ db	INPUT IMPEDANCE: _____ ohms	(1) _____ (2) _____ (3) _____ (4) _____ (5) _____ (6) _____ (7) _____		
CONFIGURATION (MAG TAPE)	FIELD TRACE NOS. _____ DATA CHANNEL NOS. _____ (ON MAG TAPE)				AUXILIARY DATA: _____ AUXILIARY CHANNEL NOS.: _____					
PARAMETER	RECORD LENGTH: _____ sec.	SAMPLE RATE: <input type="checkbox"/> 1ms. <input type="checkbox"/> 4ms. <input type="checkbox"/> 2ms. <input type="checkbox"/> _____ ms.	GAIN MODE: <input type="checkbox"/> INITIAL <input type="checkbox"/> MANUAL <input type="checkbox"/> IF? <input type="checkbox"/> FINAL <input type="checkbox"/> OPERATE	FILTERS: _____	LO CUT _____ HZ HZ SLOPE _____	FREQ. _____	HI CUT _____ HZ HZ SLOPE _____	NOTCH FILTER: <input type="checkbox"/> IN <input type="checkbox"/> OUT		
DISPLAY	MODE: <input type="checkbox"/> AGC <input type="checkbox"/> FLOAT <input type="checkbox"/> DEFLAT <input type="checkbox"/> DIRECT	AMPLIFIER DIRECT	INITIAL GAIN: _____ db	TRIP SENS: _____ db	POLARITY CONVENTION: _____	PRESSURE INC REASE ON GEOPHONE: _____	<input type="checkbox"/> NEGATIVE <input type="checkbox"/> POSITIVE	NUMBERS ON MAG TAPE: _____	<input type="checkbox"/> DOWNBREAK <input type="checkbox"/> UPBREAK	ON DISPLAY
CFS I	TYPE STACK: _____	GATE LENGTH: _____	RECORD REJECTION: _____	NOISE REDUCTION: _____	NOISE THRESHOLD: _____	CORR. SCALING: _____	R.C.U. NORM/ALT SW: _____			
SOURCE	TYPE: <input type="checkbox"/> DYNAMITE <input type="checkbox"/> VIBROSEIS <input type="checkbox"/> OTHER	PATTERN: _____	NO. OF POSITIONS: _____	INLINE SPACING: _____	LATERAL SPACING: _____	STAGGER: _____	LENGTH: _____	WIDTH: _____	LATERAL OFFSET: _____	
RECEIVER	CONNECTION: _____	RESISTANCE: _____ ohms	STAGGER: _____	LENGTH: _____	WIDTH: _____	LATERAL OFFSET: _____				
SPREAD	NO. OF GROUPS: _____	GROUP INTERVAL: _____	SHOTPOINT INTERVAL: _____	FOLD: _____	DIRECTION OF PROGRESSION: _____	LEADING GROUP: _____				

DIAGRAMS/MISC. INFORMATION:

SHOTPOINT	TR. to		TR. to		SHOT				SPREAD			REMARKS	CORR. STACK				
	REEL NO.	REC.	REEL NO.	REC.	SIZE	DEPTH	NO.	OFFSET	DIR.	CDP SWITCH	LINE GROUPS		NO.	TR. 1-24	TR. 25-48	TR. 49-96	TR. 100-120
87	722608	1136			110	10541				33	77.1	100.4					
90		1137			110	10542				29	78.1	101.4					
91		1138			110	10543	25	W		25	79.1	102.4					
92		1139			110	10544				21	80.1	103.4					
93		1140			110	10545	50	E		17	81.1	104.4					
94		1141			110	10546				13	82.1	105.4					
95		1142			110	10547	80	N		9	83.1	106.4					
96		1143			110	10548				5	84.1	107.4					

# LAND SEISMIC RECORDING LOG

CLIENT: <b>Husky</b>		PROSPECT: <b>Southern Foothills</b>		AREA: <b>NPR-A ALASKA</b>		LINE NO: <b>607</b>			
PARTY NO: <b>1186</b>		INST. ENG:		LEAVE BASE <b>7:30</b> ARRIVE FIELD <b>8:30</b>		LEAVE FIELD <b>5:30</b> ARRIVE BASE <b>6:00</b>		DATE: <b>MO 03 DAY 16 YR 79</b>	
INSTRUMENT: <b>19-TRACK</b> <input type="checkbox"/> 1 SYSTEM <input type="checkbox"/> 2 SYSTEMS <input type="checkbox"/> 1-24 & 25-46 <input type="checkbox"/> 1-48 & 49-96 <input type="checkbox"/> ODDS <input type="checkbox"/> EVENS		TYPE: <input type="checkbox"/> DFS I <input type="checkbox"/> DFS II <input type="checkbox"/> DFS III <input type="checkbox"/> OTHER		<input type="checkbox"/> 1 TRACK <input type="checkbox"/> 2 TRACK <input type="checkbox"/> 3 TRACK		GAPPED <input type="checkbox"/> UNGAPPED		PACKING DENSITY: (1) <input type="checkbox"/> 356 BPI (2) <input type="checkbox"/> 800 BPI (3) <input type="checkbox"/> 712 BPI (4) <input type="checkbox"/> 1000 BPI	
NO. BYTES IN HEADER REC: <b>128</b>		NO. BYTES IN RECORD ID:		NO. BYTES PER SCAN: <b>254</b>		RECORD NUMBERS:		GAIN CONSTANT: <b>36</b> db	
CONFIGURATION (MAG TAPE)		FIELD TRACE NOS.: <b>1-96</b>		DATA CHANNEL NOS.: <b>1-96</b>		AUXILIARY DATA:			
PARAMETER		RECORD LENGTH: <b>8</b> sec		SAMPLE RATE: <input type="checkbox"/> 1 ms. <input type="checkbox"/> 4 ms.		GAIN MODE: <input type="checkbox"/> INITIAL <input type="checkbox"/> MANUAL <input type="checkbox"/> OPERATE		FILTERS:	
DISPLAY		MODE: <input type="checkbox"/> FLOAT <input type="checkbox"/> AMPLIFIER <input type="checkbox"/> DEFLOAT <input type="checkbox"/> DIRECT		INITIAL GAIN:		TRIP SENS:		POLARITY CONVENTION:	
CFS I		TYPE STACK:		GATE LENGTH:		RECORD REJECTION:		NOISE REDUCTION:	
SOURCE		TYPE: <input type="checkbox"/> DYNAMITE <input type="checkbox"/> VIBROSEIS <input type="checkbox"/> OTHER		PATTERN: <b>Single (Inline)</b>		NO. OF POSITIONS:		INLINE SPACING:	
RECEIVER		TYPE: <b>HL 1016</b>		PATTERN: <b>INLINE</b>		NO. OF ELEMENTS: <b>10</b>		INLINE SPACING:	
SPREAD		NO. OF GROUPS:		GROUP INTERVAL: <b>220'</b>		SHOTPOINT INTERVAL: <b>880'</b>		FOLD: <b>1200%</b>	

DIAGRAMS/MISC. INFORMATION:  
 East #1  $\xrightarrow{48}$  A  $\xrightarrow{49}$   $\xrightarrow{96}$  West

SHOTPOINT	TR. 10		TR. 20		SHOT		SPREAD		REMARKS	CORR. STACK		
	REEL NO.	REC.	REEL NO.	REC.	SIZE	DEPTH	NO. OFFSET	DIR.		COP SWITCH	LINE GROUPS	TR 1-10
97	722-1008	1516			N10	105	1	49	95.1	108.4		
98		1517			N10	105	2	45	86.1	109.4		
99		1518			N10	105	3	41	87.1	110.4		
100		1519			N10	105	4	37	88.1	111.4		
101		1560			N10	105	5	33	89.1	112.4		
102		1561			N10	105	6	29	90.1	113.4		
103		1562			N10	105	7	25	91.1	114.4		
104		1563			N10	105	8	21	92.1	115.4		
105		1564			N10	105	9	17	93.1	116.4		
106	722-1009	1565			N10	105	10	13	94.1	117.4		
107		1566			N10	105	11	9	95.1	118.4		
108		1567			N10	105	12	5	96.1	119.4		
109		1568			N10	105	13	49	97.1	120.4		
110		1569			N10	105	14	45	98.1	121.4		
111		1570			N10	105	15	41	99.1	122.4		
112		1571			N10	105	16	37	100.1	123.4		
113		1572			N10	105	17	33	101.1	124.4		
114		1573			N10	105	18	29	102.1	125.4		
115		1574			N10	105	19	25	103.1	126.4		
116		1575			N10	105	20	21	104.1	127.4		

\* 100

File # 144 - Daily Tests

\* E.O. Range # 4  
 B.O. Range # 5

Tape Change File # 165 IFP

F-1+2 NOISY

Waiting on Drills

CRN 175 PLF. F O NOISY

\* Begin Range # 5 @ 5/1101 Rec 160X for continuation of Line





# LAND SEISMIC RECORDING LOG

CLIENT: <b>HUSKY</b>		PROSPECT: <b>Southern Foothills</b>		AREA: <b>APR-A ALASKA</b>		LINE NO: <b>607</b>	
PARTY NO: <b>1186</b>		INST. ENG: <b>Panko - DeLoe Jr</b>		LEAVE BASE <b>2:00 A.M.</b>		DATE: <b>MO 03 DAY 17 YR 79</b>	
ARR. FIELD <b>9:00 AM</b>		ARR. BASE <b>5:30</b>		ARR. BASE <b>7:00</b>			
INSTRUMENT: <input type="checkbox"/> 1 SYSTEM <input checked="" type="checkbox"/> 2 SYSTEMS		ODDS: <input type="checkbox"/> 1-24 & 25-48 <input type="checkbox"/> 1-48 & 49-96		TYPE: <input type="checkbox"/> DFS III <input type="checkbox"/> DFS II <input type="checkbox"/> DFS I <input type="checkbox"/> OTHER		TRACK: <input type="checkbox"/> 9 TRACK <input type="checkbox"/> 21 TRACK	
NO. BYTES IN HEADER REC: <b>128</b>		NO. BYTES IN RECORD ID: <b>254</b>		NO. BYTES PER SCAN: <b>254</b>		RECORD NUMBERS: <input type="checkbox"/> DEC. <input type="checkbox"/> OCT.	
CONFIGURATION (MAG TAPE): FIELD TRACE NOS.: <b>1-96</b>		DATA CHANNEL NOS.: <b>1-26</b>		(ON MAG TAPE)		AUXILIARY DATA: AUXILIARY CHANNEL NOS.: _____	
PARAMETER: RECORD LENGTH: <b>0</b> sec.		SAMPLE RATE: <input type="checkbox"/> 1 ml. <input type="checkbox"/> 4 ml. <input type="checkbox"/> 2 sec. <input type="checkbox"/> 4 sec.		GAIN MODE: <input type="checkbox"/> INITIAL <input type="checkbox"/> MANUAL <input type="checkbox"/> OPERATE		FILTERS: FREQ. <b>8</b> LO CUT HZ SLOPE <b>18</b>	
DISPLAY: MODE: <input type="checkbox"/> AGC <input type="checkbox"/> FLOAT <input type="checkbox"/> DEFOAT <input type="checkbox"/> DIRECT		INITIAL GAIN: _____ db		JIP SENS: _____ db		FREQ. <b>128</b> HI CUT HZ SLOPE <b>22</b>	
CFS I: TYPE STACK: _____		GATE LENGTH: _____		RECORD REJECTION: _____		POLARITY CONVENTION: <input type="checkbox"/> POSITIVE <input type="checkbox"/> NEGATIVE	
SOURCE: TYPE: <input type="checkbox"/> DYNAMITE <input type="checkbox"/> VIBROSEIS <input type="checkbox"/> OTHER		PATTERN: <b>Single (inline)</b>		NO. OF POSITIONS: _____		PRESSURE INCREASE ON GEOPHONE: <input type="checkbox"/> POSITIVE <input type="checkbox"/> NEGATIVE	
RECEIVER: TYPE: <b>HSC 104g</b>		CONNECTION: <b>SERIES</b>		RESISTANCE: _____ ohms		NOISE REDUCTION: _____	
SPREAD: NO. OF GROUPS: _____		GROUP INTERVAL: <b>220'</b>		OFFSET GROUP: <b>48, 110'</b>		STAGGER: _____	
DIAGRAMS/MISC. INFORMATION:		SP: <b>4</b>		CHG/ HOLE: <b>110</b>		HOLE DEPTH: <b>105'</b>	
CARC #1 <b>10,340</b> → <b>48</b>		<b>49</b> → <b>10,340</b>		→ <b>96</b> WEST.		SWEEP START: _____	
						SWEEP END: _____	
						SWEEP LENGTH: _____	
						SWEEP TAPER: _____	
						PHASE COMP: _____	
						LATERAL SPACING: _____	
						LATERAL OFFSET: _____	
						DIRECTION OF PROGRESSION: <b>East</b>	
						LEADING GROUP: <b>1</b>	

SHOTPOINT	TR. _____ to _____		TR. _____ to _____		SHOT		SPREAD		REMARKS	CORR. STACK				
	REEL NO.	REC.	REEL NO.	REC.	SIZE	DEPTH	NO.	OFFSET		DIR.	CDP SWITCH	LINE GROUPS		TR. 1-25
121	7226	187			110	105	1	109.1	30°W	49	109.1	132.4		
122		185			110	105	2	110.1		45	110.1	133.4		
123		186			110	105	3	111.1	30°E	41	111.1	134.4		
124		188			110	105	4	112.1	30°W	37	112.1	135.4		
125		189			110	105	5	113.1	60°N	33	113.1	136.4		
126		200			110	105	6	114.1		29	114.1	137.4		
127		201			110	105	7	115.1	30°W	25	115.1	138.4		
128		202			110	105	8	116.1		21	116.1	139.4		
129		203			110	105	9	117.1		17	117.1	140.4		
130		204			110	105	10	118.1		13	118.1	141.4		
131		205			110	105	11	119.1	60°W	9	119.1	142.4		
132		206			110	105	12	120.1		5	120.1	143.4		
133		207			110	105	13	121.1		49	121.1	144.4		
134		208			110	105	14	122.1		45	122.1	145.4		
135		209			110	105	15	123.1		41	123.1	146.4		
136		210			110	105	16	124.1	30°W	37	124.1	147.4		
137		211			110	105	17	125.1	60°W	33	125.1	148.4		
138		212			110	105	18	126.1	30°E	29	126.1	149.4		
139		213			110	105	19	127.1	60°E	25	127.1	150.4		
140		214			110	105	20	128.1		21	128.1	151.4		



# LAND SEISMIC RECORDING LOG

		CLIENT: <u>Husky</u>	PROSPECT: <u>Southern Foothills</u>	AREA: <u>NPR-A</u>	LINE NO.: <u>607</u>			
PARTY NO.: <u>1186</u>		INST. ENG.:		DATE: <u>NO. 23 DAY 10. 1979</u>				
INSTRUMENT (9-TRACK)	<input type="checkbox"/> 1 SYSTEM <input type="checkbox"/> 2 SYSTEMS	<input type="checkbox"/> 1-24 & 25-48 <input type="checkbox"/> 1-48 & 49-96	ODDS <input type="checkbox"/> EVENS	TYPE: <input type="checkbox"/> DFS III <input type="checkbox"/> DFS IV	<input type="checkbox"/> 9 TRACK <input type="checkbox"/> 21 TRACK	FORMAT: SEC	<input type="checkbox"/> GAPPED <input type="checkbox"/> UNGAPPED	PACKING DENSITY: (1) <input type="checkbox"/> 336 BPI (II) <input type="checkbox"/> 500 BPI
	NO. BYTES IN HEADER REC:	NO. BYTES IN RECORD ID:	NO. BYTES PER SCAN:	RECORD NUMBERS:	<input type="checkbox"/> DEC. <input type="checkbox"/> OCT.	GAIN CONSTANT: _____ db	INPUT IMPEDANCE: _____ ohms	(1) (2) (3) (4) (5) (6) (7)
CONFIGURATION (MAG TAPE)	FIELD TRACE NOS.: _____ DATA CHANNEL NOS.: _____			AUXILIARY DATA: _____ AUXILIARY CHANNEL NOS.: _____				
PARAMETER	RECORD LENGTH: _____ sec.	SAMPLE RATE: <input type="checkbox"/> 1 ms. <input type="checkbox"/> 4 ms. <input type="checkbox"/> 2 ms. <input type="checkbox"/> _____ ms.	GAIN MODE: <input type="checkbox"/> INITIAL <input type="checkbox"/> IFF	<input type="checkbox"/> MANUAL <input type="checkbox"/> OPERATE	FILTERS: FREQ. _____	LO CUT HZ SLOPE _____	HI CUT HZ SLOPE _____	NOTCH FILTER: <input type="checkbox"/> IN <input type="checkbox"/> OUT
DISPLAY	MODE: <input type="checkbox"/> AGC <input type="checkbox"/> FLOAT <input type="checkbox"/> DEFLOAT <input type="checkbox"/> DIRECT	AMPLIFIER <input type="checkbox"/> DIRECT	INITIAL GAIN: _____ db	TRIP SENS: _____ db	POLARITY CONVENTION: <input type="checkbox"/> NEGATIVE <input type="checkbox"/> POSITIVE	PRESSURE INCREASE ON GEOPHONE: _____	NUMBERS ON MAG. TAPE <input type="checkbox"/> DOWNBREAK <input type="checkbox"/> UPBREAK	ON DISPLAY
CFS I	TYPE STACK:	GATE LENGTH: _____	RECORD REJECTION: _____	NOISE REDUCTION: _____	NOISE THRESHOLD: _____	CORR. SCALING: _____	R.C.U. NORM./ALT SW.	
SOURCE	TYPE: <input type="checkbox"/> DYNAMITE <input type="checkbox"/> VIBROSEIS <input type="checkbox"/> OTHER	PATTERN: _____	NO. OF POSITIONS: _____	INLINE SPACING: _____	LATERAL SPACING: _____	STAGGER: _____	LENGTH: _____	WIDTH: _____
RECEIVER	CONNECTION: _____	RESISTANCE: _____	NO. OF ELEMENTS: _____	STAGGER: _____	INLINE SPACING: _____	LENGTH: _____	WIDTH: _____	LATERAL OFFSET: _____
SPREAD	NO. OF GROUPS: _____	GROUP INTERVAL: _____	SHOTPOINT INTERVAL: _____	FOLD: _____	OFFSET GROUP: _____	OFFSET GROUP 48/96: _____	DIRECTION OF PROGRESSION: LEADING GROUP: _____	

DIAGRAMS/MISC. INFORMATION:

SHOTPOINT	TR _____ to _____		TR _____ to _____		SHOT				SPREAD		REMARKS	CORR. STACK					
	REEL NO.	REC.	REEL NO.	REC.	SIZE	DEPTH	NO. OFFSET	DIR.	CDP SWITCH	LINE GROUPS		TR 24	TR 48	TR 96	REC.		
1671	22610	241	17	2023	20	27	29	30	35	37	17	147.1	170.4				
168		241			110	105	21	NE	110	13	148.1	171.4	Waiting on Drills				
167		242			110	105	23	SE	110	9	149.1	172.4	" " " "				
162		249			110	105	24	SE	110	5	150.1	173.4	" " " "				
163		250			110	105	25		110	49	151.1	174.4	3	" " " "			
164		251			110	105	26	SE	110	45	152.1	175.4	" " " "				
165		252			110	105	27	SE	110	41	153.1	176.4	" " " "				
166		253			110	105	28		110	39	154.1	177.4	" " " "				
167		254			110	105	29		110	33	155.1	178.4	" " " "				
168		255			110	105	30		110	29	156.1	179.4	" " " "				
169		256			110	105	31	SE	110	25	157.1	180.4	Waiting on Drills				
170		257			110	105	32	SE	110	21	158.1	181.4	" " " "				
171		258			110	105	33		110	17	159.1	182.4	" " " "				

# LAND SEISMIC RECORDING LOG

CLIENT: <b>Husky</b>		PROSPECT: <b>Southern Foothills</b>		AREA: <b>NPR-A ALASKA</b>		LINE NO.: <b>607</b>	
PARTY NO.: <b>1186</b>		INST. ENG.: <b>PANKO - DELEDE</b>		LEAVE BASE - NORMAN: <b>1400 FIELD - S.W.A.A.</b>		DATE: <b>MO 03 DAY 19 YR 79</b>	
INSTRUMENT (P-TRACK) <input checked="" type="checkbox"/> 1 SYSTEM <input checked="" type="checkbox"/> 2 SYSTEMS		<input type="checkbox"/> 1-24 & 25-48 <input type="checkbox"/> 1-49 & 49-96		TYPE: <input type="checkbox"/> DFS III <input type="checkbox"/> DFS IV		<input type="checkbox"/> 9 TRACK <input type="checkbox"/> 21 TRACK	
NO. BYTES IN HEADER REC.: <b>128</b>		NO. BYTES IN RECORD ID: _____		NO. BYTES PER SCAN: <b>254</b>		RECORD NUMBERS: _____	
CONFIGURATION (MAG TAPE) FIELD TRACE NOS.: <b>1-26</b> DATA CHANNEL NOS.: <b>1-26</b>		[ON MAG TAPE]		AUXILIARY DATA:		AUXILIARY CHANNEL NOS.: _____	
PARAMETER RECORD LENGTH: <b>8</b>		SAMPLE RATE: <input type="checkbox"/> 1 ms. <input type="checkbox"/> 4 ms.		GAIN MODE: <input type="checkbox"/> INITIAL <input checked="" type="checkbox"/> TRIP		FILTERS: _____	
DISPLAY MODE: <input type="checkbox"/> FLOAT <input type="checkbox"/> AMPLIFIER <input checked="" type="checkbox"/> AGC <input type="checkbox"/> DEFOAT <input type="checkbox"/> DIRECT		INITIAL GAIN: _____		TRIP SENS.: _____		POLARITY CONVENTION: _____	
CFS I TYPE: _____ STACK: _____		GATE LENGTH: _____		RECORD REJECTION: _____		NOISE REDUCTION: _____	
SOURCE TYPE: <input checked="" type="checkbox"/> DYNAMITE <input type="checkbox"/> VIBROSEIS <input type="checkbox"/> OTHER		PATTERN: <b>Single (Inline)</b>		NO. OF POSITIONS: _____		LATERAL SPACING: _____	
RECEIVER TYPE: <b>1157 1014</b>		PATTERN: <b>INLINE</b>		NO. OF ELEMENTS: <b>18</b>		LATERAL SPACING: _____	
SPREAD NO. OF GROUPS: _____		GROUP INTERVAL: _____		SHOTPOINT INTERVAL: <b>880'</b>		FOLD: <b>1200%</b>	
OFFSET GROUP 1: <b>10,450</b>		OFFSET GROUP 48: <b>110'</b>		OFFSET GROUP 49: <b>110'</b>		DIRECTION OF PROGRESSION: <b>EAST</b>	

DIAGRAMS/MISC. INFORMATION:  
*Last #1 10,340 → 48 49 → 10,340 → 96 WEST*

SHOTPOINT	TR. 10		TR. 10		SHOT		SPREAD		REMARKS	CORR. STACK		
	REEL NO.	REC.	REEL NO.	REC.	SIZE	DEPTH	NO. OFFSET	DIR.		COP SWITCH	LINE GROUPS	TR 10-11
1773	2226110	277			N10	105	1	25° E	49	160.1	183.4	1
1773		277			N10	105	2	30° E	45	161.1	184.4	
1774		277			N10	105	3	30° E	41	162.1	185.4	
1775		277			N10	105	4		37	163.1	186.4	
1776	2226111	277			N10	105	5	40° W	33	164.1	187.4	
1777		277			N10	105	6		29	165.1	188.4	
1778		277			N10	105	7		25	166.1	189.4	
1779		280			N10	105	8	30° E	21	167.1	190.4	
1780		281			N10	105	9		17	168.1	191.4	
1781		282			N10	105	10		13	169.1	192.4	
1782		283			N10	105	11	25° S	9	170.1	193.4	
1783		284			N10	105	12	25° W	5	171.1	194.4	
1784		285			N10	105	13	30° E	49	172.1	195.4	2
1785		286			N10	105	14		45	173.1	196.4	
1786		287			N10	105	15		41	174.1	197.4	
1787		288			N10	105	16		37	175.1	198.4	
1788		289			N10	105	17		33	176.1	199.4	
1789		290			N10	105	18	25° E	29	177.1	200.4	
1790		291			N10	105	19	30° E	25	178.1	201.4	
1791		292			N10	105	20		21	179.1	202.4	

File # 259-271 Daily Tests

Tape Change File # 276 IFP

TR #1 Noisy  
Lasts group Noisy 4+5

# LAND SEISMIC RECORDING LOG

		CLIENT: <b>Husky</b>	PROSPECT: <b>Southern Foothills</b>	AREA: <b>NPR-A</b>	LINE NO.: <b>607</b>		
PARTY NO.: <b>186</b>		INST. ENG.:			DATE: <b>MO 03 DAY 19 YR 79</b>		
INSTRUMENT (9-TRACK)	<input type="checkbox"/> 1 SYSTEM <input type="checkbox"/> 2 SYSTEMS	<input type="checkbox"/> 1-24 & 25-48 <input type="checkbox"/> 1-48 & 49-96	ODDS & EVENS <input type="checkbox"/>	TYPE: <input type="checkbox"/> DFS III <input type="checkbox"/> DFS II <input type="checkbox"/> OTHER	<input type="checkbox"/> 9 TRACK <input type="checkbox"/> 21 TRACK	FOPMAT: <input type="checkbox"/> SEG <input type="checkbox"/> GAPPED <input type="checkbox"/> UNGAPPED	PACKING DENSITY: (L) <input type="checkbox"/> 356 BPI <input type="checkbox"/> 800 BPI (H) <input type="checkbox"/> 712 BPI <input type="checkbox"/> 1600 BPI
	NO. BYTES IN HEADER REC:	NO. BYTES IN RECORD ID 1:	NO. BYTES PER SCAN:	RECORD NUMBERS:	<input type="checkbox"/> DEC. <input type="checkbox"/> OCT.	GAIN CONSTANT: _____ db	INPUT IMPEDANCE: _____ ohms
CONFIGURATION (MAG TAPE)	FIELD TRACE NOS.:			AUXILIARY DATA:			
	DATA CHANNEL NOS.:			AUXILIARY CHANNEL NOS.:			
PARAMETER	RECORD LENGTH: _____ sec.	SAMPLE RATE: <input type="checkbox"/> 1 mt. <input type="checkbox"/> 4 mt. <input type="checkbox"/> 2 ms. <input type="checkbox"/> 4 ms.	GAIN MODE: <input type="checkbox"/> INITIAL <input type="checkbox"/> FINAL <input type="checkbox"/> IFF <input type="checkbox"/> MANUAL <input type="checkbox"/> OPERATE	FILTERS: _____	LO CUT HZ SLOPE: _____	HI CUT HZ SLOPE: _____	NOTCH FILTER: <input type="checkbox"/> IN <input type="checkbox"/> OUT
DISPLAY	MODE: <input type="checkbox"/> AOC <input type="checkbox"/> FLOAT <input type="checkbox"/> DEFLOAT <input type="checkbox"/> AMPLIFIER <input type="checkbox"/> DIRECT	INITIAL GAIN: _____ db	TRIP SENS: _____ db	POLARITY CONVENTION: _____	PRESSURE INCREASE ON GEOPHONE: _____	<input type="checkbox"/> NEGATIVE <input type="checkbox"/> POSITIVE	NUMBERS ON MAG TAPE: <input type="checkbox"/> DOWNBREAK <input type="checkbox"/> UPBREAK ON DISPLAY: <input type="checkbox"/> A.C.U. NORM/ATT SW.
CFS I	TYPE STACK:	GATE LENGTH:	RECORD REJECTION:	NOISE REDUCTION:	NOISE THRESHOLD:	CORR SCALING:	
SOURCE	TYPE: <input type="checkbox"/> DYNAMITE <input type="checkbox"/> VISROSEIS <input type="checkbox"/> OTHER	PATTERN:	NO. OF POSITIONS:	INLINE SPACING:	LATERAL SPACING:	STAGGER:	LENGTH:
		CHG/HOLE:	HOLE DEPTH:	SWEEP POSITION:	SWEEP START:	SWEEP END:	SWEEP LENGTH:
RECEIVER	TYPE:	PATTERN:	NO. OF ELEMENTS:	INLINE SPACING:	LATERAL SPACING:	STAGGER:	LENGTH:
	CONNECTION:	RESISTANCE:	ohms	STAGGER:	LENGTH:	WIDTH:	LATERAL OFFSET:
SPREAD	NO. OF GROUPS:	GROUP INTERVAL:	SHOTPOINT INTERVAL:	FOLD:	DIRECTION OF PROGRESSION:	LEADING GROUP:	
	OFFSET GROUP 1:	OFFSET GROUP:	OFFSET GROUP:	OFFSET GROUP #8/96:			

DIAGRAMS/MISC. INFORMATION:

SHOTPOINT	TR. _____ to _____		TR. _____ to _____		SHOT					SPREAD		REMARKS	CORR STACK			
	REEL NO.	REC.	REEL NO.	REC.	SIZE	DEPTH	NO.	OFFSET	DIR.	CDP SWITCH	LINE GROUPS		TR 41	TR 42	TR 43	TR 44
199	227	293			110	105	21			17	180.1	203.4				
199		294			110	105	22			13	181.1	204.4				
199		285			110	105	23	60 S		9	182.1	205.4				
195		296			110	105	24			5	183.1	206.4				
196		297			110	105	25			<del>25</del>	184.1	207.4	3			
197		298			110	105	26			21	185.1	208.4				
198		299			110	105	27			17	186.1	209.4				
199		300			110	105	28	30 E		13	187.1	210.4				
200		301			110	105	29			9	188.1	211.4				
201		302			110	105	30			5	189.1	212.4				

## LAND SEISMIC RECORDING LOG

CLIENT: <b>Husky</b>		PROSPECT: <b>Southern Foothills</b>		AREA: <b>NPR-A ALASKA</b>		LINE NO.: <b>607</b>			
PARTY NO.: <b>1186</b>		INST. ENG.: <b>1-24 &amp; 25-48</b>		LEAVE BASE: <b>7:00 A.M.</b>		LEAVE FIELD: <b>3:00 P.M.</b>		DATE: <b>NO 03 DAY 20 YR 79</b>	
INSTRUMENT: <input checked="" type="checkbox"/> 1 SYSTEM <input checked="" type="checkbox"/> 2 SYSTEMS		ODDS & EVENS: <input type="checkbox"/> ODDS <input type="checkbox"/> EVENS		TYPE: <input type="checkbox"/> DFS III <input type="checkbox"/> DFS II <input type="checkbox"/> OTHER		<input type="checkbox"/> 1 TRACK <input type="checkbox"/> 2 TRACK		FORMAT: <b>B</b>	
NO. BYTES IN HEADER REC.: <b>128</b>		NO. BYTES IN RECORD ID.: <b>254</b>		RECORD NUMBERS: <input type="checkbox"/> DEC. <input type="checkbox"/> OCT.		GAIN CONSTANT: <b>36</b> db		INPUT IMPEDANCE: <b>2000</b> ohms	
CONFIGURATION (MAG TAPE):		FIELD TRACE NOS.: <b>1-96</b>		DATA CHANNEL NOS.: <b>1-96</b>		AUXILIARY DATA:		AUXILIARY CHANNEL NOS.:	
PARAMETER:		RECORD LENGTH: <b>8</b> sec.		SAMPLE RATE: <input type="checkbox"/> 1 ms. <input type="checkbox"/> 4 ms.		GAIN MODE: <input type="checkbox"/> INITIAL <input type="checkbox"/> MANUAL <input type="checkbox"/> OPERATE		FILTERS:	
DISPLAY:		MODE: <input type="checkbox"/> FLOAT <input type="checkbox"/> AMPLIFIER <input type="checkbox"/> DEFLOAT <input type="checkbox"/> DIRECT		INITIAL GAIN:		TRIP SENS.:		POLARITY CONVENTION:	
CFS I:		TYPE STACK:		GATE LENGTH:		RECORD REJECTION:		NOISE REDUCTION:	
SOURCE:		TYPE: <input checked="" type="checkbox"/> DYNAMIC <input type="checkbox"/> VIBROSEIS <input type="checkbox"/> OTHER		PATTERN: <b>Single (Inline)</b>		NO. OF POSITIONS:		INLINE SPACING:	
RECEIVER:		TYPE: <b>Hex 10 1/2"</b>		PATTERN: <b>Inline</b>		NO. OF ELEMENTS: <b>18</b>		INLINE SPACING:	
CONNECTION: <b>SERIES</b>		RESISTANCE:		SWEEP POSITION:		SWEEP START:		SWEEP END:	
SPREAD:		NO. OF GROUPS:		GROUP INTERVAL: <b>220'</b>		SHOTPOINT INTERVAL: <b>880'</b>		FOLD: <b>1200'6</b>	
OFFSET GROUP 1: <b>10,450</b>		OFFSET GROUP 4B: <b>110'</b>		OFFSET GROUP 49: <b>110'</b>		OFFSET GROUP 48/96: <b>10,450</b>		DIRECTION OF PROGRESSION: <b>EAST</b>	

**DIAGRAMS/MISC. INFORMATION:**

*East #1* — 10,340 —> AB 4 49 — 10,340 —> 96# WEST.

SHOTPOINT	TR. 10		TR. 20		SHOT			SPREAD		REMARKS	CORR. STACK			
	REEL NO.	REC.	REEL NO.	REC.	SIZE	DEPTH	NO. OFFSET	DIR.	CDP SWITCH		LINE GROUPS	TR 1-48	TR 49-72	TR 73-96
302	2261	315			110	105	1		49	190.1	213.4			
303		316			110	106	2		49	191.1	214.4			
304		317			110	105	3		41	192.1	215.4			
305		318			110	105	4	65°E	37	193.1	216.4			
306		319			110	105	5	85°E	33	194.1	217.4			
307		320			110	106	6		29	195.1	218.4			
308		321			110	106	7		25	196.1	219.4			
309		322			110	105	8		21	197.1	T-4			
310		323			110	105	9	84°S	17	198.1	T-8			
311		324			110	105	10		13	199.1	T-12			
312	2261R	325			110	105	11		9	200.1	T-16			TAPE CHANGE FILE# 325 BFP
313		327			110	105	12		5	201.1	T-20			
314		328			110	105	13		25	202.1	T-24			
315		329			110	105	14	EN S	21	203.1	T-28			
316		330			110	105	15		17	204.1	T-32			Record Blasted
317		331			110	105	16	21°E	13	205.1	T-36			
318		332			110	106	17	32°W	9	206.1	T-40			
319		333			110	106	18		5	207.1	T-44			
320		334			110	105	19		1	208.1	T-49			End of line 607 No. way