

# Ann's Copy

## LAND SEISMIC RECORDING LOG

14.5 Hours



CLIENT:	Husky	PROSPECT:	NPR-A	AREA:	Barrow	LINE NO.:	608										
	PARTY NO.:		1182		INST. ENG.:		Windham	DATE:	MO 2 DAY 22 YR 79								
INSTRUMENT (9-TRACK)	<input checked="" type="checkbox"/> 1 SYSTEM <input type="checkbox"/> 2 SYSTEMS	<input type="checkbox"/> 1-24 & 25-48 <input type="checkbox"/> 1-48 & 49-96	ODDS EVEN	TYPE:	<input type="checkbox"/> DFS III <input type="checkbox"/> DFS II <input type="checkbox"/> OTHER	<input checked="" type="checkbox"/> 9 TRACK <input type="checkbox"/> 21 TRACK	FORMAT: SEG B	<input type="checkbox"/> GAPPED <input type="checkbox"/> UNGAPPED	PACKING DENSITY:	(LO) <input type="checkbox"/> 354 BPI <input type="checkbox"/> 900 BPI	(HI) <input type="checkbox"/> 712 BPI <input type="checkbox"/> 1800 BPI						
	NO. BYTES IN HEADER REC.:	NO. BYTES IN RECORD ID.:	NO. BYTES PER SCAN:	134	RECORD NUMBERS:	<input checked="" type="checkbox"/> DEC. <input type="checkbox"/> OCT	GAIN CONSTANT:	36 db	INPUT IMPEDANCE:	20,000 ohms							
CONFIGURATION (MAG TAPE)	FIELD TRACE NOS.:	1-48	(ON MAG TAPE)			AUXILIARY DATA:	(1) FO (2) 04 (3) (4) (5) (6) (7)										
	DATA CHANNEL NOS.:	1-48				AUXILIARY CHANNEL NOS.:	3 4										
PARAMETER	RECORD LENGTH:	6 sec.	SAMPLE RATE:	<input type="checkbox"/> 1 ms. <input type="checkbox"/> 4 ms. ms.	GAIN MODE:	<input type="checkbox"/> INITIAL <input type="checkbox"/> MANUAL <input type="checkbox"/> IFF <input type="checkbox"/> OPERATE	FILTERS:	FREQ 8	LO CUT HZ SLOPE 10	FREQ 128	HI CUT HZ SLOPE 70	NOTCH FILTER:	<input type="checkbox"/> IN <input checked="" type="checkbox"/> OUT				
DISPLAY	MODE:	<input checked="" type="checkbox"/> AGC <input type="checkbox"/> FLOAT <input type="checkbox"/> AMPLIFIER <input type="checkbox"/> DEFOAT <input type="checkbox"/> DIRECT	INITIAL GAIN:	19 db	TRIP SENS:	18 db	POLARITY CONVENTION:	<input type="checkbox"/> PRESSURE INCREASE <input type="checkbox"/> POSITIVE	<input type="checkbox"/> NEGATIVE	<input type="checkbox"/> NUMBERS ON ON MAG TAPE	<input type="checkbox"/> DOWNBREAK <input type="checkbox"/> UPBREAK	<input type="checkbox"/> ON DISPLAY					
CFS I	TYPE STACK:		GATE LENGTH:		RECORD REJECTION:		NOISE REDUCTION:		NOISE THRESHOLD:		CORR. SCALING:		R.C.U. NORM/ALT SW.				
SOURCE	TYPE:	<input checked="" type="checkbox"/> DYNAMITE <input type="checkbox"/> VIBROSEIS <input type="checkbox"/> OTHER	PATTERN:	Single hole - Inline	NO. OF POSITIONS:	1	INLINE SPACING:		LATERAL SPACING:		STAGGER:		LENGTH:		WIDTH:		LATERAL OFFSET:
RECEIVER	TYPE:	Gsc-20d	PATTERN:	Inline	NO. OF ELEMENTS:	18	INLINE SPACING:	18'	LATERAL SPACING:		STAGGER:		LENGTH:		WIDTH:		LATERAL OFFSET:
SPREAD	CONNECTION:	Series-Parallel	RESISTANCE:	560 ohms	STAGGER:		LENGTH:		WIDTH:		LATERAL OFFSET:						
SPREAD	NO. OF GROUPS:	48	GROUP INTERVAL:	330'	SHOTPOINT INTERVAL:	1320'	FOLD:	6	DIRECTION OF PROGRESSION:	S → N	LEADING GROUP:	48	OFFSET GROUP 46/96:	7755'			
DIAGRAMS/MISC. INFORMATION:	<p>FR-1 24 group trail 124-35A1 2          TR-245 CTR-35          File# 362 → 370 Daily Test          File# 371 TEST TA</p>																

SHOTPOINT	TR 1 to 48		TR 49 to 96		SHOT		SPREAD		REMARKS	CORR STACK				
	REEL NO.	REC.	REEL NO.	REC.	SIZE	DEPTH	NO.	OFFSET		DIR.	CDP SWITCH	LINE GROUPS	SP	TR 1-48
1	751090	3712			40	59	1			41	T-1 - 6+4	1		
2		3713			40	59	2			45	T-5 - 7+4			
3		3714			40	59	3			49	T-9 - 8+4			
4		3715			40	59	4			53	T-13 - 9+4			
5		3716			40	59	5			57	T-17 - 10+4			
6		3717			40	59	6			61	T-21 - 11+4			
7		3718			40	59	7			37	1+1 - 12+4	2	Recorder @ SP-10	
8		3719			40	59	8			41	2+1 - 13+4			
9		3800			40	59	9			45	3+1 - 14+4			
10		3811			40	59	10			49	4+1 - 15+4			
11		3812			40	59	11			53	5+1 - 16+4			
12		3813			40	59	12			57	6+1 - 17+4			
13		3814			40	59	13			61	7+1 - 18+4			
14		3815			40	59	14			65	8+1 - 19+4			
15		3816			40	59	15			53	9+1 - 20+4	3	Recorder @ SP-13	
16		3817			40	59	16			29	10+1 - 21+4	4	Recorder @ SP-21	
17		3818			40	59	17			33	11+1 - 22+4			
18		3819			40	59	18			37	12+1 - 23+4			
19		3820			40	59	19			41	13+1 - 24+4			
20		3821			40	59	20			45	14+1 - 25+4			

Comp.

1109

# LAND SEISMIC RECORDING LOG



	CLIENT: <b>Husky</b>	PROSPECT: <b>NPR-A</b>	AREA: <b>Barrow</b>	LINE NO: <b>608</b>						
	PARTY NO: <b>1182</b>	INST. ENG: <b>Windham</b>		DATE: <b>MO 2 DAY 22 YR 79</b>						
INSTRUMENT (9-TRACK)	<input checked="" type="checkbox"/> 1 SYSTEM <input type="checkbox"/> 2 SYSTEMS	<input type="checkbox"/> 1-24 & 25-48 <input type="checkbox"/> 1-48 & 49-96	ODDS EVENTS	TYPE: <input type="checkbox"/> DFS III <input type="checkbox"/> DFS II <input type="checkbox"/> OTHER	<input checked="" type="checkbox"/> 9 TRACK <input type="checkbox"/> 21 TRACK	FORMAT: <b>B</b>	<input type="checkbox"/> GAPPED <input type="checkbox"/> UNGAPPED	PACKING DENSITY:	(10) <input type="checkbox"/> 350 BPI <input type="checkbox"/> 800 BPI	(11) <input type="checkbox"/> 712 BPI <input type="checkbox"/> 1000 BPI
	NO. BYTES IN HEADER REC:	NO. BYTES IN RECORD ID:	NO. BYTES PER SCAN: <b>134</b>	RECORD NUMBERS: <b>BDEC</b> <input type="checkbox"/> OCT	GAIN CONSTANT: <b>36</b> db	INPUT IMPEDANCE: <b>20,000</b> ohms.				
CONFIGURATION (MAG TAPE)	FIELD TRACE NOS.: <b>1-48</b>			AUXILIARY DATA: <b>FB 4H</b>						
	DATA CHANNEL NOS.: <b>1-48</b>			AUXILIARY CHANNEL NOS.: <b>3 4</b>						
PARAMETER	RECORD LENGTH: <b>6</b> sec.	SAMPLE RATE: <input type="checkbox"/> 1ms <input type="checkbox"/> 4ms	GAIN MODE: <input type="checkbox"/> INITIAL <input type="checkbox"/> FINAL <input type="checkbox"/> MANUAL <input type="checkbox"/> OPERATE	FILTERS:	FREQ: <b>8</b>	LO CUT HZ SLOPE: <b>18</b>	FREQ: <b>128</b>	HI CUT HZ SLOPE: <b>70</b>	NOTCH FILTER: <input type="checkbox"/> IN <input type="checkbox"/> OUT	
DISPLAY	MODE: <input checked="" type="checkbox"/> RGC <input type="checkbox"/> FLOAT <input type="checkbox"/> AMPLIFIER <input type="checkbox"/> DIRECT	INITIAL GAIN: <b>18</b> db	TRIP SENS: <b>18</b> 45	POLARITY CONVENTION:	PRESSURE INCREASE ON GEOPHONE: <input type="checkbox"/> NEGATIVE <input type="checkbox"/> POSITIVE	NUMBERS ON ON MAG. TAPE		<input type="checkbox"/> DOWNBREAK <input type="checkbox"/> UPBREAK	ON DISPLAY	
CFS I	TYPE STACK:	GATE LENGTH:	RECORD REJECTION:	NOISE REDUCTION:	NOISE THRESHOLD:	CORR. SCALING:		P.C.U. NORM./ALT SW.		
SOURCE	TYPE: <input checked="" type="checkbox"/> DYNAMITE <input type="checkbox"/> VIBROSEIS <input type="checkbox"/> OTHER	PATTERN: <b>Single hole - inline</b>	NO. OF POSITIONS: <b>1</b>	INLINE SPACING:	LATERAL SPACING:	STAGGER:	LENGTH:	WIDTH:	LATERAL OFFSET:	
	CHG/ HOLE: <b>20</b>	HOLE DEPTH: <b>75</b>	SWEEP POSITION:	SWEEP START:	SWEEP END:	SWEEP LENGTH:	SWEEP TAPER:	PHASE COMP.		
RECEIVER	TYPE: <b>Gsc-20d</b>	PATTERN: <b>inline</b>	NO. OF ELEMENTS: <b>18</b>	INLINE SPACING: <b>18'</b>	LATERAL SPACING:	STAGGER:	LENGTH:	WIDTH:	LATERAL OFFSET:	
	CONNECTION: <b>Series-Parallel</b>	RESISTANCE: <b>560</b> ohms								
SPREAD	NO. OF GROUPS: <b>48</b>	GROUP INTERVAL: <b>330'</b>	SHOTPOINT INTERVAL: <b>1320'</b>	FOLD: <b>6</b>	DIRECTION OF PROGRESSION: <b>S → N</b>	OFFSET GROUP 1: <b>7755'</b>	OFFSET GROUP 24: <b>165'</b>	OFFSET GROUP 25: <b>165'</b>	OFFSET GROUP 48/49: <b>7755'</b>	LEADING GROUP: <b>48</b>

DIAGRAMS/MISC. INFORMATION:

SHOTPOINT	TR 1 to 48		TR 19 to 48		SHOT			SPREAD			REMARKS	CORR. STACK		
	REEL NO.	REC.	REEL NO.	REC.	SIZE	DEPTH	NO.	OFFSET	DIR	COP SWITCH		LINE GROUPS	REV UP	TR 1-48
21	7511865	392			40	59	21			49	15H - 26T4	4		
22		393			40	59	22			53	16T1 - 27T4			
23		394			40	59	23			57	17T1 - 28T4			
24		395			40	59	24			29	18T1 - 29T4	5	Recorder @ SP-29	
25		396			40	59	25			33	19T1 - 30T4			
26		397			40	59	26			37	20T1 - 31T4			
27		398			40	59	27			41	21T1 - 32T4			
28		399			40	59	28			45	22T1 - 33T4			
29		400			40	59	29			49	23T1 - 34T4			
30		401			40	59	30			53	24T1 - 35T4			
31		402			40	59	31			57	25T1 - 36T4			
32		403			40	59	32			29	26T1 - 37T4	6	Recorder @ SP-37	
33		404			40	59	33			33	27T1 - 38T4			
34		405			40	59	34			37	28T1 - 39T4			
35		406			40	59	35			41	29T1 - 40T4			
36		407			40	59	36			45	30T1 - 41T4			
37		408			40	59	37			49	31T1 - 42T4			
38		409			40	59	38			53	32T1 - 43T4			
39		410			40	59	39			57	33T1 - 44T4			
40		411			40	59	40			33	34T1 - 45T4	7	Recorder @ SP-44	



# LAND SEISMIC RECORDING LOG

	CLIENT: <b>Husky</b>	PROSPECT: <b>NPR-A</b>	AREA: <b>Barrow</b>	LINE NO.: <b>608</b>			
PARTY NO.: <b>1182</b>		INST. ENG.: <b>Windham</b>		DATE: <b>23</b> MO: <b>2</b> DAY: <b>28</b> YR: <b>79</b>			
INSTRUMENT (9-TRACK)	<input checked="" type="checkbox"/> 1 SYSTEM <input checked="" type="checkbox"/> 2 SYSTEMS	<input type="checkbox"/> T-24 & 25-48 <input type="checkbox"/> 1-48 & 49-96	<input checked="" type="checkbox"/> DFS III <input type="checkbox"/> DFS II <input type="checkbox"/> OTHER	<input checked="" type="checkbox"/> 9 TRACK <input type="checkbox"/> 21 TRACK	FORMAT: <b>B</b>	<input type="checkbox"/> GAPPED <input type="checkbox"/> UNGAPPED	PACKING DENSITY: (10) <input type="checkbox"/> 350 BPI (11) <input type="checkbox"/> 712 BPI (12) <input type="checkbox"/> 1600 BPI
	NO. BYTES IN HEADER REC.	NO. BYTES IN RECORD ID:	NO. BYTES PER SCAN: <b>134</b>	RECORD NUMBERS: <input checked="" type="checkbox"/> DEC <input type="checkbox"/> OCT	GAIN CONSTANT: <b>36</b> db	INPUT IMPEDANCE: <b>20,000</b> ohms	(1) (2) (3) (4) (5) (6) (7)
CONFIGURATION (MAG TAPE)	FIELD TRACE NOS.: <b>1-48</b> DATA CHANNEL NOS.: <b>1-48</b> (ON MAG TAPE)			AUXILIARY DATA: <b>TB 4#</b> AUXILIARY CHANNEL NOS.: <b>3 4</b>			
PARAMETER	RECORD LENGTH: <b>6</b> sec	SAMPLE RATE: <input type="checkbox"/> 1 sec <input type="checkbox"/> 4 ms	GAIN MODE: <input checked="" type="checkbox"/> INITIAL <input type="checkbox"/> FINAL	FILTERS: FREQ: <b>8</b> LD CUT HZ SLOPE: <b>18</b>		HIGH CUT HZ SLOPE: <b>70</b>	NOTCH FILTER: <input type="checkbox"/> IN <input type="checkbox"/> OUT
DISPLAY	MODE: <input checked="" type="checkbox"/> REC <input type="checkbox"/> FLOAT <input type="checkbox"/> AMPLIFIER	INITIAL GAIN: <b>18</b> db	TRIP SENS: <b>18</b> db	POLARITY CONVENTION: <input type="checkbox"/> NEGATIVE <input type="checkbox"/> POSITIVE		NUMBERS ON MAG. TAPE: <input type="checkbox"/> DOWNBREAK <input type="checkbox"/> UPBREAK ON DISPLAY	
CFS I	TYPE STACK:	GATE LENGTH:	RECORD REJECTION:	NOISE REDUCTION:		NOISE THRESHOLD:	COAR. SCALING:
SOURCE	TYPE: <input checked="" type="checkbox"/> DYNAMITE <input type="checkbox"/> VIBROSEIS <input type="checkbox"/> OTHER	PATTERN: <b>Single hole - Tailline</b>	NO. OF POSITIONS:	INLINE SPACING:	LATERAL SPACING:	STAGGER:	LENGTH:
RECEIVER	CONNECTION: <b>G.S.C. - 2nd Series - Parallel</b>	PATTERN: <b>IN line</b>	RESISTANCE: <b>560</b> ohms	NO. OF ELEMENTS: <b>18</b>	INLINE SPACING: <b>18'</b>	LATERAL SPACING:	WIDTH:
SPREAD	NO. OF GROUPS: <b>48</b>	GROUP INTERVAL: <b>330'</b>	SHOTPOINT INTERVAL: <b>1320'</b>	FOLD: <b>6</b>	OFFSET GROUP 1: <b>7755'</b>	OFFSET GROUP 24: <b>165'</b>	DIRECTION OF PROGRESSION: <b>S → N</b>

DIAGRAMS/MISC. INFORMATION: **41** **42** **46** **SP-47** **48** **52** **53**  
**TR-47** **TR-48** **TR-49** **TR-25** **TR-48**  
 File # 418 → 426 Daily Tests  
 File # 427 - 428 Test TB's

SHOTPOINT	TR. 1 to 48		TR. 49 to 96		SHOT		SPREAD		REMARKS	CORR. STACK			
	REEL NO.	REC.	REEL NO.	REC.	SIZE	DEPTH	NO.	OFFSET		DIR.	CDP SWITCH	LINE GROUPS	TR. 1-48
47	7511	429			40	59	11			29	41+1 - 52+4		
48		430			40	59	2	300	Right	33	42+1 - 53+4		
49		431			40	59	3	300	Right	37	43+1 - 54+4		
50		432			40	59	4			41	44+1 - 55+4		
51		433			40	59	5	660	North	45	45+1 - 56+4		
52		434			50	55	6			49	46+1 - 57+4		
53		435			40	74	7			53	47+1 - 58+4		
54		436			50	70	8			57	48+1 - 59+4		
55		438			40	89	9			29	49+1 - 60+4	2	Recorder @ SP-60 File # 437 missing
56		439			50	85	10			33	60+1 - 61+4		
57		440			40	59	11			37	51+1 - 62+4		
58		441			50	56	12			37	52+1 - 63+4	3	Recorder @ SP-61 54+4 Dead
59		442			40	74	13			41	53+1 - 64+4		
60		443			50	70	14			45	54+1 - 65+4		
61		444			40	89	15			49	55+1 - 66+4		
62		445			50	85	16			53	56+1 - 67+4		
63		446			40	59	17			57	57+1 - 68+4		
64		447			40	59	18			61	58+1 - 69+4		
65		448			40	59	19			65	59+1 - 70+4		
66		449			40	59	20			69	60+1 - 71+4		

Change 590 - Hole Top 44 Camps

Recorder @ SP-52

offset 300' East

Inline offset

Recorder @ SP-60 File # 437 missing

Recorder @ SP-61 54+4 Dead

Cables open @ SP-59

# LAND SEISMIC RECORDING LOG

	CLIENT: <b>Husky</b>	PROSPECT: <b>NPR-A</b>	AREA: <b>Barrow</b>	LINE NO: <b>608</b>						
	PARTY NO: <b>1182</b>	INST. ENG.: <b>Windham</b>		DATE: <b>MO 2 DAY 23 YR 79</b>						
INSTRUMENT (9-TRACK)	<input checked="" type="checkbox"/> SYSTEM <input type="checkbox"/> 2 SYSTEMS	<input type="checkbox"/> 1-24 & 25-48 <input type="checkbox"/> 1-48 & 49-96	ODDS EVEN	TYPE: <input type="checkbox"/> DPS III <input type="checkbox"/> DPS II <input type="checkbox"/> OTHER	<input checked="" type="checkbox"/> 9 TRACK <input type="checkbox"/> 21 TRACK	FORMAT: <b>B</b>	<input checked="" type="checkbox"/> GAPPED <input type="checkbox"/> UNGAPPED	PACKING DENSITY: (10) <input type="checkbox"/> 356 BPI (11) <input type="checkbox"/> 712 BPI	(12) <input type="checkbox"/> 800 BPI	
NO. BYTES IN HEADER REC.	NO. BYTES IN RECORD ID:	NO. BYTES PER SCAN: <b>134</b>	RECORD NUMBERS: <input checked="" type="checkbox"/> DEC. <input type="checkbox"/> OCT	GAIN CONSTANT: <b>36</b> db	INPUT IMPEDANCE: <b>201,000</b> ohms.					
CONFIGURATION (MAG TAPE)	FIELD TRACE NOS.: <b>1-48</b>	DATA CHANNEL NOS.: <b>1-48</b>	(ON MAG TAPE)			AUXILIARY DATA: <b>1B 4H</b>	AUXILIARY CHANNEL NOS.: <b>3 4</b>			
PARAMETER	RECORD LENGTH: <b>6</b> sec.	SAMPLE RATE: <input type="checkbox"/> 1 ms. <input type="checkbox"/> 4 ms. <input type="checkbox"/> 16 ms.	GAIN MODE: <input type="checkbox"/> INITIAL <input type="checkbox"/> MANUAL <input type="checkbox"/> OPERATE	FILTERS: FREQ <b>8</b>	LO CUT HZ SLOPE <b>18</b>	FREQ <b>120</b>	HI CUT HZ SLOPE <b>70</b>	NOTCH FILTER: <input type="checkbox"/> IN <input type="checkbox"/> OUT		
DISPLAY	<input checked="" type="checkbox"/> AGC <input type="checkbox"/> FLOAT <input type="checkbox"/> AMPLIFIER <input type="checkbox"/> DIRECT	INITIAL GAIN: <b>18</b> db	TRIP SENS: <b>18</b> db	POLARITY CONVENTION: <input type="checkbox"/> NEGATIVE <input type="checkbox"/> POSITIVE	PRESSURE INCREASE ON GEOPHONE: <input type="checkbox"/> NUMBERS ON MAG. TAPE	<input type="checkbox"/> DOWNBREAK <input type="checkbox"/> UPBREAK	ON DISPLAY			
CFS I	TYPE STACK:	GATE LENGTH:	RECORD REJECTION:	NOISE REDUCTION:	NOISE THRESHOLD:	CORR. SCALING:	E.C.U. NORM./ALT SW			
SOURCE	TYPE: <input checked="" type="checkbox"/> DYNAMITE <input type="checkbox"/> VIBROSEIS <input type="checkbox"/> OTHER	PATTERN: <b>Single hole - Inline</b>	NO. OF POSITIONS:	INLINE SPACING:	LATERAL SPACING:	STAGGER:	LENGTH:	WIDTH:	LATERAL OFFSET:	
RECEIVER	TYPE: <b>Gsc-20d</b>	PATTERN: <b>Inline</b>	NO. OF ELEMENTS: <b>18</b>	INLINE SPACING: <b>18'</b>	LATERAL SPACING:	STAGGER:	LENGTH:	WIDTH:	LATERAL OFFSET:	
SPREAD	CONNECTION: <b>Series - Parallel</b>	RESISTANCE: <b>560</b> ohms	STAGGER:	LENGTH:	WIDTH:	LATERAL OFFSET:				
NO. OF GROUPS: <b>48</b>	GROUP INTERVAL: <b>330'</b>	SHOTPOINT INTERVAL: <b>1320'</b>	FOLD: <b>6</b>	DIRECTION OF PROGRESSION: <b>S → N</b>						
OFFSET GROUP 1: <b>7755'</b>	OFFSET GROUP 24: <b>165'</b>	OFFSET GROUP 25: <b>165'</b>	OFFSET GROUP 48: <b>7755'</b>	LEADING GROUP: <b>49</b>						

DIAGRAMS/MISC. INFORMATION:

SHOTPOINT	TR 1 to 16		TR 17 to 32		TR 33 to 48		SHOT		SPREAD		REMARKS	CORR. STACK	
	REEL NO.	REC.	REEL NO.	REC.	SIZE	DEPTH	NO.	OFFSET	DIR.	CDP SWITCH		LINE GROUPS	TR 1-16
67	7511085	450			40	59	21		73	61H	-72H	3	
68		451			40	59	22		77	62H	-73H		
69		452			40	59	23		81	63H	-74H		
70		453			40	59	24		29	64H	-75H	4	Recorder @ SP-75
71		454			40	59	25		33	65H	-76H		
72		455			40	59	26		37	66H	-77H		
73		456			40	59	27		41	67H	-78H		
74		457			40	59	28		29	68H	-79H	5	Recorder @ SP-79
75		458			40	59	29		33	69H	-80H		
76		459			40	59	30		37	70H	-81H		
77		460			40	59	31		41	71H	-82H		
78		461			40	59	32		45	72H	-83H		
79		462			40	59	33		49	73H	-84H		
80		463			40	59	34		53	74H	-85H		
81		464			40	59	35		57	75H	-86H		
82		465			40	59	36/45	South	29	76H	-87H	6	Recorder @ SP-87 Tailline Offset
83		466			40	59	37/49	South	37	78H	-89H		Recover SP-83
84		467			40	59	38/49	South	45	80H	-91H		Recover SP-84
85		468			40	59	39/49	South	53	82H	-93H		Recover SP-85
86		469			40	59	40/49	South	61	84H	-95H		Recover SP-86

TEMS  1-24 & 25-40  1-48 & 49-96  EVENS  DFS IX  JUNK  RECORD NUMBERS:  DEC  OCT  GAIN CONSTANT: 36 db IMPEDANCE: 20,000  
 NO. BYTES IN RECORD ID: NO. BYTES PER SCAN: 134  
 FACE NOS.: 1-48  
 CHANNEL NOS.: 1-48 (ON MAG TAPE)  
 AUXILIARY DATA: (1) TB (2) 4H  
 AUXILIARY CHANNEL NOS.: 3 4  
 SAMPLE RATE:  1 ms  2 ms  4 ms  8 ms  
 GAIN MODE:  TFP  INITIAL  FINAL  MANUAL  OPERATE  
 FILTERS: FREQ: 8 LO CUT HZ SLOPE: 18 HI CUT HZ SLOPE: 70 NOTCH FILTER:   
 INITIAL GAIN: 18 db TRIP SENS: 18 db POLARITY CONVENTION:  NEGATIVE  POSITIVE } NUMBERS ON MAG TAPE  DOWNBREAK  UPBREAK }  
 FLOAT  AMPLIFIER  DIRECT  DEFLOAT  DIRECT PRESSURE INCREASE ON GEOPHONE:  CORR. SCALING: R.C.U. NORM./?  
 GATE LENGTH: RECORD REJECTION: NOISE REDUCTION: NOISE THRESHOLD:

AMITE ROSEIS IER  
 PATTERN: Single hole - inline NO. OF POSITIONS: SWEEP POSITION: INLINE SPACING: SWEEP START: LATERAL SPACING: SWEEP END: STAGGER: LENGTH: WIDTH: LATERAL OFFSET:  
 CHG/HOLE: 40 HOLE DEPTH: 75

Csc-20d  
 SECTION: Series - Parallel PATTERN: inline NO. OF ELEMENTS: 18 INLINE SPACING: 18' LATERAL SPACING: WIDTH: LAT OFF:  
 RESISTANCE: 560 ohms STAGGER: FOLD: 6 DIRECTION OF PROGRESSION: 5-  
 GROUP INTERVAL: 330' SHOTPOINT INTERVAL: 1320' OFFSET GROUP: 25' 165' OFFSET GROUP: 77.55' LEADING GROUP: 48  
 48 77.55'


FORMATION:

to	48	1R	SHOT							SPREAD			REMARKS:	CORR	
			REC.	REEL NO.	SIZE	DEPTH	NO.	OFFSET	DIR	CDP SWITCH	LINE GROUPS	SET UP		HT	REC
895	470	17	82	40	5941	495	S	69	86+1 - 97+4	6	Recover SP-87	inline offset			
	471		93	40	5942	660	N	33	77+1 - 88+4		Recover SP-88	" "			
	472		93	40	5943	660	N	41	79+1 - 90+4		Recover SP-89	" "			
	473		93	40	5944	660	N	49	81+1 - 92+4		Recover SP-90	" "			
	474		93	40	5945	660	N	57	83+1 - 94+4		Recover SP-91	" "			
	475		93	40	5946	660	N	65	85+1 - 96+4		Recover SP-92	" "			
	476		93	40	5947	660	N	73	87+1 - 98+4						

# LAND SEISMIC RECORDING LOG


14.5 Hours

	CLIENT: <b>Husky</b>	PROSPECT: <b>NPR-A</b>	AREA: <b>Barrow</b>	LINE NO: <b>608</b>								
	PARTY NO: <b>1187</b>	INST. ENG: <b>Windham</b>		DATE: <b>2 DAY 24 79</b>								
INSTRUMENT (9-TRACK)	<input type="checkbox"/> 1 SYSTEM <input type="checkbox"/> 2 SYSTEMS	<input type="checkbox"/> 1-24 & 25-48 <input type="checkbox"/> 1-48 & 49-96	TYPE: <input type="checkbox"/> DFS III <input type="checkbox"/> DFS II <input type="checkbox"/> OTHER	<input checked="" type="checkbox"/> TRACK <input type="checkbox"/> 21 TRACK	FOPMAT: <b>B</b>	<input type="checkbox"/> GAPPED <input type="checkbox"/> UNGAPPED	PACKING DENSITY:	(10) <input type="checkbox"/> 356 BPI <input type="checkbox"/> 800 BPI	(11) <input type="checkbox"/> 712 BPI <input type="checkbox"/> 1000 BPI			
	NO. BYTES IN HEADER REC:	NO. BYTES IN RECORD ID:	NO. BYTES PER SCAN: <b>134</b>	RECORD NUMBERS:	<input checked="" type="checkbox"/> DEC <input type="checkbox"/> OCT	GAIN CONSTANT: <b>36</b>	db	INPUT IMPEDANCE: <b>2000</b> ohms				
CONFIGURATION (MAG TAPE)	FIELD TRACE NOS.: <b>1-48</b>	DATA CHANNEL NOS.: <b>1-48</b>	(ON MAG TAPE)	AUXILIARY DATA:	<b>7B</b> <b>4H</b>	(1) <b>3</b>	(2) <b>4</b>	(3)	(4)	(5)	(6)	(7)
PARAMETER	RECORD LENGTH: <b>6</b> sec	SAMPLE RATE: <input type="checkbox"/> 1 ms <input checked="" type="checkbox"/> 2 ms <input type="checkbox"/> 4 ms	GAIN MODE: <input type="checkbox"/> INITIAL <input checked="" type="checkbox"/> TRIP SENS: <b>18</b> db	<input type="checkbox"/> MANUAL <input checked="" type="checkbox"/> OPERATE	FILTERS: FREQ. <b>B</b>	LO CUT HZ: <b>18</b>	HI CUT HZ: <b>70</b>	NOTCH FILTER: <input type="checkbox"/> IN <input checked="" type="checkbox"/> OUT				
DISPLAY	MODE: <input type="checkbox"/> AGC <input type="checkbox"/> FLOAT <input type="checkbox"/> DEFLOAT	<input type="checkbox"/> AMPLIFIER <input type="checkbox"/> DIRECT	INITIAL GAIN: <b>18</b> db	RECORD REJECTION:	POLARITY CONVENTION: <input type="checkbox"/> NEGATIVE <input checked="" type="checkbox"/> POSITIVE	PRESSURE INCREASE ON GEOPHONE:	NUMBERS ON MAG TAPE: <input type="checkbox"/> ON <input checked="" type="checkbox"/> OFF	DOWNBREAK UPBREAK: <input type="checkbox"/> ON <input checked="" type="checkbox"/> OFF	ON DISPLAY			
CFS I	TYPE STACK:	DATE LENGTH:			NOISE REDUCTION:	NOISE THRESHOLD:	CORR. SCALING:	R.C.U. NORM./ALT SW:				
SOURCE	TYPE: <input checked="" type="checkbox"/> DYNAMITE <input type="checkbox"/> VIBROSEIS <input type="checkbox"/> OTHER	PATTERN: <b>Single hole - Inline</b>	NO. OF POSITIONS:	INLINE SPACING:	LATERAL SPACING:	STAGGER:	LENGTH:	WIDTH:	LATERAL OFFSET:			
RECEIVER	TYPE: <b>GSC-20d</b>	PATTERN: <b>IN line</b>	NO. OF ELEMENTS: <b>18</b>	INLINE SPACING: <b>18'</b>	LATERAL SPACING:	STAGGER:	LENGTH:	WIDTH:	LATERAL OFFSET:			
SPREAD	CONNECTION: <b>Series - Parallel</b>	RESISTANCE: <b>560</b> ohms										
	NO. OF GROUPS: <b>48</b>	GROUP INTERVAL: <b>330'</b>	SHOTPOINT INTERVAL: <b>1320'</b>	FOLD: <b>6</b>	DIRECTION OF PROGRESSION: <b>S → N</b>							
	OFFSET GROUP 1: <b>7755'</b>	OFFSET GROUP 24: <b>165'</b>	OFFSET GROUP 25: <b>165'</b>	OFFSET GROUP 48: <b>7755'</b>	LEADING GROUP: <b>48</b>							



SHOTPOINT	TR 1 to 48		TR 24 to 25		SHOT		SPREAD		REMARKS	CORR. STACK				
	REEL NO.	REC.	REEL NO.	REC.	SIZE	DEPTH	NO.	OFFSET		DIR.	CDP SWITCH	LINE GROUPS	TR 1-10	TR 11-20
94	751086	489			40	59	1	35		45	8811 - 994			
95		490			40	59	2			49	8911 - 1004			
96		491			40	59	3			53	9011 - 1014			
97		492			40	59	4			57	9111 - 1024			
98		493			40	59	5			61	9211 - 1034			
99		494			40	59	6			65	9311 - 1044			
100		495			40	59	7			69	9411 - 1054			
101		496			40	59	8			73	9511 - 1064			
102		497			40	59	9			79	9611 - 1074	2		Recorder @ SP-107
103		498			40	59	10			33	9711 - 1084			
104		499			40	59	11			37	9811 - 1094			
105		500			40	59	12			41	9911 - 1104			
106		501			40	59	13			45	10011 - 1114			
107		502			40	59	14			49	10111 - 1124			
108		503			40	59	15			53	10211 - 1134			
109		504			40	59	16			29	10311 - 1144	3		Recorder @ SP-114
110		505			40	59	17			33	10411 - 1154			
111		506			40	59	18			37	10511 - 1164			
112		507			40	59	19			41	10611 - 1174			
113		508			40	59	20			45	10711 - 1184			

# LAND SEISMIC RECORDING LOG

	CLIENT: <b>Husky</b>	PROSPECT: <b>NPR-A</b>	AREA: <b>BARROW</b>	LINE NO.: <b>608</b>						
	PARTY NO.: <b>1182</b>	INST. ENG.: <b>Windham</b>		DATE: <b>NO 2 DAY 24 YR 79</b>						
INSTRUMENT (9-TRACK)	<input type="checkbox"/> SYSTEM <input type="checkbox"/> 2 SYSTEMS	<input type="checkbox"/> 1-24 & 25-48 <input type="checkbox"/> 1-48 & 49-96	EVENTS	TYPE: <input type="checkbox"/> DPS III <input type="checkbox"/> DPS X <input type="checkbox"/> OTHER	<input type="checkbox"/> TRACK <input type="checkbox"/> 21 TRACK	FORMAT: <b>B</b>	<input type="checkbox"/> GAPPED <input type="checkbox"/> UNGAPPED	PACKING DENSITY:	(1) <input type="checkbox"/> 356 BPI <input type="checkbox"/> 600 BPI	(M) <input type="checkbox"/> 712 BPI <input type="checkbox"/> 1000 BPI
	NO. BYTES IN HEADER REC.	NO. BYTES IN RECORD ID.		NO. BYTES PER SCAN: <b>134</b>	RECORD NUMBERS: <input type="checkbox"/> SEC. <input type="checkbox"/> OCT.	GAIN CONSTANT: <b>36</b> db	INPUT IMPEDANCE: <b>20,000</b> ohms.	(3) (4) (5) (6) (7)		
CONFIGURATION (MAG TAPE)	FIELD TRACE NOS.: <b>1-48</b>	DATA CHANNEL NOS.: <b>1-48</b> (ON MAG TAPE)			AUXILIARY DATA: <b>1B 4H</b>					
PARAMETER	RECORD LENGTH: <b>6</b> sec.	SAMPLE RATE: <input type="checkbox"/> 1 ms. <input type="checkbox"/> 4 ms.	GAIN MODE: <input type="checkbox"/> INITIAL <input type="checkbox"/> MANUAL <input checked="" type="checkbox"/> TRIP <input type="checkbox"/> FINAL	FILTERS: FREQ. <b>8</b>	LO CUT HZ SLOPE <b>18</b>	HI CUT HZ SLOPE <b>70</b>	NOTCH FILTER: <input type="checkbox"/> IN <input type="checkbox"/> OUT			
DISPLAY	MODS: <input type="checkbox"/> AGC <input type="checkbox"/> FLOAT <input type="checkbox"/> AMPLIFIER <input type="checkbox"/> DIFLOAT <input type="checkbox"/> DIRECT	INITIAL GAIN: <b>18</b> db	TRIP SENS: <b>18</b> db	POLARITY CONVENTION: <input type="checkbox"/> NEGATIVE <input type="checkbox"/> POSITIVE	PRESSURE INCREASE ON GEOPHONE: <input type="checkbox"/> NEGATIVE <input type="checkbox"/> POSITIVE	NUMBERS ON MAG TAPE	<input type="checkbox"/> DOWNBREAK <input type="checkbox"/> UPBREAK	ON DISPLAY		
CFS I	TYPE STACK:	GATE LENGTH:	RECORD REJECTION:	NOISE REDUCTION:	NOISE THRESHOLD:	CORR. SCALING:	R.C.U. NORM/ALT SW.			
SOURCE	TYPE: <input checked="" type="checkbox"/> DYNAMITE <input type="checkbox"/> VIBROSEIS <input type="checkbox"/> OTHER	PATTERN: <b>Single hole - Endline</b>	NO. OF POSITIONS:	INLINE SPACING:	LATERAL SPACING:	STAGGER:	LENGTH:	WIDTH:	LATERAL OFFSET:	
RECEIVER	TYPE: <b>GSC-20d</b>	PATTERN: <b>IN line</b>	NO. OF ELEMENTS: <b>18</b>	INLINE SPACING: <b>18'</b>	LATERAL SPACING:	STAGGER:	LENGTH:	WIDTH:	LATERAL OFFSET:	
SPREAD	CONNECTION: <b>Series - Parallel</b>	RESISTANCE: <b>560</b> ohms	GROUP INTERVAL: <b>330'</b>	SHOTPOINT INTERVAL: <b>1320'</b>	FOLD: <b>6</b>	OFFSET GROUP 1: <b>77.55'</b>	OFFSET GROUP 48: <b>77.55'</b>	DIRECTION OF PROGRESSION: <b>S → N</b>	LEADING GROUP: <b>48</b>	

DIAGRAMS/MISC. INFORMATION:

SHOTPOINT	TR. 1 to 48		TR. 10		SHOT							SPREAD			REMARKS	CORR. STACK			
	REEL NO.	REC.	PEEL NO.	REC.	SIZE	DEPTH	NO.	OFFSET	DIR.	COP SWITCH	LINE GROUPS		SET	19-79		20-79	21-79	22-79	
114	751096	509			40	5921				49	108+1 - 119+4		3						
115		510			40	5922				53	109+1 - 120+4								
116		511			40	5923				57	110+1 - 121+4								
117		512			40	5924				29	111+1 - 122+4		4	Recorder @ SP-122					
118		513			40	5925				33	112+1 - 123+4								
119		514			40	5926				37	113+1 - T-4								
120		515			40	5927				41	114+1 - T-8								
121		516			40	5928				45	115+1 - T-12								
122		517			40	5929				49	116+1 - T-16								
123		518			40	5930				53	117+1 - T-20								
124		519			40	5931				57	118+1 - T-24								