

ANN'S Copy

189 S/P'S

LAND SEISMIC RECORDING LOG

15 Hours

CLIENT: Husky		PROSPECT: NPR-A		AREA: Barrow		LINE NO.: 610	
PARTY NO.: 1182		INST. ENG.: STREFF-Windham		DATE: MO 2 DAY 15 YR 79			
INSTRUMENT (9-TRACK)		NO. BYTES IN HEADER REC.		NO. BYTES IN RECORD ID.		NO. BYTES PER SCAN: 134	
CONFIGURATION (MAG TAPE)		FIELD TRACE NOS.: 1-48		AUXILIARY DATA: 7B 4H		AUXILIARY CHANNEL NOS.: 3 4	
PARAMETER		RECORD LENGTH: 6		GAIN: 36 db		INPUT IMPEDANCE: _____ ohms	
DISPLAY		MODE: <input checked="" type="checkbox"/> MAG <input type="checkbox"/> FLOAT <input type="checkbox"/> DEFLOAT <input type="checkbox"/> DIRECT		INITIAL GAIN: 18 db		POLARITY CONVENTION: <input checked="" type="checkbox"/> NEGATIVE <input type="checkbox"/> POSITIVE	
SOURCE		TYPE: <input checked="" type="checkbox"/> DYNAMITE <input type="checkbox"/> VIBROSEIS <input type="checkbox"/> OTHER		PATTERN: Single hole - inline		NO. OF POSITIONS: 1	
RECEIVER		TYPE: Gsc-20d		CONNECTION: Series - Parallel		RESISTANCE: 560 ohms	
SPREAD		NO. OF GROUPS: 48		GROUP INTERVAL: 330'		SHOTPOINT INTERVAL: 1320'	
DIAGRAMS/MISC. INFORMATION:		TR-1 24 gr Tail		TR-2 SP-1		TR-3 SP-2	
		TR-4 SP-3		TR-5 SP-4		TR-6 SP-5	
		TR-7 SP-6		TR-8 SP-7		TR-9 SP-8	
		TR-10 SP-9		TR-11 SP-10		TR-12 SP-11	
		TR-13 SP-12		TR-14 SP-13		TR-15 SP-14	
		TR-16 SP-15		TR-17 SP-16		TR-18 SP-17	
		TR-19 SP-18		TR-20 SP-19		TR-21 SP-20	
		TR-22 SP-21		TR-23 SP-22		TR-24 SP-23	
		TR-25 SP-24		TR-26 SP-25		TR-27 SP-26	
		TR-28 SP-27		TR-29 SP-28		TR-30 SP-29	
		TR-31 SP-30		TR-32 SP-31		TR-33 SP-32	
		TR-34 SP-33		TR-35 SP-34		TR-36 SP-35	
		TR-37 SP-36		TR-38 SP-37		TR-39 SP-38	
		TR-40 SP-39		TR-41 SP-40		TR-42 SP-41	
		TR-43 SP-42		TR-44 SP-43		TR-45 SP-44	
		TR-46 SP-45		TR-47 SP-46		TR-48 SP-47	
		TR-49 SP-48		TR-50 SP-49		TR-51 SP-50	
		TR-52 SP-51		TR-53 SP-52		TR-54 SP-53	
		TR-55 SP-54		TR-56 SP-55		TR-57 SP-56	
		TR-58 SP-57		TR-59 SP-58		TR-60 SP-59	
		TR-61 SP-60		TR-62 SP-61		TR-63 SP-62	
		TR-64 SP-63		TR-65 SP-64		TR-66 SP-65	
		TR-67 SP-66		TR-68 SP-67		TR-69 SP-68	
		TR-70 SP-69		TR-71 SP-70		TR-72 SP-71	
		TR-73 SP-72		TR-74 SP-73		TR-75 SP-74	
		TR-76 SP-75		TR-77 SP-76		TR-78 SP-77	
		TR-79 SP-78		TR-80 SP-79		TR-81 SP-80	
		TR-82 SP-81		TR-83 SP-82		TR-84 SP-83	
		TR-85 SP-84		TR-86 SP-85		TR-87 SP-86	
		TR-88 SP-87		TR-89 SP-88		TR-90 SP-89	
		TR-91 SP-90		TR-92 SP-91		TR-93 SP-92	
		TR-94 SP-93		TR-95 SP-94		TR-96 SP-95	
		TR-97 SP-96		TR-98 SP-97		TR-99 SP-98	
		TR-100 SP-99		TR-101 SP-100		TR-102 SP-101	

50

1010

LAND SEISMIC RECORDING LOG

		CLIENT: Husky	PROSPECT: NPR-A	AREA: Barrow	LINE NO: 610				
PARTY NO: 1182		INST. ENG: Streiff-Windham			DATE: NO 2 DAY 15 YR 79				
INSTRUMENT (9-TRACK)	<input type="checkbox"/> 1 SYSTEM <input checked="" type="checkbox"/> 2 SYSTEMS	1-24 & 25-48 1-48 & 49-96	TYPE: <input type="checkbox"/> DFS <input checked="" type="checkbox"/> DFS II <input type="checkbox"/> DFS III <input type="checkbox"/> OTHER	<input checked="" type="checkbox"/> TRACK <input type="checkbox"/> 21 TRACK	FORMAT: B <input type="checkbox"/> GAPPED <input type="checkbox"/> UNGAPPED	PACKING DENSITY: (10) <input type="checkbox"/> 354 BPI <input type="checkbox"/> 300 BPI	(11) <input type="checkbox"/> 712 BPI <input type="checkbox"/> 1400 BPI		
	NO. BYTES IN HEADER REC:	NO. BYTES IN RECORD ID:	NO. BYTES PER SCAN: 134	RECORD NUMBERS:	GAIN CONSTANT: 36 db INPUT IMPEDANCE: 20K ohms.	(1)	(2)		
CONFIGURATION (MAG TAPE)	FIELD TRACE NOS.: 1-48 DATA CHANNEL NOS.: 1-48			AUXILIARY DATA: AUXILIARY CHANNEL NOS.:					
PARAMETER	RECORD LENGTH:	SAMPLE RATE: <input type="checkbox"/> 1 ms. <input type="checkbox"/> 4 ms.	GAIN MODE: <input type="checkbox"/> INITIAL <input type="checkbox"/> MANUAL <input type="checkbox"/> OPERATE	FILTERS:	LO CUT HZ SLOPE: 128 HI CUT HZ SLOPE: 70	INCH FILTER: <input type="checkbox"/> IN <input type="checkbox"/> OUT			
DISPLAY	MODE: <input type="checkbox"/> MAGC <input type="checkbox"/> FLOAT <input type="checkbox"/> AMPLIFIER <input type="checkbox"/> DEFLAT <input type="checkbox"/> DIRECT	INITIAL GAIN: 22 db	TRIP SENS: 4 db	POLARITY CONVENTION:	PRESSURE INCREASE ON GEOPHONE: <input type="checkbox"/> NEGATIVE <input type="checkbox"/> POSITIVE	NUMBERS ON MAG. TAPE: <input type="checkbox"/> DOWNBREAK <input type="checkbox"/> UPBREAK	ON DISPLAY		
CFS I	TYPE STACK:	GATE LENGTH:	RECORD REJECTION:	NOISE REDUCTION:	NOISE THRESHOLD:	CORE SCALING:	R.C.U. NORM/ALT SW		
SOURCE	TYPE: <input type="checkbox"/> DYNAMITE <input type="checkbox"/> VIBROSEIS <input type="checkbox"/> OTHER	PATTERN: inline/hale	NO. OF POSITIONS:	INLINE SPACING:	LATERAL SPACING:	STAGGER:	LENGTH:	WIDTH:	LATERAL OFFSET:
RECEIVER	TYPE: 20-D	PATTERN: inline	NO. OF ELEMENTS: 18	INLINE SPACING: 12	LATERAL SPACING:	STAGGER:	LENGTH:	WIDTH:	LATERAL OFFSET:
SPREAD	CONNECTION: series-parallel	RESISTANCE: 500 ohms	SWEEP START:	SWEEP END:	SWEEP LENGTH:	SWEEP TAPER:	PHASE COMP.		
	NO. OF GROUPS: 48	GROUP INTERVAL: 230	SHOTPOINT INTERVAL: 1300	FOLD: 6	OFFSET GROUP 48/96: 7755	DIRECTION OF PROGRESSION: North	LEADING GROUP: 48		

DIAGRAMS/MISC. INFORMATION:

SHOTPOINT	TR. TO		TR. TO		SHOT				DIR.	COP SWITCH	SPREAD	LINE GROUPS	REMARKS	CORR STACK			
	REEL NO.	REC.	REEL NO.	REC.	SIZE	DEPTH	NO.	OFFSET						HT.	REC.	HT.	REC.
21	701891	30			20	67	21		33	15+1 - 26+1	4	Recorder @ SP 25					
22		33			20	67	22		37	16+1 - 27+1							
23		34			20	67	23		41	17+1 - 28+1							
24		35			20	67	24		45	18+1 - 29+1							
25		36			20	67	25		49	19+1 - 30+1							
26		37			20	67	26		53	20+1 - 31+1							
27		38			20	67	27		57	21+1 - 32+1							
28		39			20	67	28		61	22+1 - 33+1							
29		40			20	67	29		65	23+1 - 34+1							
30		41			20	67	30		29	24+1 - 35+1	5	Recorder @ SP-35 25+2 done					
31		42			20	67	31		33	25+1 - 36+1							
* 32 *	* 53 *				20	67	32 *	*	37	26+1 - 37+1		* SHOT OUT of sequence (file # 52) *					
33		43			20	67	33		41	27+1 - 38+1							
34		44			20	67	34		45	28+1 - 39+1							
35		47			20	67	35		49	29+1 - 40+1							
36		48			20	67	36		53	30+1 - 41+1							
37		49			20	67	37		57	31+1 - 42+1							
38		50			20	67	38		61	32+1 - 43+1							
39		51			20	67	39		65	33+1 - 44+1							
40		52			20	67	40		69	34+1 - 45+1							

49844

Recording Hrs 14

LAND SEISMIC RECORDING LOG

CLIENT: HOSNY		PROSPECT: NPR-A		AREA: Burrow		LINE NO: 610	
PARTY NO: 1182		INST. ENG: Streiff-Windham		DATE: NO 2 DAY 16 YR 79		G.S.I. Logo	
INSTRUMENT (9-TRACK): <input type="checkbox"/> 1 SYSTEM <input checked="" type="checkbox"/> 2 SYSTEMS		NO. BYTES IN HEADER REC: 134		RECORD NUMBERS: REC OCT		GAIN CONSTANT: 36 db	
CONFIGURATION (MAG TAPE): FIELD TRACE NOS.: 1-48 DATA CHANNEL NOS.: 1-48		AUXILIARY DATA: AUXILIARY CHANNEL NOS.:		FILTERS: FREQ. 128 HI CUT 7K NI CUT 7K NOTCH FILTER: DOWN		INPUT IMPEDANCE: 20K ohms	
PARAMETER: RECORD LENGTH: 6 sec.		GAIN MODE: INITIAL		POLARITY CONVENTION: POSITIVE		CORR. SCALING: E.C.U. NORM / ALT SW.	
DISPLAY: MODE: AGC		TRIP SENS.: 2 db		NOISE REDUCTION:		E.C.U. NORM / ALT SW.	
SOURCE: TYPE: DYNAMITE		PATTERN: 1 line / hole		NO. OF ELEMENTS: 18		LATERAL SPACING: 15'	
RECEIVER: TYPE: 20-D		RESISTANCE: 560 ohms		STAGGER: 15'		LATERAL SPACING: 15'	
SPREAD: NO. OF GROUPS: 48		GROUP INTERVAL: 330		SPOTPOINT INTERVAL: 1320		DIRECTION OF PROGRESSION: NORTH	

DIAGRAMS/MISC. INFORMATION:
 3541 X — X ⊗ X — 4614 X
 TRAD
 #54-62 test + 55
 #63 test time break

SHOTPOINT	TR 10		TR 10		SHOT			DIR	COP SWITCH	LINE GROUPS	REMARKS	CORR. STAT.			
	REEL NO.	REC.	REEL NO.	REC.	SIZE	DEPTH	NO. OFFSET					HT	REC	HT	REC
411	7511891	64			20	167	11	29	35+1 - 4614	1	Recorder @ SP 46				
421		65			20	167	11	33	36+1 - 4714						
431		66			20	167	11	37	37+1 - 4814						
441		67			20	167	11	41	38+1 - 4914						
451		68			20	167	11	45	39+1 - 5014						
461		69			20	167	11	49	40+1 - 5114						
471		70			20	167	11	29	41+1 - 5214	2	Recorder @ SP-52 (49+2 dead)				
481		71			20	167	11	33	42+1 - 5314						
491		72			20	167	11	37	43+1 - 5414						
501		73			20	167	11	41	44+1 - 5514						
511		74			20	167	11	45	45+1 - 5614						
521		75			20	167	11	49	46+1 - 5714						
531		76			20	167	11	33	47+1 - 5814						
541		77			20	167	11	39	48+1 - 5914	3	Recorder @ SP 59 (#77-N.G.)				
551		78			30	163	11	33	49+1 - 6014						
561		80			30	163	170	37	50+1 - 6114						
571		81			30	163	171	41	51+1 - 6214						
581		82			30	163	171	45	52+1 - 6314						
591		83			30	163	171	49	53+1 - 6414						
601		84			20	167	20	53	54+1 - 6514						

LAND SEISMIC RECORDING LOG

CLIENT: Husky		PROSPECT: NPR-A		AREA: Barrow		LINE NO.: 610	
PARTY NO.: 1183		INST. ENG.: Stieff-Windham		DATE: MO 2 DAT 16 YR 79			
INSTRUMENT (9-TRACK) <input checked="" type="checkbox"/> SYSTEM <input type="checkbox"/> 2 SYSTEMS NO. BYTES IN HEADER REC.:		<input type="checkbox"/> 1-24 & 25-48 <input type="checkbox"/> 1-48 & 49-96 EVENTS		TYPE: <input type="checkbox"/> DFS III <input type="checkbox"/> DFS III <input checked="" type="checkbox"/> OTHER		<input type="checkbox"/> 1-TRACK <input type="checkbox"/> 21 TRACK FORMAT: B SEG	
CONFIGURATION (MAG TAPE) FIELD TRACE NOS.: 1-48 DATA CHANNEL NOS.: 1-48		NO. BYTES IN RECORD ID:		NO. BYTES PER SCAN:		RECORD NUMBERS: <input type="checkbox"/> DEC. <input type="checkbox"/> OCT.	
PARAMETER RECORD LENGTH: 6 sec.		SAMPLE RATE: <input type="checkbox"/> 1 sec. <input type="checkbox"/> 4 ms.		GAIN MODE: <input checked="" type="checkbox"/> INITIAL <input type="checkbox"/> FINAL <input type="checkbox"/> MANUAL		FILTERS: <input type="checkbox"/> GAPPED <input type="checkbox"/> UNGAPPED	
DISPLAY MODE: <input type="checkbox"/> FLOAT <input type="checkbox"/> AMPLIFIER <input checked="" type="checkbox"/> AGE <input type="checkbox"/> DEFOAT <input type="checkbox"/> DIRECT		INITIAL GAIN: 24 db		TRIP SENS.: 2 db		GAIN CONSTANT: (1) (2) (3) (4) (5) (6) (7)	
CFS I TYPE STACK:		GATE LENGTH:		RECORD REJECTION:		INPUT IMPEDANCE: ohms	
SOURCE TYPE: <input checked="" type="checkbox"/> DYNAMITE <input type="checkbox"/> VIBROSEIS <input type="checkbox"/> OTHER		PATTERN: inline		NO. OF POSITIONS:		AUXILIARY DATA: (1) (2) (3) (4) (5) (6) (7)	
RECEIVER TYPE: 20-D		PATTERN: inline		NO. OF ELEMENTS: 18		AUXILIARY CHANNEL NOS.:	
SPREAD NO. OF GROUPS: 48		GROUP INTERVAL: 330 ohms		SHOTPOINT INTERVAL: 1320		NOISE REDUCTION: <input type="checkbox"/> COR. SCALING: <input type="checkbox"/> C.U. NORM/ALT SW.	
DIAGRAMS/MISC. INFORMATION:		CHG/HOLE: 2015		HOLE DEPTH: 75		POLARITY CONVENTION: <input type="checkbox"/> NEGATIVE <input type="checkbox"/> POSITIVE	
		SWEEP POSITION:		SWEEP START:		PRESSURE INCREASE ON GEOPHONE: <input type="checkbox"/> NEGATIVE <input type="checkbox"/> POSITIVE	
		RESISTANCE: 560		STAGGER:		ON MAG TAPE <input type="checkbox"/> UPBREAK <input type="checkbox"/> ON DISPLAY	
		GROUP 24: 165		SWEEP END:		CORR. SCALING: <input type="checkbox"/> C.U. NORM/ALT SW.	
		OFFSET GROUP 24: 165		SWEEP LENGTH:		SWEEP TAPER: <input type="checkbox"/> PHASE COMP.	
		OFFSET GROUP 24: 165		SWEEP END:		SWEEP TAPER: <input type="checkbox"/> PHASE COMP.	
		OFFSET GROUP 24: 165		SWEEP END:		SWEEP TAPER: <input type="checkbox"/> PHASE COMP.	

SHOTPOINT	TR 1		TR 2		SHOT		DWR	CDP SWITCH	SPREAD	REMARKS	CORR. STACK			
	REEL NO.	REC.	REEL NO.	REC.	SIZE	DEPTH					NO.	OFFSET	LINE GROUPS	TR 1
161	751	187			20	167	21	29	55+1 - 66+4	4				
162		188			20	167	22	32	56+1 - 67+4					
163		189			20	167	23	37	57+1 - 68+4					
164		190			20	167	24	41	58+1 - 69+4					
165		191			20	167	25	45	59+1 - 70+4					
166		192			20	167	26	49	60+1 - 71+4					
167		193			20	167	27	53	61+1 - 72+4					
168		194			20	167	28	29	62+1 - 73+4	5	Recorder @ SP-66 (#85, 86-88)			
169		195			20	167	29	33	63+1 - 74+4					
170		196			20	167	30	37	64+1 - 75+4					
171		197			20	167	31	41	65+1 - 76+4					
172		198			20	167	32	45	66+1 - 77+4					
173		199			20	167	33	49	67+1 - 78+4					
174		100			20	167	34	53	68+1 - 79+4					
175		101			20	167	35	57	69+1 - 80+4					
176		102			20	167	36	61	70+1 - 81+4					
177		103			20	167	37	65	71+1 - 82+4					
178		104			20	167	38	69	72+1 - 83+4					
179		105			20	167	39	73	73+1 - 84+4					
180		106			20	167	40	77	74+1 - 85+4					

LAND SEISMIC RECORDING LOG

14 Hours

CLIENT: <u>HASKY</u>		PROSPECT: <u>NPR-A</u>		AREA: <u>BARROW</u>		LINE NO: <u>610</u>	
PARTY NO: <u>1182</u>		INST. ENG: <u>STREFF-WINDHAM</u>		DATE: <u>2 DAY 17 YR 79</u>			
INSTRUMENT: <input checked="" type="checkbox"/> 1 SYSTEM <input type="checkbox"/> 2 SYSTEMS		NO. BYTES IN RECORD ID: _____		NO. BYTES PER SCAN: <u>134</u>		RECORD NUMBERS: _____	
(9-TRACK) <input type="checkbox"/> 1-24 & 25-48 <input type="checkbox"/> 1-48 & 49-96		TYPE: <input type="checkbox"/> DFS III <input type="checkbox"/> DFS IV <input type="checkbox"/> OTHER		TRACK: <input checked="" type="checkbox"/> TRACK 1 <input type="checkbox"/> 21 TRACK		GAPPED: <input type="checkbox"/> GAPPED <input type="checkbox"/> UNGAPPED	
CONFIGURATION (MAG TAPE):		FIELD TRACE NOS.: <u>1-48</u>		AUXILIARY DATA: <u>TR 18</u> <u>OH</u>		PACKING DENSITY: _____	
PARAMETER:		RECORD LENGTH: <u>6</u> sec.		SAMPLE RATE: <input type="checkbox"/> 1 ms. <input type="checkbox"/> 4 ms.		GAIN MODE: <input type="checkbox"/> INITIAL <input type="checkbox"/> MANUAL	
DISPLAY:		MODE: <input type="checkbox"/> FLOAT <input type="checkbox"/> AMPLIFIER <input type="checkbox"/> DIRECT		INITIAL GAIN: <u>18</u> db		FILTERS: FREQ <u>OUT</u> LO CUT _____ HI CUT _____	
CFS I:		TYPE STACK: _____		GATE LENGTH: _____		POLARITY CONVENTION: _____	
SOURCE:		TYPE: <input checked="" type="checkbox"/> DYNAMITE <input type="checkbox"/> VIBROSEIS <input type="checkbox"/> OTHER		PATTERN: <u>Single hole - inline</u>		STAGGER: _____	
RECEIVER:		TYPE: <u>GSC-20d</u>		PATTERN: <u>inline</u>		LENGTH: _____	
SPREAD:		CONNECTION: <u>Series-Parallel</u>		RESISTANCE: <u>560</u> ohms		STAGGER: _____	
NO. OF GROUPS: <u>48</u>		GROUP INTERVAL: <u>330'</u>		SHOTPOINT INTERVAL: <u>1320'</u>		FOLD: <u>6</u>	
OFFSET GROUP 1: <u>7755'</u>		OFFSET GROUP 24: <u>165'</u>		OFFSET GROUP 25: <u>165'</u>		OFFSET GROUP 48: <u>7755'</u>	

DIAGRAMS/MISC. INFORMATION:
 76 AAAAA ← TR-1
 77 AAAAA ← TR-24
 81 AAAAA ← TR-25
 82 AAAAA ← TR-25
 83 AAAAA ← TR-25
 84 AAAAA ← TR-25
 85 AAAAA ← TR-25
 86 AAAAA ← TR-25
 87 AAAAA ← TR-25
 88 AAAAA ← TR-25
 89 AAAAA ← TR-25
 90 AAAAA ← TR-25
 91 AAAAA ← TR-25
 92 AAAAA ← TR-25
 93 AAAAA ← TR-25
 94 AAAAA ← TR-25
 95 AAAAA ← TR-25
 96 AAAAA ← TR-25
 97 AAAAA ← TR-25
 98 AAAAA ← TR-25
 99 AAAAA ← TR-25
 100 AAAAA ← TR-25
 101 AAAAA ← TR-25
 102 AAAAA ← TR-25
 103 AAAAA ← TR-25
 104 AAAAA ← TR-25
 105 AAAAA ← TR-25
 106 AAAAA ← TR-25
 107 AAAAA ← TR-25
 108 AAAAA ← TR-25
 109 AAAAA ← TR-25
 110 AAAAA ← TR-25
 111 AAAAA ← TR-25
 112 AAAAA ← TR-25
 113 AAAAA ← TR-25
 114 AAAAA ← TR-25
 115 AAAAA ← TR-25
 116 AAAAA ← TR-25
 117 AAAAA ← TR-25
 118 AAAAA ← TR-25
 119 AAAAA ← TR-25
 120 AAAAA ← TR-25
 121 AAAAA ← TR-25
 122 AAAAA ← TR-25
 123 AAAAA ← TR-25
 124 AAAAA ← TR-25
 125 AAAAA ← TR-25
 126 AAAAA ← TR-25
 127 AAAAA ← TR-25
 128 AAAAA ← TR-25
 129 AAAAA ← TR-25
 130 AAAAA ← TR-25
 131 AAAAA ← TR-25
 132 AAAAA ← TR-25
 133 AAAAA ← TR-25
 134 AAAAA ← TR-25
 135 AAAAA ← TR-25
 136 AAAAA ← TR-25
 137 AAAAA ← TR-25
 138 AAAAA ← TR-25
 139 AAAAA ← TR-25
 140 AAAAA ← TR-25
 141 AAAAA ← TR-25
 142 AAAAA ← TR-25
 143 AAAAA ← TR-25
 144 AAAAA ← TR-25
 145 AAAAA ← TR-25
 146 AAAAA ← TR-25
 147 AAAAA ← TR-25
 148 AAAAA ← TR-25
 149 AAAAA ← TR-25
 150 AAAAA ← TR-25
 151 AAAAA ← TR-25
 152 AAAAA ← TR-25
 153 AAAAA ← TR-25
 154 AAAAA ← TR-25
 155 AAAAA ← TR-25
 156 AAAAA ← TR-25
 157 AAAAA ← TR-25
 158 AAAAA ← TR-25
 159 AAAAA ← TR-25
 160 AAAAA ← TR-25
 161 AAAAA ← TR-25
 162 AAAAA ← TR-25
 163 AAAAA ← TR-25
 164 AAAAA ← TR-25
 165 AAAAA ← TR-25
 166 AAAAA ← TR-25
 167 AAAAA ← TR-25
 168 AAAAA ← TR-25
 169 AAAAA ← TR-25
 170 AAAAA ← TR-25
 171 AAAAA ← TR-25
 172 AAAAA ← TR-25
 173 AAAAA ← TR-25
 174 AAAAA ← TR-25
 175 AAAAA ← TR-25
 176 AAAAA ← TR-25
 177 AAAAA ← TR-25
 178 AAAAA ← TR-25
 179 AAAAA ← TR-25
 180 AAAAA ← TR-25
 181 AAAAA ← TR-25
 182 AAAAA ← TR-25
 183 AAAAA ← TR-25
 184 AAAAA ← TR-25
 185 AAAAA ← TR-25
 186 AAAAA ← TR-25
 187 AAAAA ← TR-25
 188 AAAAA ← TR-25
 189 AAAAA ← TR-25
 190 AAAAA ← TR-25
 191 AAAAA ← TR-25
 192 AAAAA ← TR-25
 193 AAAAA ← TR-25
 194 AAAAA ← TR-25
 195 AAAAA ← TR-25
 196 AAAAA ← TR-25
 197 AAAAA ← TR-25
 198 AAAAA ← TR-25
 199 AAAAA ← TR-25
 200 AAAAA ← TR-25
 201 AAAAA ← TR-25
 202 AAAAA ← TR-25
 203 AAAAA ← TR-25
 204 AAAAA ← TR-25
 205 AAAAA ← TR-25
 206 AAAAA ← TR-25
 207 AAAAA ← TR-25
 208 AAAAA ← TR-25
 209 AAAAA ← TR-25
 210 AAAAA ← TR-25
 211 AAAAA ← TR-25
 212 AAAAA ← TR-25
 213 AAAAA ← TR-25
 214 AAAAA ← TR-25
 215 AAAAA ← TR-25
 216 AAAAA ← TR-25
 217 AAAAA ← TR-25
 218 AAAAA ← TR-25
 219 AAAAA ← TR-25
 220 AAAAA ← TR-25
 221 AAAAA ← TR-25
 222 AAAAA ← TR-25
 223 AAAAA ← TR-25
 224 AAAAA ← TR-25
 225 AAAAA ← TR-25
 226 AAAAA ← TR-25
 227 AAAAA ← TR-25
 228 AAAAA ← TR-25
 229 AAAAA ← TR-25
 230 AAAAA ← TR-25
 231 AAAAA ← TR-25
 232 AAAAA ← TR-25
 233 AAAAA ← TR-25
 234 AAAAA ← TR-25
 235 AAAAA ← TR-25
 236 AAAAA ← TR-25
 237 AAAAA ← TR-25
 238 AAAAA ← TR-25
 239 AAAAA ← TR-25
 240 AAAAA ← TR-25
 241 AAAAA ← TR-25
 242 AAAAA ← TR-25
 243 AAAAA ← TR-25
 244 AAAAA ← TR-25
 245 AAAAA ← TR-25
 246 AAAAA ← TR-25
 247 AAAAA ← TR-25
 248 AAAAA ← TR-25
 249 AAAAA ← TR-25
 250 AAAAA ← TR-25
 251 AAAAA ← TR-25
 252 AAAAA ← TR-25
 253 AAAAA ← TR-25
 254 AAAAA ← TR-25
 255 AAAAA ← TR-25
 256 AAAAA ← TR-25
 257 AAAAA ← TR-25
 258 AAAAA ← TR-25
 259 AAAAA ← TR-25
 260 AAAAA ← TR-25
 261 AAAAA ← TR-25
 262 AAAAA ← TR-25
 263 AAAAA ← TR-25
 264 AAAAA ← TR-25
 265 AAAAA ← TR-25
 266 AAAAA ← TR-25
 267 AAAAA ← TR-25
 268 AAAAA ← TR-25
 269 AAAAA ← TR-25
 270 AAAAA ← TR-25
 271 AAAAA ← TR-25
 272 AAAAA ← TR-25
 273 AAAAA ← TR-25
 274 AAAAA ← TR-25
 275 AAAAA ← TR-25
 276 AAAAA ← TR-25
 277 AAAAA ← TR-25
 278 AAAAA ← TR-25
 279 AAAAA ← TR-25
 280 AAAAA ← TR-25
 281 AAAAA ← TR-25
 282 AAAAA ← TR-25
 283 AAAAA ← TR-25
 284 AAAAA ← TR-25
 285 AAAAA ← TR-25
 286 AAAAA ← TR-25
 287 AAAAA ← TR-25
 288 AAAAA ← TR-25
 289 AAAAA ← TR-25
 290 AAAAA ← TR-25
 291 AAAAA ← TR-25
 292 AAAAA ← TR-25
 293 AAAAA ← TR-25
 294 AAAAA ← TR-25
 295 AAAAA ← TR-25
 296 AAAAA ← TR-25
 297 AAAAA ← TR-25
 298 AAAAA ← TR-25
 299 AAAAA ← TR-25
 300 AAAAA ← TR-25
 301 AAAAA ← TR-25
 302 AAAAA ← TR-25
 303 AAAAA ← TR-25
 304 AAAAA ← TR-25
 305 AAAAA ← TR-25
 306 AAAAA ← TR-25
 307 AAAAA ← TR-25
 308 AAAAA ← TR-25
 309 AAAAA ← TR-25
 310 AAAAA ← TR-25
 311 AAAAA ← TR-25
 312 AAAAA ← TR-25
 313 AAAAA ← TR-25
 314 AAAAA ← TR-25
 315 AAAAA ← TR-25
 316 AAAAA ← TR-25
 317 AAAAA ← TR-25
 318 AAAAA ← TR-25
 319 AAAAA ← TR-25
 320 AAAAA ← TR-25
 321 AAAAA ← TR-25
 322 AAAAA ← TR-25
 323 AAAAA ← TR-25
 324 AAAAA ← TR-25
 325 AAAAA ← TR-25
 326 AAAAA ← TR-25
 327 AAAAA ← TR-25
 328 AAAAA ← TR-25
 329 AAAAA ← TR-25
 330 AAAAA ← TR-25
 331 AAAAA ← TR-25
 332 AAAAA ← TR-25
 333 AAAAA ← TR-25
 334 AAAAA ← TR-25
 335 AAAAA ← TR-25
 336 AAAAA ← TR-25
 337 AAAAA ← TR-25
 338 AAAAA ← TR-25
 339 AAAAA ← TR-25
 340 AAAAA ← TR-25
 341 AAAAA ← TR-25
 342 AAAAA ← TR-25
 343 AAAAA ← TR-25
 344 AAAAA ← TR-25
 345 AAAAA ← TR-25
 346 AAAAA ← TR-25
 347 AAAAA ← TR-25
 348 AAAAA ← TR-25
 349 AAAAA ← TR-25
 350 AAAAA ← TR-25
 351 AAAAA ← TR-25
 352 AAAAA ← TR-25
 353 AAAAA ← TR-25
 354 AAAAA ← TR-25
 355 AAAAA ← TR-25
 356 AAAAA ← TR-25
 357 AAAAA ← TR-25
 358 AAAAA ← TR-25
 359 AAAAA ← TR-25
 360 AAAAA ← TR-25
 361 AAAAA ← TR-25
 362 AAAAA ← TR-25
 363 AAAAA ← TR-25
 364 AAAAA ← TR-25
 365 AAAAA ← TR-25
 366 AAAAA ← TR-25
 367 AAAAA ← TR-25
 368 AAAAA ← TR-25
 369 AAAAA ← TR-25
 370 AAAAA ← TR-25
 371 AAAAA ← TR-25
 372 AAAAA ← TR-25
 373 AAAAA ← TR-25
 374 AAAAA ← TR-25
 375 AAAAA ← TR-25
 376 AAAAA ← TR-25
 377 AAAAA ← TR-25
 378 AAAAA ← TR-25
 379 AAAAA ← TR-25
 380 AAAAA ← TR-25
 381 AAAAA ← TR-25
 382 AAAAA ← TR-25
 383 AAAAA ← TR-25
 384 AAAAA ← TR-25
 385 AAAAA ← TR-25
 386 AAAAA ← TR-25
 387 AAAAA ← TR-25
 388 AAAAA ← TR-25
 389 AAAAA ← TR-25
 390 AAAAA ← TR-25
 391 AAAAA ← TR-25
 392 AAAAA ← TR-25
 393 AAAAA ← TR-25
 394 AAAAA ← TR-25
 395 AAAAA ← TR-25
 396 AAAAA ← TR-25
 397 AAAAA ← TR-25
 398 AAAAA ← TR-25
 399 AAAAA ← TR-25
 400 AAAAA ← TR-25
 401 AAAAA ← TR-25
 402 AAAAA ← TR-25
 403 AAAAA ← TR-25
 404 AAAAA ← TR-25
 405 AAAAA ← TR-25
 406 AAAAA ← TR-25
 407 AAAAA ← TR-25
 408 AAAAA ← TR-25
 409 AAAAA ← TR-25
 410 AAAAA ← TR-25
 411 AAAAA ← TR-25
 412 AAAAA ← TR-25
 413 AAAAA ← TR-25
 414 AAAAA ← TR-25
 415 AAAAA ← TR-25
 416 AAAAA ← TR-25
 417 AAAAA ← TR-25
 418 AAAAA ← TR-25
 419 AAAAA ← TR-25
 420 AAAAA ← TR-25
 421 AAAAA ← TR-25
 422 AAAAA ← TR-25
 423 AAAAA ← TR-25
 424 AAAAA ← TR-25
 425 AAAAA ← TR-25
 426 AAAAA ← TR-25
 427 AAAAA ← TR-25
 428 AAAAA ← TR-25
 429 AAAAA ← TR-25
 430 AAAAA ← TR-25
 431 AAAAA ← TR-25
 432 AAAAA ← TR-25
 433 AAAAA ← TR-25
 434 AAAAA ← TR-25
 435 AAAAA ← TR-25
 436 AAAAA ← TR-25
 437 AAAAA ← TR-25
 438 AAAAA ← TR-25
 439 AAAAA ← TR-25
 440 AAAAA ← TR-25
 441 AAAAA ← TR-25
 442 AAAAA ← TR-25
 443 AAAAA ← TR-25
 444 AAAAA ← TR-25
 445 AAAAA ← TR-25
 446 AAAAA ← TR-25
 447 AAAAA ← TR-25
 448 AAAAA ← TR-25
 449 AAAAA ← TR-25
 450 AAAAA ← TR-25
 451 AAAAA ← TR-25
 452 AAAAA ← TR-25
 453 AAAAA ← TR-25
 454 AAAAA ← TR-25
 455 AAAAA ← TR-25
 456 AAAAA ← TR-25
 457 AAAAA ← TR-25
 458 AAAAA ← TR-25
 459 AAAAA ← TR-25
 460 AAAAA ← TR-25
 461 AAAAA ← TR-25
 462 AAAAA ← TR-25

LAND SEISMIC RECORDING LOG

CLIENT: Husky		PROSPECT: NPR-A		AREA: BARROW		LINE NO.: 610									
PARTY NO.: 1182		INST. ENG.: STREFF-WINDHAM		DATE: MO 3 DAY 17 TH 79											
INSTRUMENT <input checked="" type="checkbox"/> 1 SYSTEM <input type="checkbox"/> 2 SYSTEMS		NO. BYTES IN HEADER REC.: _____ NO. BYTES IN RECORD ID: _____		NO. BYTES PER SCAN: 134		TRACKS: <input checked="" type="checkbox"/> 1 TRACK <input type="checkbox"/> 2 TRACKS		FOPMAT: SEG B		GAPPED: <input type="checkbox"/> GAPPED <input type="checkbox"/> UNGAPPED		PACKING DENSITY: (10) <input type="checkbox"/> 356 BP <input type="checkbox"/> 800 BP		(M) <input type="checkbox"/> 712 BP <input type="checkbox"/> 1000 BP	
CONFIGURATION (MAG TAPE) FIELD TRACE NOS.: 1-48 DATA CHANNEL NOS.: 1-48		AUXILIARY DATA: 1A 1A AUXILIARY CHANNEL NOS.: 3 4		GAIN CONSTANT: 36 db		INPUT IMPEDANCE: _____ ohms									
PARAMETER RECORD LENGTH: 6 sec.		SAMPLE RATE: <input checked="" type="checkbox"/> 1 ml. <input type="checkbox"/> 4 ml.		GAIN MODE: <input checked="" type="checkbox"/> INITIAL <input type="checkbox"/> FINAL		FILTERS: _____		LO CUT HZ SLOPE: _____		HI CUT HZ SLOPE: 70		INDICH FILTER: <input type="checkbox"/> IN <input type="checkbox"/> OUT			
DISPLAY MODE: <input type="checkbox"/> FLOAT <input type="checkbox"/> AMPLIFIER <input type="checkbox"/> DIRECT		INITIAL GAIN: 18 db		TRIP SENS.: 24 db		POLARITY CONVENTION: _____		PRESSURE INCREASE ON GEOPHONE: _____		NEGATIVE POSITIVE } NUMBERS ON MAG TAPE		DOWNBREAK UPBREAK } ON DISPLAY			
CFS I TYPE STACK: _____		GATE LENGTH: _____		RECORD REJECTION: _____		NOISE REDUCTION: _____		NOISE THRESHOLD: _____		CORR. SCALING: _____		R.C.U. NORM./ALT SW.			
SOURCE <input type="checkbox"/> DYNAMITE <input type="checkbox"/> VIBROSEIS <input type="checkbox"/> OTHER		PATTERN: Single hole - Tallies		NO. OF POSITIONS: _____		INLINE SPACING: _____		LATERAL SPACING: _____		STAGGER: _____		LENGTH: _____		WIDTH: _____	
RECEIVER TYPE: CS-200		CONNECTION: Schive Parallel		RESISTANCE: 560 ohms		NO. OF ELEMENTS: 18		INLINE SPACING: 12'		LATERAL SPACING: _____		WIDTH: _____		LATERAL OFFSET: _____	
SPREAD NO. OF GROUPS: 48		GROUP INTERVAL: 330'		SHOTPOINT INTERVAL: 1320'		FOLD: 6		DIRECTION OF PROGRESSION: S → N		LEADING GROUP: 48					
OFFSET GROUP 1: 7755'		OFFSET GROUP 24: 165'		OFFSET GROUP 25: 165'		OFFSET GROUP 48: 7755'									

DIAGRAMS/MISC. INFORMATION:

SHOTPOINT	TR 1 to 48		TR 17 to 24		SHOT		SPREAD		REMARKS	CORR. STACK		
	REEL NO.	REC.	REEL NO.	REC.	SIZE	DEPTH	NO. OFFSET	DIR.		CDP SWITCH	LINE GROUPS	TR 1-16
1102	75189R	141			20	16721	1		29	96+1 - 107+4	6	
1103		142			20	16722	1		33	97+1 - 108+4		
1104		143			20	16723	1		37	98+1 - 109+4		
1105		144			30	16724	1		41	99+1 - 110+4		
1106		145			30	16725	1		45	100+1 - 111+4		
1107		146			30	16726	1		29	101+1 - 112+4	7	
1108		147			30	16727	1		33	102+1 - 113+4		
1109		148			30	16728	1		37	103+1 - 114+4		
1110		149			30	16729	1		41	104+1 - 115+4		
1111		150			30	16730	1		45	105+1 - 116+4		
1112		151			30	16731	1		49	106+1 - 117+4		
1113		152			30	16732	1		53	107+1 - 118+4		
1114		153			30	16733	1		57	108+1 - 119+4		
1115		154			30	16734	1		21	109+1 - 120+4	8	
1116		155			30	16735	1		25	110+1 - 121+4		
1117		156			30	16736	1		29	111+1 - 122+4		
1118		157			30	16737	1		33	112+1 - 123+4		
1119		158			30	16738	1		37	113+1 - 124+4		
1120		159			30	16739	1		41	114+1 - 125+4		
1121		160			30	16740	1		45	115+1 - 126+4		

File # 143 mis fire

Recorder @ SP-107

Recorder @ SP-112

Recorder @ SP-122

Recording hrs 14.5

LAND SEISMIC RECORDING LOG

CLIENT: HUSHY		PROSPECT: NPR-A		AREA: Barrow		LINE NO: 610	
PARTY NO: 1182		INST. ENG: Streff-Windham		DATE: NO 2 DAY 18 YR 79			
INSTRUMENT (9-TRACK) NO. BYTES IN HEADER REC. _____		NO. BYTES IN RECORD ID: _____		NO. BYTES PER SCAN: 134		RECORD NUMBERS: _____	
CONFIGURATION (MAG TAPE) FIELD TRACE NOS.: 1-48		DATA CHANNEL NOS.: 1-48		AUXILIARY DATA: _____		AUXILIARY CHANNEL NOS.: _____	
PARAMETER RECORD LENGTH: 6 sec		SAMPLE RATE: 0.7 ms		GAIN MODE: INITIAL		FILTERS: _____	
DISPLAY MODE: ACC		INITIAL GAIN: 24 db		TRIP SENS.: 0 db		POLARITY CONVENTION: _____	
SOURCE TYPE: OVNAMITE		PATTERN: Inline/Whole		NO. OF POSITIONS: _____		LATERAL SPACING: _____	
RECEIVER TYPE: 20-0		PATTERN: Inline		NO. OF ELEMENTS: 18		LATERAL SPACING: _____	
SPREAD NO. OF GROUPS: 48		GROUP INTERVAL: 330		SHOTPOINT INTERVAL: 1320		FOLD: 6	

DIAGRAMS/MISC. INFORMATION:
 11921 X ----- X ⊗ X ----- X 13044
 TR#1 TR#24 TR#25 TR#48
 #166-173 test
 #174 test

SHOTPOINT	TR 1		TR 2		SHOT		SPREAD		REMARKS	
	REEL NO.	REC.	REEL NO.	REC.	SIZE	DEPTH	NO. OFFSET	DIR.		
1125	1181	1175			20	167	1	29	119+1 - 130+4	1 Recorder @ SP-130
1126	1182	1176			20	167	2	33	120+1 - 131+4	
1127	1183	1177			20	167	3	37	121+1 - 132+4	
1128	1184	1178			20	167	4	41	122+1 - 133+4	
1129	1185	1179			20	167	5	45	123+1 - 134+4	
1130	1186	1180			20	167	6	49	124+1 - 135+4	
1131	1187	1181			20	167	7	53	125+1 - 136+4	
1132	1188	1182			20	167	8	57	126+1 - 137+4	
1133	1189	1183			20	167	9	61	127+1 - 138+4	
1134	1190	1184			20	167	10	65	128+1 - 139+4	
1135	1191	1185			20	167	11	69	129+1 - 140+4	2 Recorder @ SP-141
1136	1192	1186			20	167	12	73	130+1 - 141+4	
1137	1193	1187			20	167	13	77	131+1 - 142+4	
1138	1194	1188			20	167	14	81	132+1 - 143+4	
1139	1195	1189			20	167	15	85	133+1 - 144+4	
1140	1196	1190			20	167	16	89	134+1 - 145+4	
1141	1197	1191			20	167	17	93	135+1 - 146+4	
1142	1198	1192			20	167	18	97	136+1 - 147+4	
1143	1199	1193			20	167	19	101	137+1 - 148+4	
1144	1200	1194			20	167	20	105	138+1 - 149+4	

LAND SEISMIC RECORDING LOG

		CLIENT: Husky	PROSPECT: NPR-A	AREA: Barrow	LINE NO: 610					
PARTY NO: 1182		INST. ENG: Streiff-Windham		DATE: MO 2 DAY 18 YR 78						
INSTRUMENT (9-TRACK)	<input checked="" type="checkbox"/> 1 SYSTEM <input checked="" type="checkbox"/> 2 SYSTEMS	<input checked="" type="checkbox"/> 24 & 25-48 <input checked="" type="checkbox"/> 1-48 & 49-96	DOOS EVENTS	TYPE: <input type="checkbox"/> DFS III <input type="checkbox"/> DFS II <input type="checkbox"/> OTHER	<input type="checkbox"/> 1 TRACK <input type="checkbox"/> 2 TRACK	FORMAT: B	<input checked="" type="checkbox"/> GAPPED <input type="checkbox"/> UNGAPPED	PACKING DENSITY: (10) <input type="checkbox"/> 356 BPI (11) <input type="checkbox"/> 712 BPI (12) <input type="checkbox"/> 800 BPI (13) <input type="checkbox"/> 1600 BPI		
	NO. BYTES IN HEADER REC.	NO. BYTES IN RECORD ID	NO. BYTES PER SCAN: 134	RECORD NUMBERS: <input type="checkbox"/> DEC. <input type="checkbox"/> OCT.	GAIN CONSTANT: 36	INPUT IMPEDANCE: 20K ohms	(1) (2) (3) (4) (5) (6) (7)			
CONFIGURATION (MAG TAPE)	FIELD TRACE NOS.: 1-48			AUXILIARY DATA:			DATA CHANNEL NOS.: 1-48 (ON MAG TAPE)			
PARAMETER	RECORD LENGTH: 6 sec	SAMPLE RATE: <input type="checkbox"/> 1 sec <input type="checkbox"/> 4 sec	GAIN MODE: <input checked="" type="checkbox"/> INITIAL <input type="checkbox"/> MANUAL <input type="checkbox"/> OPERATE	FILTERS: <input type="checkbox"/> LO CUT <input type="checkbox"/> HI CUT		NOISE REDUCTION: <input type="checkbox"/> NOISE THRESHOLD: <input type="checkbox"/> CORR. SCALING: <input type="checkbox"/> R.C.U. NOEM/ALT SW.				
DISPLAY	MODE: <input type="checkbox"/> FLOAT <input type="checkbox"/> AMPLIFIER <input type="checkbox"/> DIRECT	INITIAL GAIN: 24 db	TAP SENS: 0 db	POLARITY CONVENTION: <input type="checkbox"/> PRESSURE INCREASE ON GEOPHONE: <input type="checkbox"/> POSITIVE <input type="checkbox"/> NEGATIVE		NUMBERS ON MAG. TAPE: <input type="checkbox"/> DOWNBREAK <input type="checkbox"/> UPBREAK <input type="checkbox"/> ON DISPLAY				
CFS I	TYPE STACK:	GATE LENGTH:	RECORD REJECTION:	NOISE REDUCTION:		CORR. SCALING:				
SOURCE	TYPE: <input checked="" type="checkbox"/> DYNAMITE <input type="checkbox"/> VIBROSEIS <input type="checkbox"/> OTHER	PATTERN: inline/hole	NO. OF POSITIONS: 30	INLINE SPACING: 75	LATERAL SPACING:	STAGGER: 15	LENGTH: 15	WIDTH: 48	LATERAL OFFSET:	
RECEIVER	TYPE: 200	PATTERN: inline	NO. OF ELEMENTS: 18	INLINE SPACING: 15	LATERAL SPACING:	STAGGER: 15	LENGTH: 15	WIDTH: 48	LATERAL OFFSET:	
SPREAD	CONNECTION: Series-Parallel	RESISTANCE: 560 ohms	STAGGER:	LENGTH: 15	WIDTH: 48	LATERAL OFFSET:	DIRECTION OF PROGRESSION: North			
NO. OF GROUPS: 48		GROUP INTERVAL: 330	SHOTPOINT INTERVAL: 1320	FOLD: 6	DIRECTION OF PROGRESSION: North			LEADING GROUP: 48		
OFFSET GROUP 1: 7755		OFFSET GROUP 2: 165	OFFSET GROUP 3: 165	OFFSET GROUP 40/96: 7755	DIRECTION OF PROGRESSION: North			LEADING GROUP: 48		

DIAGRAMS/MISC. INFORMATION:

SHOTPOINT	TR. 10		TR. 20		SHOT		SPREAD		REMARKS	CORR. STACK					
	REEL NO.	REC.	REEL NO.	REC.	SIZE	DEPTH	NO.	OFFSET		DIR.	COP SWITCH	LINE GROUPS	TR. 10	TR. 20	TR. 30
1145	7511872	195			20	167	21		65	139+1 - 150+4	2				
1146		196			20	167	22		29	140+1 - 151+4	3				
1147		197			20	167	23		33	141+1 - 152+4					
1148		200			20	167	24		37	142+1 - 153+4					
*1149		201			20	167	25		45	144+1 - 155+4					
1150		202			20	167	26		45	144+1 - 155+4					
1151		203			40	159	27		49	145+1 - 156+4					
1152		204			40	159	28		53	146+1 - 157+4					
1153		205			40	159	29		57	147+1 - 158+4					
1154		206			20	167	30		61	148+1 - 159+4					
1155		207			20	167	31		65	149+1 - 160+4					
1156		208			20	167	32		25	150+1 - 161+4	4				
1157		209			20	167	33		29	151+1 - 162+4					
1158		210			20	167	34		33	152+1 - 163+4					
1159		211			20	167	35		37	153+1 - 164+4					
1160		212			20	167	36		41	154+1 - 165+4					
1161		213			20	167	37		45	155+1 - 166+4					
1162		214			20	167	38		49	156+1 - 167+4					
1163		215			20	167	39		53	157+1 - 168+4					
1164		216			20	167	40		57	158+1 - 169+4					

LAND SEISMIC RECORDING LOG

		CLIENT: Husky	PROSPECT: NPR-A	AREA: Borrow	LINE NO: 610		
PARTY NO: 1182		INST. ENG: Streiff-Windham			DATE: MO 2 DAY 18 YR 79		
INSTRUMENT (9-TRACK) <input type="checkbox"/> 1 SYSTEM <input type="checkbox"/> 2 SYSTEMS <input type="checkbox"/> 1-24 & 25-48 <input type="checkbox"/> 1-48 & 49-96		NO. BYTES IN HEADER REC.:		NO. BYTES IN RECORD ID:		NO. BYTES PER SCAN: 134	
CONFIGURATION (MAG TAPE) FIELD TRACE NOS.: 1-48 DATA CHANNEL NOS.: 1-48		AUXILIARY DATA: AUXILIARY CHANNEL NOS.:					
PARAMETER RECORD LENGTH: 6 sec.		SAMPLE RATE: <input type="checkbox"/> 1 sec. <input type="checkbox"/> 4 sec.		GAIN MODE: <input checked="" type="checkbox"/> INITIAL <input type="checkbox"/> FINAL		FILTERS: <input type="checkbox"/> LO CUT <input type="checkbox"/> HI CUT	
DISPLAY MODE: <input checked="" type="checkbox"/> AGC <input type="checkbox"/> FLOAT <input type="checkbox"/> AMPLIFIER <input type="checkbox"/> DIRECT		INITIAL GAIN: 24 db		ZNR SENS.: 0 db		POLARITY CONVENTION: <input type="checkbox"/> NEGATIVE <input checked="" type="checkbox"/> POSITIVE	
CFS I TYPE STACK:		GATE LENGTH:		RECORD REJECTION:		NOISE REDUCTION: <input type="checkbox"/> CORR. SCALING: <input type="checkbox"/>	
SOURCE TYPE: <input checked="" type="checkbox"/> DYNAMITE <input type="checkbox"/> VIBROSEIS <input type="checkbox"/> OTHER		PATTERN: inline / hole		NO. OF POSITIONS:		INLINE SPACING:	
RECEIVER TYPE: 20-p		PATTERN: 1 inline		NO. OF ELEMENTS: 18		INLINE SPACING: 15'	
SPREAD NO. OF GROUPS: 48		GROUP INTERVAL: 330'		SHOTPOINT INTERVAL: 1720		FOLD: 6	
DIAGRAMS/MISC. INFORMATION:		CHG/ HOLE: 20		HOLE DEPTH: 75		SWEEP POSITION: 165	
CONNECTION: Series-Parallel		RESISTANCE: 560 ohms		STAGGER:		LENGTH:	
OFFSET GROUP 1: 7755		OFFSET GROUP 2: 165		OFFSET GROUP 3: 165		OFFSET GROUP 4: 7755	

SHOTPOINT	TR 19		TR 20		SHOT				SPREAD			REMARKS	CORR STACK		
	REEL NO.	REC.	REEL NO.	REC.	SIZE	DEPTH	NO.	OFFSET	DIR.	CDP SWITCH	LINE GROUPS		HT.	REC.	HT.
16165	75189.2	0117			20	617.41				61	159+1 - 170+4	4			
16166		0118			20	617.82				32	160+1 - 171+4	5	Recorder @ SP-172		
16167		0119			20	617.43				33	161+1 - 172+4				
16168		0120			20	617.44				37	162+1 - 173+4				

Recording Hrs. - 120

LAND SEISMIC RECORDING LOG

CLIENT: Husky		PROSPECT: NPR-A		AREA: Barrow		LINE NO: 610	
PARTY NO: 1182		INST. ENG: Streff-Windham		DATE: MO 2 DAY 19 YE 79			
INSTRUMENT (9-TRACK) <input type="checkbox"/> 1 SYSTEM <input checked="" type="checkbox"/> 2 SYSTEMS		NO. BYTES IN HEADER REC.:		NO. BYTES IN RECORD ID:		NO. BYTES PER SCAN: 134	
CONFIGURATION (MAG TAPE)		FIELD TRACE NOS.: 1-48		DATA CHANNEL NOS.: 1-48		AUXILIARY DATA:	
PARAMETER		RECORD LENGTH: 6 sec.		SAMPLE RATE: <input type="checkbox"/> 1 ms. <input type="checkbox"/> 4 ms.		GAIN MODE: <input type="checkbox"/> INITIAL <input type="checkbox"/> MANUAL <input type="checkbox"/> FINAL <input type="checkbox"/> OPERATE	
DISPLAY		MODE: <input checked="" type="checkbox"/> AGC <input type="checkbox"/> FLOAT <input type="checkbox"/> DEFLAT <input type="checkbox"/> AMPLIFIER <input type="checkbox"/> DIRECT		INITIAL GAIN: 24 db		TRIP SENS.: 0 db	
CFS I		TYPE STACK:		GATE LENGTH:		RECORD REJECTION:	
SOURCE		TYPE: <input type="checkbox"/> DYNAMIC <input type="checkbox"/> VIBROSEIS <input type="checkbox"/> OTHER		PATTERN: inline-hole		NO. OF POSITIONS: 1	
RECEIVER		CONNECTION: Series-Parallel		RESISTANCE: 560 ohms		STAGGER: 18	
SPREAD		NO. OF GROUPS: 48		GROUP INTERVAL: 330		SHOTPOINT INTERVAL: 1720	
DIAGRAMS/MISC. INFORMATION:		OFFSET GROUP 1: 7755		OFFSET GROUP 24: 165		OFFSET GROUP 48/96: 7755	

SHOTPOINT	TR		TR		SHOT		DIR.	CDP SWITCH	LINE GROUPS	REMARKS	CORR. STACK	
	NO.	REEL NO.	NO.	REC.	SIZE	DEPTH					NO.	OFFSET
11708	2311	228	2225	226	210	167	11	29	16321-17414	1	Recorder @ SP-174 (16311 drd)	
11710		2310			210	167	12	33	16411-17514			
11711		2311			210	167	13	37	16511-17614			
11712		2312			210	167	14	41	16611-17714			
11713		2313			210	167	15	45	16711-17814			
11714		2314			210	167	16	49	16811-17914			
11715		2315			210	167	17	53	16911-18014			
11716		2316			210	167	18	29	17011-18114	2	Recorder @ SP-181	
11717		2317			210	167	19	33	17111-18214			
11718		2318			210	167	20	37	17211-18314			
11719		2319			210	167	21	41	17311-18414			
11720		2320			210	167	22	45	17411-18514			
11721		2321			210	167	23	49	17511-18614			
11722		2322			210	167	24	53	17611-18714			
11723		2323			210	167	25	57	17711-18814			
11724		2324			210	167	26	57	17711-18814			
11725		2325			210	167	27	57	17711-18814			
11726		2326			210	167	28	57	17711-18814			
11727		2327			210	167	29	57	17711-18814			
11728		2328			210	167	30	57	17711-18814			
11729		2329			210	167	31	57	17711-18814			

*NO RECS # 221-228

Shooting through cable - CDP does not move

E.O.L.