


# LAND SEISMIC RECORDING LOG

	CLIENT: <b>Husky</b>	PROSPECT: <b>NPR-A</b>	AREA: <b>BARROW</b>	LINE NO: <b>612</b>						
	PARTY NO: <b>1182</b>	INST. ENG: <b>STREFF-WINDHAM</b>		DATE: <b>MO 2 DAY 9 YR 79</b>						
INSTRUMENT (9-TRACK)	<input checked="" type="checkbox"/> 1 SYSTEM <input type="checkbox"/> 2 SYSTEMS	<input checked="" type="checkbox"/> 1-24 & 25-48 <input type="checkbox"/> 1-48 & 49-96	ODDS & EVENS	TYPE: <input type="checkbox"/> DFS III <input type="checkbox"/> DFS IV	<input checked="" type="checkbox"/> 9 TRACK <input type="checkbox"/> 21 TRACK	FORMAT: <b>B</b>	<input checked="" type="checkbox"/> GAPPED <input type="checkbox"/> UNGAPPED	PACKING DENSITY: (LO) <input type="checkbox"/> 356 SFI <input type="checkbox"/> 800 SFI	(HI) <input type="checkbox"/> 712 SFI <input checked="" type="checkbox"/> 1600 SFI	
	NO. BYTES IN HEADER REC:	NO. BYTES IN RECORD ID:	NO. BYTES PER SCAN:	RECORD NUMBERS: <input checked="" type="checkbox"/> DEC. <input type="checkbox"/> OCT.	GAIN CONSTANT: <b>36</b> db	INPUT IMPEDANCE: _____ ohms.				
CONFIGURATION (MAG TAPE)	FIELD TRACE NOS.: <b>1-48</b>				AUXILIARY DATA:					
	DATA CHANNEL NOS.: <b>1-48</b> (ON MAG-TAPE)				AUXILIARY CHANNEL NOS.:					
PARAMETER	RECORD LENGTH: <b>6</b> sec.	SAMPLE RATE: <input type="checkbox"/> 1 ms. <input type="checkbox"/> 4 ms. <input checked="" type="checkbox"/> 2 ms.	GAIN MODE: <input type="checkbox"/> INITIAL <input checked="" type="checkbox"/> TRIP	<input type="checkbox"/> MANUAL <input checked="" type="checkbox"/> OPERATE	FILTERS: FREQ. <b>OUT</b>	LO CUT HZ SLOPE: <b>-</b>	FREQ. <b>128</b>	HI CUT HZ SLOPE: <b>70</b>	NOTCH FILTER: <input type="checkbox"/> IN <input checked="" type="checkbox"/> OUT	
DISPLAY	MODE: <input type="checkbox"/> FLOAT <input checked="" type="checkbox"/> AGC	<input type="checkbox"/> AMPLIFIER <input type="checkbox"/> DIRECT	INITIAL GAIN: <b>30</b> db	TRIP SENS: _____ db	POLARITY CONVENTION: _____	PRESSURE INCREASE ON GEOPHONE: _____	<input type="checkbox"/> NEGATIVE <input checked="" type="checkbox"/> POSITIVE	NUMBERS ON MAG. TAPE: _____	<input type="checkbox"/> DOWNBREAK <input checked="" type="checkbox"/> UPBREAK	
CFS I	TYPE STACK:	GATE LENGTH:	RECORD REJECTION:	NOISE REDUCTION:	NOISE THRESHOLD:	CORR. SCALING:	R.C.U. NORM/ALT SW.			
SOURCE	<input checked="" type="checkbox"/> DYNAMITE <input type="checkbox"/> VIBROSEIS <input type="checkbox"/> OTHER	PATTERN: <b>INLINE SINGLE HOLE</b>	NO. OF POSITIONS:	INLINE SPACING:	LATERAL SPACING:	STAGGER:	LENGTH:	WIDTH:	LATERAL OFFSET:	
	CHG./HOLE: <b>20</b>	HOLE DEPTH: <b>75</b>	SWEEP POSITION:	SWEEP START:	SWEEP END:	SWEEP LENGTH:	SWEEP TAPER:	PHASE COMP.		
RECEIVER	TYPE: <b>20 D</b>	PATTERN: <b>INLINE</b>	NO. OF ELEMENTS: <b>18</b>	INLINE SPACING: <b>15'</b>	LATERAL SPACING:	STAGGER:	LENGTH:	WIDTH:	LATERAL OFFSET:	
	CONNECTION: <b>SERIES / PARALLEL</b>	RESISTANCE: _____ ohms	STAGGER:	LENGTH:	WIDTH:	LATERAL OFFSET:				
SPREAD	NO. OF GROUPS: <b>48</b>	GROUP INTERVAL: <b>330'</b>	SHOTPOINT INTERVAL: <b>1320'</b>	FOLD: <b>6</b>	DIRECTION OF PROGRESSION: <b>SOUTH</b>					
	OFFSET GROUP 1: <b>7755'</b>	OFFSET GROUP 24: <b>165'</b>	OFFSET GROUP 25: <b>165'</b>	OFFSET GROUP 48/96: <b>7755'</b>	LEADING GROUP: <b>48</b>					



SHOTPOINT	TR. 1 to 16		TR. 17 to 32		SHOT		SPREAD			REMARKS:	CORR. STACK						
	REEL NO.	REC.	REEL NO.	REC.	SIZE	DEPTH	NO.	OFFSET	DIR.		CDP SWITCH	LINE GROUPS		TR. 1-16	TR. 17-32		
1	751	A518			20	67117				33	1+1	- 12+4	1				
2		A59			20	67118				33	1+1	- 12+4					
3		A60			20	67119				33	1+1	- 12+4					
4		A61			20	6720				33	1+1	- 12+4					
5		A62			20	6721				33	1+1	- 12+4					
6		A63			20	6722				33	1+1	- 12+4					
7		A64			20	6723				33	1+1	- 12+4					
8		A65			20	6724				37	2+1	- 13+4					
9		A66			20	6725				41	3+1	- 14+4					
10		A67			20	6726				45	4+1	- 15+4					
11		A68			20	6727				49	5+1	- 16+4					
12		A69			20	6728				53	6+1	- 17+4					
13		A70			20	6729				25	7+1	- 18+4	2				

# LAND SEISMIC RECORDING LOG

	CLIENT: <b>HUSKY</b>	PROSPECT: <b>NPR-A</b>	AREA: <b>BARROW</b>	LINE NO: <b>612</b>	
	PARTY NO: <b>1182</b>	INST. ENG: <b>STREFF-WINDHAM</b>		DATE: <b>MO 2 DAY 10 YR 79</b>	

INSTRUMENT (9-TRACK)	<input checked="" type="checkbox"/> 1 SYSTEM <input type="checkbox"/> 2 SYSTEMS	<input checked="" type="checkbox"/> 1-24 & 25-48 <input type="checkbox"/> 1-48 & 49-96	ODDS EVENS	TYPE: <input type="checkbox"/> DFS III <input checked="" type="checkbox"/> DFS IV <input type="checkbox"/> OTHER	<input checked="" type="checkbox"/> 9 TRACK <input type="checkbox"/> 21 TRACK	FOPMAT: <b>B</b> SEG:	<input checked="" type="checkbox"/> GAPPED <input type="checkbox"/> UNGAPPED	PACKING DENSITY: (LO) <input type="checkbox"/> 356 BPI (HI) <input type="checkbox"/> 712 BPI <input type="checkbox"/> 800 BPI <input type="checkbox"/> 1600 BPI
	NO. BYTES IN HEADER REC:	NO. BYTES IN RECORD ID:	NO. BYTES PER SCAN:	RECORD NUMBERS: <input checked="" type="checkbox"/> DEC. <input type="checkbox"/> OCT.	GAIN CONSTANT: <b>36</b> db	INPUT IMPEDANCE: (1) (2) (3) (4) (5) (6) (7) ohms.		


CONFIGURATION (MAG TAPE)	FIELD TRACE NOS.: <b>1-48</b>	AUXILIARY DATA:
	DATA CHANNEL NOS.: <b>1-48</b> (ON MAG TAPE)	AUXILIARY CHANNEL NOS.:

PARAMETER	RECORD LENGTH: <b>6</b> sec.	SAMPLE RATE: <input type="checkbox"/> 1 ms. <input type="checkbox"/> 4 ms. <input type="checkbox"/> 2 ms.	GAIN MODE: <input type="checkbox"/> INITIAL <input type="checkbox"/> MANUAL <input type="checkbox"/> FINAL <input type="checkbox"/> OPERATE	FILTERS: FREQ. LO CUT HZ SLOPE HI CUT HZ SLOPE	NOTCH FILTER: <input type="checkbox"/> IN <input type="checkbox"/> OUT
DISPLAY	MODE: <input type="checkbox"/> AGC <input type="checkbox"/> FLOAT <input type="checkbox"/> DEFLOAT <input type="checkbox"/> AMPLIFIER <input type="checkbox"/> DIRECT	INITIAL GAIN: <b>20</b> db	TRIP SENS: <b>5</b> db	POLARITY CONVENTION: <input type="checkbox"/> NEGATIVE <input type="checkbox"/> POSITIVE	NUMBERS ON MAG. TAPE: <input type="checkbox"/> DOWNBREAK <input type="checkbox"/> UPBREAK ON DISPLAY

SOURCE	TYPE: <input type="checkbox"/> DYNAMITE <input type="checkbox"/> VIBROSEIS <input type="checkbox"/> OTHER	PATTERN: <b>inline/shot</b>	NO. OF POSITIONS:	INLINE SPACING:	LATERAL SPACING:	STAGGER:	LENGTH:	WIDTH:	LATERAL OFFSET:
		CHG/ HOLE: <b>20</b>	HOLE DEPTH: <b>75</b>	SWEEP POSITION:	SWEEP START:	SWEEP END:	SWEEP LENGTH:	SWEEP TAPER:	PHASE COMP.

RECEIVER	TYPE: <b>200</b>	PATTERN: <b>inline</b>	NO. OF ELEMENTS: <b>19</b>	INLINE SPACING: <b>15'</b>	LATERAL SPACING:
	CONNECTION: <b>Series Parallel</b>	RESISTANCE: <b>500</b> ohms	STAGGER:	LENGTH:	WIDTH:

SPREAD	NO. OF GROUPS: <b>48</b>	GROUP INTERVAL: <b>330</b>	SHOTPOINT INTERVAL: <b>1330</b>	FOLD: <b>6</b>	DIRECTION OF PROGRESSION: <b>South</b>
	OFFSET GROUP 1: <b>7755</b>	OFFSET GROUP 2: <b>165</b>	OFFSET GROUP 25: <b>165</b>	OFFSET GROUP 48/96: <b>7755</b>	LEADING GROUP: <b>48</b>



SHOTPOINT	TR. 10		TR. 20		SHOT				SPREAD			REMARKS	CORR. STACK				
	REEL NO.	REC.	REEL NO.	REC.	SIZE	DEPTH	NO.	OFFSET	DIR.	COP SWITCH	LINE GROUPS		SET UP	TR 1-10	TR 11-20	TR 21-30	TR 31-40
14	761288	480			20	67	1			21	8+1 - 19+4	1					
15		481			20	67	2			25	9+1 - 20+4						
16		482			20	67	3			29	10+1 - 21+4						
17		483			20	67	4			33	11+1 - 22+4						
18		484			20	67	5			37	12+1 - 23+4						
19		485			20	67	6			41	13+1 - 24+4						
20		486			20	67	7			45	14+1 - 25+4						
21		487			20	67	8			49	15+1 - 26+4						
22		488			20	67	9			41	16+1 - 27+4	2					
23		489			20	67	10			45	17+1 - 28+4						
24		490			20	67	11			49	18+1 - 29+4						
25		491			20	67	12			53	19+1 - 30+4						
26		492			20	67	13			57	20+1 - 31+4	3					
27		493			20	67	14			57	21+1 - 32+4						
28		494			20	67	15			61	22+1 - 33+4						
29		495			20	67	16			65	23+1 - 34+4						
30		496			20	67	17			69	24+1 - 35+4	4					
31		497			20	67	18			73	25+1 - 36+4						
32		498			20	67	19			77	26+1 - 37+4						
33		499			20	67	20			81	27+1 - 38+4						

# LAND SEISMIC RECORDING LOG

	CLIENT: <u>Hess</u>	PROSPECT: <u>NPR-A</u>	AREA: <u>Permian</u>	LINE NO: <u>612</u>					
	PARTY NO: <u>11825</u>	INST. ENG: <u>Stroff-Walsh</u>		DATE: <u>MO 7 DAY 10 YR 77</u>					
INSTRUMENT (9-TRACK)	<input type="checkbox"/> 1 SYSTEM <input type="checkbox"/> 2 SYSTEMS	<input checked="" type="checkbox"/> 1-24 # 25-44 <input type="checkbox"/> 1-48 # 49-96	ODDS EVENS	TYPE: <input type="checkbox"/> DFS III <input type="checkbox"/> DFS IV <input type="checkbox"/> OTHER	<input type="checkbox"/> 9 TRACK <input type="checkbox"/> 21 TRACK	FORMAT: <u>15</u> SEG	<input type="checkbox"/> GAPPED <input type="checkbox"/> UNGAPPED	PACKING DENSITY: (LO) <input type="checkbox"/> 356 BPI <input type="checkbox"/> 800 BPI	(HI) <input type="checkbox"/> 712 BPI <input type="checkbox"/> 1600 BPI
	NO. BYTES IN HEADER REC: <u>9</u>	NO. BYTES IN RECORD ID: _____	NO. BYTES PER SCAN: _____	RECORD NUMBERS: <input type="checkbox"/> DEC. <input type="checkbox"/> OCT.	GAIN CONSTANT: <u>5.5</u> db	INPUT IMPEDANCE: _____ ohms			
CONFIGURATION (MAG TAPE)	FIELD TRACE NOS. <u>118</u>				AUXILIARY DATA: _____				
	DATA CHANNEL NOS. <u>1-4</u> (ON MAG TAPE)				AUXILIARY CHANNEL NOS.: _____				
PARAMETER	RECORD LENGTH: _____ sec.	SAMPLE RATE: <input type="checkbox"/> 1 ms. <input type="checkbox"/> 4 ms.	GAIN MODE: <input type="checkbox"/> INITIAL <input type="checkbox"/> MANUAL <input type="checkbox"/> TRF <input type="checkbox"/> FINAL <input type="checkbox"/> OPERATE	FILTERS: _____	LO CUT HZ SLOPE: _____	H1 CUT HZ SLOPE: <u>70</u>	NOTCH FILTER: <input type="checkbox"/> IN <input type="checkbox"/> OUT		
DISPLAY	MODE: <input type="checkbox"/> FLOAT <input type="checkbox"/> AMPLIFIER <input type="checkbox"/> AGC <input type="checkbox"/> DEFOAT <input type="checkbox"/> DIRECT	INITIAL GAIN: <u>30</u> db	TRIP SENS: <u>5</u> db	POLARITY CONVENTION: _____	PRESSURE INCREASE ON GEOPHONE: <input type="checkbox"/> NEGATIVE <input type="checkbox"/> POSITIVE	NUMBERS ON ON MAG. TAPE	<input type="checkbox"/> DOWNBREAK <input type="checkbox"/> UPBREAK	ON DISPLAY	
CFS I	TYPE STACK: _____	DATE LENGTH: _____	RECORD REJECTION: _____	NOISE REDUCTION: _____	NOISE THRESHOLD: _____	CORR. SCALING: _____	R.C.U. NORM/ALT SW.		
SOURCE	TYPE: <input type="checkbox"/> DYNAMITE <input type="checkbox"/> VIBROSEIS <input type="checkbox"/> OTHER	PATTERN: <u>Inline/1/4 in</u>	NO. OF POSITIONS: _____	INLINE SPACING: _____	LATERAL SPACING: _____	STAGGER: _____	LENGTH: _____	WIDTH: _____	LATERAL OFFSET: _____
RECEIVER	TYPE: <u>30-p</u>	PATTERN: <u>inline</u>	NO. OF ELEMENTS: <u>18</u>	INLINE SPACING: <u>15'</u>	LATERAL SPACING: _____	STAGGER: _____	LENGTH: _____	WIDTH: _____	LATERAL OFFSET: _____
SPREAD	CONNECTION: <u>Series-Parallel</u>	RESISTANCE: <u>500</u> ohms	SWEEP POSITION: _____	SWEEP START: _____	SWEEP END: _____	SWEEP LENGTH: _____	SWEEP TAPER: _____	PHASE COMP: _____	
	NO. OF GROUPS: <u>48</u>	GROUP INTERVAL: <u>330</u>	SHOTPOINT INTERVAL: <u>1320</u>	FOLD: <u>6</u>	DIRECTION OF PROGRESSION: <u>South</u>	OFFSET GROUP 1: <u>7755</u>	OFFSET GROUP 24: <u>165</u>	OFFSET GROUP 48/96: <u>7755</u>	LEADING GROUP: <u>48</u>

DIAGRAMS/MISC. INFORMATION:

SHOTPOINT	TR _____ to _____		TR _____ to _____		SHOT				SPREAD				REMARKS	CORR. STACK				
	REEL NO.	REC.	REEL NO.	REC.	SIZE	DEPTH	NO.	OFFSET	DIR.	CDP SWITCH	LINE GROUPS			SEP	TR 1-48	TR 48-96	TR 1-48	TR 48-96
															HY.	REC.	HY.	REC.
34	7511828	500			20	167	32			45	28+1 - 39+4	4						
35		501			20	167	32			49	29+1 - 40+4							
36		502			20	167	32			53	30+1 - 41+4							
37		503			20	167	32			57	31+1 - 42+4							
38		504			20	167	32			29	32+1 - 43+4	5	Recorder @ 70-43					
39		505			20	167	32			30	33+1 - 44+4							
40		506			20	167	32			37	34+1 - 45+4		CDP CRASH - Section - 32-33-1 -> 4000					
41		507			20	167	32			41	35+1 - 46+4							
42		508			20	167	32			45	36+1 - 47+4							
43		509			20	167	32			49	37+1 - 48+4							
44		510			20	167	32			53	38+1 - 49+4							
45		512			20	167	32			57	39+1 - 50+4							
46		513			20	167	32			29	40+1 - 51+4	6	Recorder @ SP-51					
47		514			20	167	32			33	41+1 - 52+4							
48		515			20	167	32			37	42+1 - 53+4							
49		516			20	167	32			41	43+1 - 54+4							
50		517			20	167	32			45	44+1 - 55+4							
51		518			20	167	32			49	45+1 - 56+4							
52		519			20	167	32			53	46+1 - 57+4							
53		520			20	167	40			57	47+1 - 58+4							

# LAND SEISMIC RECORDING LOG

	CLIENT: <u>Huey P</u>	PROSPECT: <u>NPR-A</u>	AREA: <u>Baylor</u>	LINE NO: <u>610</u>						
	PARTY NO: <u>1183</u>	INST. ENG: <u>31044 - Windham</u>		DATE: <u>MO 2 DAY 11 YR 72</u>						
INSTRUMENT (9-TRACK)	<input checked="" type="checkbox"/> SYSTEM <input type="checkbox"/> 2 SYSTEMS	<input type="checkbox"/> 1-24 & 25-48 <input type="checkbox"/> 1-48 & 49-96	ODDS & EVENS	TYPE: <input type="checkbox"/> DFS III <input type="checkbox"/> DFS IV	<input type="checkbox"/> DFS V <input type="checkbox"/> OTHER	<input checked="" type="checkbox"/> 9 TRACK <input type="checkbox"/> 21 TRACK	FORMAT: <u>SEG</u>	<input type="checkbox"/> GAPPED <input type="checkbox"/> UNGAPPED	PACKING DENSITY: (L) <input type="checkbox"/> 356 BPI <input type="checkbox"/> 800 BPI	(M) <input type="checkbox"/> 712 BPI <input type="checkbox"/> 1000 BPI
	NO. BYTES IN HEADER REC: <u>3</u>	NO. BYTES IN RECORD ID: <u>3</u>	NO. BYTES PER SCAN: <u>3</u>	RECORD NUMBERS: <input type="checkbox"/> DEC. <input type="checkbox"/> OCT.	GAIN CONSTANT: <u>(1)</u> <u>(2)</u> <u>(3)</u> <u>(4)</u> <u>(5)</u> <u>(6)</u> <u>(7)</u>	INPUT IMPEDANCE: <u>ohms</u>				
CONFIGURATION (MAG TAPE)	FIELD TRACE NOS.: <u>1-16</u>					AUXILIARY DATA:				
	DATA CHANNEL NOS.: <u>1-48</u> (ON MAG TAPE)					AUXILIARY CHANNEL NOS.:				
PARAMETER	RECORD LENGTH: <u>sec.</u>	SAMPLE RATE: <input type="checkbox"/> 1 ms. <input type="checkbox"/> 4 ms.	GAIN MODE: <input type="checkbox"/> INITIAL <input type="checkbox"/> MANUAL	FILTERS: <u>FREQ.</u> <u>LO CUT</u> <u>HZ SLOPE</u>		HI CUT <u>70</u> <u>HZ SLOPE</u>		NOTCH FILTER: <input type="checkbox"/> IN <input type="checkbox"/> OUT		
DISPLAY	MODE: <input type="checkbox"/> AGC <input type="checkbox"/> FLOAT <input type="checkbox"/> AMPLIFIER <input type="checkbox"/> DEFLOAT <input type="checkbox"/> DIRECT	INITIAL GAIN: <u>30</u> db	TRIP SENS: <u>5</u> db	POLARITY CONVENTION: <input type="checkbox"/> NEGATIVE <input type="checkbox"/> POSITIVE		PRESSURE INCREASE ON GEOPHONE: <input type="checkbox"/> NEGATIVE <input type="checkbox"/> POSITIVE		NUMBERS ON MAG. TAPE <input type="checkbox"/> DOWNBREAK <input type="checkbox"/> UPBREAK		
CFS I	TYPE STACK:	GATE LENGTH:	RECORD REJECTION:	NOISE REDUCTION:	NOISE THRESHOLD:	CORR. SCALING:	R.C.U. NORM / ALT SW.			
SOURCE	TYPE: <input type="checkbox"/> DYNAMITE <input type="checkbox"/> VIBROSEIS <input type="checkbox"/> OTHER	PATTERN: <u>ring/halo</u>	NO. OF POSITIONS:	INLINE SPACING:	LATERAL SPACING:	STAGGER:	LENGTH:	WIDTH:	LATERAL OFFSET:	
	CHG/ HOLE: <u>7011</u>	HOLE DEPTH: <u>75'</u>	SWEEP POSITION:	SWEEP START:	SWEEP END:	SWEEP LENGTH:	SWEEP TAPER:	PHASE COMP.		
RECEIVER	TYPE: <u>30-0</u>	PATTERN: <u>12110</u>	NO. OF ELEMENTS: <u>18</u>	INLINE SPACING: <u>15</u>	LATERAL SPACING:	STAGGER:	LENGTH:	WIDTH:	LATERAL OFFSET:	
	CONNECTION: <u>series/parallel</u>	RESISTANCE: <u>660</u> ohms	STAGGER:	LENGTH:	WIDTH:	LATERAL OFFSET:				
SPREAD	NO. OF GROUPS: <u>18</u>	GROUP INTERVAL: <u>330</u>	SHOTPOINT INTERVAL: <u>1300</u>	FOLO: <u>6</u>	DIRECTION OF PROGRESSION: <u>200+1</u>					
	OFFSET GROUP 1: <u>7755</u>	OFFSET GROUP 2: <u>105</u>	OFFSET GROUP 3: <u>105</u>	OFFSET GROUP 4: <u>7755</u>	LEADING GROUP: <u>48</u>					

DIAGRAMS/MISC. INFORMATION:

WIND - NOISE - (File #534 Noise strip) TR#1

#521 - 530 tests



#531 test + mebreak

TR#48

SHOTPOINT	TR. 1 to		TR. 2 to		SHOT		SPREAD		REMARKS:	CORR. STACK		
	REEL NO.	REC.	REEL NO.	REC.	SIZE	DEPTH	NO.	OFFSET		TR. 1-48	TR. 49-96	
54	7511810	5310			20	167	32	37	41	48+1 - 59+4	1	Recorder @ SP-56
55		5313			20	167	12		45	49+1 - 60+4		
56		5316			20	167	13		49	50+1 - 61+4		#535 N.G.
57		5317			20	167	14	75	53	51+1 - 62+4		
58		5318			20	167	15		57	52+1 - 63+4		
59		5319			20	167	16		61	53+1 - 64+4		
60		5320			20	167	17		65	54+1 - 65+4		
61		5321			20	167	18		69	55+1 - 66+4		#541 - N.G.
62		5323			20	167	19		73	56+1 - 67+4		
63		5324			20	167	20		77	57+1 - 68+4		#544 545 - N.G.
64		5325			20	167	21		81	58+1 - 69+4		#547 - 548 - N.G.
65		5326			20	167	22		85	59+1 - 70+4		
66		5327			20	167	23		29	60+1 - 71+4	2	Recorder @ SP-71
67		5328			20	167	24		33	61+1 - 72+4		
68		5329			20	167	25		37	62+1 - 73+4		#553 N.G.
69		5330			20	167	26		41	63+1 - 74+4		74+3 - dead
70		5331			20	167	27		45	64+1 - 75+4		
71		5332			20	167	28		49	65+1 - 76+4		
72		5333			20	167	29		53	66+1 - 77+4		
73		5334			20	167	30		57	67+1 - 78+4		#559 N.G.



# LAND SEISMIC RECORDING LOG

	CLIENT: <u>MUSKY</u>	PROSPECT: <u>NPA-A</u>	AREA: <u>Banyow</u>	LINE NO: <u>612</u>					
PARTY NO: <u>112</u>		INST. ENG: <u>Stiff Windham</u>		DATE: MO <u>2</u> DAY <u>11</u> YR <u>77</u>					
INSTRUMENT (9-TRACK)	<input checked="" type="checkbox"/> 1 SYSTEM <input checked="" type="checkbox"/> 2 SYSTEMS	<input type="checkbox"/> 1-24-8 28-48 <input type="checkbox"/> 1-48-8 49-96	ODDS <input type="checkbox"/> EVENS	TYPE: <input type="checkbox"/> DFS III <input type="checkbox"/> DFS IV	<input type="checkbox"/> 9 TRACK <input type="checkbox"/> 21 TRACK	FORMAT SEG <u>1</u>	<input type="checkbox"/> GAPPED <input type="checkbox"/> UNGAPPED	PACKING DENSITY: (L) <input type="checkbox"/> 356 BPI <input type="checkbox"/> 800 BPI	(M) <input type="checkbox"/> 712 BPI <input type="checkbox"/> 1600 BPI
	NO. BYTES IN HEADER REC: <u>1</u>	NO. BYTES IN RECORD ID: <u>1</u>	NO. BYTES PER SCAN: <u>1</u>	RECORD NUMBERS: <input type="checkbox"/> DEC. <input type="checkbox"/> OCT.	GAIN CONSTANT: <u>1</u> db	INPUT IMPEDANCE: _____ ohms.			
CONFIGURATION (MAG TAPE)	FIELD TRACE NOS. <u>1-18</u>			AUXILIARY DATA:			AUXILIARY CHANNEL NOS.:		
PARAMETER	RECORD LENGTH: <u>1.5</u> sec	SAMPLE RATE: <input type="checkbox"/> 1 ms. <input type="checkbox"/> 4 ms. <input type="checkbox"/> 2 ms. <input type="checkbox"/> _____ ms.	GAIN MODE: <input type="checkbox"/> INITIAL <input type="checkbox"/> FINAL	<input type="checkbox"/> MANUAL <input type="checkbox"/> OPERATE	FILTERS: FREQ. _____	LO CUT HZ SLOPE _____	HI CUT HZ SLOPE <u>70</u>	NOTCH FILTER: <input type="checkbox"/> IN <input type="checkbox"/> OUT	
DISPLAY	MODE: <input type="checkbox"/> FLOAT <input type="checkbox"/> AMPLIFIER <input type="checkbox"/> AGC <input type="checkbox"/> DEFOAT <input type="checkbox"/> DIRECT	INITIAL GAIN: <u>30</u> db	JRIP SENS: _____ db	POLARITY CONVENTION: <input type="checkbox"/> NEGATIVE <input type="checkbox"/> POSITIVE	PRESSURE INCREASE ON GEOPHONE: _____	NUMBERS ON MAG. TAPE: <input type="checkbox"/> DOWNBREAK <input type="checkbox"/> UPBREAK		ON DISPLAY	
CFS I	TYPE STACK: _____	GATE LENGTH: _____	RECORD REJECTION: _____	NOISE REDUCTION: _____	NOISE THRESHOLD: _____	CORR. SCALING: _____		R.C.U. NORM/ALT SW.	
SOURCE	TYPE: <input type="checkbox"/> DYNAMITE <input type="checkbox"/> VIBROSEIS <input type="checkbox"/> OTHER	PATTERN: <u>inline/shale</u>	NO. OF POSITIONS: _____	INLINE SPACING: _____	LATERAL SPACING: _____	STAGGER: _____	LENGTH: _____	WIDTH: _____	LATERAL OFFSET: _____
RECEIVER	TYPE: <u>20.0</u>	PATTERN: <u>inline</u>	NO. OF ELEMENTS: <u>18</u>	INLINE SPACING: <u>15</u>	LATERAL SPACING: _____	STAGGER: _____	LENGTH: _____	WIDTH: _____	LATERAL OFFSET: _____
SPREAD	NO. OF GROUPS: <u>48</u>	GROUP INTERVAL: <u>330</u>	SHOTPOINT INTERVAL: <u>1320</u>	FOLD: <u>6</u>	DIRECTION OF PROGRESSION: <u>South</u>	LEADING GROUP: <u>48</u>			
DIAGRAMS/MISC. INFORMATION:									

SHOTPOINT	TR. _____ to _____		TR. _____ to _____		SHOT				SPREAD			REMARKS:	CORR. STACK				
	REEL NO.	REC.	REEL NO.	REC.	SIZE	DEPTH	NO.	OFFSET	DIR.	CDP SWITCH	LINE GROUPS		SET UP	TR 1-48	TR 49-96	REC.	REC.
74	751	562			20	67	21			61	6811-79+1	2	#562 N.G.				
75		563			20	67	22			65	69+1-80+4		80+4 dead				
76		564			20	67	23			69	70+1-81+4						
77		566			20	67	24	4915	S	73	71+1-82+4		#565 N.G.				
78		568			20	67	25			41	72+1-83+4	3					
79		569			20	67	26			45	73+1-84+4						
80		570			20	67	27			49	74+1-85+4						
81		571			20	67	28			53	75+1-86+4						
82		574			20	67	29			57	76+1-87+4		#572, 573 N.G.				
83		576			20	67	30			61	77+1-88+4		#575 N.G.				

# LAND SEISMIC RECORDING LOG

14 Hours

	CLIENT: <b>HASKO STY</b>	PROSPECT: <b>NPR-A</b>	AREA: <b>AT BARROW</b>	LINE NO: <b>612</b>	
PARTY NO: <b>1182</b>		INST. ENG: <b>STREFF-WINDHAM</b>		DATE: <b>MO 2 DAY 12 YR 79</b>	

INSTRUMENT (9-TRACK)	<input type="checkbox"/> 1 SYSTEM <input type="checkbox"/> 2 SYSTEMS	<input type="checkbox"/> 1-24 <input type="checkbox"/> 1-48	ODDS EVENS	TYPE: <input type="checkbox"/> DFS III <input type="checkbox"/> DFS IV	<input type="checkbox"/> DFS V <input type="checkbox"/> OTHER	9 TRACK 2 TRACK	FORMAT: <b>B</b> SEG	<input type="checkbox"/> GAPPED <input type="checkbox"/> UNGAPPED	PACKING DENSITY: (10) <input type="checkbox"/> 356 BPI 800 BPI (11) <input type="checkbox"/> 712 BPI 1600 BPI		
NO. BYTES IN HEADER REC: <b>1</b>		NO. BYTES IN RECORD ID: <b>1</b>		NO. BYTES PER SCAN: <b>134</b>		RECORD NUMBERS: <input checked="" type="checkbox"/> DEC. <input type="checkbox"/> OCT.		GAIN CONSTANT: <b>36</b> db		INPUT IMPEDANCE: _____ ohms.	


CONFIGURATION (MAG TAPE)	FIELD TRACE NOS.: <b>1-48</b>	DATA CHANNEL NOS.: <b>1-48</b>	(ON MAG TAPE)	AUXILIARY DATA: <b>PR</b>	AUXILIARY CHANNEL NOS.: <b>3 4</b>
--------------------------	-------------------------------	--------------------------------	---------------	---------------------------	------------------------------------

PARAMETER	RECORD LENGTH: <b>6</b> sec.	SAMPLE RATE: <input type="checkbox"/> 1 ms. <input type="checkbox"/> 4 ms.	GAIN MODE: <input type="checkbox"/> INITIAL <input checked="" type="checkbox"/> TFP	FILTERS: FREQ. <b>OUT</b> LO CUT HZ SLOPE _____	HI CUT HZ SLOPE <b>70</b>	NOTCH FILTER: <input type="checkbox"/> IN <input checked="" type="checkbox"/> OUT
DISPLAY	MODE: <input checked="" type="checkbox"/> AGC <input type="checkbox"/> FLOAT <input type="checkbox"/> AMPLIFIER <input type="checkbox"/> DEFOAT <input type="checkbox"/> DIRECT	INITIAL GAIN: <b>18</b> db	TRIP SENS: <b>24</b> db	POLARITY CONVENTION: _____	PRESSURE INCREASE ON GEOPHONE: <input type="checkbox"/> NEGATIVE <input type="checkbox"/> POSITIVE	NUMBERS ON MAG. TAPE: <input type="checkbox"/> DOWNBREAK <input type="checkbox"/> UPBREAK

SOURCE	TYPE: <input checked="" type="checkbox"/> DYNAMITE <input type="checkbox"/> VIBROSEIS <input type="checkbox"/> OTHER	PATTERN: <b>Single hole - inline</b>	NO. OF POSITIONS: _____	INLINE SPACING: _____	LATERAL SPACING: _____	STAGGER: _____	LENGTH: _____	WIDTH: _____	LATERAL OFFSET: _____
CHG/ HOLE: <b>20</b>		HOLE DEPTH: <b>75</b>		SWEEP START: _____		SWEEP LENGTH: _____		SWEEP TAPER: _____	

RECEIVER	TYPE: <b>Gsc-20d</b>	PATTERN: <b>inline</b>	NO. OF ELEMENTS: <b>18</b>	INLINE SPACING: <b>12'</b>	LATERAL SPACING: _____
CONNECTION: <b>Series-Parallel</b>		RESISTANCE: <b>560</b> ohms		STAGGER: _____	

SPREAD	NO. OF GROUPS: <b>48</b>	GROUP INTERVAL: <b>330'</b>	SHOTPOINT INTERVAL: <b>1320'</b>	FOLD: <b>6</b>	DIRECTION OF PROGRESSION: <b>A' → S</b>
OFFSET GROUP 1: <b>7755</b>		OFFSET GROUP 24: <b>165</b>		OFFSET GROUP 48/96: <b>7755</b>	



SHOTPOINT	TR. 1 to 48		TR. to		SHOT										REMARKS	CORR. STACK	
	REEL NO.	REC.	REEL NO.	REC.	SIZE	DEPTH	NO.	OFFSET	DIR.	CDP SWITCH	LINE GROUPS		SET UP	TR 1-48		TR 48-96	
84	75118	5189			20	167	11			29	78+1 - 87+4		1				
85		5190			20	167	12			33	79+1 - 90+4						
86		5191			20	167	13			37	80+1 - 91+4						
87		5192			20	167	14			41	81+1 - 92+4						
88		5193			20	167	15			45	82+1 - 93+4				File # 593 N.G.		
89		5195			20	167	16			49	83+1 - 94+4						
90		5196			20	167	17			53	84+1 - 95+4						
91		5197			20	167	18			29	85+1 - 96+4		2		Recorder @ 5P96		
92		5198			20	167	19			33	86+1 - 97+4						
93		5199			20	167	20			37	87+1 - 98+4						
94		6000			20	167	11			41	88+1 - 99+4						
95		6001			20	167	12			45	89+1 - 100+4						
96		6002			20	167	13			49	90+1 - 101+4						
97		6004			20	167	14			29	91+1 - 102+4		3		Recorder @ 5P102		
98		6005			20	167	15			33	92+1 - 103+4						
99		6006			20	167	16			37	93+1 - 104+4						
100		6007			20	167	17			41	94+1 - 105+4						
101		6008			20	167	18			45	95+1 - 106+4						
102		6009			20	167	19			49	96+1 - 107+4						
103		6110			20	167	20			29	97+1 - 108+4		4		Recorder @ 5P108		

# LAND SEISMIC RECORDING LOG

CLIENT: <b>Husky</b>	PROSPECT: <b>NPR-A</b>	AREA: <b>Barron</b>	LINE NO: <b>612</b>
PARTY NO: <b>1182</b>	INST. ENG: <b>STREFF-Windham</b>		DATE: <b>MO 2 DAY 12 YR 77</b>

INSTRUMENT (9-TRACK)	<input checked="" type="checkbox"/> 1 SYSTEM <input type="checkbox"/> 2 SYSTEMS	<input checked="" type="checkbox"/> 24 & 25 - 48 <input type="checkbox"/> 1 - 48 & 49 - 96	ODDS EVENS <input type="checkbox"/> ODDS <input type="checkbox"/> EVENS	TYPE: <input type="checkbox"/> DFS III <input type="checkbox"/> DFS II <input type="checkbox"/> OTHER	<input checked="" type="checkbox"/> 9 TRACK <input type="checkbox"/> 21 TRACK	FOPMAT SEG: <b>B</b>	<input type="checkbox"/> GAPPED <input type="checkbox"/> UNGAPPED	PACKING DENSITY: (LO) <input type="checkbox"/> 356 BPI (HI) <input type="checkbox"/> 712 BPI <input type="checkbox"/> 1600 BPI		
NO. BYTES IN HEADER REC:	NO. BYTES IN RECORD ID:	NO. BYTES PER SCAN: <b>134</b>	RECORD NUMBERS:	<input checked="" type="checkbox"/> DEC. <input type="checkbox"/> OCT.	GAIN CONSTANT: <b>36</b> db	INPUT IMPEDANCE: _____ ohms.	(1) _____ (2) _____ (3) _____ (4) _____ (5) _____ (6) _____ (7) _____			
CONFIGURATION (MAG TAPE)	FIELD TRACE NOS. <b>1-18</b>	DATA CHANNEL NOS. <b>1-18</b>	AUXILIARY DATA: <b>7B 4H</b>	AUXILIARY CHANNEL NOS.: <b>3 11</b>						
PARAMETER	RECORD LENGTH: _____ sec.	SAMPLE RATE: <input type="checkbox"/> 1 ms. <input type="checkbox"/> 4 ms. <input checked="" type="checkbox"/> 2 ms.	GAIN MODE: <input type="checkbox"/> INITIAL <input type="checkbox"/> FINAL <input type="checkbox"/> MANUAL <input type="checkbox"/> OPERATE	FILTERS: <b>FREQ. OUT</b>	LO CUT _____ HZ SLOPE _____	FREQ. <b>120</b> HI CUT _____ HZ SLOPE <b>70</b>	NOTCH FILTER: <input type="checkbox"/> IN <input checked="" type="checkbox"/> OUT			
DISPLAY	MODE: <input checked="" type="checkbox"/> MAG <input type="checkbox"/> FLOAT <input type="checkbox"/> AMPLIFIER <input type="checkbox"/> DEFLOAT <input type="checkbox"/> DIRECT	INITIAL GAIN: <b>18</b> db	JRIP SENS: <b>24</b> db	POLARITY CONVENTION: _____	PRESSURE INCREASE ON GEOPHONE: _____	<input type="checkbox"/> NEGATIVE <input type="checkbox"/> POSITIVE	NUMBERS ON MAG. TAPE <input type="checkbox"/> DOWNBREAK <input type="checkbox"/> UPBREAK ON DISPLAY			
CFS	TYPE STACK: _____	GATE LENGTH: _____	RECORD REJECTION: _____	NOISE REDUCTION: _____	NOISE THRESHOLD: _____	CORR. SCALING: _____	R.C.U. NORM./ALT SW.			
SOURCE	TYPE: <input checked="" type="checkbox"/> DYNAMITE <input type="checkbox"/> VIBROSEIS <input type="checkbox"/> OTHER	PATTERN: <b>Single hole - inline</b>	NO. OF POSITIONS: _____	INLINE SPACING: _____	LATERAL SPACING: _____	STAGGER: _____	LENGTH: _____ WIDTH: _____ LATERAL OFFSET: _____			
RECEIVER	TYPE: <b>CSC-20d</b>	PATTERN: <b>Inline</b>	NO. OF ELEMENTS: <b>18</b>	INLINE SPACING: <b>12'</b>	LATERAL SPACING: _____	STAGGER: _____	LENGTH: _____ WIDTH: _____ LATERAL OFFSET: _____			
SPREAD	NO. OF GROUPS: <b>48</b>	GROUP INTERVAL: <b>330'</b>	SHOTPOINT INTERVAL: <b>1320'</b>	FOLD: <b>6</b>	DIRECTION OF PROGRESSION: <b>N → S</b>	OFFSET GROUP 1: <b>7755'</b>	OFFSET GROUP 24: <b>165'</b>	OFFSET GROUP 25: <b>165'</b>	OFFSET GROUP 48/96: <b>7755'</b>	LEADING GROUP: <b>48</b>

DIAGRAMS/MISC. INFORMATION:

SHOTPOINT	TR. 1 to 18		TR. 19 to 36		SHOT				SPREAD			REMARKS	CORR. STACK			
	REEL NO.	REC.	REEL NO.	REC.	SIZE	DEPTH	NO.	OFFSET	DIR.	CDP SWITCH	LINE GROUPS		SET UP	TR 1-18	TR 19-36	TR 37-54
1104	7511809	6111			20	6721				33	981 - 1094	4				
1105		6112			20	6722				37	991 - 1104					
1106		6113			20	6723				41	1001 - 1114					
1107		6114			20	6724				45	1011 - 1124					
1108		6115			20	6725				49	1021 - 1134					
1109		6116			20	6726				25	1031 - 1144	5	Recorder @ SP-115			
1110		6117			20	6727				29	1041 - 1154					
1111		6118			20	6728				33	1051 - 1164					
1112		6120			20	6729				37	1061 - 1174		File # 619 misfire			
1113		6121			20	6730				41	1071 - 1184					
1114		6122			20	6731				45	1081 - 1194					
1115		6123			20	6732				29	1091 - 1204	6	Recorder @ SP-120			
1116		6124			20	6733				33	1101 - 1214					
1117		6125			20	6734				37	1111 - 1224					
1118		6126			20	6735				41	1121 - 1234					
1119		6127			20	6736				45	1131 - 1244					
1120		6128			20	6737	6160	N		49	1141 - 1254		Inline offset			
1121		6129			20	6738				53	1151 - 1264					
1122		6131			20	6739				57	1161 - 1274		File # 630 misfire			
1123		6132			20	6740				61	1171 - 1284					







# LAND SEISMIC RECORDING LOG

	CLIENT: <b>Husky</b>	PROSPECT: <b>NPR-A</b>	AREA: <b>BARROW</b>	LINE NO: <b>612</b>									
PARTY NO: <b>1192</b>		INST. ENG: <b>STREFF - Windham</b>		DATE: <b>MO 2 DAY 17 YR 79</b>									
INSTRUMENT (9-TRACK)	<input type="checkbox"/> 1 SYSTEM	<input type="checkbox"/> 1-24 & 25-48	<input checked="" type="checkbox"/> ODDS & EVENS	TYPE: <input type="checkbox"/> DFS III	<input type="checkbox"/> DFS IV	<input type="checkbox"/> OTHER	<input type="checkbox"/> TRACK 21	FORMAT: <b>B</b>	<input type="checkbox"/> GAPPED	<input type="checkbox"/> UNGAPPED	PACKING DENSITY: (LO) <input type="checkbox"/> 356 BPI	(HI) <input type="checkbox"/> 712 BPI	<input type="checkbox"/> 1600 BPI
	NO. BYTES IN READER REC: <b>51</b>	NO. BYTES IN RECORD ID: _____	NO. BYTES PER SCAN: <b>134</b>	RECORD NUMBERS: <input checked="" type="checkbox"/> DEC	<input type="checkbox"/> OCT	GAIN CONSTANT: <b>36</b> db	INPUT IMPEDANCE: _____ ohms						
CONFIGURATION (MAG. TAPE)	FIELD TRACE NOS: <b>1-18</b>			AUXILIARY DATA: <b>TR 114</b>			AUXILIARY CHANNEL NOS: <b>3 4</b>						
	DATA CHANNEL NOS: <b>1-48</b>			(ON MAG TAPE)									
PARAMETER	RECORD LENGTH: <b>6</b> sec.	SAMPLE RATE: <input type="checkbox"/> 1 ms. <input type="checkbox"/> 4 ms.	GAIN MODE: <input type="checkbox"/> INITIAL	<input type="checkbox"/> MANUAL	FILTERS: <b>FREQ. OUT</b>		LO CUT HZ SLOPE: _____	FREQ. <b>128</b> HZ SLOPE: <b>70</b>	NOTCH FILTER: <input type="checkbox"/> IN		<input type="checkbox"/> OUT		
DISPLAY	MODE: <input checked="" type="checkbox"/> AGC	<input type="checkbox"/> FLOAT	<input type="checkbox"/> AMPLIFIER	INITIAL GAIN: <b>18</b> db	TRIP SENS: <b>24</b> db	POLARITY CONVENTION: _____	PRESSURE INCREASE ON GEOPHONE: <input type="checkbox"/> NEGATIVE	<input type="checkbox"/> POSITIVE	NUMBERS ON MAG. TAPE: <input type="checkbox"/> DOWNBREAK		<input type="checkbox"/> UPBREAK		
CFS I	TYPE STACK: _____	GATE LENGTH: _____	RECORD REJECTION: _____	NOISE REDUCTION: _____	NOISE THRESHOLD: _____	CORR. SCALING: _____	R.C.U. NORM./ALT SW. _____						
SOURCE	TYPE: <input type="checkbox"/> DYNAMITE	<input type="checkbox"/> VIBROSEIS	<input type="checkbox"/> OTHER	PATTERN: <b>Single hole - Taline</b>	NO. OF POSITIONS: _____	INLINE SPACING: _____	LATERAL SPACING: _____	STAGGER: _____	LENGTH: _____	WIDTH: _____	LATERAL OFFSET: _____		
RECEIVER	TYPE: <b>GSC-20d</b>	PATTERN: <b>Taline</b>	NO. OF ELEMENTS: <b>18</b>	CONNECTION: <b>Series - Parallel</b>	RESISTANCE: <b>560</b> ohms	STAGGER: _____	LENGTH: _____	WIDTH: _____	LATERAL OFFSET: _____				
SPREAD	NO. OF GROUPS: <b>48</b>	GROUP INTERVAL: <b>330'</b>	SHOTPOINT INTERVAL: <b>132.0'</b>	OFFSET GROUP 1: <b>77.85'</b>	OFFSET GROUP 24: <b>165'</b>	OFFSET GROUP 25: <b>165'</b>	FOLD: <b>6</b>	OFFSET GROUP 48/96: <b>77.85'</b>	DIRECTION OF PROGRESSION: <b>N → S</b>		LEADING GROUP: <b>48</b>		

DIAGRAMS/MISC. INFORMATION:

SHOTPOINT	TR. 1 to 15		TR. 16 to 30		SHOT		SPREAD		REMARKS	CORR. STACK			
	REEL NO.	REC.	REEL NO.	REC.	SIZE	DEPTH	NO.	OFFSET		TR. 41	TR. 42	TR. 43	TR. 44
1146	751809	663			20	16721	33	138+1 - 149+4	4				
1145		664			20	16722	37	139+1 - 150+4					
1146		665			20	16723	41	140+1 - 151+4					
1147		666			20	16724	45	141+1 - 152+4					
1148		667			20	16725	49	142+1 - 153+4					
1149		668			20	16726	29	143+1 - 154+4	5	Recorder @ SP 154			
1150		669			20	16727	33	144+1 - 155+4					
1151		670			20	16728	37	145+1 - 156+4					
1152		671			20	16729	41	146+1 - 157+4					
1153		672			20	16730	45	147+1 - 158+4					
1154		673			20	16731	49	148+1 - 159+4					
1155		674			20	16732	29	149+1 - 160+4	6	Recorder @ SP 160			
1156		675			20	16733	33	150+1 - 161+4					
1157		676			20	16734	37	151+1 - 162+4					
1158		677			20	16735	41	152+1 - 163+4		offset - 150' West			
1159		678			20	16736	45	153+1 - 164+4					
1160		679			20	16737	49	154+1 - 165+4					
1161		680			20	16738	53	155+1 - 166+4					
1162		682			20	16739	57	156+1 - 167+4		File # 681 misc. re			
1163		683			20	16740	61	157+1 - 168+4					

# LAND SEISMIC RECORDING LOG

*44.5 Hours*

	CLIENT: <u>Husky</u>	PROSPECT: <u>NPR-A</u>	AREA: <u>Balloon</u>	LINE NO.: <u>612</u>					
PARTY NO.: <u>1189</u>	INST. ENG.: <u>STREFF - Windham</u>	DATE: <u>NO 2 DAY 16 YR 79</u>							
INSTRUMENT (9-TRACK)	<input type="checkbox"/> 1 SYSTEM <input type="checkbox"/> 2 SYSTEMS	<input type="checkbox"/> 1-24 & 25-48 <input type="checkbox"/> 1-48 & 49-96	ODDS & EVENS: <input type="checkbox"/>	TYPE: <input type="checkbox"/> DFS III <input type="checkbox"/> DFS IV <input type="checkbox"/> OTHER	<input type="checkbox"/> TRACK <input type="checkbox"/> 21 TRACK	FORMAT: <u>B</u>	<input type="checkbox"/> GAPPED <input type="checkbox"/> UNGAPPED	PACKING DENSITY: (L) <input type="checkbox"/> 356 BPI <input type="checkbox"/> 800 BPI	(H) <input type="checkbox"/> 712 BPI <input type="checkbox"/> 1600 BPI
	NO. BYTES IN HEADER REC.:	NO. BYTES IN RECORD ID:	NO. BYTES PER SCAN: <u>134</u>	RECORD NUMBERS: <input type="checkbox"/> DEC. <input type="checkbox"/> OCT.	GAIN CONSTANT: <u>36</u> db	INPUT IMPEDANCE: _____ ohms.			
CONFIGURATION (MAG TAPE)	FIELD TRACE NOS.: <u>1-48</u>			AUXILIARY DATA: <u>78 4H</u>					
	DATA CHANNEL NOS.: <u>1-48</u> (ON MAG TAPE)			AUXILIARY CHANNEL NOS.: <u>3 4</u>					
PARAMETER	RECORD LENGTH: <u>6</u> sec.	SAMPLE RATE: <input type="checkbox"/> 1 ms. <input type="checkbox"/> 4 ms.	GAIN MODE: <input type="checkbox"/> INITIAL <input type="checkbox"/> MANUAL <input checked="" type="checkbox"/> TRIP	FILTERS: _____	LO CUT HZ SLOPE: _____	HI CUT HZ SLOPE: _____	NOTCH FILTER: <input type="checkbox"/> IN <input type="checkbox"/> OUT		
DISPLAY	MODE: <input checked="" type="checkbox"/> A-B-C <input type="checkbox"/> FLOAT <input type="checkbox"/> AMPLIFIER <input type="checkbox"/> DEFLOAT <input type="checkbox"/> DIRECT	INITIAL GAIN: <u>18</u> db	TRIP SENS: <u>24</u> db	POLARITY CONVENTION: _____	PRESSURE INCREASE ON GEOPHONE: _____	<input type="checkbox"/> NEGATIVE <input type="checkbox"/> POSITIVE	NUMBERS ON MAG. TAPE: _____	<input type="checkbox"/> DOWNBREAK <input type="checkbox"/> UPBREAK	ON DISPLAY
CFS I	TYPE STACK: _____	GATE LENGTH: _____	RECORD REJECTION: _____	NOISE REDUCTION: _____	NOISE THRESHOLD: _____	CORR. SCALING: _____	R.C.U. NORM./ALT SW.		
SOURCE	TYPE: <input checked="" type="checkbox"/> DYNAMITE <input type="checkbox"/> VIBROSEIS <input type="checkbox"/> OTHER	PATTERN: <u>Single hole - In line</u>	NO. OF POSITIONS: _____	INLINE SPACING: _____	LATERAL SPACING: _____	STAGGER: _____	LENGTH: _____	WIDTH: _____	LATERAL OFFSET: _____
RECEIVER	TYPE: <u>GSC-20d</u>	PATTERN: <u>In line</u>	NO. OF ELEMENTS: <u>18</u>	INLINE SPACING: <u>12'</u>	LATERAL SPACING: _____	STAGGER: _____	LENGTH: _____	WIDTH: _____	LATERAL OFFSET: _____
SPREAD	CONNECTION: <u>Series-Parallel</u>	RESISTANCE: <u>560</u> ohms	STAGGER: _____	LENGTH: _____	WIDTH: _____	LATERAL OFFSET: _____			
	NO. OF GROUPS: <u>48</u>	GROUP INTERVAL: <u>330'</u>	SHOTPOINT INTERVAL: <u>1320'</u>	FOLD: <u>6</u>	DIRECTION OF PROGRESSION: <u>A2 → S</u>				
	OFFSET GROUP 1: <u>775'</u>	OFFSET GROUP 2: <u>165'</u>	OFFSET GROUP 2: <u>165'</u>	OFFSET GROUP 48: <u>775'</u>	LEADING GROUP: <u>4.8</u>				

DIAGRAMS/MISC. INFORMATION: 159 159 163 SP164 165 169 170 File # 684 → 692 Daily Tests  
AAAAA ← PPPPA ← PPPPA ← PPPPA ← PPPPA ← PPPPA ← PPPPA ← PPPPA ←  
CTR-1 TR-20 CTR-25 TR-48 File # 693 - Test TB

SHOTPOINT	REEL NO.	REC.	TR.	SIZE	DEPTH	NO.	OFFSET	DIR.	CDP SWITCH	LINE GROUPS	SET UP	REMARKS	CORR. STACK		
													TR 1-48	TR 49-96	
11644	7151	1889	694	RD	67	1			29	158+1 - 169+4	1	Recorder @ SP-169			
11645			695	RD	67	2			33	159+1 - 170+4					
11646			696	RD	67	3			37	160+1 - 171+4					
11647			697	RD	67	4			41	161+1 - 172+4					
11648			698	RD	67	5			45	162+1 - 173+4					
11649			699	RD	67	6			49	163+1 - 174+4					
11710			7100	RD	67	7	1100	Right	53	164+1 - 175+4					
11711			7101	RD	67	8			57	165+1 - 176+4			173+4 Dead		
11712			7102	RD	67	9			61	166+1 - 177+4					
11713	7151	1890	7104	RD	67	10			39	167+1 - 178+4	2		Recorder @ SP-178 File # 703 Nancy Rec		
11714			7105	RD	67	11			33	168+1 - 179+4					
11715			7106	RD	67	12			37	169+1 - 180+4					
11716			7107	RD	67	13			41	170+1 - 181+4					
11717			7108	RD	67	14			39	171+1 - 182+4	3		Recorder @ SP-		
11718			7109	RD	67	15			33	172+1 - 183+4					
11719			7110	RD	67	16	300	Right	37	173+1 - 184+4					
11810			7111	RD	67	17			41	174+1 - 185+4					
11811			7112	RD	67	18			45	175+1 - 186+4					
11812			7113	RD	67	19			49	176+1 - 187+4					
11813			7114	RD	67	20			53	177+1 - 188+4					

# LAND SEISMIC RECORDING LOG

CLIENT: <b>Husky</b>		PROSPECT: <b>APR-A</b>		AREA: <b>Barrow</b>		LINE NO: <b>612</b>	
PARTY NO: <b>1182</b>		INST. ENG: <b>STREFF-Windham</b>		DATE: <b>MO. 2 DAY 14 YR 79</b>			
INSTRUMENT: <input checked="" type="checkbox"/> 1 SYSTEM <input type="checkbox"/> 2 SYSTEMS		ODDS EVENS: <input type="checkbox"/> 1-24 & 25-48 <input type="checkbox"/> 1-48 & 49-96		TYPE: <input type="checkbox"/> DFS II <input type="checkbox"/> DFS III <input type="checkbox"/> OTHER		9 TRACK <input type="checkbox"/> 21 TRACK	
NO. BYTES IN HEADER REC: _____		NO. BYTES IN RECORD ID: _____		NO. BYTES PER SCAN: <b>134</b>		RECORD NUMBERS: <input type="checkbox"/> DEC. <input type="checkbox"/> OCT.	
CONFIGURATION (MAG TAPE): <b>9 TRACK</b>		FIELD TRACE NOS: <b>9 TRACK</b>		DATA CHANNEL NOS: <b>1-48</b>		AUXILIARY DATA: <b>78 4H</b>	
PARAMETER: <b>201</b>		RECORD LENGTH: _____ sec.		SAMPLE RATE: <input type="checkbox"/> 1 ms. <input type="checkbox"/> 4 ms. <input type="checkbox"/> 2 ms.		GAIN MODE: <input type="checkbox"/> INITIAL <input type="checkbox"/> FINAL <input type="checkbox"/> MANUAL <input type="checkbox"/> OPERATE	
DISPLAY: <input checked="" type="checkbox"/> MAG <input type="checkbox"/> FLOAT <input type="checkbox"/> DENOISE <input type="checkbox"/> DIRECT		INITIAL GAIN: <b>18</b> db		TRIP SENS: <b>20</b> db		FILTERS: <b>OUT</b> LO CUT HZ SLOPE _____	
CFS I: _____		GATE LENGTH: _____		RECORD REJECTION: _____		NOISE REDUCTION: _____ NOISE THRESHOLD: _____	
SOURCE: <input type="checkbox"/> DYNAMITE <input type="checkbox"/> VIBROSEIS <input type="checkbox"/> OTHER		PATTERN: <b>Single hole - Inline</b>		NO. OF POSITIONS: _____		LATERAL SPACING: _____	
RECEIVER: <b>GSC-20d</b>		CONNECTION: <b>Series-Parallel</b>		RESISTANCE: <b>560</b> ohms		STAGGER: _____ LENGTH: _____	
SPREAD: <b>49</b>		GROUP INTERVAL: <b>330'</b>		SHOTPOINT INTERVAL: <b>1320'</b>		FOLD: <b>6</b>	
OFFSET GROUP 1: <b>7755'</b>		OFFSET GROUP 2: <b>165'</b>		OFFSET GROUP 3: <b>165'</b>		OFFSET GROUP 4: <b>7755'</b>	

DIAGRAMS/MISC. INFORMATION:

SHOTPOINT	TR. 1 to 16		TR. 17 to 32		SHOT		SPREAD		REMARKS	CORR. STACK			
	REEL NO.	REC.	REEL NO.	REC.	SIZE	DEPTH	NO.	OFFSET		DIR.	CDP SWITCH	LINE GROUPS	SET UP
184	75118910	7215			20	16721	11	39	17811 - 18944	4	Recorder @ SP-189		
185		7216			20	16722	11	33	17941 - 19044				
186		7217			20	16723	11	37	18041 - 19144				
187		7218			20	16724	11	41	18141 - 19244				
188		7219			20	16725	11	45	18241 - 19344				
189		7220			20	16726	11	49	18341 - 19444				
190		7221			20	16727	11	53	18441 - 19544				
191		7222			20	16728	11	25	18541 - 19644	5	Recorder @ SP-190		
192		7223			20	16729	11	29	18641 - 19744				
193		7224			20	16730	11	33	18741 - 19844				
194		7225			20	16731	11	37	18841 - 19944				
195		7226			20	16732	200 left	41	18941 - 20044				
196		7227			20	16733	11	45	19041 - 20144				
197		7228			20	16734	11	49	19141 - 20244				
198		7229			20	16735	11	53	19241 - T-4				
199		7230			20	16736	11	57	19341 - T-8				
200		7231			20	16737	11	61	19441 - T-12				
201		7232			20	16738	11	65	19541 - T-16				
202		7233			20	16739	11	69	19641 - T-20				
203		7234			20	16740	11	73	19741 - T-24				

Picking up Line