




# ANN'S Copy

Recording Hrs - 15.0

## LAND SEISMIC RECORDING LOG

	CLIENT: <u>Husky</u>	PROSPECT: <u>NPA-A</u>	AREA: <u>Barrow</u>	LINE NO.: <u>610</u>											
	PARTY NO.: <u>1182</u>	INST. ENG.: <u>Streiff-Windham</u>		DATE: <u>1 DAY 30.79</u>											
INSTRUMENT (9-TRACK)	<input checked="" type="checkbox"/> SYSTEM <input checked="" type="checkbox"/> 2 SYSTEMS	<input checked="" type="checkbox"/> 1-24 & 25-48 <input checked="" type="checkbox"/> 1-48 & 49-96	ODDS EVENTS	TYPE: <input type="checkbox"/> DFS III <input type="checkbox"/> DFS IX <input type="checkbox"/> OTHER	<input type="checkbox"/> TRACK <input type="checkbox"/> 21 TRACK	FORMAT: <u>SEC</u> <input type="checkbox"/> GAPPED <input type="checkbox"/> UNGAPPED	PACKING DENSITY: (L0) <input type="checkbox"/> 354 BPI (H1) <input type="checkbox"/> 772 BPI <input type="checkbox"/> 800 BPI <input type="checkbox"/> 1600 BPI								
	NO. BYTES IN HEADER REC.	NO. BYTES IN RECORD ID	NO. BYTES PER SCAN:	RECORD NUMBERS:	<input type="checkbox"/> DEC. <input type="checkbox"/> OCT	GAIN CONSTANT: (1) (2) (3) (4) (5) (6) (7)	INPUT IMPEDANCE: ohms								
CONFIGURATION (MAG TAPE)	FIELD TRACE NOS.: <u>1-48</u>			AUXILIARY DATA:			AUXILIARY CHANNEL NOS.:								
PARAMETER	RECORD LENGTH: <u>6</u> sec.	SAMPLE RATE: <input checked="" type="checkbox"/> 1 sec. <input type="checkbox"/> 4 sec.	GAIN MODE: <input type="checkbox"/> INITIAL <input type="checkbox"/> MANUAL <input type="checkbox"/> OPERATE	FILTERS: <input type="checkbox"/> HI CUT <input type="checkbox"/> HI Z SLOPE		<input type="checkbox"/> NOTCH FILTER: <input type="checkbox"/> IN <input type="checkbox"/> OFF <input type="checkbox"/> NEGATIVE <input type="checkbox"/> POSITIVE } NUMBERS ON MAG. TAPE <input type="checkbox"/> UPBREAK <input type="checkbox"/> DOWNBREAK } ON DISPLAY									
DISPLAY	<input checked="" type="checkbox"/> AGC <input type="checkbox"/> FLOAT <input type="checkbox"/> AMPLIFIER <input type="checkbox"/> DIRECT	INITIAL GAIN: <u>36</u> db	TRIP SENS.: <u>5</u> db	PRESSURE INCREASE ON GEOPHONE:		CORR. SCALING: R.C.H. NORM/ALT SW.									
CFS I	TYPE TRACK:	GATE LENGTH:	RECORD REJECTION:	NOISE REDUCTION:		NOISE THRESHOLD:									
SOURCE	TYPE: <input type="checkbox"/> SPINAMITE <input type="checkbox"/> VIBROSEIS <input type="checkbox"/> OTHER	PATTERN: <u>1 inline/hole</u>	NO. OF POSITIONS:	INLINE SPACING:	LATERAL SPACING:	STAGGER:	LENGTH: WIDTH: LATERAL OFFSET:								
RECEIVER	TYPE: <u>20.0</u>	PATTERN: <u>1 inline</u>	NO. OF ELEMENTS: <u>18</u>	INLINE SPACING: <u>12</u>	LATERAL SPACING:	STAGGER:	LENGTH: WIDTH: LATERAL OFFSET:								
SPREAD	CONNECTION: <u>Series - Parallel</u>	RESISTANCE: <u>500</u> ohms	STAGGER:	LENGTH:	WIDTH:	PHASE COMP.:	DIRECTION OF PROGRESSION: <u>South</u>								
	NO. OF GROUPS: <u>48</u>	GROUP INTERVAL: <u>220</u>	SHOTPOINT INTERVAL: <u>880</u>	FOLD: <u>6</u>	OFFSET GROUP 48/96: <u>5170</u>		LEADING GROUP: <u>48</u>								
	OFFSET GROUP 1: <u>5170</u>	OFFSET GROUP 24: <u>110</u>	OFFSET GROUP 25: <u>110</u>	OFFSET GROUP 48/96: <u>5170</u>			LEADING GROUP: <u>48</u>								
DIAGRAMS/MISC. INFORMATION:															
															
<div style="text-align: right;"> <span style="border: 1px solid black; border-radius: 50%; padding: 5px;">#1-8 4cst5</span>  <span style="border: 1px solid black; border-radius: 50%; padding: 5px;">#9 - 1cst timebreak</span> </div>															
SHOTPOINT	TR	REC.	TR	REC.	SIZE	DEPTH	NO. OFFSET	DIB.	CDP SWITCH	SPREAD	REMARKS	CORR. TRACE			
	REEL NO.		REEL NO.							LINE GROUPS		TR 1-48	TR 49-96		
1	75	21	11	4	20	167	11		49	TS.21 - 11.4	1				
2	75	21	11	4	20	167	12		49	TS.21 - 11.4					
3	75	21	11	4	20	167	13		49	TS.21 - 11.4					
4	75	21	11	4	20	167	14		49	TS.21 - 11.4					
5	75	21	11	4	20	167	15		49	TS.21 - 11.4					
6	75	21	11	4	20	167	16		49	TS.21 - 11.4					
7	75	21	11	4	20	167	17		53	2+1 - 12+4					
8	75	21	11	4	20	167	18		57	2+1 - 13+4					
9	75	21	11	4	20	167	19		61	3+1 - 14+4					
10	75	21	11	4	20	167	20		65	4+1 - 15+4					
11	75	21	11	4	20	167	21		69	5+1 - 16+4					
12	75	21	11	4	20	167	22		73	6+1 - 17+4					
13	75	21	11	4	20	167	23		77	7+1 - 18+4					
14	75	21	11	4	20	167	24		81	8+1 - 19+4					
15	75	21	11	4	20	167	25		85	9+1 - 20+4					
16	75	21	11	4	20	167	26		87	10+1 - 21+4					
17	75	21	11	4	20	167	27		93	11+1 - 22+4					
18	75	21	11	4	20	167	28		97	12+1 - 23+4					
19	75	21	11	4	20	167	29		17	13+1 - 24+4	2				
20	75	21	11	4	20	167	30		21	14+1 - 25+4					

(\* 236 S/P's)

1111

# LAND SEISMIC RECORDING LOG

CLIENT: <b>Husky</b>		PROSPECT: <b>NPR-A</b>		AREA: <b>Barrow</b>		LINE NO.: <b>616</b>					
PARTY NO.: <b>1182</b>		INST. END: <b>Staff - Nindham</b>		DATE: <b>MO 1 DAY 30 YR 77</b>							
INSTRUMENT (9-TRACK) <input type="checkbox"/> 1 SYSTEM <input type="checkbox"/> 2 SYSTEMS <input checked="" type="checkbox"/> 1-24 & 25-48 <input type="checkbox"/> 1-48 & 49-96 <input type="checkbox"/> ODDS EVENS TYPE: <input type="checkbox"/> DPS III <input type="checkbox"/> DFS IX <input type="checkbox"/> D-9 TRACK <input type="checkbox"/> 21 TRACK FORMAT: <b>B</b> <input type="checkbox"/> GAPPED <input type="checkbox"/> UNGAPPED PACKING DENSITY: (L) <input type="checkbox"/> 336 BPI <input type="checkbox"/> 600 BPI (H) <input type="checkbox"/> 712 BPI <input type="checkbox"/> 1600 BPI		NO. BYTES IN HEADER REC:		NO. BYTES IN RECORD ID:		RECORD NUMBERS: <b>DEC</b> <input type="checkbox"/> OCT GAIN CONSTANT: <b>36</b> INPUT IMPEDANCE: <b>20K</b> ohms					
CONFIGURATION (MAG TAPE) FIELD TRACE NOS.: <b>1-48</b> DATA CHANNEL NOS.: <b>1-48</b> (ON MAG TAPE)		AUXILIARY DATA: AUXILIARY CHANNEL NOS.:		FILTERS: FREQ: <b>128</b> HI CUT HZ SLOPE: <b>70</b> NOTCH FILTER: <input type="checkbox"/> IN <input type="checkbox"/> OUT							
PARAMETER RECORD LENGTH: <b>6</b> sec. SAMPLE RATE: <input type="checkbox"/> 1 ms <input type="checkbox"/> 4 ms <input checked="" type="checkbox"/> 10 ms <input type="checkbox"/> 20 ms		GAIN MODE: <input type="checkbox"/> INITIAL <input type="checkbox"/> FINAL <input type="checkbox"/> MANUAL <input type="checkbox"/> OPERATE		TRIP SENS: <b>5</b> ohms		POLARITY CONVENTION: <input type="checkbox"/> NEGATIVE <input type="checkbox"/> POSITIVE		PRESSURE INCREASE ON GEOPHONE: <input type="checkbox"/> NEGATIVE <input type="checkbox"/> POSITIVE		NUMBERS ON MAG. TAPE: <input type="checkbox"/> DOWNBREAK <input type="checkbox"/> UPBREAK	
DISPLAY MODE: <input type="checkbox"/> AGC <input type="checkbox"/> FLOAT <input type="checkbox"/> DEFOAT <input type="checkbox"/> AMPLIFIER <input type="checkbox"/> DIRECT		INITIAL GAIN: <b>18</b> db		GATE LENGTH:		NOISE REDUCTION:		NOISE THRESHOLD:		CORR. SCALING:	
CFS I TYPE STACK:		PATTERN: <b>1 hole / inline</b>		NO. OF POSITIONS: <b>1</b>		INLINE SPACING:		LATERAL SPACING:		STAAGGER:	
SOURCE TYPE: <input checked="" type="checkbox"/> DYNAMITE <input type="checkbox"/> VIBROSEIS <input type="checkbox"/> OTHER		CHOI/ HOLE: <b>2016</b> HOLE DEPTH: <b>75</b>		SWEEP POSITION:		SWEEP START:		SWEEP END:		LENGTH:	
RECEIVER TYPE: <b>20-D</b>		PATTERN: <b>INLINE</b>		NO. OF ELEMENTS: <b>18</b>		INLINE SPACING: <b>12'</b>		LATERAL SPACING:		LATERAL OFFSET:	
CONNECTION: <b>Series-Parallel</b>		RESISTANCE: <b>500</b> ohms		STAAGGER:		LENGTH:		WIDTH:		LATERAL OFFSET:	
SPREAD NO. OF GROUPS: <b>48</b>		GROUP INTERVAL: <b>220</b>		SHOTPOINT INTERVAL: <b>820</b>		FOLD: <b>6</b>		DIRECTION OF PROGRESSION: <b>SOUTH</b>			
OFFSET GROUP 1: <b>5170</b>		OFFSET GROUP 2: <b>110</b>		OFFSET GROUP 3: <b>110</b>		OFFSET GROUP 4: <b>5170</b>		LEADING GROUP: <b>48</b>			

DIAGRAMS/MISC. INFORMATION:

SHOTPOINT	TR 10		TR 10		SHOT		SPREAD		REMARKS	CORR. STACK			
	REEL NO.	REC.	REEL NO.	REC.	SIZE	DEPTH	NO.	OFFSET		TR 10	TR 10	TR 10	TR 10
21	21	121	21	121	20	167	21	25	15+1 - 26+4	2			
22	21	122	21	122	20	167	22	29	16+1 - 27+4				
23	21	123	21	123	20	167	23	33	17+1 - 28+4				
24	21	124	21	124	20	167	24	37	18+1 - 29+4				
25	21	125	21	125	20	167	25	41	19+1 - 30+4				
26	21	126	21	126	20	167	26	45	20+1 - 31+4				
27	21	127	21	127	20	167	27	49	21+1 - 32+4				
28	21	128	21	128	20	167	28	53	22+1 - 33+4				
29	21	129	21	129	20	167	29	57	23+1 - 34+4				
30	21	130	21	130	20	167	30	61	24+1 - 35+4				
31	21	131	21	131	20	167	31	65	25+1 - 36+4				
32	21	132	21	132	20	167	32	69	26+1 - 37+4				
33	21	133	21	133	20	167	33	73	27+1 - 38+4				
34	21	134	21	134	20	167	34	77	28+1 - 39+4				
35	21	135	21	135	20	167	35	81	29+1 - 40+4	3	Recorder @ 40+2 / 40+3		
36	21	136	21	136	20	167	36	85	30+1 - 41+4				
37	21	137	21	137	20	167	37	89	31+1 - 42+4				
38	21	138	21	138	20	167	38	93	32+1 - 43+4				
39	21	139	21	139	20	167	39	97	33+1 - 44+4				
40	21	140	21	140	20	167	40	101	34+1 - 45+4				

# LAND SEISMIC RECORDING LOG

CLIENT: <u>Husky</u>		PROSPECT: <u>NPR-A</u>		AREA: <u>Barrow</u>		LINE NO: <u>616</u>											
PARTY NO: <u>1182</u>		INST. ENG: <u>Stroff - Windham</u>		DATE: <u>NOV 1 DAY 30 YR 79</u>													
INSTRUMENT (9-TRACK)		<input checked="" type="checkbox"/> SYSTEM <input type="checkbox"/> 2 SYSTEMS		<input type="checkbox"/> 1-24 & 25-48 <input type="checkbox"/> 1-48 & 49-96		ODDS <input type="checkbox"/> EVENTS		TYPE: <input type="checkbox"/> DFS III <input type="checkbox"/> DFS II <input type="checkbox"/> OTHER		<input type="checkbox"/> TRACK <input type="checkbox"/> 2 TRACK		FOPMAT: <u>A</u>		<input type="checkbox"/> CAPPED <input type="checkbox"/> UNCAPPED		PACKING DENSITY: (L) <input type="checkbox"/> 350 BPI (M) <input type="checkbox"/> 712 BPI (H) <input type="checkbox"/> 1400 BPI	
NO. BYTES IN HEADER REC:		NO. BYTES IN RECORD ID:		NO. BYTES PER SCAN:		RECORD NUMBERS:		<input checked="" type="checkbox"/> DEC <input type="checkbox"/> OCT		GAIN CONSTANT: <u>30</u> db		INPUT IMPEDANCE: <u>20K</u> ohms					
CONFIGURATION (MAG TAPE)		FIELD TRACE NOS.: <u>1-48</u>		DATA CHANNEL NOS.: <u>1-48</u>		(ON MAG TAPE)		AUXILIARY DATA:		AUXILIARY CHANNEL NOS.:							
PARAMETER		RECORD LENGTH: <u>6</u> sec.		SAMPLE RATE: <input type="checkbox"/> 1 sec. <input type="checkbox"/> 4 sec.		GAIN MODE: <input type="checkbox"/> INITIAL <input type="checkbox"/> MANUAL <input type="checkbox"/> OPERATE		FILTERS: FREQ. _____		LO CUT HZ SLOPE _____		HI CUT HZ SLOPE <u>70</u>		NOTCH FILTER: <input type="checkbox"/> IN <input type="checkbox"/> OUT			
DISPLAY		<input checked="" type="checkbox"/> AGC <input type="checkbox"/> FLOAT <input type="checkbox"/> AMPLIFIER <input type="checkbox"/> DIRECT		INITIAL GAIN: <u>18</u> db		TRIP SENS: <u>5</u> db		POLARITY CONVENTION: _____		PRESSURE INCREASE ON GEOPHONE: _____		<input type="checkbox"/> NEGATIVE } NUMBERS ON MAG. TAPE <input type="checkbox"/> POSITIVE }		<input type="checkbox"/> DOWNBREAK } ON DISPLAY <input type="checkbox"/> UPBREAK }			
CFS I		TYPE STACK:		GATE LENGTH:		RECORD REJECTION:		NOISE REDUCTION:		NOISE THRESHOLD:		CORR SCALING:		C.C.U. NORM/ALT SW:			
SOURCE		<input type="checkbox"/> DYNAMITE <input type="checkbox"/> VIBROSEIS <input type="checkbox"/> OTHER		PATTERN: <u>inline/hole</u>		NO. OF POSITIONS:		INLINE SPACING:		LATERAL SPACING:		STAGGER:		LENGTH:			
RECEIVER		TYPE: <u>200</u>		PATTERN: <u>inline</u>		NO. OF ELEMENTS: <u>18</u>		INLINE SPACING: <u>12</u>		LATERAL SPACING:		STAGGER:		LENGTH:			
SPREAD		CONNECTION: <u>series parallel</u>		RESISTANCE: <u>560</u> ohms		STAGGER:		LENGTH:		WIDTH:		LATERAL OFFSET:					
		NO. OF GROUPS: <u>48</u>		GROUP INTERVAL: <u>220</u>		SHOTPOINT INTERVAL: <u>880</u>		FOLD: <u>6</u>		DIRECTION OF PROGRESSION: <u>50+1</u>		LEADING GROUP: <u>48</u>					
		OFFSET GROUP 1: <u>5170</u>		OFFSET GROUP 29: <u>110</u>		OFFSET GROUP 25: <u>110</u>		OFFSET GROUP 48/96: <u>5170</u>									

DIAGRAMS/MISC. INFORMATION:

SHOTPOINT	TR _____ to _____		TR _____ to _____		SHOT				SPREAD				REMARKS	CORR STAGE			
	REEL NO.	REC.	REEL NO.	REC.	SIZE	DEPTH	NO.	OFFSET	DIR.	CDP SWITCH	LINE GROUPS			REF	TR 1-24	TR 25-48	TR 49-72
141	3511	1519			20	167	41	11		51	35+1	-46+4	3				
142		1519			20	167	42	11		55	36+1	-47+4					
143		1516			20	167	43	11		59	37+1	-48+4					
144		1517			20	167	44	11		62	38+1	-49+4					
145		1519			20	167	45	11		67	39+1	-50+4					
146		1610			20	167	46	11		71	40+1	-51+4					
147		1611			20	167	47	11		75	41+1	-52+4					
148		1612			20	167	48	11		79	42+1	-53+4					
149		1613			20	167	49	11		23	43+1	-54+4	4	Recorder @ 55+2/55+3			
150		1614			20	167	50	11		27	44+1	-55+4					
151		1615			20	167	51	11		31	45+1	-56+4					
152		1616			20	167	52	11		35	46+1	-57+4					
153		1617			20	167	53	11		39	47+1	-58+4					
154		1618			20	167	54	11		43	48+1	-59+4					
155		1619			20	167	55	11		47	49+1	-60+4					
156		170			20	167	56	330	S	51	50+1	-61+4					
157		171			20	167	57	11		55	51+1	-62+4					
158		172			20	167	58	11		59	52+1	-63+4					
159		173			20	167	59	11		63	53+1	-64+4					
160		175			20	167	60	11		67	54+1	-65+4					
61		76			20	67	61			71	55+1	-66+4					
62		77			20	67	62			75	56+1	-67+4					

\* 58-NG \*

# 74 - NG \*

67+4 - dead

Recording Hrs. 15.0

### LAND SEISMIC RECORDING LOG

CLIENT: <u>Hushy</u>		PROSPECT: <u>NPR-A</u>		AREA: <u>Dutton</u>		LINE NO.: <u>616</u>							
PARTY NO.: <u>1182</u>		INST. ENG.: <u>Staff - Wadhwa</u>		DATE: <u>1 DAY 31 YE 79</u>									
INSTRUMENT <input type="checkbox"/> 1 SYSTEM <input checked="" type="checkbox"/> 2 SYSTEMS		<input checked="" type="checkbox"/> 1-24 & 25-48 <input type="checkbox"/> 1-48 & 49-96		ODDS EVENS <input type="checkbox"/> ODDS <input type="checkbox"/> EVENS		TYPE: <input type="checkbox"/> DFS III <input type="checkbox"/> DFS II <input type="checkbox"/> OTHER		<input checked="" type="checkbox"/> 1 TRACK <input type="checkbox"/> 2 TRACK		FOPMAT: <u>B</u> <input type="checkbox"/> GAPPED <input type="checkbox"/> UNGAPPED		PACKING DENSITY: (L) <input type="checkbox"/> 356 BPI <input type="checkbox"/> 800 BPI (H) <input type="checkbox"/> 712 BPI <input type="checkbox"/> 4000 BPI	
(P-TRACK) NO. BYTES IN HEADER REC.		NO. BYTES IN RECORD ID.		NO. BYTES PER SCAN.		RECORD NUMBERS: <input checked="" type="checkbox"/> DEC. <input type="checkbox"/> OCT		GAIN CONSTANT: <u>3.6</u> db		INPUT IMPEDANCE: <u>20K</u> ohms			
CONFIGURATION (MAG TAPE)		FIELD TRACE NOS.: <u>1-48</u>		DATA CHANNEL NOS.: <u>1-48</u> (ON MAG TAPE)		AUXILIARY DATA:		AUXILIARY CHANNEL NOS.:					
PARAMETER		RECORD LENGTH: <u>6</u> sec.		SAMPLE RATE: <input type="checkbox"/> 1 sec. <input type="checkbox"/> 4 sec.		GAIN MODE: <input type="checkbox"/> INITIAL <input type="checkbox"/> MANUAL <input type="checkbox"/> OPERATE		FILTERS: FREQ. <u>128</u>		LO CUT HZ SLOPE <u>70</u>		HI CUT HZ SLOPE <u>70</u>	
DISPLAY		MODE: <input checked="" type="checkbox"/> RGC <input type="checkbox"/> FLOAT <input type="checkbox"/> AMPLIFIER <input type="checkbox"/> DIRECT		INITIAL GAIN: <u>18</u> db		TRIP SENS.: <u>5</u> db		POLARITY CONVENTION: <input checked="" type="checkbox"/> NEGATIVE <input type="checkbox"/> POSITIVE		PRESSURE INCREASE ON GEOPHONE:		NUMBERS ON MAG TAPE: <input type="checkbox"/> DOWNBREAK <input type="checkbox"/> UPBREAK	
CFS I		TYPE: <input type="checkbox"/> STACK		GATE LENGTH:		RECORD REJECTION:		NOISE REDUCTION:		NOISE THRESHOLD:		CORR. SCALING:	
SOURCE		TYPE: <input checked="" type="checkbox"/> DYNAMITE <input type="checkbox"/> VIBROSEIS <input type="checkbox"/> OTHER		PATTERN: <u>1 inline / 1 hole</u>		NO. OF POSITIONS:		INLINE SPACING:		LATERAL SPACING:		STAGGER:	
RECEIVER		TYPE: <u>80-0</u>		PATTERN: <u>1 inline</u>		NO. OF ELEMENTS: <u>18</u>		INLINE SPACING: <u>12</u>		LATERAL SPACING:		STAGGER:	
SPREAD		CONNECTION: <u>Series-Parallel</u>		RESISTANCE: <u>560</u> ohms		STAGGER:		LENGTH:		WIDTH:		LATERAL OFFSET:	
NO. OF GROUPS: <u>48</u>		GROUP INTERVAL: <u>220</u>		SHOTPOINT INTERVAL: <u>880</u>		FOLD: <u>6</u>		DIRECTION OF PROGRESSION: <u>South</u>		LEADING GROUP: <u>48</u>		OFFSET GROUP 1: <u>5170</u>	
OFFSET GROUP 2: <u>110</u>		OFFSET GROUP 3: <u>110</u>		OFFSET GROUP 4: <u>110</u>		OFFSET GROUP 5: <u>110</u>		OFFSET GROUP 6: <u>110</u>		OFFSET GROUP 7: <u>110</u>		OFFSET GROUP 8: <u>110</u>	

DIAGRAMS/MISC. INFORMATION:

$\begin{matrix} 571 \\ \swarrow \\ \text{TR#1} \\ \searrow \\ 78+25 \end{matrix}$ 
 $\begin{matrix} 524 \text{ SPTS } 631 \\ \swarrow \\ \text{TR#2} \\ \searrow \\ 78+25 \end{matrix}$ 
 $\begin{matrix} 684 \\ \swarrow \\ \text{TR#3} \\ \searrow \\ 78+25 \end{matrix}$ 
 $\begin{matrix} 684 \\ \swarrow \\ \text{TR#4} \\ \searrow \\ 78+25 \end{matrix}$

\* 78-85 tests  
 #86 test time break

SHOTPOINT	TR. NO.		TR. NO.		SHOT		SPREAD		REMARKS	CORR. SCALE					
	REEL NO.	REC.	REEL NO.	REC.	SIZE	DEPTH	NO.	OFFSET		DIR.	CDP SWITCH	LINE GROUPS	TR. NO.	REC.	TR. NO.
163	75	188	187		20	167	1	31	57+1	68+4	1				
164		188			20	167	2	35	58+1	69+4					
165		187			20	167	3	39	59+1	70+4					
166		188			20	167	4	43	60+1	71+4					
167		191			20	167	5	47	61+1	72+4					
168		192			20	167	6	51	62+1	73+4					
169		193			20	167	7	55	63+1	74+4					
170		194			20	167	8	59	64+1	75+4					
171		195			20	167	9	63	65+1	76+4					
172		196			20	167	10	67	66+1	77+4					
173		197			20	167	11	71	67+1	78+4					
174		198			20	167	12	75	68+1	79+4					
175		199			20	167	13	79	69+1	80+4					
176		100			20	167	14	83	70+1	81+4					
177		101			20	167	15	87	71+1	82+4					
178		102			20	167	16	91	72+1	83+4					
179		103			20	167	17	95	73+1	84+4					
180		104			20	167	18	99	74+1	85+4	2				
181		105			20	167	19	31	75+1	86+4					
182		106			20	167	20	35	76+1	87+4					

# LAND SEISMIC RECORDING LOG

	CLIENT: <u>Husk Y</u>	PROSPECT: <u>NPR-A</u>	AREA: <u>Barrow</u>	LINE NO: <u>616</u>						
	PARTY NO: <u>1182</u>	INST. ENG: <u>Stieff - Windham</u>		DATE: <u>1 DAY 31 yr 79</u>						
INSTRUMENT (P-TRACK)	<input checked="" type="checkbox"/> 1 SYSTEM <input checked="" type="checkbox"/> 2 SYSTEMS	<input checked="" type="checkbox"/> 24 & 25-48 <input checked="" type="checkbox"/> 1-48 & 49-96	ODDS EVENTS	TYPE: <input type="checkbox"/> DFS III <input type="checkbox"/> DFS II	<input checked="" type="checkbox"/> 2 TRACK <input type="checkbox"/> 21 TRACK	FORMAT: <u>B</u>	<input type="checkbox"/> GAPPED <input type="checkbox"/> UNGAPPED	PACKING DENSITY:	(1) <input type="checkbox"/> 356 BPI <input type="checkbox"/> 800 BPI	(11) <input type="checkbox"/> 712 BPI <input type="checkbox"/> 1400 BPI
	NO. BYTES IN HEADER REC:	NO. BYTES IN RECORD ID:	NO. BYTES PER SCAN:	RECORD NUMBERS:	<input checked="" type="checkbox"/> DEC <input type="checkbox"/> OCT	GAIN CONSTANT: <u>76</u>	(1) (2) (3) (4) (5) (6) (7)	INPUT IMPEDANCE: <u>20K</u> ohms		
CONFIGURATION (MAG TAPE)	FIELD TRACE NOS.: <u>1-48</u>			AUXILIARY DATA:			AUXILIARY CHANNEL NOS.:			
PARAMETER	RECORD LENGTH: <u>6</u> sec.	SAMPLE RATE: <input type="checkbox"/> 1 ms <input checked="" type="checkbox"/> 2 ms <input type="checkbox"/> 4 ms	GAIN MODE: <input type="checkbox"/> INITIAL <input checked="" type="checkbox"/> FINAL	<input type="checkbox"/> MANUAL <input type="checkbox"/> OPERATE	FILTERS:	LO CUT HZ SLOPE	FREQ. <u>128</u>	HI CUT HZ SLOPE <u>70</u>	NOTCH FILTER: <input type="checkbox"/> IN <input type="checkbox"/> OUT	
DISPLAY	MODE: <input checked="" type="checkbox"/> MAGC <input type="checkbox"/> FLOAT <input type="checkbox"/> DEFOAT	<input type="checkbox"/> AMPLIFIER <input type="checkbox"/> DIRECT	INITIAL GAIN: <u>18</u> db	TRIP SENS.: <u>5</u> db	POLARITY CONVENTION: <input type="checkbox"/> NEGATIVE <input checked="" type="checkbox"/> POSITIVE	PRESSURE INCREASE ON GEOPHONE:	<input type="checkbox"/> NEGATIVE <input checked="" type="checkbox"/> POSITIVE	NUMBERS ON MAG. TAPE	<input type="checkbox"/> DOWNBREAK <input checked="" type="checkbox"/> UPBREAK	ON DISPLAY
CFS I	TYPE STACK:	GATE LENGTH:	RECORD REJECTION:	NOISE REDUCTION:	NOISE THRESHOLD:	CORR SCALING:	A.C.U. NORM / ALT SW			
SOURCE	TYPE: <input checked="" type="checkbox"/> DYNAMIC <input type="checkbox"/> VIBROSEIS <input type="checkbox"/> OTHER	PATTERN: <u>hole / inline</u>	NO. OF POSITIONS:	INLINE SPACING:	LATERAL SPACING:	STAGGER:	LENGTH:	WIDTH:	LATERAL OFFSET:	
RECEIVER	TYPE: <u>20-D</u>	PATTERN: <u>inline</u>	NO. OF ELEMENTS: <u>18</u>	INLINE SPACING: <u>12</u>	LATERAL SPACING:	STAGGER:	LENGTH:	WIDTH:	LATERAL OFFSET:	
SPREAD	NO. OF GROUPS: <u>48</u>	GROUP INTERVAL: <u>200</u>	SHOTPOINT INTERVAL: <u>880</u>	FOLD: <u>6</u>	DIRECTION OF PROGRESSION: <u>500+</u>	LEADING GROUP: <u>48</u>				



DIAGRAMS/MISC. INFORMATION:

SHOTPOINT	TR 1-10		TR 10-20		TR 20-30		TR 30-40		TR 40-50		CORE STAGE	
	TR NO.	REC.	TR NO.	REC.	TR NO.	REC.	TR NO.	REC.	TR NO.	REC.	TR 41-50	TR 51-60
1813	7511883	1107			26	67	31		39	77+1 - 88+4		
1814		1108			28	68	32		43	78+1 - 89+4		
1815		1109			29	69	33		47	79+1 - 90+4		
1816		1110			30	70	34		51	80+1 - 91+4		
1817		1111			31	71	35		55	81+1 - 92+4		
1818		1112			32	72	36		59	82+1 - 93+4		
1819		1113			33	73	37		63	83+1 - 94+4		
1820		1114			34	74	38		67	84+1 - 95+4		
1821		1115			35	75	39		71	85+1 - 96+4		
1822		1116			36	76	40		75	86+1 - 97+4		
1823		1117			37	77	41		79	87+1 - 98+4		
1824	7511884	1118			38	78	42		83	88+1 - 99+4		
1825		1119			39	79	43		87	89+1 - 100+4		
1826		1120			40	80	44		91	90+1 - 101+4		
1827		1121			41	81	45		95	91+1 - 102+4		
1828		1122			42	82	46		15	92+1 - 103+4	3	Recorder @ 106+2 / 106+3
1829		1123			43	83	47		19	93+1 - 104+4		
1830		1124			44	84	48		23	94+1 - 105+4		
1831		1125			45	85	49		27	95+1 - 106+4		
1832		1126			46	86	50		31	96+1 - 107+4		



# ANN'S COPY

## LAND SEISMIC RECORDING LOG



	CLIENT: <b>Husky</b>	PROSPECT: <b>NPR-A</b>	AREA: <b>Barrow</b>	LINE NO.: <b>616</b>									
	PARTY NO.: <b>1182</b>	INST. ENO.: <b>Stress-Windham</b>		DATE: <b>MO 1 DAY 31 YR 79</b>									
INSTRUMENT (9-TRACK)	<input type="checkbox"/> 1 SYSTEM <input type="checkbox"/> 2 SYSTEMS	<input type="checkbox"/> 1-24 & 25-48 <input type="checkbox"/> 1-48 & 49-96	<input type="checkbox"/> ODDS <input type="checkbox"/> EVENS	TYPE: <input type="checkbox"/> DFS I <input type="checkbox"/> DFS II <input type="checkbox"/> DFS III <input type="checkbox"/> OTHER	<input type="checkbox"/> 1 TRACK <input type="checkbox"/> 21 TRACK	FORMAT: <b>B</b> <input type="checkbox"/> SEG	<input type="checkbox"/> GAPPED <input type="checkbox"/> UNGAPPED	PACKING DENSITY: (L0) <input type="checkbox"/> 356 BPI (H1) <input type="checkbox"/> 712 BPI <input type="checkbox"/> 800 BPI <input type="checkbox"/> 1600 BPI	RECORD NUMBERS: <input type="checkbox"/> DEC. <input type="checkbox"/> OCT.	GAIN CONSTANT: <b>36</b> db	INPUT IMPEDANCE: <b>20K</b> ohms		
	NO. BYTES IN HEADER REC.	NO. BYTES IN RECORD ID:	NO. BYTES PER SCAN:	AUXILIARY DATA:			AUXILIARY CHANNEL NOS.:						
CONFIGURATION (MAG TAPE)	FIELD TRACE NOS.: <b>1-48</b>	DATA CHANNEL NOS.: <b>1-48</b> (ON MAG TAPE)			AUXILIARY DATA:								
PARAMETER	RECORD LENGTH: <b>6</b> sec.	SAMPLE RATE: <input type="checkbox"/> 1 ms <input type="checkbox"/> 4 ms	GAIN MODE: <input type="checkbox"/> INITIAL <input type="checkbox"/> FINAL <input type="checkbox"/> MANUAL <input type="checkbox"/> OPERATE	FILTERS: FREQ. <b>128</b> HI CUT HZ SLOPE <b>70</b>	LO CUT HZ SLOPE: <b>-</b>	FREQ. <b>128</b> HI CUT HZ SLOPE <b>70</b>	NOTCH FILTER: <input type="checkbox"/> IN <input type="checkbox"/> OUT	PRESSURE INCREASE ON GEOPHONE: <input type="checkbox"/> NEGATIVE <input type="checkbox"/> POSITIVE				NUMBERS ON MAG. TAPE: <input type="checkbox"/> DOWNBREAK <input type="checkbox"/> UPBREAK	ON DISPLAY: <input type="checkbox"/> ON <input type="checkbox"/> OFF
DISPLAY	MODE: <input type="checkbox"/> AGC <input type="checkbox"/> FLOAT <input type="checkbox"/> AMPLIFIER <input type="checkbox"/> DEFLOAT <input type="checkbox"/> DIRECT	INITIAL GAIN: <b>18</b> db	TRIP SENS.: <b>5</b> db	POLARITY CONVENTION: <input type="checkbox"/> POSITIVE <input type="checkbox"/> NEGATIVE	NOISE REDUCTION: NOISE THRESHOLD: <b>36</b> db			CORR. SCALING:	E.C.U. NORM./ALT SW.				
CFS I	TYPE STACK:	GATE LENGTH:	RECORD REJECTION:										
SOURCE	TYPE: <input type="checkbox"/> DYNAMITE <input type="checkbox"/> VIBROSEIS <input type="checkbox"/> OTHER	PATTERN: <b>Inline/Hole</b>	NO. OF POSITIONS:	INLINE SPACING:	LATERAL SPACING:	STAGGER:	LENGTH:	WIDTH:	LATERAL OFFSET:				
RECEIVER	TYPE: <b>30-0</b>	PATTERN: <b>INLINE</b>	NO. OF ELEMENTS: <b>18</b>	INLINE SPACING: <b>12</b>	LATERAL SPACING:	STAGGER:	LENGTH:	WIDTH:	LATERAL OFFSET:				
SPREAD	CONNECTION: <b>Series-Parallel</b>	RESISTANCE: <b>560</b> ohms	STAGGER:	LENGTH:	WIDTH:	PHASE COMP:							
	NO. OF GROUPS: <b>48</b>	GROUP INTERVAL: <b>220</b>	SHOTPOINT INTERVAL: <b>880</b>	FOLD: <b>6</b>	DIRECTION OF PROGRESSION: <b>South</b>								
	OFFSET GROUP 1: <b>5170</b>	OFFSET GROUP 24: <b>110</b>	OFFSET GROUP 48: <b>110</b>	OFFSET GROUP 48/96: <b>5170</b>	LEADING GROUP: <b>48</b>								

DIAGRAMS/MISC. INFORMATION:  
94 — 751884

SHOTPOINT	TR 1-10		TR 11-20		TR 21-30		TR 31-40		TR 41-50		CDP SWITCH	LINE GROUPS	REMARKS:	CORR STACK				
	REEL NO.	REC.	REEL NO.	REC.	REEL NO.	REC.	REEL NO.	REC.	REEL NO.	REC.				TR 1-10	TR 11-20	TR 21-30	TR 31-40	
11013	7511884	129									35	97+1 - 108+4	3					
11014		128									39	98+1 - 109+4		Obs. Log for S.P. 94-102 are continued from those for Tape # 751883				
11015		129									43	99+1 - 110+4						
11016		130									47	100+1 - 111+4						
11017		131									51	101+1 - 112+4						
11018		132									55	102+1 - 113+4						
11019		133									59	103+1 - 114+4						
11020		134									63	104+1 - 115+4						
11021		135									67	105+1 - 116+4						
11022		136									71	106+1 - 117+4						
11023		137									75	107+1 - 118+4						
11024		138									79	108+1 - 119+4						
11025		140									83	109+1 - 120+4						
11026		141									87	110+1 - 121+4						
11027		143									25	111+1 - 122+4						
11028		144									29	112+1 - 123+4						
11029		145									33	113+1 - 124+4						
11030		146									37	114+1 - 125+4						
11031		147									41	115+1 - 126+4						
11032		148									45	116+1 - 127+4						

**\* 139 - N.C. \***  
**\* 142 - (6) Recorder @ 91-27**

# LAND SEISMIC RECORDING LOG

	CLIENT: <b>Husky</b>	PROSPECT: <b>NPR-A</b>	AREA: <b>Barrow</b>	LINE NO.: <b>616</b>					
PARTY NO.: <b>1182</b>		INST. ENG.: <b>Streff - Winham</b>		DATE: <b>MO. 1 DAY 31 YE 79</b>					
INSTRUMENT (9-TRACK)	<input checked="" type="checkbox"/> 1 SYSTEM <input checked="" type="checkbox"/> 2 SYSTEMS	<input checked="" type="checkbox"/> 1-24 & 25-48 <input checked="" type="checkbox"/> 1-48 & 49-96	<input type="checkbox"/> DODS <input type="checkbox"/> EVENS	TYPE: <input type="checkbox"/> OPS III <input type="checkbox"/> OPS IV	<input type="checkbox"/> 9 TRACK <input type="checkbox"/> 21 TRACK	FORMAT: <b>B</b> SEG	<input type="checkbox"/> TAPPED <input type="checkbox"/> UNTAPPED	PACKING DENSITY: (10) <input type="checkbox"/> 356 BPI (11) <input type="checkbox"/> 712 BPI (12) <input type="checkbox"/> 800 BPI (13) <input type="checkbox"/> 1600 BPI	
	NO. BYTES IN HEADER REC:	NO. BYTES IN RECORD ID:	NO. BYTES PER SCAN:	RECORD NUMBERS: <input checked="" type="checkbox"/> DEC <input type="checkbox"/> OCT	GAIN CONSTANT: <b>36</b> db	INPUT IMPEDANCE: <b>20k</b> ohms			
CONFIGURATION (MAG TAPE)	FIELD TRACE NOS.: <b>1-48</b>			AUXILIARY DATA:			AUXILIARY CHANNEL NOS.:		
PARAMETER	DATA CHANNEL NOS.: <b>1-48</b> (ON MAG TAPE)			FREQ. <b>128</b> HI CUT HZ SLOPE <b>70</b> NOTCH FILTER: <input type="checkbox"/> IN <input checked="" type="checkbox"/> OUT			POLARITY CONVENTION: <input checked="" type="checkbox"/> NEGATIVE <input type="checkbox"/> POSITIVE		
DISPLAY	<input checked="" type="checkbox"/> AGC <input type="checkbox"/> FLOAT <input type="checkbox"/> AMPLIFIER <input type="checkbox"/> DIRECT	INITIAL GAIN: <b>010</b> db	TRIP SENS.: <b>5</b> db	PRESSURE INCREASE ON GEOPHONE: <input type="checkbox"/> POSITIVE <input checked="" type="checkbox"/> NEGATIVE			NUMBERS ON MAG. TAPE <input type="checkbox"/> UPBREAK <input type="checkbox"/> DOWNBREAK ON DISPLAY		
CFS I	TYPE STACK:	GATE LENGTH:	RECORD REJECTION:	NOISE REDUCTION:	NOISE THRESHOLD:	CDR. SCALING:	R.C.U. NORM./ALT. SW.		
SOURCE	TYPE: <input checked="" type="checkbox"/> DYNAMITE <input type="checkbox"/> VIBROSEIS <input type="checkbox"/> OTHER	PATTERN: <b>Incline</b>	NO. OF POSITIONS:	INLINE SPACING:	LATERAL SPACING:	STAGGER:	LENGTH:	WIDTH:	LATERAL OFFSET:
RECEIVER	TYPE: <b>200</b>	PATTERN: <b>Incline</b>	NO. OF ELEMENTS: <b>18</b>	INLINE SPACING: <b>12</b>	LATERAL SPACING:	STAGGER:	LENGTH:	WIDTH:	LATERAL OFFSET:
SPREAD	CONNECTION: <b>Series-Parallel</b>	RESISTANCE: <b>560</b> ohms	STAGGER:	LENGTH:	WIDTH:	LATERAL OFFSET:	DIRECTION OF PROGRESSION: <b>South</b>		
DIAGRAMS/MISC. INFORMATION:									

SHOTPOINT	TR. 19		TR. 18		SHOT					SPREAD			REMARKS	CORR. STACK			
	REEL NO.	REC.	REEL NO.	REC.	SIZE	DEPTH	NO.	OFFSET	DIR.	CDP SWITCH	LINE GROUPS	SET UP		TR. 19	TR. 18	TR. 17	TR. 16
11212	114	114	22	23	24	25	26	27	28	29	30	31	32	33	34	35	36
11213	114	114			20	167	61	11		49	11741-12844	4					
11214		1150			20	167	62	11		53	11741-12844						
11215		1151			20	167	63	11		57	11741-12844						
11216		1152			20	167	64	11		61	12041-13144						
										61							





Recording HRS - 14.5

### LAND SEISMIC RECORDING LOG

CLIENT: <b>HUSKY</b>		PROSPECT: <b>NPR-A</b>		AREA: <b>BARROW</b>		LINE NO.: <b>616</b>	
PARTY NO.: <b>1182</b>		INST. ENG.: <b>STREFF-Windham</b>		DATE: <b>MO 2 DAY 3 YR 79</b>			
INSTRUMENT [9-TRACK] <input type="checkbox"/> 1 SYSTEM <input type="checkbox"/> 2 SYSTEMS		ODDS: <input type="checkbox"/> 1-24 & 25-48 <input type="checkbox"/> 1-48 & 49-96		TYPE: <input type="checkbox"/> OFS III <input type="checkbox"/> OFS X <input type="checkbox"/> OFS II <input type="checkbox"/> OTHER		FOPRAT: <b>B</b> <input type="checkbox"/> 9 TRACK <input type="checkbox"/> 21 TRACK	
NO. BYTES IN HEADER REC:		NO. BYTES IN RECORD ID:		NO. BYTES PER SCAN:		RECORD NUMBERS: <input checked="" type="checkbox"/> DEC <input type="checkbox"/> OCT	
CONFIGURATION (MAG TAPE) FIELD TRACE NOS.: <b>1-48</b> DATA CHANNEL NOS.: <b>1-48</b>		[ON MAG TAPE]		AUXILIARY DATA:		AUXILIARY CHANNEL NOS.:	
PARAMETER RECORD LENGTH: <b>6</b> sec.		SAMPLE RATE: <input type="checkbox"/> 1 ml <input type="checkbox"/> 4 ms <input type="checkbox"/> 2 ms <input type="checkbox"/> 10 ms		GAIN MODE: <input type="checkbox"/> INITIAL <input type="checkbox"/> MANUAL <input type="checkbox"/> OPERATE <input checked="" type="checkbox"/> IFP <input type="checkbox"/> FINAL		FILTERS: <b>OUT</b> LO CUT HZ SLOPE <b>70</b> HI CUT HZ SLOPE <b>1200</b>	
DISPLAY MODE: <input checked="" type="checkbox"/> AGC <input type="checkbox"/> FLOAT <input type="checkbox"/> DEFLOAT <input type="checkbox"/> AMPLIFIER <input type="checkbox"/> DIRECT		INITIAL GAIN: <b>18</b> db		TRIP SENS.: <b>46</b> db		POLARITY CONVENTION: <input checked="" type="checkbox"/> NEGATIVE <input type="checkbox"/> POSITIVE	
CFS I TYPE: <input type="checkbox"/> STAGE		DATE LENGTH:		RECORD REJECTION:		NOISE REDUCTION: <input type="checkbox"/> CORE SCALING: <input type="checkbox"/> C.U. NORM/AUT SW.	
SOURCE TYPE: <input type="checkbox"/> DYNAMITE <input type="checkbox"/> VIBROSEIS <input type="checkbox"/> OTHER		PATTERN: <b>SINGLE HOLE/INLINE</b>		NO. OF POSITIONS:		INLINE SPACING:	
RECEIVER TYPE: <b>20 D</b>		PATTERN: <b>INLINE</b>		NO. OF ELEMENTS: <b>18</b>		INLINE SPACING:	
CONNECTION: <b>SERIES/PARALLEL</b>		RESISTANCE:		STAGGER:		LENGTH:	
SPREAD NO. OF GROUPS: <b>48</b>		GROUP INTERVAL: <b>220'</b>		SHOTPOINT INTERVAL: <b>440' 880</b>		FOLD: <b>6</b>	
OFFSET GROUP 1: <b>330' 5170'</b>		OFFSET GROUP 24: <b>300' 110'</b>		OFFSET GROUP 25: <b>330' 110'</b>		OFFSET GROUP 48/96: <b>5170'</b>	

DIAGRAMS/MISC. INFORMATION: 


SHOTPOINT	TR _____ TO _____		TR _____ TO _____		SHOT				SPREAD		REMARKS	CORR. STAGE			
	REEL NO.	REC.	REEL NO.	REC.	SIZE	DEPTH	NO.	OFFSET	DIR.	CDP SWITCH		LINE GROUPS	TR	RE	TR
1121	7511884	164			20	67	11			29	121+1 - 130+4				
1128		165			20	67	12			33	122+1 - 133+4				
1129		166			20	67	13			37	123+1 - 134+4				
1130		167			20	67	14			41	124+1 - 135+4				
1131		168			20	67	15			45	125+1 - 136+4				
1132		169			20	67	16			49	126+1 - 137+4				
1133		170			20	67	17			53	127+1 - 138+4				
1134		171			20	67	18			57	128+1 - 139+4				
1135		172			20	67	19			61	129+1 - 140+4				
1136		173			20	67	10			29	130+1 - 141+4	2			
1137		174			20	67	11			33	131+1 - 142+4				
1138		175			20	67	12			37	132+1 - 143+4				
1139		176			20	67	13			41	133+1 - 144+4				
1140		177			20	67	14			45	134+1 - 145+4				
1141		178			20	67	15			49	135+1 - 146+4				
1142		179			20	67	16			53	136+1 - 147+4				
1143		180			20	67	17			57	137+1 - 148+4				
1144		181			20	67	18			61	138+1 - 149+4				
1145		182			20	67	19			65	139+1 - 150+4				
1146		183			20	67	20			69	140+1 - 151+4	3			

~~1183, 184~~ N.G.  
Recorder @ 151+5 / 151+30

# LAND SEISMIC RECORDING LOG

CLIENT: <b>Husky</b>		PROSPECT: <b>NPR-A</b>		AREA: <b>Barrow</b>		LINE NO.: <b>616</b>	
PARTY NO.: <b>118J</b>		INST. ENG.: <b>Syreff-Windham</b>		DATE: <b>MO 2 DAY 3 YR 79</b>			
INSTRUMENT (9-TRACK) NO. BYTES IN HEADER REC. _____		NO. BYTES IN RECORD ID: _____		NO. BYTES PER SCAN: _____		RECORD NUMBERS: <b>0-DEC</b> <input type="checkbox"/> OCT. <input type="checkbox"/>	
CONFIGURATION (MAG TAPE) FIELD TRACE NOS.: <b>1-48</b>		DATA CHANNEL NOS.: <b>1-88</b>		(ON MAG TAPE)		AUXILIARY DATA: AUXILIARY CHANNEL NOS.: _____	
PARAMETER RECORD LENGTH: <b>4</b>		SAMPLE RATE: <input type="checkbox"/> 1 sec. <input type="checkbox"/> 2 sec. <input type="checkbox"/> 4 sec.		GAIN MODE: <input type="checkbox"/> INITIAL <input type="checkbox"/> MANUAL <input type="checkbox"/> FINAL <input type="checkbox"/> OPERATE		FILTERS: _____	
DISPLAY MODE: <input checked="" type="checkbox"/> PAGE <input type="checkbox"/> FLOAT <input type="checkbox"/> AMPLIFIER <input type="checkbox"/> DEFLOAT <input type="checkbox"/> DIRECT		INITIAL GAIN: <b>18</b>		TRIP SENS.: <b>5</b>		POLARITY CONVENTION: <input type="checkbox"/> NEGATIVE <input type="checkbox"/> POSITIVE	
CFS I TYPE STACK: _____		GATE LENGTH: _____		RECORD REJECTION: _____		NOISE REDUCTION: _____	
SOURCE <input checked="" type="checkbox"/> DYNAMITE <input type="checkbox"/> VIBROSEIS <input type="checkbox"/> OTHER		PATTERN: <b>Inline/Hole</b>		NO. OF POSITIONS: _____		INLINE SPACING: _____	
RECEIVER TYPE: <b>200</b>		PATTERN: <b>Inline</b>		NO. OF ELEMENTS: <b>18</b>		INLINE SPACING: <b>12</b>	
CONNECTION: <b>Series-Parallel</b>		RESISTANCE: <b>560</b>		STAGGER: _____		LENGTH: _____	
SPREAD NO. OF GROUPS: <b>48</b>		GROUP INTERVAL: <b>220</b>		SHOTPOINT INTERVAL: <b>880</b>		FOLD: <b>6</b>	
OFFSET GROUP 1: <b>5170</b>		OFFSET GROUP 2: <b>110</b>		OFFSET GROUP 3: <b>110</b>		OFFSET GROUP 4/7/6: <b>5170</b>	

DIAGRAMS/MISC. INFORMATION:

**WIND NOISE**

SHOTPOINT	TR 1		TR 2		SHOT				DIR.	CDF SWITCH	SPREAD		REMARKS	CORR. STAGE			
	BEEL NO.	REC.	REFL. NO.	REC.	SIZE	DEPTH	NO.	OFFSET			LINE GROUPS	NO.		NO.	NO.	NO.	
11417	1884	1188			20	167	31			31	141+1	152+1	3	Short Record (Cut off @ approx. 4.7 sec)			
11418		1188			20	167	32			35	142+1	153+1		<b>FILE # 186 MISFIRE</b>			
11419		1189			20	167	33			39	143+1	154+1					
11500		1190			20	167	34			43	144+1	155+1					
11511		1191			20	167	35			47	145+1	156+1					
11522		1192			20	167	36			51	146+1	157+1					
11533		1193			20	167	37			55	147+1	158+1					
11544		1194			20	167	38			59	148+1	159+1		FILTER P.B. 18HZ			
11555		1195			20	167	39			63	149+1	160+1					
11566		1196			20	167	40			67	150+1	161+1					
11577		1197			20	167	41			71	151+1	162+1					
11588		1198			20	167	42			75	152+1	163+1					
11599		1199			20	167	43			79	153+1	164+1					
11600		2000			20	167	44			83	154+1	165+1					
11611		2001			20	167	45			87	155+1	166+1					
11622		2002			20	167	46			91	156+1	167+1					
11633		2003			20	167	47			95	157+1	168+1		168+1 - 168+4 ARE DEAD			
11644		2004			20	167	48			33	158+1	169+1	4	RECORDER AT 168			
11655		2005			20	167	49			37	159+1	170+1		RECORD			
11666		2006			20	167	50			41	160+1	171+1					

# LAND SEISMIC RECORDING LOG

CLIENT: <b>HUSKY</b>		PROSPECT: <b>NPR-A</b>		AREA: <b>BARROW</b>		LINE NO: <b>616</b>	
PARTY NO: <b>1182</b>		INST. ENG: <b>STREFF-WINDHAM</b>		DATE: <b>NO 2 DAY 3 YR 79</b>			
INSTRUMENT [9-TRACK] <input checked="" type="checkbox"/> 1 SYSTEM <input checked="" type="checkbox"/> 2 SYSTEMS		NO. 1-24 & 25-48 <input type="checkbox"/> ODDS <input type="checkbox"/> EVENS		TYPE: <input type="checkbox"/> DFS III <input checked="" type="checkbox"/> DFS IV <input type="checkbox"/> OTHER		NO. 9 TRACK <input type="checkbox"/> 21 TRACK <input type="checkbox"/>	
NO. BYTES IN HEADER REC.		NO. BYTES IN RECORD ID		NO. BYTES PER SCAN		RECORD NUMBERS: <input type="checkbox"/> DEC. <input type="checkbox"/> OCT.	
CONFIGURATION (MAG TAPE)		FIELD TRACE NOS.: <b>1-48</b>		AUXILIARY DATA:		GAIN CONSTANT: _____ db	
DATA CHANNEL NOS.: <b>1-48</b>		(ON MAG TAPE)		AUXILIARY CHANNEL NOS.:		INPUT IMPEDANCE: _____ ohms	
PARAMETER		RECORD LENGTH: <b>6</b> sec.		SAMPLE RATE: <input type="checkbox"/> 1 ms. <input type="checkbox"/> 4 ms.		FILTERS: _____	
DISPLAY		MODE: <input type="checkbox"/> FLOAT <input type="checkbox"/> AMPLIFIER <input type="checkbox"/> DIRECT		INITIAL GAIN: <b>18</b> db		LO CUT HZ SLOPE: _____	
CFS I		TYPE: _____		GATE LENGTH: _____		CORR. SCALING: _____	
SOURCE		TYPE: <input checked="" type="checkbox"/> DYNAMITE <input type="checkbox"/> VIBROSEIS <input type="checkbox"/> OTHER		PATTERN: <b>SINGLE HOLE / INLINE</b>		NO. OF POSITIONS: _____	
		CHG/ HOLE: <b>20</b>		HOLE DEPTH: <b>75</b>		SWEEP POSITION: _____	
RECEIVER		TYPE: <b>200</b>		PATTERN: <b>INLINE</b>		NO. OF ELEMENTS: <b>18</b>	
CONNECTION: <b>SERIES / PARALLEL</b>		RESISTANCE: _____ ohms		STAGGER: _____		INLINE SPACING: <b>12'</b>	
SPREAD		NO. OF GROUPS: <b>48</b>		GROUP INTERVAL: <b>220'</b>		SHOTPOINT INTERVAL: <b>880'</b>	
OFFSET GROUP 1: <b>5170'</b>		OFFSET GROUP 24: <b>110'</b>		OFFSET GROUP 25: <b>110'</b>		OFFSET GROUP 48/96: <b>5170'</b>	

DIAGRAMS/MISC. INFORMATION: Wind Noise

SHOTPOINT	TR. 10		TR. 10		SHOT								SPREAD		REMARKS	CORR. STAGE			
	REEL NO.	REC.	REEL NO.	REC.	SIZE	DEPTH	NO.	OFFSET	DIR.	CDP SWITCH	LINE GROUPS		TR. 10	TR. 10		TR. 10	TR. 10		
1167	151894	207			20	6741					45	161+1	172+4						
1168		208			20	6742					49	162+1	173+4						
1169		209			20	6743					53	163+1	174+4						
1170		210			20	6744					57	164+1	175+4						
1171		211			20	6745					61	165+1	176+4						

Recording Hrs. 15.0

LAND SEISMIC RECORDING LOG

CLIENT: <b>HUSKY</b>		PROSPECT: <b>NPR-A</b>		AREA: <b>BARROW</b>		LINE NO.: <b>616</b>	
PARTY NO.: <b>1182</b>		INST. ENG.: <b>STREFF-WINDHAM</b>		DATE: <b>MO 7 DAY 4 YR 79</b>			
INSTRUMENT (9-TRACK): <input checked="" type="checkbox"/> 1 SYSTEM <input checked="" type="checkbox"/> 2 SYSTEMS		ODDS: <input type="checkbox"/> 1-24 & 25-48 <input type="checkbox"/> 1-48 & 49-96		EVENTS: <input type="checkbox"/> ODDS <input type="checkbox"/> EVENS		TYPE: <input type="checkbox"/> DFS <input checked="" type="checkbox"/> DFI <input type="checkbox"/> DFI <input checked="" type="checkbox"/> DFI	
NO. BYTES IN HEADER REC.		NO. BYTES IN RECORD ID:		NO. BYTES PER SCAN:		RECORD NUMBERS: <input type="checkbox"/> 9 TRACK <input type="checkbox"/> 21 TRACK	
FIELD TRACE NOS.: <b>1-48</b>		DATA CHANNEL NOS.: <b>1-48</b>		AUXILIARY DATA:		AUXILIARY CHANNEL NOS.:	
PARAMETER: RECORD LENGTH: <b>6</b> sec.		SAMPLE RATE: <input type="checkbox"/> 1 ms. <input type="checkbox"/> 4 ms. <input type="checkbox"/> 2 ms. <input type="checkbox"/> 8 ms.		GAIN MODE: <input type="checkbox"/> INITIAL <input type="checkbox"/> MANUAL <input checked="" type="checkbox"/> OPERATE		FILTERS: <input checked="" type="checkbox"/> FREQ. <b>OUT</b> <input type="checkbox"/> LO CUT <input type="checkbox"/> HI CUT	
DISPLAY: <input checked="" type="checkbox"/> AGC <input type="checkbox"/> FLOAT <input type="checkbox"/> AMPLIFIER <input type="checkbox"/> DEFLOAT <input type="checkbox"/> DIRECT		INITIAL GAIN: <b>36</b> <b>18</b> db		TRIP SENS.: <b>4</b> db		POLARITY CONVENTION: <input type="checkbox"/> NEGATIVE <input checked="" type="checkbox"/> POSITIVE	
SOURCE: <input checked="" type="checkbox"/> DYNAMITE <input type="checkbox"/> VIBROSEIS <input type="checkbox"/> OTHER		PATTERN: <b>SINGLE HOLE INLINE</b>		NO. OF POSITIONS: <b>18</b>		INLINE SPACING: <b>12'</b>	
RECEIVER: TYPE: <b>20D</b>		CONNECTION: <b>SERIES/PARALLEL</b>		RESISTANCE: _____ ohms		STAGGER: _____	
SPREAD: NO. OF GROUPS: <b>48</b>		GROUP INTERVAL: <b>220'</b>		SHOTPOINT INTERVAL: <b>880'</b>		FOLD: <b>6</b>	
DIAGRAMS/MISC. INFORMATION:		OFFSET GROUP 1: <b>5170'</b>		OFFSET GROUP 25: <b>110'</b>		OFFSET GROUP 48/96: <b>5170'</b>	



SHOTPOINT	TR #1		TR #25		TR #48		SHOT NO.	SIZE	DEPTH	NO.	OFFSET	DIR	CDP SWITCH	SPREAD	LINE GROUPS	REMARKS	CORR STACK						
	REEL NO.	REC.	REEL NO.	REC.	REEL NO.	REC.											TR #1	TR #25	TR #48	TR #96			
1172	751884	220					20	167	11					2917	166+1	- 1714	1	RECORDER AT 180					
1173		223					20	167	2					21	167+1	- 1784							
1174		224					20	167	3					25	168+1	- 179+4							
1175		225					20	167	4	330	SOUTH			29	169+1	- 180+4							
1176		226					20	167	5					33	170+1	- 181+4							
1177		227					20	167	6					37	171+1	- 182+4							
1178		228					20	167	7					41	172+1	- 183+4							
1179		229					20	167	8					45	173+1	- 184+4							
1180		230					20	167	9					49	174+1	- 185+4							
1181		231					20	167	10					53	175+1	- 186+4							
1182		232					20	167	11					57	176+1	- 187+4							
1183		233					20	167	12					61	177+1	- 188+4							
1184		234					20	167	13					65	178+1	- 189+4							
1185		235					20	167	14					69	179+1	- 190+4							
1186	751885	236					20	167	15					73	180+1	- 191+4							
1187		237					20	167	16					77	181+1	- 192+4							
1188		238					20	167	17					81	182+1	- 193+4							
1189		239					20	167	18					85	183+1	- 194+4							
1190		240					20	167	19					89	184+1	- 195+4							
1191		241					20	167	20					27	185+1	- 196+4	2	RECORDER AT 196+2					



# LAND SEISMIC RECORDING LOG

	CLIENT: <b>HUSKY</b>	PROSPECT: <b>NPR-A</b>	AREA: <b>BARROW</b>	LINE NO.: <b>616</b>					
	PARTY NO.: <b>1182</b>	INST. ENG.: <b>STREFF - WINDHAM</b>		DATE: <b>MO 2 DAY 4 YR 77</b>					
INSTRUMENT (9-TRACK)	<input type="checkbox"/> 1 SYSTEM <input type="checkbox"/> 2 SYSTEMS	<input type="checkbox"/> 1-24 & 25-48 <input type="checkbox"/> 1-48 & 49-96	<input type="checkbox"/> DDFS <input type="checkbox"/> EVENTS	TYPE: <input type="checkbox"/> DPS III <input type="checkbox"/> DPS IX <input type="checkbox"/> OTHER	<input type="checkbox"/> 9 TRACK <input type="checkbox"/> 21 TRACK	FORMAT: SEG <b>B</b>	<input checked="" type="checkbox"/> GAPPED <input type="checkbox"/> UNGAPPED	PACKING DENSITY: (10) <input type="checkbox"/> 356 BPI (11) <input type="checkbox"/> 500 BPI	(12) <input type="checkbox"/> 712 BPI (13) <input type="checkbox"/> 1000 BPI
	NO. BYTES IN HEADER REC:	NO. BYTES IN RECORD IO:	NO. BYTES PER SCAN:	RECORD NUMBERS:	<input type="checkbox"/> DEC. <input type="checkbox"/> OCT	GAIN CONSTANT: <b>36</b>	(1) (2) (3) (4) (5) (6) (7)	INPUT IMPEDANCE: ohms	
CONFIGURATION (MAG TAPE)	FIELD TRACE NOS.: <b>1-48</b>	DATA CHANNEL NOS.: <b>1-48</b> (ON MAG TAPE)			AUXILIARY DATA: AUXILIARY CHANNEL NOS.:				
PARAMETER	RECORD LENGTH: <b>6</b>	SAMPLE RATE: <b>57</b> Hz	<input type="checkbox"/> 1 hr. <input type="checkbox"/> 4 hr.	GAIN MODE: <input type="checkbox"/> INITIAL <input checked="" type="checkbox"/> FINAL	<input type="checkbox"/> MANUAL <input type="checkbox"/> OPERATE	FILTERS: FREQ <b>CUT</b>	LO CUT HZ SLOPE: <b>70</b>	NOTCH FILTER: <input type="checkbox"/> IN <input type="checkbox"/> OUT	
DISPLAY	MODE: <input type="checkbox"/> AGC <input type="checkbox"/> FLOAT <input type="checkbox"/> DEPLOY <input type="checkbox"/> DIRECT	AMPLIFIER	INITIAL GAIN: <b>18</b>	TRIP SENS: <b>48</b>	POLARITY CONVENTION: <input type="checkbox"/> NEGATIVE <input type="checkbox"/> POSITIVE	PRESSURE INCREASE ON GEOPHONE: <input type="checkbox"/> NEGATIVE <input type="checkbox"/> POSITIVE	NUMBERS ON MAG TAPE: <input type="checkbox"/> DOWNBREAK <input type="checkbox"/> UPBREAK	ON DISPLAY	
CFS I	TYPE STACK:	GATE LENGTH:	RECORD REJECTION:	NOISE REDUCTION:	NOISE THRESHOLD:	COEF. SCALING:	E.C.U. NORM/ALT SW.		
SOURCE	TYPE: <input checked="" type="checkbox"/> DYNAMITE <input type="checkbox"/> VISCOSEIS <input type="checkbox"/> OTHER	PATTERN: <b>SINGLE HOLE INLINE</b>	NO. OF POSITIONS:	INLINE SPACING:	LATERAL SPACING:	STAGGER:	LENGTH:	WIDTH:	LATERAL OFFSET:
RECEIVER	TYPE: <b>200</b>	PATTERN: <b>INLINE</b>	NO. OF ELEMENTS: <b>18</b>	INLINE SPACING: <b>12'</b>	LATERAL SPACING:	STAGGER:	LENGTH:	WIDTH:	LATERAL OFFSET:
SPREAD	CONNECTION: <b>SERIES/PARALLEL</b>	RESISTANCE:	STAGGER:	LENGTH:	WIDTH:	LATERAL OFFSET:	DIRECTION OF PROGRESSION: <b>SOUTH</b>		
	NO. OF GROUPS: <b>48</b>	GROUP INTERVAL: <b>220'</b>	SHOTPOINT INTERVAL: <b>880'</b>	FOLD: <b>6</b>	OFFSET GROUP 48/90: <b>5170'</b>	LEADING GROUP: <b>48</b>			
	OFFSET GROUP 1: <b>5170'</b>	OFFSET GROUP 24: <b>110'</b>	OFFSET GROUP 25: <b>110'</b>						

DIAGRAMS/MISC. INFORMATION:  
 186 - 75185  
 \* Tape #751885 begins w/ S.P. 186 \*  
 \* See Part Obs. Log for Tape #751884 \*

SHOTPOINT	TR 10		TR 10		SHOT				SPREAD		REMARKS	CORE STACK				
	REEL NO.	REC.	REEL NO.	REC.	SIZE	DEPTH	NO.	OFFSET	DIR.	COP SWITCH		LINE GROUPS	TR 10	TR 10	TR 10	TR 10
1182	751885	242			20	167	21			31	186+1 - 197+4					
1183		243			20	167	22			35	187+1 - 198+4					
1184		244			20	167	23			39	188+1 - 199+4					
1185		245			20	167	24			43	189+1 - 200+4					
1186		246			20	167	25			47	190+1 - 201+4					
1187		247			20	167	26			51	191+1 - 202+4					
1188		248			20	167	27			55	192+1 - 203+4					
1189		249			20	167	28			59	193+1 - 204+4					
200		250			20	167	29			21	194+1 - 205+4	3	RECORDER AT 207			
201		251			20	167	30			25	195+1 - 206+4					
202		252			20	167	31			29	196+1 - 207+4					
203		253			20	167	32			33	197+1 - 208+4					
204		254			20	167	33			37	198+1 - 209+4					
205		255			20	167	34			41	199+1 - 210+4					
206		256			20	167	35			45	200+1 - 211+4					
207		257			20	167	36			49	201+1 - 212+4					
208		258			20	167	37			53	202+1 - 213+4					
209		259			20	167	38			57	203+1 - 214+4					
210		260			20	167	39	30	South	61	204+1 - 215+4					
211		261			20	167	40			65	205+1 - 216+4					





Recording hrs. 14.5

### LAND SEISMIC RECORDING LOG

CLIENT: <b>HUSKY</b>		PROSPECT: <b>NPR-A</b>		AREA: <b>BARROW</b>		LINE NO: <b>616</b>	
PARTY NO: <b>1182</b>		INST. ENG: <b>STREFF - WINDHAM</b>		DATE: <b>MO 2 DAY 5 YR 79</b>			
INSTRUMENT [9-TRACK] <input checked="" type="checkbox"/> SYSTEM <input type="checkbox"/> 2 SYSTEMS		ODDS <input type="checkbox"/> 1-24 & 25-48 <input type="checkbox"/> 1-48 & 49-96		EVENTS <input type="checkbox"/> ODDS <input type="checkbox"/> OTHER		FORMAT: <b>SEG 8</b>	
NO. BYTES IN HEAD/RECL: _____		NO. BYTES IN RECORD ID: _____		NO. BYTES PER SCAN: <b>134</b>		RECORD NUMBERS: <b>DEC</b> <input type="checkbox"/> <b>OCT</b> <input type="checkbox"/>	
CONFIGURATION (MAG TAPE) FIELD TRACE NOS: <b>1-48</b> DATA CHANNEL NOS: <b>1-48</b>		(ON MAG TAPE)		AUXILIARY DATA:		AUXILIARY CHANNEL NOS: _____	
PARAMETER RECORD LENGTH: <b>6</b> sec.		SAMPLE RATE: <input type="checkbox"/> 1 ms <input type="checkbox"/> 4 ms		GAIN MODE: <input type="checkbox"/> INITIAL <input type="checkbox"/> MANUAL <input type="checkbox"/> FINAL		FILTERS: <b>FREQ. OUT</b> LO CUT _____ HZ SLOPE _____	
DISPLAY MODS: <input type="checkbox"/> FLAG <input type="checkbox"/> FLOAT <input type="checkbox"/> DEFLOAT <input type="checkbox"/> AMPLIFIER <input type="checkbox"/> DIRECT		INITIAL GAIN: <b>18</b> db		TRIP SENS: _____ db		POLARITY CONVENTION: _____ PRESSURE INCREASE ON GEOPHONE: <input type="checkbox"/> NEGATIVE <input type="checkbox"/> POSITIVE	
CFS I TYPE STACK: _____		DATE LENGTH: _____		RECORD REJECTION: _____		NOISE REDUCTION: _____ NOISE THRESHOLD: _____	
SOURCE TYPE: <input checked="" type="checkbox"/> DYNAMITE <input type="checkbox"/> VIBROSEIS <input type="checkbox"/> OTHER		PATTERN: <b>SINGLE HOLE INLINE</b>		NO. OF POSITIONS: _____		INLINE SPACING: _____	
RECEIVER TYPE: <b>20D</b>		PATTERN: <b>INLINE</b>		NO. OF ELEMENTS: <b>18</b>		INLINE SPACING: <b>121'</b>	
SPREAD NO. OF GROUPS: <b>48</b>		GROUP INTERVAL: <b>220'</b>		SHOTPOINT INTERVAL: <b>880'</b>		FOLD: <b>6</b>	
OFFSET GROUP 1: <b>5170'</b>		OFFSET GROUP 2: <b>110'</b>		OFFSET GROUP 25: <b>110'</b>		OFFSET GROUP 48/75: <b>5170'</b>	

DIAGRAMS/MISC. INFORMATION: *522+1 27 522+2 29 223+2 223+1*  
*TRACE 1 TRACE 24 TRACE 25 TRACE 48*  
 RECORD # 268-276 DAILY TESTS  
 FILE # 274 N.G. FILE # 277 N.G.  
 FILE # 278 TEST T.B.

SHOTPOINT	TR 10		TR 10		SHOT		SPREAD		REMARKS	CORR. STACK						
	REEL NO.	REC.	REEL NO.	REC.	SIZE	DEPTH	NO.	OFFSET		DIR.	CDP SWITCH	LINE GROUPS	TR 10	TR 10	TR 10	TR 10
218	218	219			20	617	1		27	212+1	-223+4	1				RECORDER AT 223+2
219		220			20	617	2		31	213+1	-224+4					
220		221			20	617	3		35	214+1	-225+4					
221		222			20	617	4		39	215+1	-226+4					
222		223			20	617	5		43	216+1	-227+4					
223		224			20	617	6		47	217+1	-228+4					
224		225			20	617	7		51	218+1	-229+4					
225		226			20	617	8		55	219+1	-230+4					
226		227			20	617	9		59	220+1	-231+4					
227		228			20	617	10	200 EAST	39	221+1	-232+4	2				RECORDER AT 229+2
228		229			20	617	11		43	222+1	-233+4					
229		230			20	617	12		47	223+1	-234+4					
230		231			20	617	13		51	224+1	-235+4					
231		232			20	617	14		55	225+1	-TS 4					
232		233			20	617	15		59	226+1	-TS 8					
233		234			20	617	16		63	227+1	-TS 12					
234		235			20	617	17		67	228+1	-TS 16					
235		236			20	617	18		71	229+1	-TS 20					TS 18 IS DEAD
236		237			20	617	19		75	230+1	-TS 24					TS 18 IS DEAD

ES.O. L.