

LAND SEISMIC RECORDING LOG

	CLIENT: Husky	PROSPECT: NPR-A	AREA: BARROW	LINE NO: 626N	
PARTY NO: 1182		INST. ENG: Stroff-Windham		DATE: MO 3 DAY 27 YR 79	

INSTRUMENT (9-TRACK)	<input checked="" type="checkbox"/> SYSTEM <input type="checkbox"/> 2 SYSTEMS	<input checked="" type="checkbox"/> 1-24 & 25-48 <input type="checkbox"/> 1-48 & 49-96	DDDS <input checked="" type="checkbox"/> A <input type="checkbox"/> B <input type="checkbox"/> C <input type="checkbox"/> D <input type="checkbox"/> E <input type="checkbox"/> F <input type="checkbox"/> G <input type="checkbox"/> H <input type="checkbox"/> I <input type="checkbox"/> J <input type="checkbox"/> K <input type="checkbox"/> L <input type="checkbox"/> M <input type="checkbox"/> N <input type="checkbox"/> O <input type="checkbox"/> P <input type="checkbox"/> Q <input type="checkbox"/> R <input type="checkbox"/> S <input type="checkbox"/> T <input type="checkbox"/> U <input type="checkbox"/> V <input type="checkbox"/> W <input type="checkbox"/> X <input type="checkbox"/> Y <input type="checkbox"/> Z	TYPE: <input type="checkbox"/> DFS III <input type="checkbox"/> DFS IV <input type="checkbox"/> DFS V <input type="checkbox"/> OTHER	<input checked="" type="checkbox"/> TRACK <input type="checkbox"/> 21 TRACK	FORMAT: B SEG:	<input type="checkbox"/> GAPPED <input type="checkbox"/> UNGAPPED	PACKING DENSITY: (LO) <input type="checkbox"/> 356 BPI (HI) <input type="checkbox"/> 712 BPI <input type="checkbox"/> 21 TRACK <input type="checkbox"/> 800 BPI <input type="checkbox"/> 1600 BPI			
NO. BYTES IN HEADER REC:		NO. BYTES IN RECORD ID:		NO. BYTES PER SCAN: 134		RECORD NUMBERS: <input checked="" type="checkbox"/> REC. <input type="checkbox"/> OCT.		GAIN CONSTANT: 36 db		INPUT IMPEDANCE: 20,000 ohms	


CONFIGURATION (MAG TAPE)	FIELD TRACE NOS.: 1-48 DATA CHANNEL NOS.: 1-48 (ON MAG TAPE)	AUXILIARY DATA: 1B 1H AUXILIARY CHANNEL NOS.: 3 4
-----------------------------	---	--

PARAMETER	RECORD LENGTH: 6 sec.	SAMPLE RATE: <input type="checkbox"/> 1 ms. <input type="checkbox"/> 4 ms.	GAIN MODE: <input type="checkbox"/> INITIAL <input type="checkbox"/> MANUAL <input checked="" type="checkbox"/> FINAL <input type="checkbox"/> OPERATE	FILTERS: FREQ. 8	LO CUT HZ SLOPE: 18	HI CUT HZ SLOPE: 70	NOTCH FILTER: <input type="checkbox"/> IN <input checked="" type="checkbox"/> OUT
DISPLAY	<input type="checkbox"/> FLOAT <input type="checkbox"/> AMPLIFIER <input checked="" type="checkbox"/> GGC <input type="checkbox"/> DEFOAT <input type="checkbox"/> DIRECT	INITIAL GAIN: 18 db	TRIP SENS: 18 db	POLARITY CONVENTION: <input type="checkbox"/> NEGATIVE <input checked="" type="checkbox"/> POSITIVE	PRESSURE INCREASE ON GEOPHONE: <input type="checkbox"/> NUMBERS ON MAG. TAPE	DOWNBREAK: <input type="checkbox"/> UPBREAK: <input type="checkbox"/> ON DISPLAY	
CFS I	TYPE STACK:	GATE LENGTH:	RECORD REJECTION:	NOISE REDUCTION:	NOISE THRESHOLD:	CORR. SCALING:	R.C.U. NORM/ALT SW.

SOURCE	TYPE: <input checked="" type="checkbox"/> DYNAMITE <input type="checkbox"/> VIBROSEIS <input type="checkbox"/> OTHER	PATTERN: Single hole - Inline	NO. OF POSITIONS: 18	INLINE SPACING: 12'	LATERAL SPACING:	STAGGER:	LENGTH:	WIDTH:	LATERAL OFFSET:		
CHG/ HOLE: 20		HOLE DEPTH: 75'		SWEEP START:		SWEEP END:		SWEEP TAPER:		PHASE COMP:	

RECEIVER	TYPE: GSC-20d	PATTERN: Inline	NO. OF ELEMENTS: 18	INLINE SPACING: 12'	LATERAL SPACING:	STAGGER:	LENGTH:	WIDTH:	LATERAL OFFSET:
CONNECTION: Series-Parallel		RESISTANCE: 560 ohms		STAGGER:		LENGTH:		LATERAL OFFSET:	

SPREAD	NO. OF GROUPS: 48	GROUP INTERVAL: 220'	SHOTPOINT INTERVAL: 880'	FOLD: 6	DIRECTION OF PROGRESSION: S → N
OFFSET GROUP 1: 5170		OFFSET GROUP 24 110'		OFFSET GROUP 48/100 : 5170	
LEADING GROUP: 48					



SHOTPOINT	TR 1 to 148		TR 15 to 296		SHOT		SPREAD		REMARKS	CORR. STACK						
	REEL NO.	REC.	REEL NO.	REC.	SIZE	DEPTH	NO.	OFFSET		DIR.	CDP SWITCH	LINE GROUPS	SET UP	TR 1-24	TR 25-48	TR 49-72
1	7511915	343	2223	2627	20	67	43	37	T1	-	6+4	6				
2		344			20	67	44	41	T5	-	7+4					
3		345			20	67	45	45	T9	-	8+4					
4		346			20	67	46	49	T3	-	9+4					
5		347			20	67	47	53	T17	-	10+4					
6		348			20	67	48	57	T21	-	11+4					
7		349			20	67	49	61	T1	-	12+4					

LAND SEISMIC RECORDING LOG

14.0 Hours

	CLIENT: Husky	PROSPECT: NPR-A	AREA: BARROW	LINE NO.: 626N	
PARTY NO.: 1182		INST. ENG.: Streff-windham		DATE: MO 3 DAY 28 YR 79	

INSTRUMENT (9-TRACK)	<input type="checkbox"/> 1 SYSTEM <input type="checkbox"/> 2 SYSTEMS	<input type="checkbox"/> 1-24 & 25-48 <input type="checkbox"/> 1-48 & 49-96	DDSS <input type="checkbox"/> EVENS	TYPE: <input type="checkbox"/> DFS III <input type="checkbox"/> DFS IV <input type="checkbox"/> OTHER	<input type="checkbox"/> TRACK <input type="checkbox"/> 21 TRACK	FORMAT: B SEG	<input type="checkbox"/> GAPPED <input type="checkbox"/> UNGAPPED	PACKING DENSITY: (L) <input type="checkbox"/> 356 BPI (H) <input type="checkbox"/> 712 BPI <input type="checkbox"/> 800 BPI <input type="checkbox"/> 1600 BPI			
NO. BYTES IN HEADER REC:		NO. BYTES IN RECORD ID:		NO. BYTES PER SCAN: 134		RECORD NUMBERS: <input checked="" type="checkbox"/> DEC. <input type="checkbox"/> OCT.		GAIN CONSTANT: 36 db		INPUT IMPEDANCE: 20,000 ohms.	


CONFIGURATION (MAG TAPE)	FIELD TRACE NOS.: 1-48 DATA CHANNEL NOS.: 1-48 (ON MAG TAPE)	AUXILIARY DATA: (1) 12 (2) UH (3) (4) (5) (6) (7)	AUXILIARY CHANNEL NOS.: 3 4
PARAMETER	RECORD LENGTH: 6 sec. SAMPLE RATE: <input type="checkbox"/> 1 ms. <input type="checkbox"/> 4 ms.	GAIN MODE: <input type="checkbox"/> INITIAL <input type="checkbox"/> MANUAL <input type="checkbox"/> FINAL <input type="checkbox"/> OPERATE	FILTERS: FREQ. 8 LO CUT HZ SLOPE 18

DISPLAY	MODE: <input type="checkbox"/> FLOAT <input type="checkbox"/> AMPLIFIER <input checked="" type="checkbox"/> AGC <input type="checkbox"/> DEFLOAT <input type="checkbox"/> DIRECT	INITIAL GAIN: 18 db	TRIP SENS.: 18 db	POLARITY CONVENTION:	PRESSURE INCREASE ON GEOPHONE:	<input type="checkbox"/> NEGATIVE <input type="checkbox"/> POSITIVE	NUMBERS ON ON MAG. TAPE	<input type="checkbox"/> DOWNBREAK <input type="checkbox"/> UPBREAK	ON DISPLAY
---------	---	----------------------------	--------------------------	----------------------	--------------------------------	--	-------------------------	--	------------

SOURCE	TYPE: <input checked="" type="checkbox"/> DYNAMITE <input type="checkbox"/> VIBROSEIS <input type="checkbox"/> OTHER	PATTERN: Single hole - In line	NO. OF POSITIONS: 18	INLINE SPACING:	LATERAL SPACING:	STAGGER:	LENGTH:	WIDTH:	LATERAL OFFSET:
--------	--	---------------------------------------	-----------------------------	-----------------	------------------	----------	---------	--------	-----------------

RECEIVER	TYPE: GSC-20d	PATTERN: In line	NO. OF ELEMENTS: 18	INLINE SPACING: 12'	LATERAL SPACING:
----------	----------------------	-------------------------	----------------------------	----------------------------	------------------



SPREAD	NO. OF GROUPS: 48	GROUP INTERVAL: 220'	SHOTPOINT INTERVAL: 880'	FOLD: 6	DIRECTION OF PROGRESSION: S → N
--------	--------------------------	-----------------------------	---------------------------------	----------------	--



SHOTPOINT	TR. 1 to 48		TR. to		SHOT				SPREAD		REMARKS	CORR. STACK	
	REEL NO.	REC.	REEL NO.	REC.	SIZE	DEPTH	NO.	OFFSET	DIR.	COP SWITCH		LINE GROUPS	TR 1-48
6	7511915	3162			20	617	1			29	2+1 - 13+4		
9		3163			20	617	2			33	3+1 - 14+4		
10		3164			20	617	3			37	4+1 - 15+4		
11		3165			20	617	4			29	5+1 - 16+4		
12		3166			20	617	5			33	6+1 - 17+4		
13		3167			20	617	6			37	7+1 - 18+4		
14		3168			20	617	7			41	8+1 - 19+4		
15		3169			20	617	8			45	9+1 - 20+4		
16		3170			20	617	9			49	10+1 - 21+4		
17		3171			20	617	10			29	11+1 - 22+4	3	Recorder @ SA22
18		3172			20	617	11			33	12+1 - 23+4		
19		3173			20	617	12			37	13+1 - 24+4		
20		3174			20	617	13			41	14+1 - 25+4		
21		3175			20	617	14			45	15+1 - 26+4		
22		3176			20	617	15			49	16+1 - 27+4		
23		3178			20	617	16			29	17+1 - 28+4	4	Recorder @ SA28-File # 377-misfile
24		3179			20	617	17			33	18+1 - 29+4		
25		3180			20	617	18			37	19+1 - 30+4		
26		3181			20	617	19			41	20+1 - 31+4		See Note
27		3182			20	617	20			45	21+1 - 32+4		

*NOTE SA26 shot out of Sequence - had to Redrill

LAND SEISMIC RECORDING LOG

	CLIENT: HASKY	PROSPECT: NPR-A	AREA: BARROW	LINE NO.: 626N	
PARTY NO.: 1182	INST. ENG.: STREFF-WINDHAM			DATE: MO 3 DAY 28 YR 79	
INSTRUMENT <small>(9-TRACK)</small>	<input checked="" type="checkbox"/> 1 SYSTEM <input checked="" type="checkbox"/> 2 SYSTEMS <small>NO. BYTES IN HEADER REC.</small>	<input checked="" type="checkbox"/> 1-24 & 25-48 <input checked="" type="checkbox"/> 1-48 & 49-96 <small>NO. BYTES IN RECORD ID:</small>	TYPE: <input checked="" type="checkbox"/> DFS III <input checked="" type="checkbox"/> DFS IV <input type="checkbox"/> OTHER	<input checked="" type="checkbox"/> TRACK <input checked="" type="checkbox"/> 21 TRACK <small>RECORD NUMBERS:</small>	FORMAT: SEG 8 <input checked="" type="checkbox"/> GAPPED <input type="checkbox"/> UNGAPPED <small>PACKING DENSITY:</small>
CONFIGURATION <small>(MAG TAPE)</small>	FIELD TRACE NOS.: 1-48 DATA CHANNEL NOS.: 1-48 <small>(ON MAG TAPE)</small>		<small>NO. BYTES PER SCAN:</small> 134	<small>GAIN CONSTANT:</small> 36 db <small>INPUT IMPEDANCE:</small> 20,000 ohms	
PARAMETER	<small>RECORD LENGTH:</small> 3.6 <small>MODE:</small> <input checked="" type="checkbox"/> FPGC <input type="checkbox"/> FLOAT <input type="checkbox"/> DEFLOAT <input type="checkbox"/> DIRECT	<small>SAMPLE RATE:</small> <input checked="" type="checkbox"/> 1 ms <input checked="" type="checkbox"/> 4 ms <input type="checkbox"/> 2 ms <small>INITIAL GAIN:</small> 518 db	<small>GAIN MODE:</small> <input type="checkbox"/> INITIAL <input type="checkbox"/> FINAL <input checked="" type="checkbox"/> MANUAL <input checked="" type="checkbox"/> OPERATE	<small>AUXILIARY DATA:</small> TB 014 <small>AUXILIARY CHANNEL NOS.:</small> 3 4 <small>FREQ.</small> 8 LO CUT HZ SLOPE 18 HI CUT HZ SLOPE 70 <small>FREQ.</small> 128 HI CUT HZ SLOPE 70	
DISPLAY	<small>TYPE STACK:</small> PT-85-F <small>GATE LENGTH:</small> _____		<small>JRIP SENS:</small> 18 db <small>RECORD REJECTION:</small> _____	<small>POLARITY CONVENTION:</small> <input type="checkbox"/> NEGATIVE <input checked="" type="checkbox"/> POSITIVE <small>PRESSURE INCREASE ON GEOPHONE:</small> <input type="checkbox"/> NUMBERS ON ON MAG. TAPE <input checked="" type="checkbox"/> UPBREAK <small>NOISE REDUCTION:</small> _____ <small>NOISE THRESHOLD:</small> _____ <small>CORR. SCALING:</small> _____ <small>R.C.U. NORM/ALT SW.</small> _____	
SOURCE	<small>TYPE:</small> <input checked="" type="checkbox"/> DYNAMITE <input type="checkbox"/> VIBROSEIS <input type="checkbox"/> OTHER		<small>PATTERN:</small> Single hole - Inline <small>CHG/ HOLE:</small> 20 <small>HOLE DEPTH:</small> 75'	<small>NO. OF POSITIONS:</small> _____ <small>SWEEP POSITION:</small> _____ <small>INLINE SPACING:</small> _____ <small>SWEEP START:</small> _____	<small>LATERAL SPACING:</small> _____ <small>SWEEP END:</small> _____ <small>STAGGER:</small> _____ <small>SWEEP LENGTH:</small> _____
RECEIVER	<small>TYPE:</small> GSC-20d <small>CONNECTION:</small> Series - Parallel	<small>PATTERN:</small> Inline <small>RESISTANCE:</small> 560 ohms	<small>NO. OF ELEMENTS:</small> 18 <small>STAGGER:</small> _____	<small>INLINE SPACING:</small> 12' <small>LENGTH:</small> _____ <small>WIDTH:</small> _____ <small>LATERAL OFFSET:</small> _____	
SPREAD	<small>NO. OF GROUPS:</small> 48 <small>OFFSET GROUP 1:</small> 5170'	<small>GROUP INTERVAL:</small> 220' <small>OFFSET GROUP 24:</small> 110'	<small>SHOTPOINT INTERVAL:</small> 860' <small>OFFSET GROUP 25:</small> 110'	<small>FOLD:</small> 6 <small>OFFSET GROUP 48:</small> 5170' <small>DIRECTION OF PROGRESSION:</small> S → N <small>LEADING GROUP:</small> 48	

DIAGRAMS/MISC. INFORMATION:

SHOTPOINT	TR. 1 to 48				TR. to				SHOT		SPREAD				REMARKS	CORR. STACK			
	REEL NO.	REC.	REEL NO.	REC.	SIZE	DEPTH	NO.	OFFSET	DIR.	CDP SWITCH	LINE GROUPS		SET UP	TR 1-48		TR 49-96	TR 1-48	TR 49-96	
28	383				20	6721	11			49	22+1	-33+4	4						
29	384				20	6722				53	23+1	-34+4							
30	386				20	6723				57	24+1	-35+4							
31	387				20	6724				61	25+1	-36+4							
32	388				20	6725				65	26+1	-37+4							
33	389				20	6726				69	27+1	-38+4							
34	390				20	6727				37	28+1	-39+4	5	Recorder @ SP-37					
35	391				20	6728				41	29+1	-40+4							
36	392				20	6729				45	30+1	-T4							
37	393				20	6730				49	31+1	-T8							
38	394				20	6731				53	32+1	-T12							
39	396				20	6732				57	33+1	-T16							
40	396				20	6733				61	34+1	-T20							
41	397				20	6734				65	35+1	-T24							
					E.O.I.														
											Picking up & moving to New Line								