



LAND SEISMIC RECORDING LOG

	CLIENT: Husky	PROSPECT: Southern Foothills	AREA: APP-A ALASKA	LINE NO.: 630						
	PARTY NO.: 1186	INST. ENG.: LEAVE BASE 7:00 AM. ARR. LHA 9:00 AM.	LEAVE FIELD 9:00 AM. ARR. BASE 10:30	DATE: NO. 02 DAY 25 TR 79						
INSTRUMENT (9-TRACK)	<input type="checkbox"/> 1 SYSTEM <input checked="" type="checkbox"/> 2 SYSTEMS	<input type="checkbox"/> 1-24 & 25-48 <input checked="" type="checkbox"/> 1-48 & 49-96	ODDS EVENTS: <input type="checkbox"/>	TYPE: <input type="checkbox"/> DFS III <input type="checkbox"/> DFS IX	<input type="checkbox"/> 1 TRACK <input type="checkbox"/> 2 TRACK	FORMAT: B	<input type="checkbox"/> GAPPED <input type="checkbox"/> UNGAPPED	PACKING DENSITY: (10) <input type="checkbox"/> 356 BPI (11) <input type="checkbox"/> 712 BPI (12) <input type="checkbox"/> 1400 BPI		
	NO. BYTES IN HEADER REC.: 128	NO. BYTES IN RECORD ID: _____	NO. BYTES PER SCAN: 254	RECORD NUMBERS: _____	<input type="checkbox"/> DEC. <input type="checkbox"/> OCT	GAIN CONSTANT: 36 db	INPUT IMPEDANCE: 20,000 ohms	(1) _____ (2) _____ (3) _____ (4) _____ (5) _____ (6) _____ (7) _____		
CONFIGURATION (MAG TAPE)	FIELD TRACE NOS.: 1-96	DATA CHANNEL NOS.: 1-96 (ON MAG TAPE)			AUXILIARY DATA: _____					
PARAMETER	RECORD LENGTH: 8 sec.	SAMPLE RATE: <input type="checkbox"/> 1 ms. <input type="checkbox"/> 4 ms. <input checked="" type="checkbox"/> 2 ms. <input type="checkbox"/> _____ ms.	GAIN MODE: <input type="checkbox"/> INITIAL <input checked="" type="checkbox"/> FINAL	<input type="checkbox"/> MANUAL <input checked="" type="checkbox"/> OPERATE	FILTERS: FREQ. 8	LO CUT FZ SLOPE 18	HI CUT FZ SLOPE 72	NOTCH FILTER: <input type="checkbox"/> IN <input checked="" type="checkbox"/> OUT		
DISPLAY	MODE: <input type="checkbox"/> AGC <input type="checkbox"/> FLOAT <input checked="" type="checkbox"/> DEFLOAT <input type="checkbox"/> DIRECT	AMPLIFIER: <input type="checkbox"/> DIRECT	INITIAL GAIN: _____ db	TRIP SENS.: _____ db	POLARITY CONVENTION: _____	PRESSURE INCREASE ON GEOPHONE: <input type="checkbox"/>	NEGATIVE POSITIVE	NUMBERS ON MAG. TAPE: <input type="checkbox"/>	DOWNBREAK UPBREAK ON DISPLAY	
CFS I	TYPE STACK: _____	GATE LENGTH: _____	RECORD REDUCTION: _____	NOISE THRESHOLD: _____	CORR. SCALING: _____	R.C.U. NORM./ALT SW. _____				
SOURCE	TYPE: <input checked="" type="checkbox"/> DYNAMITE <input type="checkbox"/> VIBROSEIS <input type="checkbox"/> OTHER	PATTERN: INLINE	NO. OF POSITIONS: _____	INLINE SPACING: _____	LATERAL SPACING: _____	STAGGER: _____	LENGTH: _____	WIDTH: _____	LATERAL OFFSET: _____	
RECEIVER	TYPE: Husky 10 Hz	PATTERN: INLINE	NO. OF ELEMENTS: 18	INLINE SPACING: _____	LATERAL SPACING: _____	STAGGER: _____	LENGTH: _____	WIDTH: _____	LATERAL OFFSET: _____	
SPREAD	CONNECTION: SERIES	RESISTANCE: _____ ohms	SWEEP POSITION: _____	SWEEP START: _____	SWEEP END: _____	SWEEP LENGTH: _____	SWEEP TAPER: _____	PHASE COMP. _____		
	NO. OF GROUPS: _____	GROUP INTERVAL: 320'	SHOTPOINT INTERVAL: 880'	FOLD: 1200 76	DIRECTION OF PROGRESSION: North → South	OFFSET GROUP 1: 10,450	OFFSET GROUP 48: 110'	OFFSET GROUP 49: 110'	OFFSET GROUP 48/76: 10,450	LEADING GROUP: 1-96 South



SHOTPOINT	TR. to		SHOT		DIA.	CDP SWITCH	LINE GROUPS	REMARKS	CORR. STACK	
	REEL NO.	REC.	REEL NO.	REC.					TR. 1-30	TR. 31-60
411	722600		722600	3V 1110 1015	11	5	399.1 422.4	TR 66 NOISY (ON 12B)		
412				32 1110 1015	12	5	400.1 423.4	" 62 "		
413				33 1110 1015	13	9	401.1 424.4	" 58 "		
414				34 1110 1015	14	13	402.1 425.4	" 54 "		
415				35 1110 1015	15	17	403.1 426.4	" 50 "		
416				36 1110 1015	16	21	404.1 427.4	" 46 "		
417				37 1110 1015	17	25	405.1 428.4	" 42 "		
418				38 1110 1015	18	29	406.1 429.4	" 38 "		
419				39 1110 1015	19	33	407.1 430.4	" 34 "		
420				40 1110 1015	20	37	408.1 431.4	" 30 "		
421				41 1110 1015	21	41	409.1 432.4	" 26 "		
422				42 1110 1015	22	45	410.1 433.4	" 22 "		
423				43 1110 1015	23	1	411.1 434.4	TRAC # 2 DEAD TR 18 NOISY		
424				44 1110 1015	24	5	412.1 435.4	TR 14 NOISY		
425				45 1110 1015	25	9	413.1 436.4	" 10 "		
426				46 1110 1015	26	13	414.1 437.4	" 6 "		
427				47 1110 1015	27	17	415.1 438.4	" 2 "		
428				48 1110 1015	28	21	416.1 439.4			
429				49 1110 1015	29	25	417.1 440.4			
430				50 1110 1015	30	29	418.1 441.4			

LAND SEISMIC RECORDING LOG

	CLIENT: <i>Husky</i>	PROSPECT: <i>Southern Foothills</i>	AREA: <i>NPR-A</i>	LINE NO.: <i>630</i>							
PARTY NO.: <i>1186</i>		INST. ENG.:		DATE: <i>MO 02 DAY 25 YR 79</i>							
INSTRUMENT [9-TRACK]	<input type="checkbox"/> 1 SYSTEM <input type="checkbox"/> 2 SYSTEMS	<input type="checkbox"/> 1-24 & 25-48 <input type="checkbox"/> 1-48 & 49-96	ODDS <input type="checkbox"/> EVENS	TYPE: <input type="checkbox"/> DFS III <input type="checkbox"/> DFS II <input type="checkbox"/> OTHER	<input type="checkbox"/> 9 TRACK <input type="checkbox"/> 21 TRACK	FORMAT: SEG	<input type="checkbox"/> GAPPED <input type="checkbox"/> UNGAPPED	PACKING DENSITY:	(10) <input type="checkbox"/> 356 BPI <input type="checkbox"/> 800 BPI	(11) <input type="checkbox"/> 712 BPI <input type="checkbox"/> 1600 BPI	
CONFIGURATION (MAG TAPE)	NO. BYTES IN HEADER REC.	NO. BYTES IN RECORD ID:	NO. BYTES PER SCAN:	RECORD NUMBERS:	<input type="checkbox"/> DEC. <input type="checkbox"/> OCT.	GAIN CONSTANT:	INPUT IMPEDANCE:				
PARAMETER	FIELD TRACE NOS.:	DATA CHANNEL NOS.:			AUXILIARY DATA:						
DISPLAY	MODE: <input type="checkbox"/> AOC <input type="checkbox"/> FLOAT <input type="checkbox"/> DEFLOAT <input type="checkbox"/> DIRECT	SAMPLE RATE: <input type="checkbox"/> 1 ms. <input type="checkbox"/> 2 ms. <input type="checkbox"/> 4 ms.	GAIN MODE: <input type="checkbox"/> IFF <input type="checkbox"/> INITIAL <input type="checkbox"/> FINAL <input type="checkbox"/> MANUAL <input type="checkbox"/> OPERATE	FILTERS: FREQ.	LO CUT HZ SLOPE	FREQ.	HI CUT HZ SLOPE	NOTCH FILTER:	<input type="checkbox"/> IN <input type="checkbox"/> OUT		
CFS I	TYPE STACK:	INITIAL GAIN:	TRIP SENS:	POLARITY CONVENTION:	PRESSURE INCREASE ON GEOPHONE:	<input type="checkbox"/> NEGATIVE <input type="checkbox"/> POSITIVE	NUMBERS ON MAG. TAPE	<input type="checkbox"/> DOWNBREAK <input type="checkbox"/> UPBREAK	ON DISPLAY		
SOURCE	TYPE: <input type="checkbox"/> DYNAMITE <input type="checkbox"/> VIBROSEIS <input type="checkbox"/> OTHER	PATTERN:	NO. OF POSITIONS:	INLINE SPACING:	LATERAL SPACING:	STAGGER:	LENGTH:	WIDTH:	LATERAL OFFSET:		
RECEIVER	CONNECTION:	RESISTANCE:	STAGGER:	LENGTH:	WIDTH:	LATERAL OFFSET:					
SPREAD	NO. OF GROUPS:	GROUP INTERVAL:	SHOTPOINT INTERVAL:	FOLD:	DIRECTION OF PROGRESSION:			LEADING GROUP:			

DIAGRAMS/MISC. INFORMATION:

SHOTPOINT	TR. to		TR. to		SHOT				SPREAD		REMARKS	CORR. STACK			
	REEL NO.	REC.	REEL NO.	REC.	SIZE	DEPTH	NO.	OFFSET	DIR.	COP SWITCH		LINE GROUPS	TR 1-21	TR 41-79	TR 81-96
431	722600	151			110	105	21			33	419.1	442.4			
432		52			110	105	22			37	420.1	443.4			
433		53			110	105	23			41	421.1	444.4			
434		54			110	105	24			45	422.1	445.4			
435	722600	56			110	105	25			1	423.1	446.4	3		Tape change File # 55 Dummy Rec.
436		57			110	105	26			5	424.1	447.4			
437		58			110	105	27			9	425.1	448.4			
438		59			110	105	28			13	426.1	449.4			
439		60			110	105	29			17	427.1	450.4			
440		61			110	105	30			21	428.1	451.4			
441		62			110	105	31			25	429.1	452.4			
442		63			110	105	32			29	430.1	453.4			
443		64			110	105	33			33	431.1	454.4			
444		65			110	105	34			37	432.1	455.4			
445		66			110	105	35			41	433.1	456.4			
446		67			110	105	36			45	434.1	457.4			
447		68			110	105	37			1	435.1	458.4	4		
448		69			110	105	38			5	436.1	459.4			Trace #1 Dead
449		70			110	105	39			9	437.1	460.4			
450		71			110	105	40			13	438.1	461.4			



LAND SEISMIC RECORDING LOG

CLIENT: Husky		PROSPECT: Southern Foothills		AREA: APR-A Alaska		LINE NO: 630	
PARTY NO: 1186		INST. ENG: Panko-Loss		LEAVE BASE - 7:00 AM ARR. Base - 9:00 AM		DATE: MO 02 DAY 26 YR 79	
INSTRUMENT: <input checked="" type="checkbox"/> 1 SYSTEM <input checked="" type="checkbox"/> 2 SYSTEMS		NO. BYTES IN HEADER REC: 128		NO. BYTES IN RECORD ID:		NO. BYTES PER SCAN: 254	
CONFIGURATION (MAG TAPE):		FIELD TRACE NOS.: 1-96		DATA CHANNEL NOS.: 1-96		AUXILIARY DATA:	
PARAMETER:		RECORD LENGTH: 9 sec.		SAMPLE RATE: <input type="checkbox"/> 1 ms <input type="checkbox"/> 4 ms <input checked="" type="checkbox"/> 2 ms		GAIN MODE: <input type="checkbox"/> INITIAL <input type="checkbox"/> MANUAL <input checked="" type="checkbox"/> FINAL	
DISPLAY:		MODE: <input type="checkbox"/> FLOAT <input type="checkbox"/> AMPLIFIER <input type="checkbox"/> DIRECT		INITIAL GAIN:		FILTERS:	
CFS I:		TYPE STACK:		GATE LENGTH:		RECORD REJECTION:	
SOURCE:		TYPE: <input checked="" type="checkbox"/> DYNAMITE <input type="checkbox"/> VIBROSEIS <input type="checkbox"/> OTHER		PATTERN: INLINE		NO. OF POSITIONS:	
RECEIVER:		TYPE: 660 10 Hz		PATTERN: INLINE		NO. OF ELEMENTS: 18	
CONNECTION: SERIES		RESISTANCE:		STAGGER:		INLINE SPACING:	
SPREAD:		NO. OF GROUPS:		GROUP INTERVAL: 220'		SHOTPOINT INTERVAL: 880'	
OFFSET GROUP 1: 10,450		OFFSET GROUP 48: 110'		OFFSET GROUP 49: 110'		FOLD: 1200%	
DIAGRAMS/MISC. INFORMATION:		NORTH: 10,340		SOUTH: 10,340		DIRECTION OF PROGRESSION: South	

North **10,340** → 48 4 49 → 10,340 → 96' South

SHOTPOINT	TR 10		TR 10		SHOT		SPREAD		REMARKS	CORR STACK		
	REEL NO.	REC.	REEL NO.	REC.	SIZE	DEPTH	NO.	OFFSET		DIR.	CDP SWITCH	LINE GROUPS
4519	1021	1071			1110	1015	1			1	447.1 470.4	X File # 80 → 88 Daily Tests File # 88-90 TEST T.B. Trace # 60, 68, 69 Trace # 50, 60, 68
4520	1022	1072			1110	1015	5		5	448.1 471.4		
4521	1023	1073			1110	1015	9		9	449.1 472.4		
4522	1024	1074			1110	1015	13		13	450.1 473.4		
4523	1025	1075			1110	1015	17		17	451.1 474.4		
4524	1026	1076			1110	1015	21		21	452.1 475.4		
4525	1027	1077			1110	1015	25		25	453.1 476.4		
4526	1028	1078			1110	1015	29		29	454.1 477.4		
4527	1029	1079			1110	1015	33		33	455.1 478.4		
4528	1030	1080			1110	1015	37		37	456.1 479.4		
4529	1031	1081			1110	1015	41		41	457.1 480.4		
4530	1032	1082			1110	1015	45		45	458.1 481.4		
4531	1033	1083			1110	1015	1		1	459.1 482.4	Trace change File # 101 Summary Rec. NOT USED	
4532	1034	1084			1110	1015	5		5	460.1 483.4		
4533	1035	1085			1110	1015	9		9	461.1 484.4		
4534	1036	1086			1110	1015	13		13	462.1 485.4		
4535	1037	1087			1110	1015	17		17	463.1 486.4		
4536	1038	1088			1110	1015	21		21	464.1 487.4		
4537	1039	1089			1110	1015	25		25	465.1 488.4		
4538	1040	1090			1110	1015	29		29	466.1 489.4	File # 110-112 NOT USED	

LAND SEISMIC RECORDING LOG

	CLIENT: <i>Husk</i>	PROSPECT: <i>Southern Foothills</i>	AREA: <i>NPR-A</i>	LINE NO: <i>630</i>							
PARTY NO: <i>1186</i>		INST. ENG:		DATE: <i>MO 2 DAY 26 YR 79</i>							
INSTRUMENT (9-TRACK)	<input type="checkbox"/> 1 SYSTEM	<input type="checkbox"/> 1-24 & 25-48	<input type="checkbox"/> ODDS EVENTS	TYPE: <input type="checkbox"/> DFS III	<input type="checkbox"/> DFS IV	<input type="checkbox"/> OTHER	<input type="checkbox"/> 9 TRACK	FORMAT: <input type="checkbox"/> SEG	<input type="checkbox"/> GAPPED	PACKING DENSITY: (LO) <input type="checkbox"/> 356 BPI	(HI) <input type="checkbox"/> 712 BPI
	<input type="checkbox"/> 2 SYSTEMS	<input type="checkbox"/> 1-48 & 49-96		<input type="checkbox"/> DFS III	<input type="checkbox"/> DFS IV	<input type="checkbox"/> OTHER	<input type="checkbox"/> 21 TRACK		<input type="checkbox"/> UNGAPPED	<input type="checkbox"/> 800 BPI	<input type="checkbox"/> 1000 BPI
NO. BYTES IN HEADER REC:	NO. BYTES IN RECORD ID:	NO. BYTES PER SCAN:	RECORD NUMBERS:	<input type="checkbox"/> DEC.	<input type="checkbox"/> OCT.	GAIN CONSTANT:	INPUT IMPEDANCE: (1) (2) (3) (4) (5) (6) (7)				
CONFIGURATION (MAG TAPE)	FIELD TRACE NOS.:	DATA CHANNEL NOS.:	AUXILIARY DATA:			AUXILIARY CHANNEL NOS.:					
PARAMETER	RECORD LENGTH: _____ sec.	SAMPLE RATE: <input type="checkbox"/> 1 ms. <input type="checkbox"/> 4 ms.	GAIN MODE: <input type="checkbox"/> INITIAL <input type="checkbox"/> MANUAL	FILTERS: _____		LO CUT HZ SLOPE: _____	HI CUT HZ SLOPE: _____	NOTCH FILTER: <input type="checkbox"/> IN <input type="checkbox"/> OUT			
DISPLAY	MODE: <input type="checkbox"/> AGC <input type="checkbox"/> FLOAT <input type="checkbox"/> DEFLAT <input type="checkbox"/> AMPLIFIER <input type="checkbox"/> DIRECT	INITIAL GAIN: _____ db	JRIP SENS: _____ db	POLARITY CONVENTION: <input type="checkbox"/> NEGATIVE <input type="checkbox"/> POSITIVE		PRESSURE INCREASE ON GEOPHONE: <input type="checkbox"/> NEGATIVE <input type="checkbox"/> POSITIVE		NUMBERS ON MAG. TAPE: <input type="checkbox"/> DOWNBREAK <input type="checkbox"/> UPBREAK	ON DISPLAY		
CFS I	TYPE STACK:	GATE LENGTH: _____	RECORD REJECTION: _____	NOISE REDUCTION: _____		NOISE THRESHOLD: _____	CORR. SCALING: _____	R.C.U. NORM/ALT SW.			
SOURCE	TYPE: <input type="checkbox"/> DYNAMITE <input type="checkbox"/> VIBROSEIS <input type="checkbox"/> OTHER	PATTERN: _____	NO. OF POSITIONS: _____	INLINE SPACING: _____	LATERAL SPACING: _____	STAGGER: _____	LENGTH: _____	WIDTH: _____	LATERAL OFFSET: _____		
RECEIVER	TYPE: _____	PATTERN: _____	NO. OF ELEMENTS: _____	RESISTANCE: _____ ohms	STAGGER: _____	INLINE SPACING: _____	LENGTH: _____	WIDTH: _____	LATERAL OFFSET: _____		
SPREAD	NO. OF GROUPS: _____	GROUP INTERVAL: _____	SHOTPOINT INTERVAL: _____	OFFSET GROUP 1: _____	OFFSET GROUP _____	FOLD: _____	OFFSET GROUP 48/96: _____	DIRECTION OF PROGRESSION: _____			

DIAGRAMS/MISC. INFORMATION:

SHOTPOINT	TR. _____ to _____		TR. _____ to _____		SHOT					DIR.	SPREAD		REMARKS:	CORR. STACK	
	REEL NO.	REC.	REEL NO.	REC.	SIZE	DEPTH	NO.	OFFSET	CDP SWITCH		LINE GROUPS	TR 48-96		TR 24-48	
479	2236	12	1115	17	11.10	105	21	11	33	467.1	490.4				
480		12	1115	17	11.10	105	22	11	37	468.1	491.4				
481		12	1115	17	11.10	105	23	11	41	469.1	492.4				
482		12	1115	17	11.10	105	24	11	45	470.1	493.4				
483		12	1115	17	11.0	105	25	11	1	471.1	494.4	3			
484		12	1115	17	11.0	105	26	11	5	472.1	495.4				
485		12	1115	17	11.0	105	27	11	9	473.1	496.4				
486		12	1115	17	11.0	105	28	11	13	474.1	497.4				
487		12	1115	17	11.0	105	29	11	17	475.1	498.4				
488		12	1115	17	11.0	105	30	11	21	476.1	499.4				
489		12	1115	17	11.0	105	31	11	25	477.1	500.4				
490		12	1115	17	11.0	105	32	11	29	478.1	501.4				
491		12	1115	17	11.0	105	33	11	33	479.1	502.4				
492		12	1115	17	11.0	105	34	11	37	480.1	503.4				
493		12	1115	17	11.0	105	35	11	41	481.1	504.4				
494		12	1115	17	11.0	105	36	11	45	482.1	505.4				
495		12	1115	17	11.0	105	37	11	1	483.1	506.4	4			
496		12	1115	17	11.0	105	38	11	5	484.1	507.4				
497		12	1115	17	11.0	105	39	11	9	485.1	508.4				
498		12	1115	17	11.0	105	40	11	13	486.1	509.4				

LAND SEISMIC RECORDING LOG

CLIENT: Husk		PROSPECT:		AREA:		LINE NO.: 630			
PARTY NO.: 1186		INST. ENG.:		DATE:		MO. 2 DAY 26 YR 79			
INSTRUMENT (9-TRACK)		NO. BYTES IN HEADER REC.:		NO. BYTES IN RECORD ID.:		NO. BYTES PER SCAN.:		RECORD NUMBERS:	
<input type="checkbox"/> 1 SYSTEM <input type="checkbox"/> 2 SYSTEMS		<input type="checkbox"/> 1-24 & 25-48 <input type="checkbox"/> 1-48 & 49-96		TYPE: <input type="checkbox"/> DES III <input type="checkbox"/> DES II <input type="checkbox"/> DFS <input type="checkbox"/> ODDS <input type="checkbox"/> EVENS		<input type="checkbox"/> 9 TRACK <input type="checkbox"/> 21 TRACK		FOMAT: <input type="checkbox"/> DEC. <input type="checkbox"/> OCT. <input type="checkbox"/> GAPPED <input type="checkbox"/> UNGAPPED	
CONFIGURATION (MAG TAPE)		FIELD TRACE NOS.:		DATA CHANNEL NOS.:		AUXILIARY DATA:		AUXILIARY CHANNEL NOS.:	
PARAMETER		RECORD LENGTH: _____ sec.		SAMPLE RATE: <input type="checkbox"/> 1 ms. <input type="checkbox"/> 4 ms. <input type="checkbox"/> 2 ms. <input type="checkbox"/> _____ ms.		GAIN MODE: <input type="checkbox"/> INITIAL <input type="checkbox"/> MANUAL <input type="checkbox"/> FINAL <input type="checkbox"/> IFF <input type="checkbox"/> OPERATE		FILTERS: _____	
DISPLAY		MODE: <input type="checkbox"/> FLOAT <input type="checkbox"/> AMPLIFIER <input type="checkbox"/> AGC <input type="checkbox"/> DEFLOAT <input type="checkbox"/> DIRECT		INITIAL GAIN: _____ db		TRIP SENS: _____ db		POLARITY CONVENTION: <input type="checkbox"/> PRESSURE INCREASE ON GEOPHONE <input type="checkbox"/> NEGATIVE <input type="checkbox"/> POSITIVE	
CFS I		TYPE STACK:		GATE LENGTH:		RECORD REJECTION:		NOISE REDUCTION: _____	
SOURCE		TYPE: <input type="checkbox"/> DYNAMITE <input type="checkbox"/> VIBROSEIS <input type="checkbox"/> OTHER		PATTERN:		NO. OF POSITIONS:		INLINE SPACING:	
RECEIVER		CONNECTION:		RESISTANCE: _____ ohms		STAGGER:		LENGTH:	
SPREAD		NO. OF GROUPS:		GROUP INTERVAL:		SHOTPOINT INTERVAL:		FOLD:	
		OFFSET GROUP 1:		OFFSET GROUP _____		OFFSET GROUP _____		OFFSET GROUP 48/96:	

DIAGRAMS/MISC. INFORMATION:

SHOTPOINT	TR _____ TO _____		YR _____ TO _____		SHOT					SPREAD		REMARKS:	CORR. STACK			
	REEL NO.	REC.	REEL NO.	REC.	SIZE	DEPTH	NO.	OFFSET	DIR.	CDP SWITCH	LINE GROUPS		TR 1-4	TR 5-8	TR 9-12	TR 13-16
509	222	102			11.0	105	41			17	487.1	510.4				
508		134			11.0	105	42			21	488.1	511.4				
5011		137			11.0	105	43			25	489.1	512.4				
5012		138			11.0	105	44			29	490.1	513.4				
5013		139			11.0	105	45			33	491.1	514.4				
5014		140			11.0	105	46			37	492.2	515.4				
5015		141			11.0	105	47	11.0	504.7	41	493.1	516.4				
5016		142			11.0	105	48			45	494.1	517.4				
5017		143			11.0	105	49			1	495.1	518.4				5
5018		144			11.0	105	50			5	496.1	519.4				
5019		146			11.0	105	51			9	497.1	520.4				
5010		147			11.0	105	52			13	498.1	521.4				
5011		148			11.0	105	53	11.0	504.7	17	499.1	522.4				7.5
5012		149			11.0	105	54			21	500.1	523.4				

TAPES CHANGE FILE 145 dummy.

TR 2 lead.
9.5 TR lead.

LAND SEISMIC RECORDING LOG

CLIENT: <u>Husky</u>		PROSPECT: <u>Southern Foothills</u>		AREA: <u>NPR-A</u>		LINE NO: <u>630</u>			
PARTY NO: <u>186</u>		INST. ENG: <u>Butch Lass</u>		Leave Base <u>700</u> Arrive Field <u>745</u>		Leave Field <u>830</u> Arrive Base <u>1000</u>		DATE: <u>MO 2 DAY 27 YR 74</u>	
INSTRUMENT: <input checked="" type="checkbox"/> 1 SYSTEM <input type="checkbox"/> 2 SYSTEMS NO. BYTES IN HEADER REC: <u>128</u>		TYPE: <input type="checkbox"/> DFS III <input type="checkbox"/> DFS IV <input type="checkbox"/> OTHER NO. BYTES IN RECORD 10: _____		RECORD NUMBERS: <input checked="" type="checkbox"/> 9 TRACK <input type="checkbox"/> 21 TRACK NO. BYTES PER SCAN: <u>251</u>		FOPMAT: <u>B</u> GAIN CONSTANT: <u>36</u> db		PACKING DENSITY: (L) <input type="checkbox"/> 356 BPI (H) <input type="checkbox"/> 712 BPI (M) <input type="checkbox"/> 600 BPI (L) <input type="checkbox"/> 1500 BPI	
CONFIGURATION (MAG TAPE): FIELD TRACE NOS.: <u>1-96</u> DATA CHANNEL NOS.: <u>1-96</u> (ON MAG TAPE)		AUXILIARY DATA: _____ AUXILIARY CHANNEL NOS.: _____		FILTERS: _____ FREQ: <u>8</u>		LO CUT HZ SLOPE: _____ HI CUT HZ SLOPE: _____		NOISE REDUCTION: _____ NOISE THRESHOLD: _____	
PARAMETER: RECORD LENGTH: <u>8</u> sec. DISPLAY: MODE: <input type="checkbox"/> AGC <input type="checkbox"/> FLOAT <input type="checkbox"/> DEFLOAT <input type="checkbox"/> AMPLIFIER <input type="checkbox"/> DIRECT		SAMPLE RATE: <input type="checkbox"/> 1 ms <input type="checkbox"/> 2 ms <input type="checkbox"/> 4 ms INITIAL GAIN: <u>0</u> db		GAIN MODE: <input type="checkbox"/> INITIAL <input type="checkbox"/> FINAL <input type="checkbox"/> MANUAL <input type="checkbox"/> OPERATE TRIP SENS: <u>0</u> db		POLARITY CONVENTION: _____ PRESSURE INCREASE ON GEOPHONE: <input type="checkbox"/> NEGATIVE <input type="checkbox"/> POSITIVE		NUMBERS ON MAG TAPE: _____ DOWNBREAK UPBREAK: <input type="checkbox"/> ON DISPLAY	
SOURCE: TYPE: <input checked="" type="checkbox"/> DYNAMITE <input type="checkbox"/> VIBROSEIS <input type="checkbox"/> OTHER PATTERN: <u>Single Hole</u>		NO. OF POSITIONS: _____ SWEEP POSITION: _____		INLINE SPACING: _____ SWEEP START: _____		LATERAL SPACING: _____ SWEEP END: _____		STAGGER: _____ SWEEP LENGTH: _____	
RECEIVER: TYPE: <u>70-0 10 HZ</u> CONNECTION: <u>Series</u>		PATTERN: <u>inline</u> RESISTANCE: _____ ohms		NO. OF ELEMENTS: <u>18</u> STAGGER: _____		INLINE SPACING: <u>15'</u> LENGTH: _____		LATERAL SPACING: _____ WIDTH: _____	
SPREAD: NO. OF GROUPS: <u>96</u> OFFSET GROUP 1: <u>1450'</u>		GROUP INTERVAL: <u>220'</u> OFFSET GROUP <u>48</u> <u>110'</u>		SHOTPOINT INTERVAL: <u>880'</u> OFFSET GROUP <u>44</u> <u>110'</u>		FOLD: <u>12</u> OFFSET GROUP <u>44/96</u> : <u>1450</u>		DIRECTION OF PROGRESSION: <u>North → South</u> LEADING GROUP: <u>96 → South</u>	



DIAGRAMS/MISC. INFORMATION:



SHOTPOINT	TR. 10		TR. 10		SHOT				SPREAD		REMARKS	CORR. STACK				
	REEL NO.	REC.	REEL NO.	REC.	SIZE	DEPTH	NO.	OFFSET	DIR.	CDP SWITCH		LINE GROUPS	TR. 10	TR. 10	TR. 10	TR. 10
5113	7246193	789			11.10	10.15	1			1	501.1	524.4				
5114		160			11.10	10.15	2			5	502.1	525.4				
5115		161			11.10	10.15	3			9	503.1	526.4				
5116		162			11.10	10.15	4			13	504.1	527.4				
5117		163			11.10	10.15	5			17	505.1	528.4				
5118		164			11.10	10.15	6	500A		21	506.1	529.4				
5119		165			11.10	10.15	7	1415 south		25	507.1	530.4				
5120		166			11.10	10.15	8			29	508.1	531.4				
5121		167			11.10	10.15	9			33	509.1	532.4				
5122		168			11.10	10.15	10			37	510.1	533.4				
5123		169			11.10	10.15	11			41	511.1	534.4				
5124		170			11.10	10.15	12			45	512.1	535.4				
5125		171			11.10	10.15	13			1	513.1	536.4	2			
5126		172			11.10	10.15	14			5	514.1	537.4				
5127		173			11.10	10.15	15			9	515.1	538.4				
5128		174			11.10	10.15	16	715 north		13	516.1	539.4				
5129		175			11.10	10.15	17	160 west		17	517.1	540.4				
5130		176			11.10	10.15	18			21	518.1	541.4				
5131		177			11.10	10.15	19			25	519.1	542.4				
5132		178			11.10	10.15	20			29	520.1	543.4				

LAND SEISMIC RECORDING LOG

page 2

	CLIENT: Husky	PROSPECT: Southern Frontiers	AREA: NPR-A	LINE NO.: 1230					
	PARTY NO.: 1186	INST. ENO.:		DATE: MO 2 DAY 27 YR 74					
INSTRUMENT (9-TRACK)	<input type="checkbox"/> 1 SYSTEM <input type="checkbox"/> 2 SYSTEMS	<input type="checkbox"/> 1-24 & 25-48 <input type="checkbox"/> 1-48 & 49-96	ODDS EVENS	TYPE: <input type="checkbox"/> DFS III <input type="checkbox"/> DFS IV	<input type="checkbox"/> 9 TRACK <input type="checkbox"/> 21 TRACK	FORMAT: SEG	<input type="checkbox"/> GAPPED <input type="checkbox"/> UNGAPPED	PACKING DENSITY: (LO) <input type="checkbox"/> 356 BPI <input type="checkbox"/> 800 BPI	(HI) <input type="checkbox"/> 712 BPI <input type="checkbox"/> 1600 BPI
	NO. BYTES IN HEADER REC.	NO. BYTES IN RECORD ID:	NO. BYTES PER SCAN:	RECORD NUMBERS:	<input type="checkbox"/> DEC. <input type="checkbox"/> OCT.	GAIN CONSTANT: _____ db	INPUT IMPEDANCE: _____ ohms.	(1) _____ (2) _____ (3) _____ (4) _____ (5) _____ (6) _____ (7) _____	
CONFIGURATION (MAG TAPE)	FIELD TRACE NOS. _____ DATA CHANNEL NOS. _____ (ON MAG TAPE)			AUXILIARY DATA: AUXILIARY CHANNEL NOS. _____					
PARAMETER	RECORD LENGTH: _____ sec.	SAMPLE RATE: <input type="checkbox"/> 1 sec. <input type="checkbox"/> 2 sec. <input type="checkbox"/> 4 sec. <input type="checkbox"/> 8 sec.	GAIN MODE: <input type="checkbox"/> INITIAL <input type="checkbox"/> FINAL <input type="checkbox"/> IFF <input type="checkbox"/> OPERATE	FILTERS: _____	LO CUT HZ SLOPE _____	FREQ. _____	HI CUT HZ SLOPE _____	NOTCH FILTER: <input type="checkbox"/> IN <input type="checkbox"/> OUT	
DISPLAY	MODE: <input type="checkbox"/> AGC <input type="checkbox"/> FLOAT <input type="checkbox"/> AMPLIFIER <input type="checkbox"/> DEFLOAT <input type="checkbox"/> DIRECT	INITIAL GAIN: _____ db	TRIP SENS: _____ db	POLARITY CONVENTION: _____	PRESSURE INCREASE ON GEOPHONE: <input type="checkbox"/> NEGATIVE <input type="checkbox"/> POSITIVE	NUMBERS ON MAG. TAPE	DOWNBREAK <input type="checkbox"/> UPBREAK	ON DISPLAY	
CFS I	TYPE STACK:	GATE LENGTH:	RECORD REJECTION:	NOISE REDUCTION:	NOISE THRESHOLD:	CORR. SCALING:	R.C.U. NORM./ALT SW.		
SOURCE	TYPE: <input type="checkbox"/> DYNAMITE <input type="checkbox"/> VIBROSEIS <input type="checkbox"/> OTHER	PATTERN: _____	NO. OF POSITIONS: _____	INLINE SPACING: _____	LATERAL SPACING: _____	STAGGER: _____	LENGTH: _____	WIDTH: _____	LATERAL OFFSET: _____
RECEIVER	CONNECTION: _____	PATTERN: _____	RESISTANCE: _____ ohms	STAGGER: _____	INLINE SPACING: _____	LENGTH: _____	WIDTH: _____	LATERAL OFFSET: _____	
SPREAD	NO. OF GROUPS: _____	GROUP INTERVAL: _____	SHOTPOINT INTERVAL: _____	FOLD: _____	DIRECTION OF PROGRESSION: _____	LEADING GROUP: _____			

DIAGRAMS/MISC. INFORMATION:

SHOTPOINT	TR. _____ TO _____		TR. _____ TO _____		SHOT				SPREAD		REMARKS	CORR. STACK					
	REEL NO.	REC.	REEL NO.	REC.	SIZE	DEPTH	NO.	OFFSET	DIR.	CDP SWITCH		LINE GROUPS	TR 1-48	TR 49-96	TR 1-48	TR 49-96	
	HT.	REC.	HT.	REC.									HT.	REC.	HT.	REC.	
1513	1213	16	2223	26	27	29	30	32	35	37	33	521.1	544.4				
1514	1180				110	1015	212	180	247	237	522.1	545.4					
1515	1181				110	1015	213			11	523.1	546.4					
1516	1182				110	1015	214	310	200	215	524.1	547.4					
1517	1183				110	1015	215			1	525.1	548.4					
1518	1184				110	1015	216			5	526.1	549.4					
1519	1185				110	1015	217			9	527.1	550.4					
1520	1186				110	1015	218	110	500	73	528.1	551.4					
1521	1187				110	1015	219			17	529.1	552.4					
1522	1188				110	1015	220			21	530.1	553.4					
1523	1189				110	1015	221			25	531.1	554.4					
1524	1190				110	1015	222			29	532.1	555.4					
1525	1191				110	1015	223	220	500	23	533.1	556.4					
1526	1192				110	1015	224	250	400	37	534.1	557.4					
1527	1193				110	1015	225			41	535.1	558.4					
1528	1194				110	1015	226			45	536.1	559.4					

File # 143 Dummy Rec. Not used

LAND SEISMIC RECORDING LOG

CLIENT: Husky		PROSPECT: Southern Foothills		AREA: NPR-A ALASKA		LINE NO.: 630			
PARTY NO.: 1186		INST. ENG.: PanKo - Boss		LEAVE BASE 7:00 AM ARR. FIELD 8:00 AM		LEAVE FIELD 9:00 P.M. ARR. BASE 10:00 P.M.		DATE: MO 12 DAY 28 YR 79	
INSTRUMENT: <input type="checkbox"/> 1 SYSTEM <input checked="" type="checkbox"/> 2 SYSTEMS <input type="checkbox"/> 1-24 & 25-48 <input type="checkbox"/> 1-48 & 49-96 <input type="checkbox"/> ODDS <input type="checkbox"/> EVENS		TYPE: <input type="checkbox"/> DFS III <input type="checkbox"/> DFS II <input type="checkbox"/> OTHER		<input type="checkbox"/> 9 TRACK <input type="checkbox"/> 21 TRACK		FORMAT: SEC. B		PACKING DENSITY: <input type="checkbox"/> 354 BPI <input type="checkbox"/> 800 BPI <input type="checkbox"/> 712 BPI <input type="checkbox"/> 1600 BPI	
NO. BYTES IN HEADER REC.: 128		NO. BYTES IN RECORD ID:		NO. BYTES PER SCAN: 254		RECORD NUMBERS: <input type="checkbox"/> DEC. <input type="checkbox"/> OCT.		GAIN CONSTANT: 36 db	
FIELD TRACE NOS.: 1-76		DATA CHANNEL NOS.: 1-96 [ON MAG TAPE]		AUXILIARY DATA:		AUXILIARY CHANNEL NOS.:		INPUT IMPEDANCE: 600 ohms	
RECORD LENGTH: 8 sec.		SAMPLE RATE: <input type="checkbox"/> 1 ms. <input type="checkbox"/> 4 ms. <input checked="" type="checkbox"/> 8 ms.		GAIN MODE: <input type="checkbox"/> INITIAL <input type="checkbox"/> FINAL <input type="checkbox"/> MANUAL <input type="checkbox"/> OPERATE		FILTERS: B		LO CUT HZ SLOPE: 18	
DISPLAY: <input checked="" type="checkbox"/> AGC <input type="checkbox"/> FLOAT <input type="checkbox"/> AMPLIFIER <input type="checkbox"/> DIRECT		INITIAL GAIN:		TRIP SENS:		POLARITY CONVENTION: <input type="checkbox"/> NEGATIVE <input type="checkbox"/> POSITIVE		PRESSURE INCREASE ON GEOPHONE:	
CFS I: <input type="checkbox"/> TYPE STACK		GATE LENGTH:		RECORD REJECTION:		NOISE REDUCTION:		CORR. SCALING:	
SOURCE: <input type="checkbox"/> DYNAMITE <input type="checkbox"/> VIBROSEIS <input type="checkbox"/> OTHER		PATTERN: SINGLE (LINE)		NO. OF POSITIONS:		INLINE SPACING:		LATERAL SPACING:	
RECEIVER: Next 10 Hz		PATTERN: In line		NO. OF ELEMENTS: 18		INLINE SPACING:		LATERAL SPACING:	
CONNECTION: Series		RESISTANCE:		STAGGER:		LENGTH:		WIDTH:	
SPREAD: 10,450		GROUP INTERVAL: 220'		SHOTPOINT INTERVAL: 880'		FOLD: 1200%		DIRECTION OF PROGRESSION: South	
OFFSET GROUP 1:		OFFSET GROUP 2:		OFFSET GROUP 3:		OFFSET GROUP 48/96:		LEADING GROUP: 96	

DIAGRAMS/MISC. INFORMATION:

10,340 → 48 49 → 10,340 → 96 South

SHOTPOINT	TR. NO. TO		TR. NO. TO		SHOT		SPREAD		REMARKS	CORR. STACK		
	REEL NO.	REC.	PEEL NO.	REC.	NO.	OFFSET	DIR.	CDP SWITCH		LINE GROUPS	TR. 48	TR. 96
5149	2226	14			110	105	1	1	537.1	560.4	1	
5150		210			110	105	2		538.1	561.4		
5151		211			110	105	3	56	539.1	562.4		
5152		212			110	105	4	230	540.1	563.4		
5153		213			110	105	5		541.1	564.4		
5154		214			110	105	6		542.1	565.4		
5155		215			110	105	7		543.1	566.4		
5156		216			110	105	8	N	544.1	567.4		
5157		217			110	105	9		545.1	568.4		
5158		218			110	105	10		546.1	569.4		
5159		219			110	105	11		547.1	570.4		
5160		220			110	105	12		548.1	571.4		
5161		221			110	105	13		549.1	572.4	2	
5162		222			110	105	14	160	550.1	573.4		
5163		223			110	105	15		551.1	574.4		
5164		224			110	105	16	30	552.1	575.4		
5165		225			110	105	17		553.1	576.4		
5166		226			110	105	18		554.1	577.4		
5167		227			110	105	19		555.1	578.4		
5168		228			110	105	20		556.1	579.4		

File # 194-206 Tests
 File # 207 TB test TR 49 NOISY
 File # 209 M.F.

575.3
 767.8
 24
 20
 16
 12


TR 96 dead. Lost 5th
 TR 85 NOISY Recorder was
 TR 88 dead. down.

72 dead.

48 dead

LAND SEISMIC RECORDING LOG

CLIENT: Husky		PROSPECT: Southern Foothills		AREA: NPR-19		LINE NO: 630			
PARTY NO: 1186		INST. ENG.:		LOGS: Leave Base 7:00 A.M. ARR Base 9:30 A.M.		DATE: MO 03 DAY 02 YR 79			
INSTRUMENT (9-TRACK):		<input type="checkbox"/> 1 SYSTEM <input checked="" type="checkbox"/> 2 SYSTEMS		TYPE: <input type="checkbox"/> DFS III <input type="checkbox"/> DFS IV <input type="checkbox"/> DFS V <input type="checkbox"/> OTHER		<input type="checkbox"/> 9 TRACK <input checked="" type="checkbox"/> 21 TRACK		GAIN CONSTANT: 36 db	
NO. BYTES IN HEADER REC: 128		NO. BYTES IN RECORD ID:		NO. BYTES PER SCAN: 254		RECORD NUMBERS:		INPUT IMPEDANCE: 20,000 ohms	
CONFIGURATION (MAG TAPE)		FIELD TRACE NOS.: 1-96		DATA CHANNEL NOS.: 1-96 (ON MAG TAPE)		AUXILIARY DATA:		AUXILIARY CHANNEL NOS.:	
PARAMETER		RECORD LENGTH: 8 sec.		SAMPLE RATE: <input type="checkbox"/> 1 ms. <input type="checkbox"/> 4 ms. <input checked="" type="checkbox"/> 2 ms.		GAIN MODE: <input checked="" type="checkbox"/> INITIAL <input type="checkbox"/> FINAL		FILTERS:	
DISPLAY		MODE: <input checked="" type="checkbox"/> AGC <input type="checkbox"/> FLOAT <input type="checkbox"/> DEFLOAT <input type="checkbox"/> DIRECT		INITIAL GAIN:		JIP SENS:		LO CUT HZ SLOPE: 18	
CFS I		TYPE STACK:		GATE LENGTH:		RECORD REJECTION:		HI CUT HZ SLOPE: 22	
SOURCE		TYPE: <input checked="" type="checkbox"/> DYNAMITE <input type="checkbox"/> VIBROSEIS <input type="checkbox"/> OTHER		PATTERN: IMLINE		NO. OF POSITIONS:		LO CUT HZ SLOPE: 18	
RECEIVER		CONNECTION: Series		RESISTANCE:		STAGGER:		INLINE SPACING: 115'	
SPREAD		NO. OF GROUPS:		GROUP INTERVAL: 220'		SHOTPOINT INTERVAL: 880'		FOLD: 1200%	
OFFSET GROUP 1: 10,450		OFFSET GROUP 48: 110'		OFFSET GROUP 49: 110'		OFFSET GROUP 96: 10,450		DIRECTION OF PROGRESSION: South	



SHOTPOINT	TR. 10		TR. 10		SHOT				SPREAD		REMARKS	CORR. STACK			
	REEL NO.	REC.	REEL NO.	REC.	SIZE	DEPTH	NO.	OFFSET	DIR.	CDP SWITCH		LINE GROUPS	REEL	REC.	REEL
15716	222606	1263			110	105	11			13	564.1	587.4			
15717		1264			110	105	12			17	565.1	588.4			
15718		1265			110	105	13			21	566.1	589.4			
15719		1266			110	105	14			25	567.1	590.4			
15810		1267			110	105	15			29	568.1	591.4			
15811		1268			110	105	16			33	569.1	592.4			
15812		1269			110	105	17			37	570.1	593.4			
15813		1270			110	105	18			41	571.1	594.4			
15814		1271			110	105	19			45	572.1	595.4			

REMARKS: **File 231-261 Day 7075**
File 262 Test 7B
Filtered - dump



LAND SEISMIC RECORDING LOG

	CLIENT: <i>Husky</i>	PROSPECT: <i>Southern Foothills</i>	AREA: <i>NPR-A</i>	LINE NO: <i>630</i>							
	PARTY NO: <i>1186</i>	INST. ENG: <i>Batch Lass</i>		DATE: <i>MO 3 DAY 3 YR 79</i>							
INSTRUMENT (9-TRACK)	<input checked="" type="checkbox"/> 1 SYSTEM <input type="checkbox"/> 2 SYSTEMS	<input type="checkbox"/> 1-24 & 25-48 <input type="checkbox"/> 1-48 & 49-96	ODDS EVENS <input type="checkbox"/>	TYPE: <input type="checkbox"/> DFS III <input type="checkbox"/> DFS IV	<input type="checkbox"/> DFS V <input type="checkbox"/> OTHER	<input type="checkbox"/> 9 TRACK <input type="checkbox"/> 21 TRACK	FORMAT: <i>SEG B</i>	<input type="checkbox"/> GAPPED <input type="checkbox"/> UNGAPPED	PACKING DENSITY: (L) <input type="checkbox"/> 356 BPI (H) <input type="checkbox"/> 800 BPI	(L) <input type="checkbox"/> 712 BPI (H) <input type="checkbox"/> 1500 BPI	
	NO. BYTES IN HEADER REC: <i>128</i>	NO. BYTES IN RECORD ID: _____	NO. BYTES PER SCAN: <i>254</i>	RECORD NUMBERS: <input type="checkbox"/> DEC. <input type="checkbox"/> OCT.	GAIN CONSTANT: _____ db	INPUT IMPEDANCE: _____ ohms.	AUXILIARY DATA: (1) _____ (2) _____ (3) _____ (4) _____ (5) _____ (6) _____ (7) _____				
CONFIGURATION (MAG TAPE)	FIELD TRACE NOS.: <i>1-96</i>		AUXILIARY CHANNEL NOS.: _____			DATA CHANNEL NOS.: <i>1-96</i> (ON MAG TAPE)					
PARAMETER	RECORD LENGTH: <i>8</i> sec.	SAMPLE RATE: <input checked="" type="checkbox"/> 1 ms. <input type="checkbox"/> 4 ms. <input type="checkbox"/> 16 ms.	GAIN MODE: <input type="checkbox"/> INITIAL <input checked="" type="checkbox"/> IFP	<input type="checkbox"/> MANUAL <input checked="" type="checkbox"/> OPERATE	FILTERS: FREQ. <i>8</i>	LO CUT HZ SLOPE: _____	HI CUT HZ SLOPE: <i>22</i>	NOTCH FILTER: <input type="checkbox"/> IN <input checked="" type="checkbox"/> OUT			
DISPLAY	MODE: <input type="checkbox"/> FLOAT <input type="checkbox"/> AMPLIFIER <input checked="" type="checkbox"/> AGC <input type="checkbox"/> DEFLOAT <input type="checkbox"/> DIRECT	INITIAL GAIN: _____ db	TRIP SENS: _____ db	POLARITY CONVENTION: <input type="checkbox"/> NEGATIVE <input checked="" type="checkbox"/> POSITIVE	PRESSURE INCREASE ON GEOPHONE: _____	NUMBERS ON MAG TAPE: _____	DOWNBREAK UPBREAK: <input type="checkbox"/> ON DISPLAY				
CFS I	TYPE STACK: _____	GATE LENGTH: _____	RECORD REJECTION: _____	NOISE REDUCTION: _____	NOISE THRESHOLD: _____	CORR. SCALING: _____	R.C.U. NORM/ALT SW. _____				
SOURCE	TYPE: <input checked="" type="checkbox"/> DYNAMITE <input type="checkbox"/> VIBROSEIS <input type="checkbox"/> OTHER	PATTERN: <i>Single hole</i>	NO. OF POSITIONS: _____	INLINE SPACING: _____	LATERAL SPACING: _____	STAGGER: _____	LENGTH: _____	WIDTH: _____	LATERAL OFFSET: _____		
RECEIVER	TYPE: <i>70-10</i>	PATTERN: <i>inline</i>	NO. OF ELEMENTS: <i>18</i>	STAGGER: _____	INLINE SPACING: <i>15'</i>	LENGTH: _____	WIDTH: _____	LATERAL OFFSET: _____			
SPREAD	NO. OF GROUPS: <i>96</i>	GROUP INTERVAL: <i>220</i>	SHOTPOINT INTERVAL: <i>980'</i>	OFFSET GROUP 1: _____	OFFSET GROUP 48: <i>110'</i>	FOLD: <i>17</i>	OFFSET GROUP 48/96: _____	DIRECTION OF PROGRESSION: <i>South</i> LEADING GROUP: <i>96</i>			

DIAGRAMS/MISC. INFORMATION: *SP*
North #1 10,340 → 49 110' 9 110 49 → 10,340 → 96 South

SHOTPOINT	TR. _____ to _____		TR. _____ to _____		SHOT		SPREAD		REMARKS	CORR. STACK				
	REEL NO.	REC.	REEL NO.	REC.	SIZE	DEPTH	NO.	OFFSET		TR 41	TR 48-96			
5815	222	10	17	22	23	26	27	29	30	32	35	37		
5816	222	10	17	22	23	26	27	29	30	32	35	37		
5817	222	10	17	22	23	26	27	29	30	32	35	37		
5818	222	10	17	22	23	26	27	29	30	32	35	37		
5819	222	10	17	22	23	26	27	29	30	32	35	37		
5820	222	10	17	22	23	26	27	29	30	32	35	37		
5821	222	10	17	22	23	26	27	29	30	32	35	37		
5822	222	10	17	22	23	26	27	29	30	32	35	37		
5823	222	10	17	22	23	26	27	29	30	32	35	37		
5824	222	10	17	22	23	26	27	29	30	32	35	37		
5825	222	10	17	22	23	26	27	29	30	32	35	37		
5826	222	10	17	22	23	26	27	29	30	32	35	37		
5827	222	10	17	22	23	26	27	29	30	32	35	37		
5828	222	10	17	22	23	26	27	29	30	32	35	37		
5829	222	10	17	22	23	26	27	29	30	32	35	37		
5830	222	10	17	22	23	26	27	29	30	32	35	37		
5831	222	10	17	22	23	26	27	29	30	32	35	37		
5832	222	10	17	22	23	26	27	29	30	32	35	37		
5833	222	10	17	22	23	26	27	29	30	32	35	37		
5834	222	10	17	22	23	26	27	29	30	32	35	37		
5835	222	10	17	22	23	26	27	29	30	32	35	37		
5836	222	10	17	22	23	26	27	29	30	32	35	37		
5837	222	10	17	22	23	26	27	29	30	32	35	37		
5838	222	10	17	22	23	26	27	29	30	32	35	37		
5839	222	10	17	22	23	26	27	29	30	32	35	37		
5840	222	10	17	22	23	26	27	29	30	32	35	37		
5841	222	10	17	22	23	26	27	29	30	32	35	37		
5842	222	10	17	22	23	26	27	29	30	32	35	37		
5843	222	10	17	22	23	26	27	29	30	32	35	37		
5844	222	10	17	22	23	26	27	29	30	32	35	37		
5845	222	10	17	22	23	26	27	29	30	32	35	37		
5846	222	10	17	22	23	26	27	29	30	32	35	37		
5847	222	10	17	22	23	26	27	29	30	32	35	37		
5848	222	10	17	22	23	26	27	29	30	32	35	37		
5849	222	10	17	22	23	26	27	29	30	32	35	37		
5850	222	10	17	22	23	26	27	29	30	32	35	37		
5851	222	10	17	22	23	26	27	29	30	32	35	37		
5852	222	10	17	22	23	26	27	29	30	32	35	37		
5853	222	10	17	22	23	26	27	29	30	32	35	37		
5854	222	10	17	22	23	26	27	29	30	32	35	37		
5855	222	10	17	22	23	26	27	29	30	32	35	37		
5856	222	10	17	22	23	26	27	29	30	32	35	37		
5857	222	10	17	22	23	26	27	29	30	32	35	37		
5858	222	10	17	22	23	26	27	29	30	32	35	37		
5859	222	10	17	22	23	26	27	29	30	32	35	37		
5860	222	10	17	22	23	26	27	29	30	32	35	37		
5861	222	10	17	22	23	26	27	29	30	32	35	37		
5862	222	10	17	22	23	26	27	29	30	32	35	37		
5863	222	10	17	22	23	26	27	29	30	32	35	37		
5864	222	10	17	22	23	26	27	29	30	32	35	37		
5865	222	10	17	22	23	26	27	29	30	32	35	37		
5866	222	10	17	22	23	26	27	29	30	32	35	37		
5867	222	10	17	22	23	26	27	29	30	32	35	37		
5868	222	10	17	22	23	26	27	29	30	32	35	37		
5869	222	10	17	22	23	26	27	29	30	32	35	37		
5870	222	10	17	22	23	26	27	29	30	32	35	37		
5871	222	10	17	22	23	26	27	29	30	32	35	37		
5872	222	10	17	22	23	26	27	29	30	32	35	37		
5873	222	10	17	22	23	26	27	29	30	32	35	37		
5874	222	10	17	22	23	26	27	29	30	32	35	37		
5875	222	10	17	22	23	26	27	29	30	32	35	37		
5876	222	10	17	22	23	26	27	29	30	32	35	37		
5877	222	10	17	22	23	26	27	29	30	32	35	37		
5878	222	10	17	22	23	26	27	29	30	32	35	37		
5879	222	10	17	22	23	26	27	29	30	32	35	37		
5880	222	10	17	22	23	26	27	29	30	32	35	37		
5881	222	10	17	22	23	26	27	29	30	32	35	37		
5882	222	10	17	22	23	26	27	29	30	32	35	37		
5883	222	10	17	22	23	26	27	29	30	32	35	37		
5884	222	10	17	22	23	26	27	29	30	32	35	37		
5885	222	10	17	22	23	26	27	29	30	32	35	37		
5886	222	10	17	22	23	26	27	29	30	32	35	37		
5887	222	10	17	22	23	26	27	29	30	32	35	37		
5888	222	10	17	22	23	26	27	29	30	32	35	37		
5889	222	10	17	22	23	26	27	29	30	32	35	37		
5890	222	10	17	22	23	26	27	29	30	32	35	37		
5891	222	10	17	22	23	26	27	29	30	32	35	37		
5892	222	10	17	22	23	26	27	29	30	32	35	37		
5893	222	10	17	22	23	26	27	29	30	32	35	37		
5894	222	10	17	22	23	26	27	29	30	32	35	37		
5895	222	10	17	22	23	26	27	29	30	32	35	37		
5896	222	10	17	22	23	26	27	29	30	32	35	37		
5897	222	10	17	22										

LAND SEISMIC RECORDING LOG

	CLIENT: Husky	PROSPECT: Southern Foothills	AREA: NPR-A ALASKA	LINE NO: 630	
PARTY NO: 1186		INST. ENG: PANKO-DELEDE		DATE: MO 03 DAY 22 YR 79	
LEAVE BASE - 7:00 A.M.		ARR. FIELD - 10:00 A.M.		LEAVE FIELD - 4:00	
ARR. BASE - 8:30					

INSTRUMENT (9-TRACK)	<input type="checkbox"/> 1 SYSTEM <input checked="" type="checkbox"/> 2 SYSTEMS	<input type="checkbox"/> 1-24 & 25-48 <input type="checkbox"/> 1-48 & 49-96	<input type="checkbox"/> ODDS <input type="checkbox"/> EVENS	TYPE: <input type="checkbox"/> DFS III <input type="checkbox"/> DFS II	<input checked="" type="checkbox"/> 9 TRACK <input type="checkbox"/> 21 TRACK	FORMAT: SEG B	<input type="checkbox"/> GAPPED <input type="checkbox"/> UNGAPPED	PACKING DENSITY: (LO) <input type="checkbox"/> 356 BPI <input type="checkbox"/> 800 BPI	(HI) <input type="checkbox"/> 712 BPI <input type="checkbox"/> 1600 BPI
NO. BYTES IN HEADER REC:	178	NO. BYTES IN RECORD ID:		NO. BYTES PER SCAN:	754	RECORD NUMBERS:	<input type="checkbox"/> DEC. <input type="checkbox"/> OCT.	GAIN CONSTANT: 36 db	INPUT IMPEDANCE: 20 ohms

CONFIGURATION (MAG TAPE)	FIELD TRACE NOS.: 1-96	AUXILIARY DATA: (1) (2) (3) (4) (5) (6) (7)
	DATA CHANNEL NOS.: 1-96	AUXILIARY CHANNEL NOS.:

PARAMETER	RECORD LENGTH: 8 sec.	SAMPLE RATE: <input type="checkbox"/> 1 ms. <input type="checkbox"/> 4 ms. <input checked="" type="checkbox"/> 2 ms. <input type="checkbox"/> ms.	GAIN MODE: <input checked="" type="checkbox"/> JFF <input type="checkbox"/> INITIAL <input type="checkbox"/> FINAL	FILTERS: <input type="checkbox"/> INITIAL <input type="checkbox"/> MANUAL <input type="checkbox"/> OPERATE	LO CUT HZ SLOPE 18	HI CUT HZ SLOPE 72	NOTCH FILTER: <input type="checkbox"/> IN <input checked="" type="checkbox"/> OUT
DISPLAY	MODE: <input type="checkbox"/> FLOAT <input type="checkbox"/> AMPLIFIER <input checked="" type="checkbox"/> DEFLOAT <input type="checkbox"/> DIRECT	INITIAL GAIN: _____ db	TRIP SENS: _____ db	POLARITY CONVENTION: <input type="checkbox"/> NEGATIVE <input type="checkbox"/> POSITIVE	PRESSURE INCREASE ON GEOPHONE: <input type="checkbox"/>	NUMBERS ON MAG. TAPE: <input type="checkbox"/>	DOWNBREAK UPBREAK ON DISPLAY: <input type="checkbox"/>
CFS I	TYPE STACK:	GATE LENGTH:	RECORD REJECTION:	NOISE REDUCTION:	NOISE THRESHOLD:	CORR. SCALING:	R.C.U. NORM/ALT SW.

SOURCE	TYPE: <input checked="" type="checkbox"/> DYNAMITE <input type="checkbox"/> VIBROSEIS <input type="checkbox"/> OTHER	PATTERN: Single (In line)	NO. OF POSITIONS:	INLINE SPACING:	LATERAL SPACING:	STAGGER:	LENGTH:	WIDTH:	LATERAL OFFSET:
	CHG/ HOLE: 110	HOLE DEPTH: 105	SWEEP POSITION:	SWEEP START:	SWEEP END:	SWEEP LENGTH:	SWEEP TAPER:	PHASE COMP:	

RECEIVER	TYPE: Hot 10 Hz	PATTERN: IN LINE	NO. OF ELEMENTS: 18	INLINE SPACING:	LATERAL SPACING:
	CONNECTION: SERIES	RESISTANCE: _____ ohms	STAGGER:	LENGTH:	WIDTH:



SPREAD	NO. OF GROUPS:	GROUP INTERVAL: 220'	SHOTPOINT INTERVAL: 880'	FOLD: 1200%	DIRECTION OF PROGRESSION: South
	OFFSET GROUP 1: 10,450	OFFSET GROUP 48 : 110'	OFFSET GROUP 49 : 110'	OFFSET GROUP 48/96 : 10,450	LEADING GROUP: 96

DIAGRAMS/MISC. INFORMATION:


North #1 $\xrightarrow{1,340}$ \rightarrow 48 $\xrightarrow{4}$ 49 $\xrightarrow{10,340}$ \rightarrow 96 South

SHOTPOINT	TR. _____ to _____		TR. _____ to _____		SHOT			SPREAD			REMARKS	CORR. STACK					
	REEL NO.	REC.	REEL NO.	REC.	SIZE	DEPTH	NO.	OFFSET	DIR.	CDP SWITCH		LINE GROUPS	SET UP	TR 1-48	TR 48-96	REC.	REC.
598	122613	14			N.P.	105	1			1	586.1	609.4					
599		15			N.P.	105	2			5	587.1	610.4					
600		16			N.P.	105	3			9	588.1	611.4					
601		17			N.P.	105	4			13	589.1	612.4					
602		18			N.P.	105	5			17	590.1	613.4					
603		19			N.P.	105	6	125' S 50' W		21	591.1	614.4					
604		20			N.P.	105	7	125' S		25	592.1	615.4					
605		21			N.P.	105	8			29	593.1	616.4					
606		22			N.P.	105	9	100' S		33	594.1	617.4					
607		23			N.P.	105	10	30' S		37	595.1	618.4					
608		24			N.P.	105	11			41	596.1	619.4					
609		25			N.P.	105	12			45	597.1	620.4					
610		26			N.P.	105	13			1	598.1	621.4					
611		27			N.P.	105	14			5	599.1	622.4					
612		28			N.P.	105	15	55' E		9	600.1	623.4					
613		29			N.P.	105	16	130' S		13	601.1	624.4					
614		30			N.P.	105	17	35' S		17	602.1	625.4					
615		31			N.P.	105	18	200' S		21	603.1	626.4					
616		32			N.P.	105	19			25	604.1	627.4					
617		33			N.P.	105	20	440' S		29	605.1	628.4					

LAND SEISMIC RECORDING LOG

	CLIENT: <i>Husky</i>	PROSPECT: <i>Southern Foothills</i>	AREA: <i>NPR-A Alaska</i>	LINE NO.: <i>630</i>	
PARTY NO.: <i>1186</i>		INST. ENG.: <i>Banko - DEBIDE</i>		DATE: <i>MO 03 DAY 23 YR 79</i>	
LEAVE BASE - <i>7:00 A.M.</i>		ARR. FIELD - <i>7:30 A.M.</i>		LEAVE FIELD - <i>9:00 P.M.</i>	
ARR. BASE - <i>11:00 A.M.</i>					
INSTRUMENT (9-TRACK): <input type="checkbox"/> 1 SYSTEM <input checked="" type="checkbox"/> 2 SYSTEMS		TYPE: <input type="checkbox"/> DFS I <input checked="" type="checkbox"/> DFS II <input type="checkbox"/> OTHER		FORMAT: <input checked="" type="checkbox"/> 9 TRACK <input type="checkbox"/> 21 TRACK	
NO. BYTES IN HEADER REC.: <i>128</i>		NO. BYTES IN RECORD ID: <i>254</i>		RECORD NUMBERS: <input type="checkbox"/> DEC. <input type="checkbox"/> OCT.	
GAIN CONSTANT: <i>36</i> db		INPUT IMPEDANCE: <i>20,000</i> ohms			
FIELD TRACE NOS.: <i>1-96</i>		AUXILIARY DATA:			
DATA CHANNEL NOS.: <i>1-96</i> (ON MAG TAPE)		AUXILIARY CHANNEL NOS.:			
RECORD LENGTH: <i>8</i> sec.		SAMPLE RATE: <input type="checkbox"/> 1 ms. <input type="checkbox"/> 4 ms. <input checked="" type="checkbox"/> 2 ms. <input type="checkbox"/> ms.		GAIN MODE: <input type="checkbox"/> INITIAL <input type="checkbox"/> MANUAL <input checked="" type="checkbox"/> FINAL <input type="checkbox"/> OPERATE	
MODE: <input type="checkbox"/> FLOAT <input type="checkbox"/> AMPLIFIER <input checked="" type="checkbox"/> AGC <input type="checkbox"/> DEFLOAT <input type="checkbox"/> DIRECT		INITIAL GAIN: <i>db</i>		TRIP SENS: <i>db</i>	
TYPE STACK:		GATE LENGTH:		RECORD REJECTION:	
TYPE: <input type="checkbox"/> DYNAMITE <input type="checkbox"/> VIBROSEIS <input type="checkbox"/> OTHER		PATTERN: <i>Single Line</i>		NO. OF POSITIONS:	
CHG/ HOLE: <i>110</i>		HOLE DEPTH: <i>105'</i>		SWEEP POSITION:	
TYPE: <i>West 101 1/2</i>		PATTERN: <i>In Line</i>		NO. OF ELEMENTS: <i>18</i>	
CONNECTION: <i>SERIES</i>		RESISTANCE: <i>ohms</i>		STAGGER:	
NO. OF GROUPS:		GROUP INTERVAL: <i>220'</i>		SHOTPOINT INTERVAL: <i>990'</i>	
OFFSET GROUP 1: <i>10,450</i>		OFFSET GROUP 49: <i>110'</i>		OFFSET GROUP 49/96: <i>10,450</i>	
TYPE: <i>West 101 1/2</i>		PATTERN: <i>In Line</i>		NO. OF ELEMENTS: <i>18</i>	
CONNECTION: <i>SERIES</i>		RESISTANCE: <i>ohms</i>		STAGGER:	
NO. OF GROUPS:		GROUP INTERVAL: <i>220'</i>		SHOTPOINT INTERVAL: <i>990'</i>	
OFFSET GROUP 1: <i>10,450</i>		OFFSET GROUP 49: <i>110'</i>		OFFSET GROUP 49/96: <i>10,450</i>	

DIAGRAMS/MISC. INFORMATION:



SHOTPOINT	TR. _____ TO _____		TR. _____ TO _____		SHOT			SPREAD			REMARKS:	CORR. STACK				
	REEL NO.	REC.	REEL NO.	REC.	SIZE	DEPTH	NO.	OFFSET	DIR.	CDP SWITCH		LINE GROUPS	SET UP	TR 1-48	TR 48-96	
													HT.	REC.	HT.	REC.
620	722613	50			110	105	1			1	610.1 633.4	1				
623		51			100	105	2	110'S	5	611.1 634.4						
624		52			110	105	3		9	612.1 635.4						
625		53			110	105	4		13	613.1 636.4						
626		54			110	105	5		17	614.1 637.4						
627		55			110	105	6		21	615.1 638.4						
628		56			110	105	7		25	616.1 639.4						
629		57			110	105	8		29	617.1 640.4						
630		58			110	105	9		33	618.1 641.4						
631		59			110	105	10		37	619.1 642.4						
632	722614	60			110	105	11		41	620.1 643.4						
633		61			110	105	12	110'S	45	621.1 644.4						
634		62			110	105	13		49	622.1 645.4						
635		63			110	105	14		5	623.1 646.4	2					
636		64			110	105	15	300' N	9	624.1 647.4						
637		65			110	105	16	150' N	13	625.1 648.4						
638		66			110	105	17	110' N	17	626.1 649.4						
639		67			110	110	18	20' S	21	627.1 650.4						
640		68			110	105	19	55' 35' W	25	628.1 651.4						
641		69			110	105	20	110' N	29	629.1 652.4						

96

LAND SEISMIC RECORDING LOG



CLIENT: Husky	PROSPECT: Southern Foothills	AREA: NPR-A ALASKA	LINE NO: 630
PARTY NO: 1186	INST. ENG:	DATE: MO 03 DAY 23 YR 79	

INSTRUMENT (9-TRACK)	<input type="checkbox"/> 1 SYSTEM <input type="checkbox"/> 2 SYSTEMS	<input type="checkbox"/> 1-24 & 25-48 <input type="checkbox"/> 1-48 & 49-96	ODDS EVENS <input type="checkbox"/> ODDS <input type="checkbox"/> EVENS	TYPE: <input type="checkbox"/> DFS III <input type="checkbox"/> DFS IV <input type="checkbox"/> OTHER	<input type="checkbox"/> 9 TRACK <input type="checkbox"/> 21 TRACK	FORMAT: SEG <input type="checkbox"/> GAPPED <input type="checkbox"/> UNGAPPED	PACKING DENSITY: (LO) <input type="checkbox"/> 356 BPI <input type="checkbox"/> 800 BPI (HI) <input type="checkbox"/> 712 BPI <input type="checkbox"/> 1600 BPI			
NO. BYTES IN HEADER REC:	NO. BYTES IN RECORD ID:	NO. BYTES PER SCAN:	RECORD NUMBERS:	<input type="checkbox"/> DEC. <input type="checkbox"/> OCT.	GAIN CONSTANT: _____ db	INPUT IMPEDANCE: _____ ohms.				
FIELD TRACE NOS.:	DATA CHANNEL NOS.:			(ON MAG TAPE)						
PARAMETER	RECORD LENGTH: _____ sec.	SAMPLE RATE: <input type="checkbox"/> 1 ms. <input type="checkbox"/> 4 ms. <input type="checkbox"/> 2 ms. <input type="checkbox"/> _____ ms.	GAIN MODE: <input type="checkbox"/> INITIAL <input type="checkbox"/> MANUAL <input type="checkbox"/> IFP <input type="checkbox"/> FINAL <input type="checkbox"/> OPERATE	FILTERS: _____	LO CUT HZ SLOPE _____	HI CUT HZ SLOPE _____	NOTCH FILTER: <input type="checkbox"/> IN <input type="checkbox"/> OUT			
DISPLAY	MODE: <input type="checkbox"/> FLOAT <input type="checkbox"/> AMPLIFIER <input type="checkbox"/> AGC <input type="checkbox"/> DEFLOAT <input type="checkbox"/> DIRECT	INITIAL GAIN: _____ db	JRIP SENS: _____ db	POLARITY CONVENTION: <input type="checkbox"/> NEGATIVE <input type="checkbox"/> POSITIVE	PRESSURE INCREASE ON GEOPHONE: <input type="checkbox"/> YES <input type="checkbox"/> NO	NUMBERS ON ON MAG. TAPE: _____	DOWNBREAK UPBREAK: <input type="checkbox"/> ON DISPLAY			
CFS I	TYPE STACK:	GATE LENGTH: _____	RECORD REJECTION:	NOISE REDUCTION:	NOISE THRESHOLD: _____	CORR. SCALING:	R.C.U. NORM/ALT SW.			
SOURCE	TYPE: <input type="checkbox"/> DYNAMITE <input type="checkbox"/> VIBROSEIS <input type="checkbox"/> OTHER	PATTERN:	NO. OF POSITIONS:	INLINE SPACING:	LATERAL SPACING:	STAGGER:	LENGTH: _____	WIDTH: _____	LATERAL OFFSET: _____	
RECEIVER	CONNECTION:	RESISTANCE: _____ ohms	CHG/ HOLE:	HOLE DEPTH:	SWEEP POSITION:	SWEEP START:	SWEEP END:	SWEEP LENGTH:	SWEEP TAPER:	PHASE COMP:
SPREAD	NO. OF GROUPS:	GROUP INTERVAL:	SHOTPOINT INTERVAL:	FOLD:	DIRECTION OF PROGRESSION:	LEADING GROUP:	OFFSET GROUP 1:	OFFSET GROUP 48/96:		

DIAGRAMS/MISC. INFORMATION:

SHOTPOINT	TR. _____ to _____		TR. _____ to _____		SHOT					SPREAD		REMARKS:	CORR. STACK	
	REEL NO.	REC.	REEL NO.	REC.	SIZE	DEPTH	NO.	OFFSET	DIR.	CDP SWITCH	LINE GROUPS		TR 1-48	TR 48-96
642	122	11	17	22	110	105	21	35	S	33	630.1	653.4		
643		12			110	105	32	135	S	37	631.1	654.4		
644		13			110	105	23	24	N	41	632.1	655.4		
645		14			110	105	24			45	633.1	656.4		
646		15			110	105	25			1	634.1	657.4		
647		16			110	105	26			5	635.1	658.4		
648		17			110	105	27			9	636.1	659.4		
649		18			110	105	28	30	N	13	637.1	660.4		
650		19			110	105	29	50	E	17	638.1	661.4		
651		20			110	105	30			21	639.1	662.4		
652		21			110	105	31	30	S	25	640.1	663.4	WAITING ON DRILL	
653		22			110	105	32	300	N	29	641.1	664.4		
654		23			110	105	33	40	N	33	642.1	665.4		
655		24			110	105	34			37	643.1	666.4		
656		25			110	105	35			41	644.1	667.4		
657		26			110	105	36			45	645.1	668.4		

LAND SEISMIC RECORDING LOG

Page #1 of 2

	CLIENT: Husky	PROSPECT: Southern Foothills	AREA: NPR-A ALASKA	LINE NO: 630	
PARTY NO: 1186		INST. ENG: DEREDE		DATE: MO 3 DAY 24 YR 79	
INSTRUMENT (9-TRACK)		TYPE: <input type="checkbox"/> DFS III <input checked="" type="checkbox"/> DFS IV <input type="checkbox"/> OTHER		RECORD NUMBERS: <input checked="" type="checkbox"/> DEC. <input type="checkbox"/> OCT.	
CONFIGURATION (MAG TAPE)		FIELD TRACE NOS.: -96		AUXILIARY DATA:	
PARAMETER		SAMPLE RATE: <input type="checkbox"/> 1ms <input type="checkbox"/> 4ms <input checked="" type="checkbox"/> 2ms		GAIN CONSTANT: 36 db	
DISPLAY		MODE: <input type="checkbox"/> AGC <input type="checkbox"/> DEFLOAT <input type="checkbox"/> DIRECT		INITIAL GAIN: _____ db	
SOURCE		PATTERN: SINGLE HOLE		NO. OF POSITIONS: _____	
RECEIVER		TYPE: H.S.T. 10HZ.		PATTERN: IN LINE	
SPREAD		NO. OF GROUPS: 96		GROUP INTERVAL: 220'	

DIAGRAMS/MISC. INFORMATION: **N** **S.P.** **S.**

#1 10340' #48 110' #49 110' #96 →

SHOTPOINT	TR. _____ to _____		TR. _____ to _____		SHOT				SPREAD		REMARKS	CORR. STACK		
	REEL NO.	REC.	REEL NO.	REC.	SIZE	DEPTH	NO.	OFFSET	DIR.	CDP SWITCH		#1 LINE GROUPS	TR 1-48	TR 49-96
658	722614	102			1.10	105	1	100	N	1	646.1	669.4		
659		103			1.10	105	2			5	647.1	670.4		
660		104			1.10	105	3	55	E	9	648.1	671.4		
661		105			1.10	105	4	30	N	13	649.1	672.4		
662		106			1.10	105	5			17	650.1	673.4		
663		107			1.10	105	6	70	W	21	651.1	674.4		
664		108			1.10	105	7	60	S	25	652.1	675.4		
665		109			1.10	105	8			29	653.1	676.4		
666		110			1.10	105	9			33	654.1	677.4		
667		111			1.10	105	10			37	655.1	678.4		
668		112			1.10	105	11	35	N	41	656.1	679.4		
669	722615	114			1.10	105	12	55	E	45	657.1	680.4		
670		115			1.10	105	13			1	658.1	681.4		
671		116			1.10	105	14			5	659.1	682.4		
672		117			1.10	105	15			9	660.1	683.4		
673		120			1.10	105	16	345	S	13	661.1	684.4		
674		121			1.10	105	17	20	N	17	662.1	685.4		
675		122			1.10	105	18			17	-	-		
676		123			1.10	105	19			-	-	-		
677		124			1.10	105	20	25	S	-	-	-		

SPE 95'

DAILY TESTS REC*87 TO REC*101

135' E INST 663.4 & 664.1

WAITING ON DRILL.

TAPE CHANGE

SKIP REC*113.

INST 675.4 & 676.1

LAST MILE OF LINE ROCKY TERRAIN

SKIP REC*118 & 119. →

NO TAIL SPREAD (LINE ENDS AT A CLIFF). WALKING SHOOTER THROUGH SPREAD.

