

# LAND SEISMIC RECORDING LOG

Page 1 of 2

	CLIENT: <b>Husky</b>	PROSPECT: <b>SOUTHERN FOOTHILLS</b>	AREA: <b>NPR-A ALASKA</b>	LINE NO: <b>632</b>					
	PARTY NO: <b>1196</b>	INST. ENG: <b>DELEDE</b>	LEAVE BASE: <b>LEAVE FIELD 10:30</b>	DATE: <b>MO 2 DAY 11 YR 79</b>					
			ARRIVE FIELD: <b>ARRIVE DATE 8:00</b>						
INSTRUMENT (9-TRACK)	<input type="checkbox"/> 1 SYSTEM <input checked="" type="checkbox"/> 2 SYSTEMS	<input type="checkbox"/> 1-24 & 25-48 <input type="checkbox"/> 1-48 & 49-96	ODDS EVENS	TYPE: <input type="checkbox"/> DFS III <input type="checkbox"/> DFS IX	<input type="checkbox"/> 9 TRACK <input type="checkbox"/> 21 TRACK	FORMAT SEG: <b>12</b>	<input type="checkbox"/> GAPPED <input type="checkbox"/> UNGAPPED	PACKING DENSITY: (LO) <input type="checkbox"/> 356 BPI <input type="checkbox"/> 800 BPI	(HI) <input type="checkbox"/> 712 BPI <input type="checkbox"/> 1600 BPI
	NO. BYTES IN HEADER REC: <b>128</b>	NO. BYTES IN RECORD ID: _____	NO. BYTES PER SCAN: <b>254</b>	RECORD NUMBERS: <input type="checkbox"/> DEC. <input type="checkbox"/> OCT.	GAIN CONSTANT: _____ db	INPUT IMPEDANCE: _____ ohms.			
CONFIGURATION (MAG TAPE)	FIELD TRACE NOS.: <b>1-96</b>			AUXILIARY DATA:			AUXILIARY CHANNEL NOS.:		
PARAMETER	RECORD LENGTH: <b>8</b> sec.	SAMPLE RATE: <input type="checkbox"/> 1ms <input type="checkbox"/> 4ms <input type="checkbox"/> 2ms <input type="checkbox"/> _____ ms.	GAIN MODE: <input type="checkbox"/> INITIAL <input checked="" type="checkbox"/> FINAL	<input type="checkbox"/> MANUAL <input type="checkbox"/> OPERATE	FILTERS: FREQ. <b>3</b>	LO CUT HZ SLOPE <b>18</b>	HI CUT HZ SLOPE <b>72</b>	NOTCH FILTER: <input type="checkbox"/> IN <input type="checkbox"/> OUT	
DISPLAY	MODE: <input type="checkbox"/> AGC <input type="checkbox"/> FLOAT <input type="checkbox"/> DEFLAT	<input type="checkbox"/> AMPLIFIER <input type="checkbox"/> DIRECT	INITIAL GAIN: _____ db	TRIP SENS: _____ db	POLARITY CONVENTION: <input type="checkbox"/> NEGATIVE <input checked="" type="checkbox"/> POSITIVE	PRESSURE INCREASE ON GEOPHONE: <input type="checkbox"/> NEGATIVE <input checked="" type="checkbox"/> POSITIVE	NUMBERS ON MAG. TAPE: <input type="checkbox"/> DOWNBREAK <input type="checkbox"/> UPBREAK	ON DISPLAY: <input type="checkbox"/> DOWNBREAK <input type="checkbox"/> UPBREAK	
CFS I	TYPE STACK:	GATE LENGTH:	RECORD REJECTION:	NOISE REDUCTION:	NOISE THRESHOLD:	CORR. SCALING:	R.C.U. NORM/ALT SW.		
SOURCE	TYPE: <input type="checkbox"/> DYNAMITE <input type="checkbox"/> VIBROSEIS <input type="checkbox"/> OTHER	PATTERN: <b>SINGLE HOLE</b>	NO. OF POSITIONS:	INLINE SPACING:	LATERAL SPACING:	STAGGER:	LENGTH:	WIDTH:	LATERAL OFFSET:
		CNG/HOLE: <b>115'</b>	HOLE DEPTH: <b>105'</b>	SWEEP POSITION:	SWEEP START:	SWEEP END:	SWEEP LENGTH:	SWEEP TAPER:	PHASE COMP:
RECEIVER	TYPE: <b>H.S.T 1047</b>	PATTERN: <b>IN LINE</b>	NO. OF ELEMENTS: <b>18</b>	INLINE SPACING: <b>15'</b>	LATERAL SPACING:	STAGGER:	LENGTH:	WIDTH:	LATERAL OFFSET:
	CONNECTION: <b>SERIES</b>	RESISTANCE: _____ ohms							
SPREAD	NO. OF GROUPS: <b>96</b>	GROUP INTERVAL: <b>220'</b>	SHOTPOINT INTERVAL: <b>980'</b>	FOLD: <b>1200%</b>	DIRECTION OF PROGRESSION: <b>SOUTH → NORTH</b>	OFFSET GROUP 1: <b>12450</b>	OFFSET GROUP 96: <b>10450</b>	LEADING GROUP:	



SHOTPOINT	TR. _____ TO _____		TR. _____ TO _____		SHOT				SPREAD		REMARKS	CORR. STACK		
	REEL NO.	REC.	REEL NO.	REC.	SIZE	DEPTH	NO.	OFFSET	DIR.	CDP SWITCH		# LINE GROUPS	TR. 41-48	TR. 49-96
269	722585	13	2223	2622	110	105	11	35	37	49	271.4	26.1		
270		14			110	105	12			45	272.4	26.1		
271		15			110	105	13			41	273.4	26.1		
272		16			110	105	14			37	274.4	26.1		
273		17			110	105	15			33	275.4	26.1		
274		18			110	105	16			29	276.4	26.1		
275		19			110	105	17			25	277.4	26.1		
276		20			110	105	18			21	278.4	26.1		
277		21			110	105	19			17	279.4	26.1		
278		22			110	105	20			13	280.4	26.1		
279		23			110	105	21			9	281.4	26.1		
280		24			110	105	22			5	282.4	26.1		
281		25			110	105	23	340	N	49	283.4	26.1		
282		26			110	105	24	510	N	45	284.4	26.1		
283		27			110	105	25			41	285.4	26.1		
284		28			110	105	26			37	286.4	26.1		
285		29			110	105	27	390	S	33	287.4	26.1		
286		30			110	105	28	110	S	29	288.4	26.1		
287		31			110	105	29			25	289.4	26.1		
288		32			110	105	30	790	S	21	290.4	26.1		

REMARKS: **DAILY TESTS REC#1 TO REC#12**

**INST 265.4 + 266.1**

**INST 277.4 + 278.1**

**\*95 noisy**

**WAITING ON DRILLS.**



# LAND SEISMIC RECORDING LOG

PAGE 1 OF 3

	CLIENT: <b>HUSA</b>	PROSPECT: <b>SOUTHERN FOOTHILLS</b>	AREA: <b>APR A ALASKA</b>	LINE NO: <b>632</b>					
	PARTY NO: <b>1183</b>	INST. ENG: <b>DE RUBE</b>	LEAVE FIELD <b>9:30</b>	DATE: <b>MO. 2 DAY 12 YR 79</b>					
			ARRIVE BASE <b>11:00</b>						
<b>INSTRUMENT</b>	<input type="checkbox"/> 1 SYSTEM <input type="checkbox"/> 2 SYSTEMS	<input type="checkbox"/> 1-24 & 25-48 <input type="checkbox"/> 1-48 & 49-96	CODES <input type="checkbox"/> ODDS <input type="checkbox"/> EVENS	TYPE: <input type="checkbox"/> DFS III <input type="checkbox"/> DFS IV <input type="checkbox"/> OTHER	<input type="checkbox"/> 9 TRACK <input type="checkbox"/> 21 TRACK	FORMAT: <b>B</b>	<input type="checkbox"/> GAPPED <input type="checkbox"/> UNGAPPED	PACKING DENSITY: (L) <input type="checkbox"/> 356 BPI (M) <input type="checkbox"/> 712 BPI (H) <input type="checkbox"/> 1400 BPI	
<b>(9-TRACK)</b>	NO. BYTES IN HEADER REC: <b>23</b>	NO. BYTES IN RECORD ID: _____	NO. BYTES PER SCAN: <b>254</b>	RECORD NUMBERS: <input type="checkbox"/> DEC. <input type="checkbox"/> OCT.	GAIN CONSTANT: <b>36</b> db	INPUT IMPEDANCE: <b>2000</b> ohms			
<b>CONFIGURATION (MAG TAPE)</b>	FIELD TRACE NOS.: <b>96</b>				AUXILIARY DATA: _____				
	DATA CHANNEL NOS.: <b>96</b> (ON MAG TAPE)				AUXILIARY CHANNEL NOS.: _____				
<b>PARAMETER</b>	RECORD LENGTH: <b>B</b> sec.	SAMPLE RATE: <input type="checkbox"/> 1 sec. <input type="checkbox"/> 4 sec.	GAIN MODE: <input type="checkbox"/> INITIAL <input type="checkbox"/> MANUAL <input type="checkbox"/> OPERATE	FILTERS: FREQ. <b>B</b>	LO CUT HZ SLOPE <b>18</b>	FREQ. <b>128</b>	HI CUT HZ SLOPE <b>72</b>	NOTCH FILTER: <input type="checkbox"/> IN <input type="checkbox"/> OUT	
<b>DISPLAY</b>	MODE: <input type="checkbox"/> FLOAT <input type="checkbox"/> AMPLIFIER <input type="checkbox"/> AGC <input type="checkbox"/> DEFLOAT <input type="checkbox"/> DIRECT	INITIAL GAIN: _____ db	TRIP SENS: _____ db	POLARITY CONVENTION: _____	PRESSURE INCREASE ON GEOPHONE: <input type="checkbox"/> NEGATIVE <input type="checkbox"/> POSITIVE	NUMBERS ON ON MAG. TAPE <input type="checkbox"/> DOWNBREAK <input type="checkbox"/> UPBREAK		ON DISPLAY	
<b>CFS I</b>	TYPE STACK: _____	GATE LENGTH: _____	RECORD REJECTION: _____	NOISE REDUCTION: _____	NOISE THRESHOLD: _____	CORR. SCALING: _____	R.C.U. NORM/ALT SW.		
<b>SOURCE</b>	TYPE: <input type="checkbox"/> DYNAMITE <input type="checkbox"/> VIBROSEIS <input type="checkbox"/> OTHER	PATTERN: <b>SINGLE HOLE</b>	NO. OF POSITIONS: _____	INLINE SPACING: _____	LATERAL SPACING: _____	STAGGER: _____	LENGTH: _____	WIDTH: _____	LATERAL OFFSET: _____
		CHO/HOLE: <b>110LP</b>	HOLE DEPTH: <b>105'</b>	SWEEP START: _____	SWEEP END: _____	SWEEP LENGTH: _____	SWEEP TAPER: _____	PHASE COMP: _____	
<b>RECEIVER</b>	TYPE: <b>H.S.T 10HZ.</b>	PATTERN: <b>IN LINE</b>	NO. OF ELEMENTS: <b>18</b>	INLINE SPACING: <b>15'</b>	LATERAL SPACING: _____	STAGGER: _____	LENGTH: _____	WIDTH: _____	LATERAL OFFSET: _____
	CONNECTION: <b>SERIES</b>	RESISTANCE: _____ ohms	STAGGER: _____	LENGTH: _____	WIDTH: _____	LATERAL OFFSET: _____			
<b>SPREAD</b>	NO. OF GROUPS: <b>96</b>	GROUP INTERVAL: <b>220'</b>	SHOTPOINT INTERVAL: <b>380'</b>	FOLD: <b>1200%</b>	DIRECTION OF PROGRESSION: <b>SOUTH → NORTH</b>				
	OFFSET GROUP 1: <b>10450'</b>	OFFSET GROUP <b>18</b> : <b>110'</b>	OFFSET GROUP <b>19</b> : <b>110'</b>	OFFSET GROUP <b>48(96)</b> : <b>10450'</b>	LEADING GROUP: <b>1</b>				

DIAGRAMS/MISC. INFORMATION: **SOUTH**

**SP. NORTH**

**96 10340' #49 110' #110' #48 10340' #1**

SHOTPOINT	TR. 1		TR. 2		SHOT		SPREAD		REMARKS:	CORR. STACK			
	REEL NO.	REC.	REEL NO.	REC.	SIZE	DEPTH	NO.	OFFSET		DIR.	COP SWITCH	LINE GROUPS	TR 1-48
289	225585	16	17	2223	110	105	11	35	37	49	272.1 295.4	1	DAILY TESTS REC#37 TO REC#45
285		17			110	105	12			45	273.1 296.4		INST 289.4 & 290.1 (*3 NOISY)
286		18			110	105	3	50	N	41	274.1 297.4		WAITING ON DRILLS
287		44			110	105	4			37	275.1 298.4		
288		50			110	105	5			33	276.1 299.4		
289		51			110	105	6			29	277.1 300.4		
290		52			110	105	7	30	S	25	278.1 301.4		
291		53			110	105	8	50	N	21	279.1 302.4		
292		54			110	105	9			17	280.1 303.4		
293		55			110	105	10			13	281.1 304.4		
294		56			110	105	11	105	E	9	282.1 305.4		
295		57			110	105	12			5	283.1 306.4		END OF TAPE
296	225586	58			110	105	13			49	284.1 307.4		REC#58 TEST INST 301.4 & 302.1
297		60			110	105	14			45	285.1 308.4		
298		61			110	105	15	40	S	41	286.1 309.4		
299		62			110	105	16	45	N	37	287.1 310.4		
300		63			110	105	17			33	288.1 311.4		
301		64			110	105	18			29	289.1 312.4		
302		65			110	105	19			-25	290.1 313.4		
303		66			110	105	20			21	291.1 314.4		

# LAND SEISMIC RECORDING LOG



Page #2 of 3

	CLIENT: Husky		PROSPECT: SOUTHERN FOOT HILLS		AREA: NPR-A ALASKA		LINE NO: 632		
	PARTY NO: 1186		INST. ENG:				DATE: MO 2 DAY 12 YR 79		
INSTRUMENT (9-TRACK)	<input type="checkbox"/> 1 SYSTEM <input type="checkbox"/> 2 SYSTEMS		<input type="checkbox"/> 1-24 & 25-48 <input type="checkbox"/> 1-48 & 49-96		TYPE: <input type="checkbox"/> DFS III <input type="checkbox"/> DFS II <input type="checkbox"/> OTHER		<input type="checkbox"/> 9-TRACK <input type="checkbox"/> 21-TRACK		
	NO. BYTES IN HEADER REC:		NO. BYTES IN RECORD ID:		NO. BYTES PER SCAN:		RECORD NUMBERS: <input type="checkbox"/> DEC. <input type="checkbox"/> OCT.		
CONFIGURATION (MAG TAPE)	FIELD TRACE NOS.:				AUXILIARY DATA:				
PARAMETER	DATA CHANNEL NOS.:				AUXILIARY CHANNEL NOS.:				
RECORDED LENGTH:	SAMPLE RATE: <input type="checkbox"/> 1 ms. <input type="checkbox"/> 4 ms. <input type="checkbox"/> 2 ms. <input type="checkbox"/> ms.		GAIN MODE: <input type="checkbox"/> INITIAL <input type="checkbox"/> MANUAL <input type="checkbox"/> IFF <input type="checkbox"/> OPERATE		FILTERS: FREQ. _____		LO CUT HZ SLOPE _____		
DISPLAY	MODE: <input type="checkbox"/> FLOAT <input type="checkbox"/> AMPLIFIER <input type="checkbox"/> AGC <input type="checkbox"/> DEFOAT <input type="checkbox"/> DIRECT		INITIAL GAIN: _____ db		TRIP SENS: _____ db		POLARITY CONVENTION: _____		
CFS I	TYPE STACK:		GATE LENGTH:		RECORD REJECTION:		NOISE REDUCTION:		
SOURCE	TYPE: <input type="checkbox"/> DYNAMITE <input type="checkbox"/> VIBROSEIS <input type="checkbox"/> OTHER		PATTERN:		NO. OF POSITIONS:		INLINE SPACING:		
RECEIVER	CONNECTION:		RESISTANCE: _____ ohms		STAGGER:		LATERAL SPACING:		
SPREAD	NO. OF GROUPS:		GROUP INTERVAL:		SHOTPOINT INTERVAL:		FOLD:		
DIAGRAMS/MISC. INFORMATION:		OFFSET GROUP 1:		OFFSET GROUP _____		OFFSET GROUP 48/96:		DIRECTION OF PROGRESSION: LEADING GROUP:	

SHOTPOINT	TR. _____ TO _____		TR. _____ TO _____		SHOT				SPREAD			REMARKS	CORR. STACK		
	REEL NO.	REC.	REEL NO.	REC.	SIZE	DEPTH	NO.	OFFSET	DIR.	CDP SWITCH	*96 LINE GROUPS * L		ST	TR 1-48	TR 48-96
304	727586	67			110	10521				17	292.1	315.4			
305		68			110	10522				13	293.1	316.4			
306		69			110	10523				9	294.1	317.4			
307		70			110	10524				5	295.1	318.4			
308		71			110	10525				49	296.1	319.4	3	INST 313.4 to 314.1	
309		72			110	10526				45	297.1	320.4			
310		73			110	10527				41	298.1	321.4			
311		74			110	10528				37	299.1	322.4			
312		75			110	10529				33	300.1	323.4			
313		76			110	10530				29	301.1	324.4			
314		77			110	10531				25	302.1	325.4			
315		78			110	10532				21	303.1	326.4			
316		79			110	10533				17	304.1	327.4			
317		80			110	10534				13	305.1	328.4			
318		81			110	10535				9	306.1	329.4			
319		82			110	10536				5	307.1	330.4			
320		83			110	10537				49	308.1	331.4		INST 325.4 to 326.1	
321		84			110	10538				45	309.1	332.4			
322		85			110	10539				41	310.1	333.4			
323		86			110	10540	65	N		37	311.1	334.4			

# LAND SEISMIC RECORDING LOG

Page 3 of 3

	CLIENT: <b>Husky</b>	PROSPECT: <b>SOUTHERN FOOT HILLS</b>	AREA: <b>N.P.R. - A ALASKA</b>	LINE NO.: <b>632</b>							
	PARTY NO.: <b>1186</b>	INST. ENG.:		DATE: <b>MO 2 DAY 12 YR 79</b>							
INSTRUMENT <b>(9-TRACK)</b>	<input type="checkbox"/> 1 SYSTEM <input type="checkbox"/> 2 SYSTEMS	<input type="checkbox"/> 1-24 & 25-48 <input type="checkbox"/> 1-48 & 49-96	ODDS <input type="checkbox"/> EVENS	TYPE: <input type="checkbox"/> DFS III <input type="checkbox"/> DFS III	<input type="checkbox"/> DFS IV <input type="checkbox"/> OTHER	<input type="checkbox"/> 9-TRACK <input type="checkbox"/> 21-TRACK	FORMAT: <input type="checkbox"/> SEG	<input type="checkbox"/> GAPPED <input type="checkbox"/> UNGAPPED	PACKING DENSITY: (L0) <input type="checkbox"/> 356 BPI <input type="checkbox"/> 800 BPI	(H1) <input type="checkbox"/> 712 BPI <input type="checkbox"/> 1600 BPI	
CONFIGURATION <b>(MAG TAPE)</b>	FIELD TRACE NOS.:	DATA CHANNEL NOS.:	(ON MAG TAPE)		AUXILIARY DATA:	AUXILIARY CHANNEL NOS.:					
PARAMETER	RECORD LENGTH: _____ sec.	SAMPLE RATE: <input type="checkbox"/> 1 ms. <input type="checkbox"/> 4 ms. <input type="checkbox"/> 2 ms. <input type="checkbox"/> _____ ms.	GAIN MODE: <input type="checkbox"/> INITIAL <input type="checkbox"/> IFF	<input type="checkbox"/> MANUAL <input type="checkbox"/> OPERATE	FILTERS: _____	LO CUT HZ SLOPE _____	FREQ. _____	HI CUT HZ SLOPE _____	NOISE FILTER: <input type="checkbox"/> IN <input type="checkbox"/> OUT		
DISPLAY	MODE: <input type="checkbox"/> FLOAT <input type="checkbox"/> AMPLIFIER <input type="checkbox"/> AGC <input type="checkbox"/> DEFOAT <input type="checkbox"/> DIRECT	INITIAL GAIN: _____ db	TRIP SENS: _____ db	POLARITY CONVENTION: _____	PRESSURE INCREASE ON GEOPHONE: <input type="checkbox"/> NEGATIVE <input type="checkbox"/> POSITIVE	NUMBERS ON MAG TAPE: <input type="checkbox"/> DOWNBREAK <input type="checkbox"/> UPBREAK	ON DISPLAY				
CFS I	TYPE STACK: _____	GATE LENGTH: _____	RECORD REJECTION: _____	NOISE REDUCTION: _____	NOISE THRESHOLD: _____	CORR. SCALING: _____	E.C.U. NORM/ALT SW.				
SOURCE	TYPE: <input type="checkbox"/> DYNAMITE <input type="checkbox"/> VIBROSEIS <input type="checkbox"/> OTHER	PATTERN: _____	NO. OF POSITIONS: _____	INLINE SPACING: _____	LATERAL SPACING: _____	STAGGER: _____	LENGTH: _____	WIDTH: _____	LATERAL OFFSET: _____		
RECEIVER	CONNECTION: _____	PATTERN: _____	RESISTANCE: _____ ohms	NO. OF ELEMENTS: _____	STAGGER: _____	INLINE SPACING: _____	LENGTH: _____	WIDTH: _____	LATERAL OFFSET: _____		
SPREAD	NO. OF GROUPS: _____	GROUP INTERVAL: _____	SHOTPOINT INTERVAL: _____	FOLD: _____	DIRECTION OF PROGRESSION: _____	OFFSET GROUP 1: _____	OFFSET GROUP _____	OFFSET GROUP 48/96: _____	LEADING GROUP: _____		


DIAGRAMS/MISC. INFORMATION:

SHOTPOINT	TR. _____ to _____		TR. _____ to _____		SHOT				SPREAD				REMARKS:	CORR. STACK				
	REEL NO.	REC.	REEL NO.	REC.	SIZE	DEPTH	NO.	OFFSET	DIR.	CDP SWITCH	*96 LINE GROUPS	*1		SEV UP	TR 1-48	TR 49-96	TR 49-96	TR 49-96
324	7235	86	87	2223	2627	2930	31	35	37	33	312.1	335.4						
325		88			110	105	42			29	313.1	336.4						
326		89			110	105	43			25	314.1	337.4						
327		90			110	105	44			21	315.1	338.4						
328		91			110	105	45			17	316.1	339.4						
329		92			110	105	46			13	317.1	340.4						
330		93			110	105	47			9	318.1	341.4						
331		94			110	105	48			5	319.1	342.4						

# LAND SEISMIC RECORDING LOG

Page 1 of 3

	CLIENT: Husky	PROSPECT: SOUTHERN FOOTHILLS	AREA: NPRCA ALASKA	LINE NO: 632					
PARTY NO: 486	INST. ENG: DE REDE	LEAVE BASE 7:00	ARRIVE FIELD 8:00	LEAVE FIELD 9:30	ARRIVE BASE 11:00				
DATE: MO 2 DAY 13 YR 79									
INSTRUMENT (9-TRACK)	<input type="checkbox"/> 1 SYSTEM <input checked="" type="checkbox"/> 2 SYSTEMS	<input type="checkbox"/> 1-24 & 25-48 <input checked="" type="checkbox"/> 1-48 & 49-96	<input type="checkbox"/> ODDS <input checked="" type="checkbox"/> EVENS	TYPE: <input type="checkbox"/> DFS <input checked="" type="checkbox"/> DFS	<input type="checkbox"/> 9 TRACK <input checked="" type="checkbox"/> 21 TRACK	FORMAT: SEG. B	<input type="checkbox"/> GAPPED <input type="checkbox"/> UNGAPPED	PACKING DENSITY: (L0) <input type="checkbox"/> 356 BPI <input type="checkbox"/> 800 BPI	(H1) <input type="checkbox"/> 712 BPI <input type="checkbox"/> 1600 BPI
	NO. BYTES IN HEADER REC: 128	NO. BYTES IN RECORD ID:	NO. BYTES PER SCAN: 254	RECORD NUMBERS: <input type="checkbox"/> DEC. <input type="checkbox"/> OCT.	GAIN CONSTANT: 36 db	INPUT IMPEDANCE: 20000 ohms.			
CONFIGURATION (MAG TAPE)	FIELD TRACE NOS.: 1-96	DATA CHANNEL NOS.: 1-96			AUXILIARY DATA: (1) (2) (3) (4) (5) (6) (7)				
PARAMETER	RECORD LENGTH: B sec.	SAMPLE RATE: <input type="checkbox"/> 1 ms. <input type="checkbox"/> 4 ms. <input checked="" type="checkbox"/> 2 ms.	GAIN MODE: <input type="checkbox"/> INITIAL <input checked="" type="checkbox"/> IFP	<input type="checkbox"/> MANUAL <input checked="" type="checkbox"/> OPERATE	FILTERS: FREQ. 8	LO CUT HZ SLOPE 18	FREQ. 128	HI CUT HZ SLOPE 72	NOTCH FILTER: <input type="checkbox"/> IN <input checked="" type="checkbox"/> OUT
DISPLAY	MODE: <input type="checkbox"/> AGC <input checked="" type="checkbox"/> FLOAT <input type="checkbox"/> DEFLOAT	<input type="checkbox"/> AMPLIFIER <input checked="" type="checkbox"/> DIRECT	INITIAL GAIN: db	TRIP SENS: db	POLARITY CONVENTION: <input type="checkbox"/> NEGATIVE <input checked="" type="checkbox"/> POSITIVE	PRESSURE INCREASE ON GEOPHONE: <input type="checkbox"/> NEGATIVE <input checked="" type="checkbox"/> POSITIVE	NUMBERS ON MAG. TAPE: <input type="checkbox"/> DOWNBREAK <input checked="" type="checkbox"/> UPBREAK	ON DISPLAY	
CFS I	TYPE STACK:	GATE LENGTH:	RECORD REJECTION:	NOISE REDUCTION:	NOISE THRESHOLD:	CORR. SCALING:	R.C.U. NORM/ALT SW.		
SOURCE	TYPE: <input type="checkbox"/> DYNAMITE <input type="checkbox"/> VIRROSEIS <input type="checkbox"/> OTHER	PATTERN: SINGLE HOLE	NO. OF POSITIONS:	INLINE SPACING:	LATERAL SPACING:	STAGGER:	LENGTH:	WIDTH:	LATERAL OFFSET:
RECEIVER	TYPE: H.S.T. 10 HZ.	PATTERN: IN LINE	NO. OF ELEMENTS: 10	INLINE SPACING: 15'	LATERAL SPACING:	STAGGER:	LENGTH:	WIDTH:	LATERAL OFFSET:
SPREAD	NO. OF GROUPS: 96	GROUP INTERVAL: 220'	SHOTPOINT INTERVAL: 880'	FOLD: 120090	DIRECTION OF PROGRESSION: SOUTH → NORTH	OFFSET GROUP 1: 10450'	OFFSET GROUP 48/96: 10450'	LEADING GROUP: 1	



SHOTPOINT	TR. 1 to		TR. 2 to		SHOT		SPREAD		REMARKS	CORR. STACK	
	REEL NO.	REC.	REEL NO.	REC.	SIZE	DEPTH	NO.	OFFSET		TR 1-48	TR 48-96
332	722586	1104			110	105	1	320.1	343.4	1	DAILY TESTS REC#95 TO REC#103
333		1105			110	105	2	321.1	344.4		INST 337.4 & 338.1
334	722587	1107			110	105	3	322.1	345.4		TAPE CHANGE
335		1108			110	105	4	323.1	346.4		REC#106 TEST
336		1109			110	105	5	324.1	347.4		
337		1111			110	105	6	325.1	348.4		SKIP REC#110
338		1112			110	105	7	326.1	349.4		
339		1113			110	105	8	327.1	350.4		*17 DEAD
340		1114			110	105	9	328.1	351.4		
341		1115			110	105	10	329.1	352.4		
342		1116			110	105	11	330.1	353.4		
343		1117			110	105	12	331.1	354.4		
344		1118			110	105	13	332.1	355.4	7	INST 349.4 & 350.1
345		1119			110	105	14	333.1	356.4		
346		1120			110	105	15	334.1	357.4		
347		1121			110	105	16	335.1	358.4		
348		1122			110	105	17	336.1	359.4		
349		1123			110	105	18	337.1	360.4		
350		1124			110	105	19	338.1	361.4		*5 DEAD
351		1125			110	105	20	339.1	362.4		SHOT AS S.P. 351 SHOOTER AT WRONG S.P. *5 DEAD.

# LAND SEISMIC RECORDING LOG

PAGE 2 OF 3



CLIENT: <b>Husky</b>	PROSPECT: <b>SOUTHERN FOOTHILLS</b>	AREA: <b>NPR-A ALASKA</b>	LINE NO: <b>632</b>
PARTY NO: <b>186</b>	INST. ENG.:	DATE: <b>MO 2 DAY 13 YR 79</b>	



INSTRUMENT (9-TRACK)	<input type="checkbox"/> 1 SYSTEM <input type="checkbox"/> 2 SYSTEMS	<input type="checkbox"/> 1-24 & 25-48 <input type="checkbox"/> 1-48 & 49-96	ODDS & EVENS	TYPE: <input type="checkbox"/> DFS III <input type="checkbox"/> DFS X <input type="checkbox"/> OTHER	<input type="checkbox"/> 9 TRACK <input type="checkbox"/> 21 TRACK	FORMAT: SEG	<input type="checkbox"/> GAPPED <input type="checkbox"/> UNGAPPED	PACKING DENSITY: (L) <input type="checkbox"/> 356 BPI (H) <input type="checkbox"/> 712 BPI <input type="checkbox"/> 1600 BPI	
NO. BYTES IN HEADER REC.	NO. BYTES IN RECORD ID	NO. BYTES PER SCAN	RECORD NUMBERS: <input type="checkbox"/> DEC. <input type="checkbox"/> OCT.	GAIN CONSTANT: (1) (2) (3) (4) (5) (6) (7)	INPUT IMPEDANCE: ohms.				
CONFIGURATION (MAG TAPE)	FIELD TRACE NOS.:				AUXILIARY DATA:				
PARAMETER	DATA CHANNEL NOS.:				AUXILIARY CHANNEL NOS.:				
DISPLAY	RECORD LENGTH: sec.	SAMPLE RATE: <input type="checkbox"/> 1 sec. <input type="checkbox"/> 4 sec. <input type="checkbox"/> 2 sec. <input type="checkbox"/> sec.	GAIN MODE: <input type="checkbox"/> INITIAL <input type="checkbox"/> FINAL <input type="checkbox"/> MANUAL <input type="checkbox"/> OPERATE	FILTERS: FREQ. LO CUT HZ SLOPE HI CUT HZ SLOPE	NOTCH FILTER: <input type="checkbox"/> IN <input type="checkbox"/> OUT				
CFS I	MODE: <input type="checkbox"/> AGC <input type="checkbox"/> FLOAT <input type="checkbox"/> AMPLIFIER <input type="checkbox"/> DEFLOAT <input type="checkbox"/> DIRECT	INITIAL GAIN: db	TRIP SENS: db	POLARITY CONVENTION: PRESSURE INCREASE ON GEOPHONE: <input type="checkbox"/> NEGATIVE <input type="checkbox"/> POSITIVE	NUMBERS ON MAG. TAPE: <input type="checkbox"/> DOWNBREAK <input type="checkbox"/> UPBREAK ON DISPLAY				
SOURCE	TYPE: <input type="checkbox"/> DYNAMITE <input type="checkbox"/> VIBROSEIS <input type="checkbox"/> OTHER	PATTERN:	NO. OF POSITIONS:	INLINE SPACING:	LATERAL SPACING:	STAGGER:	LENGTH:	WIDTH:	LATERAL OFFSET:
RECEIVER	CONNECTION:	RESISTANCE:	SWEEP POSITION:	SWEEP START:	SWEEP END:	SWEEP LENGTH:	SWEEP TAPER:	PHASE COMP:	
SPREAD	NO. OF GROUPS:	GROUP INTERVAL:	SHOTPOINT INTERVAL:	OFFSET GROUP:	FOLD:	OFFSET GROUP 48/96:	DIRECTION OF PROGRESSION:	LEADING GROUP:	

DIAGRAMS/MISC. INFORMATION:

SHOTPOINT	TR. to		TR. to		SHOT				CDP SWITCH	SPREAD		REMARKS:	CORR. STACK			
	REEL NO.	REC.	REEL NO.	REC.	SIZE	DEPTH	NO.	OFFSET		DIR.	LINE GROUPS		ST	TR 1-48	TR 48-96	TR 1-48
351	722587	126			1.10	1.05	21		21	339.1	362.4	*96 DEAD.				
353		127			1.10	1.05	22		13	341.1	364.4					
354		128			1.10	1.05	23		9	342.1	365.4					
355		129			1.10	1.05	24		5	343.1	366.4					
356		130			1.10	1.05	25		49	344.1	367.4	3 INST 361.4 & 362.1				
357		131			1.10	1.05	26		45	345.1	368.4					
358		132			1.10	1.05	27		41	346.1	369.4					
359		133			1.10	1.05	28		37	347.1	370.4					
360		134			1.10	1.05	29		37	347.1	370.4	WRONG CDP SHOT AS S.P. 359. (93-96 DEAD)				
361		135			1.10	1.05	30		29	349.1	372.4					
362		136			1.10	1.05	31		25	350.1	373.4					
363		137			1.10	1.05	32		21	351.1	374.4	*B DEAD.				
364		138			1.10	1.05	33		17	352.1	375.4					
365		139			1.10	1.05	34		13	353.1	376.4					
366		140			1.10	1.05	35		9	354.1	377.4					
367		141			1.10	1.05	36		5	355.1	378.4					
368		142			1.10	1.05	37		49	356.1	379.4	4 INST 373.4 & 374.1				
369		143			1.10	1.05	38		45	357.1	380.4					
370		144			1.10	1.05	39		41	358.1	381.4					
371		145			1.10	1.05	40		37	359.1	382.4					

# LAND SEISMIC RECORDING LOG

Page # 3 of 3

	CLIENT: <b>Husky</b>	PROSPECT: <b>Southern Foothills</b>	AREA: <b>NPR-A ALASKA</b>	LINE NO: <b>632</b>							
PARTY NO: <b>1186</b>		INST. ENG:		DATE: <b>MO 2 DAY 13 YR 79</b>							
INSTRUMENT (9-TRACK)	<input type="checkbox"/> 1 SYSTEM	<input type="checkbox"/> 1-24 & 25-48	<input type="checkbox"/> ODDS	TYPE: <input type="checkbox"/> DFS III	<input type="checkbox"/> DFS II	<input type="checkbox"/> 9 TRACK	FORMAT: <input type="checkbox"/> SEG	<input type="checkbox"/> GAPPED	PACKING DENSITY:	(LO) <input type="checkbox"/> 356 BPI	(HI) <input type="checkbox"/> 712 BPI
	<input type="checkbox"/> 2 SYSTEMS	<input type="checkbox"/> 1-48 & 49-96	<input type="checkbox"/> EVENS	<input type="checkbox"/> DFS III	<input type="checkbox"/> DFS II	<input type="checkbox"/> 21 TRACK	<input type="checkbox"/> UNGAPPED	<input type="checkbox"/> UNGAPPED		<input type="checkbox"/> 800 BPI	<input type="checkbox"/> 1600 BPI
NO. BYTES IN HEADER REC.	NO. BYTES IN RECORD ID:	NO. BYTES PER SCAN:	RECORD NUMBERS:	<input type="checkbox"/> DEC.	<input type="checkbox"/> OCT.	GAIN CONSTANT:	INPUT IMPEDANCE:		ohms		
CONFIGURATION (MAG TAPE)	FIELD TRACE NOS.:		AUXILIARY DATA:			AUXILIARY CHANNEL NOS.:					
PARAMETER	RECORD LENGTH:	SAMPLE RATE:	GAIN MODE:	<input type="checkbox"/> INITIAL	<input type="checkbox"/> MANUAL	FILTERS:	LO CUT	HI CUT	NOTCH	<input type="checkbox"/> IN	<input type="checkbox"/> OUT
DISPLAY	MODE: <input type="checkbox"/> AGC	<input type="checkbox"/> FLOAT	<input type="checkbox"/> AMPLIFIER	<input type="checkbox"/> IFF	<input type="checkbox"/> FINAL	<input type="checkbox"/> OPERATE	FREQ.	FREQ.	FREQ.	<input type="checkbox"/> DOWNBREAK	<input type="checkbox"/> UPBREAK
CFS I	TYPE STACK:	GATE LENGTH:	TRIP SENS:	POLARITY CONVENTION:		PRESSURE INCREASE ON GEOPHONE:	<input type="checkbox"/> NEGATIVE	<input type="checkbox"/> POSITIVE	NUMBERS ON MAG. TAPE	ON DISPLAY	
SOURCE	TYPE: <input type="checkbox"/> DYNAMITE	PATTERN:	NO. OF POSITIONS:	INLINE SPACING:	LATERAL SPACING:	STAGGER:	LENGTH:	WIDTH:	LATERAL OFFSET:	I.C.U. NORM./ALT SW.	
RECEIVER	CONNECTION:	RESISTANCE:	CHG/ HOLE:	HOLE DEPTH:	SWEEP POSITION:	SWEEP START:	SWEEP END:	SWEEP LENGTH:	SWEEP TAPER:	PHASE COMP.	
SPREAD	NO. OF GROUPS:	GROUP INTERVAL:	SHOTPOINT INTERVAL:	OFFSET GROUP:	FOLD:	OFFSET GROUP 48/96:	DIRECTION OF PROGRESSION:		LEADING GROUP:		



DIAGRAMS/MISC. INFORMATION:

SHOTPOINT	TR. _____ to _____		TR. _____ to _____		SHOT				SPREAD				REMARKS:	CORE STACK			
	REEL NO.	REC.	REEL NO.	REC.	SIZE	DEPTH	NO.	OFFSET	DIR.	COP SWITCH	LINE GROUPS	1		2	3	4	
372	722587	146			110	10541				33	360.1	383.4					
373		147			110	10542				29	361.1	384.4					
374	722588	148			110	10543				25	362.1	385.4	REC # 148 TEST				
375		150			110	10544				21	363.1	386.4					
376		151			110	10545				17	364.1	387.4					
377		152			110	10546				13	365.1	388.4					
378		153			110	10547				9	366.1	389.4					
379		154			110	10548				5	367.1	390.4					



# LAND SEISMIC RECORDING LOG

Page #1 of 3

	CLIENT: <b>Husky</b>	PROSPECT: <b>SOUTHERN FOOTHILLS</b>	AREA: <b>NPR-A ALASKA</b>	LINE NO: <b>632</b>	
PARTY NO: <b>1186</b>		INST. ENG: <b>SARDE</b>		DATE: <b>MO 2 DAY 15 YR 79</b>	
LEAVE BASE 1:00		ARRIVE FIELD 3:00		LEAVE FIELD 12:00	
ARRIVE BASE 11:00					

INSTRUMENT (9-TRACK)	<input type="checkbox"/> 1 SYSTEM <input checked="" type="checkbox"/> 2 SYSTEMS NO. BYTES IN HEADER REC: <b>128</b>	<input type="checkbox"/> 1-24 & 25-48 <input type="checkbox"/> 1-48 & 49-96 NO. BYTES IN RECORD ID: _____	TYPE: <input type="checkbox"/> DFS III <input type="checkbox"/> DFS IX <input type="checkbox"/> DFS X <input type="checkbox"/> OTHER _____	<input type="checkbox"/> 9 TRACK <input type="checkbox"/> 21 TRACK RECORD NUMBERS: <input type="checkbox"/> DEC. <input type="checkbox"/> OCT.	FOMAT: <b>B</b> SEG _____ <input type="checkbox"/> GAPPED <input type="checkbox"/> UNGAPPED PACKING DENSITY: (LO) <input type="checkbox"/> 356 BPI (HI) <input type="checkbox"/> 712 BPI <input type="checkbox"/> 1500 BPI	
CONFIGURATION (MAG TAPE)	FIELD TRACE NOS.: <b>1-16</b>		AUXILIARY DATA: _____		AUXILIARY CHANNEL NOS.: _____	
PARAMETER	RECORD LENGTH: <b>8</b>	SAMPLE RATE: <input type="checkbox"/> 1ms. <input type="checkbox"/> 4ms. <input type="checkbox"/> 2ms. <input type="checkbox"/> _____	GAIN MODE: <input type="checkbox"/> INITIAL <input type="checkbox"/> MANUAL <input type="checkbox"/> OPERATE	FILTERS: FREQ. <b>B</b> LO CUT HZ SLOPE <b>15</b>	H CUT HZ SLOPE <b>12</b>	NOTCH FILTER: <input type="checkbox"/> IN <input type="checkbox"/> OUT
DISPLAY	MODE: <input type="checkbox"/> AGC <input type="checkbox"/> FLOAT <input type="checkbox"/> DEFOAT <input type="checkbox"/> AMPLIFIER <input type="checkbox"/> DIRECT	INITIAL GAIN: _____	TRIP SENS: _____	POLARITY CONVENTION: _____	PRESSURE INCREASE ON GEOPHONE: <input type="checkbox"/> NEGATIVE <input type="checkbox"/> POSITIVE	NUMBERS ON MAG. TAPE <input type="checkbox"/> DOWNBREAK <input type="checkbox"/> UPBREAK ON DISPLAY
CFS I	TYPE STACK: _____	GATE LENGTH: _____	RECORD REJECTION: _____	NOISE REDUCTION: _____	NOISE THRESHOLD: _____	CORR. SCALING: _____ R.C.U. NORM/ALT SW
SOURCE	TYPE: <input type="checkbox"/> DYNAMITE <input type="checkbox"/> VIBROSEIS <input type="checkbox"/> OTHER	PATTERNS: <b>SINGLE HOLE</b>	NO. OF POSITIONS: _____	INLINE SPACING: _____	LATERAL SPACING: _____	STAGGER: _____ LENGTH: _____ WIDTH: _____ LATERAL OFFSET: _____
RECEIVER	TYPE: <b>H.S.T 10 HZ.</b>	PATTERN: <b>1 N LINE</b>	NO. OF ELEMENTS: <b>18</b>	INLINE SPACING: <b>15'</b>	LATERAL SPACING: _____	STAGGER: _____ LENGTH: _____ WIDTH: _____ LATERAL OFFSET: _____
SPREAD	CONNECTION: <b>SERIES</b>	RESISTANCE: _____	STAGGER: _____	LENGTH: _____	WIDTH: _____	LATERAL OFFSET: _____
	NO. OF GROUPS: <b>46</b>	GROUP INTERVAL: <b>220'</b>	SHOTPOINT INTERVAL: <b>880'</b>	FOLD: <b>1200%</b>	DIRECTION OF PROGRESSION: <b>SOUTH → NORTH</b>	LEADING GROUP: <b>L</b>
	OFFSET GROUP 1: <b>10450'</b>	OFFSET GROUP: <b>48, 110'</b>	OFFSET GROUP: <b>49, 110'</b>	OFFSET GROUP 48/96: <b>10450'</b>		



DIAGRAMS/MISC. INFORMATION **SOUTH ST.**

#76 10340' #49 110' #48 10340' #1 →

SHOTPOINT	TR. 1 to		TR. 2 to		SHOT		SPREAD		REMARKS	CORR. STACK									
	REEL NO.	REC.	REEL NO.	REC.	SIZE	DEPTH	NO.	OFFSET		DIR.	CDP SWITCH	LINE GROUPS	TR 1-48	TR 49-96					
380	722588	164	17	2223	26	29	30	25	35	37	49	368.1	391.4	1	INST 385.4 & 386.1				
381		166									45	369.1	392.4		SKIP REC # 155				
384		161									41	370.1	393.4						
385		160									37	371.1	394.4						
387		169									33	372.1	395.4						
382		170									29	373.1	396.4						
386		171									25	374.1	397.4						
387		172									21	375.1	398.4						
388		173									17	376.1	399.4						
389		174									13	377.1	400.4						
390		175									9	378.1	401.4						
391		176									5	379.1	402.4						
392		177									49	380.1	403.4	2	INST 397.4 & 398.1				
393		178									45	381.1	404.4						
394		179									41	382.1	405.4						
395		180									37	383.1	406.4						
396		181									33	384.1	407.4						
397		182									29	385.1	408.4						
398		183									25	386.1	409.4						
399		184									21	387.1	410.4						

# LAND SEISMIC RECORDING LOG

Page 2 of 3

	CLIENT: <i>Husky</i>	PROSPECT: <i>Southern Foothills</i>	AREA: <i>NPR-A</i>	LINE NO: <i>632</i>						
PARTY NO: <i>1186</i>		INST. ENG.:		DATE: <i>MO 2 DAY 14 YR 79</i>						
INSTRUMENT (9-TRACK)	<input type="checkbox"/> 1 SYSTEM <input type="checkbox"/> 2 SYSTEMS	<input type="checkbox"/> 1-24 & 25-48 <input type="checkbox"/> 1-48 & 49-96	ODDS & EVENS	TYPE: <input type="checkbox"/> DFS III <input type="checkbox"/> DFS IV	<input type="checkbox"/> 9 TRACK <input type="checkbox"/> 21 TRACK	FORMAT: SEG	<input type="checkbox"/> GAPPED <input type="checkbox"/> UNGAPPED	PACKING DENSITY: (LO) <input type="checkbox"/> 356 BPI <input type="checkbox"/> 800 BPI	(HI) <input type="checkbox"/> 712 BPI <input type="checkbox"/> 1800 BPI	
	NO. BYTES IN HEADER REC:	NO. BYTES IN RECORD ID:	NO. BYTES PER SCAN:	RECORD NUMBERS: <input type="checkbox"/> DEC. <input type="checkbox"/> OCT.	GAIN CONSTANT: _____ db	INPUT IMPEDANCE: _____ ohms.				
CONFIGURATION (MAG TAPE)	FIELD TRACE NOS.:			AUXILIARY DATA:			AUXILIARY CHANNEL NOS.:			
PARAMETER	RECORD LENGTH: _____ sec.	SAMPLE RATE: <input type="checkbox"/> 1 ms. <input type="checkbox"/> 4 ms. <input type="checkbox"/> 2 ms. <input type="checkbox"/> _____ ms.	GAIN MODE: <input type="checkbox"/> INITIAL <input type="checkbox"/> MANUAL <input type="checkbox"/> IFP <input type="checkbox"/> FINAL <input type="checkbox"/> OPERATE	FILTERS: _____	LO CUT HZ SLOPE	FREQ. _____	HI CUT HZ SLOPE	NOTCH FILTER: <input type="checkbox"/> IN <input type="checkbox"/> OUT		
DISPLAY	MODE: <input type="checkbox"/> FLOAT <input type="checkbox"/> AMPLIFIER <input type="checkbox"/> AGC <input type="checkbox"/> DEFLOAT <input type="checkbox"/> DIRECT	INITIAL GAIN: _____ db	TRIP SENS: _____ db	POLARITY CONVENTION: _____	PRESSURE INCREASE ON GEOPHONE: _____	<input type="checkbox"/> NEGATIVE <input type="checkbox"/> POSITIVE	NUMBERS ON ON MAG. TAPE	<input type="checkbox"/> DOWNBREAK <input type="checkbox"/> UPBREAK	ON DISPLAY	
CFS I	TYPE STACK:	GATE LENGTH:	RECORD REJECTION:	NOISE REDUCTION:	NOISE THRESHOLD:	CORR. SCALING:		R.C.U. NORM / ALT SW.		
SOURCE	TYPE: <input type="checkbox"/> DYNAMITE <input type="checkbox"/> VIBROSEIS <input type="checkbox"/> OTHER	PATTERN:	NO. OF POSITIONS:	INLINE SPACING:	LATERAL SPACING:	STAGGER:	LENGTH:	WIDTH:	LATERAL OFFSET:	
RECEIVER	CONNECTION:	RESISTANCE: _____ ohms	STAGGER:	INLINE SPACING:	LENGTH:	WIDTH:	LATERAL OFFSET:			
SPREAD	NO. OF GROUPS:	GROUP INTERVAL:	SHOTPOINT INTERVAL:	FOLD:	DIRECTION OF PROGRESSION:	LEADING GROUP:				
DIAGRAMS/MISC. INFORMATION:										

SHOTPOINT	TR _____ to _____		TR _____ to _____		SHOT					SPREAD			REMARKS	CORR. STACK			
	REEL NO.	REC.	REEL NO.	REC.	SIZE	DEPTH	NO.	OFFSET	DIB.	COP SWITCH	LINE GROUPS #1	SEP ID		YE 1-31	YE 32-40	YE 41-50	YE 51-60
4010	22121518	11815									17	388.1	411.4				
4011		1186									13	389.1	412.4				
4012		1187									9	390.1	413.4				
4013		1188									5	391.1	414.4				
4014		1189									49	392.1	415.4	3			
4015		1190									45	393.1	416.4				
4016		1191									41	394.1	417.4				
4017		1192									37	395.1	418.4				
4018		1193									33	396.1	419.4				
4019		1194									29	397.1	420.4				
4020		1195									25	398.1	421.4				
4021		1196									21	399.1	422.4				
4022	22121519	1198									21	399.1	422.4				
4023		1199									13	401.1	424.4				
4024		1200									9	402.1	425.4				
4025		1201									5	403.1	426.4				
4026		1202									49	404.1	427.4	4			
4027		1203									45	405.1	428.4				
4028		1204									41	406.1	429.4				
4029		1205									37	407.1	430.4				




# LAND SEISMIC RECORDING LOG

	CLIENT: <u>Husky</u>	PROSPECT: <u>Southern Foot hills</u>	AREA: <u>NPR-A</u>	LINE NO: <u>632</u>
	PARTY NO: <u>1186</u>	INST. ENG: <u>BuTech Loss</u>	LEAVE BASE <u>7:00</u> ARRIVE FIELD <u>3:00</u>	DATE: <u>MO 2 DAY 15 YR 79</u>
			LEAVE FIELD <u>9:00</u> ARRIVE BASE <u>10:00</u>	
INSTRUMENT	<input type="checkbox"/> 1 SYSTEM <input type="checkbox"/> 2 SYSTEMS	<input type="checkbox"/> 1-24 & 25-48 <input type="checkbox"/> 48 & 49-96	EVENTS	TYPE: <input type="checkbox"/> DPS III <input type="checkbox"/> DPS IX <input type="checkbox"/> OTHER
(9-TRACK)	NO. BYTES IN HEADER REC: <u>135</u>	NO. BYTES IN RECORD ID: <u>354</u>	NO. BYTES PER SCAN: <u>354</u>	RECORD NUMBERS: <input type="checkbox"/> DEC. <input type="checkbox"/> OCT.
CONFIGURATION (MAG TAPE)	FIELD TRACE NOS.: <u>1-96</u>	DATA CHANNEL NOS.: <u>1-96</u>	(ON MAG TAPE)	AUXILIARY DATA: (1) (2) (3) (4) (5) (6) (7)
PARAMETER	RECORD LENGTH: <u>2</u> sec.	SAMPLE RATE: <input type="checkbox"/> 1 ms. <input checked="" type="checkbox"/> 2 ms. <input type="checkbox"/> 4 ms.	GAIN MODE: <input checked="" type="checkbox"/> INITIAL <input type="checkbox"/> FINAL	FILTERS: <input type="checkbox"/> LO CUT <input type="checkbox"/> HI CUT
DISPLAY	MODE: <input type="checkbox"/> AGC <input type="checkbox"/> FLOAT <input type="checkbox"/> DEFOAT <input type="checkbox"/> DIRECT	INITIAL GAIN: <u>      </u> db	TRIP SENS: <u>      </u> db	FREQ. <u>8</u> HZ SLOPE <u>      </u>
CFS I	TYPE STACK:	GATE LENGTH:	RECORD REJECTION:	NOISE REDUCTION: <input type="checkbox"/> NEGATIVE <input type="checkbox"/> POSITIVE
SOURCE	TYPE: <input checked="" type="checkbox"/> DYNAMITE <input type="checkbox"/> VIBROSEIS <input type="checkbox"/> OTHER	PATTERN: <u>Single hole</u>	NO. OF POSITIONS: <u>      </u>	INLINE SPACING: <u>      </u>
		CHG. HOLE: <u>110</u>	HOLE DEPTH: <u>105</u>	LATERAL SPACING: <u>      </u>
RECEIVER	TYPE: <u>20-D 1042</u>	PATTERN: <u>inline</u>	NO. OF ELEMENTS: <u>18</u>	INLINE SPACING: <u>15'</u>
	CONNECTION: <u>SERIES - PARALLEL</u>	RESISTANCE: <u>      </u> ohms	STAGGER: <u>      </u>	LENGTH: <u>      </u>
SPREAD	NO. OF GROUPS: <u>96</u>	GROUP INTERVAL: <u>220'</u>	SHOTPOINT INTERVAL: <u>880'</u>	FOLD: <u>1200</u>
	OFFSET GROUP 1: <u>10450'</u>	OFFSET GROUP <u>45</u> : <u>110'</u>	OFFSET GROUP <u>49</u> : <u>110'</u>	OFFSET GROUP 48/96: <u>10450'</u>
DIAGRAMS/MISC. INFORMATION:				

SHOTPOINT NO.	TR. 10		TR. 10		SHOT			SPREAD		REMARKS	CORR. STACK			
	REEL NO.	REC.	REEL NO.	REC.	SIZE	DEPTH	NO.	OFFSET	DIR.		CDP SWITCH	LINE GROUPS	YR 1-48	TR 48-96
428	222589	2213			1120	11015	1			49	426.1	437.4		
429		2214			1120	1015	2			45	417.1	440.4		
430		2215			1120	1015	3			41	418.1	441.4		
431		2216			1120	1005	4			37	419.1	442.4		
432		2217			1120	1105	5			33	420.1	443.4		
433		2218			1120	1105	6			29	421.1	444.4		
434		2219			1120	1015	7			25	422.1	445.4		
435		2310			1120	1015	8			21	423.1	446.4		
436		2311			1120	1015	9			17	424.1	447.4		
437		2312			1120	1015	10			13	425.1	448.4		
438		2313			1120	1015	11			9	426.1	449.4		
439		2314			1120	1105	12			5	427.1	450.4		
440		2315			1120	1015	13			49	428.1	451.4	2	INST 345.4 to 346.1
441		2316			1120	10514				45	429.1	452.4		
442		2317			1120	10515				41	430.1	453.4		
443		2318			1120	10516				37	431.1	454.4		
444		2319			1120	10517				33	432.1	455.4		
445		240			1120	10518				29	433.1	456.4		
446		241			1120	10519				25	434.1	457.4		
447		242			1120	10520				21	435.1	458.4		

# LAND SEISMIC RECORDING LOG

1977 07 28 3

	CLIENT: _____	PROSPECT: _____	AREA: _____	LINE NO.: _____					
	PARTY NO.: _____	INST. ENG.: _____		DATE: _____					
				MO. _____ DAY _____ YR. _____					
INSTRUMENT (9-TRACK)	<input type="checkbox"/> 1 SYSTEM <input type="checkbox"/> 2 SYSTEMS	<input type="checkbox"/> 1-24 & 25-48 <input type="checkbox"/> 1-48 & 49-96	ODDS EVENTS	TYPE: <input type="checkbox"/> DFS III <input type="checkbox"/> DFS IX <input type="checkbox"/> OTHER _____	<input type="checkbox"/> 9 TRACK <input type="checkbox"/> 21 TRACK	FORMAT: _____ SLG _____	<input type="checkbox"/> GAPPED <input type="checkbox"/> UNGAPPED	PACKING DENSITY: (L) <input type="checkbox"/> 356 BPI (H) <input type="checkbox"/> 712 BPI <input type="checkbox"/> 1400 BPI	
	NO. BYTES IN HEADER REC: _____	NO. BYTES IN RECORD ID: _____	NO. BYTES PER SCAN: _____	RECORD NUMBERS: _____	<input type="checkbox"/> DEC. <input type="checkbox"/> OCT	GAIN CONSTANT: _____ db	INPUT IMPEDANCE: _____ ohms.		
CONFIGURATION (MAG TAPE)	FIELD TRACE NOS.: _____				AUXILIARY DATA: _____				
	DATA CHANNEL NOS.: _____ (ON MAG TAPE)				AUXILIARY CHANNEL NOS.: _____				
PARAMETER	RECORD LENGTH: _____ sec.	SAMPLE RATE: <input type="checkbox"/> 1 ml. <input type="checkbox"/> 4 ml. <input type="checkbox"/> 2 ml. _____ ms.	GAIN MODE: <input type="checkbox"/> INITIAL <input type="checkbox"/> IFP	<input type="checkbox"/> MANUAL <input type="checkbox"/> OPERATE	FILTERS: _____	LO CUT HZ SLOPE _____	H1 CUT HZ SLOPE _____	NOTCH FILTER: <input type="checkbox"/> IN <input type="checkbox"/> OUT	
DISPLAY	MODE: <input type="checkbox"/> FLOAT <input type="checkbox"/> AMPLIFIER <input type="checkbox"/> AGC <input type="checkbox"/> DEFLOAT <input type="checkbox"/> DIRECT	INITIAL GAIN: _____ db	TRIP SENS: _____ db	POLARITY CONVENTION: _____	PRESSURE INCREASE ON GEOPHONE: <input type="checkbox"/> NEGATIVE <input type="checkbox"/> POSITIVE	NUMBERS ON MAG. TAPE	<input type="checkbox"/> DOWNBREAK <input type="checkbox"/> UPBREAK	ON DISPLAY	
CFS I	TYPE STACK: _____	GATE LENGTH: _____	RECORD REJECTION: _____	NOISE REDUCTION: _____	NOISE THRESHOLD: _____	CORR. SCALING: _____	P.C.U. NORM/ALT SW.		
SOURCE	TYPE: <input type="checkbox"/> DYNAMITE <input type="checkbox"/> VIBROSEIS <input type="checkbox"/> OTHER _____	PATTERN: _____	NO. OF POSITIONS: _____	INLINE SPACING: _____	LATERAL SPACING: _____	STAGGER: _____	LENGTH: _____	WIDTH: _____	LATERAL OFFSET: _____
	CHG/ HOLE: _____	HOLE DEPTH: _____	SWEEP POSITION: _____	SWEEP START: _____	SWEEP END: _____	SWEEP LENGTH: _____	SWEEP TAPER: _____	PHASE COMP: _____	
RECEIVER	TYPE: _____	PATTERN: _____	NO. OF ELEMENTS: _____	INLINE SPACING: _____	LATERAL SPACING: _____	STAGGER: _____	LENGTH: _____	WIDTH: _____	LATERAL OFFSET: _____
	CONNECTION: _____	RESISTANCE: _____ ohms							
SPREAD	NO. OF GROUPS: _____	GROUP INTERVAL: _____	SHOTPOINT INTERVAL: _____	FOLD: _____	DIRECTION OF PROGRESSION: _____				
	OFFSET GROUP 1: _____	OFFSET GROUP _____	OFFSET GROUP _____	OFFSET GROUP 48/96: _____	LEADING GROUP: _____				

DIAGRAMS/MISC. INFORMATION: \_\_\_\_\_

SHOTPOINT	TR. _____ TO _____		TR. _____ TO _____		SHOT				SPREAD		REMARKS	CORE STACK			
	REEL NO.	REC.	REEL NO.	REC.	SIZE	DEPTH	NO.	OFFSET	DIR.	CDP SWITCH		LINE GROUPS	#1	REC.	#2
448	722589	243				10621				17	436.1	459.4			
449		244				10622				13	437.1	460.4			
450	722590	246				10623				9	438.1	461.4			
451		247				10624				5	439.1	462.4			
452		248				10625				49	440.1	463.4			
453		249				10626				45	441.1	464.4			
454		250				10627				41	442.1	465.4			
455		251				10628				37	443.1	466.4			
456		252				10629				33	444.1	467.4			
457		253				10630				29	445.1	468.4			
458		254				10631				25	446.1	469.4			
459		255				10632				21	447.1	470.4			
460		256				10633				17	448.1	471.4			
461		257				10634				13	449.1	472.4			
462		258				10635				9	450.1	473.4			
463		259				10636				5	451.1	474.4			
464		260				10637				49	452.1	475.4			
465		261				10638				45	453.1	476.4			
466		262				10639				41	454.1	477.4			
467		263				10640				37	455.1	478.4			

100' 170'



REC\*245 TEST

offset 75'

offset 200'

# LAND SEISMIC RECORDING LOG

7023073



	CLIENT: <u>Husky</u>	PROSPECT: <u>Sussex Basin</u>	AREA: <u>S 1728-A</u>	LINE NO: <u>650</u>									
	PARTY NO: <u>1186</u>	INST. ENG:		DATE: <u>MO 2 DAY 15 YR 74</u>									
INSTRUMENT (9-TRACK)	<input type="checkbox"/> 1 SYSTEM <input type="checkbox"/> 2 SYSTEMS	<input type="checkbox"/> 1-24 & 25-48 <input type="checkbox"/> 1-48 & 49-96	<input type="checkbox"/> ODDS & EVENS	TYPE: <input type="checkbox"/> DFS III <input type="checkbox"/> DFS II	<input type="checkbox"/> 9 TRACK <input type="checkbox"/> 21 TRACK	FORMAT: <input type="checkbox"/> SEG	<input type="checkbox"/> GAPPED <input type="checkbox"/> UNGAPPED	PACKING DENSITY: (L) <input type="checkbox"/> 356 BPI <input type="checkbox"/> 800 BPI	(M) <input type="checkbox"/> 712 BPI <input type="checkbox"/> 1600 BPI				
	NO. BYTES IN HEADER REC:	NO. BYTES IN RECORD ID:	NO. BYTES PER SCAN:	RECORD NUMBERS: <input type="checkbox"/> DEC. <input type="checkbox"/> OCT.	GAIN CONSTANT: _____ db	INPUT IMPEDANCE: _____ ohms.	(1)	(2)	(3)	(4)	(5)	(6)	(7)
CONFIGURATION (MAG TAPE)	FIELD TRACE NOS.: _____ DATA CHANNEL NOS.: _____ (ON MAG TAPE)			AUXILIARY DATA: AUXILIARY CHANNEL NOS.: _____									
PARAMETER	RECORD LENGTH: _____ sec.	SAMPLE RATE: <input type="checkbox"/> 1 ms. <input type="checkbox"/> 4 ms. <input type="checkbox"/> 2 ms. <input type="checkbox"/> _____ ms.	GAIN MODE: <input type="checkbox"/> INITIAL <input type="checkbox"/> MANUAL <input type="checkbox"/> IFP <input type="checkbox"/> FINAL <input type="checkbox"/> OPERATE	FILTERS: _____	LO CUT _____	HZ SLOPE _____	FREQ. _____	H1 CUT _____	H2 SLOPE _____	NOTCH FILTER: <input type="checkbox"/> IN <input type="checkbox"/> OUT			
DISPLAY	MODE: <input type="checkbox"/> AGC <input type="checkbox"/> FLOAT <input type="checkbox"/> AMPLIFIER <input type="checkbox"/> DEFLOAT <input type="checkbox"/> DIRECT	INITIAL GAIN: _____ db	TRIP SENS: _____ db	POLARITY CONVENTION: _____	PRESSURE INCREASE ON GEOPHONE: <input type="checkbox"/> NEGATIVE <input type="checkbox"/> POSITIVE	NUMBERS ON ON MAG. TAPE: <input type="checkbox"/> DOWNBREAK <input type="checkbox"/> UPBREAK	ON DISPLAY						
CFS I	TYPE STACK: _____	GATE LENGTH: _____	RECORD REJECTION: _____	NOISE REDUCTION: _____	NOISE THRESHOLD: _____	CORR. SCALING: _____	R.C.U. NORM. ALT SW.						
SOURCE	TYPE: <input type="checkbox"/> DYNAMITE <input type="checkbox"/> VIBROSEIS <input type="checkbox"/> OTHER	PATTERN: _____	NO. OF POSITIONS: _____	INLINE SPACING: _____	LATERAL SPACING: _____	STAGGER: _____	LENGTH: _____	WIDTH: _____	LATERAL OFFSET: _____				
RECEIVER	CONNECTION: _____	RESISTANCE: _____	STAGGER: _____	LENGTH: _____	WIDTH: _____	LATERAL OFFSET: _____							
SPREAD	NO. OF GROUPS: _____	GROUP INTERVAL: _____	SHOTPOINT INTERVAL: _____	OFFSET GROUP: _____	FOLD: _____	DIRECTION OF PROGRESSION: _____							

DIAGRAMS/MISC. INFORMATION:

SHOTPOINT	TR _____ No _____		TR _____ No _____		SHOT				SPREAD			REMARKS	CORR. STACK			
	REEL NO.	REC.	REEL NO.	REC.	SIZE	DEPTH	NO.	OFFSET	DIR.	COF SWITCH	LINE GROUPS		1	2	3	4
468	22570	2614			110	10541				33	482.1	479.4				
469		2615			110	110542				29	453.1	480.4				
470		2616			110	11543				25	458.1	481.4				
471		2617			110	12044				21	459.1	482.4				
472		2618			110	12545				17	460.1	483.4				
473		2619			110	13046				13	461.1	484.4				
474		2620			110	13547				9	462.1	485.4				
475		2621			110	14048				5	463.1	486.4				



# LAND SEISMIC RECORDING LOG

	CLIENT:	PROSPECT:	AREA:	LINE NO:							
	PARTY NO:	INST. ENG:		DATE:							
				MO: DAY: YR:							
INSTRUMENT (9-TRACK)	<input type="checkbox"/> 1 SYSTEM <input type="checkbox"/> 2 SYSTEMS	<input type="checkbox"/> 1-24 & 25-48 <input type="checkbox"/> 1-48 & 49-96	ODDS & EVENS <input type="checkbox"/>	TYPE: <input type="checkbox"/> DFS III <input type="checkbox"/> DFS IV	<input type="checkbox"/> 9 TRACK <input type="checkbox"/> 21 TRACK	FORMAT: SEG	<input type="checkbox"/> GAPPED <input type="checkbox"/> UNGAPPED	PACKING DENSITY: (LO) <input type="checkbox"/> 356 BPM <input type="checkbox"/> 800 BPM	(HI) <input type="checkbox"/> 712 BPM <input type="checkbox"/> 1400 BPM		
	NO. BYTES IN HEADER REC:	NO. BYTES IN RECORD ID:	NO. BYTES PER SCAN:	RECORD NUMBERS:	<input type="checkbox"/> DEC. <input type="checkbox"/> OCT.	GAIN CONSTANT: _____ db	INPUT IMPEDANCE: _____ ohms				
CONFIGURATION (MAG TAPE)	FIELD TRACE NOS.:				AUXILIARY DATA:						
	DATA CHANNEL NOS.:				AUXILIARY CHANNEL NOS.:						
PARAMETER	RECORD LENGTH: _____ sec.	SAMPLE RATE: <input type="checkbox"/> 1 ms. <input type="checkbox"/> 4 ms. <input type="checkbox"/> 2 ms. <input type="checkbox"/> _____ ms.	GAIN MODE: <input type="checkbox"/> INITIAL <input type="checkbox"/> MANUAL <input type="checkbox"/> IFF <input type="checkbox"/> FINAL <input type="checkbox"/> OPERATE	FILTERS: _____	LO CUT _____ HZ HZ SLOPE _____	HI CUT _____ HZ HZ SLOPE _____	NOTCH FILTER: <input type="checkbox"/> IN <input type="checkbox"/> OUT				
DISPLAY	MODE: <input type="checkbox"/> FLOAT <input type="checkbox"/> AMPLIFIER <input type="checkbox"/> AGC <input type="checkbox"/> DEFLOAT <input type="checkbox"/> DIRECT	INITIAL GAIN: _____ db	TRIP SENS: _____ db	POLARITY CONVENTION: _____	PRESSURE INCREASE ON GEOPHONE: _____	<input type="checkbox"/> NEGATIVE <input type="checkbox"/> POSITIVE	NUMBERS ON MAG TAPE: _____	<input type="checkbox"/> DOWNBREAK <input type="checkbox"/> UPBREAK	ON DISPLAY		
CFS I	TYPE STACK:	GATE LENGTH:	RECORD REJECTION:	NOISE REDUCTION:	NOISE THRESHOLD:	CORR. SCALING:	F.C.U. NORM./ALT SW.				
SOURCE	TYPE: <input type="checkbox"/> DYNAMITE <input type="checkbox"/> VIBROSEIS <input type="checkbox"/> OTHER	PATTERN:	NO. OF POSITIONS:	INLINE SPACING:	LATERAL SPACING:	STAGGER:	LENGTH:	WIDTH:	LATERAL OFFSET:		
	CHG/HOLE:	HOLE DEPTH:	SWEEP POSITION:	SWEEP START:	SWEEP END:	SWEEP LENGTH:	SWEEP TAPER:	PHASE COMP:			
RECEIVER	TYPE:	PATTERN:	NO. OF ELEMENTS:	INLINE SPACING:	LATERAL SPACING:	STAGGER:	LENGTH:	WIDTH:	LATERAL OFFSET:		
	CONNECTION:	RESISTANCE: _____ ohms	STAGGER:	LENGTH:	WIDTH:						
SPREAD	NO. OF GROUPS:	GROUP INTERVAL:	SHOTPOINT INTERVAL:	FOLD:	DIRECTION OF PROGRESSION:						
	OFFSET GROUP 1:	OFFSET GROUP _____:	OFFSET GROUP _____:	OFFSET GROUP 48/96:	LEADING GROUP:						

DIAGRAMS/MISC. INFORMATION:

SHOTPOINT	TR. _____ No. _____		TR. _____ No. _____		SHOT								SPREAD			REMARKS	CORR STACK			
	REEL NO.	REC.	REEL NO.	REC.	SIZE	DEPTH	NO.	OFFSET	DIR.	CDP SWITCH	LINE GROUPS		FT.	REC.	FT.		REC.			
4916	2125	1303	17	22	23	26	27	29	30	33	35	37	17							
4917	2125	1304											13							
4918		1305											9							
4917		1306											5							
5010		1307											11							
5011		1308											17							
5012		1309											17							
5013		1310											13							
5014		1311											9							