


# LAND SEISMIC RECORDING LOG

14.5 Hours

Page #1 of 1

	CLIENT: <u>Husky</u>	PROSPECT: <u>NPR-A</u>	AREA: <u>BARROW</u>	LINE NO: <u>651</u>	
PARTY NO: <u>1189</u>		INST. ENG: <u>STREFF-Windham</u>		DATE: <u>NO 1 DAY 13 YR 79</u>	

INSTRUMENT	<input type="checkbox"/> 1 SYSTEM <input type="checkbox"/> 2 SYSTEMS	<input type="checkbox"/> 1-24 & 25-48 <input type="checkbox"/> 1-48 & 49-96	ODDS EVENS	TYPE: <input type="checkbox"/> DFS III <input type="checkbox"/> DFS III <input type="checkbox"/> OTHER	<input checked="" type="checkbox"/> 9 TRACK <input type="checkbox"/> 21 TRACK	FOPMAT: <u>B</u> SEG	<input type="checkbox"/> GAPPED <input type="checkbox"/> UNGAPPED	PACKING DENSITY: (L0) <input type="checkbox"/> 356 BPI <input type="checkbox"/> 800 BPI (H1) <input type="checkbox"/> 712 BPI <input type="checkbox"/> 1600 BPI
(9-TRACK)	NO. BYTES IN HEADER REC:	NO. BYTES IN RECORD ID:	NO. BYTES PER SCAN: <u>134</u>	RECORD NUMBERS: <input checked="" type="checkbox"/> DEC. <input type="checkbox"/> OCT.	GAIN CONSTANT: <u>36</u> db	INPUT IMPEDANCE: _____ ohms.		


CONFIGURATION (MAG TAPE)	FIELD TRACE NOS.: <u>1-48</u>	AUXILIARY DATA: <u>(1) TB (2) UT (3) (4) (5) (6) (7)</u>
	DATA CHANNEL NOS.: <u>1-48</u> (ON MAG TAPE)	AUXILIARY CHANNEL NOS.: <u>2 3</u>

PARAMETER	RECORD LENGTH: <u>2</u> sec.	SAMPLE RATE: <input type="checkbox"/> 1 ms. <input type="checkbox"/> 4 ms. <input type="checkbox"/> 2 ms. <input type="checkbox"/> _____ ms.	GAIN MODE: <input type="checkbox"/> INITIAL <input type="checkbox"/> MANUAL <input checked="" type="checkbox"/> TRIP <input type="checkbox"/> FINAL <input type="checkbox"/> OPERATE	FILTERS: FREQ. <u>OUT</u> LO CUT HZ SLOPE _____ HI CUT HZ SLOPE <u>70</u>	NOTCH FILTER: <input type="checkbox"/> IN <input type="checkbox"/> OUT
DISPLAY	MODE: <input type="checkbox"/> AGC <input type="checkbox"/> FLOAT <input type="checkbox"/> AMPLIFIER <input type="checkbox"/> DIRECT	INITIAL GAIN: <u>12</u> db	TRIP SENS: <u>12</u> db	POLARITY CONVENTION: <input type="checkbox"/> NEGATIVE <input type="checkbox"/> POSITIVE	NUMBERS ON MAG. TAPE <input type="checkbox"/> DOWNBREAK <input type="checkbox"/> UPBREAK ON DISPLAY
CFS I	TYPE STACK:	GATE LENGTH:	RECORD REJECTION:	NOISE REDUCTION:	NOISE THRESHOLD: _____ CORR. SCALING: _____ R.C.U. NORM./ALT SW.

SOURCE	TYPE: <input checked="" type="checkbox"/> DYNAMITE <input type="checkbox"/> VIBROSEIS <input type="checkbox"/> OTHER	PATTERN: <u>Single hole - IN line</u>	NO. OF POSITIONS: _____	INLINE SPACING: _____	LATERAL SPACING: _____	STAGGER: _____	LENGTH: _____	WIDTH: _____	LATERAL OFFSET: _____
		CHG/ HOLE: <u>10</u>	HOLE DEPTH: <u>75</u>	SWEEP POSITION: _____	SWEEP START: _____	SWEEP END: _____	SWEEP LENGTH: _____	SWEEP TAPER: _____	PHASE COMP: _____

RECEIVER	TYPE: <u>C SC-30d</u>	PATTERN: <u>IN LINE</u>	NO. OF ELEMENTS: <u>9</u>	INLINE SPACING: <u>3'</u>	LATERAL SPACING: _____	STAGGER: _____	LENGTH: _____	WIDTH: _____	LATERAL OFFSET: _____
	CONNECTION: <u>Series - Parallel</u>	RESISTANCE: <u>280</u> ohms							



SPREAD	NO. OF GROUPS: <u>48</u>	GROUP INTERVAL: <u>110'</u>	SHOTPOINT INTERVAL: <u>440'</u>	FOLD: <u>6</u>	DIRECTION OF PROGRESSION: <u>N → S</u>
	OFFSET GROUP 1: <u>2695'</u>	OFFSET GROUP 24: <u>165'</u>	OFFSET GROUP 48: <u>165'</u>	OFFSET GROUP 48/96: <u>2695'</u>	LEADING GROUP: <u>48</u>



SHOTPOINT	TR 1 to 48		TR 17 to 24		SHOT		DIR.	CDP SWITCH	SPREAD		REMARKS	CORR. STACK			
	REEL NO.	REC.	REEL NO.	REC.	SIZE	DEPTH			NO.	LINE GROUPS		SET UP	TR 1-11	TR 12-22	TR 23-33
1	351869	436			10	75	1	24	7+4	- SP7+1	1				
2		437			10	75	2	28	75	- SP8+1					
3		438			10	75	3	32	79	- SP9+1					
4		439			10	75	4	36	7-13	- SP10+1					
5		441			10	75	5	40	7-17	- SP11+1					
6		442			10	75	6	44	7-21	- SP12+1					
7		443			10	75	7	48	7-25	- SP13+1					
8		444			10	75	8	52	1+4	- SP14+1					
9		445			10	75	9	56	2+4	- 15+1					
10		446			10	75	10	60	3+4	- 16+1					
11		447			10	75	11	64	4+4	- 17+1					
12		448			10	75	12	68	5+4	- 18+1					
13		449			10	75	13	72	6+4	- 19+1					
14		450			10	75	14	76	7+4	- 20+1	2	RECORDER AT SP 22			
15		451			10	75	15	80	8+4	- 21+1					
16		452			10	75	16	84	9+4	- 22+1					
17		453			10	75	17	88	10+4	- 23+1					
18		454			10	75	18	92	11+4	- 24+1					
19		455			10	75	19	96	12+4	- 25+1					
20		456			10	75	20	100	13+4	- 26+1					

# LAND SEISMIC RECORDING LOG

Page # 2 of 4

	CLIENT: <b>Husky</b>	PROSPECT: <b>NPR-A</b>	AREA: <b>BARROW</b>	LINE NO.: <b>651</b>						
	PARTY NO.: <b>1182</b>	INST. ENG.: <b>STREEF / WINDHAM</b>		DATE: <b>MO 1 DAY 13 YR 79</b>						
INSTRUMENT (9-TRACK)	<input checked="" type="checkbox"/> 1 SYSTEM <input type="checkbox"/> 2 SYSTEMS	<input checked="" type="checkbox"/> 1-24 & 25-48 <input type="checkbox"/> 1-48 & 49-96	<input type="checkbox"/> ODDS <input type="checkbox"/> EVENS	TYPE: <input type="checkbox"/> DFS III <input type="checkbox"/> DFS IV <input type="checkbox"/> OTHER	<input checked="" type="checkbox"/> 9 TRACK <input type="checkbox"/> 21 TRACK	FORMAT: <b>B</b>	<input type="checkbox"/> GAPPED <input type="checkbox"/> UNGAPPED	PACKING DENSITY:	<input type="checkbox"/> 800 BPI <input type="checkbox"/> 1000 BPI	<input type="checkbox"/> 712 BPI <input type="checkbox"/> 1000 BPI
	NO. BYTES IN HEADER REC:	NO. BYTES IN RECORD ID:	NO. BYTES PER SCAN: <b>134</b>	RECORD NUMBERS: <input checked="" type="checkbox"/> DEC. <input type="checkbox"/> OCT.	GAIN CONSTANT: <b>36</b> db	INPUT IMPEDANCE: _____ ohms				
CONFIGURATION (MAG TAPE)	FIELD TRACE NOS.: <b>1-48</b>			AUXILIARY DATA: (1) (2) (3) (4) (5) (6) (7)						
	DATA CHANNEL NOS.: <b>1-48</b>			AUXILIARY CHANNEL NOS.:						
PARAMETER	RECORD LENGTH: <b>2</b> sec.	SAMPLE RATE: <input checked="" type="checkbox"/> 1 ms. <input type="checkbox"/> 4 ms. <input type="checkbox"/> 2 ms. <input type="checkbox"/> 8 ms.	GAIN MODE: <input checked="" type="checkbox"/> INITIAL <input type="checkbox"/> FINAL	<input type="checkbox"/> MANUAL <input type="checkbox"/> OPERATE	FILTERS: <b>FREQ OUT</b>	LO CUT HZ SLOPE: _____	FREQ <b>256</b> H1 CUT HZ SLOPE <b>70</b>	NOTCH FILTER: <input type="checkbox"/> IN <input type="checkbox"/> OUT		
DISPLAY	MODE: <input checked="" type="checkbox"/> AGC <input type="checkbox"/> FLOAT <input type="checkbox"/> DEFLOAT	<input type="checkbox"/> AMPLIFIER <input type="checkbox"/> DIRECT	INITIAL GAIN: <b>12</b> db	TRIP SENS: <b>12</b> db	POLARITY CONVENTION: <input type="checkbox"/> NEGATIVE <input type="checkbox"/> POSITIVE	PRESSURE INCREASE ON GEOPHONE: _____	<input type="checkbox"/> NUMBERS ON MAG TAPE	<input type="checkbox"/> DOWNBREAK <input type="checkbox"/> UPBREAK	ON DISPLAY	
CFS I	TYPE STACK:	GATE LENGTH:	RECORD REJECTION:	NOISE REDUCTION:	NOISE THRESHOLD:	CORR. SCALING:	R.C.U. NORM./ALT SW.			
SOURCE	TYPE: <input checked="" type="checkbox"/> DYNAMITE <input type="checkbox"/> VIBROSEIS <input type="checkbox"/> OTHER	PATTERN: <b>SINGLE HOLE INLINE</b>	NO. OF POSITIONS:	INLINE SPACING:	LATERAL SPACING:	STAGGER:	LENGTH:	WIDTH:	LATERAL OFFSET:	
		CHG/HOLE: <b>10</b>	HOLE DEPTH: <b>75</b>	SWEEP POSITION:	SWEEP START:	SWEEP END:	SWEEP LENGTH:	SWEEP TAPER:	PHASE COMP:	
RECEIVER	TYPE: <b>65C-20D</b>	PATTERN: <b>INLINE</b>	NO. OF ELEMENTS: <b>9</b>	INLINE SPACING: <b>3'</b>	LATERAL SPACING:	STAGGER:	LENGTH:	WIDTH:	LATERAL OFFSET:	
	CONNECTION: <b>SERIES/PARALLEL</b>	RESISTANCE: <b>280</b> ohms								
SPREAD	NO. OF GROUPS: <b>48</b>	GROUP INTERVAL: <b>110'</b>	SHOTPOINT INTERVAL: <b>440'</b>	FOLD: <b>6</b>	DIRECTION OF PROGRESSION: <b>N75</b>					
	OFFSET GROUP 1: <b>2695'</b>	OFFSET GROUP 24: <b>165'</b>	OFFSET GROUP 25: <b>165'</b>	OFFSET GROUP 48/96: <b>2695'</b>	LEADING GROUP: <b>48</b>					

DIAGRAMS/MISC. INFORMATION:

SHOTPOINT	TR 1		TR 2		SHOT				DIR.	CDP SWITCH	SPREAD		REMARKS:	CORR. STACK	
	REEL NO.	REC.	REEL NO.	REC.	SIZE	DEPTH	NO.	OFFSET			LINE GROUPS	SE		TR 1	TR 2
21	751869	A57			10	7521			44	14+4	-27+1				
22		A58			10	7522			48	15+4	-28+1				
23		A59			10	7523			52	16+4	-29+1				
24		A60			10	7524			56	17+4	-30+1				
25		A61			10	7525			60	18+4	-31+1				
26		A62			10	7526			64	19+4	-32+1				
27		A63			10	7527			68	20+4	-33+1				
28		A64			10	7528			72	21+4	-34+1				
29		A65			10	7529			76	22+4	-35+1				
30		A66			5	7530			80	23+4	-36+1				
31		A67			5	7531			12	24+4	-37+1	3	TRACE 24+4 IS DEAD/RECORDED @ 40		
32		A68			5	7532			39	21+3	-43+4		WRONG CDP		
32A		A69			10	7533			16	25+4	-38+1		REDRILLED		
33		A70			10	7534			20	26+4	-39+1				
34		A71			10	7535			24	27+4	-40+1				
35		A72			10	7536			28	28+4	-41+1				
36		A73			10	7537			32	29+4	-42+1				
37		A74			10	7538			36	30+4	-43+1				
38		A75			10	7539			40	31+4	-44+1				
39		A76			10	7540			44	32+4	-45+1				

# LAND SEISMIC RECORDING LOG


Page # 3 of 4

		CLIENT: <b>Husky</b>	PROSPECT: <b>NPR-A</b>	AREA: <b>PARROW</b>	LINE NO: <b>651</b>				
PARTY NO: <b>1132</b>		INST. ENG: <b>Streff-Gundlach</b>		DATE: <b>MO 1 DAY 13 YR 79</b>					
INSTRUMENT (9-TRACK)	<input type="checkbox"/> 1 SYSTEM <input type="checkbox"/> 2 SYSTEMS	<input type="checkbox"/> 1-24 & 25-48 <input type="checkbox"/> 1-48 & 49-96	ODDS EVENS	TYPE: <input type="checkbox"/> DFS III <input type="checkbox"/> DFS IV	<input type="checkbox"/> 9 TRACK <input type="checkbox"/> 21 TRACK	FORMAT: <b>B</b> SEG	<input type="checkbox"/> GAPPED <input type="checkbox"/> UNGAPPED		
	NO. BYTES IN HEADER REC:	NO. BYTES IN RECORD ID:	NO. BYTES PER SCAN: <b>134</b>	RECORD NUMBERS: <input checked="" type="checkbox"/> DEC <input type="checkbox"/> OCT	GAIN CONSTANT: <b>36</b> db	PACKING DENSITY: (L0) <input type="checkbox"/> 350 BPI (M1) <input type="checkbox"/> 712 BPI	INPUT IMPEDANCE: _____ ohms		
CONFIGURATION (MAG TAPE)	FIELD TRACE NOS.: <b>1-48</b>			AUXILIARY DATA: <b>11) 78 (2) 14 (3) (4) (5) (6) (7)</b>					
	DATA CHANNEL NOS.: <b>1-48</b> (ON MAG TAPE)			AUXILIARY CHANNEL NOS.: <b>2 3</b>					
PARAMETER	RECORD LENGTH: <b>5</b> sec.	SAMPLE RATE: <input type="checkbox"/> 1 ms. <input type="checkbox"/> 4 ms. <input type="checkbox"/> 2 ms. _____ ms.	GAIN MODE: <input type="checkbox"/> INITIAL <input type="checkbox"/> MANUAL <input type="checkbox"/> IFP <input type="checkbox"/> OPERATE	FILTERS: _____	LO CUT _____	HZ SLOPE _____	NOTCH FILTER: <input checked="" type="checkbox"/> IN <input type="checkbox"/> OUT		
DISPLAY	MODE: <input type="checkbox"/> FLOAT <input type="checkbox"/> AMPLIFIER <input checked="" type="checkbox"/> AGC <input type="checkbox"/> DEFLAT <input type="checkbox"/> DIRECT	INITIAL GAIN: <b>12</b> db	TRIP SENS: <b>12</b> db	POLARITY CONVENTION: _____	PRESSURE INCREASE ON GEOPHONE: <input type="checkbox"/> NEGATIVE <input type="checkbox"/> POSITIVE	NUMBERS ON ON MAG. TAPE <input type="checkbox"/> DOWNBREAK <input type="checkbox"/> UPBREAK	ON DISPLAY		
CFS I	TYPE STACK: _____	GATE LENGTH: _____	RECORD REJECTION: _____	NOISE REDUCTION: _____	NOISE THRESHOLD: _____	CORR. SCALING: _____	R.C.U. NORM./ALT SW. _____		
SOURCE	TYPE: <input checked="" type="checkbox"/> DYNAMITE <input type="checkbox"/> VIBROSEIS <input type="checkbox"/> OTHER	PATTERN: <b>Single hole - IN line</b>	NO. OF POSITIONS: _____	INLINE SPACING: _____	LATERAL SPACING: _____	STAGGER: _____	LENGTH: _____	WIDTH: _____	LATERAL OFFSET: _____
RECEIVER	TYPE: <b>GSC-20d</b>	PATTERN: <b>IN line</b>	NO. OF ELEMENTS: <b>9</b>	INLINE SPACING: <b>3'</b>	LATERAL SPACING: _____	STAGGER: _____	LENGTH: _____	WIDTH: _____	LATERAL OFFSET: _____
	CONNECTION: <b>Series - Parallel</b>	RESISTANCE: <b>280</b> ohms	STAGGER: _____	SWEEP LENGTH: _____	SWEEP TAPER: _____	PHASE COMP. _____			
SPREAD	NO. OF GROUPS: <b>48</b>	GROUP INTERVAL: <b>110'</b>	SHOTPOINT INTERVAL: <b>440'</b>	FOLD: <b>6</b>	DIRECTION OF PROGRESSION: <b>N → S</b>	LEADING GROUP: <b>48</b>			
	OFFSET GROUP 1: <b>2695'</b>	OFFSET GROUP 2: <b>165'</b>	OFFSET GROUP 3: <b>165'</b>	OFFSET GROUP 4: <b>2695'</b>					

DIAGRAMS/MISC. INFORMATION:

SHOTPOINT	TR 10		TR 10		SHOT				SPREAD			REMARKS:	CORR. STACK	
	REEL NO.	REC.	REEL NO.	REC.	SIZE	DEPTH	NO.	OFFSET	DIR.	CDP SWITCH	LINE GROUPS		SET UP	TR 1-41
40	751089	477			10	7541				48	33+4 - 46+4			
41		478			10	7542				52	34+4 - 47+1			
42		479			10	7543				56	35+4 - 48+1			
43		480			10	7544				60/2	36+4 - 49+1	4	RECORDER AT 52	
44		481			10	7545				16	37+4 - 50+1			
45		482			10	7546				20	38+4 - 51+1			
46		483			10	7547				24	39+4 - 52+1			
47		484			10	7548				28	40+4 - 53+1			
48		485			10	7549				32	41+4 - 54+1			
49		486			10	7550				36	42+6 - 55+1			
50		487			10	7551				40	43+6 - 56+1			
51		488			10	7552				46	45+4 - 57+1			
52		489			10	7553				48	46+6 - 58+1			
53		490			10	7554				52	47+6 - 59+1			
54		491			10	7555				56	48+6 - 60+1			
55		492			10	7556				60	49+6 - 61+1			
56		493			10	7557	100	left		64	50+6 - 62+1			
57		494			10	7558				68	51+6 - 63+1			
58		495			10	7559				72	52+6 - 64+1			
59		496			10	7560				76	53+6 - 65+1			

# LAND SEISMIC RECORDING LOG

	CLIENT: Husky	PROSPECT: NPR-A	AREA: Barrow	LINE NO: 651							
	PARTY NO: 1182	INST. ENG: STREFF-Windham		DATE: MO 1 DAY 13 YR 79							
INSTRUMENT (9-TRACK)	<input checked="" type="checkbox"/> 1 SYSTEM <input checked="" type="checkbox"/> 2 SYSTEMS	<input checked="" type="checkbox"/> 1-24 & 25-48 <input checked="" type="checkbox"/> 1-48 & 49-96	ODDS & EVENS	TYPE: <input type="checkbox"/> DFS III <input type="checkbox"/> DFS IV	<input checked="" type="checkbox"/> 9 TRACK <input type="checkbox"/> 21 TRACK	FORMAT: SEG B	<input checked="" type="checkbox"/> GAPPED <input type="checkbox"/> UNGAPPED	PACKING DENSITY:	(LO) <input type="checkbox"/> 356 BPI <input type="checkbox"/> 800 BPI	(HI) <input type="checkbox"/> 712 BPI <input type="checkbox"/> 1600 BPI	
	NO. BYTES IN HEADER REC:	NO. BYTES IN RECORD ID:	NO. BYTES PER SCAN: 134	RECORD NUMBERS: <input checked="" type="checkbox"/> REC <input type="checkbox"/> OCT	GAIN CONSTANT: 36 db	INPUT IMPEDANCE: ohms					
CONFIGURATION (MAG TAPE)	FIELD TRACE NOS.: 1-48				AUXILIARY DATA: (1) TR (2) UT (3) (4) (5) (6) (7)						
	DATA CHANNEL NOS.: 1-48 (ON MAG TAPE)				AUXILIARY CHANNEL NOS.: 2 3						
PARAMETER	RECORD LENGTH: 2 sec.	SAMPLE RATE: <input checked="" type="checkbox"/> 2 ms. <input type="checkbox"/> 4 ms.	GAIN MODE: <input checked="" type="checkbox"/> INITIAL <input type="checkbox"/> MANUAL	FILTERS: FREQ. OUT LO CUT HZ SLOPE		HI CUT HZ SLOPE 70		NOTCH FILTER: <input type="checkbox"/> IN <input checked="" type="checkbox"/> OUT			
DISPLAY	MODE: <input checked="" type="checkbox"/> ACC <input type="checkbox"/> FLOAT <input type="checkbox"/> AMPLIFIER <input type="checkbox"/> DIRECT	INITIAL GAIN: 12 db	TRIP SENS: 12 db	POLARITY CONVENTION: <input type="checkbox"/> NEGATIVE <input checked="" type="checkbox"/> POSITIVE		PRESSURE INCREASE ON GEOPHONE		NUMBERS ON MAG. TAPE		<input type="checkbox"/> DOWNBREAK <input type="checkbox"/> UPBREAK ON DISPLAY	
CFS I	TYPE STACK:	GATE LENGTH:	RECORD REJECTION:	NOISE REDUCTION:		NOISE THRESHOLD:		CORR. SCALING:		R.C.U. NORM./ALT SW.	
SOURCE	TYPE: <input checked="" type="checkbox"/> DYNAMITE <input type="checkbox"/> VIBROSEIS <input type="checkbox"/> OTHER	PATTERN: Single hole - Inline	NO. OF POSITIONS:	INLINE SPACING:	LATERAL SPACING:	STAGGER:	LENGTH:	WIDTH:	LATERAL OFFSET:		
		CHG. HOLE: 40	HOLE DEPTH: 75	SWEEP POSITION:	SWEEP START:	SWEEP END:	SWEEP LENGTH:	SWEEP TAPER:	PHASE COMP:		
RECEIVER	TYPE: GSC-20d	PATTERN: Inline	NO. OF ELEMENTS: 9	INLINE SPACING: 3'		LATERAL SPACING:		LATERAL OFFSET:			
	CONNECTION: Series Parallel	RESISTANCE: 280 ohms	STAGGER:	LENGTH:		WIDTH:		LATERAL OFFSET:			
SPREAD	NO. OF GROUPS: 48	GROUP INTERVAL: 110'	SHOTPOINT INTERVAL: 440'	FOLD: 6		DIRECTION OF PROGRESSION: N → S		LEADING GROUP: 48			
	OFFSET GROUP 1: 2695'	OFFSET GROUP 24: 165'	OFFSET GROUP 25: 165'	OFFSET GROUP 48: 2695'		LEADING GROUP: 48					

DIAGRAMS/MISC. INFORMATION:

SHOTPOINT	TR. 1 to 48		TR. to		SHOT								SPREAD	REMARKS:	CORR. STACK			
	REEL NO.	REC.	REEL NO.	REC.	SIZE	DEPTH	NO.	OFFSET	DIR.	CDP SWITCH	LINE GROUPS	SET UP			TR 1-48	TR 48-96	TR 1-48	TR 48-96
60	251869	497			10	2561					80	5674 - T13	6					
61		498			10	2562					84	5576 - T17						
62		499			10	2563					88	5676 - T21						
63		500			10	2564					92	5774 - T25		T25 dead				
					E. O. DeL...													