

LAND SEISMIC RECORDING LOG

	CLIENT: <i>Husk</i>	PROSPECT: <i>NPR-A</i>	AREA: <i>BARRON</i>	LINE NO: <i>652</i>	
	PARTY NO: <i>1180</i>	INST. ENG: <i>STRICKLAND</i>		DATE: <i>1 DAY 14 TR 79</i>	

INSTRUMENT (9-TRACK)	<input type="checkbox"/> 1 SYSTEM <input type="checkbox"/> 2 SYSTEMS	<input type="checkbox"/> 1-24 & 25-48 <input type="checkbox"/> 1-48 & 49-96	TYPE: <input type="checkbox"/> DFS I <input type="checkbox"/> DFS II <input type="checkbox"/> DFS III <input type="checkbox"/> OTHER	<input type="checkbox"/> 9 TRACK <input type="checkbox"/> 21 TRACK	FORMAT: <i>R</i> SEG:	<input type="checkbox"/> GAPPED <input type="checkbox"/> UNGAPPED	PACKING DENSITY: (L0) <input type="checkbox"/> 356 BPI (H1) <input type="checkbox"/> 712 BPI (H2) <input type="checkbox"/> 1400 BPI
	NO. BYTES IN HEADER REC: <i>1</i>	NO. BYTES IN RECORD ID: <i>134</i>	NO. BYTES PER SCAN: <i>134</i>	RECORD NUMBERS: <input checked="" type="checkbox"/> DEC <input type="checkbox"/> OCT	GAIN CONSTANT: <i>36</i> db	INPUT IMPEDANCE: _____ ohms	
CONFIGURATION (MAG TAPE)	FIELD TRACE NOS.: <i>1-48</i>		DATA CHANNEL NOS.: <i>1-48</i>		AUXILIARY DATA: (1) <i>FB</i> (2) <i>UH</i> (3) _____ (4) _____ (5) _____ (6) _____ (7) _____		
PARAMETER	RECORD LENGTH: <i>2</i> sec.	SAMPLE RATE: <input type="checkbox"/> 1 ms <input type="checkbox"/> 4 ms	GAIN MODE: <input type="checkbox"/> INITIAL <input type="checkbox"/> FINAL	<input type="checkbox"/> MANUAL <input type="checkbox"/> OPERATE	FILTERS: FREQ. <i>OUT</i> LO CUT _____ HZ SLOPE _____		
DISPLAY	MODE: <input type="checkbox"/> AGC <input type="checkbox"/> FLOAT <input type="checkbox"/> DEFLOAT <input type="checkbox"/> AMPLIFIER <input type="checkbox"/> DIRECT	INITIAL GAIN: <i>12</i> db	TRIP SENS: <i>12</i> db	POLARITY CONVENTION: <input type="checkbox"/> POSITIVE <input type="checkbox"/> NEGATIVE	PRESSURE INCREASE ON GEOPHONE: _____		
CFS I	TYPE STACK: _____	GATE LENGTH: _____	RECORD REJECTION: _____	NOISE REDUCTION: _____	NOISE THRESHOLD: _____	CORR. SCALING: _____	R.C.U. NORM/ALT SW: _____

SOURCE	<input type="checkbox"/> DYNAMITE <input type="checkbox"/> VIBROSEIS <input type="checkbox"/> OTHER	PATTERN: <i>Single h-h - inline</i>	NO. OF POSITIONS: _____	INLINE SPACING: _____	LATERAL SPACING: _____	STAGGER: _____	LENGTH: _____	WIDTH: _____	LATERAL OFFSET: _____
RECEIVER	TYPE: <i>GSC-2nd</i>	PATTERN: <i>Inline</i>	NO. OF ELEMENTS: <i>9</i>	INLINE SPACING: <i>3'</i>	LATERAL SPACING: _____	STAGGER: _____	LENGTH: _____	WIDTH: _____	LATERAL OFFSET: _____
SPREAD	CONNECTION: <i>Series Parallel</i>	RESISTANCE: <i>280</i> ohms	STAGGER: _____	LENGTH: _____	WIDTH: _____	LATERAL OFFSET: _____	DIRECTION OF PROGRESSION: <i>S → N</i>		
	NO. OF GROUPS: <i>48</i>	GROUP INTERVAL: <i>110'</i>	SHOTPOINT INTERVAL: <i>440'</i>	FOLD: <i>6</i>	OFFSET GROUP 1: <i>2695'</i>				
	OFFSET GROUP 1: <i>2695'</i>	OFFSET GROUP 2: <i>165'</i>	OFFSET GROUP 25: <i>165'</i>	OFFSET GROUP 48: <i>2695'</i>	LEADING GROUP: <i>48</i>				





SHOTPOINT	TR 1 to 24		TR 25 to 48		SHOT		DIR	CDP SWITCH	SPREAD		REMARKS	CORR. STACK			
	REEL NO.	REC.	REEL NO.	REC.	SIZE	DEPTH			NO.	OFFSET		LINE GROUPS	HT.	REC.	HT.
160	7511870	15116			10	75	11		24	75.25	-55+4	1	RECORDER AT 56/75.25 IS DEAD		
161		15117			10	75	12		28	75.21	-54+4				
160		15118			10	75	13		32	75.17	-53+4				
159		15119			10	75	14		36	75.13	-52+4				
158		15120			10	75	15		40	75.9	-51+4				
157		15121			10	75	16		44	75.5	-50+4				
156		15122			10	75	17		48	75.1	-49+4				
155		15123			10	75	18		52	61+1	-48+4				
154		15124			10	75	19		56	60+1	-47+4				
153		15125			10	75	10		60	59+1	-46+4				
152		15126			10	75	11		64	58+1	-45+4				
151		15127			10	75	12		68	57+1	-44+4	2	RECORDER AT 47		
150		15128			10	75	13		36	56+1	-43+4				
149		15129			10	75	14		40	55+1	-42+4				
148		15130			10	75	15		44	54+1	-41+4				
147		15131			10	75	16		48	53+1	-40+4	3	RECORDER AT 38		
146		15132			10	75	17		16	52+1	-39+4				
145		15133			10	75	18		20	51+1	-38+4				
144		15134			10	75	19		24	50+1	-37+4				
143		15135			10	75	20		28	49+1	-36+4				

LAND SEISMIC RECORDING LOG

	CLIENT: Husky	PROSPECT: NPR-A	AREA: BARROW	LINE NO: 652					
PARTY NO: 1182		INST. ENG: STREFF-WINDHAM			DATE: MO 1 DAY 14 YR 79				
INSTRUMENT	<input type="checkbox"/> 1 SYSTEM <input type="checkbox"/> 2 SYSTEMS	<input type="checkbox"/> 1-24 & 25-48 <input type="checkbox"/> 1-48 & 49-96	ODDS EVENTS	TYPE: <input type="checkbox"/> DFS III <input type="checkbox"/> DFS III <input type="checkbox"/> OTHER	<input checked="" type="checkbox"/> 9 TRACK <input type="checkbox"/> 21 TRACK	FORMAT: B	<input type="checkbox"/> GAPPED <input type="checkbox"/> UNGAPPED	PACKING DENSITY: (LO) <input type="checkbox"/> 356 BPI (HI) <input type="checkbox"/> 712 BPI <input type="checkbox"/> 800 BPI <input type="checkbox"/> 1600 BPI	
[9-TRACK]	NO. BYTES IN HEADER REC:	NO. BYTES IN RECORD ID:	NO. BYTES PER SCAN: 134	RECORD NUMBERS: <input checked="" type="checkbox"/> DEC. <input type="checkbox"/> OCT.	GAIN CONSTANT: 36 db	INPUT IMPEDANCE: _____ ohms.			
CONFIGURATION (MAG TAPE)	FIELD TRACE NOS.: 1-48		AUXILIARY DATA: 413 214			AUXILIARY CHANNEL NOS.: 2 3			
PARAMETER	RECORD LENGTH: 2 sec.	SAMPLE RATE: <input type="checkbox"/> 1 ms. <input type="checkbox"/> 4 ms. <input type="checkbox"/> 2 ms. <input type="checkbox"/> _____ ms.	GAIN MODE: <input checked="" type="checkbox"/> INITIAL <input type="checkbox"/> FINAL <input type="checkbox"/> MANUAL <input type="checkbox"/> OPERATE	FILTERS: FREQ. Out LO CUT _____ HZ SLOPE _____		FREQ. 256 HI CUT 70 NOTCH FILTER: <input type="checkbox"/> IN <input type="checkbox"/> OUT			
DISPLAY	MODE: <input checked="" type="checkbox"/> AGC <input type="checkbox"/> DEFLOAT <input type="checkbox"/> AMPLIFIER DIRECT	INITIAL GAIN: 12 db	JRIP SENS.: 12 db	POLARITY CONVENTION: _____		PRESSURE INCREASE ON GEOPHONE: <input type="checkbox"/> NEGATIVE <input type="checkbox"/> POSITIVE		NUMBERS ON MAG. TAPE: <input type="checkbox"/> DOWNBREAK <input type="checkbox"/> UPBREAK	
CFS I	TYPE STACK:	GATE LENGTH:	RECORD REJECTION:	NOISE REDUCTION:		NOISE THRESHOLD:		CORR. SCALING: _____ R.C.U. NORM/ALT SW.	
SOURCE	TYPE: <input checked="" type="checkbox"/> DYNAMITE <input type="checkbox"/> VIBROSEIS <input type="checkbox"/> OTHER	PATTERN: String to hole - Tailwire	NO. OF POSITIONS:	INLINE SPACING:	LATERAL SPACING:	STAGGER:	LENGTH:	WIDTH:	LATERAL OFFSET:
RECEIVER	TYPE: GSI-20d	PATTERN: TW line	NO. OF ELEMENTS: 9	INLINE SPACING: 3'	LATERAL SPACING:	STAGGER:	LENGTH:	WIDTH:	LATERAL OFFSET:
SPREAD	NO. OF GROUPS: 48	GROUP INTERVAL: 110'	SHOTPOINT INTERVAL: 440'	FOLD: 6	DIRECTION OF PROGRESSION: S → N	LEADING GROUP: 48			
DIAGRAMS/MISC. INFORMATION:									

SHOTPOINT	TR. 1 to 40		TR. _____ to _____		SHOT										SPREAD	REMARKS	CORR. STACK			
	REEL NO.	REC.	REEL NO.	REC.	SIZE	DEPTH	NO.	OFFSET	DIR.	CDP SWITCH	LINE GROUPS		HT.	REC.			HT.	REC.		
121	75V 8170	5316			110	75	21				32	48+1	-35+4							
122		5317			110	75	22				36	47+1	-34+4							
123		5318			110	75	23				40	46+1	-33+4							
124		5319			110	75	24				44	45+1	-32+4							
125		5410			110	75	25				48	44+1	-31+4							
126		5411			110	75	26				52	43+1	-30+4							
127		5412			110	75	27				56	42+1	-29+4							
128		5413			110	75	28				60	41+1	-28+4							
129		5414			110	75	29				64	40+1	-27+4							
130		5415			110	75	30				68	39+1	-26+4							
131		5416			110	75	31				72	38+1	-25+4							
132		5417			110	75	32				76	37+1	-24+4							
133		5418			110	75	33				80	36+1	-23+4							
134		5419			110	75	34				84	35+1	-22+4							
135		5510			110	75	35				88	34+1	-21+4							
136		5511			110	75	36				92	33+1	-20+4							
137		5512			110	75	37				96	32+1	-19+4	4	Recorder @ 17					
138		5513			110	75	38				100	31+1	-18+4							
139		5514			110	75	39				104	30+1	-17+4							
140		5515			110	75	40				108	29+1	-16+4							

LAND SEISMIC RECORDING LOG

	CLIENT: <u>Nasiky</u>	PROSPECT: <u>NPR-A</u>	AREA: <u>BARROW</u>	LINE NO: <u>652</u>					
	PARTY NO: <u>1182</u>	INST. ENG: <u>STREFF-Windham</u>		DATE: <u>1</u> DAY <u>14</u> YR <u>79</u>					
INSTRUMENT (9-TRACK)	<input type="checkbox"/> 1 SYSTEM <input type="checkbox"/> 2 SYSTEMS	<input type="checkbox"/> 1-24 & 25-48 <input type="checkbox"/> 1-48 & 49-96	ODDS EVENTS	TYPE: <input type="checkbox"/> DFS III <input type="checkbox"/> DFS III	<input type="checkbox"/> 9 TRACK <input type="checkbox"/> 27 TRACK	FORMAT: <u>13</u>	<input type="checkbox"/> GAPPED <input type="checkbox"/> UNGAPPED	PACKING DENSITY: (LO) <input type="checkbox"/> 336 BPI (HI) <input type="checkbox"/> 1600 BPI	
	NO. BYTES IN HEADER REC:	NO. BYTES IN RECORD ID:	NO. BYTES PER SCAN: <u>134</u>	RECORD NUMBERS: <input type="checkbox"/> DEC. <input type="checkbox"/> OCT.	GAIN CONSTANT: <u>36</u> db	INPUT IMPEDANCE: _____ ohms.			
CONFIGURATION (MAG TAPE)	FIELD TRACE NOS.: <u>1-48</u>	DATA CHANNEL NOS.: <u>1-48</u>	(ON MAG TAPE)	AUXILIARY DATA: <u>1B</u> <u>12H</u>	AUXILIARY CHANNEL NOS.: <u>2</u> <u>3</u>				
PARAMETER	RECORD LENGTH: <u>2</u> sec.	SAMPLE RATE: <input type="checkbox"/> 1 ms. <input type="checkbox"/> 4 ms. <input type="checkbox"/> 2 ms. <input type="checkbox"/> _____ ms.	GAIN MODE: <input type="checkbox"/> INITIAL <input checked="" type="checkbox"/> TFP	<input type="checkbox"/> MANUAL <input type="checkbox"/> OPERATE	FILTERS: FREQ. <u>OUT</u> LO CUT _____ HZ SLOPE _____	FREQ. <u>256</u> HI CUT _____ HZ SLOPE <u>70</u>	NOTCH FILTER: <input type="checkbox"/> IN <input type="checkbox"/> OUT		
DISPLAY	MODE: <input type="checkbox"/> FLOAT <input type="checkbox"/> AMPLIFIER <input checked="" type="checkbox"/> AGC <input type="checkbox"/> DEFLOAT <input type="checkbox"/> DIRECT	INITIAL GAIN: <u>12</u> db	TRIP SENS: <u>12</u> db	POLARITY CONVENTION: _____	PRESSURE INCREASE ON GEOPHONE: <input type="checkbox"/> POSITIVE	<input type="checkbox"/> NEGATIVE } NUMBERS ON MAG. TAPE	<input type="checkbox"/> DOWNBREAK } ON DISPLAY	<input type="checkbox"/> UPBREAK	
CFS I	TYPE STACK: _____	GATE LENGTH: _____	RECORD REJECTION: _____	NOISE REDUCTION: _____	NOISE THRESHOLD: _____	CORR. SCALING: _____	R.C.U. NORM/ALT SW. _____		
SOURCE	TYPE: <input type="checkbox"/> DYNAMITE <input type="checkbox"/> VIBROSEIS <input type="checkbox"/> OTHER	PATTERN: <u>Single hole: Inline</u>	NO. OF POSITIONS: _____	INLINE SPACING: _____	LATERAL SPACING: _____	STAGGER: _____	LENGTH: _____	WIDTH: _____	LATERAL OFFSET: _____
RECEIVER	TYPE: <u>RSC-20d</u>	PATTERN: <u>Inline</u>	NO. OF ELEMENTS: <u>9</u>	INLINE SPACING: <u>3'</u>	LATERAL SPACING: _____	STAGGER: _____	LENGTH: _____	WIDTH: _____	LATERAL OFFSET: _____
SPREAD	CONNECTION: <u>Series Parallel</u>	RESISTANCE: <u>280</u> ohms	SHOTPOINT INTERVAL: <u>110'</u>	FOLD: <u>6</u>	DIRECTION OF PROGRESSION: <u>S → N</u>	SWEEP START: _____	SWEEP TAPER: _____	PHASE COMP: _____	LEADING GROUP: <u>48</u>

DIAGRAMS/MISC. INFORMATION:

SHOTPOINT	TR 1 to 48		TR 49 to 96		SHOT			SPREAD		REMARKS	CORR. STACK	
	REEL NO.	REC.	REEL NO.	REC.	SIZE	DEPTH	NO. OFFSET	DIR.	CDP SWITCH		LINE GROUPS	TR 1-48
1	7511870	556			110	7.5	41		28	28+1 - 15.4		
2		557			110	7.5	42		32	27+1 - 14.4		
3		558			110	7.5	43	PP W	36	26+1 - 13.4		
4		559			110	7.5	44		40	25+1 - 12.4		
5		560			110	7.5	45		44	24+1 - 11.4		
6		561			110	7.5	46		48	23+1 - 10.4		
7		562			110	7.5	47	3P W	52	22+1 - 9.4		
8		563			110	7.5	48		56	21+1 - 8.4		
9		564			110	7.5	49		60	20+1 - 7.4		
10		565			110	7.5	50		64	19+1 - 6.4		
11		566			110	7.5	51		68	18+1 - 5.4		
12		567			110	7.5	52		72	17+1 - 4.4		
13		568			110	7.5	53		76	16+1 - 3.4		
14		569			110	7.5	54		80	15+1 - 2.4		
15		570			110	7.5	55		84	14+1 - 1.4		
16		571			110	7.5	56		88	13+1 - T5.1		
17		572			110	7.5	57		68	12+1 - T5.5	5	Recorder @ SP-11
18		573			110	7.5	58		72	11+1 - T5.9		
19		574			110	7.5	59		76	10+1 - T5.13		
20		575			110	7.5	60		80	9+1 - T5.17		
21		576			110	7.5	61		84	8+1 - T5.21		
22		578			110	7.5	62		88	7+1 - T5.25		

ICE ROAD SP-1 → T5.1 - NOISE!

Recorder @ SP-11

T5-21 dead

File # 577 - N.G.