


LAND SEISMIC RECORDING LOG

14.5 Hours

	CLIENT: Husky	PROSPECT: NPR-A	AREA: BARROW	LINE NO: 653	
	PARTY NO: 1192	INST. ENG: STROFF-WINDHAM		DATE: MO. 1 DAY 11 YR 79	



INSTRUMENT (9-TRACK)	<input type="checkbox"/> 1 SYSTEM <input type="checkbox"/> 2 SYSTEMS	<input type="checkbox"/> 1-24 & 25-48 <input type="checkbox"/> 1-48 & 49-96	ODDS EVENS <input checked="" type="checkbox"/> ODDS	TYPE: <input type="checkbox"/> DFS I <input type="checkbox"/> DFS II <input type="checkbox"/> DFS III <input type="checkbox"/> OTHER	<input type="checkbox"/> 1 TRACK <input checked="" type="checkbox"/> 2 TRACK	FORMAT: SEG. R	<input type="checkbox"/> GAPPED <input type="checkbox"/> UNGAPPED	PACKING DENSITY: (L) <input type="checkbox"/> 356 BPI (H) <input type="checkbox"/> 712 BPI <input type="checkbox"/> 1600 BPI
NO. BYTES IN HEADER REC:	NO. BYTES IN RECORD ID:	NO. BYTES PER SCAN: 134	RECORD NUMBERS: <input checked="" type="checkbox"/> DEC. <input type="checkbox"/> OCT.	GAIN CONSTANT: 36 db	INPUT IMPEDANCE: ohms.			
CONFIGURATION (MAG TAPE)	FIELD TRACE NOS.: 1-48				AUXILIARY DATA: (1) 78 (2) R-114 (3) (4) (5) (6) (7)			
	DATA CHANNEL NOS.: 1-48 (ON MAG TAPE)				AUXILIARY CHANNEL NOS.: 2 3			
PARAMETER	RECORD LENGTH: 2 sec.	SAMPLE RATE: <input type="checkbox"/> 1 ms. <input type="checkbox"/> 4 ms. <input type="checkbox"/> 2 ms. <input type="checkbox"/> ms.	GAIN MODE: <input type="checkbox"/> INITIAL <input type="checkbox"/> MANUAL <input type="checkbox"/> OPERATE	FILTERS: FREQ. OUT LO CUT HZ SLOPE		H CUT HZ SLOPE 70		NOTCH FILTER: <input type="checkbox"/> IN <input type="checkbox"/> OUT
DISPLAY	MODP: <input type="checkbox"/> FLOAT <input type="checkbox"/> AMPLIFIER <input type="checkbox"/> DIRECT	INITIAL GAIN: 12 db	TRIP SENS: 12 db	POLARITY CONVENTION: PRESSURE INCREASE ON GEOPHONE		NEGATIVE POSITIVE } NUMBERS ON MAG. TAPE		DOWNBREAK } ON DISPLAY
CFS I	TYPE STACK:	GATE LENGTH:	RECORD REJECTION:	NOISE REDUCTION:		NOISE THRESHOLD:	CORR. SCALING:	R.C.U. NORM/ALT SW.

SOURCE	TYPE: <input type="checkbox"/> DYNAMITE <input type="checkbox"/> VIBROSEIS <input type="checkbox"/> OTHER	PATTERN: Single-hole - T-wire	NO. OF POSITIONS:	INLINE SPACING:	LATERAL SPACING:	STAGGER:	LENGTH:	WIDTH:	LATERAL OFFSET:
		CHG/ HOLE: 10 HOLE DEPTH: 75	SWEEP POSITION:	SWEEP START:	SWEEP END:	SWEEP LENGTH:	SWEEP TAPER:	PHASE COMP.	
RECEIVER	TYPE: GSC-20d	PATTERN: T-wire	NO. OF ELEMENTS: 9	INLINE SPACING: 3'	LATERAL SPACING:	STAGGER:	LENGTH:	WIDTH:	LATERAL OFFSET: <u>SE</u>
	CONNECTION: Series-Parallel	RESISTANCE: ohms	STAGGER:	LENGTH:	WIDTH:				
SPREAD	NO. OF GROUPS: 48	GROUP INTERVAL: 110'	SHOTPOINT INTERVAL: 140'	FOLD: 6	DIRECTION OF PROGRESSION: N → S	OFFSET GROUP 1: 2695'	OFFSET GROUP 48/96: 2695'	LEADING GROUP: 48	



SHOTPOINT	TR. 1 to 48		TR. to		SHOT		DIR.	COP SWITCH	SPREAD	REMARKS:	CORR. STACK				
	REEL NO.	REC.	REEL NO.	REC.	SIZE	DEPTH					NO.	OFFSET	LINE GROUPS	TR 1-48	TR 48-96
1	1512	71518167	2915		110	175	67	24	F1 - 45+4	5	F-1 Dead				
2	1513		2916		110	175	68	28	F-5 - 44+4						
3	1514		2917		110	175	69	32	F-9 - 43+4						
4	149		2918		110	175	70	36	F-12 - 42+4						
5	148		2919		110	175	71	40	F-17 - 41+4						
6	147		3020		110	175	72	44	F-21 - 40+4						
7	146		3021		110	175	73	48	F-25 - 39+4						
8	145		3022		110	175	74	52	51+1 - 38+4						
9	144		3023		110	175	75	56	50+1 - 37+4						
10	143		3024		110	175	76	60	49+1 - 36+4		36+4 Dead				

LAND SEISMIC RECORDING LOG

	CLIENT: Husky	PROSPECT: NPR-A	AREA: BARROW	LINE NO: 653					
	PARTY NO: 1182	INST. ENG: STreff - Windham		DATE: MO 1 DAY 12 YR 79					
INSTRUMENT (9-TRACK)	<input checked="" type="checkbox"/> 1 SYSTEM <input type="checkbox"/> 2 SYSTEMS	<input type="checkbox"/> 1-24 & 25-48 <input type="checkbox"/> 1-48 & 49-96	<input checked="" type="checkbox"/> ODDS <input type="checkbox"/> EVENS	TYPE: <input type="checkbox"/> DFS III <input type="checkbox"/> DFS IV <input type="checkbox"/> OTHER	<input checked="" type="checkbox"/> 9 TRACK <input type="checkbox"/> 21 TRACK	FORMAT: A	<input checked="" type="checkbox"/> GAPPED <input type="checkbox"/> UNGAPPED	PACKING DENSITY: (L) <input type="checkbox"/> 356 BPI <input type="checkbox"/> 800 BPI	(H) <input type="checkbox"/> 712 BPI <input type="checkbox"/> 1600 BPI
	NO. BYTES IN HEADER REC:	NO. BYTES IN RECORD ID:	NO. BYTES PER SCAN: 134	RECORD NUMBERS: <input checked="" type="checkbox"/> DEC. <input type="checkbox"/> OCT.	GAIN CONSTANT: 36 db	INPUT IMPEDANCE: _____ ohms.			
CONFIGURATION (MAG TAPE)	FIELD TRACE NOS.: 1-48	DATA CHANNEL NOS.: 1-48	(ON MAG TAPE)	AUXILIARY DATA: TR (1) R-UP (2)	AUXILIARY CHANNEL NOS.: 2 3				
PARAMETER	RECORD LENGTH: 2 sec.	SAMPLE RATE: <input type="checkbox"/> 1 ms. <input type="checkbox"/> 4 ms.	GAIN MODE: <input checked="" type="checkbox"/> INITIAL <input type="checkbox"/> MANUAL <input type="checkbox"/> OPERATE	FILTERS: <input type="checkbox"/> LO CUT <input type="checkbox"/> HZ SLOPE	FREQ. OUT	LO CUT HZ SLOPE	FREQ. 256 HZ SLOPE 70	NOTCH FILTER: <input type="checkbox"/> IN <input type="checkbox"/> OUT	
DISPLAY	MODE: <input type="checkbox"/> AGC <input type="checkbox"/> FLOAT <input type="checkbox"/> AMPLIFIER <input type="checkbox"/> DEFOAT <input type="checkbox"/> DIRECT	INITIAL GAIN: 12 db	TRIP SENS: 12 db	POLARITY CONVENTION: _____	PRESSURE INCREASE ON GEOPHONE: _____	<input type="checkbox"/> NEGATIVE } NUMBERS ON <input type="checkbox"/> POSITIVE } ON MAG TAPE	<input type="checkbox"/> DOWNBREAK } <input type="checkbox"/> UPBREAK } ON DISPLAY		
CFS I	TYPE STACK: _____	GATE LENGTH: _____	RECORD REJECTION: _____	NOISE REDUCTION: _____	NOISE THRESHOLD: _____	CORR. SCALING: _____	R.G.U. NORM/ALT SW. _____		
SOURCE	TYPE: <input checked="" type="checkbox"/> DYNAMITE <input type="checkbox"/> VIBROSEIS <input type="checkbox"/> OTHER	PATTERN: Single hole - Twinline	NO. OF POSITIONS: _____	INLINE SPACING: _____	LATERAL SPACING: _____	STAGGER: _____	LENGTH: _____	WIDTH: _____	LATERAL OFFSET: _____
RECEIVER	TYPE: GSC-20d	PATTERN: Twinline	NO. OF ELEMENTS: 9	INLINE SPACING: _____	LATERAL SPACING: _____	STAGGER: _____	LENGTH: 3'	WIDTH: _____	LATERAL OFFSET: _____
SPREAD	CONNECTION: Series - Parallel	RESISTANCE: _____ ohms	STAGGER: _____	SHOTPOINT INTERVAL: 110'	SHOTPOINT OFFSET GROUP 25: 165'	FOLD: 6	OFFSET GROUP 46/20: 2695'	DIRECTION OF PROGRESSION: N 25 E	LEADING GROUP: 48

DIAGRAMS/MISC. INFORMATION: **SP41 SP48 SP43 SP42 SP41 SP36 SP35**
TR#15 TR#24 TR#25 TR#46
File # 305-370 Daily Test
File # 321 - Test 70

SHOTPOINT	TR. 1 to 48		TR. 49 to 96		SHOT		SPREAD		REMARKS	CORR. STACK					
	REEL NO.	REC.	REEL NO.	REC.	SIZE	DEPTH	NO.	OFFSET		DIR.	CDP SWITCH	LINE GROUPS	HT.	REC.	HT.
142	71511867	13212			110	76	11	11		4	48+1 - 35+4				
141		323			110	75	2	11		8	47+1 - 34+4				
140		1324			110	75	3	11		12	46+1 - 33+4				
139		325			110	75	4	11		16	45+1 - 32+4				
138		1326			110	75	5	11		20	44+1 - 31+4				
137		327			110	75	6	11		24	43+1 - 30+4				
136		328			110	75	7	11		28	42+1 - 29+4				
135		329			110	75	8	11		32	41+1 - 28+4				
134		330			110	75	9	11		36	40+1 - 27+4				
133		331			110	75	10	11		40	39+1 - 26+4				
132		332			110	75	11	110 N		44	38+1 - 25+4				
131		1334			110	75	12	11		48	37+1 - 24+4				
130		335			110	75	13	11		52	36+1 - 23+4				
129		336			110	75	14	11		56	35+1 - 22+4				
128		337			110	75	15	11		60	34+1 - 21+4				
127		338			110	75	16	11		64	33+1 - 20+4				
126		339			110	75	17	11		68	32+1 - 19+4				
125		340			110	75	18	11		72	31+1 - 18+4				
124		341			110	75	19	11		76	30+1 - 17+4				
123		342			110	75	20	11		80	29+1 - 16+4				

