

Ann's Personal Copy

56 S/P I's

Rec.Hrs. - 7

LAND SEISMIC RECORDING LOG

		CLIENT: HUSKY PARTY NO: 1182	PROSPECT: NPR-A INST. ENG: JERRY WINDHAM	AREA: BARROW	LINE NO: 655 DATE: MO 1 DAY 8 YR 79						
INSTRUMENT <input checked="" type="checkbox"/> 1 SYSTEM <input type="checkbox"/> 2 SYSTEMS		ODDS: <input type="checkbox"/> 1-24 & 25-48 <input type="checkbox"/> 1-48 & 49-96 EVENS: <input type="checkbox"/>		TYPE: <input type="checkbox"/> DFS III <input type="checkbox"/> DFS IX <input type="checkbox"/> OTHER		<input checked="" type="checkbox"/> 9 TRACK <input type="checkbox"/> 21 TRACK FORMAT: B SEG:		GAPPED: <input type="checkbox"/> UNGAPPED: <input type="checkbox"/>		PACKING DENSITY: (L) <input type="checkbox"/> 354 BPI (H) <input type="checkbox"/> 712 BPI <input type="checkbox"/> 800 BPI (M) <input type="checkbox"/> 1600 BPI	
NO. BYTES IN HEADER REC:		NO. BYTES IN RECORD ID:		NO. BYTES PER SCAN: 134		RECORD NUMBERS:		DEC: <input checked="" type="checkbox"/> OCT: <input type="checkbox"/>		GAIN CONSTANT: 36 db INPUT IMPEDANCE: 20k ohms.	
FIELD TRACE NOS.: 1-48		DATA CHANNEL NOS.: 1-48		(ON MAG TAPE)		AUXILIARY DATA: WIRE UN (1) T.B. (2) REP III (3)		AUXILIARY CHANNEL NOS.: 1 (4) 2 (5) 3 (6)		(7) (8) (9) (10) (11) (12) (13) (14) (15) (16) (17)	
RECORD LENGTH: 2 sec.		SAMPLE RATE: <input checked="" type="checkbox"/> 1 ms. <input type="checkbox"/> 4 ms. <input type="checkbox"/> 2 ms. <input type="checkbox"/>		GAIN MODE: <input checked="" type="checkbox"/> INITIAL <input type="checkbox"/> MANUAL <input type="checkbox"/> FINAL		FILTERS: <input checked="" type="checkbox"/> FREQ. <input type="checkbox"/> LO CUT <input type="checkbox"/> HZ SLOPE		HI CUT: 256 HZ SLOPE: 70		NOTCH FILTER: <input type="checkbox"/> IN <input type="checkbox"/> OUT	
DISPLAY MODE: <input type="checkbox"/> FLOAT <input type="checkbox"/> AMPLIFIER <input checked="" type="checkbox"/> TRACE <input type="checkbox"/> DIRECT		INITIAL GAIN:		TRIP SENS.:		POLARITY CONVENTION:		PRESSURE INCREASE ON GEOPHONE:		NEGATIVE POSITIVE } NUMBERS ON MAG TAPE <input type="checkbox"/> UPBREAK <input type="checkbox"/> ON DISPLAY	
CFS I TYPE STACK:		GATE LENGTH:		RECORD REJECTION:		NOISE REDUCTION:		NOISE THRESHOLD:		CORR. SCALING:	
SOURCE TYPE: <input type="checkbox"/> DYNAMITE <input type="checkbox"/> VIBROSEIS <input type="checkbox"/> OTHER		PATTERN: INLINE		NO. OF POSITIONS: 1		INLINE SPACING: 440		LATERAL SPACING: 0		STAGGER: 0	
RECEIVER TYPE: 20D		PATTERN: INLINE		NO. OF ELEMENTS: 9		INLINE SPACING: 3FT		LATERAL SPACING: NONE		CONNECTION: SERIES/PARALLEL	
RESISTANCE: 400 ohms		STAGGER: NONE		LENGTH: 24 FT		WIDTH:		LATERAL OFFSET:		NO. OF GROUPS: 48	
GROUP INTERVAL: 110 FT		SHOTPOINT INTERVAL: 440 FT		FOLD: 6		DIRECTION OF PROGRESSION: S.E.		OFFSET GROUP 1: 2695		LEADING GROUP: 48	
OFFSET GROUP 1: 2695		OFFSET GROUP 2: 165		OFFSET GROUP 3: 165		OFFSET GROUP 4: 2695		CORR. SCALING:		R.C.U. NORM/ALT SW.	

DIAGRAMS/MISC. INFORMATION:
 2 GROUP GAP 3' 4' } phone layout
8000000000

SHOTPOINT	TR. 10		TR. 10		SHOT		SPREAD		REMARKS	CORR. STACK			
	REEL NO.	REC.	REEL NO.	REC.	SIZE	DEPTH	NO.	OFFSET		DIR.	TR. 10	TR. 10	TR. 10
01	71518	165			20'	20'	33	33	48	1T - 7+1			
02		174			"	"			52	4T - 8+1			
03		171			"	"			56	8T - 9+1			
04		178							60	12T - 10+1			
05		179							64	16T - 11+1			
* Recs. 100-119 N.G.													

LINE

LAND SEISMIC RECORDING LOG

10 Hours

	CLIENT: Husky	PROSPECT: NPR-A	AREA: Barrow
	PARTY NO: 1182	INST. ENG: Streiff - Windham	LINE NO: 655
			DATE: MO 1 DAY 9 TR 78

INSTRUMENT (9-TRACK)	<input type="checkbox"/> 1 SYSTEM <input type="checkbox"/> 2 SYSTEMS <input type="checkbox"/> 1-24 & 25-48 <input type="checkbox"/> 1-48 & 49-96	ODDS EVENS <input type="checkbox"/> ODDS <input type="checkbox"/> EVENS	TYPE: <input type="checkbox"/> DFS III <input type="checkbox"/> DFS IV <input type="checkbox"/> DFS V <input type="checkbox"/> OTHER	<input type="checkbox"/> 9 TRACK <input type="checkbox"/> 21 TRACK	I.FORMAT: B SEG: B	<input type="checkbox"/> GAPPED <input type="checkbox"/> UNGAPPED	PACKING DENSITY: (L) <input type="checkbox"/> 356 BPI <input type="checkbox"/> 400 BPI (H) <input type="checkbox"/> 712 BPI <input type="checkbox"/> 1000 BPI
	NO. BYTES IN HEADER REC: _____	NO. BYTES IN RECORD ID: _____	NO. BYTES PER SCAN: 134	RECORD NUMBERS: <input checked="" type="checkbox"/> DEC. <input type="checkbox"/> OCT.	GAIN CONSTANT: 36 db	INPUT IMPEDANCE: _____ ohms	


CONFIGURATION (MAG TAPE) FIELD TRACE NOS.: 1-48 DATA CHANNEL NOS.: 1-48 (ON MAG TAPE)	AUXILIARY DATA: W/OUT 78 R-OUT AUXILIARY CHANNEL NOS.: 1 2 3
---	---

PARAMETER	RECORD LENGTH: 2 sec.	SAMPLE RATE: <input type="checkbox"/> 1 ml. <input type="checkbox"/> 4 ml. <input type="checkbox"/> 2 ms. <input type="checkbox"/> 4 ms.	GAIN MODE: <input type="checkbox"/> INITIAL <input type="checkbox"/> MANUAL <input checked="" type="checkbox"/> IFF <input type="checkbox"/> FINAL <input type="checkbox"/> OPERATE	FILTERS: <input type="checkbox"/> LO CUT <input type="checkbox"/> HZ SLOPE <input type="checkbox"/> HI CUT <input type="checkbox"/> HZ SLOPE	FREQ: OUT POLARITY CONVENTION: <input type="checkbox"/> NEGATIVE <input type="checkbox"/> POSITIVE	PRESSURE INCREASE ON GEOPHONE: <input type="checkbox"/> NEGATIVE <input type="checkbox"/> POSITIVE CORE SCALING: _____
DISPLAY	<input type="checkbox"/> MODET <input type="checkbox"/> ACC <input type="checkbox"/> FLOAT <input type="checkbox"/> DEPLOY <input type="checkbox"/> DIRECT	INITIAL GAIN: 12 db	TRIP SENS: 12 db	NOISE REDUCTION: _____	NOISE THRESHOLD: _____	CORE SCALING: _____ A.C.U. NORM/ALT SW.

SOURCE	TYPE: <input checked="" type="checkbox"/> DYNAMIC <input type="checkbox"/> VIBROSEIS <input type="checkbox"/> OTHER	PATTERN: Single hole - Tail line	NO. OF POSITIONS: _____	INLINE SPACING: _____	LATERAL SPACING: _____	STAGGER: _____	LENGTH: _____	WIDTH: _____	LATERAL OFFSET: _____
		CHG/ HOLE: 10	HOLE DEPTH: 75	SWEEP POSITION: _____	SWEEP START: _____	SWEEP END: _____	SWEEP LENGTH: _____	SWEEP PAPER: _____	PHASE COMP. _____

RECEIVER	TYPE: GSC-200	PATTERN: Tail line	NO. OF ELEMENTS: 9	INLINE SPACING: 3'	LATERAL SPACING: _____	STAGGER: _____	LENGTH: _____	WIDTH: _____	LATERAL OFFSET: _____
	CONNECTION: Series - Parallel	RESISTANCE: _____	ohms	STAGGER: _____	LENGTH: _____	WIDTH: _____	LATERAL OFFSET: _____		

SPREAD	NO. OF GROUPS: 48	GROUP INTERVAL: 110'	SHOTPOINT INTERVAL: 440'	FOLD: 6	DIRECTION OF PROGRESSION: NW -> SE
	OFFSET GROUP 1: 2695	OFFSET GROUP 2: 165	OFFSET GROUP 25: 165	OFFSET GROUP 48/20: 2695	LEADING GROUP: 48



SHOTPOINT	TR 1-10		TR 10-20		SHOT		SPREAD		REMARKS	CORE STACK		
	REEL NO.	REC.	REEL NO.	REC.	SIZE	DEPTH	NO. OFFSET	DIR.		COP SWITCH	LINE GROUPS	TR 1-10
106	7511865	1113			110	175	11	11	20	20T - 12+1	1	Recorder @ SP-13
107		1114			110	175	12	11	24	24T - 13+1		
108		1115			110	175	13	11	28	14+ - 14+1		*File # 115 - mis fire
109		1117			110	175	14	11	32	24+ - 15+1		
110		1118			110	175	15	11	36	34+ - 16+1		
111		1119			110	175	16	11	40	44+ - 17+1		
112		1120			110	175	17	11	44	54+ - 18+1		
113		1121			110	175	18	11	44	54+ - 18+1		WRONG COP
114		1120			110	175	19	11	52	74+ - 20+1		54+ Dead
115		1123			110	175	110	11	56	84+ - 21+1		
116		1124			110	175	111	11	60	94+ - 22+1		
117		1125			110	175	112	11	64	104+ - 23+1		
118		1126			110	175	113	11	68	114+ - 24+1		
119		1127			110	175	114	11	72	124+ - 25+1		
120		1128			110	175	115	1165 SE	78	14+2 - 26+3		Inline offset
121		1129			110	175	116	11	80	144+ - 27+1		
122		1130			110	175	117	11	84	154+ - 28+1		
123		1131			110	175	118	11	88	164+ - 29+1		
124		1132			110	175	119	11	92	174+ - 30+1		
125		1133			110	175	120	11	0	184+ - 31+1	2	Recorder @ SP-37

LAND SEISMIC RECORDING LOG


		CLIENT: <u>Husky</u>	PROSPECT: <u>12R-A</u>	AREA: <u>Barrow</u>	LINE NO: <u>655</u>				
PARTY NO: <u>1182</u>		INST. ENG: <u>Streiff - Windham</u>		DATE: <u>MO 1 DAY 9 YR 78</u>					
INSTRUMENT (9-TRACK)	<input type="checkbox"/> 1 SYSTEM <input type="checkbox"/> 2 SYSTEMS	<input type="checkbox"/> 1-24 & 25-48 <input type="checkbox"/> 1-48 & 49-96	ODDS EVENTS	TYPE: <input type="checkbox"/> D75 III <input type="checkbox"/> D75 II <input type="checkbox"/> D75 I <input type="checkbox"/> OTHER	<input type="checkbox"/> 9 TRACK <input type="checkbox"/> 21 TRACK	FORMAT: <u>B</u> SEG	<input type="checkbox"/> GAPPED <input type="checkbox"/> UNGAPPED	PACKING DENSITY: (10) <u>350 BPI</u> <u>400 BPI</u> (11) <input type="checkbox"/> 712 BPI <input type="checkbox"/> 1000 BPI	
	NO. BYTES IN HEADER REC: _____		NO. BYTES IN RECORD ID: _____	NO. BYTES PER SCAN: <u>134</u>	RECORD NUMBERS: <input type="checkbox"/> DEC. <input type="checkbox"/> OCT.	GAIN CONSTANT: <u>36</u> db	INPUT IMPEDANCE: _____ ohms.		
CONFIGURATION (MAG TAPE)	FIELD TRACE NOS.: <u>1-48</u>		(ON MAG TAPE)		AUXILIARY DATA: <u>W/L-UT 78</u>	AUXILIARY CHANNEL NOS.: <u>1 2 3</u>			
PARAMETER	RECORD LENGTH: <u>2</u> sec.	SAMPLE RATE: <input type="checkbox"/> 1 ms. <input type="checkbox"/> 2 ms. <input type="checkbox"/> 4 ms. <input type="checkbox"/> 8 ms.	GAIN MODE: <input type="checkbox"/> INITIAL <input type="checkbox"/> MANUAL <input checked="" type="checkbox"/> CLIP <input type="checkbox"/> FINAL <input type="checkbox"/> OPERATE	FILTERS: _____	LO CUT _____	HI CUT _____	NOTCH FILTER: <input type="checkbox"/> IN <input type="checkbox"/> OUT		
DISPLAY	MODE: <input checked="" type="checkbox"/> AGC <input type="checkbox"/> FLOAT <input type="checkbox"/> AMPLIFIER <input type="checkbox"/> DEFLOAT <input type="checkbox"/> DIRECT	INITIAL GAIN: <u>12</u> db	JIP SENS.: <u>12</u> db	POLARITY CONVENTION: _____	PRESSURE INCREASE ON GEOPHONE: _____	<input type="checkbox"/> NEGATIVE POSITIVE	<input type="checkbox"/> NUMBERS ON MAG TAPE <input type="checkbox"/> DOWNBREAK } ON DISPLAY		
CFS I	TYPE STACK: _____	GATE LENGTH: _____	RECORD REJECTION: _____	NOISE REDUCTION: _____	NOISE THRESHOLD: _____	CORR. SCALING: _____	R.C.U. NORM./ALT SW. _____		
SOURCE	TYPE: <input checked="" type="checkbox"/> PYRAMITE <input type="checkbox"/> VIBROSEIS <input type="checkbox"/> OTHER	PATTERN: <u>Single hole - InLine</u>	NO. OF POSITIONS: _____	INLINE SPACING: _____	LATERAL SPACING: _____	STAGGER: _____	LENGTH: _____	WIDTH: _____	LATERAL OFFSET: _____
RECEIVER	TYPE: <u>65C-20d</u>	PATTERN: <u>InLine</u>	RESISTANCE: _____	NO. OF ELEMENTS: <u>9</u>	INLINE SPACING: <u>3'</u>	LATERAL SPACING: _____		WIDTH: _____	
SPREAD	CONNECTION: <u>Series - Parallel</u>	CHG/HOLE: <u>10</u>	SWEEP POSITION: _____	STAGGER: _____	LENGTH: _____	PHASE COMP: _____			
	NO. OF GROUPS: <u>48</u>	GROUP INTERVAL: <u>110'</u>	SHOTPOINT INTERVAL: _____	SHOTPOINT INTERVAL: <u>440'</u>	FOLD: <u>6</u>	DIRECTION OF PROGRESSION: <u>RW → SE</u>			
	OFFSET GROUP 1: <u>2695</u>	OFFSET GROUP 24: <u>165</u>	OFFSET GROUP 25: _____	OFFSET GROUP 25: <u>165</u>	OFFSET GROUP 48/96: <u>2695</u>	LEADING GROUP: <u>48</u>			
DIAGRAMS/MISC. INFORMATION:									

SHOTPOINT	TR		TR		SHOT				SPREAD		REMARKS	CORR. STACK			
	REEL NO.	REC.	REEL NO.	REC.	SIZE	DEPTH	NO.	OFFSET	DIR.	CDP SWITCH		LINE GROUPS	TR	TR	TR
<u>266</u>	<u>751186</u>	<u>37134</u>			<u>1.0</u>	<u>7521</u>				<u>4</u>	<u>19+4-32+1</u>				
<u>267</u>	<u>135</u>				<u>1.0</u>	<u>7522</u>				<u>8</u>	<u>20+4-33+1</u>				
										<u>12</u>	<u>21+4-34+1</u>				
*No Recs. 136-165															

LAND SEISMIC RECORDING LOG

14 hrs.

CLIENT: <u>Husky</u>		PROSPECT: <u>NPR-A</u>		AREA: <u>BARROW</u>		LINE NO. <u>655</u>			
PARTY NO. <u>1182</u>		INST. ENG. <u>Steeff-Windham</u>		DATE: <u>1 DAY 10 79</u>		MO: <u>1</u> DAY <u>10</u> YR <u>79</u>			
INSTRUMENT <input checked="" type="checkbox"/> 1 SYSTEM <input type="checkbox"/> 2 SYSTEMS		NO. BYTES IN HEADER REC: _____ NO. BYTES IN RECORD IS: _____ NO. BYTES PER SCAN: <u>134</u>		TYPE: <input type="checkbox"/> DFS I <input type="checkbox"/> DFS II <input type="checkbox"/> DFS III <input type="checkbox"/> DFS IV <input type="checkbox"/> OTHER		9 TRACK <input type="checkbox"/> 21 TRACK <input type="checkbox"/>		FORMAT: <u>B</u>	
CONFIGURATION (MAG TAPE) FIELD TRACE NOS.: <u>1-48</u> DATA CHANNEL NOS.: <u>1-48</u>		RECORD LENGTH: <u>2</u> sec. SAMPLE RATE: <input checked="" type="checkbox"/> 1 ml. <input type="checkbox"/> 4 ml.		GAIN MODE: <input type="checkbox"/> INITIAL <input type="checkbox"/> MANUAL <input type="checkbox"/> OPERATE		FILTERS: _____		LO CUT _____ HZ SLOPE _____	
PARAMETER MODE: <input checked="" type="checkbox"/> AC <input type="checkbox"/> DC <input type="checkbox"/> FLOAT <input type="checkbox"/> AMPLIFIER <input type="checkbox"/> DIRECT		INITIAL GAIN: <u>12</u> db		TRIP SENS: <u>12</u> db		POLARITY CONVENTION: _____		PRESSURE INCREASE ON GEDPHONE: _____	
DISPLAY <input type="checkbox"/> DYNAMITE <input type="checkbox"/> VIBROSEIS <input type="checkbox"/> OTHER		PATTERN: <u>Single 46-Endline</u>		NO. OF POSITIONS: _____		INLINE SPACING: _____		LATERAL SPACING: _____	
CFS I TYPE STACK: _____		GATE LENGTH: _____		RECORD REJECTION: _____		NOISE REDUCTION: _____		NOISE THRESHOLD: _____	
SOURCE TYPE: _____		CHG. MOLE: <u>10</u>		HOLE DEPTH: <u>75</u>		STAGGER: _____		LENGTH: _____	
RECEIVER TYPE: <u>Qsc-20d</u>		PATTERN: <u>Inline</u>		NO. OF ELEMENTS: <u>9</u>		INLINE SPACING: _____		LATERAL SPACING: _____	
CONNECTION: <u>Series-Parallel</u>		RESISTANCE: _____ ohms		STAGGER: _____		LENGTH: <u>3'</u>		WIDTH: _____	
SPREAD NO. OF GROUPS: <u>48</u>		GROUP INTERVAL: <u>110'</u>		SHOTPOINT INTERVAL: <u>440'</u>		FOLD: <u>6</u>		DIRECTION OF PROGRESSION: <u>NW-SE</u>	
OFFSET GROUP 1: <u>2695</u>		OFFSET GROUP 2: <u>165</u>		OFFSET GROUP 3: <u>165</u>		OFFSET GROUP 4: <u>2695</u>		LEADING GROUP: <u>68</u>	



SHOTPOINT	TR. 10		TR. 20		TR. 30		TR. 40		DIR.	CDP SWITCH	SPREAD LINE GROUPS	REMARKS	CORR. STACK				
	REEL NO.	REC.	REEL NO.	REC.	REEL NO.	REC.	REEL NO.	REC.					TR 1-10	TR 11-20	TR 21-30	TR 31-40	
28	751	165	1164		110	75	1	11		12	21+4 — 34+1	1	RECORDER AT S.P. 37				
29			1165		110	75	2	11		12	21+4 — 34+1		WRONG CDP				
30			1166		110	75	3	11		20	23+4 — 36+1						
31			1167		110	75	4	11		24	24+4 — 37+1						
32			1168		110	75	5	11		28	25+4 — 38+1						
33			1169		110	75	6	11		32	26+4 — 39+1						
34			1170		110	75	7	11		36	27+4 — 40+1						
35			1171		110	75	8	11		40	28+4 — 41+1						
36			1172		110	75	9	11		44	29+4 — 42+1						
37			1173		110	75	10	11		12	30+4 — 43+1	2	RECORDER AT S.P. 46				
38			1174		110	75	11	11		16	31+4 — 44+1						
39			1175		110	75	12	11		20	32+4 — 45+1						
40			1177		110	75	13	11		24	33+4 — 46+1		*FILE # 176 - MISEIRE*				
41			1178		110	66	14	11		28	34+4 — 47+1						
42			1179		110	66	15	11		32	35+4 — 48+1						
43			1180		110	75	16	11		36	36+4 — 49+1						
44			1181		110	75	17	11		40	37+4 — 50+1						
45			1182		110	75	18	11		44	38+4 — 51+1						
46			1183		110	75	19	11		48	39+4 — 52+1	3	RECORDER AT T.S. 2				
47			1184		110	75	20	11		44	40+4 — 53+1						

LAND SEISMIC RECORDING LOG

CLIENT: HUSKY		PROSPECT: NPR-A		AREA: BARROW		LINE NO: 655							
PARTY NO: 1182		INST. ENG: STREFF - WINDHAM				DATE: NO 1 DAY 10 YR 77							
INSTRUMENT (9-TRACK)		NO. BYTES IN HEADER REC:		NO. BYTES IN RECORD ID:		NO. BYTES PER SCAN: 134		RECORD NUMBERS:		GAIN CONSTANT: 36 db		INPUT IMPEDANCE: _____ ohms.	
CONFIGURATION (MAG TAPE)		FIELD TRACE NOS.: 1-48				AUXILIARY DATA:				NO. OF TRACKS: <input checked="" type="checkbox"/> 9 TRACK <input type="checkbox"/> 21 TRACK		PACKING DENSITY: (L) <input type="checkbox"/> 356 BPI (H) <input type="checkbox"/> 712 BPI	
PARAMETER		RECORD LENGTH: 2 sec.		SAMPLE RATE: <input checked="" type="checkbox"/> 1 ms <input type="checkbox"/> 4 ms		GAIN MODE: <input type="checkbox"/> INITIAL <input type="checkbox"/> MANUAL <input type="checkbox"/> OPERATE		FILTERS: FREQ. CUT LO CUT _____ HI CUT _____		CORR. SCALING: _____		CORR. SCALING: _____	
DISPLAY		MODE: <input checked="" type="checkbox"/> AGC <input type="checkbox"/> FLOAT <input type="checkbox"/> AMPLIFIER <input type="checkbox"/> DEFOAT <input type="checkbox"/> DIRECT		INITIAL GAIN: 12 db		TRIP SENS.: 12 db		POLARITY CONVENTION: <input type="checkbox"/> NEGATIVE <input type="checkbox"/> POSITIVE		PRESSURE INCREASE ON GEOPHONE: <input type="checkbox"/> NUMBERS ON MAG TAPE <input type="checkbox"/> DOWNBREAK <input type="checkbox"/> UPBREAK		ON DISPLAY: <input type="checkbox"/> NOTCH FILTER <input type="checkbox"/> OUT	
SOURCE		TYPE: <input checked="" type="checkbox"/> DYNAMITE <input type="checkbox"/> VIBROSEIS <input type="checkbox"/> OTHER		PATTERN: SINGLE HOLE/INLINE		NO. OF POSITIONS: _____		INLINE SPACING: _____		LATERAL SPACING: _____		STAGGER: _____	
RECEIVER		TYPE: GSC-20D		PATTERN: INLINE		NO. OF ELEMENTS: 9		INLINE SPACING: 3'		LATERAL SPACING: _____		STAGGER: _____	
SPREAD		NO. OF GROUPS: 48		GROUP INTERVAL: 110'		SHOTPOINT INTERVAL: 440'		FOLD: 6		DIRECTION OF PROGRESSION: NW → SE		LEADING GROUP: 49	

DIAGRAMS/MISC. INFORMATION:

SHOTPOINT	TR. _____ TO _____		TR. _____ TO _____		SHOT		SPREAD				REMARKS	CORR. STACK				
	REEL NO.	REC.	REEL NO.	REC.	SIZE	DEPTH	NO.	OFFSET	DIR.	CDP SWITCH		LINE GROUPS	SET UP	TR. 1-48	TR. 49-96	TR. 1-48
148	75T1864	1865			110	7521				8	41+4 — 54+1					
149		1866			110	7522				12	42+4 — 55+1					
150		1867			110	7523				16	43+4 — 75.1					
151		1868			110	7524				20	44+4 — 75.5					
152		1869			110	7525				24	45+4 — 75.9					
153		1870			110	7526				28	46+4 — 75.13					
154		1871			110	7527				32	47+4 — 75.17					
155		1872			110	7528				36	48+4 — 75.21					
156		1873			110	7529				40	49+4 — 75.25					F.O.L.