


*Anna Personal Copy*

79 S/P's

LAND SEISMIC RECORDING LOG

14 Hours

CLIENT: <b>Husky</b>		PROSPECT: <b>WPR-A</b>		AREA: <b>BARROW</b>		LINE NO: <b>657</b>	
PARTY NO: <b>1182</b>		INST. ENG: <b>STREFF-WINDHAM</b>		DATE: <b>MO 1 DAY 10 YR 79</b>			
INSTRUMENT: <input checked="" type="checkbox"/> 1 SYSTEM <input type="checkbox"/> 2 SYSTEMS		TYPE: <input type="checkbox"/> DFS <input type="checkbox"/> DFS II <input type="checkbox"/> DFS III <input type="checkbox"/> OTHER		TRACK: <input checked="" type="checkbox"/> 9 TRACK <input type="checkbox"/> 21 TRACK		FORMAT: <b>B</b>	
NO. BYTES IN HEADER REC: _____		NO. BYTES IN RECORD ID: _____		NO. BYTES PER SCAN: <b>134</b>		RECORD NUMBERS: _____	
FIELD TRACE NOS.: <b>1-48</b>		DATA CHANNEL NOS.: <b>1-48</b>		AUXILIARY DATA: <b>W/H W/H TR R-UH</b>		AUXILIARY CHANNEL NOS.: <b>1 2 3</b>	
PARAMETER: RECORD LENGTH: <b>2</b>		SAMPLE RATE: <input type="checkbox"/> 1 ms <input type="checkbox"/> 4 ms		GAIN MODE: <input type="checkbox"/> INITIAL <input type="checkbox"/> MANUAL <input type="checkbox"/> OPERATE		FILTERS: _____	
DISPLAY: MODE: <input type="checkbox"/> FLOAT <input type="checkbox"/> AMPLIFIER <input type="checkbox"/> DIRECT		INITIAL GAIN: <b>12</b>		TRIP SENS: <b>12</b>		POLARITY CONVENTION: _____	
SOURCE: TYPE: <input checked="" type="checkbox"/> DYNAMITE <input type="checkbox"/> VIBROSEIS <input type="checkbox"/> OTHER		PATTERN: <b>Single hole - inline</b>		NO. OF POSITIONS: _____		INLINE SPACING: _____	
RECEIVER: TYPE: <b>GSC-20d</b>		PATTERN: <b>inline</b>		NO. OF ELEMENTS: <b>9</b>		INLINE SPACING: <b>3'</b>	
SPREAD: NO. OF GROUPS: <b>48</b>		GROUP INTERVAL: <b>110'</b>		SHOTPOINT INTERVAL: <b>440'</b>		FOLO: <b>6</b>	
DIAGRAMS/MISC. INFORMATION:		GROUP OFFSET: <b>2695'</b>		SHOTPOINT GROUP 25: <b>165'</b>		OFFSET GROUP 48/96: <b>2695'</b>	



SHOTPOINT	TR. 1 - no 48		TR. 2 - no 48		SHOT		DIR.	CDP SWITCH	LINE GROUPS	REMARKS:	CORE STACK			
	REEL NO.	REC.	REEL NO.	REC.	SIZE	DEPTH					NO.	OFFSET	TR 1-48	TR 2-48
1	1818	666	1196		110	175	30	24	T25 - 7H	Bad Time bank				
2			1198		110	175	31	28	T31 - 8H	File # 197 Mis Fire *				
3			1199		110	175	32	32	T17 - 9H					
4			2000		110	175	33	36	T12 - 10H					
5			2011		110	175	34	40	T9 - 11H					
6			2004		110	175	35	44	T5 - 12H	File # 202 & 203 - Mis Fire *				
7			2005		110	175	36	48	T1 - 13H					
8			2006		110	175	37	52	T4 - 14H					
9			2007		110	176	38	56	2+4 - 15H					
10			2008		110	174	39	60	3+4 - 16H					
11			2009		110	171	40	64	4+4 - 17H					
12			2100		110	175	41	68	5+4 - 18H					
13			3101		110	175	42	72	6+4 - 19H	TRACE 48 - (19H) Dead				

# LAND SEISMIC RECORDING LOG

<b>CLIENT:</b> Husky	<b>PROSPECT:</b> NPR-A	<b>AREA:</b> BARROW	<b>LINE NO.:</b> 657
<b>PARTY NO.:</b> 1182	<b>INST. ENG.:</b> STREFF - Windham		<b>DATE:</b> NO 1 DAY 11 YR 79

<b>INSTRUMENT</b> (9-TRACK)	<input type="checkbox"/> 1 SYSTEM <input type="checkbox"/> 2 SYSTEMS	<input type="checkbox"/> 1-24 & 25-48 <input type="checkbox"/> 1-48 & 49-96	<b>TYPE:</b> <input type="checkbox"/> DFS III <input type="checkbox"/> DFS IV <input checked="" type="checkbox"/> DFS V <input type="checkbox"/> OTHER	<input checked="" type="checkbox"/> 9 TRACK <input type="checkbox"/> 21 TRACK	<b>FORMAT:</b> SEG B	<input type="checkbox"/> GAPPED <input type="checkbox"/> UNGAPPED	<b>PACKING DENSITY:</b> (10) <input type="checkbox"/> 356 BPI (11) <input type="checkbox"/> 800 BPI (12) <input type="checkbox"/> 712 BPI (13) <input type="checkbox"/> 1600 BPI
<b>NO. BYTES IN HEADER REC:</b>	<b>NO. BYTES IN RECORD ID:</b>	<b>NO. BYTES PER SCAN:</b> 134	<b>RECORD NUMBERS:</b> DEC <input checked="" type="checkbox"/> OCT <input type="checkbox"/>	<b>GAIN CONSTANT:</b> 36 db	<b>INPUT IMPEDANCE:</b> ohms		

<b>CONFIGURATION (MAG TAPE)</b>	<b>FIELD TRACE NOS.:</b> 1-48 <b>DATA CHANNEL NOS.:</b> 1-48 (ON MAG TAPE)	<b>AUXILIARY DATA:</b> (1) WLL # (2) TD (3) R-4H (4) (5) (6) (7) <b>AUXILIARY CHANNEL NOS.:</b> 1 2 3
---------------------------------	---	--

<b>PARAMETER</b>	<b>RECORD LENGTH:</b> 2 sec.	<b>SAMPLE RATE:</b> <input type="checkbox"/> 1 ms. <input type="checkbox"/> 4 ms. <input type="checkbox"/> 2 ms. <input type="checkbox"/> 8 ms.	<b>GAIN MODE:</b> <input type="checkbox"/> INITIAL <input type="checkbox"/> MANUAL <input type="checkbox"/> OPERATE <input checked="" type="checkbox"/> TRIP	<b>FILTERS:</b> LO CUT HZ SLOPE: _____ HI CUT HZ SLOPE: 70 FREQ. OUT	<b>NOTCH FILTER:</b> <input type="checkbox"/> IN <input type="checkbox"/> OUT		
<b>DISPLAY</b>	<input type="checkbox"/> MODE: <input type="checkbox"/> FLOAT <input type="checkbox"/> AMPLIFIER <input type="checkbox"/> DIRECT <input type="checkbox"/> AGC <input type="checkbox"/> DEFLAT	<b>INITIAL GAIN:</b> 12 db	<b>TRIP SENS.:</b> 12 db	<b>POLARITY CONVENTION:</b> PRESSURE INCREASE ON GEOPHONE: <input type="checkbox"/> NEGATIVE <input type="checkbox"/> POSITIVE	<b>NUMBERS ON MAG. TAPE:</b> <input type="checkbox"/> DOWNBREAK <input type="checkbox"/> UPBREAK ON DISPLAY		
<b>CFS I</b>	<b>TYPE STACK:</b> _____	<b>GATE LENGTH:</b> _____	<b>RECORD REJECTION:</b> _____	<b>NOISE REDUCTION:</b> _____	<b>NOISE THRESHOLD:</b> _____	<b>CORR. SCALING:</b> _____	<input type="checkbox"/> R.C.U. NORM/ALT SW.

<b>SOURCE</b>	<b>TYPE:</b> <input checked="" type="checkbox"/> DYNAMITE <input type="checkbox"/> VIBROSEIS <input type="checkbox"/> OTHER	<b>PATTERN:</b> Single hole - inline CHG/ HOLE: 10	<b>NO. OF POSITIONS:</b> _____ <b>HOLE DEPTH:</b> 75	<b>INLINE SPACING:</b> _____ <b>SWEEP START:</b> _____	<b>LATERAL SPACING:</b> _____ <b>SWEEP END:</b> _____	<b>STAGGER:</b> _____ <b>SWEEP LENGTH:</b> _____	<b>LENGTH:</b> _____ <b>SWEEP TAPER:</b> _____	<b>WIDTH:</b> _____ <b>PHASE COMP.</b> _____	<b>LATERAL OFFSET:</b> _____
---------------	--	---	---	---	--	---	---	---	------------------------------

<b>RECEIVER</b>	<b>TYPE:</b> GSC-200 <b>CONNECTION:</b> Series-Parallel	<b>PATTERN:</b> IN line <b>RESISTANCE:</b> _____ ohms	<b>NO. OF ELEMENTS:</b> 9 <b>STAGGER:</b> _____	<b>INLINE SPACING:</b> 3' <b>LENGTH:</b> _____	<b>LATERAL SPACING:</b> _____ <b>WIDTH:</b> _____	<b>LATERAL OFFSET:</b> _____
-----------------	--	--	--	---	--	------------------------------

<b>SPREAD</b>	<b>NO. OF GROUPS:</b> 48 <b>OFFSET GROUP 1:</b> 2695'	<b>GROUP INTERVAL:</b> 110' <b>OFFSET GROUP 24:</b> 165'	<b>SHOTPOINT INTERVAL:</b> 440' <b>OFFSET GROUP 25:</b> 165'	<b>FOLD:</b> 6 <b>OFFSET GROUP 48/96:</b> 2695'	<b>DIRECTION OF PROGRESSION:</b> SW → NE <b>LEADING GROUP:</b> 48
---------------	--	---	---	--	--



SHOTPOINT	TR. 1 to 48		TR. 10 to		SHOT		SPREAD		REMARKS	CORR. STACK					
	REEL NO.	REC.	REEL NO.	REC.	SIZE	DEPTH	NO.	OFFSET		DIR.	CDP SWITCH	LINE GROUPS	TR. 1-48	TR. 41-48	
													HY.	REC.	HY.
114	25106	228			110	76	11	37		28	7+4 - 20+1	1			
115		229			110	75	12	37		32	8+4 - 21+1				
116		220			110	76	13	37		36	9+4 - 22+1				
117		221			110	75	14	37		40	10+4 - 23+1				
118		222			110	75	15	37		44	11+4 - 24+1				
119		222			110	75	16	37		48	12+4 - 25+1				
120		224			110	75	17	37		52	13+4 - 26+1				
121		225			110	75	18	37		56	14+4 - 27+1				
122		226			110	75	19	37		24	15+4 - 28+1	2	Recorder @ SA-28		
123		227			110	75	20	37		28	16+4 - 29+1				
124		228			110	76	21	37		32	17+4 - 30+1				
125		229			110	76	22	37		36	18+4 - 31+1				
126		240			110	76	23	37		40	19+4 - 32+1				
127		241			110	75	24	37		44	20+4 - 33+1				
128		242			110	75	25	37		48	21+4 - 34+1				
129		243			110	76	26	37		52	22+4 - 35+1				
130		244			110	76	27	37		56	23+4 - 36+1				
131		245			110	76	28	37		60	24+4 - 37+1				
132		246			110	76	29	37		64	25+4 - 38+1				
133		247			110	76	30	37		68	26+4 - 39+1				



## LAND SEISMIC RECORDING LOG

CLIENT: <b>Husky</b>		PROSPECT: <b>NPR-A</b>		AREA: <b>Barrow</b>		LINE NO.: <b>657</b>	
PARTY NO.:		INST. ENG.:		DATE:		NO. 1 DAY 11 79	
INSTRUMENT (9-TRACK)		NO. BYTES IN HEADER REC.:		NO. BYTES IN RECORD ID.:		NO. BYTES PER SCAN: <b>134</b>	
CONFIGURATION (MAG TAPE)		FIELD TRACE NOS.: <b>1-48</b>		DATA CHANNEL NOS.: <b>1-48</b>		AUXILIARY DATA: <b>WJL-48 78 R-48</b>	
PARAMETER		RECORD LENGTH: <b>2</b>		SAMPLE RATE: <input type="checkbox"/> 1 sec <input type="checkbox"/> 4 ms		GAIN MODE: <input type="checkbox"/> INITIAL <input type="checkbox"/> MANUAL <input type="checkbox"/> OPERATE	
DISPLAY		MODE: <input type="checkbox"/> FLOAT <input type="checkbox"/> AMPLIFIER <input type="checkbox"/> DIRECT		INITIAL GAIN: <b>12</b> db		JIP SENS: <b>12</b> db	
CFS I		TYPE STACK:		GATE LENGTH:		RECORD REJECTION:	
SOURCE		TYPE: <input type="checkbox"/> DYNAMITE <input type="checkbox"/> VIBROSEIS <input type="checkbox"/> OTHER		PATTERN: <b>Single hole - Inline</b>		NO. OF POSITIONS:	
RECEIVER		TYPE: <b>GSC-20d</b>		CONNECTION: <b>Series-Parallel</b>		RESISTANCE:	
SPREAD		NO. OF GROUPS: <b>48</b>		GROUP INTERVAL: <b>110'</b>		SHOTPOINT INTERVAL: <b>440'</b>	
		OFFSET GROUP 1: <b>2695'</b>		OFFSET GROUP 24: <b>165'</b>		OFFSET GROUP 25: <b>165'</b>	
						FOLD: <b>6</b>	
						DIRECTION OF PROGRESSION: <b>SW → NE</b>	
						LEADING GROUP: <b>48</b>	

DIAGRAMS/MISC. INFORMATION:

SHOTPOINT	TR. 1 to 48		TR. 10		SHOT		SPREAD		REMARKS	CORR. STACK	
	REEL NO.	REC.	REEL NO.	REC.	SIZE	DEPTH	NO.	OFFSET		TR. 1-24	TR. 25-48
34	2148	2148			110	76	21	72	274 - 40+1	2	
35	2149				110	76	22	76	284 - 41+1		
36	2150				110	76	23	80	294 - 42+1		
37	2151				110	76	24	84	304 - 43+1		
38	2152				110	76	25	16	314 - 44+1	3	Recorder @ SP41
39	2153				110	76	26	20	324 - 45+1		
40	2154				110	76	27	24	334 - 46+1		No 13 dual
41	2155				110	76	28	28	344 - 47+1		
42	2156				110	76	29	32	354 - 48+1		
43	2157				110	76	30	36	364 - 49+1		
44	2158				110	76	31	40	374 - 50+1		
45	2159				110	76	32	44	384 - 51+1		
46	2160				110	76	33	48	394 - 52+1		
47	2161				110	76	34	52	404 - 53+1		
48	2162				110	76	35	56	414 - 54+1		
49	2163				110	76	36	60	424 - 55+1		
50	2164				110	76	37	16	434 - 56+1	4	Recorder @ SP58
51	2165				110	76	38	20	444 - 57+1		
52	2166				110	76	39	24	454 - 58+1		
53	2167				110	76	40	28	464 - 59+1		

# LAND SEISMIC RECORDING LOG

	CLIENT: <u>Husky</u>	PROSPECT: <u>NPR-A</u>	AREA: <u>BARROW</u>	LINE NO: <u>657</u>						
PARTY NO: <u>1192</u>		INST. ENG: <u>STREff - Windham</u>		DATE: <u>11.79</u>						
INSTRUMENT (9-TRACK)	<input type="checkbox"/> 1 SYSTEM <input type="checkbox"/> 2 SYSTEMS	<input type="checkbox"/> 1-24 & 25-48 <input type="checkbox"/> 1-48 & 49-96	<input type="checkbox"/> ODDS <input type="checkbox"/> EVENS	TYPE: <input type="checkbox"/> DFS III <input type="checkbox"/> DFS IV <input type="checkbox"/> OTHER	<input type="checkbox"/> 9 TRACK <input type="checkbox"/> 21 TRACK	FORMAT: <u>B</u>	<input type="checkbox"/> GAPPED <input type="checkbox"/> UNGAPPED	PACKING DENSITY: (L) <input type="checkbox"/> 356 BPI <input type="checkbox"/> 800 BPI	(H) <input type="checkbox"/> 712 BPI <input type="checkbox"/> 1500 BPI	
	NO. BYTES IN HEADER REC:	NO. BYTES IN RECORD ID:	NO. BYTES PER SCAN: <u>136</u>	RECORD NUMBERS: <input type="checkbox"/> DEC. <input type="checkbox"/> OCT.	GAIN CONSTANT: <u>36</u> db	INPUT IMPEDANCE: _____ ohms.				
CONFIGURATION (MAG TAPE)	FIELD TRACE NOS.: <u>1-48</u>			AUXILIARY DATA: (1) <u>W-UH</u> (2) <u>73</u> (3) <u>R-UH</u> (4) _____ (5) _____ (7) _____			AUXILIARY CHANNEL NOS.: <u>1</u> <u>2</u> <u>3</u>			
PARAMETER	RECORD LENGTH: <u>2</u> sec.	SAMPLE RATE: <input type="checkbox"/> 1 ms. <input type="checkbox"/> 4 ms. <input type="checkbox"/> 2 ms. <input type="checkbox"/> _____ ms.	GAIN MODE: <input type="checkbox"/> INITIAL <input type="checkbox"/> FINAL	<input type="checkbox"/> MANUAL <input type="checkbox"/> OPERATE	FILTERS: FREQ. <u>Out</u>	LO CUT HZ SLOPE: _____	HIGH CUT HZ SLOPE: <u>70</u>	NOTCH FILTER: <input type="checkbox"/> IN <input type="checkbox"/> OUT		
DISPLAY	MODE: <input type="checkbox"/> FLOAT <input type="checkbox"/> AMPLIFIER <input type="checkbox"/> GAGC <input type="checkbox"/> DEFLOAT <input type="checkbox"/> DIRECT	INITIAL GAIN: <u>12</u> db	TRIP SENS: <u>12</u> db	POLARITY CONVENTION: _____	PRESSURE INCREASE ON GEOPHONE: <input type="checkbox"/> NEGATIVE <input type="checkbox"/> POSITIVE	NUMBERS ON MAG. TAPE: _____		DOWNBREAK UPBREAK: <input type="checkbox"/> ON DISPLAY <input type="checkbox"/> OFF		
CFS I	TYPE STACK: _____	GATE LENGTH: _____	RECORD REJECTION: _____	NOISE REDUCTION: _____	NOISE THRESHOLD: _____	CORR. SCALING: _____	R.C.U. NORM/ALT SW: _____			
SOURCE	TYPE: <input checked="" type="checkbox"/> DYNAMITE <input type="checkbox"/> VIBROSEIS <input type="checkbox"/> OTHER	PATTERN: <u>Single hole - inline</u>	NO. OF POSITIONS: _____	INLINE SPACING: _____	LATERAL SPACING: _____	STAGGER: _____	LENGTH: _____	WIDTH: _____	LATERAL OFFSET: _____	
RECEIVER	TYPE: <u>656-20d</u>	PATTERN: <u>Inline</u>	NO. OF ELEMENTS: <u>9</u>	INLINE SPACING: <u>3'</u>	LATERAL SPACING: _____	STAGGER: _____	LENGTH: _____	WIDTH: _____	LATERAL OFFSET: _____	
SPREAD	CONNECTION: <u>Series - Parallel</u>	RESISTANCE: _____ ohms	STAGGER: _____	LENGTH: _____	WIDTH: _____	LATERAL OFFSET: _____	NO. OF GROUPS: <u>48</u>			
	GROUP INTERVAL: <u>110'</u>	SHOTPOINT INTERVAL: <u>440'</u>	FOLD: <u>6</u>	DIRECTION OF PROGRESSION: <u>SW -&gt; NE</u>			OFFSET GROUP 1: <u>2695</u>			
	GROUP 2: <u>165'</u>	OFFSET GROUP 2: <u>165'</u>	OFFSET GROUP 2: <u>25</u>	OFFSET GROUP 2: <u>165'</u>	OFFSET GROUP 2: <u>2695</u>	LEADING GROUP: <u>48</u>	DIAGRAMS/MISC. INFORMATION:			

SHOTPOINT	TR. 1 to 12		TR. 13 to 24		TR. 25 to 36		TR. 37 to 48		SHOT NO.	DEPTH	OFFSET	DIR.	CDP SWITCH	SPREAD	REMARKS	CORR. STACK					
	REEL NO.	REC.	REEL NO.	REC.	REEL NO.	REC.	REEL NO.	REC.								TR 1-12	TR 13-24	TR 25-36	TR 37-48		
54	75118166	12169							110	775	611		32	47ft - 60+1	4	File # 268 - mis fire					
55		2170							110	775	612		36	48ft - 61+1							
56		2171							110	775	613		40	49ft - 62+1							
57		2172							110	775	614		44	50ft - 63+1							
58		2173							110	775	615		48	51ft - 64+1		63+2 dead					
59		2174							110	775	616		52	52ft - 65+1							
60		2175							110	775	617		56	53ft - 66+1							
61		2176						5	770	775	618		60	54ft - 67+1							
62		2177						5	770	775	619		64	55ft - 68+1							
63		2178						5	770	775	620		68	56ft - 69+1							
64		2179							110	775	621		70	58ft - 70+1		wrong CDP					
65		2180							110	775	622		60	58ft - 71+1							
66		2181							110	775	623		64	59ft - 72+1							
67		2182							110	775	624		68	60ft - 73+1							
68		2183							110	775	625		72	61ft - 74+1							
69		2184							110	775	626		76	62ft - 75+1							
70		2185							110	775	627		80	63ft - 76+1							
71		2186							110	775	628	NE	84	64ft - 77+1		inline offset - cables plugged together wrong					
72		2187							110	775	629		88	65ft - 78+1							
73		2188							110	775	630		92	66ft - 79+1							

