

Ann's Copy

LAND SEISMIC RECORDING LOG

CLIENT: *Husky* PROSPECT: *NPR-1* AREA: *BARROW* LINE NO.: *659 W*

PARTY NO.: *1182* INST. ENG.: *STREFF-WINDHAM* DATE: *NOV 3 1979*

INSTRUMENT: 1 SYSTEM 7 SYSTEMS 1-24 & 25-48 ODDS 1-48 & 49-96 EVENS TYPE: DFS III DFS II DFS I OTHER

NO. TRACKS: 9 TRACK 27 TRACK FOPMAT: *B* GAPPED UNGAPPED PACKING DENSITY: (10) 356 BPI (11) 712 BPI (12) 1000 BPI

NO. BYTES IN RECORD ID: _____ NO. BYTES PER SCAN: *134* RECORD NUMBERS: DEC. OCT. GAIN CONSTANT: *36* db INPUT IMPEDANCE: *20,000* ohms

CONFIGURATION (MAG TAPE): FIELD TRACE NOS.: *1-48* DATA CHANNEL NOS.: *1-48* (ON MAG TAPE) AUXILIARY DATA: (1) *7B* (2) *4H* (3) _____ (4) _____ (5) _____ (6) _____ (7) _____

PARAMETER: RECORD LENGTH: *6* sec. SAMPLE RATE: 1ms 4ms. 2ms. GAIN MODE: INITIAL MANUAL OPERATE FINAL

DISPLAY: MODE: SGC FLOAT DIRECT AMPLIFIER INITIAL GAIN: *18* db TRIP SENS.: *18* db POLARITY CONVENTION: NEGATIVE POSITIVE

CFS I: TYPE STACK: _____ GATE LENGTH: _____ RECORD REJECTION: _____ NOISE REDUCTION: _____ NOISE THRESHOLD: _____ CORE SCALING: _____

SOURCE: TYPE: DYNAMITE VIBROSEIS OTHER PATTERN: *Single hole - inline* NO. OF POSITIONS: _____ INLINE SPACING: _____ LATERAL SPACING: _____ SWEEP START: _____ SWEEP END: _____ SWEEP LENGTH: _____ SWEEP TAPER: _____ SWEEP COMP: _____

RECEIVER: TYPE: *6 SC-20d* CONNECTION: *Serlex Parallel* RESISTANCE: *560* ohms STAGGER: _____ NO. OF ELEMENTS: *18* INLINE SPACING: *12'* LATERAL SPACING: _____ WIDTH: _____ LATERAL OFFSET: _____

SPREAD: NO. OF GROUPS: *48* GROUP INTERVAL: *220'* SHOTPOINT INTERVAL: *880'* FOLD: *6* DIRECTION OF PROGRESSION: *E → W (SE-NW)* LEADING GROUP: *48* OFFSET GROUP 1: *5170'* OFFSET GROUP 2: *110'* OFFSET GROUP 3: _____ OFFSET GROUP 4: _____

DIAGRAMS/MISC. INFORMATION: *24-group trail* *TR-24* *TR-25* *TR-48* *SP-1* *SP-2* *SP-7* *SP-20* *SP-21* *SP-22* *SP-23* *SP-24* *SP-25* *SP-26* *SP-27* *SP-28* *SP-29* *SP-30* *SP-31* *SP-32* *SP-33* *SP-34* *SP-35* *SP-36* *SP-37* *SP-38* *SP-39* *SP-40* *SP-41* *SP-42* *SP-43* *SP-44* *SP-45* *SP-46* *SP-47* *SP-48* *SP-49* *SP-50* *SP-51* *SP-52* *SP-53* *SP-54* *SP-55* *SP-56* *SP-57* *SP-58* *SP-59* *SP-60* *SP-61* *SP-62* *SP-63* *SP-64* *SP-65* *SP-66* *SP-67* *SP-68* *SP-69* *SP-70* *SP-71* *SP-72* *SP-73* *SP-74* *SP-75* *SP-76* *SP-77* *SP-78* *SP-79* *SP-80* *SP-81* *SP-82* *SP-83* *SP-84* *SP-85* *SP-86* *SP-87* *SP-88* *SP-89* *SP-90* *SP-91* *SP-92* *SP-93* *SP-94* *SP-95* *SP-96* *SP-97* *SP-98* *SP-99* *SP-100*

SHOTPOINT	TR. 1 to 48		TR. 49 to 96		SHOT		DIR.	COP SWITCH	LINE GROUPS	REMARKS	CORR STACK			
	REEL NO.	REC.	REEL NO.	REC.	SIZE	DEPTH					NO.	OFFSET	TR. 1-10	TR. 11-20
1	71519110	609			20	67	17	25	T1 - 6+4	Recorded @ SP-7 File # 608 - Danny Board				
2		610			20	67	18	29	T5 - 7+4					
3		611			20	67	19	33	T9 - 8+4					
4		612			20	67	10	37	T-13 - 9+4					
5		613			20	67	11	41	F-17 - 10+4					
6		614			20	67	12	45	F-21 - 11+4					
7		615			20	67	13	49	1+1 - 12+4					
8		616			20	67	14	53	2+1 - 13+4					
9		617			20	67	15	57	3+1 - 14+4					
10		618			20	67	16	61	4+1 - 15+4					
11		619			20	67	17	65	5+1 - 16+4					
12		620			20	67	18	69	6+1 - 17+4					
13		621			20	67	19	73	7+1 - 18+4					
14		622			20	61	20	77	8+1 - 19+4		Recorded @ SP-20+2			
15		623			20	67	21	27	9+1 - 20+4					
16		624			20	67	22	31	10+1 - 21+4					
17		625			20	67	23	31	10+1 - 21+4		Recorded SP-17			
18		626			20	67	24	39	13+1 - 23+4					
19		627			20	67	25	43	13+1 - 24+4					
20		628			20	67	26	47	14+1 - 25+4					

16011

LAND SEISMIC RECORDING LOG

CLIENT: Husky		PROSPECT: NPR-A		AREA: BARROW		LINE NO.: 659W			
PARTY NO.: 1182		INST. ENG.: Streff-windham		DATE: 31/11/79		NO. 3 DAY: 31 YR: 79			
INSTRUMENT (9-TRACK) <input type="checkbox"/> 1 SYSTEM <input type="checkbox"/> 2 SYSTEMS		FIELD TRACE NOS.: 1-48		NO. BYTES IN RECORD ID: 134		RECORD NUMBERS: <input type="checkbox"/> DEC. <input type="checkbox"/> OCT.		GAIN CONSTANT: 36 db	
CONFIGURATION (MAG TAPE) DATA CHANNEL NOS.: 1-48		AUXILIARY DATA: AUXILIARY CHANNEL NOS.: 3 4		NO. OF POSITIONS: 18		LATERAL SPACING: 12'		STAGGER: 6	
PARAMETER RECORD LENGTH: 6 sec.		SAMPLE RATE: <input type="checkbox"/> 1 ms. <input type="checkbox"/> 4 ms.		GAIN MODE: <input type="checkbox"/> INITIAL <input type="checkbox"/> MANUAL <input type="checkbox"/> FINAL <input type="checkbox"/> OPERATE		FILTERS: FREQ. 8		LO CUT HZ SLOPE 18	
DISPLAY MODE: <input type="checkbox"/> ACC <input type="checkbox"/> FLOAT <input type="checkbox"/> DEFLOAT <input type="checkbox"/> DIRECT		INITIAL GAIN: 18 db		TRIP SENS: 19 db		POLARITY CONVENTION: <input type="checkbox"/> NEGATIVE <input type="checkbox"/> POSITIVE		PRESSURE INCREASE ON GEOPHONE: <input type="checkbox"/> NEGATIVE <input type="checkbox"/> POSITIVE	
CFS I TYPE STACK:		GATE LENGTH:		RECORD REJECTION:		NOISE REDUCTION:		NOISE THRESHOLD:	
SOURCE TYPE: <input checked="" type="checkbox"/> DYNAMITE <input type="checkbox"/> VIBROSEIS <input type="checkbox"/> OTHER		PATTERN: Single hole - inline		NO. OF POSITIONS: 18		LATERAL SPACING: 12'		STAGGER: 6	
RECEIVER TYPE: GSC-20d		PATTERN: Inline		NO. OF ELEMENTS: 18		LATERAL SPACING: 12'		STAGGER: 6	
SPREAD NO. OF GROUPS: 48		RESISTANCE: 560 ohms		GROUP INTERVAL: 220'		SHOTPOINT INTERVAL: 880'		FOLD: 6	
OFFSET GROUP 1: 5170'		OFFSET GROUP 2: 110'		OFFSET GROUP 3: 25'		OFFSET GROUP 4: 110'		OFFSET GROUP 48: 5170'	

DIAGRAMS/MISC. INFORMATION:

SHOTPOINT	TR. 1 to 48		TR. 1 to 48		SHOT		SPREAD		REMARKS	CORR. STACK			
	REEL NO.	REC.	REEL NO.	REC.	SIZE	DEPTH	NO. OFFSET	DIR.		CDP SWITCH	LINE GROUPS		TR 1-48
21	751911B	629			20	61727	11	51	15+1	-26+4			
22		630			20	61728	11	55	16+1	-27+4			
23		631			20	61729	11	59	17+1	-28+4			
24		632			20	61730	11	27	18+1	-29+4	4	RECORDER @ 29+2	
25		633			20	61731	11	31	19+1	-30+4			
26		634			20	61732	11	35	20+1	-31+4			
27		635			20	61733	11	33,33	21+1	-32+4	5	RECORDER @ 31	
28		636			20	61734	11	37	22+1	-33+4			
29		637			20	61735	11	41	23+1	-34+4			
30		638			20	61736	11	45	24+1	-35+4			
31		639			20	61737	11	49	25+1	-36+4			
32		640			20	61738	11	53	26+1	-37+4			
33		641			20	61739	11	57	27+1	-38+4			
34		642			20	61740	11	61	28+1	-39+4			
35		643			20	61741	11	65	29+1	-40+4			
36		644			20	61742	11	69	30+1	-41+4			
37		645			20	61743	11	73	31+1	-42+4			
38		646			20	61744	11	77	32+1	-43+4			
39		647			20	61745	11	81	33+1	-44+4			
40		648			20	61746	11	13	34+1	-45+4	6	RECORDER @ 49	

LAND SEISMIC RECORDING LOG

CLIENT: <u>Husky</u>		PROSPECT: <u>NPR-A</u>		AREA: <u>BARROW</u>		LINE NO.: <u>659 W</u>			
PARTY NO.: <u>1182</u>		INST. ENG.: <u>Streff-Windham</u>		DATE: <u>MO. 3 DAY 31 YR 79</u>					
INSTRUMENT: <input checked="" type="checkbox"/> SYSTEM <input type="checkbox"/> SYSTEMS [9-TRACK] NO. BYTES IN HEADER REC.: _____ NO. BYTES IN RECORD ID: _____ NO. BYTES PER SCAN: <u>134</u>		TYPE: <input type="checkbox"/> DFS III <input type="checkbox"/> DFS IV <input type="checkbox"/> OTHER		TRACK: <input checked="" type="checkbox"/> TRACK <input type="checkbox"/> SEG. <u>8</u>		GAPPED: <input type="checkbox"/> GAPPED <input type="checkbox"/> UNGAPPED		PACKING DENSITY: (10) <input type="checkbox"/> 356 BPI (11) <input type="checkbox"/> 712 BPI	
CONFIGURATION (MAG TAPE): FIELD TRACE NOS.: <u>1-48</u> DATA CHANNEL NOS.: <u>1-48</u> (ON MAG TAPE)		AUXILIARY DATA: (1) <u>73</u> (2) <u>114</u> (3) _____ (4) _____ (5) _____ (6) _____ (7) _____		AUXILIARY CHANNEL NOS.: <u>3</u> <u>4</u>		RECORD NUMBERS: <input type="checkbox"/> DEC. <input type="checkbox"/> OCT.		GAIN CONSTANT: <u>36</u> db INPUT IMPEDANCE: <u>70,000</u> ohms	
PARAMETER: RECORD LENGTH: <u>6</u> sec. SAMPLE RATE: <input type="checkbox"/> 1 sec. <input type="checkbox"/> 4 sec.		GAIN MODE: <input checked="" type="checkbox"/> INITIAL <input type="checkbox"/> MANUAL <input type="checkbox"/> OPERATE		FILTERS: FREQ. <u>8</u> LO CUT HZ SLOPE <u>18</u> HI CUT HZ SLOPE <u>70</u>		NOTCH FILTER: <input type="checkbox"/> IN <input type="checkbox"/> OUT			
DISPLAY: MODE: <input checked="" type="checkbox"/> AGC <input type="checkbox"/> FLOAT <input type="checkbox"/> AMPLIFIER <input type="checkbox"/> DEFLOAT <input type="checkbox"/> DIRECT		INITIAL GAIN: <u>18</u> db TRIP SENS.: <u>18</u> db		POLARITY CONVENTION: <input type="checkbox"/> NEGATIVE <input type="checkbox"/> POSITIVE		PRESSURE INCREASE ON GEOPHONE: <input type="checkbox"/> NEGATIVE <input type="checkbox"/> POSITIVE		NUMBERS ON MAG. TAPE: <input type="checkbox"/> DOWNBREAK <input type="checkbox"/> UPBREAK ON DISPLAY	
CFS I: TYPE STACK: _____ GATE LENGTH: _____ RECORD REJECTION: _____		NOISE REDUCTION: _____ NOISE THRESHOLD: _____ CORR. SCALING: _____		P.C.U. NORM / ALT SW.					
SOURCE: TYPE: <input checked="" type="checkbox"/> DYNAMITE <input type="checkbox"/> VIBROSEIS <input type="checkbox"/> OTHER		PATTERN: <u>Single hole - Inline</u> NO. OF POSITIONS: _____ INLINE SPACING: _____		LATERAL SPACING: _____ STAGGER: _____ LENGTH: _____ WIDTH: _____		LATERAL OFFSET: _____			
RECEIVER: TYPE: <u>GSC-20d</u> CONNECTION: <u>Series-Parallel</u>		PATTERN: <u>IN line</u> RESISTANCE: <u>560</u> ohms		NO. OF ELEMENTS: <u>18</u> STAGGER: _____		INLINE SPACING: <u>12'</u> LENGTH: _____		LATERAL SPACING: _____ WIDTH: _____ LATERAL OFFSET: _____	
SPREAD: NO. OF GROUPS: <u>48</u> OFFSET GROUP 1: <u>5770'</u>		GROUP INTERVAL: <u>220'</u> OFFSET GROUP 24: <u>110'</u>		SHOTPOINT INTERVAL: <u>880'</u> OFFSET GROUP 25: <u>110'</u>		FOLD: <u>6</u> OFFSET GROUP 41: <u>5770'</u>		DIRECTION OF PROGRESSION: <u>E → W</u> LEADING GROUP: <u>48</u>	

DIAGRAMS/MISC. INFORMATION:

SHOTPOINT	IR		TR		SHOT				SPREAD				REMARKS	CORR. STACK				
	REEL NO.	REC.	REEL NO.	REC.	SIZE	DEPTH	NO. OFFSET	DIR.	CDP SWITCH	LINE GROUPS				SET	TR 1-28	TR 29-48	TR 49-72	TR 73-96
649	267107	18			20	61747			17	35+1	-46+4			6				
650					20	61748			21	36+1	-47+4							
651					20	61749			25	37+1	-48+4							
652					20	61750			29	38+1	-49+4							
653					20	61751			33	39+1	-50+4							
654					20	61752			37	40+1	-51+4							
655					20	61753			41	41+1	-52+4							
656					20	61754			45	42+1	-53+4							
657					20	61755	250	Right	49	43+1	-54+4							
658					20	61756	440	West	49	44+1	-55+4							
659					20	61757	490	West	57	45+1	-56+4							
660					20	61758			61	46+1	-57+4							
661					20	61759			65	47+1	-58+4							
662					20	61760			69	48+1	-59+4							
663					20	61761			73	49+1	-60+4							

RECOVER SP 50 INLINE OFFSET
 REC# 654-660 N.G.

Recording Hrs - 14.0

LAND SEISMIC RECORDING LOG

CLIENT: Husky		PROSPECT: NPR-A		AREA: BARROW		LINE NO: 659-W	
PARTY NO: 1182		INST. ENG: Steff-Windham		DATE: 4 DAY 1 79		MO: 4 DAY 1 79	
INSTRUMENT (9-TRACK): <input type="checkbox"/> 1 SYSTEM <input type="checkbox"/> 2 SYSTEMS		NO. BYTES IN HEADER REC: 1-24 & 25-48 <input type="checkbox"/> 1-48 & 49-96		TYPE: <input type="checkbox"/> DFS III <input type="checkbox"/> DFS IX		FORMAT: 8 <input type="checkbox"/> TRACK <input type="checkbox"/> SEG	
NO. BYTES IN RECORD ID: 134		RECORD NUMBERS: 26		GAIN CONSTANT: 36 db		PACKING DENSITY: (10) <input type="checkbox"/> 356 BPI (11) <input type="checkbox"/> 712 BPI	
CONFIGURATION (MAG TAPE): FIELD TRACE NOS.: 1-48 DATA CHANNEL NOS.: 1-48		AUXILIARY DATA: 18 (1) 118 (2) 114 (3) (4) (5) (6) (7)		AUXILIARY CHANNEL NOS.: 3 4		INPUT IMPEDANCE: 20,000 ohms	
PARAMETER: RECORD LENGTH: 6 sec.		SAMPLE RATE: <input type="checkbox"/> 2000 <input type="checkbox"/> 4000		GAIN MODE: <input type="checkbox"/> INITIAL <input type="checkbox"/> FINAL		FILTERS: FREQ: 8 LO CUT HZ SLOPE: 18 HI CUT HZ SLOPE: 70 NOTCH FILTER: <input type="checkbox"/> IN <input type="checkbox"/> OUT	
DISPLAY: MODE: <input type="checkbox"/> AGC <input type="checkbox"/> FLOAT <input type="checkbox"/> DEFLOAT <input type="checkbox"/> AMPLIFIER <input type="checkbox"/> DIRECT		INITIAL GAIN: 18 db		STRIP SPEED: 18 db		POLARITY CONVENTION: <input type="checkbox"/> NEGATIVE <input type="checkbox"/> POSITIVE	
CFS I: TYPE STACK:		GATE LENGTH:		RECORD REJECTION:		NOISE REDUCTION: NOISE THRESHOLD: CORE SCALING: R.C.U. NORM/ALT SW.	
SOURCE: TYPE: <input type="checkbox"/> DYNAMITE <input type="checkbox"/> VIBROSEIS <input type="checkbox"/> OTHER		PATTERN: Single hole - inline		NO. OF POSITIONS: INLINE SPACING: SWEEP START: SWEEP END:		LATERAL SPACING: STAGGER: LENGTH: WIDTH: LATERAL OFFSET:	
RECEIVER: TYPE: GSC-20d		PATTERN: IN line		NO. OF ELEMENTS: 18		INLINE SPACING: 12'	
CONNECTION: Series-Parallel		RESISTANCE: 560 ohms		STAGGER: LENGTH: WIDTH: LATERAL OFFSET:		LATERAL SPACING: WIDTH: LATERAL OFFSET:	
SPREAD: NO. OF GROUPS: 48		GROUP INTERVAL: 220'		SHOTPOINT INTERVAL: 880'		FOLD: 6	
OFFSET GROUP 1: 5170'		OFFSET GROUP 24: 110'		OFFSET GROUP 25: 110'		OFFSET GROUP 48: 5170'	

DIAGRAMS/MISC. INFORMATION:

SHOTPOINT	TR 1 to 48		TR 49 to 96		SHOT				SPREAD				REMARKS	CORR. STAGE					
	REEL NO.	REC.	REEL NO.	REC.	SIZE	DEPTH	NO.	OFFSET	DIR.	CDP SWITCH	LINE GROUPS			SEN	TH	REC	TH	REC	
150	7511A11B	280			20	167	11			29	51+1 - 61+4								
151		681			20	167	12			33	51+1 - 62+4								
152		682			20	167	13			37	52+1 - 63+4								
153		683			20	167	14			41	53+1 - 64+4								
160		684			20	167	15			45	54+1 - 65+4								
161		685			20	167	16			49	55+1 - 66+4								
162		686			20	167	17			53	56+1 - 67+4								
163		687			20	167	18			57	57+1 - 68+4								
164		688			20	167	19			61	58+1 - 69+4								
165		689			20	167	20			29	59+1 - 70+4								
166		690			20	167	21			33	60+1 - 71+4								
167		691			20	167	22			37	61+1 - 72+4								
168		692			20	167	23			41	62+1 - 73+4								
169		693			20	167	24			45	63+1 - 74+4								
170		694			20	167	25			49	64+1 - 75+4								
171		695			20	167	26			53	65+1 - 76+4								
172		696			20	167	27			57	66+1 - 77+4								
173		697			20	167	28			61	67+1 - 78+4								
174		698			20	167	29			65	68+1 - 79+4								
175		699			20	167	30			69	69+1 - 80+4								



LAND SEISMIC RECORDING LOG

CLIENT: Husky		PROSPECT: NPR-A		AREA: BARROW		LINE NO.: 659-w			
PARTY NO.: 1182		INST. ENG.: Streff-Windham		DATE: MO 4 DAY 1 YR 79					
INSTRUMENT (9-TRACK) <input type="checkbox"/> 1 SYSTEM <input checked="" type="checkbox"/> 2 SYSTEMS		NO. BYTES IN READER REC.: 134		RECORD NUMBERS: DEC. OCT.		GAIN CONSTANT: 36 db		INPUT IMPEDANCE: 20,000 ohms	
CONFIGURATION (MAG TAPE) FIELD TRACE NOS.: 1-48		NO. BYTES IN RECORD ID:		AUXILIARY DATA: 18 4H		AUXILIARY CHANNEL NOS.: 3 4			
PARAMETER RECORD LENGTH: 6 sec		SAMPLE RATE: <input type="checkbox"/> 1 ms. <input checked="" type="checkbox"/> 4 ms.		GAIN MODE: <input type="checkbox"/> INITIAL <input type="checkbox"/> MANUAL <input type="checkbox"/> OPERATE		FILTERS: FREQ. 0 LO CUT HZ SLOPE 18		HI CUT HZ SLOPE 70	
DISPLAY MODE: <input checked="" type="checkbox"/> FLOAT <input type="checkbox"/> AMPLIFIER <input type="checkbox"/> DIRECT		INITIAL GAIN: 18 db		TRF SENS: 18 db		POLARITY CONVENTION: <input type="checkbox"/> NEGATIVE <input type="checkbox"/> POSITIVE		NUMBERS ON MAG. TAPE <input type="checkbox"/> DOWNBREAK <input type="checkbox"/> UPBREAK	
CFS I TYPE STACK:		GATE LENGTH:		RECORD REJECTION:		NOISE THRESHOLD:		CORR. SCALING:	
SOURCE TYPE: <input checked="" type="checkbox"/> DYNAMITE <input type="checkbox"/> VIBROSEIS <input type="checkbox"/> OTHER		PATTERN: Single hole - Inline		NO. OF POSITIONS: 18		LATERAL SPACING: 12'		LATERAL OFFSET:	
RECEIVER TYPE: GSC-20d		CONNECTION: Series-Parallel		RESISTANCE: 560 ohms		STAGGER: 12'		LATERAL OFFSET:	
SPREAD NO. OF GROUPS: 48		GROUP INTERVAL: 720'		SHOTPOINT INTERVAL: 880'		FOLD: 6		DIRECTION OF PROGRESSION: West	
OFFSET GROUP 1: 5170'		OFFSET GROUP 2: 110'		OFFSET GROUP 3: 110'		OFFSET GROUP 4: 5170'		LEADING GROUP: 48	

DIAGRAMS/MISC. INFORMATION:

SHOTPOINT	TR 1 to		TR 2 to		SHOT			SPREAD			REMARKS	CORE STACK			
	REEL NO.	REC.	REEL NO.	REC.	SIZE	DEPTH	NO.	OFFSET	DIR.	CDP SWITCH		LINE GROUPS	TR 11	TR 12	TR 13
176	7511918	702			20	167	21	11		73	70+1 - 81+4				
177		703			20	167	22	11		29	71+1 - 82+4	3			Recorder @ SP-82
178		704			20	167	23	11		33	72+1 - 83+4				
179		705			20	167	24	11		37	73+1 - 84+4				
180		706			20	167	25	11		41	74+1 - 85+4				
181		707			20	167	26	11		45	75+1 - 86+4				
182		708			20	167	27	11		49	76+1 - 87+4				
183		709			20	167	28	6510 N		53	77+1 - 88+4				
184		710			20	167	29	11		57	78+1 - 89+4				
185		711			20	167	30	11		61	79+1 - 90+4				
186		712			20	167	31	11		65	80+1 - 91+4				
187		713			20	167	32	11		69	81+1 - 92+4				
188		714			20	167	33	11		73	82+1 - 93+4				
189		715			20	167	34	11		77	83+1 - 94+4				
190		716			20	167	35	11		81	84+1 - 95+4				
191		717			20	167	36	220 SW		31	85+1 - 96+4	4			Recorder @ SP 95+2/95+3
192		718			20	167	37	11		35	86+1 - 97+4				
193		719			20	167	38	11		39	87+1 - 98+4				
194		720			20	167	39	11		43	88+1 - 99+4				
195	7511919	717			20	167	40	11		47	89+1 - 100+4				TAPE CHANGE

LAND SEISMIC RECORDING LOG

	CLIENT: Husky	PROSPECT: NPR-A	AREA: Barrow	LINE NO.: 659W						
	PARTY NO.: 1182	INST. ENG.: Streff-Windham		DATE: 4 DAY 1 YR 79						
INSTRUMENT (9-TRACK)	<input type="checkbox"/> 1 SYSTEM <input type="checkbox"/> 2 SYSTEMS		<input type="checkbox"/> 1-24 & 25-48 <input type="checkbox"/> 48 & 49-96	<input type="checkbox"/> ODDS <input type="checkbox"/> EVENS	<input type="checkbox"/> TYPE: <input type="checkbox"/> DFS III <input type="checkbox"/> DFS II <input type="checkbox"/> DFS I <input type="checkbox"/> OTHER	<input type="checkbox"/> 9 TRACK <input type="checkbox"/> 21 TRACK	<input type="checkbox"/> FORMAT: SLG <input type="checkbox"/> GAPPED <input type="checkbox"/> UNGAPPED	<input type="checkbox"/> PACKING DENSITY: (1) (2) (3) (4) (5) (6) (7)	<input type="checkbox"/> 356 BPI <input type="checkbox"/> 600 BPI	<input type="checkbox"/> (M) <input type="checkbox"/> 712 BPI <input type="checkbox"/> 1000 BPI
	NO. BYTES IN HEADER REC:		NO. BYTES IN RECORD ID:		NO. BYTES PER SCAN:		RECORD NUMBERS:	GAIN CONSTANT: (1) (2) (3) (4) (5) (6) (7)	INPUT IMPEDANCE: ohms	
CONFIGURATION (MAG TAPE)	FIELD TRACE NOS.:					AUXILIARY DATA:				
	DATA CHANNEL NOS.:					AUXILIARY CHANNEL NOS.:				
PARAMETER	RECORD LENGTH:	SAMPLE RATE: <input type="checkbox"/> 1 ms. <input type="checkbox"/> 4 ms. <input type="checkbox"/> 2 ms. <input type="checkbox"/> 8 ms.	GAIN MODE: <input type="checkbox"/> INITIAL <input type="checkbox"/> FINAL <input type="checkbox"/> MANUAL <input type="checkbox"/> OPERATE	FILTERS: FREQ. LO CUT HZ SLOPE HI CUT HZ SLOPE	NOTCH FILTER: <input type="checkbox"/> IN <input type="checkbox"/> OUT	POLARITY CONVENTION: <input type="checkbox"/> NEGATIVE <input type="checkbox"/> POSITIVE		PRESSURE INCREASE ON GEOPHONE: <input type="checkbox"/> NEGATIVE <input type="checkbox"/> POSITIVE		NUMBERS ON MAG. TAPE: <input type="checkbox"/> DOWNBREAK <input type="checkbox"/> UPBREAK
DISPLAY	MODE: <input type="checkbox"/> AGC <input type="checkbox"/> FLOAT <input type="checkbox"/> DEFLOAT <input type="checkbox"/> DIRECT	AMPLIFIER: <input type="checkbox"/> DIRECT	TRIP SENS: db	CORR. SCALING: R.C.U. NORM/ALT SW.		NOISE REDUCTION: NOISE THRESHOLD:		CORR. SCALING:		R.C.U. NORM/ALT SW.
CFS I	TYPE STACK:	GATE LENGTH:	RECORD REJECTION:	STAGGER:		LENGTH:	WIDTH:	LATERAL OFFSET:		
SOURCE	TYPE: <input type="checkbox"/> DYNAMITE <input type="checkbox"/> VIBROSEIS <input type="checkbox"/> OTHER	PATTERN:	NO. OF POSITIONS:	INLINE SPACING:	LATERAL SPACING:	STAGGER:	LENGTH:	WIDTH:	LATERAL OFFSET:	
	CHG/ HOLE:	HOLE DEPTH:	SWEPT POSITION:	SWEPT START:	SWEPT END:	SWEPT LENGTH:	SWEPT TAPER:	PHASE COMP.		
RECEIVER	TYPE:	PATTERN:	NO. OF ELEMENTS:	INLINE SPACING:	LATERAL SPACING:	STAGGER:	LENGTH:	WIDTH:	LATERAL OFFSET:	
	CONNECTION:	RESISTANCE:	ohms	STAGGER:	LENGTH:	WIDTH:	LATERAL OFFSET:			
SPREAD	NO. OF GROUPS: 48	GROUP INTERVAL: 220	SHOTPOINT INTERVAL: 780	FOLD: 6	DIRECTION OF PROGRESSION: West	OFFSET GROUP 1: 5170	OFFSET GROUP 48/96: 5170	LEADING GROUP: 48		

DIAGRAMS/MISC. INFORMATION:

5170 - Start of Tape # 751919



SHOTPOINT	TR 10		TR 20		SHOT		SPREAD		REMARKS	CORR. STACK			
	REEL NO.	REC.	REEL NO.	REC.	SIZE	DEPTH	NO.	OFFSET		DIR.	CDP SWITCH	LINE GROUPS	SP
716	715	119119	7120	119119	20	167	41	51		90+1 - 101+4	4		
717		720			20	167	42	55		91+1 - 102+4			
718		721			20	167	43	59		92+1 - 103+4			
719		722			20	167	44	63		93+1 - 104+4			
720		723			20	167	45	67		94+1 - 105+4			
721		724			20	167	46	71		95+1 - 106+4			
722		725			20	167	47	75		96+1 - 107+4			
723		726			20	167	48	79		97+1 - 108+4			
724		727			20	167	49	53		98+1 - 109+4			
725		728			20	167	50	57		99+1 - 110+4			
726		729			20	167	51	61		100+1 - 111+4			
727		730			20	167	52	65		101+1 - 112+4			
728		731			20	167	53	69		102+1 - 113+4			
729		732			20	167	54	55		103+1 - 114+4	6		
730		733			20	167	55	59	W	104+1 - 115+4			
731		734			20	167	56	63		105+1 - 116+4			
732		735			20	167	57	67		106+1 - 117+4			
733		736			20	167	58	71		107+1 - 118+4			
734		737			20	167	59	75		108+1 - 119+4			
735		738			20	167	60	79		109+1 - 120+4			

728 - N.G. Recorder Q 51-103

700' South

Recording Hrs - 14.0

LAND SEISMIC RECORDING LOG

		CLIENT: Husky	PROSPECT: NPA-1	AREA: Barrow	LINE NO: 659 W				
PARTY NO: 118		INST. ENG: Steff Windham		DATE: 4 DAY 2 YR 79					
INSTRUMENT (9-TRACK)	<input type="checkbox"/> 1 SYSTEM <input type="checkbox"/> 2 SYSTEMS	<input type="checkbox"/> 24 & 28-48 <input type="checkbox"/> 48 & 49-96	ODDS <input type="checkbox"/> EVENS	TYPE: <input type="checkbox"/> DFS I <input type="checkbox"/> DFS II <input type="checkbox"/> DFS III <input type="checkbox"/> OTHER	<input type="checkbox"/> TRACK <input type="checkbox"/> 2 TRACK	FOPMAT: A SEG:	<input type="checkbox"/> GAPPED <input type="checkbox"/> UNGAPPED	PACKING DENSITY: (10) <input type="checkbox"/> 356 BPI <input type="checkbox"/> 800 BPI (11) <input type="checkbox"/> 712 BPI <input type="checkbox"/> 1400 BPI	
	NO. BYTES IN HEADER REC:	NO. BYTES IN RECORD ID:	NO. BYTES PER SCAN: 134	RECORD NUMBERS: 36	GAIN CONSTANT: 36 db	INPUT IMPEDANCE: 2015 ohms			
CONFIGURATION (MAG TAPE)	FIELD TRACE NOS.: 1-48			AUXILIARY DATA:			AUXILIARY CHANNEL NOS.:		
PARAMETER	RECORD LENGTH: 6 sec	SAMPLE RATE: <input type="checkbox"/> 1 ml. <input type="checkbox"/> 4 ms. <input type="checkbox"/> 2 sec. <input type="checkbox"/> 10 sec.	GAIN MODE: <input type="checkbox"/> INITIAL <input type="checkbox"/> MANUAL <input type="checkbox"/> OPERATE	FILTERS: 8 LO CUT 18 HI CUT 70	NOTCH FILTER: <input type="checkbox"/> IN <input type="checkbox"/> OUT				
DISPLAY	<input type="checkbox"/> AGC <input type="checkbox"/> DEFOAT <input type="checkbox"/> DIRECT	AMPLIFIER: <input type="checkbox"/> INITIAL <input type="checkbox"/> FINAL	TRIP SENS: 0 db	POLARITY CONVENTION: <input type="checkbox"/> POSITIVE <input type="checkbox"/> NEGATIVE	PRESSURE INCREASE ON GEOPHONE: <input type="checkbox"/> POSITIVE <input type="checkbox"/> NEGATIVE			<input type="checkbox"/> NUMBERS ON MAG TAPE <input type="checkbox"/> DOWNBREAK ON DISPLAY <input type="checkbox"/> UPBREAK ON DISPLAY	
CFS I	TYPE STACK:	GATE LENGTH:	RECORD REJECTION:	NOISE REDUCTION:	NOISE THRESHOLD:	CORR. SCALING:	R.C.U. NORM/ALT SW.		
SOURCE	<input type="checkbox"/> DYNAMITE <input type="checkbox"/> VIBROSEIS <input type="checkbox"/> OTHER	PATTERN: inline-hole	NO. OF POSITIONS:	INLINE SPACING:	LATERAL SPACING:	STAGGER:	LENGTH:	WIDTH:	LATERAL OFFSET:
RECEIVER	TYPE: 20-0	PATTERN: inline	NO. OF ELEMENTS: 18	INLINE SPACING: 12'	LATERAL SPACING:	STAGGER:	LENGTH:	WIDTH:	LATERAL OFFSET:
SPREAD	CONNECTION: Series-parallel	RESISTANCE: 500 ohms	SWEPT START:	SWEPT END:	SWEPT LENGTH:	SWEPT TAPER:	PHASE COMP.	DIRECTION OF PROGRESSION: West + (SE) NW	
NO. OF GROUPS: 48		GROUP INTERVAL: 220	SHOTPOINT INTERVAL: 880	FOLD: 6	OFFSET GROUP #8/96: 5170				
OFFSET GROUP 1: 5170		OFFSET GROUP 24: 110	OFFSET GROUP 25: 110	OFFSET GROUP 48/96: 5170		LEADING GROUP: 48			

DIAGRAMS/MISC. INFORMATION:
 TR#1 $\xrightarrow{110+1}$ $\xrightarrow{115+500}$ $\xrightarrow{116+1}$ $\xrightarrow{121+4}$ TR#48
 X @ X @ X @ X

SHOTPOINT	TR. to		TR. to		SHOT			DIR.	CDP SWITCH	SPREAD	REMARKS:	CORR. STAGE		
	REEL NO.	REC.	REEL NO.	REC.	SIZE	DEPTH	NO. OFFSET					ST1	ST2	ST3
11116	75119	17514			210	167	21		29	110+1 - 121+4	1 Recorder @ SP121			
11117		17515			210	167	12		33	111+1 - 122+4				
11118		17516			210	167	13	E	37	112+1 - 123+4				
11119		17517			210	167	14	W	41	113+1 - 124+4				
11120		17518			210	167	15		45	114+1 - 125+4				
11121		17519			210	167	16		49	115+1 - 126+4				
11122		17600			210	167	17		53	116+1 - 127+4				
11123		17601			210	167	18		57	117+1 - 128+4				
11124		17602			210	167	19		61	118+1 - 129+4				
11125		17603			210	167	20		65	119+1 - 130+4				
11126		17604			210	167	21		69	120+1 - 131+4				
11127		17605			210	167	22		73	121+1 - 132+4				
11128		17606			210	167	23		79	122+1 - 133+4	2 Recorder @ SP-133			
11129		17607			210	167	24		33	123+1 - 134+4				
11130		17608			210	167	25		37	124+1 - 135+4				
11131		17609			210	167	26		41	125+1 - 136+4				
11132		17710			210	167	27		45	126+1 - 137+4				
11133		17711			210	167	28		49	127+1 - 138+4				
11134		17712			210	167	29		53	128+1 - 139+4				
11135		17713			210	167	30		57	129+1 - 140+4				

753 - first time break

LAND SEISMIC RECORDING LOG

CLIENT: Husky PARTY NO.: 1182		INST. ENG.: Streiff-Windham		PROSPECT: NPA-A		AREA: Barrow		LINE NO.: 659W	
INSTRUMENT: <input type="checkbox"/> 1 SYSTEM <input type="checkbox"/> 2 SYSTEMS NO. BYTES IN HEADER REC.: _____ NO. BYTES IN RECORD ID.: _____		TYPE: <input type="checkbox"/> DFS III <input type="checkbox"/> DFS IV <input type="checkbox"/> OTHER		RECORD NUMBERS: _____		FORMAT: B		PACKING DENSITY: _____	
CONFIGURATION (MAG TAPE):		FIELD TRACE NOS.: 1-48		NO. BYTES PER SCAN: 134		GAIN CONSTANT: 36		INPUT IMPEDANCE: 20K	
PARAMETER:		DATA CHANNEL NOS.: 1-48		NO. OF POSITIONS: _____		AUXILIARY DATA:		COR. SCALING: _____	
DISPLAY:		RECORD LENGTH: 6		SAMPLE RATE: <input type="checkbox"/> 1 ms <input type="checkbox"/> 4 ms		FILTERS:		POLARITY CONVENTION: <input type="checkbox"/> POSITIVE <input type="checkbox"/> NEGATIVE	
CFS 1:		MODE: <input type="checkbox"/> FLOAT <input type="checkbox"/> AMPLIFIER <input type="checkbox"/> DEFLOAT <input type="checkbox"/> DIRECT		INITIAL GAIN: 0		FREQ. 8		LO CUT HZ SLOPE 18	
SOURCE:		TYPE: <input type="checkbox"/> DYNAMITE <input type="checkbox"/> VIBROSEIS <input type="checkbox"/> OTHER		PATTERN: inline-hole		NOISE REDUCTION: _____		HI CUT HZ SLOPE 70	
RECEIVER:		TYPE: 20-D		ENG/HOLE: 20		HOLE DEPTH: 75		IN-OUT: <input type="checkbox"/> IN <input type="checkbox"/> OUT	
SPREAD:		CONNECTION: Series-Parallel		RESISTANCE: 560		NO. OF ELEMENTS: 18		STAGGER: _____	
DIAGRAMS/MISC. INFORMATION:		NO. OF GROUPS: 48		GROUP INTERVAL: 220		SWEEP START: _____		SWEEP END: _____	
OFFSET GROUP 1: 5170		OFFSET GROUP 2: 110		OFFSET GROUP 3: 110		SHOTPOINT INTERVAL: 870		FOLD: 6	
LATERAL SPACING: _____		LENGTH: _____		WIDTH: _____		LATERAL OFFSET: _____		DIRECTION OF PROGRESSION: West	
STAGGER: _____		LENGTH: 12		WIDTH: _____		LATERAL OFFSET: _____		LEADING GROUP: 48	
OFFSET GROUP 48/96: 5170		LATERAL SPACING: _____		LENGTH: _____		WIDTH: _____		LATERAL OFFSET: _____	

SHOTPOINT	TR. 19		TR. 20		SHOT		DIR.	CDP SWITCH	SPREAD		REMARKS	CORR. STAGE			
	REEL NO.	REC.	REEL NO.	REC.	SIZE	DEPTH			NO.	OFFSET		LINE GROUPS	SET UP	TR. 19	TR. 20
11316	782	1917	1774	22	20	167	21	11	61	130+1 - 141+4	2				
11317			1775		20	167	22	11	29	131+1 - 142+4	3				
11318			1776		20	167	23	11	33	132+1 - 143+4					
11319			1777		20	167	24	11	37	133+1 - 144+4					
11320			1778		20	167	25	11	41	134+1 - 145+4					
11411			1780		20	167	26	11	45	135+1 - 146+4					
11412			1781		20	167	27	11	49	136+1 - 147+4					
11413			1782		20	167	28	11	53	137+1 - 148+4					
11414			1783		20	167	29	11	57	138+1 - 149+4					
11415			1784		20	167	30	1000 5	61	139+1 - 150+4					
11416			1785		20	167	31	11	65	140+1 - 151+4					
11417			1786		20	167	32	11	69	141+1 - T4					
11418			1787		20	167	33	11	73	142+1 - T. 8					
11419			1788		20	167	34	11	77	143+1 - T. 12					
11511			1789		20	167	35	11	81	144+1 - T. 16					
11512			1790		20	167	36	11	85	145+1 - T. 20					
11513			1791		20	167	37	11	89	146+1 - T. 24					

E. O. L.