

Recording Hrs - 14.5

LAND SEISMIC RECORDING LOG

CLIENT: Ausky		PROSPECT: NPR-A		AREA: Barrow		LINE NO: 663	
PARTY NO: 1182		INST. ENG: Streiff-Windham		DATE: MO 3 DAY 13 YR 79			
INSTRUMENT: 2 SYSTEMS		ODDS: 24 & 25 - 48		TYPE: DFS III		FORMAT: B	
NO. BYTES IN HEADER REC: 1-48 & 49-96		NO. BYTES IN RECORD ID: 1-48 & 49-96		NO. BYTES PER SCAN: 1-48 & 49-96		RECORD NUMBERS: DEC OCT	
CONFIGURATION (9-TRACK)		FIELD TRACE NOS.: 1-48		DATA CHANNEL NOS.: 1-48		AUXILIARY DATA:	
PARAMETER		RECORD LENGTH: 6		SAMPLE RATE: 1 ms		GAIN MODE: INITIAL	
DISPLAY		MODE: AGC		INITIAL GAIN: 18		TRIP SENS: 0	
CFS 1		TYPE STACK:		GATE LENGTH:		RECORD REJECTION:	
SOURCE		TYPE: DYNAMIC		PATTERN: Inline-hole		NO. OF POSITIONS: 18	
RECEIVER		TYPE: 20-0		PATTERN: Inline		NO. OF ELEMENTS: 18	
SPREAD		NO. OF GROUPS: 48		GROUP INTERVAL: 330		SHOTPOINT INTERVAL: 1320	

DIAGRAMS/MISC. INFORMATION:
 2+1 X 744 578 8+1 13+4 X
 TR#1 X @ X TR#48
 146-156 Acsts
 157 test time 6/10/79

SHOTPOINT	TR. 10		TR. 11		SHOT		SPREAD		REMARKS	CORR. STACK						
	REEL NO.	REC.	REEL NO.	REC.	SIZE	DEPTH	NO.	OFFSET		DIR.	CDP SWITCH	LINE GROUPS	TR 10 REC.	TR 11 REC.	TR 12 REC.	TR 13 REC.
8	750	1198			50	70	1	11		29	2+1 - 13+4					Recorder @ SP 13
9		1199			50	70	2	11		33	3+1 - 14+4					
10		1160			50	70	3	11		37	4+1 - 15+4					
11		1161			50	70	4	11		41	5+1 - 16+4					
12		1162			50	70	5	11		45	6+1 - 17+4					
13		1163			50	70	6	11		49	7+1 - 18+4					
14		1164			50	70	7	11		53	8+1 - 19+4					
15		1165			50	70	8	11		57	9+1 - 20+4					
16		1166			50	70	9	11		61	10+1 - 21+4					
17		1167			50	70	10	11		65	11+1 - 22+4					
18		1168			50	70	11	11		69	12+1 - 23+4					
19		1169			50	70	12	11		73	13+1 - 24+4					
* 20		1170			50	70	13	11		81	15+1 - 26+4					Stacked on SP-19 offset 850' W
* 21		1171			50	70	14	11		77	14+1 - 25+4					Stacked on SP-22
22		1172			50	70	15	11		85	16+1 - 27+4					SP 171 noise
23		1173			50	70	16	11		25	17+1 - 28+4					Recorder @ SP 29
24		1174			50	70	17	11		27	18+1 - 29+4					
25		1175			50	70	18	11		33	19+1 - 30+4					
26		1176			50	70	19	11		37	20+1 - 31+4					
27		1177			50	70	20	11		41	21+1 - 32+4					

EXTRA HOLE
 * SP 22 Aic # 172 * 50 70 69 12+1 - 23+4

LAND SEISMIC RECORDING LOG

		CLIENT: Husky	PROSPECT: NPR-A	AREA: Baton	LINE NO. 663		
PARTY NO. 1182		INST. ENG. Streff Windham		DATE: 3 DAY 13 YEAR 79			
INSTRUMENT (9-TRACK)	<input type="checkbox"/> 1 SYSTEM <input checked="" type="checkbox"/> 2 SYSTEMS NO. BYTES IN HEADER REC:	<input type="checkbox"/> 1-24 & 25-48 <input type="checkbox"/> 1-48 & 49-96 @ ODDS EVENS	TYPE: <input type="checkbox"/> DFS III <input type="checkbox"/> DFS IV <input type="checkbox"/> OTHER	<input type="checkbox"/> 2 TRACK <input checked="" type="checkbox"/> 21 TRACK	FOP MAT: SEG B <input type="checkbox"/> GAPPED <input type="checkbox"/> UNGAPPED	PACKING DENSITY: (1) <input type="checkbox"/> 356 BPI <input type="checkbox"/> 400 BPI	(M) <input type="checkbox"/> 712 BPI <input checked="" type="checkbox"/> 800 BPI
	NO. BYTES IN RECORD ID: _____		NO. BYTES PER SCAN: 134		RECORD NUMBERS: <input checked="" type="checkbox"/> DEC <input type="checkbox"/> OCT	GAIN CONSTANT: _____ db	INPUT IMPEDANCE: 20K ohms (1) (2) (3) (4) (5) (6) (7)
CONFIGURATION (MAG TAPE)	FIELD TRACE NOS.: 1-18		AUXILIARY DATA:		AUXILIARY CHANNEL NOS.: _____		
PARAMETER	RECORD LENGTH: 6 sec.	SAMPLE RATE: <input type="checkbox"/> 1 sec. <input type="checkbox"/> 4 sec.	GAIN MODE: <input type="checkbox"/> INITIAL <input type="checkbox"/> MANUAL	FILTERS: FREQ. 8	LO CUT HZ SLOPE 16	HI CUT HZ SLOPE 20	NOTCH FILTER: <input type="checkbox"/> IN <input type="checkbox"/> OUT
DISPLAY	<input type="checkbox"/> MODE <input checked="" type="checkbox"/> AGC <input type="checkbox"/> DEFLOAT <input type="checkbox"/> DIRECT	INITIAL GAIN: 18 db	TRIP SENS: 0 db	POLARITY CONVENTION: <input type="checkbox"/> PRESSURE INCREASE ON GEOPHONE	<input type="checkbox"/> NEGATIVE NUMBERS ON MAG. TAPE <input type="checkbox"/> POSITIVE ON MAG. TAPE	<input type="checkbox"/> DOWNBREAK <input type="checkbox"/> UPBREAK	ON DISPLAY
CFS I	TYPE STACK:	GATE LENGTH:	RECORD REJECTION:	NOISE REDUCTION:	NOISE THRESHOLD:	CORR. SCALING:	R.C.U. NORM./ALT SW.
SOURCE	TYPE: <input checked="" type="checkbox"/> DYNAMITE <input type="checkbox"/> VIBROSEIS <input type="checkbox"/> OTHER	PATTERN: Shot-Inline	NO. OF POSITIONS:	INLINE SPACING:	LATERAL SPACING:	STAGGER:	LENGTH: WIDTH: LATERAL OFFSET:
RECEIVER	TYPE: 20-9 CONNECTION: Series-Parallel	PATTERN: inline	RESISTANCE: 560 ohms	NO. OF ELEMENTS: 18	INLINE SPACING: 18	STAGGER:	LENGTH: WIDTH: LATERAL OFFSET:
SPREAD	NO. OF GROUPS: 48	GROUP INTERVAL: 730	SHOTPOINT INTERVAL: 1300	FOLO: 6	DIRECTION OF PROGRESSION: East	LEADING GROUP: 48	
DIAGRAMS/MISC. INFORMATION:							

SHOTPOINT	TR. 10		TR. 19		SHOT				SPREAD				REMARKS	CORR. STACK			
	REEL NO.	REC.	REEL NO.	REC.	SIZE	DEPTH	NO.	OFFSET	DIR.	CDP SWITCH	LINE GROUPS			TR. 10	REC.	TR. 19	REC.
20	1851	1806	1808		150	70	21			45	22+1	33+4	2				
21			1808		150	70	22			49	23+1	34+4					
22			1808		150	70	23			53	24+1	35+4					
23			1808		150	70	24			33	25+1	36+4	3	Recorder @ SP 35			
24			1809		150	70	25			37	26+1	37+4					
25			1809		150	70	26			41	27+1	38+4					
26			1806		150	70	27			45	28+1	39+4					
27			1807		150	70	28			49	29+1	40+4					
28			1808		150	70	29			53	30+1	41+4					
29			1809		150	70	30			57	31+1	42+4		42+3 dead			
30			1809		150	70	31			61	32+1	43+4		43+3 dead			
31			1811		150	70	32			33	33+1	44+4	4	Recorder @ SP-43			
32			1812		150	70	33			37	34+1	45+4					
33			1813		150	70	34			41	35+1	46+4					
34			1814		150	70	35			45	36+1	47+4					
35			1805		150	70	36			49	37+1	48+4					
36			1806		150	70	37			53	38+1	49+4					
37			1807		150	70	38			57	39+1	50+4					
38			1808		150	70	39			61	40+1	51+4					
39			1809		150	70	40			65	41+1	52+4					

LAND SEISMIC RECORDING LOG

		CLIENT: Husky	PROSPECT: NPA-A	AREA: Barrow	LINE NO: 663		
PARTY NO: 1182		INST. ENG. Steff-Windham		DATE: MO 3 DAY 13 YR 79			
INSTRUMENT (9-TRACK) <input type="checkbox"/> 1 SYSTEM <input type="checkbox"/> 2 SYSTEMS		<input type="checkbox"/> 1-24 & 25-48 ODDS <input type="checkbox"/> 1-48 & 49-96 EVENS		TYPE: <input type="checkbox"/> DFS III <input type="checkbox"/> DFS II <input type="checkbox"/> DFS I <input type="checkbox"/> OTHER		<input type="checkbox"/> 9 TRACK <input type="checkbox"/> 2 TRACK	
NO. BYTES IN HEADER REC:		NO. BYTES IN RECORD ID:		NO. BYTES PER SCAN:		RECORD NUMBERS:	
CONFIGURATION (MAG TAPE)		FIELD TRACE NOS.:		DATA CHANNEL NOS.:		AUXILIARY DATA:	
PARAMETER		RECORD LENGTH: _____ sec.		SAMPLE RATE: <input type="checkbox"/> 1 ms. <input type="checkbox"/> 4 ms. <input type="checkbox"/> 2 ms. _____ ms.		GAIN MODE: <input type="checkbox"/> INITIAL <input type="checkbox"/> MANUAL <input type="checkbox"/> FINAL <input type="checkbox"/> OPERATE	
DISPLAY		MODE: <input type="checkbox"/> AGC <input type="checkbox"/> FLOAT <input type="checkbox"/> DEFOAT <input type="checkbox"/> AMPLIFIER <input type="checkbox"/> DIRECT		INITIAL GAIN: _____ db		TRIP SENS: _____ db	
CFS I		TYPE STACK:		GATE LENGTH: _____		RECORD REJECTION:	
SOURCE		TYPE: <input type="checkbox"/> DYNAMITE <input type="checkbox"/> VIBROSEIS <input type="checkbox"/> OTHER		PATTERN:		NO. OF POSITIONS: _____	
RECEIVER		TYPE:		PATTERN:		NO. OF ELEMENTS: _____	
SPREAD		NO. OF GROUPS: 48		GROUP INTERVAL: 330		SHOTPOINT INTERVAL: 1320	
DIAGRAMS/MISC. INFORMATION:		OFFSET GROUP 1: 7755		OFFSET GROUP 24: 165		OFFSET GROUP 48/96: 7755	

SHOTPOINT	TR. 10		TR. 20		SHOT				SPREAD		REMARKS	CORR. STACK				
	REFL NO.	REC.	REFL NO.	REC.	SIZE	DEPTH	NO.	OFFSET	DIR.	CDP SWITCH		LINE GROUPS	SET UP	TR. 10	TR. 20	TR. 30
48	251906	2010			150	70	41			29	42+1 - 53+4	5				
49		2011			150	70	42			33	43+1 - 54+4					
50		2012			150	70	43			37	44+1 - 55+4					
51		2013			150	70	44			41	45+1 - 56+4					
52		2014			150	70	45			45	46+1 - 57+4					
53		2015			150	70	46			49	47+1 - 58+4					
54		2016			150	70	47			53	48+1 - 59+4					
55		2017			150	70	48			57	49+1 - 60+4					

