


Anna Copy

LAND SEISMIC RECORDING LOG

CLIENT: <i>Husky</i>		PROSPECT: <i>NPR-A</i>		AREA: <i>Borlow</i>		LINE NO: <i>665</i>	
PARTY NO: <i>1183</i>		INST. ENG: <i>Streff</i>		DATE: <i>MO 5 DAY 58</i>		YEAR: <i>58</i>	
INSTRUMENT <input checked="" type="checkbox"/> 1 SYSTEM <input type="checkbox"/> 2 SYSTEMS		NO. BYTES IN HEADER REC: _____		NO. BYTES IN RECORD ID: _____		NO. BYTES PER SCAN: <i>134</i>	
CONFIGURATION (MAG TAPE)		FIELD TRACE NOS.: <i>1-48</i>		DATA CHANNEL NOS.: <i>1-48</i>		RECORD NUMBERS: <input checked="" type="checkbox"/> DEC. <input type="checkbox"/> OCT.	
PARAMETER		RECORD LENGTH: <i>6</i>		SAMPLE RATE: <input type="checkbox"/> 1 sec. <input type="checkbox"/> 4 sec.		GAIN MODE: <input checked="" type="checkbox"/> TEF <input type="checkbox"/> INITIAL <input type="checkbox"/> MANUAL	
DISPLAY		MODE: <input checked="" type="checkbox"/> AGC <input type="checkbox"/> FLOAT <input type="checkbox"/> DEFOAT <input type="checkbox"/> AMPLIFIER <input type="checkbox"/> DIRECT		INITIAL GAIN: <i>12</i> db		TRIP SENS: <i>0</i> db	
CFS I		TYPE: _____		GATE LENGTH: _____		RECORD REJECTION: _____	
SOURCE		TYPE: <input type="checkbox"/> SEISMITE <input type="checkbox"/> VIBROSEIS <input type="checkbox"/> OTHER		PATTERN: <i>inline-hole</i>		NO. OF POSITIONS: _____	
RECEIVER		TYPE: _____		CONNECTION: <i>Series-Parallel</i>		PATTERN: <i>inline</i>	
SPREAD		NO. OF GROUPS: <i>48</i>		GROUP INTERVAL: <i>220</i>		SHOTPOINT INTERVAL: <i>880</i>	
DIAGRAMS/MISC. INFORMATION		OFFSET GROUP 1: <i>5170</i>		OFFSET GROUP 2: <i>5170</i>		OFFSET GROUP 3: _____	



SHOTPOINT	TR. 1 to		TR. 2 to		SIZE	DEPTH	NO. OFFSET	D/G	COR SWITCH	SPREAD	REMARKS	CORR. STACK	
	REEL NO.	REC.	REEL NO.	REC.								TR. 1	TR. 2
1	781191407	266			120	16789	330	E	47	121-12+4	CDP does not move shooting through		
2		266			120	16790			47	111-12+4	Recorder @ SP-7		
3		267			120	16791	440	E	47	121-12+4			
4		268			120	16792			47	121-12+4			
5		269			120	16793			47	121-12+4			
6		270			010	16794			47	121-12+4			
7		271			120	16795			47	121-12+4			

665

LAND SEISMIC RECORDING LOG

CLIENT: Husky	PROJECT: NRA-A	AREA: Barrow	LINE NO.: 615	
PARTY NO.: 1182	INST. ENG.: Streff	DATE: NO 5 DAY 2 TH 79		

INSTRUMENT (9-TRACK)	<input type="checkbox"/> 1 SYSTEM <input type="checkbox"/> 2 SYSTEMS <input type="checkbox"/> 1-24 & 25-48 <input type="checkbox"/> 1-48 & 49-96	TYPE: <input type="checkbox"/> DPS III <input type="checkbox"/> DPS IV <input type="checkbox"/> OTHER	TRACKS: <input type="checkbox"/> 1 TRACK <input type="checkbox"/> 2 TRACKS FORMAT: <input type="checkbox"/> REG <input type="checkbox"/> DEC <input type="checkbox"/> OCT	PACKING DENSITY: (10) <input type="checkbox"/> 554 BPI (11) <input type="checkbox"/> 712 BPI (12) <input type="checkbox"/> 800 BPI	NO. BYTES IN HEADER REC: _____ NO. BYTES IN RECORD ID: _____ NO. BYTES PER SCAN: 134	RECORD NUMBERS: _____ GAIN CONSTANT: 36 INPUT IMPEDANCE: 200 ohms
CONFIGURATION (MAG TAPE)	FIELD TRACE NOS.: 1-48		AUXILIARY DATA:		NOISE THRESHOLD: _____	
PARAMETER	RECORD LENGTH: 6 sec.	SAMPLE RATE: <input type="checkbox"/> 5 sec. <input type="checkbox"/> 1 sec.	GAIN MODE: <input type="checkbox"/> INITIAL <input type="checkbox"/> FINAL	FILTERS: _____	LO CUT Hz SLOPE: 18	
DISPLAY	MODE: <input type="checkbox"/> ABC <input type="checkbox"/> FLOAT <input type="checkbox"/> DIRECT	INITIAL GAIN: 12 db	TRIP SENS.: 0 db	POLARITY CONVENTION: _____	HI CUT Hz SLOPE: 70	
CFS I	TYPE STACK: _____	GATE LENGTH: _____	RECORD REJECTION: _____	NOISE REDUCTION: _____	COBB SCALING: _____	
SOURCE	TYPE: <input type="checkbox"/> DYNAMIC <input type="checkbox"/> VIBROSEIS <input type="checkbox"/> OTHER	PATTERN: Inline-Shots	NO. OF POSITIONS: _____	INLINE SPACING: _____	STAGGER: _____	
RECEIVER	TYPE: 20-D	CONNECTION: Series-Parallel	RESISTANCE: 560 ohms	NO. OF ELEMENTS: 17	INLINE SPACING: 12	
SPREAD	NO. OF GROUPS: 48	GROUP INTERVAL: 020	SHOTPOINT INTERVAL: PP0	FOID: 6	DIRECTION OF PROGRESSION: East	

DIAGRAMS/MISC. INFORMATION: **241** **77, 308** **1349** **0270-282-70545**

TAM1 **TAM2**

SHOTPOINT	TR	TR		TR		SHOT		SPREAD		REMARKS	COBB STACK	
		TR	TR	TR	TR	SIZE	DEPTH	NO.	OFFSET		LINE GROUPS	TR
17		25117.91	2815			280	167	11	29	2+1 - 13+4	1	Recorder @ SP 13
18			286			280	167	12	33	3+1 - 14+4		
19			287			280	167	13	37	4+1 - 15+4		
20			288			280	167	14	41	5+1 - 16+4		
21			289			280	167	15	45	6+1 - 17+4		
22			290			280	167	16	49	7+1 - 18+4		
23			291			280	167	17	53	8+1 - 19+4		
24			292			280	167	18	57	9+1 - 20+4		
25			293			280	167	19	61	10+1 - 21+4		
26			294			280	167	20	65	11+1 - 22+4		
27			295			280	167	21	69	12+1 - 23+4		
28			296			280	167	22	73	13+1 - 24+4		
29			297			280	167	23	29	14+1 - 25+4	2	Recorder @ SP-25
30			298			280	167	24	33	15+1 - 26+4		
31			299			280	167	25	37	16+1 - 27+4		#299, 200-N.G.
32			300			280	167	26	41	17+1 - 28+4		
33			301			280	167	27	45	18+1 - 29+4		
34			302			280	167	28	49	19+1 - 30+4		
35			303			280	167	29	53	20+1 - 31+4		
36			304			280	167	30	57	21+1 - 32+4		

LAND SEISMIC RECORDING LOG

CLIENT: Husky		PROSPECT: UPR-A		AREA: Barrow		LINE NO.: 665			
PARTY NO.: 1182		INST. ENG.: SELEFF		DATE: MO 5 DAY 2 YE 79					
INSTRUMENT (9-TRACK) <input type="checkbox"/> 1 SYSTEM <input type="checkbox"/> 2 SYSTEMS NO. BYTES IN HEADER REC: _____		TYPE: <input type="checkbox"/> DFS III <input type="checkbox"/> DFS IV <input type="checkbox"/> DFS V <input type="checkbox"/> OTHER		FORMAT: B SLG		GAPPED: <input type="checkbox"/> GAPPED <input type="checkbox"/> UNGAPPED		PACKING DENSITY: (10) <input type="checkbox"/> 354 BPI 800 BPI (M) <input type="checkbox"/> 712 BPI 1000 BPI	
CONFIGURATION (MAG TAPE) FIELD TRACE NOS.: 1-4F DATA CHANNEL NOS.: 1-4F		AUXILIARY DATA: AUXILIARY CHANNEL NOS.: _____		RECORD NUMBERS: _____		GAIN CONSTANT: 26		INPUT IMPEDANCE: 20K ohms	
PARAMETER RECORD LENGTH: 6 sec.		SAMPLE RATE: <input type="checkbox"/> 1 sec. <input type="checkbox"/> 4 sec. 57 sec.		GAIN MODE: <input type="checkbox"/> INITIAL <input checked="" type="checkbox"/> FINAL		FILTERS: _____		LO CUT HZ SLOPE: 18	
DISPLAY MODE: <input type="checkbox"/> FLOAT <input type="checkbox"/> AMPLIFIER <input checked="" type="checkbox"/> DIRECT		INITIAL GAIN: 12 db		TRIP SENS: 0 db		POLARITY CONVENTION: <input type="checkbox"/> NEGATIVE <input checked="" type="checkbox"/> POSITIVE		HI CUT HZ SLOPE: 20	
CFS I TYPE STACK: _____		GATE LENGTH: _____		RECORD REACTION: _____		NOISE REDUCTION: _____		CORR. SCALING: _____	
SOURCE TYPE: <input type="checkbox"/> DYNAMITE <input type="checkbox"/> VIBROSEIS <input type="checkbox"/> OTHER		PATTERN: 10line		NO. OF POSITIONS: _____		INLINE SPACING: _____		LATERAL SPACING: _____	
RECEIVER CONNECTION: Series-Parallel		RESISTANCE: 560 ohms		SWEEP POSITION: _____		SWEEP END: _____		SWEEP START: _____	
SPREAD NO. OF GROUPS: 48		GROUP INTERVAL: 200		SHOTPOINT INTERVAL: 800		FOLD: 6		DIRECTION OF PROGRESSION: East	
DIAGRAMS/MISC. INFORMATION:		OFFSET GROUP 1: 5170		OFFSET GROUP 2: 110		OFFSET GROUP 2E: 110		OFFSET GROUP 48: 5170	

SHOTPOINT	TR 10		TR 10		SHOT		SPREAD		REMARKS	CORR. STACK				
	REEL NO.	REC.	REEL NO.	REC.	SIZE	DEPTH	NO.	OFFSET		DIR.	CDP SWITCH	LINE GROUPS		
128	251947	207			20	167	21			61	22+1 - 33+4	2		
129		208			20	167	22			65	23+1 - 34+4			
130		209			20	167	23			69	24+1 - 35+4			
131		210			20	167	24			25	25+1 - 36+4	3	Recorder @ SP-37	# 310 - 110 N.G
132		211			20	167	25			29	26+1 - 37+4			
133		212			20	167	26			33	27+1 - 38+4			# 315 N.G
134		213			20	167	27			37	28+1 - 39+4			
135		214			20	167	28			41	29+1 - 40+4			
136		215			20	167	29			45	30+1 - 41+4			# 318 N.G
137		216			20	167	30			49	31+1 - 42+4			
138		217			20	167	31			53	32+1 - 43+4			
139		218			20	167	32			57	33+1 - 44+4			# 323 N.G
140		219			20	167	33			61	34+1 - 45+4			
141		220			20	167	34			65	35+1 - 46+4			
142		221			20	167	35			69	36+1 - 47+4			
143		222			20	167	36			73	37+1 - 48+4			
144		223			20	167	37			77	38+1 - 49+4			
145		224			20	167	38			81	39+1 - 50+4			
146		225			20	167	39			85	40+1 - 51+4			
147		226			20	167	40			29	41+1 - 52+4	4	Recorder @ SP-52	

LAND SEISMIC RECORDING LOG

		CLIENT: HUSTY	PROSPECT: NPA-A	AREA: Barrow	LINE NO.: 665		
PART NO.: 1172		INST. ENG.: Steff		DATE: MO 5 DAY 2 YR 79			
INSTRUMENT (9-TRACK)	<input checked="" type="checkbox"/> 1 SYSTEM <input checked="" type="checkbox"/> 2 SYSTEMS	<input type="checkbox"/> T-24 & 25-48 <input type="checkbox"/> 1-48 & 49-96	TYPE: <input type="checkbox"/> DPS IZ <input type="checkbox"/> DPS IX <input type="checkbox"/> OTHER	<input type="checkbox"/> 9 TRACK <input type="checkbox"/> 21 TRACK	FORMAT: A SEC	<input type="checkbox"/> GAPPED <input type="checkbox"/> UNGAPPED	PACKING DENSITY: (L) <input type="checkbox"/> 356 BPI <input type="checkbox"/> 800 BPI (M) <input type="checkbox"/> 715 BPI <input type="checkbox"/> 1000 BPI
	NO. BYTES IN HEADER REC:	NO. BYTES IN RECORD ID:	NO. BYTES PER SCAN:	RECORD NUMBERS:	<input type="checkbox"/> DEC <input type="checkbox"/> OCT	GAIN CONSTANT: 26 (1) (2) (3) (4) (5) (6) (7)	INPUT IMPEDANCE: 204 ohms
CONFIGURATION (MAG TAPE)	FIELD TRACE NO.: 1-48		[ON MAG TAPE]		AUXILIARY DATA:		
PARAMETER	RECORD LENGTH: 6 sec.	SAMPLE RATE: <input type="checkbox"/> 1 ms. <input type="checkbox"/> 4 ms. <input type="checkbox"/> 8 ms. <input type="checkbox"/> 16 ms.	GAIN MODE: <input type="checkbox"/> INITIAL <input type="checkbox"/> FINAL <input type="checkbox"/> MANUAL <input type="checkbox"/> OPERATE	FILTERS: FREQ. 8 LO CUT HZ SLOPE 18 HI CUT HZ SLOPE 172		WHICH FILTER: <input type="checkbox"/> IN <input type="checkbox"/> OUT <input type="checkbox"/> DOWNBREAK <input type="checkbox"/> UPBREAK ON DISPLAY	
DISPLAY	<input type="checkbox"/> MODE: <input type="checkbox"/> FLOAT <input type="checkbox"/> DEFOAT <input type="checkbox"/> DIRECT <input type="checkbox"/> AMPLIFIER <input type="checkbox"/> DIRECT	INITIAL GAIN: 12 - 46	TRIP SENS: 0 - 4	POLARITY CONVENTION: <input type="checkbox"/> NEGATIVE <input type="checkbox"/> POSITIVE		NUMBERS ON MAG. TAPE <input type="checkbox"/> POSITIVE <input type="checkbox"/> NEGATIVE B.C.U. NORM./AIT SW	
CFS I	TYPE STACK:	GATE LENGTH:	RECORD SELECTION:	NOISE REDUCTION:	NOISE THRESHOLD:	CONV. SCALING:	
SOURCE	TYPE: <input type="checkbox"/> DYNAMIC <input type="checkbox"/> VIBROSEIS <input type="checkbox"/> OTHER PATTERN: inline-hole	NO. OF POSITIONS:	INLINE SPACING:	LATERAL SPACING:	STAGGER:	LENGTH:	WIDTH:
RECEIVER	TYPE: 20-0 CONNECTION: Series-Parallel	RESISTANCE: 540 ohms	SWEEP START:	SWEEP END:	SWEEP LENGTH:	SWEEP TAPE:	PHASE COMP.
SREAD	NO. OF GROUPS: 48	GROUP INTERVAL: 220	SHOTPOINT INTERVAL: 470	FOLD: 6	DIRECTION OF PROGRESSION: East		
DIAGRAMS/MISC. INFORMATION:							

SHOTPOINT NO.	FA		TB		SHOT		SPREAD		REMARKS:	CORR. STACK					
	REEL NO.	REC.	REEL NO.	REC.	SIZE	DEPTH	NO.	OFFSET		DIS.	CDP SWITCH	LINE GROUPS	1	2	3
1	3511	323			120	167	41		33		42+1 - 53+4				
2	3511	324			120	167	42		37		43+1 - 54+4				
3	3511	325			120	167	43		41		44+1 - 55+4				
4	3511	326			120	167	44		45		45+1 - 56+4				
5	3511	327			120	167	45		49		46+1 - 57+4				
6	3511	328			120	167	46		53		47+1 - 58+4				
7	3511	329			120	167	47		57		48+1 - 59+4				
8	3511	330			120	167	48		61		49+1 - 60+4				
9	3511	331			120	167	49		65		50+1 - 61+4				
10	3511	332			120	167	50		69		51+1 - 62+4				
11	3511	333			120	167	51		19		52+1 - 63+4				
12	3511	334			120	167	52		23		53+1 - 64+4				
13	3511	335			120	167	53		27		54+1 - 65+4				
14	3511	336			120	167	54		31		55+1 - 66+4				
15	3511	337			120	167	55		35		56+1 - 67+4				
16	3511	338			120	167	56		39		57+1 - 68+4				
17	3511	339			120	167	57		43		58+1 - 69+4				
18	3511	340			120	167	58		47		59+1 - 70+4				
19	3511	341			120	167	59		51		60+1 - 71+4				
20	3511	342			120	167	60		55		61+1 - 72+4				

319-M.C.

Recorder @ SA-25+2/1511

LAND SEISMIC RECORDING LOG

CLIENT: HUSKY		PROSPECT: NPR-A		AREA: Balkan		LINE NO: 665	
PARTY NO: 1112		INST. ENG: S. J. Hoff		DATE: MO 5 DAY 2 yr 79			
INSTRUMENT (9-TRACK)		TYPE: <input type="checkbox"/> DFC III <input type="checkbox"/> DFC IV <input type="checkbox"/> DFC V <input type="checkbox"/> OTHER		FORMAT: <input type="checkbox"/> 9 TRACK <input type="checkbox"/> 21 TRACK		<input type="checkbox"/> GAPPED <input type="checkbox"/> UNGAPPED <input type="checkbox"/> 2 SYSTEMS <input type="checkbox"/> 1-24 & 25-48 <input type="checkbox"/> 2 SYSTEMS <input type="checkbox"/> 1-48 & 49-96	
NO. BYTES IN HEADER REC.		NO. BYTES IN RECORDED ID		RECORD NUMBERS: <input type="checkbox"/> DEC <input type="checkbox"/> OCT		GAIN CONSTANT: (1) (2) (3) (4) (5) (6) INPUT IMPEDANCE: (7) (8) (9)	
CONFIGURATION (MAG TAPE)		FIELD TRACE NOS.		AUXILIARY DATA:		AUXILIARY CHANNEL NOS.	
DATA CHANNEL NOS.		(ON MAG TAPE)		FREQ. HI CUT HZ SLOPE		<input type="checkbox"/> NOTCH FILTER <input type="checkbox"/> IN <input type="checkbox"/> OUT <input type="checkbox"/> POLARITY CONVENTION: <input type="checkbox"/> NEGATIVE <input type="checkbox"/> POSITIVE	
PARAMETER		SAMPLE RATE: <input type="checkbox"/> 1 ms <input type="checkbox"/> 4 ms <input type="checkbox"/> 9 ms		GAIN MODE: <input type="checkbox"/> INITIAL <input type="checkbox"/> MANUAL <input type="checkbox"/> OPERATE		<input type="checkbox"/> LO CUT HZ SLOPE <input type="checkbox"/> PRESSURE INCREASE ON GEOPHONE	
DISPLAY		MODE: <input type="checkbox"/> AOC <input type="checkbox"/> FLOAT <input type="checkbox"/> DEFLAT <input type="checkbox"/> AMPLIFIER <input type="checkbox"/> DIRECT		TRIP SENS: <input type="checkbox"/> 45		<input type="checkbox"/> NOISE REDUCTION: <input type="checkbox"/> NOISE THRESHOLD: <input type="checkbox"/> CORR SCALING:	
CFS I		TYPE STACK:		PATTERN:		<input type="checkbox"/> DOWNBREAK <input type="checkbox"/> UPBREAK ON DISPLAY <input type="checkbox"/> B.C.U. NORM / ALT SW	
SOURCE		TYPE: <input type="checkbox"/> DYNAMIC <input type="checkbox"/> VIBROSEIS <input type="checkbox"/> OTHER		NO. OF POSITIONS		INLINE SPACING: SWEEP START: SWEEP END: SWEEP POSITION: SWEEP TAPER: PHASE COMP.	
RECEIVER		TYPE:		PATTERN:		STAGGER: LENGTH: WIDTH: LATERAL SPACING: LATERAL OFFSET:	
SPREAD		NO. OF GROUPS: 48		GROUP INTERVAL: 220		SHOTPOINT INTERVAL: 110 FOLD: 6 DIRECTION OF PROGRESSION: East	
DIAGRAMS/MISC. INFORMATION		OFFSET GROUP 1: 5170		OFFSET GROUP 25: 110		OFFSET GROUP 48/96: 5170 LEADING GROUP: 41	

SHOTPOINT	TR _____ TO _____		TR _____ TO _____		SHOT		SPREAD		REMARKS	CORR STACK	
	TR NO	REC.	TR NO	REC.	SIZE	DEPTH	NO. OFFSET	DIR.		TR NO	TR NO
168	3519A	417	31516		120	167	68	59	63+1 - 73+4	5	
169			31517		120	167	69	63	63+1 - 74+4		# 357-N.G.
170			31518		120	167	67	67	64+1 - 75+4		
171			31619		120	167	64	71	65+1 - 76+4		
172			31611		120	167	63	75	66+1 - 77+4		
173			31612		120	167	64	79	67+1 - 78+4		# 362-N.G.
174			31614		120	167	67	79	68+1 - 79+4	6	Recorder @ SP-79
175			31616		120	167	68	33	69+1 - 80+4		# 365-N.G.
176			31618		120	167	63	37	70+1 - 81+4		# 367-N.G.
177			31711		120	167	70	41	71+1 - 82+4		# 369-N.G.
178			31710		120	167	71	45	72+1 - 83+4		
179			31713		120	167	70	49	73+1 - 84+4		# 372-N.G.
180			31714		120	167	72	53	74+1 - 85+4		
181			31716		120	167	73	57	75+1 - 86+4		# 375-N.G.
182			31718		120	167	74	61	76+1 - 87+4		# 377-N.G.
183			31719		120	167	76	65	77+1 - 88+4		# -
184			31721		120	167	77	69	78+1 - 89+4		
185			31811		120	167	78	25	79+1 - 90+4	7	Recorder @ SP-91
186			31812		120	167	79	29	80+1 - 91+4		
187			31813		120	167	80	33	81+1 - 92+4		



LAND SEISMIC RECORDING LOG

CLIENT: <u>Husky</u>		PROSPECT: <u>NPR-A</u>		AREA: <u>Barron</u>		LINE NO: <u>665</u>							
PARTY NO: <u>1182</u>		INST. ENG: <u>Stieff</u>		DATE: <u>MO 5 DAY 2 YE 79</u>									
INSTRUMENT (9-TRACK)		NO. BYTES IN HEADER REC.		NO. BYTES IN RECORD ID		NO. BYTES PER SCAN		RECORD NUMBERS		GAIN CONSTANT		INPUT IMPEDANCE	
CONFIGURATION (MAG TAPE)		FIELD TRACE NOS.		DATA CHANNEL NOS.		AUXILIARY DATA		AUXILIARY CHANNEL NOS.					
PARAMETER		RECORD LENGTH		SAMPLE RATE		GAIN MODE		FILTERS		LO CUT		HI CUT	
DISPLAY		MODE		INITIAL GAIN		TRIP SENS.		POLARITY CONVENTION		PRESSURE INCREASE ON GEPHONE		NEGATIVE POSITIVE	
CFS 1		TYPE STACK		GATE LENGTH		RECORD REJECTION		NOISE REDUCTION		NOISE THRESHOLD		CORR. SCALING	
SOURCE		TYPE		PATTERN		NO. OF POSITIONS		INLINE SPACING		LATERAL SPACING		STAGGER	
RECEIVER		CONNECTION		RESISTANCE		STAGGER		INLINE SPACING		LENGTH		LATERAL SPACING	
SPREAD		NO. OF GROUPS		GROUP INTERVAL		SHOTPOINT INTERVAL		FOG		DIRECTION OF PROGRESSION		LEADING GROUP	

DIAGRAMS/MISC. INFORMATION:

SHOTPOINT	TR		TR		SHOT			SPREAD			REMARKS	CORE STACK	
	REEL NO	REC.	REEL NO	REC.	SIZE	DEPTH	NO. OFFSET	ONE	CDP SWITCH	LINE GROUPS		TR	REC.
187	781947	388			20	167	61	1	37	82+1-73+4	7		
188		388			20	167	83	1	41	83+1-74+4			
189		388			20	167	83	1	45	84+7-95+4			
190		388			20	167	84	1	49	85+1-96+4			
191	751948	388			20	167	85	1	53	86+1-97+4			
192		388			20	167	86	1	57	87+1-98+4			
193		388			20	167	87	1	61	88+1-99+4			
194		388			20	167	88	1	65	89+1-100+4			
195		388			20	167	89	1	69	90+1-101+4			
196		388			20	167	90	1	73	91+1-102+4			
197		388			20	167	91	1	77	92+1-103+4			
198		388			20	167	92	1	81	93+1-104+4			
199		388			20	167	93	1	85	94+1-105+4			
200		388			20	167	94	1	89	95+1-106+4			
201		388			20	167	95	1	93	96+1-107+4			
202		388			20	167	96	1	97	97+1-108+4			
203		388			20	167	97	1	5.3	98+1-109+4			
204		388			20	167	98	1	57	99+1-110+4			
205		388			20	167	99	1	61	100+1-111+4			
206		388			20	167	100	1	65	101+1-112+4			



LAND SEISMIC RECORDING LOG

	CLIENT: Husky	PROSPECT: NPR-A	AREA: Barron	LINE NO: 665					
	PARTY NO: 1132	INST. ENG: Steff		DATE: MO 5 DAY 2 YR 79					
INSTRUMENT (9-TRACK)	<input type="checkbox"/> 1 SYSTEM <input type="checkbox"/> 2 SYSTEMS	<input type="checkbox"/> 1-24 & 25-48 <input type="checkbox"/> 1-48 & 49-96	<input type="checkbox"/> OOPS <input type="checkbox"/> EVNS	TYPE: <input type="checkbox"/> DFS 1Z <input type="checkbox"/> DFS 2Z <input type="checkbox"/> DFS 3Z <input type="checkbox"/> OTHER	<input type="checkbox"/> 9 TRACK <input type="checkbox"/> 21 TRACK	FORMAT-SEG: <input type="checkbox"/> GAPPED <input type="checkbox"/> UNGAPPED	PACKING DENSITY: (L) <input type="checkbox"/> 250 BPI <input type="checkbox"/> 500 BPI	(M) <input type="checkbox"/> 712 BPI <input type="checkbox"/> 1400 BPI	
	NO. BYTES IN HEADER REC:	NO. BYTES IN RECORD ID:	NO. BYTES PER SCAN:	RECORD NUMBERS:	<input type="checkbox"/> DEC. <input type="checkbox"/> OCT	GAIN CONSTANT: (1) (2) (3) (4)	INPUT IMPEDANCE: (5) (6) (7)	ohms	
CONFIGURATION (MAG TAPE)	FIELD TRACE NOS.:	(ON MAG TAPE)			AUXILIARY DATA:	AUXILIARY CHANNEL NOS.:			
PARAMETER	RECORD LENGTH: sec.	SAMPLE RATE: <input type="checkbox"/> 1 sec. <input type="checkbox"/> 4 sec. <input type="checkbox"/> 2 sec. <input type="checkbox"/> 8 sec.	GAIN MODE: <input type="checkbox"/> INITIAL <input type="checkbox"/> 1PP <input type="checkbox"/> FINAL	<input type="checkbox"/> MANUAL <input type="checkbox"/> OPERATE	FILTERS: FREQ	LO CUT HZ SLOPE	H1 CUT HZ SLOPE	NOTCH FILTER: <input type="checkbox"/> IN <input type="checkbox"/> OUT	
DISPLAY	MODE: <input type="checkbox"/> AGC <input type="checkbox"/> FLOAT <input type="checkbox"/> DEPLOY <input type="checkbox"/> AMPLIFIER <input type="checkbox"/> DIRECT	INITIAL GAIN: db	TRIP SENS: db	POLARITY CONVENTION: <input type="checkbox"/> NEGATIVE <input type="checkbox"/> POSITIVE	PRESSURE IN. 22 CASE ON GEOPHONE:	NUMBERS ON MAG TAPE		<input type="checkbox"/> DOWNBREAK <input type="checkbox"/> UPBREAK ON DISPLAY	
CFS I	TYPE STACK:	GATE LENGTH:	RECORD REJECTION:	NOISE REDUCTION:	NOISE THRESHOLD:	CORR. SCALING:		R.C.U. NORM./ALT SW	
SOURCE	TYPE: <input type="checkbox"/> DYNAMITE <input type="checkbox"/> VIBROSEIS <input type="checkbox"/> OTHER	PATTERN:	NO. OF POSITIONS:	INLINE SPACING:	LATERAL SPACING:	STAGGER:	LENGTH:	WIDTH:	LATERAL OFFSET:
RECEIVER	CONNECTION:	RESISTANCE: ohms	STAGGER:	INLINE SPACING:	LENGTH:	WIDTH:	LATERAL OFFSET:		
SPREAD	NO. OF GROUPS: 48	GROUP INTERVAL: 200	SHOTPOINT INTERVAL: 480	FOLD: 6	DIRECTION OF PROGRESSION: East		LEADING GROUP: 48		
	OFFSET GROUP 1: 5170	OFFSET GROUP 24: 110	OFFSET GROUP 28: 110	OFFSET GROUP 48/20: 5170					

DIAGRAMS/MISC INFORMATION:

SHOTPOINT	TR 19		TR 10		SHOT					SPREAD		REMARKS	CORR STACK			
	REEL NO.	REC.	REEL NO.	REC.	SIZE	DEPTH	NO.	OFFSET	DIR.	CDP SWITCH	LINE GROUPS		TR 19	TR 10	TR 19	TR 10
11018	751	1844	4018		120	167	181	11		69	102+1-113+4					
11019		4019			120	167	182	11		73	103+1-114+4					
11020		4020			120	167	183	11		77	104+1-115+4					
11021		4021			120	167	184	11		27	105+1-116+4	9	Recorder @ 11622/11623			
11022		4022			120	167	185	11		31	106+1-117+4					
11023		4023			120	167	186	11		35	107+1-118+4					
11024		4024			120	167	187	11		39	108+1-119+4					
11025		4025			120	167	188	11		43	109+1-120+4					
11026		4026			120	167	189	11		47	110+1-121+4					
11027		4027			120	167	190	11		51	111+1-122+4					
11028		4028			120	167	191	11		55	112+1-123+4					
11029		4029			120	167	192	11		59	113+1-124+4					
11030		4030			120	167	193	11		63	114+1-125+4					
11031		4031			120	167	194	11		67	115+1-126+4					
11032		4032			120	167	195	11		71	116+1-127+4					
11033		4033			120	167	196	11		75	117+1-128+4					
11034		4034			120	167	197	11		25	118+1-129+4	10	Recorder @ 50-130			
11035		4035			120	167	198	11		29	119+1-130+4					
11036		4036			120	167	199	11		33	120+1-131+4					
11037		4037			120	167	200	11		77	121+1-132+4					

LAND SEISMIC RECORDING LOG

	CLIENT: Husky	PROSPECT: NPR-A	AREA: Dallan	LINE NO: 665	
	PARTY NO. 1182	INST. ENG. Stieff		DATE: MO. 5 DAY 2 YR 79	
INSTRUMENT (9-TRACK)	<input type="checkbox"/> 1 SYSTEM <input type="checkbox"/> 1-24 & 25-48 <input type="checkbox"/> CROSS EVENTS <input type="checkbox"/> 2 SYSTEMS <input type="checkbox"/> 1-48 & 49-96		TYPE: <input type="checkbox"/> DFS 1X <input type="checkbox"/> DFS 2X <input type="checkbox"/> DFS 3X <input type="checkbox"/> OTHER	9 TRACK <input type="checkbox"/> 21 TRACK RECORD NUMBERS: <input type="checkbox"/> DEC <input type="checkbox"/> OCT	GAPPED <input type="checkbox"/> UNGAPPED <input type="checkbox"/> GAIN CONSTANT FACING DENSITY: (10) (11) (12) (13) (14) (15) (16) (17)
CONFIGURATION (MAG TAPE)	FIELD TRACE NOS.: _____ DATA CHANNEL NOS.: _____		AUXILIARY DATA: (1) (2) (3) (4) (5) (6) (7)		
PARAMETER	RECORD LENGTH: _____	SAMPLE RATE: <input type="checkbox"/> 1 ms <input type="checkbox"/> 4 ms <input type="checkbox"/> 2 ms GAIN MODE: <input type="checkbox"/> INITIAL <input type="checkbox"/> MANUAL <input type="checkbox"/> OPERATE <input type="checkbox"/> IFP <input type="checkbox"/> FINAL		FILTERS: FREQ. TO CUT Hz SLOPE HI CUT Hz SLOPE NOISE FILTER: <input type="checkbox"/> IN <input type="checkbox"/> OUT <input type="checkbox"/> NEGATIVE <input type="checkbox"/> POSITIVE NUMBERS ON MAG TAPE <input type="checkbox"/> DOWNBREAK <input type="checkbox"/> UPBREAK ON DISPLAY	
DISPLAY	MODE: <input type="checkbox"/> AOC <input type="checkbox"/> FLOAT <input type="checkbox"/> DEFLOAT <input type="checkbox"/> AMPLIFIER <input type="checkbox"/> DIRECT	INITIAL GAIN: _____	NOISE REDUCTION: NOISE THRESHOLD: _____ CORR. SCALING: _____ P.C.U. NORM./ALT SW.		
CFS I	TYPE STACK: _____	GATE LENGTH: _____	TRIP BENS: _____ RECORD REJECTION: _____		
SOURCE	TYPE: <input type="checkbox"/> DYNAMITE <input type="checkbox"/> VIBROSEIS <input type="checkbox"/> OTHER	PATTERN: _____	NO. OF POSITIONS: _____ SWEEP POSITION: _____	IN-LINE SPACING: _____ SWEEP START: _____	LATERAL SPACING: _____ SWEEP END: _____
RECEIVER	TYPE: _____	CONNECTION: _____	RESISTANCE: _____ GROUP INTERVAL: _____	NO. OF ELEMENTS: _____ STAGGER: _____	SWEEP LENGTH: _____ SWEEP TAPE: _____
SPREAD	NO. OF GROUPS: 48 OFFSET GROUP 1: 5170	GROUP INTERVAL: 220 OFFSET GROUP 24: 110	SNAPSHOT INTERVAL: 880 OFFSET GROUP 25: 110	FOLD: 6 OFFSET GROUP 48/96: 5170	LATERAL SPACING: _____ WIDTH: _____ LATERAL OFFSET: _____ DIRECTION OF PROGRESSION: EAST LEADING GROUP: 48

DIAGRAMS/MISC. INFORMATION:

SHOTPOINT	TR 10		TR 20		SHOT			DB	CDP SWITCH	SPREAD	REMARKS	CORR. STACK	
	REEL NO.	REC.	REEL NO.	REC.	SIZE	DEPTH	NO. OFFSET					TR 10	TR 20
1128	7516	432			20	167	121		41	122+1 - 133+4			
1129		433			20	167	122		45	123+1 - 134+4			
1130		434			20	167	123		49	124+1 - 135+4			
1131		435			20	167	124		53	125+1 - T.4			
1132		436			20	167	125		57	126+1 - T.8			
1133		437			20	167	126		61	127+1 - T.12			
1134		440			20	167	127		65	128+1 - T.16			
1135		444			20	167	128		69	129+1 - T.20			
1136		447			20	167	129		73	130+1 - T.24			

E.O.L.