

Recording His - 14.0

LAND SEISMIC RECORDING LOG

CLIENT: <u>Husky</u>		PROSPECT: <u>NPR-1</u>		AREA: <u>Burrow</u>		LINE NO: <u>666</u>			
PARTY NO: <u>1182</u>		INST. ENG: <u>Streff-Windham</u>		DATE: <u>11</u>		DAY: <u>9</u>		YEAR: <u>79</u>	
INSTRUMENT <input type="checkbox"/> 1 SYSTEM <input type="checkbox"/> 2 SYSTEMS NO. BYTES IN HEADER REC.		<input type="checkbox"/> 1-24 & 25-48 <input type="checkbox"/> 1-48 & 49-96 ODDS EVENS		TYPE: <input type="checkbox"/> DFS III <input type="checkbox"/> DFS II <input type="checkbox"/> OTHER		<input type="checkbox"/> 9 TRACK <input type="checkbox"/> 21 TRACK SEC: <u>A</u>		<input type="checkbox"/> GAPPED <input type="checkbox"/> UNGAPPED PACKING DENSITY: (L0) <input type="checkbox"/> 356 BPI <input type="checkbox"/> 500 BPI (H1) <input type="checkbox"/> 712 BPI <input type="checkbox"/> 1000 BPI	
CONFIGURATION (MAG TAPE) FIELD TRACE NOS.: <u>1-48</u> DATA CHANNEL NOS.: <u>1-48</u>		NO. BYTES IN RECORD ID:		NO. BYTES PER SCAN: <u>134</u>		RECORD NUMBERS:		GAIN CONSTANT: <u>36</u> db INPUT IMPEDANCE: <u>200</u> ohms	
PARAMETER RECORD LENGTH: <u>1</u> sec		SAMPLE RATE: <input type="checkbox"/> 1 ms <input type="checkbox"/> 2 ms <input type="checkbox"/> 4 ms <input type="checkbox"/> 8 ms		GAIN MODE: <input type="checkbox"/> INITIAL <input type="checkbox"/> MANUAL <input checked="" type="checkbox"/> FINAL <input type="checkbox"/> OPERATE		FILTERS: <input type="checkbox"/> 20 CUT <input type="checkbox"/> HZ SLOPE <u>18</u> <input type="checkbox"/> HI CUT <input type="checkbox"/> HZ SLOPE <u>70</u>		NOTCH FILTER: <input type="checkbox"/> IN <input type="checkbox"/> OUT	
DISPLAY MODE: <input type="checkbox"/> AGC <input type="checkbox"/> FLOAT <input type="checkbox"/> DEFLOAT <input type="checkbox"/> AMPLIFIER <input type="checkbox"/> DIRECT		INITIAL GAIN: <u>11</u> db		TRIP SENS: <u>0</u> db		POLARITY CONVENTION: <input type="checkbox"/> NEGATIVE <input type="checkbox"/> POSITIVE		NUMBERS ON MAG TAPE: <input type="checkbox"/> UPBREAK <input type="checkbox"/> DOWNBREAK <input type="checkbox"/> ON DISPLAY	
CFS I TYPE STACK:		GATE LENGTH:		RECORD REJECTION:		NOISE REDUCTION:		CORR. SCALING:	
SOURCE <input type="checkbox"/> DYNAMITE <input type="checkbox"/> VIBROSEIS <input type="checkbox"/> OTHER		PATTERN: <u>Inline hole</u> CHG/HOLE: <u>20</u> HOLE DEPTH: <u>75</u>		NO. OF POSITIONS:		INLINE SPACING:		LATERAL SPACING:	
RECEIVER TYPE: <u>20-D</u> CONNECTION: <u>Series-Parallel</u>		PATTERN: <u>Inline</u> RESISTANCE: <u>560</u> ohms		NO. OF ELEMENTS: <u>18</u>		INLINE SPACING: <u>12</u>		LATERAL SPACING:	
SPREAD NO. OF GROUPS: <u>48</u> OFFSET GROUP 1: <u>5170</u>		GROUP INTERVAL: <u>220</u> OFFSET GROUP 24: <u>110</u>		SHOTPOINT INTERVAL: <u>440</u> OFFSET GROUP 25: <u>110</u>		FOLD: <u>6</u> OFFSET GROUP 48/96: <u>5170</u>		DIRECTION OF PROGRESSION: <u>North</u> LEADING GROUP: <u>48</u>	



DIAGRAMS/MISC. INFORMATION:

SHOTPOINT	TR 10		TR 10		SHOT				DIR	COP SWITCH	SPREAD		REMARKS	CORR SECT			
	REEL NO	REC.	REEL NO	REC.	SIZE	DEPTH	NO.	OFFSET			LINE GROUPS	FEET		TR 10	TR 10	TR 10	TR 10
1	151	102	01		20	167	312	11		25	T.1 - 6+4	1	Recorder @ SP 7				
2			02		20	167	313	11		29	T.5 - 7+4						
3			03		20	167	314	11		33	T.9 - 8+4						
4			04		20	167	315	11		37	T.13 - 9+4						
5			05		20	167	316	11		41	T.17 - 10+4						
6			06		20	167	317	11		45	T.21 - 11+4						
7			07		20	167	318	11		37	1+1 - 12+4	2	Recorder @ SP-10				
8			08		20	167	319	300	S	41	2+1 - 13+4						
9			09		20	167	400	400	W	45	3+1 - 14+4						
10			10		20	167	401	120	W	49	4+1 - 15+4						
11			11		20	167	402	11		53	5+1 - 16+4						
12			12		20	167	403	11		27	6+1 - 17+4	3					
13			13		20	167	404	11		31	7+1 - 18+4						
14			14		20	167	405	11		35	8+1 - 19+4						
15			15		20	167	406	11		39	9+1 - 20+4						
16			16		20	167	407	11		43	10+1 - 21+4						
17			17		20	167	408	11		47	11+1 - 22+4						
18			18		20	167	409	11		51	12+1 - 23+4						
19			19		20	167	500	11		55	13+1 - 24+4						
20			20		20	167	501	11		59	14+1 - 25+4						

666

Recording Hrs 14.5

LAND SEISMIC RECORDING LOG


		CLIENT: Husky	PROSPECT: NRB-A	AREA: Barrow	LINE NO. 666		
PARTY NO. 1122		INST. ENG. Streff-Windham		DATE. 10/18/79		MO. 4 DAY. 10/18/79	
INSTRUMENT		NO. BYTES IN HEADER REC.		NO. BYTES IN RECORD ID:		NO. BYTES PER SCAN: 154	
CONFIGURATION (MAG TAPE)		FIELD TRACE NOS. 1-48		DATA CHANNEL NOS. 1-48		AUXILIARY DATA:	
PARAMETER		RECORD LENGTH: 6		SAMPLE RATE: 18		GAIN MODE: INITIAL	
DISPLAY		MODE: AGC		INITIAL GAIN: 18		FILTERS: FREQ 8	
CFS 1		TYPE STACK:		GATE LENGTH:		NOISE REDUCTION:	
SOURCE		TYPE: DYNAMITE		PATTERN: inline hole		NO. OF POSITIONS: 18	
RECEIVER		TYPE: 20-D		PATTERN: inline		NO. OF ELEMENTS: 18	
SPREAD		CONNECTION: Series-Parallel		RESISTANCE: 500		STAGGER: 13	
DIAGRAMS/MISC. INFORMATION:		NO. OF GROUPS: 48		GROUP INTERVAL: 220		SHOTPOINT INTERVAL: 880	
		OFFSET GROUP 1: 5170		OFFSET GROUP 2: 110		OFFSET GROUP 48: 5170	

DIAGRAMS/MISC. INFORMATION:
 X ²⁴²¹ X ²⁴²⁴ X ^{SP-30} X ³²¹¹ X ³⁵¹⁴ X
 TAM 1 TRM 48

31-41 tests
 # 42 test - limb break

SHOTPOINT	TR		TR		SHOT			SPREAD		REMARKS		
	REEL NO.	REC.	REEL NO.	REC.	SIZE	DEPTH	NO. OFFSET	DIR.	CDP SWITCH			
120	751	26			20	167	11		27	24+1 - 35+4	1	Recorder @ SP 3512/3517
121		27			20	167	12		31	25+1 - 36+4		
122		28			20	167	13		35	26+1 - 37+4		
123		29			20	167	14		39	27+1 - 38+4		
124		30			20	167	15		43	28+1 - 39+4		
125		31			20	167	16		47	29+1 - 40+4		
126		32			20	167	17		51	30+1 - 41+4		
127		33			20	167	18		55	31+1 - 42+4		
128		34			20	167	19		59	32+1 - 43+4		
129		35			20	167	20		63	33+1 - 44+4		
130		36			20	167	21		67	34+1 - 45+4		
131		37			20	167	22		71	35+1 - 46+4		
132		38			20	167	23		27	36+1 - 47+4	2	Recorder @ SP 4712/4717
133		39			20	167	24		33	37+1 - 48+4		CDP ERROR
134		40			20	167	25		35	38+1 - 49+4		
135		41			20	167	26		39	39+1 - 50+4		
136		42			20	167	27		43	40+1 - 51+4		
137		43			20	167	28		47	41+1 - 52+4		
138		44			20	167	29		51	42+1 - 53+4		
139		45			20	167	30		55	43+1 - 54+4		

LAND SEISMIC RECORDING LOG

	CLIENT: Husky	PROSPECT: NPA-A	AREA: Barrow	LINE NO: 666
	PARTY NO. 1182	INST. ENG. Streff-Wadhwan		DATE: MO 4 DAY 10 YR 79
INSTRUMENT (9-TRACK)	<input type="checkbox"/> 1 SYSTEM <input type="checkbox"/> 2 SYSTEMS	<input type="checkbox"/> 1-24 & 25-48 <input type="checkbox"/> 1-48 & 49-96	TYPE: <input type="checkbox"/> DFS III <input type="checkbox"/> DFS IX	<input type="checkbox"/> 21 TRACK <input type="checkbox"/> 22 TRACK
	NO. BYTES IN HEADER REC.	NO. BYTES IN RECORD ID	NO. BYTES PER SCAN: 134	RECORD NUMBERS: <input type="checkbox"/> DEC. <input type="checkbox"/> OCT.
CONFIGURATION (MAG TAPE)	FIELD TRACE NOS.: 1-48	DATA CHANNEL NOS.: 1-48	AUXILIARY DATA: (1) (2) (3) (4) (5) (6) (7)	
PARAMETER	RECORD LENGTH: 6 sec.	SAMPLE RATE: <input type="checkbox"/> 1 ms. <input type="checkbox"/> 4 ms.	GAIN MODE: <input type="checkbox"/> INITIAL <input type="checkbox"/> MANUAL <input type="checkbox"/> OPERATE	FILTERS: FREQ. 12 Hz CUT 18 Hz SLOPE 20
DISPLAY	MODE: <input type="checkbox"/> AGC <input type="checkbox"/> FLOAT <input type="checkbox"/> AMPLIFIER <input type="checkbox"/> DEFLOAT <input type="checkbox"/> DIRECT	INITIAL GAIN: 18 db	TRIP SENS.: 0 db	POLARITY CONVENTION: <input type="checkbox"/> NEGATIVE <input type="checkbox"/> POSITIVE
CFS I	TYPE STACK:	GATE LENGTH:	RECORD REJECTION:	NOISE REDUCTION: <input type="checkbox"/> CORR. SCALING: <input type="checkbox"/>
SOURCE	TYPE: <input type="checkbox"/> DYNAMITE <input type="checkbox"/> VIBROSEIS <input type="checkbox"/> OTHER	PATTERN: inline-hole	NO. OF POSITIONS: 18	LATERAL SPACING: 10
RECEIVER	TYPE: 20-D	PATTERN: inline	NO. OF ELEMENTS: 18	LATERAL SPACING: 10
SPREAD	NO. OF GROUPS: 48	GROUP INTERVAL: 220	SHOTPOINT INTERVAL: 480	FOLD: 6

DIAGRAMS/MISC. INFORMATION:

SHOTPOINT	TR 1		TR 2		SHOT		DIR	CDP SWITCH	SPREAD	REMARKS	CORR. STACK				
	REEL NO.	REC.	REEL NO.	REC.	SIZE	DEPTH					NO.	OFFSET	TR 1	TR 2	TR 3
150	751172C	163			120	167	21	11	59	44+1 - 55+4	2				
151		164			120	167	22	11	63	45+1 - 56+4					
152		165			120	167	23	11	67	46+1 - 57+4					
153		166			120	167	24	11	71	47+1 - 58+4					
154		167			120	167	25	11	33	48+1 - 59+4					
155		168			120	167	26	11	37	49+1 - 60+4					
156		170			120	167	27	11	41	50+1 - 61+4					
157		172			120	167	28	11	45	51+1 - 62+4					
158		172			120	167	29	11	49	52+1 - 63+4					
159		173			120	167	30	11	53	53+1 - 64+4					
160		174			120	167	31	11	57	54+1 - 65+4	3	Recorder @ SP 67			
161		175			120	167	32	W	25	55+1 - 66+4	3				
162		176			120	167	33	W	29	56+1 - 67+4					
163		177			120	167	34	W	33	57+1 - 68+4					
164		178			120	167	35	W	37	58+1 - 69+4					
165		179			120	167	36	W	41	59+1 - 70+4					
166		180			120	167	37	11	45	60+1 - 71+4					
167		181			120	167	38	11	49	61+1 - 72+4					
168		182			120	167	39	11	53	62+1 - 73+4					
169		183			120	167	40	11	57	63+1 - 74+4					

LAND SEISMIC RECORDING LOG

		CLIENT: <u>Hughes</u> PARTY NO.: <u>1182</u> INST. ENG.: <u>Steff-Winham</u>	PROSPECT: <u>NPP-1</u> AREA: <u>Bullw</u>	LINE NO.: <u>666</u> DATE: <u>MO 4 DAY 18 1979</u>	
INSTRUMENT (9-TRACK) <input type="checkbox"/> 1 SYSTEM <input type="checkbox"/> 2 SYSTEMS NO. BYTES IN HEADER REC.: _____ NO. BYTES IN RECORD ID.: _____		TYPE: <input type="checkbox"/> DFS III <input type="checkbox"/> DFS IV <input type="checkbox"/> OTHER TRACKS: <input type="checkbox"/> 9 TRACK <input type="checkbox"/> 21 TRACK POPMAT: <u>B</u> SEC GAPPED: <input type="checkbox"/> GAPPED <input type="checkbox"/> UNGAPPED PACKING DENSITY: (L) <input type="checkbox"/> 350 RPI (H) <input type="checkbox"/> 712 RPI <input type="checkbox"/> 500 RPI <input type="checkbox"/> 1400 RPI		RECORD NUMBERS: <input type="checkbox"/> DEC <input type="checkbox"/> OCT GAIN CONSTANT: <u>36</u> db INFLT IMPEDANCE: <u>20k</u> ohms (1) (2) (3) (4) (5) (6) (7)	
CONFIGURATION (MAG TAPE) FIELD TRACE NOS.: <u>1-48</u> DATA CHANNEL NOS.: <u>1-48</u>		AUXILIARY DATA: AUXILIARY CHANNEL NOS.: _____ FILTERS: _____ LO CUT HZ SLOPE: <u>18</u> HI CUT HZ SLOPE: <u>20</u> NOTCH FILTER: <input type="checkbox"/> IN <input type="checkbox"/> OFF FREQ: <u>8</u> PRESSURE INCREASE ON GEOPHONE: <input type="checkbox"/> NEGATIVE <input type="checkbox"/> POSITIVE NUMBERS ON MAG TAPE: <input type="checkbox"/> DOWNBREAK <input type="checkbox"/> UPBREAK ON DISPLAY POLARITY CONVENTION: _____ NOISE REDUCTION: _____ CORP SCALING: _____ R.C.U. NORM / ALT SW			
PARAMETER RECORD LENGTH: _____ MODE: <input type="checkbox"/> RUC <input type="checkbox"/> FLOAT <input type="checkbox"/> DEFOAT <input type="checkbox"/> AMPLIFIER <input type="checkbox"/> DIRECT SAMPLE RATE: <input type="checkbox"/> 1 ms <input type="checkbox"/> 2 ms <input type="checkbox"/> 4 ms INITIAL GAIN: <u>18</u> db GATE LENGTH: _____ GAIN MODE: <input type="checkbox"/> TIME <input type="checkbox"/> INITIAL <input type="checkbox"/> FINAL <input type="checkbox"/> MANUAL <input type="checkbox"/> OPERATE TRIP SENS: <u>0</u> db RECORD REJECTION: _____		SOURCE TYPE: <input type="checkbox"/> DYNAMITE <input type="checkbox"/> VIBROSEIS <input type="checkbox"/> OTHER PATTERN: <u>Inline-Hole</u> CHG/ HOLE: <u>20</u> HOLE DEPTH: <u>75</u> NO. OF POSITIONS: _____ INLINE SPACING: _____ SWEEP POSITION: _____ SWEEP START: _____ SWEEP END: _____ STAGGER: _____ LENGTH: _____ WIDTH: _____ LATERAL OFFSET: _____ SWEEP LENGTH: _____ SWEEP TAPER: _____ PHASE COMP: _____			
RECEIVER TYPE: <u>30-0</u> CONNECTION: <u>Series-Parallel</u> RESISTANCE: <u>510</u> ohms		PATTERN: <u>Inline</u> NO. OF ELEMENTS: <u>18</u> STAGGER: _____ INLINE SPACING: <u>12</u> LENGTH: _____ WIDTH: _____ LATERAL OFFSET: _____		SPREAD NO. OF GROUPS: <u>48</u> OFFSET GROUP 1: <u>5170</u> GROUP INTERVAL: <u>220</u> OFFSET GROUP 24: <u>110</u> SHOTPOINT INTERVAL: <u>480</u> OFFSET GROUP 48/96: <u>5170</u> POLD: <u>6</u> DIRECTION OF PROGRESSION: <u>NORTH</u> LEADING GROUP: <u>48</u>	

DIAGRAMS/MISC. INFORMATION:

SHOTPOINT	TR		YR		SHOT		SPREAD		REMARKS	CORP STACK					
	TR NO.	REC.	YR NO.	REC.	SIZE	DEPTH	NO.	OFFSET		DIR.	COP SWITCH	LINE GROUPS	TR 41	TR 42	TR 43
77	7511	1815	17	111	120	167	41	11	61	64+1 - 75+4	3				
78	7511	1815	17	111	120	167	41	11	17	65+1 - 76+4	4				Recorder @ SP-79
79	7511	1815	17	111	120	167	41	11	22	66+1 - 77+4					
80	7511	1815	17	111	120	167	41	11	25	67+1 - 78+4					
81	7511	1815	17	111	120	167	41	11	29	68+1 - 79+4					
82	7511	1815	17	111	120	167	41	11	33	69+1 - 80+4					
83	7511	1815	17	111	120	167	41	11	37	70+1 - 81+4					
84	7511	1815	17	111	120	167	41	11	41	71+1 - 82+4					
85	7511	1815	17	111	120	167	41	11	45	72+1 - 83+4					
86	7511	1815	17	111	120	167	41	11	49	73+1 - 84+4					
87	7511	1815	17	111	120	167	41	11	53	74+1 - 85+4					
88	7511	1815	17	111	120	167	41	11	57	75+1 - 86+4					
89	7511	1815	17	111	120	167	41	11	61	76+1 - 87+4					
90	7511	1815	17	111	120	167	41	11	65	77+1 - 88+4					
91	7511	1815	17	111	120	167	41	11	33	78+1 - 89+4	5				Recorder @ SP-88
92	7511	1815	17	111	120	167	41	11	37	79+1 - 90+4					
93	7511	1815	17	111	120	167	41	11	41	80+1 - 91+4					
94	7511	1815	17	111	120	167	41	11	45	81+1 - 92+4					
95	7511	1815	17	111	120	167	41	11	49	82+1 - T.12					
96	7511	1815	17	111	120	167	41	11	53	83+1 - T.16					
97	7511	1815	17	111	120	167	41	11	57	84+1 - T.20					
98	7511	1815	17	111	120	167	41	11	61	85+1 - T.24					

F.O.B.