

67 Sp
Recording Hrs 15.0

LAND SEISMIC RECORDING LOG

CLIENT: Husky		PROSPECT: NPR-A		AREA: Barrow		LINE NO: 664	
PARTY NO: 1182		INST ENG: Stieff-Windham		DATE: MO 4 DAY 11 TH 79			
INSTRUMENT [9-TRACK] <input type="checkbox"/> 1 SYSTEM <input type="checkbox"/> 2 SYSTEMS		ODDS <input type="checkbox"/> 1-24 & 25-49 <input type="checkbox"/> 1-48 & 49-96		TYPE: <input type="checkbox"/> OPS III <input type="checkbox"/> OPS II <input type="checkbox"/> OPS I		<input type="checkbox"/> 9 TRACK <input type="checkbox"/> 21 TRACK	
NO BYTES IN HEADER REC:		NO BYTES IN RECORD ID:		NO BYTES PER SCAN: 134		RECORD NUMBERS: <input type="checkbox"/> DEC <input type="checkbox"/> OCT	
CONFIGURATION [MAG TAPE]		FIELD TRACE NOS: 1-48		AUXILIARY DATA		PACKING DENSITY: (LO) <input type="checkbox"/> 156 BPI (HI) <input type="checkbox"/> 712 BPI	
DATA CHANNEL NOS: 1-48		(ON MAG TAPE)		AUXILIARY CHANNEL NOS:		GAIN CONSTANT: 36 db	
PARAMETER		RECORD LENGTH: 6 sec		SAMPLE RATE: <input type="checkbox"/> 1 sec <input type="checkbox"/> 4 sec		FILTERS: <input type="checkbox"/> LO CUT <input type="checkbox"/> HI CUT	
DISPLAY		MODE: <input type="checkbox"/> PAGE <input type="checkbox"/> FLOAT <input type="checkbox"/> DIRECT		INITIAL GAIN: 18 db		FREQ: 6 Hz SLOPE 18 Hz SLOPE 70	
CFS I		TYPE STACK:		GATE LENGTH:		POLARITY CONVENTION: <input type="checkbox"/> NEGATIVE <input type="checkbox"/> POSITIVE	
SOURCE		TYPE: <input type="checkbox"/> DYNAMITE <input type="checkbox"/> VIBROSEIS <input type="checkbox"/> OTHER		PATTERN: Inline-Note		PRESSURE INCREASE ON GEOPHONE: <input type="checkbox"/> REG. <input type="checkbox"/> POSITIVE	
RECEIVER		TYPE: 351		PATTERN: Inline		CORR SCALING: <input type="checkbox"/> U. NORM. <input type="checkbox"/> ALT SW	
SPREAD		CONNECTION: Spacer-Bar 1/2"		RESISTANCE: 560 ohms		NOISE REDUCTION: <input type="checkbox"/> NOISE THRESHOLD: <input type="checkbox"/> CORR SCALING	

DIAGRAMS/MISC. INFORMATION: **751** **124 SP 1 11** **649**
X **X** **X** **X** **X**
TAN1 **TAN44** **#107-118-Tests** **#119 test line 10/11**

SHOTPOINT	SR				ER				SHOT				SPREAD		REMARKS	CUBE STACK		
	REFL NO	REC	REFL NO	REC	SIZE	DEPTH	NO	OFFSET	CDP	CDP SWITCH	LINE GROUPS	SEC	TR	LINE		TR	LINE	
11	751	1227	1121		210	167	11		27	75.1	- 614	1						
12			1122		210	167	12		29	75.2	- 724							
13			1123		210	167	13		33	75.9	- 814							
14			1124		210	167	14		37	75.13	- 914							
15			1125		210	167	15		41	75.17	- 1014							
16			1126		210	167	16		45	75.21	- 1114							
17			1127		210	167	17		49	81.1	- 1214							
18			1128		210	167	18		53	241	- 1314							
19			1129		210	167	19		57	311	- 1414							
20			1130		210	167	20		61	411	- 1514							
21			1131		210	167	21		65	511	- 1614							
22			1132		210	167	22	200	69	611	- 1714							
23			1133		310	167	23	500	73	711	- 1814							
24			1134		210	167	24		77	811	- 1914							
25			1135		210	167	25		81	911	- 2014							
26			1136		210	167	26		85	1011	- 2114							
27			1137		210	167	27		89	1111	- 2214							
28			1138		210	167	28		93	1211	- 2314							
29			1139		210	167	29		97	1311	- 2414							
30			1140		210	167	30		101	1411	- 2514							

#133-N.C.
#134-N.C.

#141-N.C.

Recorder @ SP-7
Recorder @ SP-31

LAND SEISMIC RECORDING LOG

CLIENT: Husky		PROSPECT: NPR-A		AREA: Burrow		LINE NO: 168	
PARTY NO: 112		INST ENG: Steff - Winthorn		DATE: MO 4 DAY 11 YR 79			
INSTRUMENT (9-TRACK) <input type="checkbox"/> 1 SYSTEM <input checked="" type="checkbox"/> 2 SYSTEMS NO BYTES IN HEADER REC: _____		TYPE <input type="checkbox"/> 1-24 & 25-48 <input type="checkbox"/> 1-48 & 49-96 <input type="checkbox"/> ODDS <input type="checkbox"/> EVENS		NO. BYTES PER SCAN: 124		RECORD NUMBERS: _____	
CONFIGURATION (MAG TAPE) FIELD TRACE NOS: 1-48 DATA CHANNEL NOS: L-48		[ON MAG TAPE]		AUXILIARY DATA AUXILIARY CHANNEL NOS: _____			
PARAMETER RECORD LENGTH: 6		SAMPLE RATE: <input type="checkbox"/> 1 ml. <input type="checkbox"/> 4 ml.		GAIN MODE: <input type="checkbox"/> INITIAL <input type="checkbox"/> MANUAL <input type="checkbox"/> OPERATE		FILTERS: <input type="checkbox"/> 1 Hz SLOPE <input type="checkbox"/> 18	
DISPLAY MODE: <input type="checkbox"/> FLOAT <input type="checkbox"/> AMPLIFIED <input type="checkbox"/> DIRECT		INITIAL GAIN: 0		TRIP SENS: 0		POLARITY CONVENTION: _____	
CFS I TYPE STACK: _____		GATE LENGTH: _____		RECORD REJECTION: _____		NOISE THRESHOLD: _____	
SOURCE TYPE: <input type="checkbox"/> DYNAMITE <input type="checkbox"/> VIBROSEIS <input type="checkbox"/> OTHER		PATTERN: inline - 10/10		NO. OF POSITIONS: _____		LATERAL SPACING: _____	
RECEIVER TYPE: 30 D		PATTERN: inline		NO. OF ELEMENTS: 18		LATERAL SPACING: 12	
SPREAD NO. OF GROUPS: 48		GROUP INTERVAL: 220		SHOTPOINT INTERVAL: 44		DIRECTION OF PROGRESSION: SW	

DIAGRAMS/MISC. INFORMATION:

SHOTPOINT NO.	TR 1		TR 2		SHOT			SPREAD	REMARKS	CORR STACK	
	REEL NO.	REC.	REEL NO.	REC.	SIZF	DEPTH	NO. OFFSET			LINE GROUPS	TR 1
101	751	1144			20	167	21	9	15+1 - 20+4		
102		1145			20	167	22	13	16+1 - 27+4		
103		1146			20	167	23	17	17+1 - 28+4		
104		1147			20	167	24	21	18+1 - 29+4	#147-N.G.	
105		1150			20	167	25	25	19+1 - 30+4		
106		1151			20	167	26	29	20+1 - 31+4	#149-N.G.	
107		1154			20	167	27	33	21+1 - 32+4	#152-153-N.G.	
108		1155			20	167	28	37	22+1 - 33+4		
109		1157			20	167	29	41	23+1 - 34+4	#156-N.G.	
110		1158			20	167	30	49	25+1 - 36+4	GOOD ERROR	
111		1160			20	167	31	49	25+1 - 36+4	#155	
112		1162			20	167	32	53	26+1 - 37+4	#161-N.G.	
113		1163			20	167	33	57	27+1 - 38+4		
114		1165			20	167	34	61	28+1 - 39+4	#164-N.G.	
115		1166			20	167	35	65	29+1 - 40+4	Double Record #165	
116		1166			20	167	36	33	30+1 - 41+4	Recorder @ 52-40	
117		1168			20	167	37	37	31+1 - 42+4	#167-N.G.	
118		1169			20	167	38	41	32+1 - 43+4		
119		1170			20	167	39	45	33+1 - 44+4		
120		1172			20	167	40	49	34+1 - 45+4	#171-N.G.	

*Two Reels 165

LAND SEISMIC RECORDING LOG

		CLIENT: <u>Husky</u>	PROSPECT: <u>NPR-1</u>	AREA: <u>Barron</u>	LINE NO: <u>668</u>		
PARTY NO: <u>1182</u>		INST ENG: <u>Steeff - Windham</u>		DATE: <u>MO. 9 - DAY 11 - YR 72</u>			
INSTRUMENT (9-TRACK)	<input type="checkbox"/> SYSTEM <input type="checkbox"/> 2 SYSTEMS	<input type="checkbox"/> 1-24 & 25-48 <input type="checkbox"/> 1-48 & 49-96	<input type="checkbox"/> ODDS <input type="checkbox"/> EVENS	TYPE: <input type="checkbox"/> DFS III <input type="checkbox"/> DFS III <input type="checkbox"/> DFS III <input type="checkbox"/> OTHER	<input type="checkbox"/> 9 TRACK <input type="checkbox"/> 21 TRACK	FORMAT: <u>SEG</u>	<input type="checkbox"/> GAPPED <input type="checkbox"/> UNGAPPED
	NO BYTES IN HEADER REC:	NO BYTES IN RECORD ID:	NO BYTES PER SCAN: <u>134</u>	RECORD NUMBERS:	<input type="checkbox"/> DEC <input type="checkbox"/> OCT	GAIN CONSTANT: <u>36</u>	INPUT IMPEDANCE: <u>100</u>
CONFIGURATION (MAG TAPE)	FIELD TRACE NOS: <u>1-48</u>			AUXILIARY DATA			
	DATA CHANNEL NOS: <u>1-48</u>			AUXILIARY CHANNEL NOS:			
PARAMETER	RECORD LENGTH: <u>6</u> sec	SAMPLE RATE: <input type="checkbox"/> 1 ms <input type="checkbox"/> 4 ms <input type="checkbox"/> 7 ms <input type="checkbox"/> 2 ms	GAIN MODE: <input type="checkbox"/> INITIAL <input type="checkbox"/> FINAL	<input type="checkbox"/> MANUAL <input type="checkbox"/> OPERATE	FILTERS: FREQ <u>Y</u>	LO CUT HZ SLOPE <u>18</u>	HI CUT HZ SLOPE <u>70</u>
DISPLAY	MODE: <input type="checkbox"/> FLOAT <input type="checkbox"/> MAGC	<input type="checkbox"/> AMPLIFIER <input type="checkbox"/> DIRECT	INITIAL GAIN: <u>0</u>	JRP SENS: <u>0</u>	POLARITY CONVENTION	PRESSURE INCREASE ON GLOPHONE:	<input type="checkbox"/> NEGATIVE <input type="checkbox"/> POSITIVE
CFS I	TYPE STACK:	GATE LENGTH:	RECORD REJECTION:	NOISE REDUCTION:	NOISE THRESHOLD:	CORR. SCALING:	<input type="checkbox"/> IN <input type="checkbox"/> OUT
SOURCE	TYPE: <input type="checkbox"/> DYNAMITE <input type="checkbox"/> VIBROSEIS <input type="checkbox"/> OTHER	PATTERN: <u>Latent 1 hole</u>	NO. OF POSITIONS:	INLINE SPACING:	LATERAL SPACING:	STAGGER:	LENGTH:
	CHG/ HOLE: <u>20</u>	HOLE DEPTH: <u>75</u>	SWEEP POSITION:	SWEEP START:	SWEEP END:	SWEEP LENGTH:	SWEEP TAPE:
RECEIVER	TYPE: <u>20 P</u>	PATTERN: <u>10 line</u>	RESISTANCE: <u>510</u>	NO. OF ELEMENTS: <u>18</u>	INLINE SPACING: <u>12</u>	LATERAL SPACING:	WIDTH:
	CONNECTION: <u>Series-Parallel</u>			STAGGER:	LENGTH:	SWEEP COMP.	LATERAL OFFSET:
SPREAD	NO. OF GROUPS: <u>48</u>	GROUP INTERVAL: <u>220</u>	SHOTPOINT INTERVAL: <u>YX0</u>	FOLD: <u>6</u>	DIRECTION OF PROGRESSION: <u>S.W.</u>	LEADING GROUP: <u>48</u>	
	OFFSET GROUP 1: <u>5170</u>	GROUP 24: <u>110</u>	OFFSET GROUP 24: <u>110</u>	OFFSET GROUP 48/96: <u>5170</u>			

DIAGRAMS/MISC. INFORMATION:

SHOTPOINT	TR		TR		SHOT			SPREAD			REMARKS	CORR STACK			
	REEL NO	REC.	REEL NO	REC.	SIZE	DEPTH	NO. OFFSET	DIR	COP SWITCH	LINE GROUPS		ST	REC	TR	SR
141	7511	1772			20	167	41		53	35+1 - 4114	3				
142		1773			20	167	42		57	36+1 - 4214					
143		1774			20	167	43		61	37+1 - 4314					
144		1775			20	167	44		65	38+1 - 4414					
145		1776			20	167	45		69	39+1 - 5014					
146		1777			20	167	46		31	40+1 - 5114	4				
147		1778			20	167	47		35	41+1 - 5214					
148		1779			20	167	48		39	42+1 - 5314					
149		1780			20	167	49		43	43+1 - 5414					
150		1781			20	167	50		47	44+1 - 5514					
151		1782			20	167	51		31	45+1 - 5614					
152		1783			20	167	52		53	46+1 - 5714					
153		1784			20	167	53		57	47+1 - 5814					
154		1785			20	167	54		63	48+1 - 5914					
155		1786			20	167	55		67	49+1 - 6014					
156		1787			20	167	56		71	50+1 - 6114					
157		1788			20	167	57		27	51+1 - 6214	5				
158		1789			20	167	58		31	52+1 - 6314					
159		1790			20	167	59		35	53+1 - 6414					
160		1791			20	167	60		39	54+1 - 6514					

LAND SEISMIC RECORDING LOG

CLIENT: <u>Hustler</u>		PROSPECT: <u>NPR-A</u>		AREA: <u>Barrow</u>		LINE NO: <u>668</u>	
PARTY NO: <u>1182</u>		INST. ENG: <u>Steff-windham</u>		DATE: <u>4 DAY 11 TR 78</u>			
INSTRUMENT (9-TRACK) <input type="checkbox"/> 1 SYSTEM <input type="checkbox"/> 2 SYSTEMS <input type="checkbox"/> 1-24 & 25-48 <input type="checkbox"/> 1-48 & 49-96		ODDS <input type="checkbox"/> EVENS		TYPE <input type="checkbox"/> DFS III <input type="checkbox"/> DFS II <input type="checkbox"/> DFS I <input type="checkbox"/> OTHER		<input type="checkbox"/> 9 TRACK <input type="checkbox"/> 21 TRACK FORMAT: _____ SEG: _____ <input type="checkbox"/> GAPPED <input type="checkbox"/> UNGAPPED PACKING DENSITY: _____ (L) <input type="checkbox"/> 350 BPI <input type="checkbox"/> 800 BPI (H) <input type="checkbox"/> 712 BPI <input type="checkbox"/> 1600 BPI	
NO BYTES IN HEADER REC. _____		NO BYTES IN RECORD ID. _____		NO. BYTES PER SCAN _____		RECORD NUMBERS: _____ <input type="checkbox"/> DEC <input type="checkbox"/> OCT GAIN CONSTANT: _____ db INPUT IMPEDANCE: _____ ohms	
CONFIGURATION (MAG TAPE) FIELD TRACE NOS.: _____ DATA CHANNEL NOS.: _____		[ON MAG TAPE]		AUXILIARY DATA: AUXILIARY CHANNEL NOS.: _____			
PARAMETER RECORD LENGTH: _____		SAMPLE RATE: <input type="checkbox"/> 1ms <input type="checkbox"/> 4ms <input type="checkbox"/> 2ms		GAIN MODE: <input type="checkbox"/> INITIAL <input type="checkbox"/> MANUAL <input type="checkbox"/> IFF <input type="checkbox"/> FINAL <input type="checkbox"/> OPERATE		FILTERS: _____ LO CUT _____ HZ HZ SLOPE _____ HI CUT _____ HZ HZ SLOPE _____ FREQ. _____ NOISE REDUCTION: _____ NOISE THRESHOLD: _____ CORR. SCALING: _____	
DISPLAY MODE: <input type="checkbox"/> AGC <input type="checkbox"/> FLOAT <input type="checkbox"/> AMPLIFIER <input type="checkbox"/> DEFOAT <input type="checkbox"/> DIRECT		INITIAL GAIN: _____ db		TRIP SENS.: _____ db		POLARITY CONVENTION: _____ PRESSURE INCREASE ON GEOPHONE: _____ <input type="checkbox"/> NEGATIVE <input type="checkbox"/> POSITIVE NUMBERS ON ON MAG TAPE: _____ <input type="checkbox"/> DOWNBREAK <input type="checkbox"/> UPBREAK ON DISPLAY: _____ P.C.U. NORM./ALT SW	
CFS I TYPE STACK: _____		GATE LENGTH: _____		RECORD REJECTION: _____		CORR. SCALING: _____	
SOURCE TYPE: <input type="checkbox"/> DYNAMITE <input type="checkbox"/> VIBROSEIS <input type="checkbox"/> OTHER		PATTERN: _____		NO. OF POSITIONS: _____		INLINE SPACING: _____ LATERAL SPACING: _____ STAGGER: _____ LENGTH: _____ WIDTH: _____ LATERAL OFFSET: _____	
RECEIVER TYPE: _____		PATTERN: _____		NO. OF ELEMENTS: _____		INLINE SPACING: _____ LATERAL SPACING: _____ STAGGER: _____ LENGTH: _____ WIDTH: _____ LATERAL OFFSET: _____	
SPREAD NO. OF GROUPS: <u>48</u>		GROUP INTERVAL: <u>220</u>		SHOTPOINT INTERVAL: <u>220</u>		FIELD: <u>6</u> DIRECTION OF PROGRESSION: <u>SW</u> LEADING GROUP: <u>48</u>	
OFFSET GROUP 1: <u>5170</u>		OFFSET GROUP 2: <u>110</u>		OFFSET GROUP 3: <u>110</u>		OFFSET GROUP 4: <u>5170</u>	

DIAGRAMS/MISC. INFORMATION.

SHOTPOINT	TR 10		TR 20		SHOT		SPREAD		REMARKS	CORR. STAGE	
	REEL NO.	REC.	REEL NO.	REC.	SIZE	DEPTH	NO.	OFFSET		DIR	CDP SWITCH
611	7511	217	217	217	20	67	41	43	55+1 - 664	5	11200, 207, 208 - N.G.
612		218			20	67	42	47	56+1 - 7.4		11210 - N.G.
613		219			20	67	43	51	57+1 - 7.8		
614		220			20	67	44	55	58+1 - 7.12		
615		221			20	67	45	59	59+1 - 7.16		
616		222			20	67	46	63	60+1 - 7.20		
617		223			20	67	47	67	61+1 - 7.24		
									FOL		

E.O.L.