

81 S/P's

LAND SEISMIC RECORDING LOG

CLIENT: <b>HUSKY</b>		PROSPECT: <b>NPK-4</b>		AREA: <b>BARROW</b>		LINE NO: <b>670</b>	
PARTY NO: <b>1182</b>		INST. ENG: <b>STREFF - WINDHAM</b>		DATE: <b>24</b> DAY <b>8</b> TH <b>79</b>		Globe Logo	
INSTRUMENT (9-TRACK) <input checked="" type="checkbox"/> 1 SYSTEM <input type="checkbox"/> 2 SYSTEMS		NO. BYTES IN RECORDED ID: <b>1-48</b>		NO. BYTES PER SCAN: <b>134</b>		RECORD NUMBERS: <input checked="" type="checkbox"/> DEC <input type="checkbox"/> OCT	
CONFIGURATION (MAG TAPE) FIELD TRACE NOS. <b>1-48</b> DATA CHANNEL NOS. <b>1-48</b>		AUXILIARY DATA: <b>7B</b> <b>4M</b>		AUXILIARY CHANNEL NOS. <b>3</b> <b>4</b>		GAIN CONSTANT: <b>36</b>	
PARAMETER RECORD LENGTH: <b>6</b> sec		SAMPLE RATE: <b>1</b> sec		GAIN MODE: <input type="checkbox"/> INITIAL <input type="checkbox"/> FINAL <input type="checkbox"/> MANUAL <input type="checkbox"/> OPERATE		FILTERS: <b>FREQ 8</b>	
DISPLAY MODE: <input checked="" type="checkbox"/> AGC <input type="checkbox"/> FLOAT <input type="checkbox"/> DEFOAT <input type="checkbox"/> DIRECT		INITIAL GAIN: <b>18</b> db		JTRIP SENS: <b>18</b> db		POLARITY CONVENTION: <input type="checkbox"/> NEGATIVE <input type="checkbox"/> POSITIVE	
CFS I TYPE STACK:		GATE LENGTH:		RECORD REJECTION:		NOISE THRESHOLD:	
SOURCE TYPE: <input checked="" type="checkbox"/> DYNAMIC <input type="checkbox"/> VIBROSEIS <input type="checkbox"/> OTHER		PATTERN: <b>single hole - inline</b>		NO. OF POSITIONS: <b>18</b>		INLINE SPACING: <b>12'</b>	
RECEIVER TYPE: <b>GSC-20 D</b>		PATTERN: <b>inline</b>		NO. OF ELEMENTS: <b>18</b>		INLINE SPACING: <b>12'</b>	
CONNECTION: <b>Series-parallel</b>		RESISTANCE: <b>560 Ω</b>		STAGGER:		LATERAL SPACING:	
SPREAD NO. OF GROUPS: <b>48</b>		GROUP INTERVAL: <b>220'</b>		SHOTPOINT INTERVAL: <b>880'</b>		FOLD: <b>6</b>	
OFFSET GROUP 1: <b>5170'</b>		OFFSET GROUP 2: <b>110'</b>		OFFSET GROUP 25: <b>110'</b>		OFFSET GROUP 48/48: <b>5170'</b>	

DIAGRAMS/MISC. INFORMATION: *TR-1 24 sp trail* → *TR-24 TR-25* *SP 2* *SP 6* *SP 7*

SHOTPOINT	TR 1		TR 2		POP		SHOT DEPTH	NO. OFFSET	DIR	CDP SWITCH	LINE GROUPS	REMARKS	CORE STACK	
	TR 1	TR 2	TR 1	TR 2	SIZE	DEPTH							TR 1	TR 2
1	7519	25	353		28	67	11		25	7-1	6+4	2		
2			354		28	67	12		27	7-5	7+4			
3			355		28	67	13		33	7-9	8+4			
4			356		28	67	14		37	7-13	9+4			
5			357		28	67	15		41	7-17	10+4			
6			358		28	67	16		45	7-21	11+4			
7			359		28	67	17		49	7-25	12+4			
8			360		28	67	18		53	2+1	13+4			
9			361		28	67	19		57	3+1	14+4			
10			362		28	67	20		61	4+1	15+4			
11			363		28	67	21		65	5+1	16+4			
12			364		28	67	22		69	6+1	17+4			
13			365		28	67	23		25	7+1	18+4	3	revised at SP 19	
14			366		28	67	24		29	8+1	19+4		File #366 → 367	
15			367		28	67	25		33	9+1	20+4		musings	
16			368		28	67	26		37	10+1	21+4			
17			369		28	67	27		41	11+1	22+4			
18			370		28	67	28		45	12+1	23+4			
19			371		28	67	29		49	13+1	24+4			
20			372		28	67	30		53	14+1	25+4			

## LAND SEISMIC RECORDING LOG

CLIENT: <b>HUSKY</b>		PROSPECT: <b>NPR-4</b>		AREA: <b>BARRROW</b>		LINE NO.: <b>670</b>																																																																																																																																																																																																																																																																																																																																																																																																																						
PARTY NO.: <b>1182</b>		INST. ENG.: <b>STREFF - WINDHILL</b>		DATE: <b>MO. 4 DAY 8 YR 79</b>																																																																																																																																																																																																																																																																																																																																																																																																																								
INSTRUMENT (9-TRACK)		<input checked="" type="checkbox"/> 1 SYSTEM <input type="checkbox"/> 2 SYSTEMS		<input type="checkbox"/> 1-24 & 35-48 <input type="checkbox"/> 1-48 & 49-96		TYP: <input type="checkbox"/> DFS III <input type="checkbox"/> DFS IX <input type="checkbox"/> OTHER		<input checked="" type="checkbox"/> 1 TRACK <input type="checkbox"/> 2 TRACKS		FORMAT: <b>SEC</b> <input type="checkbox"/> SEC <input type="checkbox"/> OCT		<input type="checkbox"/> GAPPED <input type="checkbox"/> UNGAPPED		PACKING DENSITY: (10) <input type="checkbox"/> 350 BPM (11) <input type="checkbox"/> 500 BPM (12) <input type="checkbox"/> 712 BPM (13) <input type="checkbox"/> 800 BPM																																																																																																																																																																																																																																																																																																																																																																																																														
NO. BYTES IN HEADER REC:		NO. BYTES IN RECORD ID:		NO. BYTES PER SCAN: <b>134</b>		RECORD NUMBERS:		GAIN CONSTANT: <b>36</b>		INPUT IMPEDANCE: <b>20,000</b>																																																																																																																																																																																																																																																																																																																																																																																																																		
CONFIGURATION (MAG TAPE)		FIELD TRACE NOS.: <b>1-48</b>		DATA CHANNEL NOS.: <b>1-48</b> (ON MAG TAPE)		AUXILIARY DATA:		AUXILIARY CHANNEL NOS.: <b>3 4</b>																																																																																																																																																																																																																																																																																																																																																																																																																				
PARAMETER		RECORD LENGTH: <b>6</b>		SAMPLE RATE: <input type="checkbox"/> 1 sec. <input type="checkbox"/> 4 sec.		GAIN MODE: <input type="checkbox"/> INITIAL <input type="checkbox"/> FINAL		MANUAL OPERATE		FILTERS: FREQ <b>8</b>		LO CUT Hz SLOPE <b>18</b>		HI CUT Hz SLOPE <b>70</b>		NOISE FILTER: <input type="checkbox"/> IN <input type="checkbox"/> OUT																																																																																																																																																																																																																																																																																																																																																																																																												
DISPLAY		MODE: <input type="checkbox"/> FLOAT <input type="checkbox"/> AMPLIFIER		INITIAL GAIN: <b>18</b>		TYPE SENS: <b>18</b>		RECORD REJECTION:		POLARITY CONVENTION: <input type="checkbox"/> PRESSURE INCREASE ON GEOPHONES		NEGATIVE POSITIVE		NUMBERS ON MAG TAPE		DOWNBREAK UPBREAK ON DISPLAY																																																																																																																																																																																																																																																																																																																																																																																																												
CFS I		TYPE STAGE:		GATE LENGTH:		RECORD REJECTION:		NOISE REDUCTION:		NOISE THRESHOLD:		CORR SCALING:		CORR SCALE:		F.C.U. NORM/ALT SW																																																																																																																																																																																																																																																																																																																																																																																																												
SOURCE		TYPE: <input type="checkbox"/> DYNAMIE <input type="checkbox"/> VIBROSEIS <input type="checkbox"/> OTHER		PATTERN: <b>Single Hole - inline</b>		NO. OF POSITIONS:		INLINE SPACING:		LATERAL SPACING:		STAGGER:		LENGTH:		WIDTH:		LATERAL OFFSET:																																																																																																																																																																																																																																																																																																																																																																																																										
RECEIVER		TYPE: <b>ESC-20 D</b>		PATTERN: <b>inline</b>		NO. OF ELEMENTS: <b>18</b>		INLINE SPACING: <b>12'</b>		LATERAL SPACING:		STAGGER:		LENGTH:		WIDTH:		LATERAL OFFSET:																																																																																																																																																																																																																																																																																																																																																																																																										
SPREAD		CONNECTION: <b>Series - Parallel</b>		RESISTANCE: <b>560</b>		STAGGER:		LENGTH:		WIDTH:		LATERAL OFFSET:																																																																																																																																																																																																																																																																																																																																																																																																																
		NO. OF GROUPS: <b>48</b>		GROUP INTERVAL: <b>220'</b>		SHOTPOINT INTERVAL: <b>880'</b>		FOLD: <b>6</b>		DIRECTION OF PROGRESSION: <b>N → S</b>																																																																																																																																																																																																																																																																																																																																																																																																																		
		OFFSET GROUP 1: <b>5170</b>		OFFSET GROUP 2: <b>110'</b>		OFFSET GROUP 3: <b>110'</b>		OFFSET GROUP 4: <b>5170'</b>		LEADING GROUP: <b>48</b>																																																																																																																																																																																																																																																																																																																																																																																																																		
DIAGRAMS/MISC. INFORMATION:																																																																																																																																																																																																																																																																																																																																																																																																																												
<table border="1" style="width: 100%; border-collapse: collapse;"> <thead> <tr> <th rowspan="2">SHOTPOINT</th> <th colspan="2">TR 1 to 48</th> <th colspan="2">TR 49 to 96</th> <th colspan="4">SHOT</th> <th colspan="4">SPREAD</th> <th rowspan="2">REMARKS</th> <th colspan="4">CORR STACK</th> </tr> <tr> <th>REEL NO.</th> <th>REC.</th> <th>REEL NO.</th> <th>REC.</th> <th>SIZE</th> <th>DEPTH</th> <th>NO.</th> <th>OFFSET</th> <th>DIR.</th> <th>CDP SWITCH</th> <th colspan="2">LINE GROUPS</th> <th>OFF</th> <th>TR 1</th> <th>TR 2</th> <th>TR 3</th> <th>TR 4</th> </tr> </thead> <tbody> <tr><td>21</td><td>3519</td><td>375</td><td></td><td></td><td>20</td><td>67</td><td>31</td><td></td><td></td><td>57</td><td>15+1</td><td>-26+4</td><td>3</td><td></td><td></td><td></td><td></td></tr> <tr><td>22</td><td></td><td>376</td><td></td><td></td><td>20</td><td>67</td><td>32</td><td></td><td></td><td>61</td><td>16+1</td><td>-27+4</td><td></td><td></td><td></td><td></td><td></td></tr> <tr><td>23</td><td></td><td>377</td><td></td><td></td><td>20</td><td>67</td><td>33</td><td></td><td></td><td>65</td><td>17+1</td><td>-28+4</td><td></td><td></td><td></td><td></td><td></td></tr> <tr><td>24</td><td></td><td>378</td><td></td><td></td><td>20</td><td>67</td><td>34</td><td></td><td></td><td>69</td><td>18+1</td><td>-29+4</td><td></td><td></td><td></td><td></td><td></td></tr> <tr><td>25</td><td></td><td>379</td><td></td><td></td><td>20</td><td>67</td><td>35</td><td></td><td></td><td>73</td><td>19+1</td><td>-30+4</td><td></td><td></td><td></td><td></td><td></td></tr> <tr><td>26</td><td></td><td>380</td><td></td><td></td><td>20</td><td>67</td><td>36</td><td></td><td></td><td>77</td><td>20+1</td><td>-31+4</td><td>4</td><td>Recorder at SP. 31</td><td></td><td></td><td></td></tr> <tr><td>27</td><td></td><td>381</td><td></td><td></td><td>20</td><td>67</td><td>37</td><td></td><td></td><td>81</td><td>21+1</td><td>-32+4</td><td></td><td></td><td></td><td></td><td></td></tr> <tr><td>28</td><td></td><td>382</td><td></td><td></td><td>20</td><td>67</td><td>38</td><td></td><td></td><td>85</td><td>22+1</td><td>-33+4</td><td></td><td></td><td></td><td></td><td></td></tr> <tr><td>29</td><td></td><td>383</td><td></td><td></td><td>20</td><td>67</td><td>39</td><td></td><td></td><td>89</td><td>23+1</td><td>-34+4</td><td></td><td></td><td></td><td></td><td></td></tr> <tr><td>30</td><td></td><td>384</td><td></td><td></td><td>20</td><td>67</td><td>40</td><td></td><td></td><td>93</td><td>24+1</td><td>-35+4</td><td></td><td></td><td></td><td></td><td></td></tr> <tr><td>31</td><td></td><td>385</td><td></td><td></td><td>20</td><td>67</td><td>41</td><td></td><td></td><td>97</td><td>25+1</td><td>-36+4</td><td></td><td></td><td></td><td></td><td></td></tr> <tr><td>32</td><td></td><td>386</td><td></td><td></td><td>20</td><td>67</td><td>42</td><td></td><td></td><td>101</td><td>26+1</td><td>-37+4</td><td></td><td></td><td></td><td></td><td></td></tr> <tr><td>33</td><td></td><td>387</td><td></td><td></td><td>20</td><td>67</td><td>43</td><td></td><td></td><td>105</td><td>27+1</td><td>-38+4</td><td></td><td></td><td></td><td></td><td></td></tr> <tr><td>34</td><td></td><td>388</td><td></td><td></td><td>20</td><td>67</td><td>44</td><td></td><td></td><td>109</td><td>28+1</td><td>-39+4</td><td></td><td></td><td></td><td></td><td></td></tr> <tr><td>35</td><td></td><td>389</td><td></td><td></td><td>20</td><td>67</td><td>45</td><td></td><td></td><td>113</td><td>29+1</td><td>-40+4</td><td></td><td></td><td></td><td></td><td></td></tr> <tr><td>36</td><td></td><td>390</td><td></td><td></td><td>20</td><td>67</td><td>46</td><td></td><td></td><td>117</td><td>30+1</td><td>-41+4</td><td></td><td></td><td></td><td></td><td></td></tr> <tr><td>37</td><td></td><td>391</td><td></td><td></td><td>20</td><td>67</td><td>47</td><td></td><td></td><td>121</td><td>31+1</td><td>-42+4</td><td></td><td></td><td></td><td></td><td></td></tr> <tr><td>38</td><td></td><td>392</td><td></td><td></td><td>20</td><td>67</td><td>48</td><td></td><td></td><td>125</td><td>32+1</td><td>-43+4</td><td></td><td></td><td></td><td></td><td></td></tr> <tr><td>39</td><td></td><td>393</td><td></td><td></td><td>20</td><td>67</td><td>49</td><td></td><td></td><td>129</td><td>33+1</td><td>-44+4</td><td>5</td><td>Recorder at SP. 44 + 2 pins</td><td></td><td></td><td></td></tr> <tr><td>40</td><td></td><td>394</td><td></td><td></td><td>20</td><td>67</td><td>50</td><td></td><td></td><td>133</td><td>34+1</td><td>-45+4</td><td></td><td></td><td></td><td></td><td></td></tr> </tbody> </table>																		SHOTPOINT	TR 1 to 48		TR 49 to 96		SHOT				SPREAD				REMARKS	CORR STACK				REEL NO.	REC.	REEL NO.	REC.	SIZE	DEPTH	NO.	OFFSET	DIR.	CDP SWITCH	LINE GROUPS		OFF	TR 1	TR 2	TR 3	TR 4	21	3519	375			20	67	31			57	15+1	-26+4	3					22		376			20	67	32			61	16+1	-27+4						23		377			20	67	33			65	17+1	-28+4						24		378			20	67	34			69	18+1	-29+4						25		379			20	67	35			73	19+1	-30+4						26		380			20	67	36			77	20+1	-31+4	4	Recorder at SP. 31				27		381			20	67	37			81	21+1	-32+4						28		382			20	67	38			85	22+1	-33+4						29		383			20	67	39			89	23+1	-34+4						30		384			20	67	40			93	24+1	-35+4						31		385			20	67	41			97	25+1	-36+4						32		386			20	67	42			101	26+1	-37+4						33		387			20	67	43			105	27+1	-38+4						34		388			20	67	44			109	28+1	-39+4						35		389			20	67	45			113	29+1	-40+4						36		390			20	67	46			117	30+1	-41+4						37		391			20	67	47			121	31+1	-42+4						38		392			20	67	48			125	32+1	-43+4						39		393			20	67	49			129	33+1	-44+4	5	Recorder at SP. 44 + 2 pins				40		394			20	67	50			133	34+1	-45+4					
SHOTPOINT	TR 1 to 48		TR 49 to 96		SHOT				SPREAD				REMARKS	CORR STACK																																																																																																																																																																																																																																																																																																																																																																																																														
	REEL NO.	REC.	REEL NO.	REC.	SIZE	DEPTH	NO.	OFFSET	DIR.	CDP SWITCH	LINE GROUPS			OFF	TR 1	TR 2	TR 3	TR 4																																																																																																																																																																																																																																																																																																																																																																																																										
21	3519	375			20	67	31			57	15+1	-26+4	3																																																																																																																																																																																																																																																																																																																																																																																																															
22		376			20	67	32			61	16+1	-27+4																																																																																																																																																																																																																																																																																																																																																																																																																
23		377			20	67	33			65	17+1	-28+4																																																																																																																																																																																																																																																																																																																																																																																																																
24		378			20	67	34			69	18+1	-29+4																																																																																																																																																																																																																																																																																																																																																																																																																
25		379			20	67	35			73	19+1	-30+4																																																																																																																																																																																																																																																																																																																																																																																																																
26		380			20	67	36			77	20+1	-31+4	4	Recorder at SP. 31																																																																																																																																																																																																																																																																																																																																																																																																														
27		381			20	67	37			81	21+1	-32+4																																																																																																																																																																																																																																																																																																																																																																																																																
28		382			20	67	38			85	22+1	-33+4																																																																																																																																																																																																																																																																																																																																																																																																																
29		383			20	67	39			89	23+1	-34+4																																																																																																																																																																																																																																																																																																																																																																																																																
30		384			20	67	40			93	24+1	-35+4																																																																																																																																																																																																																																																																																																																																																																																																																
31		385			20	67	41			97	25+1	-36+4																																																																																																																																																																																																																																																																																																																																																																																																																
32		386			20	67	42			101	26+1	-37+4																																																																																																																																																																																																																																																																																																																																																																																																																
33		387			20	67	43			105	27+1	-38+4																																																																																																																																																																																																																																																																																																																																																																																																																
34		388			20	67	44			109	28+1	-39+4																																																																																																																																																																																																																																																																																																																																																																																																																
35		389			20	67	45			113	29+1	-40+4																																																																																																																																																																																																																																																																																																																																																																																																																
36		390			20	67	46			117	30+1	-41+4																																																																																																																																																																																																																																																																																																																																																																																																																
37		391			20	67	47			121	31+1	-42+4																																																																																																																																																																																																																																																																																																																																																																																																																
38		392			20	67	48			125	32+1	-43+4																																																																																																																																																																																																																																																																																																																																																																																																																
39		393			20	67	49			129	33+1	-44+4	5	Recorder at SP. 44 + 2 pins																																																																																																																																																																																																																																																																																																																																																																																																														
40		394			20	67	50			133	34+1	-45+4																																																																																																																																																																																																																																																																																																																																																																																																																

# LAND SEISMIC RECORDING LOG



CLIENT: <b>MUSKY</b>		PROSPECT: <b>NPR-4</b>		AREA: <b>BARROW / ALASKA</b>		LINE NO: <b>670</b>							
PARTY NO: <b>1182</b>		INST ENG: <b>STREFF - WINDHAM</b>		DATE: <b>MO 4 DAY 8 YR 77</b>		TRACK: <input checked="" type="checkbox"/> 1 TRACK <input type="checkbox"/> 2 TRACK		FORMAT: <b>B</b>		GAPPED: <input type="checkbox"/> GAPPED <input type="checkbox"/> UNGAPPED		PACKING DENSITY: (10) <input type="checkbox"/> 336 BPI (M) <input type="checkbox"/> 712 BPI (11) <input type="checkbox"/> 800 BPI	
INSTRUMENT (9 TRACK): <input checked="" type="checkbox"/> 1 SYSTEM <input type="checkbox"/> 2 SYSTEMS		NO BYTES IN HEADER REC: <input type="checkbox"/> 1-24 & 29-48 <input type="checkbox"/> 1-48 & 49-96		NO BYTES IN RECORD IO: <input type="checkbox"/> 134		RECORD NUMBERS: <input checked="" type="checkbox"/> DEC <input type="checkbox"/> OCT		GAIN CONSTANT: <b>36</b>		INPUT IMPEDANCE: <b>30,000</b> ohms		(1) <input type="checkbox"/> (2) <input type="checkbox"/> (3) <input type="checkbox"/> (4) <input type="checkbox"/> (5) <input type="checkbox"/> (6) <input type="checkbox"/> (7) <input type="checkbox"/> (8) <input type="checkbox"/> (9) <input type="checkbox"/> (10) <input type="checkbox"/> (11) <input type="checkbox"/> (12) <input type="checkbox"/>	
CONFIGURATION (MAG TAPE):		FIELD TRACE NOS: <b>1-48</b>		DATA CHANNEL NOS: <b>1-48</b> (ON MAG TAPE)		AUXILIARY DATA:		AUXILIARY CHANNEL NOS: <b>3 4</b>		FILTERS:		LO CUT: <b>18</b> HI CUT: <b>128</b> INDIC. FILTER: <input type="checkbox"/> IN <input type="checkbox"/> OUT	
PARAMETER:		RECORD LENGTH: <b>6</b> sec.		SAMPLE RATE: <input type="checkbox"/> 1 sec <input type="checkbox"/> 4 sec <input type="checkbox"/> 7 sec		GAIN MODE: <input type="checkbox"/> INITIAL <input type="checkbox"/> FINAL <input type="checkbox"/> MANUAL <input type="checkbox"/> OPERATE		POLARITY CONVENTION:		PRESSURE INCREASE ON GEOPHONE: <input type="checkbox"/> NEGATIVE <input type="checkbox"/> POSITIVE		NUMBERS ON MAG TAPE: <input type="checkbox"/> DOWNBREAK <input type="checkbox"/> UPBREAK ON DISPLAY	
DISPLAY:		MODE: <input type="checkbox"/> AGC <input type="checkbox"/> FLOAT <input type="checkbox"/> DEFOAT <input type="checkbox"/> AMPLIFIER <input type="checkbox"/> DIRECT		INITIAL GAIN: <b>18</b> db		STRIP SENS: <b>18</b> db		NOISE REDUCTION:		CORE SCALING:		B.C.U. NORM/ALT SW	
CFS I:		TYPE STACK:		GATE LENGTH:		RECORD REJECTION:		STAGGER:		LENGTH:		WIDTH:	
SOURCE:		TYPE: <input checked="" type="checkbox"/> DYNAMITE <input type="checkbox"/> VIBRATORS <input type="checkbox"/> OTHER		PATTERN: <b>Single Hole - inline</b>		NO. OF POSITIONS:		INLINE SPACING:		LATERAL SPACING:		SWEEP:	
RECEIVER:		TYPE: <b>GSC-20 D</b>		PATTERN: <b>inline</b>		SWEEP START:		SWEEP END:		SWEEP LENGTH:		SWEEP TAPER:	
CONNECTION: <b>Series parallel</b>		RESISTANCE: <b>560 ohms</b>		STAGGER:		NO. OF ELEMENTS: <b>18</b>		INLINE SPACING: <b>12'</b>		LATERAL SPACING:		LATERAL OFFSET:	
NO. OF GROUPS: <b>48</b>		GROUP INTERVAL: <b>220'</b>		SHOTPOINT INTERVAL: <b>880'</b>		FOLD: <b>6</b>		DIRECTION OF PROGRESSION: <b>N → S</b>		LEADING GROUP: <b>48</b>		OFFSET GROUP:	
SPREAD:		OFFSET GROUP 1: <b>5170'</b>		OFFSET GROUP 24: <b>110'</b>		OFFSET GROUP 25: <b>110'</b>		OFFSET GROUP 48/90: <b>5170'</b>		LEADING GROUP:		OFFSET GROUP:	

DIAGRAMS/MISC. INFORMATION:

SHOTPOINT	TR 1 - 48		TR 2 - 96		SHOT		SPREAD		CDP SWITCH	LINE GROUPS	REMARKS	CORR STACK		
	REEL NO	REC	REEL NO	REC	SIZE	DEPTH	NO.	OFFSET				TR 1	TR 2	TR 3
41	351925	397			20	67	51		35	35+1 - 46+4	5			
42		398			20	67	52		39	36+1 - 47+4				
43		399			20	67	53		43	37+1 - 48+4				
44		400			20	67	54		47	38+1 - 49+4		44+4 Dead fence		
45		401			20	67	55		51	39+1 - 50+4				
46		402			20	67	56		55	40+1 - 51+4				
47		403			20	67	57		59	41+1 - 52+4				
48		404			20	67	58		63	42+1 - 53+4				
49		405			20	67	59		67	43+1 - 54+4				
50		406			20	67	60		71	44+1 - 55+4				

# LAND SEISMIC RECORDING LOG

14 Hours

	CLIENT: <b>Husky</b>	PROSPECT: <b>NPRA</b>	AREA: <b>BARROW</b>	LINE NO: <b>670</b>					
	PARTY NO: <b>1192</b>	INST. ENG: <b>Streff-Windham</b>		DATE: <b>4 DAY 9 YE 79</b>					
INSTRUMENT (9-TRACK)	<input type="checkbox"/> 1 SYSTEM <input type="checkbox"/> 2 SYSTEMS	<input type="checkbox"/> 1-24 & 25-48 <input type="checkbox"/> 1-48 & 49-96	EVENTS	TYPE: <input type="checkbox"/> DFS <input type="checkbox"/> DFS II <input type="checkbox"/> DFS III <input type="checkbox"/> OTHER	<input type="checkbox"/> 9 TRACK <input type="checkbox"/> 21 TRACK	FORMAT: <b>B</b>	<input type="checkbox"/> GAPPED <input type="checkbox"/> UNGAPPED	PACKING DENSITY: (1) <input type="checkbox"/> 350 BPI (11) <input type="checkbox"/> 712 BPI	(2) <input type="checkbox"/> 800 BPI (12) <input type="checkbox"/> 1000 BPI
CONFIGURATION (MAG TAPE)	FIELD TRACE NOS: <b>1-48</b>	NO. BYTES IN HEADER REC:	NO. BYTES IN RECORD ID:	NO. BYTES PER SCAN: <b>134</b>	RECORD NUMBERS: <input checked="" type="checkbox"/> DEC <input type="checkbox"/> OCT	GAIN CONSTANT: <b>3.6</b>	dB	INPUT IMPEDANCE: <b>20,000</b>	ohms
PARAMETER	RECORD LENGTH: <b>6</b>	SAMPLE RATE: <input type="checkbox"/> 1 sec <input type="checkbox"/> 4 sec	GAIN MODE: <input checked="" type="checkbox"/> OFF	<input type="checkbox"/> INITIAL <input type="checkbox"/> MANUAL <input type="checkbox"/> OPERATE	FILTERS: <b>8</b>	LO CUT: <b>18</b>	HI CUT: <b>120</b>	NI CUT: <b>70</b>	NOTCH FILTER: <input type="checkbox"/> IN <input type="checkbox"/> OUT
DISPLAY	<input type="checkbox"/> AGC <input type="checkbox"/> DEFLAT <input type="checkbox"/> DIRECT	INITIAL GAIN: <b>18</b>	TRIP SENS: <b>18</b>	dB	POLARITY CONVENTION	PRESSURE INCREASE ON GEOPHONE: <input type="checkbox"/> NEGATIVE <input type="checkbox"/> POSITIVE	NUMBERS ON MAG TAPE	<input type="checkbox"/> DOWNBREAK <input type="checkbox"/> UPBREAK	ON DISPLAY
CFS I	TYPE STACK:	GATE LENGTH:	RECORD REJECTION:	NOISE REDUCTION:	NOISE THRESHOLD:	CORR. SCALING:	P.C. U. NORM/ALT SW		
SOURCE	TYPE: <input checked="" type="checkbox"/> DYNAMIC <input type="checkbox"/> VIBROSEIS <input type="checkbox"/> OTHER	PATTERN: <b>Single hole - inline</b>	NO. OF POSITIONS:	INLINE SPACING:	LATERAL SPACING:	STAGGER:	LENGTH:	WIDTH:	LATERAL OFFSET:
RECEIVER	TYPE: <b>GSC-20d</b>	PATTERN: <b>IN LINE</b>	NO. OF ELEMENTS: <b>18</b>	INLINE SPACING: <b>12'</b>	LATERAL SPACING:	STAGGER:	LENGTH:	WIDTH:	LATERAL OFFSET:
SPREAD	CONNECTION: <b>Series-Parallel</b>	RESISTANCE: <b>56</b>	STAGGER:	LENGTH:	WIDTH:	LATERAL OFFSET:	NO. OF GROUPS: <b>48</b>		
	GROUP INTERVAL: <b>220'</b>	SHOTPOINT INTERVAL: <b>880'</b>	FOUR: <b>6</b>	DIRECTION OF PROGRESSION: <b>N-S</b>	LEADING GROUP: <b>44</b>	OFFSET GROUP 1: <b>5170'</b>			
	OFFSET GROUP 24: <b>110'</b>	OFFSET GROUP 25: <b>110'</b>	OFFSET GROUP 48: <b>5170'</b>	DIAGRAMS/MISC. INFORMATION: <b>SP5 46</b>					

SHOTPOINT	TR 1 to 48		TR 49 to 96		SHOT		SPREAD		REMARKS	
	REEL NO	REC	REEL NO	REC	SIZE	DEPTH	NO.	OFFSET		
51	7511	1026			20	167	13	37	27 45+1 - 56+4	1 Recorder @ SP-5612/5613
52		1411			20	167	12	31	46+1 - 57+4	430 N.G.
53		4123			20	167	12	35	47+1 - 58+4	
54		4124			20	167	14	39	48+1 - 59+4	(H 42) N.G.
55		4125			20	167	15	43	49+1 - 60+4	
56		4126			20	167	16	17	50+1 - 61+4	2 (H 42) N.G. Recorder @ SP-64
57		4128			20	167	17	21	51+1 - 62+4	
58		4129			20	167	18	25	52+1 - 63+4	
59		4130			20	167	19	29	53+1 - 64+4	
60		4131			20	167	20	33	54+1 - 65+4	
61		4132			20	167	21	37	55+1 - 66+4	
62		4133			20	167	22	41	56+1 - 67+4	
63		4134			20	167	23	45	57+1 - 68+4	
64		4135			20	167	24	49	58+1 - 69+4	
65		4136			20	167	25	53	59+1 - 70+4	
66		4137			20	167	26	57	60+1 - 71+4	
67		4139			20	167	27	61	61+1 - 72+4	4138 - N.G.
68		4140			20	167	28	65	62+1 - 73+4	
69		4141			20	167	29	69	63+1 - 74+4	
70		4142			20	167	30	73	64+1 - 75+4	

# 418 test 175+4  
# 417 test 4

# LAND SEISMIC RECORDING LOG

CLIENT: <u>Husky</u>		PROSPECT: <u>NPA-1</u>		AREA: <u>Barrow</u>		LINE NO: <u>670</u>													
PARTY NO: <u>1182</u>		INST. ENG: <u>Staff-William</u>		DATE: <u>NO 4 DAY 9 YE 77</u>															
INSTRUMENT (9-TRACK) <input type="checkbox"/> 1 SYSTEM <input type="checkbox"/> 2 SYSTEMS <input type="checkbox"/> T-24 & 25-48 <input type="checkbox"/> 1-48 & 49-96 NO BYTES IN HEADER REC: _____		TYPE <input type="checkbox"/> DFS III <input type="checkbox"/> DFS IV <input type="checkbox"/> DFS V <input type="checkbox"/> OTHER		TRACKS <input type="checkbox"/> 1 TRACK <input type="checkbox"/> 2 TRACK		FORMAT SEG <u>11</u>		GAPPED <input type="checkbox"/> GAPPED <input type="checkbox"/> UNGAPPED		PACKING DENSITY: _____ LLO: <input type="checkbox"/> 356 BPI <input type="checkbox"/> 800 BPI (HI) <input type="checkbox"/> 712 BPI <input type="checkbox"/> 1060 BPI									
CONFIGURATION (MAG TAPE) FIELD TRACE NOS: <u>1-48</u> DATA CHANNEL NOS: <u>1-48</u> (ON MAG TAPE)		NO BYTES IN RECORD ID: _____		NO BYTES PER SCAN: <u>174</u>		RECORD NUMBERS: <input type="checkbox"/> DEC <input type="checkbox"/> OCT		GAIN CONSTANT: <u>36</u> db		INPUT IMPEDANCE: <u>200</u> ohms									
PARAMETER RECORD LENGTH: <u>6</u> sec		SAMPLE RATE: <input type="checkbox"/> 1 ms <input checked="" type="checkbox"/> 2 ms <input type="checkbox"/> 4 ms		GAIN MODE: <input type="checkbox"/> INITIAL <input type="checkbox"/> FINAL <input type="checkbox"/> MANUAL <input type="checkbox"/> OPERATE		FILTERS: FREQ <u>2</u> LO CUT HZ SLOPE <u>18</u>		HI CUT HZ SLOPE <u>70</u>		NOTCH FILTER: <input type="checkbox"/> IN <input type="checkbox"/> OUT									
DISPLAY MODE: <input type="checkbox"/> AGC <input type="checkbox"/> FLOAT <input type="checkbox"/> DIRECT		INITIAL GAIN: <u>18</u> db		TRIP SENS: <u>0</u> db		POLARITY CONVENTION <input type="checkbox"/> POSITIVE <input type="checkbox"/> NEGATIVE		PRESSURE INCREASE ON GEOPHONE		NUMBERS ON MAG TAPE <input type="checkbox"/> UPBLK <input type="checkbox"/> DOWNBLK ON DISPLAY									
CFS I TYPE STACK: _____		GATE LENGTH: _____		RECORD REJECTION: _____		NOISE REDUCTION: _____		NOISE THRESHOLD: _____		CORR SCALING: _____ P.C.U. NORM. ALT SW									
SOURCE TYPE: <input type="checkbox"/> DYNAMITE <input type="checkbox"/> VIBROSEIS <input type="checkbox"/> OTHER		PATTERN: <u>1/2 line - 1 hole</u>		NO. OF POSITIONS: _____		INLINE SPACING: _____		LATERAL SPACING: _____		STAGGER: _____ LENGTH: _____ WIDTH: _____ LATERAL OFFSET: _____									
RECEIVER TYPE: <u>20-D</u>		PATTERN: <u>1/2 line</u>		NO. OF ELEMENTS: <u>18</u>		INLINE SPACING: <u>12</u>		LATERAL SPACING: _____		CONNECTION: <u>Series-parallel</u>		RESISTANCE: <u>500</u> ohms		STAGGER: _____ LENGTH: _____ WIDTH: _____ LATERAL OFFSET: _____					
SPREAD NO. OF GROUPS: <u>48</u>		GROUP INTERVAL: <u>220</u>		SHOTPOINT INTERVAL: <u>880</u>		FOLD: <u>6</u>		DIRECTION OF PROGRESSION: <u>SOUTH</u>		OFFSET GROUP 1: <u>5170</u>		OFFSET GROUP 24: <u>16</u>		OFFSET GROUP 25: <u>110</u>		OFFSET GROUP 48/96: <u>5170</u>		LEADING GROUP: <u>48</u>	

DIAGRAMS/MISC. INFORMATION:

SHOTPOINT	TR _____ to _____		TR _____ to _____		SHOT			SPREAD				REMARKS	CORR STACK					
	REEL NO.	REC.	REEL NO.	REC.	SIZE	DEPTH	NO.	OFFSET	DIR	COP SWITCH	LINE GROUPS			TR 1-24	TR 25-48	TR 49-72	TR 73-96	
171	15119	25	14413		20	167	21		27		65+1	-	76+4	3	Recorder @ SP 7712/7713			
172			14414		20	167	22		27		66+1	-	77+4					
173			14415		20	167	23		31		67+1	-	78+4					
174			14416		20	167	24		35		68+1	-	79+4					
175			14417		20	167	25		39		69+1	-	80+4					
176			14418		20	167	26		43		70+1	-	T.4					
177			14419		20	167	27		47		71+1	-	T.8					
178			14420		20	167	28		33		72+1	-	T.12					
179			14421		20	167	29		37		73+1	-	T.16					
180			14422		20	167	30		41		74+1	-	T.20					
181			14423		20	167	31		45		75+1	-	T.24					
<div style="font-size: 2em; font-weight: bold; margin-top: 50px;">E.O.B</div>																		