



ANN'S - PI

LAND SEISMIC RECORDING LOG

Recording No. 14.5



	CLIENT: <u>HUSKY</u>	PROSPECT: <u>NPR-A</u>	AREA: <u>BALLOU</u>	LINE NO: <u>672</u>		
	PARTY NO: <u>1182</u>	INST ENG: <u>Stieff</u>		DATE: <u>MO 4 DAY 25 YR 79</u>		
INSTRUMENT	<input type="checkbox"/> 1 SYSTEM <input type="checkbox"/> 2 SYSTEMS <input type="checkbox"/> 1-24 & 25-48 <input type="checkbox"/> 1-48 & 49-96	<input type="checkbox"/> ODDS <input type="checkbox"/> EVENS	TYPE: <input type="checkbox"/> DES III <input type="checkbox"/> DES II <input type="checkbox"/> OTHER	<input type="checkbox"/> 1 TRACK <input type="checkbox"/> 2 TRACKS	FORMAT: <u>B</u> <input type="checkbox"/> GAPPED <input type="checkbox"/> UNGAPPED	PACKING DENSITY: (10) <input type="checkbox"/> 358 BPI <input type="checkbox"/> 800 BPI (14) <input type="checkbox"/> 712 BPI <input type="checkbox"/> 7600 BPI
(9 TRACK)	NO BYTES IN HEADER REC.	NO BYTES IN RECORD ID.	NO BYTES PER SCAN: <u>134</u>	RECORD NUMBERS: <input type="checkbox"/> DEC. <input type="checkbox"/> OCT	GAIN CONSTANT: <u>36</u> db	INPUT IMPEDANCE: <u>20K</u> ohms
CONFIGURATION (MAG TAPE)	FIELD TRACE NOS: <u>1-48</u>	DATA CHANNEL NOS: <u>1-48</u>	(ON MAG TAPE)	AUXILIARY DATA:	(11) (12) (13) (14) (15) (16) (17)	
PARAMETER	RECORD LENGTH: <u>6</u> sec	SAMPLE RATE: <input type="checkbox"/> 1 ms <input type="checkbox"/> 4 ms <input type="checkbox"/> 2 ms <input type="checkbox"/> 8 ms	GAIN MODE: <input type="checkbox"/> INITIAL <input type="checkbox"/> FINAL <input type="checkbox"/> OFF <input type="checkbox"/> OPERATE	FILTERS:	LO CUT: <u>18</u> Hz	HI CUT: <u>70</u> Hz
DISPLAY	MODE: <input type="checkbox"/> FLOAT <input type="checkbox"/> AMPLIFIER <input type="checkbox"/> DIRECT <input type="checkbox"/> DE FLOAT	INITIAL GAIN: <u>12</u> db	TRIP SENS: <u>0</u> db	POLARITY CONVENTION:	NEGATIVE <input type="checkbox"/> POSITIVE <input type="checkbox"/>	NUMBERS ON MAG TAPE: <input type="checkbox"/> DOWNPEAK <input type="checkbox"/> UPPEAK
CFS I	TYPE: <input type="checkbox"/> DYNAMIFF <input type="checkbox"/> VIBROSEIS <input type="checkbox"/> OTHER	PATTERN: <u>inline-base</u>	NO. OF POSITIONS:	INLINE SPACING:	LATERAL SPACING:	STAGGER:
SOURCE	CHG/NOLE: <u>20</u>	HOLE DEPTH: <u>75</u>	SWEEP POSITION:	SWEEP START:	SWEEP END:	SWEEP LENGTH:
RECEIVER	TYPE: <u>20-P</u>	PATTERN: <u>inline</u>	NO. OF ELEMENTS: <u>18</u>	INLINE SPACING: <u>12</u>	LATERAL SPACING:	STAGGER:
SPREAD	CONNECTION: <u>series-parallel</u>	RESISTANCE: <u>560</u> ohms	STAGGER:	LENGTH:	WIDTH:	LATERAL OFFSET:
	NO. OF GROUPS: <u>48</u>	GROUP INTERVAL: <u>220</u>	SHOTPOINT INTERVAL: <u>870</u>	FOLO: <u>6</u>	DIRECTION OF PROGRESSION: <u>South</u>	
	OFFSET GROUP 1: <u>5170</u>	OFFSET GROUP 24: <u>110</u>	OFFSET GROUP 95: <u>110</u>	OFFSET GROUP 48/96: <u>5170</u>	LEADING GROUP: <u>48</u>	

DIAGRAMS/MISC. INFORMATION:
 T-X 7.25 5' X 11 6' X

SHOTPOINT	TR 1		TR 2		SHOT		SPREAD		REMARKS	CORR. STACK					
	REEL NO.	REC.	REEL NO.	REC.	SIZE	DEPTH	NO.	OFFSET		DIR.	CDP SWITCH	LINE GROUPS	TR 1	TR 2	TR 3
1	751	1940	2164		20	167	23	31	T.1 - 6+4	1	Recorder @ 512/513				
2			2168		20	167	24	35	T.5 - 7+4						
3			2166		20	167	25	39	T.9 - 8+4						
4			2167		20	167	26	43	T.13 - 9+4						
5			2168		20	167	27	47	T.17 - 10+4						
6			2167		20	167	28	51	T.21 - 11+4						
7			2170		20	167	29	55	1+1 - 12+4						
8			2171		20	167	30	59	1+1 - 13+4						
9			2172		20	167	31	63	3+1 - 14+4						
10			2173		20	167	32	67	4+1 - 15+4						
11			2174		20	167	33	71	5+1 - 16+4						
12			2175		20	167	34	75	6+1 - 17+4						
13			2176		20	167	35	79	7+1 - 18+4						
14			2177		20	167	36	83	8+1 - 19+4						
15			2178		20	167	37	87	9+1 - 20+4						
16			2179		20	167	38	19	10+1 - 21+4	2	Recorder @ 2312/2313				
17			2180		20	167	39	23	11+1 - 22+4						
18			2181		20	167	40	27	12+1 - 23+4						
19			2182		20	167	41	31	13+1 - 24+4						
20			2183		20	167	42	35	14+1 - 25+4						

COR-ERROR

LAND SEISMIC RECORDING LOG

	CLIENT: <u>Husky</u>	PROSPECT: <u>NRA-A</u>	AREA: <u>Baton</u>	LINE NO: <u>672</u>					
	PARTY NO: <u>1182</u>	INST. ENG: <u>Shiff</u>		DATE: <u>MO 4 DAY 21 - 1978</u>					
INSTRUMENT [9-TRACK]	<input type="checkbox"/> 1 SYSTEM <input type="checkbox"/> 2 SYSTEMS <input type="checkbox"/> 1-24 & 25-48 <input type="checkbox"/> 1-48 & 49-96	<input type="checkbox"/> ODD <input type="checkbox"/> EVENS	TYPE: <input type="checkbox"/> DFS III <input type="checkbox"/> DFS IV <input type="checkbox"/> OTHER	<input type="checkbox"/> 7 TRACK <input type="checkbox"/> 21 TRACK	FORMAT: <u>B</u>	<input type="checkbox"/> GAPPED <input type="checkbox"/> UNGAPPED	PACKING DENSITY: (L) <input type="checkbox"/> 226 BPI <input type="checkbox"/> 800 BPI	(H) <input type="checkbox"/> 772 BPI <input type="checkbox"/> 1000 BPI	
	NO. BYTES IN HEADER REC.	NO. BYTES IN RECORD ID	NO. BYTES PER SCAN: <u>134</u>	RECORD NUMBERS: <input type="checkbox"/> DEC <input type="checkbox"/> OCT	GAIN CONSTANT: <u>36</u>	INPUT IMPEDANCE: <u>200</u> ohms			
CONFIGURATION (MAG TAPE)	FIELD TRACE NOS: <u>1-78</u>	DATA CHANNEL NOS: <u>1-48</u> (ON MAG TAPE)		AUXILIARY DATA: (1) (2) (3) (4) (5) (6) (7)					
PARAMETER	RECORD LENGTH: <u>6</u> sec	SAMPLE RATE: <input type="checkbox"/> 1 sec <input type="checkbox"/> 4 sec <input type="checkbox"/> 2 mil <input type="checkbox"/> 4 mil	GAIN MODE: <input type="checkbox"/> INITIAL <input type="checkbox"/> FINAL <input type="checkbox"/> OPERATE	FILTERS: FREQ <u>1</u>	LO CUT HZ SLOPE <u>18</u>	HI CUT HZ SLOPE <u>70</u>	INDIC. FILTER: <input type="checkbox"/> IN <input type="checkbox"/> OUT		
DISPLAY	MODE: <input type="checkbox"/> FLOAT <input type="checkbox"/> AMPLIFIER <input type="checkbox"/> DIRECT	INITIAL GAIN: <u>18</u> dB	TRIP SENS: <u>0</u> dB	POLARITY CONVENTION: <input type="checkbox"/> NEGATIVE <input type="checkbox"/> POSITIVE	PRESSURE INCREASE ON DEEPHONE: <input type="checkbox"/> NEGATIVE <input type="checkbox"/> POSITIVE	NUMBERS ON MAG TAPE: <input type="checkbox"/> DOWNBEAR <input type="checkbox"/> UPBREAK		ON DISPLAY	
CFS I	TYPE STACK:	GATE LENGTH:	RECORD REJECTION:	NOISE REDUCTION:	NOISE THRESHOLD:	CORR. SCALING:	P.C.U. NORM./ALT SW		
SOURCE	TYPE: <input type="checkbox"/> DYNAMITE <input type="checkbox"/> VIBROSEIS <input type="checkbox"/> OTHER	PATTERN: <u>inline-hole</u>	NO. OF POSITIONS:	INLINE SPACING:	LATERAL SPACING:	STAGGER:	LENGTH:	WIDTH:	LATERAL OFFSET:
RECEIVER	TYPE: <u>20-P</u>	PATTERN: <u>12' inc</u>	NO. OF ELEMENTS: <u>18</u>	INLINE SPACING: <u>12</u>	LATERAL SPACING:	STAGGER:	LENGTH:	WIDTH:	LATERAL OFFSET:
SPREAD	CONNECTION: <u>Series-Parallel</u>	RESISTANCE: <u>500</u> ohms	STAGGER:	LENGTH:	WIDTH:	LATERAL OFFSET:	DIRECTION OF PROGRESSION: <u>SOUTH</u>		
	NO. OF GROUPS: <u>12</u>	GROUP INTERVAL: <u>220</u>	SHOTPOINT INTERVAL: <u>800</u>	FOLO: <u>6</u>	DIRECTION OF PROGRESSION: <u>SOUTH</u>			LEADING GROUP: <u>48</u>	
	OFFSET GROUP 1: <u>5170</u>	OFFSET GROUP 2: <u>110</u>	OFFSET GROUP 3: <u>110</u>	OFFSET GROUP 4: <u>5170</u>					


DIAGRAMS/MISC. INFORMATION

SHOTPOINT	78				79				SHOT	SPREAD	REMARKS	COM STAGE			
	REFL NO	SEC	REFL NO	SEC	SIZE	DEPTH	NO. OFFSET	DIR				CDP SWITCH	LINE GROUPS	ST	RE
21					20	167	43		37	15+1 - 26+4	2				
22					20	167	44		43	16+1 - 27+4					
23					20	167	45		47	17+1 - 28+4					
24					20	167	46		51	18+1 - 29+4					
25					20	167	47		31	19+1 - 30+4	3	Recorder @ 29+2/29+3			
26					20	167	48		35	20+1 - 31+4		#290-N.G.			
27					20	167	49		39	21+1 - 32+4					
28					20	167	50		43	22+1 - 33+4					
29					20	167	51		47	23+1 - 34+4		#294-295-N.G.			
30					20	167	52		51	24+1 - 35+4		#297-298-N.G.			
31					20	167	53		55	25+1 - 36+4		#300-N.G.			
32					20	167	54		59	26+1 - 37+4					
33					20	167	55		21	27+1 - 38+4	4	Recorder @ 50-40			
34					20	167	56		25	28+1 - 39+4		#304-N.G.			
35					20	167	57		29	29+1 - 40+4		#306-N.G.			
36					20	167	58		33	30+1 - 41+4					
37					20	167	59		37	31+1 - 42+4		#309-N.G.			
38					20	167	60		41	32+1 - 43+4					
39					20	167	61		45	33+1 - 44+4		#312-N.G.			
40					20	167	62		49	34+1 - 45+4					

LAND SEISMIC RECORDING LOG

Recording Hrs = 14.5

CLIENT: Husky		PROSPECT: NPR-A		AREA: Barrow		LINE NO.: 672	
PARTY NO.: 1172		INST. ENG.: Street		DATE: MO 4 DAY 26 YR 79			
INSTRUMENT <input type="checkbox"/> 1 SYSTEM <input checked="" type="checkbox"/> 2 SYSTEMS		TYPE <input type="checkbox"/> DIS 7E <input type="checkbox"/> DIS 7E		FORMAT: 11		PACKING DENSITY: <input type="checkbox"/> 1101 <input type="checkbox"/> 330 BPI <input type="checkbox"/> 400 BPI	
NO. BYTES IN HEADER REC		NO. BYTES IN RECORD ID		NO. BYTES PER SCAN: 134		RECORD NUMBERS: <input checked="" type="checkbox"/> DEC <input type="checkbox"/> OCT	
CONFIGURATION (MAG TAPE)		FIELD TRACE NOS.		AUXILIARY DATA		AUXILIARY CHANNEL NOS.	
PARAMETER		RECORD LENGTH: 6		SAMPLE RATE: <input type="checkbox"/> 1ms <input type="checkbox"/> 4ms		GAIN MODE: <input type="checkbox"/> INITIAL <input type="checkbox"/> MANUAL	
DISPLAY		MODE: <input type="checkbox"/> FLOAT <input type="checkbox"/> AMP/FILTER <input type="checkbox"/> DIRECT		INITIAL GAIN: 12		TRIP SENS: 0	
CFS 1		TYPE STACK:		DATE LENGTH:		RECORD REJECTION:	
SOURCE		TYPE: <input checked="" type="checkbox"/> SYMMETRIC		PATTERN: inline-hole		NO. OF POSITIONS:	
RECEIVER		TYPE: 20-0		PATTERN: inline		NO. OF ELEMENTS: 18	
SPREAD		NO. OF GROUPS: 48		GROUP INTERVAL: 220		SHOTPOINT INTERVAL: 880	



SHOTPOINT	REEL NO.		REC.		SIZE	DEPTH	SHOT NO.	OFFSET	DR.	CDF SWITCH	SPREAD		REMARKS	CORR STACK		
	1	2	1	2							LINE	GROUPS		1	2	3
145	3151	1910	12319	10	120	167	11	11		27	39+1 - 50+4	1	Recorder @ 500/5013	#333-N.G.		
146			3139		120	167	12	11		31	40+1 - 51+4					
147			3136		120	167	13	11		35	41+1 - 52+4					
148			3137		120	167	14	11		39	42+1 - 53+4					
149			3139		120	167	15	11		43	43+1 - 54+4			#338-N.G.		
150			3140		120	167	16	11		47	44+1 - 55+4					
151			3141		120	167	17	11		51	45+1 - 56+4					
152			3142		120	167	18	11		55	46+1 - 57+4			#342-N.G.		
153			3144		120	167	19	11		59	47+1 - 58+4					
154			3145		120	167	10	11		27	48+1 - 59+4	2	Recorder @ 5912/5913			
155			3147		120	167	21	11		31	49+1 - 60+4			#346-N.G.		
156			3148		120	167	12	11		35	50+1 - 61+4					
157			3149		120	167	13	11		39	51+1 - 62+4					
158			3150		120	167	14	11		43	52+1 - 63+4					
159			3152		120	167	15	11		47	53+1 - 64+4					
160			3153		120	167	16	11		51	54+1 - 65+4					
161			3154		120	167	17	11		55	55+1 - 66+4	3	Recorder @ SP-61			
162			3155		120	167	18	11		59	56+1 - 67+4					
163			3156		120	167	19	11		57	57+1 - 68+4					
164			3157		120	167	20	11		61	58+1 - 69+4					



LAND SEISMIC RECORDING LOG

	CLIENT: Husky	PROSPECT: NPA-D	AREA: Barron	LINE NO.: C72					
	PARTY NO.: 1182	INST. ENG.: S+off		DATE: 9 DAY 26 YE 78					
INSTRUMENT (9-TRACK)	<input type="checkbox"/> 1 SYSTEM <input type="checkbox"/> 2 SYSTEMS	<input type="checkbox"/> 1-24 & 25-48 <input type="checkbox"/> 1-48 & 49-96	<input type="checkbox"/> ODD <input type="checkbox"/> EVENS	TYPE: <input type="checkbox"/> DFS III <input type="checkbox"/> DFS II	<input type="checkbox"/> 1 TRACK <input type="checkbox"/> 2 TRACK	FORMAT: <input type="checkbox"/> SEG <input type="checkbox"/> GAPPED <input type="checkbox"/> UNGAPPED	PACING DENSITY: (L) <input type="checkbox"/> 328 BPM (M) <input type="checkbox"/> 800 BPM (H) <input type="checkbox"/> 712 BPM <input type="checkbox"/> 1600 BPM		
	NO. BYTES IN HEADER REC.	NO. BYTES IN RECORD ID.	NO. BYTES PER SCAN.	RECORD NUMBERS: <input type="checkbox"/> DEC <input type="checkbox"/> OCT	GAIN CONSTANT: _____ db	INPUT IMPEDANCE: _____ ohms			
CONFIGURATION (MAG TAPE)	FIELD TRACE NOS. _____ DATA CHANNEL NOS. _____		(ON MAG TAPE)	AUXILIARY DATA: _____ AUXILIARY CHANNEL NOS. _____					
PARAMETER	RECORD LENGTH: _____ sec.	SAMPLE RATE: <input type="checkbox"/> 1 ml. <input type="checkbox"/> 4 ml. <input type="checkbox"/> 2 mv. <input type="checkbox"/> _____ mv.	GAIN MODE: <input type="checkbox"/> INITIAL <input type="checkbox"/> MANUAL <input type="checkbox"/> OPERATE	FILTERS: _____	LO CUT _____ Hz	HI CUT _____ Hz	NOTCH FILTER: <input type="checkbox"/> IN <input type="checkbox"/> OUT		
DISPLAY	MODE: <input type="checkbox"/> FLOAT <input type="checkbox"/> AMPLIFIER <input type="checkbox"/> AGC <input type="checkbox"/> OFFGAIN <input type="checkbox"/> DIRECT	INITIAL GAIN: _____ db	ZIP SENS: _____ db	POLARITY CONVENTION: _____	PRESSURE INCREASE ON GEOPHONE: <input type="checkbox"/> NEGATIVE <input type="checkbox"/> POSITIVE	NUMBERS ON MAG. TAPE: <input type="checkbox"/> DOWNBREAK <input type="checkbox"/> UPBREAK	ON DISPLAY: <input type="checkbox"/> ON DISPLAY		
CFS I	TYPE: _____	GATE LENGTH: _____	RECORD REJECTION: _____	NOISE REDUCTION: _____	NOISE THRESHOLD: _____	COR. SCALING: _____	U. S. NORM. ALT SW <input type="checkbox"/>		
SOURCE	TYPE: <input type="checkbox"/> DYNAMIC <input type="checkbox"/> VIBROSLIP <input type="checkbox"/> OTHER	PATTERN: _____	NO. OF POSITIONS: _____	INLINE SPACING: _____	LATERAL SPACING: _____	STAGGER: _____	LENGTH: _____	WIDTH: _____	LATERAL OFFSET: _____
RECEIVER	TYPE: _____	PATTERN: inline	NO. OF ELEMENTS: 18	INLINE SPACING: 12	LATERAL SPACING: _____	STAGGER: _____	LENGTH: _____	WIDTH: _____	LATERAL OFFSET: _____
SPREAD	CONNECTION: 200 Series-Parallel	RESISTANCE: 50 ohms	STAGGER: _____	LENGTH: _____	WIDTH: _____	LATERAL OFFSET: _____			
	NO. OF GROUPS: 48	GROUP INTERVAL: 220	SHOTPOINT INTERVAL: 880	FOLD: 6	DIRECTION OF PROGRESSION: South	LEADING GROUP: 48			
	OFFSET GROUP: 5170	GROUP: 24	OFFSET GROUP: 110	OFFSET GROUP: 25	OFFSET GROUP: 5170				

DIAGRAMS/MISC INFORMATION:

SHOTPOINT	TA		TB		SHOT			SPREAD		REMARKS	CORR. STACK				
	FEEL NO.	REC.	FEEL NO.	REC.	SURF	DEPTH	NO.	OFFSET	DIR		CDR SWITCH	LINE GROUPS	1	2	3
185	381	184	388		20	167	41	11	55	79+1-90+4	5				#387-N.G.
186		388			20	167	42	11	59	80+1-91+4					#389-N.G.
187		391			20	167	43	100	9	81+1-92+4	6				Recorder @ SP-97
188		392			20	167	44	11	13	82+1-93+4					
189		393			20	167	45	11	17	83+1-94+4					
190		394			20	167	46	11	21	84+1-95+4					
191		395			20	167	47	11	25	85+1-96+4					
192		398			20	167	48	11	29	86+1-97+4					File # 395 on tape twice
193		398			20	167	49	11	33	87+1-98+4					
194		398			20	167	50	11	37	88+1-99+4					#397-N.G.
195		399			20	167	51	11	41	89+1-100+4					
196		400			20	167	52	11	45	90+1-101+4					
197		401			20	167	52	11	49	91+1-102+4					
198		402			20	167	54	11	53	92+1-103+4					
199		403			20	167	55	11	57	93+1-104+4					#403-404-N.G.
100		407			20	167	56	11	61	94+1-105+4					#406-N.G.
101		410			20	167	57	11	65	95+1-106+4					#408, 409
102		412			20	167	58	11	69	96+1-107+4					
103		414			20	167	59	11	73	97+1-108+4					
104		415			20	167	60	11	77	98+1-109+4					D.F.S. Quit Recording at 1 sec.

LAND SEISMIC RECORDING LOG

	CLIENT: Husky	PROSPECT: NPR-A	AREA: Barrow	LINE NO: 672		
	PART NO: 1183	INST ENG: Streff		DATE: MO 4 DAY 26 YR 79		
INSTRUMENT (0 TRACK)	<input type="checkbox"/> 1 SYSTEM <input type="checkbox"/> 2 SYSTEMS	<input type="checkbox"/> 24 & 25-48 <input type="checkbox"/> 48 & 49-96	TYPE <input type="checkbox"/> DFS III <input type="checkbox"/> DFS II	<input type="checkbox"/> 9 TRACK <input type="checkbox"/> 21 TRACK	<input type="checkbox"/> GAPPED <input type="checkbox"/> UNGAPPED	PACKING DENSITY: (L) <input type="checkbox"/> 354 BPI <input type="checkbox"/> 800 BPI
	NO BYTES IN HEADER REC.	NO BYTES IN RECORD ID.	NO BYTES REP SCAN: 134	RECORD NUMBERS: <input type="checkbox"/> DEC <input type="checkbox"/> OCT	GAIN CONSTANT: 36	INPUT IMPEDANCE: 20k
CONFIGURATION (MAG TAPE)	FIELD TRACE NOS: 1-48	DATA CHANNEL NOS: 1-48	AUXILIARY DATA:			
PARAMETER	RECORD LENGTH: 6	SAMPLE RATE: <input type="checkbox"/> 1 ms <input type="checkbox"/> 4 ms	GAIN MODE: <input type="checkbox"/> INITIAL <input type="checkbox"/> MANUAL <input type="checkbox"/> OPERATE	FILTERS: FREQ. LO CUT Hz SLOPE 18 HI CUT Hz SLOPE 70		
DISPLAY	MODE: <input type="checkbox"/> FLOAT <input type="checkbox"/> AMPLIFIER <input type="checkbox"/> DIRECT	INITIAL GAIN: 10	TRIP SENS: 0	POLARITY CONVENTION: <input type="checkbox"/> NEGATIVE <input type="checkbox"/> POSITIVE		
CFS I	TYPE: <input type="checkbox"/> STAKE	GATE LENGTH:	RECORD REJECTION:	NOISE REDUCTION: <input type="checkbox"/> NOISE THRESHOLD: CORR. SCALING: <input type="checkbox"/> E.C.U. NORM/ALT SW		
SOURCE	TYPE: <input type="checkbox"/> GEOPHONE <input type="checkbox"/> VIBROSEIS <input type="checkbox"/> OTHER	PATTERN: 1 line - 1 hole	NO. OF POSITIONS: 20	INLINE SPACING: 75	LATERAL SPACING:	STAGGER: LENGTH: WIDTH: LATERAL OFFSET:
RECEIVER	TYPE: 20-2	PATTERN: 19 line	NO. OF ELEMENTS: 18	INLINE SPACING: 12	LATERAL SPACING:	STAGGER: LENGTH: WIDTH: LATERAL OFFSET:
SPREAD	NO. OF GROUPS: 48	GROUP INTERVAL: 200	SHOFPPOINT INTERVAL: 170	FOLD: 6	DIRECTION OF PROGRESSION: South	LEADING GROUP: 48

DIAGRAMS/MISC. INFORMATION:

SHOTPOINT	TR 10		TR 19		SHOT		SPREAD				REMARKS	CORE STACK				
	REEL NO.	REC.	REEL NO.	REC.	SIZE	DEPTH	NO.	CHASSIS	DIP	CDP SWITCH		LINE GROUPS	TR 10	TR 19	TR 28	TR 30
11103	7151	8111	1911		20	167	61	11		27	99+1 - 11014					Recorder @ 11022/11023
11104		1912			20	167	62	11		31	100+1 - 11114					
11107		1918			20	167	63	11		35	101+1 - 11214					
11108		1919			20	167	64	11		39	102+1 - 11314					
11109		1920			20	167	67	11		43	103+1 - 11414					
11110		1921			20	167	66	11		47	104+1 - 11514					
11111		1922			20	167	67	11		51	105+1 - 11614					
11112		1923			20	167	68	11		55	106+1 - 11714					
11113		1924			20	167	69	11		59	107+1 - 11814					
11114		1925			20	167	70	11		63	108+1 - 11914					# 425-426-N.G.
11115		1926			20	167	71	11		67	109+1 - 12014					# 428-N.G.
11116		1927			20	167	72	11		71	110+1 - 12114					# 430-N.G.

LAND SEISMIC RECORDING LOG

	CLIENT: Husky	PROSPECT: NPR-A	AREA: Barrow	LINE NO.: 673
	PARTY NO.: 1182	INST. ENG.: Stieff		DATE: MO 4 DAY 27 yr 79
INSTRUMENT (9 TRACK)	<input type="checkbox"/> 1 SYSTEM <input type="checkbox"/> 2 SYSTEMS	<input type="checkbox"/> 1-28 & 28-48 <input type="checkbox"/> 1-48 & 48-96	<input type="checkbox"/> PDS <input type="checkbox"/> PDS	<input type="checkbox"/> 356 BPI <input type="checkbox"/> 800 BPI <input type="checkbox"/> 212 BPI <input type="checkbox"/> 1000 BPI
	NO BYTES IN HEADR BPC	NO BYTES IN RECORD ID	NO BYTES PER SCAN: 134	RECORD NUMBERS: <input type="checkbox"/> DEC. <input type="checkbox"/> OCT
CONFIGURATION (MAG TAPE)	FIELD TRACE NOS.: 1-48	DATA CHANNEL NOS.: 1-48	AUXILIARY DATA: AUXILIARY CHANNEL NOS.:	
PARAMETER	RECORD LENGTH: 6 sec	SAMPLE RATE: <input type="checkbox"/> 1000 <input type="checkbox"/> 2000	GAIN MODE: <input type="checkbox"/> INITIAL <input checked="" type="checkbox"/> FINAL	FILTERS: <input type="checkbox"/> 10 CUT <input type="checkbox"/> 20
DISPLAY	MODE: <input type="checkbox"/> FLOAT <input type="checkbox"/> OFFLOG	AMPLIFIER: <input type="checkbox"/> DIRECT	INITIAL GAIN: 12	POLARITY CONVENTION: <input type="checkbox"/> NEGATIVE <input type="checkbox"/> POSITIVE
CFS I	TYPE: <input type="checkbox"/> DYNAMIC <input type="checkbox"/> VIBROSEIS <input type="checkbox"/> OTHER	PATTERN: 1 hole - 1 line	NO. OF POSITIONS: 16	INLINE SPACING: 12
SOURCE	END/ HOLE: 30	HOLE DEPTH: 75	SWEEP POSITION: 16	SWEEP START: 16
RECEIVER	TYPE: 20-P	PATTERN: 1 line	NO. OF ELEMENTS: 16	INLINE SPACING: 12
SPREAD	CONNECTION: Series-parallel	RESISTANCE: 560 ohms	STAGGER: 16	LENGTH: 6
DIAGRAMS/MISC INFORMATION:	NO. OF GROUPS: 48	GROUP INTERVAL: 220	SHOTPOINT INTERVAL: 880	FOLD: 6
	OFFSET GROUP 1: 5170	OFFSET GROUP 2: 110	OFFSET GROUP 25: 110	OFFSET GROUP 48/24: 5170

SHOTPOINT	TR	TR NO	TR		SHOT		SPREAD		DIB	COP SWITCH	REMARKS	CORR STACK			
			REC	PEEL NO.	SIZE	DEPTH	NO.	OFFSET				LINE GROUPS	TR	TR	TR
11217	28	119411	4147		20	167	11	11	27	111+1 - 122+4	1	Recorder @ 122+2/122+3			
11218			4148		20	167	12	11	31	112+1 - 123+4					
11219			4146		20	167	13	11	35	113+1 - 124+4					
11220			4147		20	167	14	11	39	114+1 - 125+4					
11221			4148		20	167	15	11	43	115+1 - 126+4					
11222			4149		20	167	16	11	47	116+1 - 127+4					
11223			4150		20	167	17	11	51	117+1 - 128+4					
11224			4151		20	167	18	11	55	118+1 - 129+4					
11225			4152		20	167	19	11	59	119+1 - 130+4					
11226			4153		20	167	20	11	63	120+1 - 131+4					
11227			4154		20	167	21	11	67	121+1 - 132+4					
11228			4155		20	167	22	11	71	122+1 - 133+4					
11229			4157		20	167	23	11	75	123+1 - T. 8					
11310			4158		210	167	24	ASP	79	124+1 - T. 10					
11315			4159		210	167	25		83	125+1 - T. 12					
11320			4160		210	167	26		87	126+1 - T. 20					
11330			4161		210	167	27		91	127+1 - T. 24					

CDP-FABOR = (-59 - 117+1 - 130+4)

4955-NIG