

Chris Copy

Recording Hrs 11.0

LAND SEISMIC RECORDING LOG

CLIENT: <i>Hosky</i>		PROSPECT: <i>NPR-A</i>		AREA: <i>Barrow</i>		LINE NO: <i>674</i>	
PARTY NO: <i>1182</i>		INST. ENG: <i>Streff</i>		DATE: <i>MO 4 DAY 19 YR 79</i>		G.S.I. Logo	
INSTRUMENT (9-TRACK) <input type="checkbox"/> 1 SYSTEM <input type="checkbox"/> 2 SYSTEMS NO. BYTES IN HEADER REC: _____		<input type="checkbox"/> T-24 & 25-48 <input type="checkbox"/> 1-48 & 49-96 ODDS & EVENS TYPE: <input type="checkbox"/> DFS III <input type="checkbox"/> DFS IV <input type="checkbox"/> OTHER _____		<input type="checkbox"/> 0 TRACK <input type="checkbox"/> 2 TRACK FORMAT: <i>B</i> SEG: _____		PACKING DENSITY: (L) <input type="checkbox"/> 356 BPI (H) <input type="checkbox"/> 712 BPI <input type="checkbox"/> 1000 BPI	
CONFIGURATION (MAG TAPE) FIELD TRACE NOS: <i>1-48</i> DATA CHANNEL NOS: <i>1-48</i> (ON MAG TAPE)		NO. BYTES IN RECORD ID: _____		NO. BYTES PER SCAN: <i>134</i>		RECORD NUMBERS: <input type="checkbox"/> DEC <input type="checkbox"/> OCT GAIN CONSTANT: <i>3.6</i> db INFLU IMPEDANCE: <i>204</i> ohms	
PARAMETER RECORD LENGTH: <i>6</i> sec SAMPLE RATE: <input type="checkbox"/> 1 ms <input type="checkbox"/> 4 ms <input type="checkbox"/> 7 ms <input type="checkbox"/> _____ ms		GAIN MODE: <input type="checkbox"/> INITIAL <input type="checkbox"/> MANUAL <input type="checkbox"/> OFF <input type="checkbox"/> FINAL <input type="checkbox"/> OPERATE		FILTERS: FREQ: <i>8</i> LO CUT HZ SLOPE <i>18</i> HI CUT HZ SLOPE <i>70</i>		NOISE FILTER: <input type="checkbox"/> IN <input type="checkbox"/> OUT	
DISPLAY MODE: <input type="checkbox"/> FLOAT <input type="checkbox"/> DEFLOAT <input type="checkbox"/> DIRECT <input type="checkbox"/> AGC <input type="checkbox"/> AMPLIFIER		INITIAL GAIN: <i>12</i> db TRIP SENS: <i>0</i> db		POLARITY CONVENTION: <input type="checkbox"/> NEGATIVE <input type="checkbox"/> POSITIVE		NUMBERS ON MAG TAPE: <input type="checkbox"/> DOWNBREAK <input type="checkbox"/> UPBREAK	
CFS I TYPE STACK: _____		GATE LENGTH: _____		RECORD REJECTION: _____		NOISE REDUCTION: _____ NOISE THRESHOLD: _____ CORR SCALING: _____	
SOURCE TYPE: <input type="checkbox"/> DYNAMITE <input type="checkbox"/> VIBROSEIS <input type="checkbox"/> OTHER _____		PATTERN: <i>inline-hole</i>		NO. OF POSITIONS: _____ CHG/ HOLE: <i>20</i> HOLE DEPTH: <i>75</i>		INLINE SPACING: _____ SWEEP START: _____	
RECEIVER TYPE: <i>20-n</i>		PATTERN: <i>inline</i>		NO. OF ELEMENTS: <i>18</i>		INLINE SPACING: <i>12</i>	
CONNECTION: <i>Series-Parallel</i>		RESISTANCE: <i>560</i> ohms		STAGGER: _____		LENGTH: _____	
SPREAD NO. OF GROUPS: <i>48</i> OFFSET GROUP 1: <i>5170</i>		GROUP INTERVAL: <i>230</i> OFFSET GROUP 2: <i>110</i>		SHOTPOINT INTERVAL: <i>880</i> OFFSET GROUP 25: <i>110</i>		FIELD: <i>6</i> DIRECTION OF PROGRESSION: <i>NORTH</i> LEADING GROUP: <i>48</i>	



DIAGRAMS/MISC. INFORMATION:
T-1 7.24 SA 111 674 #234-244-tests
X X X X
TAN 1 TAN 48 #245 test time block

SHOTPOINT	IR		1R		SHOT			SPREAD		REMARKS	CORR STACK						
	FR	TO	FR	TO	NO.	DEPTH	NO.	OFFSET	CDP SWITCH		LINE GROUPS	IR	1R	2R	3R		
1	751	1715	2146		22	23	26	27	28	30	32	35	37				
11														19	T.1 - 6+4	1	Recorder @ 8+2/8+3
12														23	T.5 - 7+4		
13														27	T.9 - 8+4		
14														31	T.12 - 9+4		
15														35	T.17 - 10+4		
16														39	T.21 - 11+4		
17														43	T.1 - 12+4		
18														47	T.1 - 13+4		
19														51	T.1 - 14+4		
20														55	T.1 - 15+4		
21														59	T.1 - 16+4		
22														63	T.1 - 17+4		
23														67	T.1 - 18+4		
24														71	T.1 - 19+4		
25														75	T.1 - 20+4		
26														79	T.1 - 21+4		
27														83	T.1 - 22+4		
28														87	T.1 - 23+4		
29														91	T.1 - 24+4		
30														95	T.1 - 25+4		
31														99	T.1 - 26+4		
32														103	T.1 - 27+4		
33														107	T.1 - 28+4		
34														111	T.1 - 29+4		
35														115	T.1 - 30+4		
36														119	T.1 - 31+4		
37														123	T.1 - 32+4		
38														127	T.1 - 33+4		
39														131	T.1 - 34+4		
40														135	T.1 - 35+4		
41														139	T.1 - 36+4		
42														143	T.1 - 37+4		
43														147	T.1 - 38+4		
44														151	T.1 - 39+4		
45														155	T.1 - 40+4		
46														159	T.1 - 41+4		
47														163	T.1 - 42+4		
48														167	T.1 - 43+4		
49														171	T.1 - 44+4		
50														175	T.1 - 45+4		

2 #258-N.G.

674

LAND SEISMIC RECORDING LOG

	CLIENT: <u>HUSHY</u>	PROSPECT: <u>NPR-A</u>	AREA: <u>Barrow</u>	LINE NO: <u>674</u>								
PARTY NO: <u>1182</u>		INST. ENG: <u>Stieff</u>		DATE: <u>4 DAY 19 YR 79</u>								
INSTRUMENT (9-TRACK)	<input checked="" type="checkbox"/> SYSTEM <input type="checkbox"/> 2 SYSTEMS		<input type="checkbox"/> 24 & 25-48 <input type="checkbox"/> 1-48 & 49-96	<input checked="" type="checkbox"/> ODDS <input type="checkbox"/> EVENS	TYPE: <input type="checkbox"/> DFS III <input type="checkbox"/> DFS IX <input type="checkbox"/> OTHER	<input checked="" type="checkbox"/> TRACK <input type="checkbox"/> 21 TRACK	FORMAT: <u>A</u> SEG	<input type="checkbox"/> GAPPED <input type="checkbox"/> UNGAPPED	PACKING DENSITY: (L0) <input type="checkbox"/> 356 BPI (H1) <input type="checkbox"/> 712 BPI <input type="checkbox"/> 800 BPI <input type="checkbox"/> 1600 BPI			
	NO. BYTES IN HEADER REC:		NO. BYTES IN RECORD ID:		NO. BYTES PER SCAN: <u>1311</u>		RECORD NUMBERS:	<input checked="" type="checkbox"/> DEC <input type="checkbox"/> OCT	GAIN CONSTANT: <u>30</u> db	INPUT IMPEDANCE: <u>200</u> ohms		
CONFIGURATION (MAG TAPE)	FIELD TRACE NOS.: <u>1-48</u>				AUXILIARY DATA:		AUXILIARY CHANNEL NOS.:					
	DATA CHANNEL NOS.: <u>1-48</u> [ON MAG TAPE]											
PARAMETER	RECORD LENGTH: <u>6</u> sec.	SAMPLE RATE: <input type="checkbox"/> 1 ms <input type="checkbox"/> 4 ms <input checked="" type="checkbox"/> 7 ms	GAIN MODE: <input type="checkbox"/> INITIAL <input type="checkbox"/> MANUAL <input type="checkbox"/> FINAL <input type="checkbox"/> OPERATE	FILTERS: FREQ: <u>Y</u> LO CUT HZ SLOPE: <u>18</u> HI CUT HZ SLOPE: <u>70</u> NOTCH FILTER: <input type="checkbox"/> IN <input type="checkbox"/> OUT								
DISPLAY	MODE: <input checked="" type="checkbox"/> GGC <input type="checkbox"/> FLOAT <input type="checkbox"/> AMPLIFIER <input type="checkbox"/> DEFOAT <input type="checkbox"/> DIRECT	INITIAL GAIN: <u>12</u> db	JRIP SENS: <u>0</u> db	POLARITY CONVENTION: <input type="checkbox"/> NEGATIVE <input type="checkbox"/> POSITIVE		PRESSURE INCREASE ON GEOPHONE: <input type="checkbox"/> NEGATIVE <input type="checkbox"/> POSITIVE		NUMBERS ON MAG TAPE: <input type="checkbox"/> DOWNBREAK <input type="checkbox"/> UPBREAK		ON DISPLAY: <input type="checkbox"/> ON DISPLAY		
CFS I	TYPE STACK:	GATE LENGTH:	RECORD REJECTION:	NOISE REDUCTION:		NOISE THRESHOLD:		CORR. SCALING:		R.C.U. NORM./ALT SW.		
SOURCE	TYPE: <input checked="" type="checkbox"/> DYNAMITE <input type="checkbox"/> VIBROSEIS <input type="checkbox"/> OTHER		PATTERN: <u>inline-hole</u>		NO. OF POSITIONS:		INLINE SPACING:		LATERAL SPACING:		STAGGER:	
	CHG/ HOLE: <u>20</u>		HOLE DEPTH: <u>75</u>		SWEEP POSITION:		SWEEP START:		SWEEP END:		SWEEP TAPER:	
RECEIVER	TYPE: <u>200</u>		PATTERN: <u>inline</u>		NO. OF ELEMENTS: <u>18</u>		INLINE SPACING: <u>12</u>		LATERAL SPACING:		STAGGER:	
	CONNECTION: <u>Series-Parallel</u>		RESISTANCE:		STAGGER:		LENGTH:		WIDTH:		LATERAL OFFSET:	
SPREAD	NO. OF GROUPS: <u>4</u>		GROUP INTERVAL: <u>220</u>		SHOTPOINT INTERVAL: <u>880</u>		FOLD: <u>6</u>		DIRECTION OF PROGRESSION: <u>NORTH</u>			
	OFFSET GROUP 1: <u>5170</u>		OFFSET GROUP 2: <u>110</u>		OFFSET GROUP 25: <u>110</u>		OFFSET GROUP 48/96: <u>5170</u>		LEADING GROUP: <u>48</u>			

DIAGRAMS/MISC. INFORMATION:

SHOTPOINT	TR		TR		SHOT				SPREAD				REMARKS	CORR STACK				
	REEL NO	REC.	REEL NO	REC.	SIZE	DEPTH	NO.	OFFSET	DIR	CDP SWITCH	LINE GROUPS			SET UP	TR 1-48	TR 48-96	TR 1-48	TR 48-96
															REC	REC	REC	REC
1	251	16	22	26	20	167	31	11		57	15+1	-26+4	2					
2	268				20	167	22	11		61	16+1	-27+4						
3	269				20	167	23	30	W	65	17+1	-28+4						
4	270				20	167	24	11		69	18+1	-29+4						
5	271				20	167	25	11		73	19+1	-30+4						
6	272				20	167	26	11		77	20+1	-31+4						
7	273				20	167	27	11		27	21+1	-32+4						
8	274				20	167	28	11		31	22+1	-33+4						
9	275				20	167	29	11		35	23+1	-34+4						
10	277				20	167	30	11		39	24+1	-35+4						
11	278				20	167	31	11		43	25+1	-36+4						
12	279				20	167	32	11		47	26+1	-37+4						
13	280				20	167	33	11		51	27+1	-38+4						
14	281				20	167	34	110	S	55	28+1	-39+4						
15	282				20	167	35	110	S	59	29+1	-40+4						

#275 - N.G.

Recording Hrs. - 15.0

LAND SEISMIC RECORDING LOG

		CLIENT: HUSKY	PROSPECT: NPR-A	AREA: Barrow	LINE NO.: 674			
PARTY NO.: 1182		INST. ENG.: STREFF		DATE: MO 4 DAY 20 YR 79				
INSTRUMENT	<input checked="" type="checkbox"/> 1 SYSTEM <input checked="" type="checkbox"/> 2 SYSTEMS	<input checked="" type="checkbox"/> 1-24 & 25-48 <input checked="" type="checkbox"/> 1-48 & 49-96	ODDS & EVENS	TYPE: <input type="checkbox"/> DFS III <input type="checkbox"/> DFS IX	<input checked="" type="checkbox"/> 9 TRACK <input type="checkbox"/> 21 TRACK	FORMAT: B	<input checked="" type="checkbox"/> GAPPED <input type="checkbox"/> UNGAPPED	PACKING DENSITY: (LO) <input type="checkbox"/> 386 BPI (HI) <input type="checkbox"/> 712 BPI
(9-TRACK)	NO. BYTES IN HEADER REC:	NO. BYTES IN RECORD ID:	NO. BYTES PER SCAN:	RECORD NUMBERS:	<input checked="" type="checkbox"/> DEC <input type="checkbox"/> OCT	GAIN CONSTANT: 36	db	INPUT IMPEDANCE: 20,000 ohms
CONFIGURATION (MAG TAPE)	FIELD TRACE NOS.: 1-48		DATA CHANNEL NOS.: 1-48		AUXILIARY DATA:			
PARAMETER	RECORD LENGTH: 6 sec	SAMPLE RATE: <input type="checkbox"/> 1 ms <input type="checkbox"/> 4 ms <input checked="" type="checkbox"/> 2 ms	GAIN MODE: <input checked="" type="checkbox"/> INITIAL <input type="checkbox"/> FINAL	<input type="checkbox"/> MANUAL <input type="checkbox"/> OPERATE	FILTERS:	LD CUT HZ SLOPE	FREQ.	HI CUT HZ SLOPE
DISPLAY	MODE: <input checked="" type="checkbox"/> AGC <input type="checkbox"/> FLOAT	<input type="checkbox"/> AMPLIFIER <input type="checkbox"/> DIRECT	INITIAL GAIN: 18 db	TRIP SENS.: 0 db	POLARITY CONVENTION:	<input type="checkbox"/> NEGATIVE <input type="checkbox"/> POSITIVE	NUMBERS ON MAG. TAPE	<input type="checkbox"/> DOWNBREAK <input type="checkbox"/> UPBREAK
CFS I	TYPE STACK:	DATE LENGTH:	RECORD REJECTION:	NOISE REDUCTION:	NOISE THRESHOLD:	CORR. SCALING:	R.C.U. NORM./ALT SW	
SOURCE	TYPE: <input type="checkbox"/> DYNAMITE <input type="checkbox"/> VIBROSEIS <input type="checkbox"/> OTHER	PATTERN: inline-hole	NO. OF POSITIONS:	INLINE SPACING:	LATERAL SPACING:	STAGGER:	LENGTH:	WIDTH:
RECEIVER	TYPE: 20-0	PATTERN: inline	NO. OF ELEMENTS: 1X	INLINE SPACING: 12	LATERAL SPACING:	STAGGER:	LENGTH:	WIDTH:
SPREAD	CONNECTION: Series-Parallel	RESISTANCE: 560 ohms	SWEEP POSITION:	SWEEP START:	SWEEP END:	SWEEP LENGTH:	SWEEP TAPER:	PHASE COMP.
	NO. OF GROUPS: 48	GROUP INTERVAL: 220	SHOTPOINT INTERVAL: 180	OFFSET GROUP 1: 5170	OFFSET GROUP 2: 110	OFFSET GROUP 48/50: 5170	DIRECTION OF PROGRESSION: North	LEADING GROUP: 48

#283 - 293 tests
#294 - test-time break

SHOTPOINT	TR 1 to		TR 2 to		SHOT				SPREAD			REMARKS	CORE STACK			
	REEL NO.	REC.	PEEL NO.	REC.	SIZE	DEPTH	NO.	OFFSET	DIP	CDP SWITCH	LINE GROUPS		SP	TR 1	TR 2	TR 3
316	75119138	295			20	167	11			27	30+1 - 41+4	1				
317		296			20	167	12			31	31+1 - 42+4					
318		297			20	167	13			35	32+1 - 43+4					
319		298			20	167	14			39	33+1 - 44+4					
320		299			20	167	15			43	34+1 - 45+4					
341		300			20	167	16			47	35+1 - 46+4					
342		301			20	167	17			51	36+1 - 47+4					
343		302			20	167	18			55	37+1 - 48+4					
344		303			20	167	19			59	38+1 - 49+4					
345		304			20	167	20			63	39+1 - 50+4					
346		305			20	167	21			67	40+1 - 51+4					
347		306			20	167	22			71	41+1 - 52+4					
348		307			20	167	23			75	42+1 - 53+4					
349		308			20	167	24			79	43+1 - 54+4					
350		310			20	167	25			89	44+1 - 55+4	2				
351		311			20	167	26			33	45+1 - 56+4					
352		312			20	167	27			37	46+1 - 57+4					
353		313			20	167	28			41	47+1 - 58+4					
354		314			20	167	29			45	48+1 - 59+4					
355		315			20	167	30			49	49+1 - 60+4					

#301, ~~302~~ - M.G.

Recorder @ SP. 55



LAND SEISMIC RECORDING LOG

CLIENT: Husky		PROSPECT: NPR-A		AREA: Barrow		LINE NO: 674											
PARTY NO. 1182		INST. NO. Stieff		DATE: 4 DAY 20th 79													
INSTRUMENT (9-TRACK)		<input type="checkbox"/> SYSTEM <input checked="" type="checkbox"/> 2 SYSTEMS		<input type="checkbox"/> 1-24 & 25-48 <input type="checkbox"/> 1-48 & 49-96		ODDS <input type="checkbox"/> 2 EVENS <input type="checkbox"/> 1		TYPE: <input type="checkbox"/> DFS III <input type="checkbox"/> DFS III <input type="checkbox"/> OTHER		<input type="checkbox"/> 2 TRACK <input type="checkbox"/> 1 TRACK		FOPMAT: B SEG		<input type="checkbox"/> GAPPED <input type="checkbox"/> UNGAPPED		PACKING DENSITY: (LO) <input type="checkbox"/> 358 BPI <input type="checkbox"/> 800 BPI (HI) <input type="checkbox"/> 712 BPI <input type="checkbox"/> 1080 BPI	
NO. BYTES IN HEADER REC:		NO. BYTES IN RECORD ID:		NO. BYTES PER SCAN: 134		RECORD NUMBERS:		<input checked="" type="checkbox"/> DEC <input type="checkbox"/> OCT		GAIN CONSTANT: 36 db		INPUT IMPEDANCE: 20K ohms					
CONFIGURATION (MAG TAPE)		FIELD TRACE NOS.:		DATA CHANNEL NOS.:		AUXILIARY DATA:		AUXILIARY CHANNEL NOS.:									
PARAMETER		RECORD LENGTH: 1 sec.		SAMPLE RATE: <input type="checkbox"/> 1 ms. <input type="checkbox"/> 4 ms. <input type="checkbox"/> 2 ms. <input type="checkbox"/> 10 ms.		GAIN MODE: <input checked="" type="checkbox"/> TRF <input type="checkbox"/> INITIAL <input type="checkbox"/> FINAL		FILTERS: <input type="checkbox"/> LO CUT <input type="checkbox"/> HI CUT FREQ: 8 HZ SLOPE: 18		NOISE REDUCTION: <input type="checkbox"/> PRESSURE INCREASE ON GEOPHONE <input type="checkbox"/> POSITIVE <input type="checkbox"/> NEGATIVE		COR. SCALING: <input type="checkbox"/> R.C.U. NORM/ALT SW.					
DISPLAY		<input type="checkbox"/> MODE: <input type="checkbox"/> FLOAT <input type="checkbox"/> DEFLOAT <input type="checkbox"/> DIRECT		INITIAL GAIN: 12 db		TRIP SENS: 0 db		POLARITY CONVENTION:		PHASE COMP: <input type="checkbox"/> DOWNBREAK <input type="checkbox"/> UPBREAK		ON DISPLAY					
CFS I		TYPE STACK:		GATE LENGTH:		RECORD REJECTION:		NOISE THRESHOLD:		COR. SCALING:		R.C.U. NORM/ALT SW.					
SOURCE		<input checked="" type="checkbox"/> DYNAMITE <input type="checkbox"/> VIBROSEIS <input type="checkbox"/> OTHER		PATTERN: Line-Hole		NO. OF POSITIONS:		INLINE SPACING:		LATERAL SPACING:		STAGGER:		LENGTH:			
RECEIVER		TYPE: 30.0		PATTERN: Line		NO. OF ELEMENTS: 18		INLINE SPACING: 12		LATERAL SPACING:		STAGGER:		LENGTH:			
SPREAD		CONNECTION: Series-Parallel		RESISTANCE: 560 ohms		STAGGER:		LENGTH:		WIDTH:		LATERAL OFFSET:					
NO. OF GROUPS: 48		GROUP INTERVAL: 220		SHOTPOINT INTERVAL: 880		FOLD: 6		DIRECTION OF PROGRESSION: North		LEADING GROUP: 48							
OFFSET GROUP 1: 5170		OFFSET GROUP 24: 110		OFFSET GROUP 25: 110		OFFSET GROUP 48/96: 5170											

DIAGRAMS/MISC. INFORMATION:

SHOTPOINT	TR		TR		SHOT					SPREAD			REMARKS	CORR STAGE			
	REEL NO	REC.	REEL NO	REC.	SIZE	DEPTH	NO.	OFFSET	DIR	COP SWITCH	LINE GROUPS	SP		HT	REC.	HT	REC.
56	7511	1315	311	16	210	67	211	11	11	41	50+1 - 61+4	3					
57		1317			210	67	212	11	11	45	51+1 - 62+4						
58		1318			210	67	213	11	11	49	52+1 - 63+4						
59		1317			210	67	214	11	11	53	53+1 - 64+4						
60		1320			210	67	215	11	11	21	54+1 - 65+4	4					
61		1321			210	67	216	11	11	25	55+1 - 66+4						
62		1322			210	67	217	11	11	29	56+1 - 67+4						
63		1323			210	67	218	11	11	33	57+1 - 68+4						
64		1324			210	67	219	11	11	37	58+1 - 69+4						
65		1325			210	67	30	11	11	41	59+1 - 70+4						
66		1326			210	67	31	11	11	45	60+1 - 71+4						
67		1327			210	67	32	11	11	49	61+1 - 72+4						
68		1328			210	67	33	11	11	53	62+1 - 73+4						
69		1329			210	67	34	11	11	57	63+1 - 74+4						
70		1330			210	67	35	11	11	61	64+1 - 75+4						
71		1331			210	67	36	11	11	65	65+1 - 76+4						
72		1332			210	67	37	11	11	69	66+1 - 77+4						
73		1333			210	67	38	11	11	73	67+1 - 78+4						
74		1334			210	67	39	11	11	29	68+1 - 79+4	5					
75		1335			210	67	40	11	11	33	69+1 - 80+4						

LAND SEISMIC RECORDING LOG



	CLIENT: Husky	PROSPECT: NPR-A	AREA: Barrow	LINE NO: 674									
	PARTY NO: 1112	INST. ENG: Stieff		DATE: 4 DAY 02 YR 79									
INSTRUMENT (9-TRACK)	<input type="checkbox"/> 1 SYSTEM <input type="checkbox"/> 2 SYSTEMS	<input type="checkbox"/> 1-24 & 25-48 <input type="checkbox"/> 1-48 & 49-96	TYPE: <input type="checkbox"/> DFS III <input type="checkbox"/> DFS IV	<input type="checkbox"/> TRACK <input type="checkbox"/> 21 TRACK	FOPMAT: B	<input type="checkbox"/> GAPPED <input type="checkbox"/> UNGAPPED	PACKING DENSITY: (L) <input type="checkbox"/> 356 BPI <input type="checkbox"/> 600 BPI	(M) <input type="checkbox"/> 712 BPI <input type="checkbox"/> 1000 BPI					
CONFIGURATION (MAG TAPE)	FIELD TRACE NOS.:	DATA CHANNEL NOS.:	(ON MAG TAPE)	AUXILIARY DATA:			(1)	(2)	(3)	(4)	(5)	(6)	(7)
PARAMETER	RECORD LENGTH: 6	SAMPLE RATE: <input type="checkbox"/> 1 ms <input checked="" type="checkbox"/> 2 ms <input type="checkbox"/> 4 ms	GAIN MODE: <input type="checkbox"/> INITIAL <input checked="" type="checkbox"/> FINAL	FILTERS: FREQ 8 Hz SLOPE 18	LO CUT	HI CUT	NOTCH FILTER: <input type="checkbox"/> IN <input type="checkbox"/> OUT						
DISPLAY	MODE: <input type="checkbox"/> AGC <input type="checkbox"/> FLOAT <input type="checkbox"/> DEFLOAT <input type="checkbox"/> DIRECT	AMPLIFIER: <input type="checkbox"/> DIRECT	INITIAL GAIN: 12 db	TRIP SENS: 0 db	POLARITY CONVENTION: <input type="checkbox"/> NEGATIVE <input type="checkbox"/> POSITIVE	PRESSURE INCREASE ON GEOPHONE: <input type="checkbox"/> POSITIVE <input type="checkbox"/> NEGATIVE	NUMBERS ON MAG TAPE: <input type="checkbox"/> DOWNBREAK <input type="checkbox"/> UPBREAK	ON DISPLAY: <input type="checkbox"/> ON DISPLAY					
CFS I	TYPE STACK:	GATE LENGTH:	RECORD REJECTION:	NOISE REDUCTION:	NOISE THRESHOLD:	CORR. SCALING:	R.C.U. NORM / ALT SW						
SOURCE	TYPE: <input checked="" type="checkbox"/> DYNAMITE <input type="checkbox"/> VIBROSEIS <input type="checkbox"/> OTHER	PATTERN: inline - 1 hole	NO. OF POSITIONS:	INLINE SPACING:	LATERAL SPACING:	STAGGER:	LENGTH:	WIDTH:	LATERAL OFFSET:				
RECEIVER	TYPE: 20-0	PATTERN: inline	NO. OF ELEMENTS: 18	INLINE SPACING: 12	LATERAL SPACING:	STAGGER:	LENGTH:	WIDTH:	LATERAL OFFSET:				
SPREAD	CONNECTION: Series-Parallel	RESISTANCE: 560 ohms	STAGGER:	LENGTH:	WIDTH:	LATERAL OFFSET:							
	NO. OF GROUPS: 48	GROUP INTERVAL: 220	SHOTPOINT INTERVAL: 880	FOLD: 6	DIRECTION OF PROGRESSION: North	LEADING GROUP: 48							
	OFFSET GROUP 1: 5170	OFFSET GROUP 24: 110	OFFSET GROUP 25: 110	OFFSET GROUP 48/90: 5180									

DIAGRAMS/MISC. INFORMATION:

SHOTPOINT	TR		TR		SHOT				SPREAD			REMARKS	CORR STACK			
	REEL NO.	REC.	REEL NO.	REC.	SIZE	DEPTH	NO.	OFFSET	DIP	CDP SWITCH	LINE GROUPS		HT	TR 1-20	TR 21-40	TR 41-60
716	751191315	3317			20	167	41			37	70+1 - 81+4	#336-N.G.				
717		3318			20	167	42			41	71+1 - 82+4					
718		3319			20	167	43			45	72+1 - 83+4					
719		3340			20	167	44			49	73+1 - 84+4					
720		3341			20	167	45			53	74+1 - 85+4					
721		3342			20	167	46			57	75+1 - 86+4	#343-N.G.				
722		3343			20	167	47			61	76+1 - 87+4					
723		3345			20	167	48			65	77+1 - 88+4					
724		3346			20	167	49			69	78+1 - 89+4					
725		3347			20	167	50			25	79+1 - 90+4	Recorder @ 5P-91				
726		3348			20	167	51			29	80+1 - 91+4					
727		3349			20	167	52			33	81+1 - 92+4					
728		3350			20	167	53			37	82+1 - 93+4					
729		3351			20	167	54			41	83+1 - 94+4					
730		3352			20	167	55			45	84+1 - 95+4					
731		3353			20	167	56			49	85+1 - 96+4	#353-N.G.				
732		3355			20	167	57			53	86+1 - 97+4					
733		3356			20	167	58			57	87+1 - 98+4					
734	75119126	3357			20	167	59			61	88+1 - 99+4	TAPE CHANGE				
735		3358			20	167	60			65	89+1 - 100+4					

Recording Hrs - 14.



LAND SEISMIC RECORDING LOG

		CLIENT: <u>Husky</u>	PROSPECT: <u>NPR-A</u>	AREA: <u>Barrow</u>	LINE NO: <u>674</u>				
PARTY NO: <u>1192</u>		INST. ENG: <u>Streff</u>		DATE: <u>MO 41 DAY 21 YR 77</u>					
INSTRUMENT {9-TRACK}	<input type="checkbox"/> 1 SYSTEM <input type="checkbox"/> 2 SYSTEMS	<input type="checkbox"/> 1-24 & 25-48 <input type="checkbox"/> 1-48 & 49-96	ODDS & EVENS <input type="checkbox"/> ODDS <input type="checkbox"/> EVENS	TYPE: <input type="checkbox"/> DFS III <input type="checkbox"/> DFS IX <input type="checkbox"/> OTHER	<input type="checkbox"/> 1 TRACK <input type="checkbox"/> 2 TRACK	FOPMAT: <u>B</u> SEG	<input type="checkbox"/> GAPPED <input type="checkbox"/> UNGAPPED	PACKING DENSITY: (L) <input type="checkbox"/> 356 BPI (H) <input type="checkbox"/> 712 BPI <input type="checkbox"/> 800 BPI <input type="checkbox"/> 1600 BPI	
	NO. BYTES IN HEADER REC:		NO. BYTES IN RECORD ID: <u>174</u>		RECORD NUMBERS: <input type="checkbox"/> DEC <input type="checkbox"/> OCT		GAIN CONSTANT: <u>36</u> db		
CONFIGURATION (MAG TAPE)	FIELD TRACE NOS.:			AUXILIARY DATA:			INPUT IMPEDANCE: <u>20k</u> ohms		
PARAMETER	RECORD LENGTH: <u>6</u> sec	SAMPLE RATE: <input type="checkbox"/> 1 ms <input type="checkbox"/> 4 ms	GAIN MODE: <input type="checkbox"/> INITIAL <input type="checkbox"/> MANUAL <input type="checkbox"/> OPERATE	FILTERS: FREQ <u>8</u> LO CUT HZ SLOPE <u>18</u>		HI CUT HZ SLOPE <u>72</u>		NOISE FILTER: <input type="checkbox"/> IN <input type="checkbox"/> OUT	
DISPLAY	MODE: <input type="checkbox"/> FLOAT <input type="checkbox"/> AMPLIFIER <input type="checkbox"/> DIRECT	INITIAL GAIN: <u>12</u> db	TRIP SENS: <u>2</u> db	POLARITY CONVENTION: <input type="checkbox"/> NEGATIVE <input type="checkbox"/> POSITIVE		NUMBERS ON MAG. TAPE <input type="checkbox"/> DOWNBREAK <input type="checkbox"/> UPBREAK		ON DISPLAY	
CFS I	TYPE STACK:	GATE LENGTH:	RECORD REJECTION:	NOISE REDUCTION:		NOISE THRESHOLD:	CORR. SCALING:	R.C.U. NORM/ALT SW	
SOURCE	TYPE: <input type="checkbox"/> DYNAMITE <input type="checkbox"/> VIBROSEIS <input type="checkbox"/> OTHER	PATTERN: <u>In-line - 1 Hole</u>	NO. OF POSITIONS:	INLINE SPACING:	LATERAL SPACING:	STAGGER:	LENGTH:	WIDTH:	LATERAL OFFSET:
RECEIVER	TYPE: <u>30-0</u>	PATTERN: <u>In-line</u>	NO. OF ELEMENTS: <u>18</u>	INLINE SPACING: <u>12</u>	LATERAL SPACING:	STAGGER:	LENGTH:	WIDTH:	LATERAL OFFSET:
SPREAD	CONNECTION: <u>Series-Parallel</u>	RESISTANCE: <u>560</u> ohms	STAGGER:	LENGTH:	WIDTH:	LATERAL OFFSET:			
	NO. OF GROUPS: <u>48</u>	GROUP INTERVAL: <u>220</u>	SHOTPOINT INTERVAL: <u>880</u>	FOLD: <u>6</u>	DIRECTION OF PROGRESSION: <u>NORTH</u>			LEADING GROUP: <u>48</u>	
	OFFSET GROUP 1: <u>5170</u>	OFFSET GROUP 2: <u>110</u>	OFFSET GROUP 25: <u>110</u>	OFFSET GROUP 48/96: <u>5170</u>					

DIAGRAMS/MISC. INFORMATION: 3011 75-4 50-70 101-4 N 359-309-10515
X X @ X X
7A#1 7R#4 #370 test-timecheck

SHOTPOINT	TR 10		TR 20		SHOT										SPREAD		REMARKS	CORR. STACK			
	REEL NO.	REC.	REFL NO.	REC.	NO.	OFFSET	DIR	COP SWITCH	LINE GROUPS		SET	10-10	10-20	10-30	10-40						
1196	75119316	13171			20	20	30	37		21	9011 - 10114	1									
1197		13172			20	167	12		25	9111 - 10214											
1198		13173			20	167	13		29	9211 - 10314											
1199		13174			20	167	14		33	9311 - 10414											
11100		13175			20	167	15		37	9411 - 10514											
11101		13176			20	167	16		41	9511 - 10614											
11102		13177			20	167	17		45	9611 - 10714											
11103		13178			20	167	18		49	9711 - 10814											
11104		13179			20	167	19		53	9811 - 10914						#379 - N.G.					
11105		13180			20	167	20		57	9911 - 11014						#381 - N.G.					
11106		13181			20	167	21		61	10011 - 11114						#383 - N.G.					
11107		13182			20	167	22		65	10111 - 11214						#385 - N.G.					
11108		13183			20	167	23		69	10211 - 11314											
11109		13184			20	167	24		73	10311 - 11414											
11110		13185			20	167	25		77	10411 - 11514						#389 - 390 - N.G.					
11111		13186			20	167	26		81	10511 - 11614											
11112		13187			20	167	27		85	10611 - 11714						#393 - N.G.					
11113		13188			20	167	28		89	10711 - 11814						#395 - N.G.					
11114		13189			20	167	29		93	10811 - 11914											
11115		13190			20	167	30		97	10911 - 12014											

LAND SEISMIC RECORDING LOG

	CLIENT: <u>HUSKY</u>	PROSPECT: <u>NPA-A</u>	AREA: <u>Barrow</u>	LINE NO: <u>674</u>					
	PARTY NO: <u>1183</u>	INST. ENG: <u>Stieff</u>		DATE: <u>MO 4 DAY 21 YR 75</u>					
INSTRUMENT (9-TRACK)	<input checked="" type="checkbox"/> 1 SYSTEM <input checked="" type="checkbox"/> 2 SYSTEMS	<input checked="" type="checkbox"/> 1-24 & 25-48 <input checked="" type="checkbox"/> 1-48 & 49-96	ODDS EVENTS	TYPE: <input type="checkbox"/> DFS III <input type="checkbox"/> DFS IV <input type="checkbox"/> OTHER	<input checked="" type="checkbox"/> 9 TRACK <input type="checkbox"/> 21 TRACK	FORMAT: <u>B</u>	<input type="checkbox"/> GAPPED <input type="checkbox"/> UNGAPPED	PACKING DENSITY: (L) <input type="checkbox"/> 350 BPI (M) <input type="checkbox"/> 712 BPI <input type="checkbox"/> 1600 BPI	
	NO. BYTES IN HEADER REC:	NO. BYTES IN RECORD ID:	NO. BYTES PER SCAN: <u>134</u>	RECORD NUMBERS: <input checked="" type="checkbox"/> DEC <input type="checkbox"/> OCT	GAIN CONSTANT: <u>36</u> db	INPUT IMPEDANCE: <u>700</u> ohms			
CONFIGURATION (MAG TAPE)	FIELD TRACE NOS: <u>1-48</u>			AUXILIARY DATA:			AUXILIARY CHANNEL NOS.:		
PARAMETER	RECORD LENGTH: <u>6</u> sec	SAMPLE RATE: <input type="checkbox"/> 1 ms <input type="checkbox"/> 4 ms <input checked="" type="checkbox"/> 2 ms	GAIN MODE: <input checked="" type="checkbox"/> INITIAL <input type="checkbox"/> FINAL <input type="checkbox"/> MANUAL <input type="checkbox"/> OPERATE	FILTERS: FREQ. <u>8</u> LO CUT HZ SLOPE <u>18</u> HI CUT HZ SLOPE <u>70</u> NOTCH FILTER: <input type="checkbox"/> IN <input type="checkbox"/> OUT					
DISPLAY	MODE: <input type="checkbox"/> FLOAT <input type="checkbox"/> AMPLIFIER <input type="checkbox"/> DIRECT	INITIAL GAIN: <u>12</u> db	TRIP SENS: <u>0</u> db	POLARITY CONVENTION: <input type="checkbox"/> NEGATIVE <input type="checkbox"/> POSITIVE	PRESSURE INCREASE ON GEOPHONE: <input type="checkbox"/> NEGATIVE <input type="checkbox"/> POSITIVE		ON MAG TAPE <input type="checkbox"/> DOWNPEAK <input type="checkbox"/> UPBREAK ON DISPLAY		
CFS I	TYPE STACK:	GATE LENGTH:	RECORD REJECTION:	NOISE REDUCTION:	NOISE THRESHOLD:	CORR. SCALING:	R.C.U. NORM./ALT SW.		
SOURCE	TYPE: <input type="checkbox"/> DYNAMITE <input type="checkbox"/> VIBROSEIS <input type="checkbox"/> OTHER	PATTERN: <u>inline-hole</u>	NO. OF POSITIONS:	INLINE SPACING:	LATERAL SPACING:	STAGGER:	LENGTH:	WIDTH:	LATERAL OFFSET:
RECEIVER	TYPE: <u>20-0</u>	PATTERN: <u>inline</u>	NO. OF ELEMENTS: <u>18</u>	INLINE SPACING: <u>12</u>	LATERAL SPACING:	STAGGER:	LENGTH:	WIDTH:	LATERAL OFFSET:
SPREAD	NO. OF GROUPS: <u>48</u>	GROUP INTERVAL: <u>220</u>	SHOTPOINT INTERVAL: <u>990</u>	FOLD: <u>6</u>	DIRECTION OF PROGRESSION: <u>North</u>	DIAGRAMS/MISC. INFORMATION:			
	OFFSET GROUP 1: <u>5170</u>	OFFSET GROUP 24: <u>110</u>	OFFSET GROUP 25: <u>110</u>	OFFSET GROUP 48/96: <u>5170</u>	LEADING GROUP: <u>48</u>				

SHOTPOINT	TR 1 to		TR 2 to		SHOT					SPREAD			REMARKS	CORR STACK			
	REEL NO	REC.	REEL NO.	REC.	SIZE	DEPTH	NO.	OFFSET	DIR.	COP SWITCH	LINE GROUPS	SEC		TR 1-48	TR 48-96	TR 1-48	TR 48-96
1116	7511936	12919			20	167	21			53	110+1 - 121+4	2					
1117		1402			20	167	22			57	111+1 - 122+4						
1118		1403			20	167	23			61	112+1 - 123+4						
1119		1405			20	167	24			65	113+1 - 124+4						
1120		1406			20	167	25			69	114+1 - 125+4						
1121		1407			20	167	26			73	115+1 - 126+4						
1122		1408			20	167	27			77	116+1 - 127+4						
1123		1409			20	167	28			81	117+1 - 128+4						
1124		1410			20	167	29			85	118+1 - 129+4						
1125		1411			20	167	30			29	119+1 - 130+4	3	Recorder @ SP-130				
1126		1412			20	167	31			33	120+1 - 131+4						
1127		1413			20	167	32			37	121+1 - 132+4						
1128		1414			20	167	33			41	122+1 - 133+4						
1129		1415			20	167	34	30.10	E	45	123+1 - 134+4						
1130		1416			20	167	35	20.10	E	49	124+1 - 135+4						
1131		1417			20	167	36			53	125+1 - 136+4						
1132		1418			20	167	37			33	126+1 - 137+4	4	Recorder @ SP-130				
1133		1420			20	167	38			37	127+1 - 138+4						
1134		1421			20	167	39			41	128+1 - 139+4						
1135		1422			20	167	40			45	129+1 - 140+4						

LAND SEISMIC RECORDING LOG

	CLIENT: <u>HUSBY</u>	PROSPECT: <u>NPR-A</u>	AREA: <u>Barrow</u>	LINE NO: <u>674</u>						
	PARTY NO: <u>1182</u>	INST. ENG: <u>Streiff</u>		DATE: <u>MO 4 DAY 21 YR 79</u>						
INSTRUMENT (9-TRACK)	<input type="checkbox"/> 1 SYSTEM <input type="checkbox"/> 2 SYSTEMS	<input type="checkbox"/> 1-24 & 25-48 <input type="checkbox"/> 1-48 & 49-96	ODDS <input type="checkbox"/> EVENS	TYPE: <input type="checkbox"/> DFS III <input type="checkbox"/> DFS IX <input type="checkbox"/> OTHER	<input checked="" type="checkbox"/> 7 TRACK <input type="checkbox"/> 21 TRACK	FORMAT: <u>SEG</u>	<input type="checkbox"/> GAPPED <input type="checkbox"/> UNGAPPED	PACKING DENSITY: (LO) <input type="checkbox"/> 356 BPI (HI) <input type="checkbox"/> 712 BPI <input type="checkbox"/> 1000 BPI		
	NO. BYTES IN HEADER REC:	NO. BYTES IN RECORD ID: <u>98</u>	NO. BYTES PER SCAN: <u>134</u>	RECORD NUMBERS: <input checked="" type="checkbox"/> DEC. <input type="checkbox"/> OCT	GAIN CONSTANT: <u>2.5</u> db	INPUT IMPEDANCE: <u>20K</u> ohms				
CONFIGURATION (MAG TAPE)	FIELD TRACE NOS.: <u>1-48</u>			AUXILIARY DATA:			AUXILIARY CHANNEL NOS.: _____			
PARAMETER	RECORD LENGTH: <u>6</u> sec	SAMPLE RATE: <input type="checkbox"/> 1 ms <input type="checkbox"/> 4 ms <input checked="" type="checkbox"/> 7 ms <input type="checkbox"/> _____ ms	GAIN MODE: <input type="checkbox"/> TFP <input type="checkbox"/> INITIAL <input type="checkbox"/> FINAL <input type="checkbox"/> MANUAL <input type="checkbox"/> OPERATE	FILTERS: _____	LO CUT _____ HZ SLOPE <u>18</u>	FREQ. <u>125</u> H1 CUT _____ H2 SLOPE <u>30</u>	NOTCH FILTER: <input type="checkbox"/> IN <input type="checkbox"/> OUT			
DISPLAY	MODE: <input checked="" type="checkbox"/> ADC <input type="checkbox"/> FLOAT <input type="checkbox"/> AMPLIFIER <input type="checkbox"/> DEFOAT <input type="checkbox"/> DIRECT	INITIAL GAIN: <u>12</u> db	JRIP SPNS: <u>2</u> db	POLARITY CONVENTION: <input type="checkbox"/> NEGATIVE <input type="checkbox"/> POSITIVE	PRESSURE INCREASE ON GEOPHONE: <input type="checkbox"/> NUMBERS ON MAG TAPE	<input type="checkbox"/> DOWNBREAK <input type="checkbox"/> UPBREAK	ON DISPLAY			
CFS I	TYPE STACK:	GATE LENGTH:	RECORD REJECTION:	NOISE REDUCTION:	NOISE THRESHOLD:	CORP SCALING:	F.C.U. NORM/ALT SW.			
SOURCE	TYPE: <input checked="" type="checkbox"/> DYNAMITE <input type="checkbox"/> VIBROSEIS <input type="checkbox"/> OTHER	PATTERN: <u>inline</u>	NO. OF POSITIONS: _____	INLINE SPACING: _____	LATERAL SPACING: _____	STAGGER: _____	LENGTH: _____	WIDTH: _____	LATERAL OFFSET: _____	
RECEIVER	TYPE: <u>200</u>	PATTERN: <u>0 inline</u>	NO. OF ELEMENTS: <u>18</u>	INLINE SPACING: <u>12</u>	LATERAL SPACING: _____	STAGGER: _____	LENGTH: _____	WIDTH: _____	LATERAL OFFSET: _____	
SPREAD	CONNECTION: <u>Series Parallel</u>	RESISTANCE: <u>560</u> ohms	SWEEP POSITION: _____	SWEEP START: _____	SWEEP END: _____	SWEEP LENGTH: _____	SWEEP TAPER: _____	PHASE COMP: _____		
	NO. OF GROUPS: <u>48</u>	GROUP INTERVAL: <u>220</u>	SHOTPOINT INTERVAL: <u>880</u>	FOLD: <u>6</u>	DIRECTION OF PROGRESSION: <u>North</u>	OFFSET GROUP 48/96: <u>5170</u>	LEADING GROUP: <u>41</u>			

DIAGRAMS/MISC. INFORMATION:

SHOTPOINT	TR 10		TR 20		SHOT				SPREAD			REMARKS	CORR STACK			
	REEL NO.	REC.	REEL NO.	REC.	SIZE	DEPTH	NO.	OFFSET	DIR	CDP SWITCH	LINE GROUPS		SET UP	TR 1-10	TR 11-20	TR 21-30
11316	25119316	14123			20	167	41			49	130+1 - 141+4	4				
11317		14234			20	167	42			29	131+1 - 142+4	5	Recorder @ SP-14			
11318		14215			20	167	43	20.0	W	33	132+1 - 143+4					
11319		14216			20	167	44			37	133+1 - 144+4					
11410		14217			20	167	45			41	134+1 - 145+4					
11411		14218			20	167	46			45	135+1 - 146+4					
11412		14219			20	167	47			49	136+1 - 147+4					
11413		14310			20	167	48	2.20	N	53	137+1 - 148+4					
11414		14311			20	167	49			57	138+1 - 149+4					
11415		14312			20	167	50			61	139+1 - 150+4					
11416		14313			20	167	51			65	140+1 - 151+4					
11417		14314			20	167	52			69	141+1 - 152+4					
11418		14315			20	167	53			73	142+1 - 153+4					

E.O. L.

* No Rec #435