

ANN'S C.

Recording Hrs - 15.0

LAND SEISMIC RECORDING LOG

| | | | | | | | |
|--------------------------|--|--|--|---|--|--|--|
| CLIENT: HUGH | | PROSPECT: NCR-A | | AREA: Barrow | | LINE NO: 676 | |
| PARTY NO: 1182 | | INST. ENG: Streff | | DATE: 41 DAY 23 YR 79 | | | |
| INSTRUMENT | | TYPE: <input type="checkbox"/> DIS III <input type="checkbox"/> DIS XX <input type="checkbox"/> OTHER | | FORMAT: <input checked="" type="checkbox"/> TRACK <input type="checkbox"/> 21 TRACK | | PACKING DENSITY: (LO) <input type="checkbox"/> 350 SFI (HI) <input type="checkbox"/> 712 SFI | |
| NO. BYTES IN READER REC. | | NO. BYTES IN RECORD ID: | | NO. BYTES PER SCAN: 124 | | RECORD NUMBERS: <input checked="" type="checkbox"/> DEC. <input type="checkbox"/> OCT. | |
| CONFIGURATION (MAG TAPE) | | FIELD TRACE NOS: 1-48 | | AUXILIARY DATA: | | AUXILIARY CHANNEL NOS: | |
| PARAMETER | | RECORD LENGTH: 6 sec. | | SAMPLE RATE: <input type="checkbox"/> 1 sec. <input type="checkbox"/> 4 sec. | | GAIN MODE: <input type="checkbox"/> INITIAL <input type="checkbox"/> MANUAL <input type="checkbox"/> OPERATE | |
| DISPLAY | | MODE: <input type="checkbox"/> FLOAT <input type="checkbox"/> AMPLIFIER <input type="checkbox"/> DIRECT | | INITIAL GAIN: 12 db | | TRIP SENS: 0 db | |
| CFS I | | TYPE STACK: | | GATE LENGTH: | | RECORD REJECTION: | |
| SOURCE | | TYPE: <input checked="" type="checkbox"/> DYNAMITE <input type="checkbox"/> VIBROSEIS <input type="checkbox"/> OTHER | | PATTERN: Inline-Hole | | NO. OF POSITIONS: 18 | |
| RECEIVER | | TYPE: 20-0 | | PATTERN: Inline | | NO. OF ELEMENTS: 18 | |
| SPREAD | | NO. OF GROUPS: 48 | | GROUP INTERVAL: 220 | | SHOTPOINT INTERVAL: 480 | |

DIAGRAMS/MISC. INFORMATION:
 SP1 111
 @ X
 TRA1
 12+4
 X @ X
 TRA48
 # 1-11-1055
 # 12-1055 time break

| SHOTPOINT | TR 10 | | TR 10 | | SHOT | | | SPREAD | | REMARKS | CORR. STACK | | | | |
|-----------|----------|------|----------|------|------|-------|-----|--------|------|---------|-------------|-------------|---------|----------|----------|
| | REEL NO. | REC. | REEL NO. | REC. | SIZE | DEPTH | NO. | OFFSET | DIR. | | CDP SWITCH | LINE GROUPS | TR 1-24 | TR 25-48 | TR 49-72 |
| 1 | 731 | 17 | 17 | 17 | 20 | 167 | 17 | 11 | 61 | 1+1 | -12+4 | | | | |
| 2 | 731 | 15 | | | 20 | 167 | 12 | 11 | 61 | 1+1 | -12+4 | | | | |
| 3 | | 16 | | | 20 | 167 | 13 | 11 | 61 | 1+1 | -12+4 | | | | |
| 4 | | 17 | | | 20 | 167 | 14 | 11 | 61 | 1+1 | -12+4 | | | | |
| 5 | | 18 | | | 20 | 167 | 15 | 11 | 61 | 1+1 | -12+4 | | | | |
| 6 | | 19 | | | 20 | 167 | 16 | 11 | 61 | 1+1 | -12+4 | | | | |
| 7 | | 20 | | | 20 | 167 | 17 | 11 | 61 | 1+1 | -12+4 | | | | |
| 8 | | 21 | | | 20 | 167 | 18 | 11 | 65 | 2+1 | -13+4 | | | | |
| 9 | | 22 | | | 20 | 167 | 19 | 11 | 69 | 3+1 | -14+4 | | | | |
| 10 | | 23 | | | 20 | 167 | 20 | 11 | 73 | 4+1 | -15+4 | | | | |
| 11 | | 24 | | | 20 | 167 | 21 | 11 | 77 | 5+1 | -16+4 | | | | |
| 12 | | 25 | | | 20 | 167 | 22 | 11 | 81 | 6+1 | -17+4 | | | | |
| 13 | | 26 | | | 20 | 167 | 23 | 11 | 85 | 7+1 | -18+4 | | | | |
| 14 | | 27 | | | 20 | 167 | 24 | 11 | 89 | 8+1 | -19+4 | | | | |
| 15 | | 28 | | | 20 | 167 | 25 | 11 | 93 | 9+1 | -20+4 | | | | |
| 16 | | 29 | | | 20 | 167 | 26 | 11 | 97 | 10+1 | -21+4 | | | | |
| 17 | | 30 | | | 20 | 167 | 27 | 11 | 29 | 11+1 | -22+4 | 2 | | | |
| 18 | | 31 | | | 20 | 167 | 28 | 11 | 33 | 12+1 | -23+4 | | | | |
| 19 | | 32 | | | 20 | 167 | 29 | 11 | 37 | 13+1 | -24+4 | | | | |
| 20 | | 33 | | | 20 | 167 | 30 | 11 | 41 | 14+1 | -25+4 | | | | |

Recorder @ SP-4 #13-A.G.
 Shooting through cable - CDP does not move.

Recorder @ SP-22

LAND SEISMIC RECORDING LOG

| | | | | | | | | | | | | | | | | | |
|--------------------------|--|--|--|--|--|--|--|---|--|--|--|--|--|--|--|--|--|
| CLIENT: <u>Hasny</u> | | PROSPECT: <u>NPR-A</u> | | AREA: <u>Barrow</u> | | LINE NO.: <u>676</u> | | | | | | | | | | | |
| PARTY NO.: <u>1182</u> | | INST. ENG.: <u>Streff</u> | | DATE: <u>NO. 4 DAY 23 YR 79</u> | | | | | | | | | | | | | |
| INSTRUMENT (9-TRACK) | | <input type="checkbox"/> 1 SYSTEM <input type="checkbox"/> 2 SYSTEMS | | <input type="checkbox"/> 7-24 & 25-48 <input type="checkbox"/> 1-48 & 49-96 | | ODDS EVENS <input type="checkbox"/> ODDS <input type="checkbox"/> EVENS | | TYPE: <input type="checkbox"/> DFS III <input type="checkbox"/> DFS XX <input type="checkbox"/> OTHER | | <input type="checkbox"/> TRACK <input type="checkbox"/> 2 TRACK | | FOPMAT: <u>B</u> SEG. | | <input type="checkbox"/> GAPPED <input type="checkbox"/> UNGAPPED | | PACKING DENSITY: (10) <input type="checkbox"/> 355 BPI (11) <input type="checkbox"/> 712 BPI (12) <input type="checkbox"/> 800 BPI | |
| NO. BYTES IN HEADER REC: | | NO. BYTES IN RECORD ID: | | NO. BYTES PER SCAN: <u>134</u> | | RECORD NUMBERS: | | <input type="checkbox"/> DEC. <input type="checkbox"/> OCT | | GAIN CONSTANT: <u>36</u> db | | INPUT IMPEDANCE: <u>200</u> ohms | | | | | |
| CONFIGURATION (MAG TAPE) | | FIELD TRACE NOS.: <u>1-48</u> | | DATA CHANNEL NOS.: <u>1-48</u> | | (ON MAG TAPE) | | AUXILIARY DATA: | | AUXILIARY CHANNEL NOS.: | | | | | | | |
| PARAMETER | | RECORD LENGTH: <u>6</u> sec. | | SAMPLE RATE: <input type="checkbox"/> 1 ms. <input type="checkbox"/> 4 ms. | | GAIN MODE: <input type="checkbox"/> INITIAL <input type="checkbox"/> MANUAL <input type="checkbox"/> OPERATE | | FILTERS: FREQ. <u>P</u> | | LO CUT HZ SLOPE: <u>18</u> | | HI CUT HZ SLOPE: <u>70</u> | | NOTCH FILTER: <input type="checkbox"/> IN <input type="checkbox"/> OUT | | | |
| DISPLAY | | <input type="checkbox"/> MODE <input type="checkbox"/> FLOAT <input type="checkbox"/> AMPLIFIER <input type="checkbox"/> DEFLOAT <input type="checkbox"/> DIRECT | | INITIAL GAIN: <u>13</u> db | | TRIP SENS.: <u>0</u> db | | POLARITY CONVENTION: <input type="checkbox"/> NEGATIVE <input type="checkbox"/> POSITIVE | | PRESSURE INCREASE ON GEOPHONE: <input type="checkbox"/> NUMBERS ON MAG. TAPE | | <input type="checkbox"/> DOWNBREAK <input type="checkbox"/> UPBREAK | | ON DISPLAY | | | |
| CFS I | | TYPE STACK: | | GATE LENGTH: | | RECORD REJECTION: | | NOISE REDUCTION: | | NOISE THRESHOLD: | | CORR. SCALING: | | R.C.U. NORM/ALT SW. | | | |
| SOURCE | | TYPE: <input type="checkbox"/> DYNAMITE <input type="checkbox"/> VIBROSEIS <input type="checkbox"/> OTHER | | PATTERN: <u>inline-hole</u> | | NO. OF POSITIONS: <u>20</u> | | INLINE SPACING: <u>HOLE DEPTH: 75</u> | | LATERAL SPACING: <u>SWEEP START:</u> | | STAGGER: <u>SWEEP LENGTH:</u> | | LENGTH: <u>SWEEP TAPER:</u> | | | |
| RECEIVER | | TYPE: <u>20-p</u> | | PATTERN: <u>inline</u> | | NO. OF ELEMENTS: <u>18</u> | | INLINE SPACING: <u>12</u> | | LATERAL SPACING: <u>LENGTH:</u> | | STAGGER: <u>WIDTH:</u> | | LATERAL OFFSET: | | | |
| SPREAD | | CONNECTION: <u>Series-Parallel</u> | | RESISTANCE: <u>560</u> ohms | | SHOTPOINT INTERVAL: <u>0.20</u> | | SHOTPOINT INTERVAL: <u>1.00</u> | | FOLD: <u>6</u> | | DIRECTION OF PROGRESSION: <u>South</u> | | LEADING GROUP: <u>48</u> | | | |
| SPREAD | | NO. OF GROUPS: <u>48</u> | | GROUP INTERVAL: <u>0.20</u> | | SHOTPOINT INTERVAL: <u>1.00</u> | | SHOTPOINT INTERVAL: <u>1.00</u> | | FOLD: <u>6</u> | | DIRECTION OF PROGRESSION: <u>South</u> | | LEADING GROUP: <u>48</u> | | | |
| SPREAD | | OFFSET GROUP 1: <u>5170</u> | | OFFSET GROUP 2: <u>110</u> | | SHOTPOINT INTERVAL: <u>1.00</u> | | SHOTPOINT INTERVAL: <u>1.00</u> | | FOLD: <u>6</u> | | DIRECTION OF PROGRESSION: <u>South</u> | | LEADING GROUP: <u>48</u> | | | |

DIAGRAMS/MISC. INFORMATION:

| SHOTPOINT | TR. 1 to 10 | | TR. 11 to 20 | | SHOT | | SPREAD | | REMARKS | CORR. STACK | | | |
|-----------|-------------|------|--------------|------|------|-------|--------|--------|---------|-------------|-------------|-------------|---------------------------|
| | REEL NO. | REC. | REEL NO. | REC. | SIZE | DEPTH | NO. | OFFSET | | DIR. | COP SWITCH | LINE GROUPS | TR 1-10 |
| 121 | 751937 | 37 | | | 120 | 167 | 21 | 11 | | 33 | 15+1 - 2024 | 3 | Recorder @ SP-25 #36-N.G. |
| 122 | | 38 | | | 120 | 167 | 22 | 11 | | 37 | 16+1 - 2724 | | |
| 123 | | 39 | | | 120 | 167 | 23 | 11 | | 41 | 17+1 - 2824 | | |
| 124 | | 40 | | | 120 | 167 | 24 | 11 | | 45 | 18+1 - 2924 | | |
| 125 | | 42 | | | 120 | 167 | 25 | 11 | | 49 | 19+1 - 3024 | | #41-N.C. |
| 126 | | 43 | | | 120 | 167 | 26 | 11 | | 53 | 20+1 - 3124 | | |
| 127 | | 44 | | | 120 | 167 | 27 | 11 | | 53 | 20+1 - 3124 | | <u>COP-ERROR</u> |
| 128 | | 45 | | | 120 | 167 | 28 | 11 | | 61 | 22+1 - 3324 | | |
| 129 | | 46 | | | 120 | 167 | 29 | 11 | | 29 | 23+1 - 3424 | 4 | Recorder @ SP-34 |
| 130 | | 47 | | | 120 | 167 | 30 | 11 | | 33 | 24+1 - 3524 | | |
| 131 | | 48 | | | 120 | 167 | 31 | 11 | | 37 | 25+1 - 3624 | | |
| 132 | | 49 | | | 120 | 167 | 32 | 11 | | 41 | 26+1 - 3724 | | |
| 133 | | 50 | | | 120 | 167 | 33 | 11 | | 45 | 27+1 - 3824 | | |
| 134 | | 51 | | | 120 | 167 | 34 | 11 | | 49 | 28+1 - 3924 | | |
| 135 | | 52 | | | 120 | 167 | 35 | 11 | | 53 | 29+1 - 4024 | | |
| 136 | | 53 | | | 120 | 167 | 36 | 11 | | 57 | 30+1 - 4124 | | |
| 137 | | 54 | | | 120 | 167 | 37 | 11 | | 61 | 31+1 - 4224 | | |
| 138 | | 56 | | | 120 | 167 | 38 | 11 | | 27 | 32+1 - 4324 | 5 | Recorder @ SP-43 #55-N.G. |
| 139 | | 57 | | | 120 | 167 | 39 | 11 | | 33 | 33+1 - 4424 | | |
| 140 | | 58 | | | 120 | 167 | 40 | 11 | | 37 | 34+1 - 4524 | | #58-N.G. |

LAND SEISMIC RECORDING LOG

| | | | | | | | | | | | | | | | | | | | | | |
|--|--|---|--|--|--|--|--|-------------------------------|--|---|--|---|--|---|--|----------------------------|--|----------------------------|--|--|--|
| CLIENT: <u>Hushy</u> | | PROSPECT: <u>NPA-A</u> | | AREA: <u>Barrow</u> | | LINE NO.: <u>676</u> | | | | | | | | | | | | | | | |
| PARTY NO.: <u>1171</u> | | INST. ENG.: <u>Slieff</u> | | DATE: <u>41 DAY 23 YR 79</u> | | | | | | | | | | | | | | | | | |
| INSTRUMENT: <input type="checkbox"/> 1 SYSTEM <input type="checkbox"/> 2 SYSTEMS | | <input type="checkbox"/> 1-24 & 25-48 <input type="checkbox"/> ODDS EVENS | | TYPE: <input type="checkbox"/> DFS III <input type="checkbox"/> DFS IV <input type="checkbox"/> DFS V <input type="checkbox"/> OTHER | | <input type="checkbox"/> 9 TRACK <input type="checkbox"/> 21 TRACK | | FORMAT: <u>13</u> SEC | | <input type="checkbox"/> GAPPED <input type="checkbox"/> UNGAPPED | | PACKING DENSITY: (L) <input type="checkbox"/> 350 BPI (H) <input type="checkbox"/> 712 BPI <input type="checkbox"/> 800 BPI <input type="checkbox"/> 1600 BPI | | | | | | | | | |
| NO. BYTES IN HEADER REC: | | NO. BYTES IN RECORD ID: | | NO. BYTES PER SCAN: <u>134</u> | | RECORD NUMBERS: | | GAIN CONSTANT: <u>0.36</u> db | | INPUT IMPEDANCE: <u>204</u> ohms. | | | | | | | | | | | |
| CONFIGURATION (MAG TAPE) | | FIELD TRACE NOS.: <u>1-48</u> | | | | AUXILIARY DATA: | | | | DATA CHANNEL NOS.: <u>1-48</u> (ON MAG TAPE) | | | | AUXILIARY CHANNEL NOS.: | | | | | | | |
| PARAMETER | | RECORD LENGTH: <u>6</u> sec. | | SAMPLE RATE: <input type="checkbox"/> 1 ms <input type="checkbox"/> 4 ms <input type="checkbox"/> 7 ms | | GAIN MODE: <input type="checkbox"/> INITIAL <input type="checkbox"/> MANUAL <input type="checkbox"/> OPERATE | | FILTERS: | | LO CUT HZ SLOPE: <u>18</u> | | HI CUT HZ SLOPE: <u>70</u> | | NOTCH FILTER: <input type="checkbox"/> IN <input type="checkbox"/> OUT | | | | | | | |
| DISPLAY | | MODE: <input type="checkbox"/> FLOAT <input type="checkbox"/> AMPLIFIER <input type="checkbox"/> DIRECT | | INITIAL GAIN: <u>12</u> db | | TRIP SENS: <u>0</u> db | | POLARITY CONVENTION: | | PRESSURE INCREASE ON GEOPHONE: | | <input type="checkbox"/> NEGATIVE <input type="checkbox"/> POSITIVE | | NUMBERS ON MAG TAPE: <input type="checkbox"/> DOWNBREAK <input type="checkbox"/> UPBREAK ON DISPLAY | | | | | | | |
| CFS I | | TYPE STACK: | | GATE LENGTH: | | RECORD REJECTION: | | NOISE REDUCTION: | | NOISE THRESHOLD: | | CORE SCALING: | | R.C.U. NORM/ALT SW. | | | | | | | |
| SOURCE | | TYPE: <input type="checkbox"/> DYNAMITE <input type="checkbox"/> VIBROSEIS <input type="checkbox"/> OTHER | | PATTERN: <u>inline - hole</u> | | NO. OF POSITIONS: | | INLINE SPACING: | | LATERAL SPACING: | | STAGGER: | | LENGTH: | | WIDTH: | | LATERAL OFFSET: | | | |
| RECEIVER | | TYPE: | | PATTERN: <u>inline</u> | | NO. OF ELEMENTS: <u>18</u> | | STAGGER: | | INLINE SPACING: <u>13</u> | | LATERAL SPACING: | | LENGTH: | | WIDTH: | | LATERAL OFFSET: | | | |
| SPREAD | | CONNECTION: <u>Series-Parallel</u> | | RESISTANCE: <u>560</u> ohms | | SWEEP POSITION: | | SWEEP START: | | SWEEP END: | | SWEEP LENGTH: | | SWEEP TAPER: | | PHASE COMP. | | FOLD: <u>6</u> | | DIRECTION OF PROGRESSION: <u>500ft</u> | |
| NO. OF GROUPS: <u>48</u> | | GROUP INTERVAL: <u>220</u> | | OFFSET GROUP 1: <u>5170</u> | | OFFSET GROUP 2: <u>110</u> | | OFFSET GROUP 2: <u>110</u> | | OFFSET GROUP 2: <u>110</u> | | OFFSET GROUP 2: <u>110</u> | | OFFSET GROUP 2: <u>110</u> | | OFFSET GROUP 2: <u>110</u> | | OFFSET GROUP 2: <u>110</u> | | OFFSET GROUP 2: <u>110</u> | |

DIAGRAMS/MISC. INFORMATION:

| SHOTPOINT | TR | TR 1 to | | TR 2 to | | SIZE | DEPTH | NO. | OFFSET | DIR | CDF SWITCH | SPREAD | | REMARKS | CORR STACK | | | |
|-----------|----|----------|------|----------|------|------|-------|-----|--------|-----|------------|-------------|-------------|---------|------------------------|----|-----|--|
| | | REEL NO. | REC. | REEL NO. | REC. | | | | | | | LINE GROUPS | HT | | REL | HT | REL | |
| 41 | 17 | 1213 | 16 | 17 | 2023 | 2027 | 2030 | 33 | 85 | 33 | | 41 | 38+1 - 46+4 | 5 | | | | |
| 42 | | | 1612 | | | | 120 | 167 | 41 | | | 45 | 36+1 - 47+4 | | | | | |
| 43 | | | 1613 | | | | 120 | 167 | 43 | | | 49 | 37+1 - 48+4 | | # 62-N.G. | | | |
| 44 | | | 1616 | | | | 120 | 167 | 44 | | | 53 | 38+1 - 49+4 | | #64-65-N.G. | | | |
| 45 | | | 1618 | | | | 120 | 167 | 45 | | | 57 | 39+1 - 50+4 | | #67-N.G. | | | |
| 46 | | | 1710 | | | | 120 | 167 | 46 | | | 61 | 40+1 - 51+4 | | #69-N.G. | | | |
| 47 | | | 1711 | | | | 120 | 167 | 47 | | | 65 | 41+1 - 52+4 | | | | | |
| 48 | | | 1713 | | | | 120 | 167 | 48 | | | 69 | 42+1 - 53+4 | | #72-N.G. | | | |
| 49 | | | 1716 | | | | 120 | 167 | 49 | | | 73 | 43+1 - 54+4 | | #79, 75-N.G. | | | |
| 50 | | | 1719 | | | | 120 | 167 | 50 | | | 77 | 44+1 - 55+4 | | #77, 78-N.G. | | | |
| 51 | | | 1811 | | | | 120 | 167 | 51 | | | 81 | 45+1 - 56+4 | | #80-N.G. | | | |
| 52 | | | 1812 | | | | 120 | 167 | 52 | | | 85 | 46+1 - 57+4 | | | | | |
| 53 | | | 1814 | | | | 120 | 167 | 53 | | | 89 | 47+1 - 58+4 | | #83-N.G. | | | |
| 54 | | | 1815 | | | | 120 | 167 | 54 | | | 93 | 48+1 - 59+4 | 6 | Recorder R 59+2 / 59+3 | | | |
| 55 | | | 1816 | | | | 120 | 167 | 55 | | | 31 | 49+1 - 60+4 | | | | | |
| 56 | | | 1817 | | | | 120 | 167 | 56 | | | 35 | 50+1 - 61+4 | | | | | |
| 57 | | | 1818 | | | | 120 | 167 | 57 | | | 39 | 51+1 - 62+4 | | | | | |
| 58 | | | 1819 | | | | 120 | 167 | 58 | | | 43 | 52+1 - 64+4 | | Stached on SP 7 | | | |
| 59 | | | 1910 | | | | 120 | 167 | 59 | | | 47 | 53+1 - 64+4 | | | | | |
| 60 | | | 1911 | | | | 120 | 167 | 60 | | | 51 | 54+1 - 65+4 | | | | | |

LAND SEISMIC RECORDING LOG

| | | | | | | | | | |
|---|--|--|--|--|--|---|--|---|--|
| CLIENT: Husky | | PROSPECT: NPR-A | | AREA: Barrow | | LINE NO.: 676 | | | |
| PARTY NO.: 1182 | | INST. ENG.: Streff | | DATE: NOV 4 DAY 23, 1979 | | | | | |
| INSTRUMENT (9-TRACK) <input type="checkbox"/> 1 SYSTEM <input type="checkbox"/> 1-24 & 25-48 <input type="checkbox"/> ODDS <input type="checkbox"/> 2 SYSTEMS <input type="checkbox"/> 1-48 & 49-96 <input type="checkbox"/> EVENS | | TYPE: <input type="checkbox"/> DFS III <input type="checkbox"/> DFS II <input type="checkbox"/> DFS I <input type="checkbox"/> OTHER | | FORMAT: <input type="checkbox"/> 8 TRACK <input type="checkbox"/> 21 TRACK | | GAIN: <input type="checkbox"/> GAPPED <input type="checkbox"/> UNGAPPED | | PACKING DENSITY: (L) <input type="checkbox"/> 256 BPI (H) <input type="checkbox"/> 712 BPI (V) <input type="checkbox"/> 800 BPI (M) <input type="checkbox"/> 1600 BPI | |
| NO. BYTES IN HEADER REC: _____ | | NO. BYTES IN RECORD ID: _____ | | NO. BYTES PER SCAN: _____ | | RECORD NUMBERS: <input type="checkbox"/> DEC. <input type="checkbox"/> OCT. | | GAIN CONSTANT: _____ db INPUT IMPEDANCE: _____ ohms | |
| CONFIGURATION (MAG TAPE) FIELD TRACE NOS.: _____ DATA CHANNEL NOS.: _____ | | (ON MAG TAPE) AUXILIARY DATA: _____ AUXILIARY CHANNEL NOS.: _____ | | | | | | | |
| PARAMETER RECORD LENGTH: _____ sec. SAMPLE RATE: <input type="checkbox"/> 1 ms <input type="checkbox"/> 4 ms <input type="checkbox"/> 2 ms <input type="checkbox"/> 4 ms | | GAIN MODE: <input type="checkbox"/> INITIAL <input type="checkbox"/> MANUAL <input type="checkbox"/> OPERATE | | FILTERS: _____ | | LO CUT HZ SLOPE: _____ | | HI CUT HZ SLOPE: _____ | |
| DISPLAY <input type="checkbox"/> AGC <input type="checkbox"/> FLOAT <input type="checkbox"/> AMPLIFIER <input type="checkbox"/> INITIAL GAIN: _____ db <input type="checkbox"/> DEFLOAT <input type="checkbox"/> DIRECT | | TRIP SENS.: _____ db | | POLARITY CONVENTION: <input type="checkbox"/> NEGATIVE <input type="checkbox"/> POSITIVE | | PRESSURE INCREASE ON GEOPHONE: _____ | | NUMBERS ON MAG TAPE: <input type="checkbox"/> DOWNBREAK <input type="checkbox"/> UPBREAK <input type="checkbox"/> ON DISPLAY | |
| CFS I TYPE STACK: _____ | | GATE LENGTH: _____ | | RECORD REJECTION: _____ | | NOISE REDUCTION: _____ | | CORP. SCALING: _____ | |
| SOURCE <input type="checkbox"/> DYNAMITE <input type="checkbox"/> VIBROSEIS <input type="checkbox"/> OTHER | | PATTERN: _____ | | NO. OF POSITIONS: _____ | | INLINE SPACING: _____ | | LATERAL SPACING: _____ | |
| RECEIVER CONNECTION: _____ | | RESISTANCE: _____ ohms | | STAGGER: _____ | | LENGTH: _____ | | WIDTH: _____ | |
| SPREAD NO. OF GROUPS: 48 OFFSET GROUP 1: 5170 | | GROUP INTERVAL: 200 OFFSET GROUP 24: 110 | | SHOTPOINT INTERVAL: 880 OFFSET GROUP 25: 110 | | FOLD: 6 OFFSET GROUP 48/96: 5190 | | DIRECTION OF PROGRESSION: South LEADING GROUP: 48 | |

DIAGRAMS/MISC. INFORMATION:

| SHOTPOINT | TR 10 | | TR 20 | | SHOT | | SPREAD | | | | REMARKS | CORP. STACK | | | | |
|-----------|----------|------|----------|------|------|-------|--------|--------|------|------------|-------------|-------------|-------|-------|-------|-------|
| | REEL NO. | REC. | REEL NO. | REC. | SIZE | DEPTH | NO. | OFFSET | DIR. | CDP SWITCH | | LINE GROUPS | TR 10 | TR 20 | TR 30 | TR 40 |
| 161 | 781 | 7137 | 1 | 92 | 120 | 167 | 61 | | | 55 | 55+1 - 66+4 | 6 | | | | |
| 162 | | | | | 120 | 167 | 62 | | | 59 | 56+1 - 67+4 | | | | | |
| 163 | | | | | 120 | 167 | 63 | | | 63 | 57+1 - 68+4 | | | | | |
| 164 | | | | | 120 | 167 | 64 | | | 67 | 58+1 - 69+4 | | | | | |
| 165 | | | | | 120 | 167 | 65 | | | 71 | 59+1 - 70+4 | | | | | |
| 166 | | | | | 120 | 167 | 66 | | | 37 | 60+1 - 71+4 | 7 | | | | |
| 167 | | | | | 120 | 167 | 67 | | | 81 | 61+1 - 72+4 | | | | | |
| 168 | | | | | 120 | 167 | 68 | | | 35 | 62+1 - 73+4 | | | | | |
| 169 | | | | | 120 | 167 | 69 | | | 39 | 63+1 - 74+4 | | | | | |
| 170 | | | | | 120 | 167 | 70 | | | 43 | 64+1 - 75+4 | | | | | |
| 171 | | | | | 120 | 167 | 71 | | | 47 | 65+1 - 76+4 | | | | | |
| 172 | | | | | 120 | 167 | 72 | | | 51 | 66+1 - 77+4 | | | | | |
| 173 | | | | | 120 | 167 | 73 | | | 55 | 67+1 - 78+4 | | | | | |
| 174 | | | | | 120 | 167 | 74 | | | 59 | 68+1 - 79+4 | | | | | |
| 175 | | | | | 120 | 167 | 75 | | | 63 | 69+1 - 80+4 | | | | | |
| | | | | | | | | | | | E.O.L. | | | | | |