


Chris Best Copy

Recording Hrs - 14.0

LAND SEISMIC RECORDING LOG

CLIENT: <u>Husky</u>		PROSPECT: <u>NPA-1</u>		AREA: <u>Barrow</u>		LINE NO: <u>678</u>	
PARTY NO: <u>1182</u>		INST. ENG: <u>Streck-Windham</u>		DATE: <u>MO 4 DAY 16 YR 79</u>			
INSTRUMENT <input checked="" type="checkbox"/> SYSTEM <input type="checkbox"/> 2 SYSTEMS		T-24 & 25-48 <input type="checkbox"/> 1-40 & 49-95		ODDS <input type="checkbox"/> EVENS		TYPE: <input type="checkbox"/> DFS III <input type="checkbox"/> DFS IV <input type="checkbox"/> OTHER	
(9-TRACK) NO. BYTES IN HEADER REC: _____		NO. BYTES IN RECORD ID: _____		NO. BYTES PER SCAN: <u>134</u>		RECORD NUMBERS: <u>0-DEC</u> <input type="checkbox"/> OCT	
CONFIGURATION (MAG TAPE) FIELD TRACE NOS: <u>1-48</u>		DATA CHANNEL NOS: <u>1-48</u>		(ON MAG TAPE)		AUXILIARY DATA: AUXILIARY CHANNEL NOS: _____	
PARAMETER RECORD LENGTH: <u>6</u> sec.		SAMPLE RATE: <input type="checkbox"/> 3 ml. <input type="checkbox"/> 4 ml.		GAIN MODE: <input checked="" type="checkbox"/> INITIAL <input type="checkbox"/> FINAL		FILTERS: <input type="checkbox"/> LO CUT <input type="checkbox"/> HZ SLOPE <u>18</u>	
DISPLAY MODE: <input checked="" type="checkbox"/> GAGE <input type="checkbox"/> FLOAT <input type="checkbox"/> DEFLOAT		AMPLIFIER <input type="checkbox"/> DIRECT		INITIAL GAIN: <u>12</u> db		TRIP SENS: <u>0</u> db	
CFS I TYPE STACK: _____		GATE LENGTH: _____		RECORD REJECTION: _____		NOISE REDUCTION: _____	
SOURCE TYPE: <input checked="" type="checkbox"/> DYNAMITE <input type="checkbox"/> VIBROSEIS <input type="checkbox"/> OTHER		PATTERN: <u>inline - 1 hole</u>		NO. OF POSITIONS: _____		INLINE SPACING: _____	
RECEIVER TYPE: <u>30-0</u>		PATTERN: <u>inline</u>		NO. OF ELEMENTS: <u>18</u>		INLINE SPACING: <u>12</u>	
CONNECTION: <u>Series-Parallel</u>		RESISTANCE: <u>510</u> ohms		STAGGER: _____		LATERAL SPACING: _____	
SPREAD NO. OF GROUPS: <u>48</u>		GROUP INTERVAL: <u>330</u>		SHOTPOINT INTERVAL: <u>480</u>		FIELD: <u>6</u>	
OFFSET GROUP 1: <u>5170</u>		OFFSET GROUP 24: <u>110</u>		OFFSET GROUP 25: <u>110</u>		OFFSET GROUP 48/46: <u>5170</u>	



SHOTPOINT	TR 10		TR 10		SHOT				SPREAD		REMARKS	CORR. STACK			
	REEL NO.	REC.	REEL NO.	REC.	SIZE	DEPTH	NO.	OFFSET	DIR.	CDP SWITCH		LINE GROUPS	TR 10	TR 10	TR 10
25	751930	113			20	167	17			25	T.1 - 6+4				
26		114			20	167	18			29	T.5 - 7+4				
27		115			20	167	19			33	7.9 - 8+4				
28		116			20	167	19			37	7.12 - 9+4				
29		117			20	167	18			41	7.17 - 10+4				
30		118			20	167	15			45	7.21 - 11+4				
31		119			20	167	17			49	1+1 - 12+4				
32		120			20	167	16			53	2+1 - 13+4				
33		121			20	167	14			57	3+1 - 14+4				
34		122			20	167	10			61	4+1 - 15+4				
35		123			20	167	11			65	5+1 - 16+4				
36		124			20	167	11			69	6+1 - 17+4				
37		125			20	167	12			73	7+1 - 18+4				
38		126			20	167	12			77	8+1 - 19+4				
39		127			20	167	14			81	9+1 - 20+4				
40		128			20	167	18			13	10+1 - 21+4				
41		129			20	167	17			17	11+1 - 22+4				
42		130			20	167	18			21	12+1 - 23+4				
43		131			20	167	19			25	13+1 - 24+4				
44		132			20	167	20			29	14+1 - 25+4				

678

LAND SEISMIC RECORDING LOG

		CLIENT: <u>Husky</u>	PROSPECT: <u>NPA-A</u>	AREA: <u>Barrow</u>	LINE NO: <u>678</u>		
PARTY NO: <u>1182</u>		INST. ENG: <u>Streff-Windham</u>		DATE: <u>MO 4 DAY 16 YE 79</u>			
INSTRUMENT (9-TRACK) <input type="checkbox"/> 1 SYSTEM <input type="checkbox"/> 2 SYSTEMS		<input type="checkbox"/> 1-24 & 25-48 <input type="checkbox"/> 1-48 & 49-96		TYPE: <input type="checkbox"/> DFS III <input type="checkbox"/> DFS IV <input type="checkbox"/> OTHER		<input type="checkbox"/> 9 TRACK <input type="checkbox"/> 21 TRACK	
NO. BYTES IN HEADER REC: _____		NO. BYTES IN RECORD ID: _____		NO. BYTES PER SCAN: <u>134</u>		RECORD NUMBERS: _____	
CONFIGURATION (MAG TAPE) FIELD TRACE NOS.: <u>1-48</u>		DATA CHANNEL NOS.: <u>1-48</u>		(ON MAG TAPE)		AUXILIARY DATA: AUXILIARY CHANNEL NOS.: _____	
PARAMETER RECORD LENGTH: <u>6</u> sec.		SAMPLE RATE: <input type="checkbox"/> 1 ms. <input type="checkbox"/> 4 ms. <input type="checkbox"/> 2 ms. <input type="checkbox"/> _____ ms.		GAIN MODE: <input type="checkbox"/> INITIAL <input type="checkbox"/> FINAL		FILTERS: _____	
DISPLAY MODE: <input type="checkbox"/> FLOAT <input type="checkbox"/> DEFOAT		INITIAL GAIN: <u>1.2</u> db		TRIP SENS: <u>0</u> db		POLARITY CONVENTION: <input type="checkbox"/> POSITIVE <input type="checkbox"/> NEGATIVE	
CFS I TYPE STACK: _____		GATE LENGTH: _____		RECORD REJECTION: _____		NOISE THRESHOLD: _____	
SOURCE TYPE: <input type="checkbox"/> DYNAMITE <input type="checkbox"/> VIBROSEIS <input type="checkbox"/> OTHER		PATTERN: <u>inline-hole</u>		NO. OF POSITIONS: _____		INLINE SPACING: _____	
RECEIVER TYPE: <u>30-0</u>		PATTERN: <u>inline</u>		NO. OF ELEMENTS: <u>18</u>		INLINE SPACING: <u>12</u>	
CONNECTION: <u>Series-Parallel</u>		RESISTANCE: <u>560</u> ohms		STAGGER: _____		LENGTH: _____	
SPREAD NO. OF GROUPS: <u>48</u>		GROUP INTERVAL: <u>220</u>		SHOTPOINT INTERVAL: <u>480</u>		FOLD: <u>6</u>	
OFFSET GROUP 1: <u>5170</u>		OFFSET GROUP 24: <u>110</u>		OFFSET GROUP 25: <u>110</u>		OFFSET GROUP 48/96: <u>5170</u>	
DIAGRAMS/MISC. INFORMATION: _____							

SHOTPOINT	TR 10		TR 20		SHOT		SPREAD		REMARKS	CORR STACK				
	REEL NO.	REC.	REEL NO.	REC.	SIZE	DEPTH	NO.	OFFSET		DIR.	COP SWITCH	LINE GROUPS		
211	75119122	134			120	167	31			33	15+1 - 26+4	2		
212		135			120	167	22			33	15+1 - 26+4			COP-error
213		136			120	167	23			41	17+1 - 28+4			
214		137			120	167	24			45	18+1 - 29+4			*REC 37/38 N.G.
215		140			120	167	25			31	17+1 - 30+4	3		Recorder @ SP-2912/2913
216		143			120	167	26			35	20+1 - 31+4			H 41-43-N.G.
217		145			120	167	27			39	21+1 - 32+4			# 44
218		146			120	167	28			43	22+1 - 33+4			
219		148			120	167	29			47	23+1 - 34+4			H 47-N.G.
219		149			120	167	30			51	24+1 - 35+4			
220		150			120	167	31	180	S	55	25+1 - 36+4			
221		151			120	167	32			59	26+1 - 37+4			
222		152			120	167	33			63	27+1 - 38+4			
223		153			120	167	34			67	28+1 - 39+4			
224		155			120	167	35	440	N	71	29+1 - 40+4			H 54-N.G.
225		156			120	167	36	900	N	77	30+1 - 41+4	4		Recorder @ 41+2/41+3 Stacked on 35
226		157			120	167	37	440	S	31	31+1 - 42+4			
227		158			120	167	38			35	32+1 - 43+4			
228		159			120	167	39			39	33+1 - 44+4			
229		160			120	167	40			99	39+1 - 44+4			Stacked on SP-41

LAND SEISMIC RECORDING LOG

CLIENT: <u>Husky</u> PROSPECT: <u>NPA-A</u> AREA: <u>Barrow</u> LINE NO.: <u>678</u>	
PARTY NO.: <u>117</u> INST. ENG.: <u>Street-Windham</u> DATE: <u>MO 4 DAY 11 YR 78</u>	
INSTRUMENT (9-TRACK) <input type="checkbox"/> 1 SYSTEM <input checked="" type="checkbox"/> 2 SYSTEMS <input type="checkbox"/> 1-24 & 25-48 <input checked="" type="checkbox"/> 1-48 & 49-96 <input type="checkbox"/> ODDS <input type="checkbox"/> EVENS TYPE: <input type="checkbox"/> DFS III <input type="checkbox"/> DFS IV <input type="checkbox"/> OTHER <input type="checkbox"/> 9 TRACK <input type="checkbox"/> 21 TRACK <input type="checkbox"/> 1 SLC <input type="checkbox"/> B <input type="checkbox"/> GAPPED <input type="checkbox"/> UNGAPPED PACKING DENSITY: (10) <input type="checkbox"/> 356 BPI (11) <input type="checkbox"/> 712 BPI (12) <input type="checkbox"/> 800 BPI (13) <input type="checkbox"/> 1400 BPI	
NO. BYTES IN HEADER REC. _____ NO. BYTES IN RECORD ID. _____ NO. BYTES PER SCAN: <u>134</u> RECORD NUMBERS: <input checked="" type="checkbox"/> DEC. <input type="checkbox"/> OCT GAIN CONSTANT: <u>36</u> db INPUT IMPEDANCE: <u>200</u> ohms	
CONFIGURATION (MAG TAPE) FIELD TRACE NOS.: <u>1-48</u> DATA CHANNEL NOS.: <u>1-48</u> (ON MAG TAPE) AUXILIARY DATA: (1) _____ (2) _____ (3) _____ (4) _____ (5) _____ (6) _____ (7) _____	
PARAMETER RECORD LENGTH: <u>6</u> sec. SAMPLE RATE: <input type="checkbox"/> 1 ml. <input checked="" type="checkbox"/> 4 ms. GAIN MODE: <input type="checkbox"/> INITIAL <input type="checkbox"/> MANUAL <input type="checkbox"/> FINAL <input type="checkbox"/> OPERATE FILTERS: FREQ. <u>8</u> Hz CUT: _____ Hz SLOPE <u>18</u> FREQ. <u>128</u> Hz CUT: _____ Hz SLOPE <u>20</u> NOTCH FILTER: <input type="checkbox"/> IN <input type="checkbox"/> OUT	
DISPLAY MODE: <input type="checkbox"/> FLOAT <input type="checkbox"/> AMPLIFIER <input checked="" type="checkbox"/> TAGC <input type="checkbox"/> DEFLAT <input type="checkbox"/> DIRECT INITIAL GAIN: <u>12</u> db TRIP SENS: <u>0</u> db POLARITY CONVENTION: <input type="checkbox"/> NEGATIVE <input type="checkbox"/> POSITIVE PRESSURE INCREASE ON GEOPHONE: <input type="checkbox"/> NEGATIVE <input type="checkbox"/> POSITIVE NUMBERS ON MAG TAPE: <input type="checkbox"/> DOWNBREAK <input type="checkbox"/> UPBREAK ON DISPLAY	
CFS I TYPE STACK: _____ GATE LENGTH: _____ RECORD REJECTION: _____ NOISE REDUCTION: _____ NOISE THRESHOLD: _____ CORR. SCALING: _____ R.C.U. NORM/ALT SW	
SOURCE TYPE: <input checked="" type="checkbox"/> DYNAMIC <input type="checkbox"/> VIBROSEIS <input type="checkbox"/> OTHER PATTERN: <u>Inline-Hole</u> NO. OF POSITIONS: _____ INLINE SPACING: _____ LATERAL SPACING: _____ STAGGER: _____ LENGTH: _____ WIDTH: _____ LATERAL OFFSET: _____	
RECEIVER TYPE: <u>20-0</u> PATTERN: <u>inline</u> NO. OF ELEMENTS: <u>18</u> CONNECTION: <u>Series-Parallel</u> RESISTANCE: <u>560</u> ohms STAGGER: _____ INLINE SPACING: <u>12</u> LENGTH: _____ WIDTH: _____ LATERAL OFFSET: _____	
SPREAD NO. OF GROUPS: <u>48</u> GROUP INTERVAL: <u>220</u> SHOFPPOINT INTERVAL: <u>440</u> FOLD: <u>6</u> DIRECTION OF PROGRESSION: <u>South</u> OFFSET GROUP 1: <u>5170</u> OFFSET GROUP 25: <u>110</u> OFFSET GROUP 25: <u>110</u> OFFSET GROUP 48/90: <u>5170</u> LEADING GROUP: <u>48</u>	

DIAGRAMS/MISC. INFORMATION:

SHOTPOINT	TR 10		TR 20		SHOT		SPREAD		REMARKS	CORR STACK			
	REEL NO.	REC.	REEL NO.	REC.	SIZE	DEPTH	NO.	DIR		LINE GROUPS	TR 10	TR 20	TR 30
411	751	102	10	10	20	167	41	47	35+1 - 46+4	4			
412		162			20	167	42	51	36+1 - 47+4				
413		164			20	167	43	55	37+1 - 48+4				
414		165			20	167	44	59	38+1 - 49+4				
415		166			20	167	45	63	39+1 - 50+4				
416		167			20	167	46	67	40+1 - 51+4				
417		168			20	167	47	71	41+1 - 52+4				
418		170			20	167	48	27	42+1 - 53+4	5			
419		171			20	167	49	31	43+1 - 54+4				
501		172			20	167	50	35	44+1 - 55+4				
511		173			20	167	51	39	45+1 - 56+4				
521		174			20	167	52	43	46+1 - 57+4				
531		175			20	167	53	47	47+1 - 58+4				
541		176			20	167	54	51	48+1 - 59+4				
551		177			20	167	55	55	49+1 - 60+4				
561		178			20	167	56	59	50+1 - 61+4				
571		179			20	167	57	63	51+1 - 62+4				
581		180			20	167	58	67	52+1 - 63+4				
591		181			20	167	59	71	53+1 - 64+4				
601		182			20	167	60	75	54+1 - 65+4				
611		183			20	167	61	79	55+1 - 66+4				

E.O.L.