

LAND SEISMIC RECORDING LOG

		CLIENT: <u>Husky</u>	PROSPECT: <u>NPA-A</u>	AREA: <u>Barrow</u>	LINE NO: <u>680</u>																			
PARTY NO: <u>114</u>		INST. ENG: <u>SI-47</u>		DATE: <u>MO 4 DAY 17 YR 79</u>																				
INSTRUMENT (9-TRACK)	<input type="checkbox"/> 1 SYSTEM <input type="checkbox"/> 2 SYSTEMS	<input type="checkbox"/> 1-24 & 25-48 <input type="checkbox"/> 1-48 & 49-96	ODDS EVENS: <input type="checkbox"/>	TYPE: <input type="checkbox"/> DFS III <input type="checkbox"/> DFS IV <input type="checkbox"/> OTHER	<input type="checkbox"/> 9 TRACK <input type="checkbox"/> 21-TRACK	FORMAT: <u>A</u> SEG	<input type="checkbox"/> GAPPED <input type="checkbox"/> UNGAPPED	PACKING DENSITY: (LO) <input type="checkbox"/> 356 BPI <input type="checkbox"/> 800 BPI (HI) <input type="checkbox"/> 712 BPI <input type="checkbox"/> 1600 BPI																
	NO. BYTES IN HEADER REC.		NO. BYTES IN RECORD ID:	NO. BYTES PER SCAN: <u>124</u>	RECORD NUMBERS: <input type="checkbox"/> DEC. <input type="checkbox"/> OCT.	GAIN CONSTANT: <u>30</u> db	INPUT IMPEDANCE: <u>200</u> ohms.																	
CONFIGURATION (MAG TAPE)	FIELD TRACE NOS.: <u>117</u>			AUXILIARY DATA:			AUXILIARY CHANNEL NOS.: (1) (2) (3) (4) (5) (6) (7)																	
PARAMETER	RECORD LENGTH: <u>1</u> sec.	SAMPLE RATE: <input type="checkbox"/> 1 ms. <input type="checkbox"/> 4 ms. <input type="checkbox"/> 2 ms. <input type="checkbox"/>	GAIN MODE: <input type="checkbox"/> INITIAL <input type="checkbox"/> MANUAL <input type="checkbox"/> IFFP <input type="checkbox"/> FINAL <input type="checkbox"/> OPERATE	FILTERS: FREQ. <u>8</u> LO CUT HZ SLOPE <u>18</u>	HI CUT HZ SLOPE <u>70</u>		NOTCH FILTER: <input type="checkbox"/> IN <input type="checkbox"/> OUT																	
DISPLAY	MODE: <input type="checkbox"/> AGC <input type="checkbox"/> FLOAT <input type="checkbox"/> DEFLOAT <input type="checkbox"/> AMPLIFIER <input type="checkbox"/> DIRECT	INITIAL GAIN: <u>12</u> db	JRIP SENS: <u>0</u> db	POLARITY CONVENTION: <input type="checkbox"/> NEGATIVE <input type="checkbox"/> POSITIVE	PRESSURE INCREASE ON GEOPHONE: <input type="checkbox"/> NUMBERS ON MAG. TAPE <input type="checkbox"/> DOWNBREAK <input type="checkbox"/> UPBREAK		ON DISPLAY																	
CFS I	TYPE STACK:	GATE LENGTH:	RECORD REJECTION:	NOISE REDUCTION:	NOISE THRESHOLD:	CORR. SCALING:	R.C.U. NORM/ALT SW.																	
SOURCE	TYPE: <input type="checkbox"/> DYNAMITE <input type="checkbox"/> VIBROSEIS <input type="checkbox"/> OTHER	PATTERN: <u>inline-hole</u>	NO. OF POSITIONS:	INLINE SPACING:	LATERAL SPACING:	STAGGER:	LENGTH:	WIDTH:	LATERAL OFFSET:															
RECEIVER	CONNECTION: <u>30-0</u>	RESISTANCE: <u>400</u> ohms	CHG/ HOLE: <u>30</u>	HOLE DEPTH: <u>75</u>	SWEEP POSITION:	SWEEP START:	SWEEP END:	SWEEP LENGTH:	SWEEP TAPER:	PHASE COMP.	LATERAL SPACING:	WIDTH:	LATERAL OFFSET:											
SPREAD	NO. OF GROUPS: <u>18</u>	GROUP INTERVAL: <u>220</u>	SHOTPOINT INTERVAL: <u>850</u>	FOLD: <u>6</u>	DIRECTION OF PROGRESSION: <u>N20E</u>	OFFSET GROUP 1: <u>510</u>	GROUP 2: <u>110</u>	GROUP 3: <u>110</u>	GROUP 4: <u>110</u>	GROUP 5: <u>110</u>	GROUP 6: <u>110</u>	GROUP 7: <u>110</u>	GROUP 8: <u>110</u>	GROUP 9: <u>110</u>	GROUP 10: <u>110</u>	GROUP 11: <u>110</u>	GROUP 12: <u>110</u>	GROUP 13: <u>110</u>	GROUP 14: <u>110</u>	GROUP 15: <u>110</u>	GROUP 16: <u>110</u>	GROUP 17: <u>110</u>	GROUP 18: <u>110</u>	LEADING GROUP: <u>48</u>

DIAGRAMS/MISC. INFORMATION: T.R. 114 7#47 #104-4031-11-11-79

SHOTPOINT	TR. <u>114</u> to <u>47</u>		TR. <u>114</u> to <u>47</u>		SHOT										SPREAD		REMARKS:	CORR. STACK			
	REEL NO.	REC.	REEL NO.	REC.	SIZE	DEPTH	NO.	OFFSET	DIR.	CDP SWITCH	LINE GROUPS		SET UP	TR 1-48	TR 24-52	TR 48-52		TR 24-52			
1	7511933	105			20	67	1				49	T.1 - 6+4	1		Recorder @ SP-1						
2		106			20	67	2				53	T.5 - 7+4									
3		107			20	67	3				57	T.9 - 8+4									
4		108			20	67	4				61	T.13 - 9+4									
5		109			20	67	5				65	T.17 - 10+4									
6		110			20	67	6				69	T.21 - 11+4									
7		111			20	67	7				73	T.1 - 12+4									
8		112			20	67	8				77	2+1 - 13+4									
9		113			20	67	9				81	3+1 - 14+4									
10		114			20	67	10				85	4+1 - 15+4									
11		115			20	67	11				89	5+1 - 16+4									
12		116			20	67	12				93	6+1 - 17+4									
13		117			20	67	13	4th	9		97	7+1 - 18+4									
14		118			20	67	14				29	8+1 - 19+4	2	Recorder @ SP 19							
15		119			20	67	15				33	9+1 - 20+4									
16		120			20	67	16				37	10+1 - 21+4									
17		121			20	67	17				49	11+1 - 22+4									
18		122			20	67	18				45	12+1 - 23+4									
19		123			20	67	19				49	13+1 - 24+4									
20		124			20	67	20				53	14+1 - 25+4									

LAND SEISMIC RECORDING LOG



	CLIENT: <u>14283</u>	PROSPECT: <u>NPR-A</u>	AREA: <u>Borixon</u>	LINE NO: <u>680</u>										
	PARTY NO: <u>117</u>	INST. ENG: <u>Small</u>		DATE: <u>MO 4 DAY 17 YE 77</u>										
INSTRUMENT (9-TRACK)	<input type="checkbox"/> 1 SYSTEM <input type="checkbox"/> 2 SYSTEMS	<input type="checkbox"/> T-24 & 25-48 <input type="checkbox"/> 1-48 & 49-96	ODDS & EVENS	TYPE: <input type="checkbox"/> DFS III <input type="checkbox"/> DFS IV <input type="checkbox"/> OTHER	<input type="checkbox"/> 9 TRACK <input type="checkbox"/> 21 TRACK	FORMAT: <u>SEG</u>	<input type="checkbox"/> GAPPED <input type="checkbox"/> UNGAPPED	PACKING DENSITY: (L) <input type="checkbox"/> 356 BPI <input type="checkbox"/> 800 BPI	(H) <input type="checkbox"/> 712 BPI <input type="checkbox"/> 1600 BPI					
	NO. BYTES IN HEADER REC.	NO. BYTES IN RECORD ID: <u>1</u>	NO. BYTES PER SCAN: <u>137</u>	RECORD NUMBERS: <input type="checkbox"/> DEC. <input type="checkbox"/> OCT.	GAIN CONSTANT: <u>2.0</u> db	INPUT IMPEDANCE: <u>200</u> ohms	(1)	(2)	(3)	(4)	(5)	(6)	(7)	
CONFIGURATION (MAG TAPE)	FIELD TRACE NOS.: <u>1-47</u>			DATA CHANNEL NOS.: <u>1-48</u>			AUXILIARY DATA: AUXILIARY CHANNEL NOS.: <u>1-4</u>							
PARAMETER	RECORD LENGTH: <u>1</u> sec.	SAMPLE RATE: <input type="checkbox"/> 1 ml. <input type="checkbox"/> 4 ml. <input type="checkbox"/> 2 ml. <input type="checkbox"/> 8 ml.	GAIN MODE: <input type="checkbox"/> INITIAL <input type="checkbox"/> MANUAL <input type="checkbox"/> TRIP <input type="checkbox"/> FINAL <input type="checkbox"/> OPERATE	FILTERS: FREQ. <u>4</u> LO CUT HZ SLOPE <u>12</u>		HI CUT HZ SLOPE <u>70</u>		NOTCH FILTER: <input type="checkbox"/> IN <input type="checkbox"/> OUT		PRESSURE INCREASE ON GEOPHONE: <input type="checkbox"/> NEGATIVE <input type="checkbox"/> POSITIVE			NUMBERS ON MAG. TAPE <input type="checkbox"/> DOWNBREAK <input type="checkbox"/> UPBREAK	ON DISPLAY
DISPLAY	MODE: <input type="checkbox"/> AGC <input type="checkbox"/> FLOAT <input type="checkbox"/> AMPLIFIER <input type="checkbox"/> D-FLOAT <input type="checkbox"/> DIRECT	INITIAL GAIN: <u>1.0</u> db	TRIP SENS.: <u>0</u> db	NOISE REDUCTION: <input type="checkbox"/> RECORD REJECTION	NOISE THRESHOLD:	CORR. SCALING:	R.C.U. NORM/ALT SW.							
CFS I	TYPE STACK:	GATE LENGTH:	PATTERN: <u>In-line</u>	NO. OF POSITIONS:	INLINE SPACING:	LATERAL SPACING:	STAGGER:	LENGTH:	WIDTH:	LATERAL OFFSET:				
SOURCE	<input type="checkbox"/> DYNAMITE <input type="checkbox"/> VIBROSEIS <input type="checkbox"/> OTHER	CHG/HOLE: <u>20</u>	HOLE DEPTH: <u>75</u>	SWEEP POSITION:	SWEEP START:	SWEEP END:	SWEEP LENGTH:	SWEEP TAPER:	PHASE COMP.	RECEIVER				
RECEIVER	TYPE: <u>20-D</u>	PATTERN: <u>In-line</u>	NO. OF ELEMENTS: <u>18</u>	INLINE SPACING: <u>12</u>	LATERAL SPACING:	WIDTH:	LATERAL OFFSET:	CONNECTION: <u>Series-Parallel</u>	RESISTANCE: <u>560</u> ohms	STAGGER:	LENGTH:	WIDTH:	LATERAL OFFSET:	
SPREAD	NO. OF GROUPS: <u>48</u>	GROUP INTERVAL: <u>220</u>	SHOTPOINT INTERVAL: <u>810</u>	FOLD: <u>6</u>	DIRECTION OF PROGRESSION: <u>North</u>	LEADING GROUP: <u>46</u>	OFFSET GROUP: <u>5170</u>	OFFSET GROUP 48/96: <u>5170</u>	DIAGRAMS/MISC. INFORMATION:					

SHOTPOINT	TR. 1 to		TR. 2 to		SHOT		SPREAD			REMARKS	CORR STACK					
	REEL NO.	REC.	REEL NO.	REC.	SIZE	DEPTH	NO.	OFFSET	DIR.		CDP SWITCH	LINE GROUPS	SET UP	TR 1-24	TR 25-48	TR 49-72
21	15	123			20	67	21			57	15+1 - 26+4	0				
22		124			20	67	22			61	16+1 - 27+4					
23		127			20	67	23			65	17+1 - 28+4					
24		128			20	67	24			69	18+1 - 29+4					
25		129			20	67	25			73	19+1 - 30+4					
26		130			20	67	26			77	20+1 - 31+4					
27		131			20	67	27			27	21+1 - 32+4					
28		132			20	67	28			31	22+1 - 33+4					
29		133			20	67	29			35	23+1 - 34+4					
30		134			20	67	30			39	24+1 - 35+4					
31		135			20	67	31			43	25+1 - 36+4					
32		SKIPPED			20	67	32			47	26+1 - 37+4					
33		138			20	67	33	500 E		51	27+1 - 38+4					
34		139			20	67	34			55	28+1 - 39+4					
35		140			20	67	35			59	29+1 - 40+4					
36		141			20	67	36			27	30+1 - 41+4					
37		142			20	67	37			31	31+1 - 42+4					
38		143			20	67	38			35	32+1 - 43+4					
39		144			20	67	39			39	33+1 - 44+4					
40		145			20	67	40			43	34+1 - 45+4					

D.F.S. did not record this shot

Recorder @ 41.2/41.3

LAND SEISMIC RECORDING LOG

	CLIENT: <u>Hess</u>	PROSPECT: <u>APR A</u>	AREA: <u>Bear</u>	LINE NO.: <u>680</u>						
PARTY NO.: <u>102</u>		INST. ENG.: <u>S. [unclear]</u>		DATE: <u>MO 4 DAY 14 YR 77</u>						
INSTRUMENT (9-TRACK)	<input type="checkbox"/> 1 SYSTEM <input type="checkbox"/> 2 SYSTEMS	<input type="checkbox"/> 1-24 & 25-48 <input type="checkbox"/> 1-48 & 49-96	<input type="checkbox"/> ODDS <input type="checkbox"/> EVENS	TYPE: <input type="checkbox"/> DFS III <input type="checkbox"/> DFS III	<input type="checkbox"/> 9 TRACK <input type="checkbox"/> 21 TRACK	FORMAT: <u>1</u> SEG. <u>1</u>	<input type="checkbox"/> GAPPED <input type="checkbox"/> UNGAPPED	PACKING DENSITY: (L) <input type="checkbox"/> 356 BPI <input type="checkbox"/> 800 BPI	(M) <input type="checkbox"/> 712 BPI <input type="checkbox"/> 1000 BPI	
	NO. BYTES IN HEADER REC.:	NO. BYTES IN RECORD ID:	NO. BYTES PER SCAN: <u>134</u>	RECORD NUMBERS: <input type="checkbox"/> DEC. <input type="checkbox"/> OCT.	GAIN CONSTANT: <u>36</u> db	INPUT IMPEDANCE: <u>200</u> ohms	AUXILIARY DATA: (1) (2) (3) (4) (5) (6) (7)			
CONFIGURATION (MAG TAPE)	FIELD TRACE NOS.: <u>1-45</u>			AUXILIARY CHANNEL NOS.:						
	DATA CHANNEL NOS.: <u>1-48</u> (ON MAG TAPE)									
PARAMETER	RECORD LENGTH: <u>1</u> sec.	SAMPLE RATE: <input type="checkbox"/> 1 ms. <input type="checkbox"/> 4 ms. <input type="checkbox"/> 2 ms. <input type="checkbox"/> ms.	GAIN MODE: <input type="checkbox"/> INITIAL <input type="checkbox"/> FINAL	<input type="checkbox"/> MANUAL <input type="checkbox"/> OPERATE	FILTERS: FREQ. <u>8</u>	LO CUT HZ SLOPE <u>12</u>	H1 CUT HZ SLOPE <u>70</u>	NOTCH FILTER: <input type="checkbox"/> IN <input type="checkbox"/> OUT		
DISPLAY	MODE: <input type="checkbox"/> FLOAT <input type="checkbox"/> AMPLIFIER <input type="checkbox"/> AGC <input type="checkbox"/> DEFLOAT <input type="checkbox"/> DIRECT	INITIAL GAIN: <u>24</u> db	TRIP SENS.: <u>0</u> db	POLARITY CONVENTION: <input type="checkbox"/> NEGATIVE <input type="checkbox"/> POSITIVE	PRESSURE INCREASE ON GEOPHONE: <input type="checkbox"/> NEGATIVE <input type="checkbox"/> POSITIVE	NUMBERS ON MAG. TAPE: <input type="checkbox"/> DOWNBREAK <input type="checkbox"/> UPBREAK		ON DISPLAY: <input type="checkbox"/> DOWNBREAK <input type="checkbox"/> UPBREAK		
CFS I	TYPE STACK:	GATE LENGTH:	RECORD REJECTION:	NOISE REDUCTION:	NOISE THRESHOLD:	CORR. SCALING:	R.C.U. NORM./ALT SW.			
SOURCE	TYPE: <input type="checkbox"/> DYNAMITE <input type="checkbox"/> VIBROSEIS <input type="checkbox"/> OTHER	PATTERN: <u>inline-hole</u>	NO. OF POSITIONS:	INLINE SPACING:	LATERAL SPACING:	STAGGER:	LENGTH:	WIDTH:	LATERAL OFFSET:	
	CHG/ MOLE: <u>20</u>	MOLE DEPTH: <u>75</u>	SWEEP POSITION:	SWEEP START:	SWEEP END:	SWEEP LENGTH:	SWEEP TAPER:	PHASE COMP.		
RECEIVER	TYPE: <u>20-D</u>	PATTERN: <u>inline</u>	NO. OF ELEMENTS: <u>18</u>	INLINE SPACING: <u>12</u>	LATERAL SPACING:	STAGGER:	LENGTH:	WIDTH:	LATERAL OFFSET:	
	CONNECTION: <u>See 103-Partial</u>	RESISTANCE: <u>520</u> ohms	STAGGER:	LENGTH:	WIDTH:	LATERAL OFFSET:				
SPREAD	NO. OF GROUPS: <u>48</u>	GROUP INTERVAL: <u>200</u>	SHOTPOINT INTERVAL: <u>410</u>	FOLD: <u>1</u>	DIRECTION OF PROGRESSION: <u>NORTH</u>	LEADING GROUP: <u>118</u>				
	OFFSET GROUP 1: <u>5170</u>	OFFSET GROUP 2: <u>110</u>	OFFSET GROUP 3: <u>110</u>	OFFSET GROUP 4: <u>5170</u>						


DIAGRAMS/MISC. INFORMATION:

7841

#180 - test - finished

SHOTPOINT	TR. 1 to 12		TR. 13 to 24		TR. 25 to 36		TR. 37 to 48		SHOT		SPREAD		REMARKS	CORR. STACK			
	REEL NO.	REC.	REEL NO.	REC.	SIZE	DEPTH	NO.	OFFSET	DIR	COP SWITCH	LINE GROUPS	SET UP		TR 1-12	TR 13-24	TR 25-36	TR 37-48
61	25193	181			20	167	1			25	55+1 - 66+4	1	Noisy Traces - Due to Bare Ice				
62		182			20	167	2			29	56+1 - 67+3		Recorder @ SP-67				
63		183			20	167	3			33	57+1 - 68+4						
64		184			20	167	4			37	58+1 - 69+4						
65		185			20	167	5			41	59+1 - 70+4						
66		186			20	167	6			45	60+1 - 71+4						
67		187			20	167	7			49	61+1 - 72+4						
68		188			20	167	8			53	62+1 - 73+4						
69		189			20	167	9			57	63+1 - 74+4						
70		190			20	167	10			61	64+1 - 75+4						
71		191			20	167	11	440	S	65	65+1 - 76+4						
72		192			20	167	12			69	66+1 - 77+4						
73		193			20	167	13			73	67+1 - 78+4						
74		194			20	167	14	220	S	77	68+1 - 79+4						
75		195			20	167	15			85	70+1 - 81+4		Stacked on 74 offset 220' same				
76		196			20	167	16	660	W	85	70+1 - 81+4						
77		197			20	167	17			89	71+1 - 82+4						
78		198			20	167	18			27	72+1 - 83+4	2	Recorder @ 83+2/43+3				
79		199			20	167	19			31	73+1 - 84+4						
80		200			20	167	20			35	74+1 - 85+4						



LAND SEISMIC RECORDING LOG

	CLIENT: <i>NA</i>	PROSPECT: <i>NPA-A</i>	AREA: <i>Basson</i>	LINE NO: 680						
	PARTY NO: <i>200</i>	INST. ENG: <i>3100</i>		DATE: <i>4 DAY 19 YR 77</i>						
INSTRUMENT (9-TRACK)	<input type="checkbox"/> 1 SYSTEM <input type="checkbox"/> 2 SYSTEMS	<input type="checkbox"/> 1-24 & 25-48 <input type="checkbox"/> 1-48 & 49-96	ODDS <input type="checkbox"/> EVENS	TYPE: <input type="checkbox"/> DFS III <input type="checkbox"/> DFS IV <input type="checkbox"/> OTHER	<input type="checkbox"/> 9 TRACK <input type="checkbox"/> 21 TRACK	FORMAT: SEG <i>12</i>	<input type="checkbox"/> GAPPED <input type="checkbox"/> UNGAPPED	PACKING DENSITY:	(LO) <input type="checkbox"/> 356 BPI <input type="checkbox"/> 800 BPI	(HI) <input type="checkbox"/> 712 BPI <input type="checkbox"/> 1600 BPI
	NO. BYTES IN HEADER REC:	NO. BYTES IN RECORD ID:	NO. BYTES PER SCAN: <i>130</i>	RECORD NUMBERS:	<input type="checkbox"/> DEC. <input type="checkbox"/> OCT.	GAIN CONSTANT: <i>70</i> db	INPUT IMPEDANCE: _____ ohms			
CONFIGURATION (MAG TAPE)	FIELD TRACE NOS.: <i>1-12</i>	DATA CHANNEL NOS.: <i>1-12</i>		(ON MAG TAPE)			AUXILIARY DATA: (1) _____ (2) _____ (3) _____ (4) _____ (5) _____ (6) _____ (7) _____			
PARAMETER	RECORD LENGTH: <i>1</i> sec	SAMPLE RATE: <input type="checkbox"/> 1 ms. <input type="checkbox"/> 4 ms. <input type="checkbox"/> 2 ms. <input type="checkbox"/> _____ ms.	GAIN MODE: <input type="checkbox"/> INITIAL <input type="checkbox"/> IFP <input type="checkbox"/> FINAL <input type="checkbox"/> OPERATE	FILTERS: FREQ. <i>1</i> LO CUT HZ SLOPE <i>14</i>		HI CUT HZ SLOPE <i>70</i>		NOTCH FILTER: <input type="checkbox"/> IN <input type="checkbox"/> OUT		
DISPLAY	MODE: <input type="checkbox"/> FLOAT <input type="checkbox"/> AMPLIFIER <input type="checkbox"/> AGC <input type="checkbox"/> DEFOAT <input type="checkbox"/> DIRECT	INITIAL GAIN: <i>70</i> db	TRIP SENS: <i>0</i> db	POLARITY CONVENTION: <input type="checkbox"/> PRESSURE INCREASE ON GEOPHONE <input type="checkbox"/> NEGATIVE <input type="checkbox"/> POSITIVE		NUMBERS ON ON MAG. TAPE		<input type="checkbox"/> DOWNBREAK <input type="checkbox"/> UPBREAK		ON DISPLAY
CFS I	TYPE STACK:	GATE LENGTH:	RECORD REJECTION:	NOISE REDUCTION:		NOISE THRESHOLD:		CORR. SCALING:		R.C.U. NORM/ALT SW.
SOURCE	TYPE: <input type="checkbox"/> DYNAMITE <input type="checkbox"/> VIBROSEIS <input type="checkbox"/> OTHER	PATTERN: <i>50 line - 1 hole</i>	NO. OF POSITIONS:	INLINE SPACING:	LATERAL SPACING:	STAGGER:	LENGTH:	WIDTH:	LATERAL OFFSET:	
RECEIVER	TYPE: <i>74-0</i>	PATTERN: <i>50 line</i>	NO. OF ELEMENTS: <i>11</i>	INLINE SPACING: <i>12</i>	LATERAL SPACING:	STAGGER:	LENGTH:	WIDTH:	LATERAL OFFSET:	
SPREAD	CONNECTION: <i>Spring Parallel</i>	RESISTANCE: <i>500</i> ohms	SWEEP POSITION:	SWEEP START:	SWEEP END:	SWEEP LENGTH:	SWEEP TAPER:	PHASE COMP.		
	NO. OF GROUPS: <i>47</i>	GROUP INTERVAL: <i>220</i>	SHOTPOINT INTERVAL: <i>880</i>	FOLD: <i>6</i>		DIRECTION OF PROGRESSION: <i>N-114</i>		LEADING GROUP: <i>47</i>		
	OFFSET GROUP 1: <i>5170</i>	OFFSET GROUP 2: <i>110</i>	OFFSET GROUP 25: <i>110</i>	OFFSET GROUP 48/96: <i>5170</i>						

DIAGRAMS/MISC. INFORMATION:

SHOTPOINT	TR. _____ TO _____		TR. _____ TO _____		SHOT				SPREAD				REMARKS:	CORR STACK			
	REEL NO.	REC.	REEL NO.	REC.	SIZE	DEPTH	NO.	OFFSET	DIR.	CDP SWITCH	LINE GROUPS			HY.	TR. 48	REC.	HY.
81	751933	201			20	167	21	440	5	39	75+1	- 80+4	2				
82		202			20	167	22			43	76+1	- 87+4					
83		203			20	167	23			47	77+1	- 88+4					
84		204			20	167	24			51	78+1	- 89+4					
85		205			20	167	25			55	79+1	- 90+4					
86		206			20	167	26			59	80+1	- 91+4					
87		207			20	167	27			63	81+1	- 92+1					
88		208			20	167	28			67	82+1	- 93+1					
89		209			20	167	29			71	83+1	- 94+4					
90		210			20	167	30			27	84+1	- 95+1	3	Recorder @ 95+2/95+3			
91		211			20	167	31			31	85+1	- 96+4					
92		212			20	167	32			35	86+1	- 97+4					
93	751934	213			20	167	33			39	87+1	- 98+4		Tape Change # 213 N.G.			
94		214			20	167	34			43	88+1	- 99+4					
95		215			20	167	35			47	89+1	- 100+4					
96		216			20	167	36			51	90+1	- 101+4					
97		217			20	167	37			55	91+1	- 102+4					
98		218			20	167	38			59	92+1	- 103+4					
99		219			20	167	39			63	93+1	- 104+4					
100		220			20	167	40			67	94+1	- 105+4					

LAND SEISMIC RECORDING LOG

	CLIENT: <u>Hughes</u>	PROSPECT: <u>NPR-A</u>	AREA: <u>No. 200</u>	LINE NO: <u>680</u>					
PARTY NO: <u>112</u>		INST. ENG: <u>Stieff</u>		DATE: <u>MO 11 DAY 17 YR 79</u>					
INSTRUMENT (9-TRACK)	<input type="checkbox"/> 1 SYSTEM <input type="checkbox"/> 2 SYSTEMS	<input type="checkbox"/> 1-24 & 25-48 <input type="checkbox"/> 1-48 & 49-96	ODDS <input type="checkbox"/> EVENS	TYPE: <input type="checkbox"/> DFS III <input type="checkbox"/> DFS IV	<input type="checkbox"/> 9 TRACK <input type="checkbox"/> 21 TRACK	FORMAT: <u>SEG</u>	<input type="checkbox"/> GAPPED <input type="checkbox"/> UNGAPPED	PACKING DENSITY: (L) <input type="checkbox"/> 356 BPI <input type="checkbox"/> 600 BPI (M) <input type="checkbox"/> 712 BPI <input type="checkbox"/> 1600 BPI	
	NO. BYTES IN HEADER REC.:		NO. BYTES IN RECORD ID.:	NO. BYTES PER SCAN: <u>174</u>	RECORD NUMBERS: <input type="checkbox"/> DEC. <input type="checkbox"/> OCT.	GAIN CONSTANT: <u>32</u> db	INPUT IMPEDANCE: <u>200</u> ohms.		
CONFIGURATION (MAG TAPE)	FIELD TRACE NOS.: <u>1-48</u>			AUXILIARY DATA:			AUXILIARY CHANNEL NOS.:		
PARAMETER	RECORD LENGTH: <u>1</u> sec.	SAMPLE RATE: <input type="checkbox"/> 1 ms. <input type="checkbox"/> 4 ms. <input type="checkbox"/> 2 ms. <input type="checkbox"/> 8 ms.	GAIN MODE: <input type="checkbox"/> INITIAL <input type="checkbox"/> MANUAL <input type="checkbox"/> FINAL <input type="checkbox"/> OPERATE	FILTERS: FREQ. <u>4</u> LO CUT HZ SLOPE <u>18</u>		HI CUT HZ SLOPE <u>70</u>		NOTCH FILTER: <input type="checkbox"/> IN <input type="checkbox"/> OUT	
DISPLAY	MODE: <input type="checkbox"/> XDC <input type="checkbox"/> DEFOAT <input type="checkbox"/> DIRECT	AMPLIFIER <input type="checkbox"/> DIRECT	INITIAL GAIN: <u>24</u> db	JRIP SENS: <u>0</u> db	POLARITY CONVENTION: <input type="checkbox"/> NEGATIVE <input type="checkbox"/> POSITIVE	PRESSURE INCREASE ON GEOPHONE: <input type="checkbox"/> NEGATIVE <input type="checkbox"/> POSITIVE		NUMBERS ON MAG. TAPE <input type="checkbox"/> DOWNBREAK <input type="checkbox"/> UPBREAK } ON DISPLAY	
CFS I	TYPE STACK:	GATE LENGTH:	RECORD REJECTION:	NOISE REDUCTION:	NOISE THRESHOLD:	CORR. SCALING:		R.C.U. NORM/ALT SW.	
SOURCE	TYPE: <input type="checkbox"/> DYNAMITE <input type="checkbox"/> VIBROSEIS <input type="checkbox"/> OTHER	PATTERN: <u>inlac-hole</u>	NO. OF POSITIONS:	INLINE SPACING:	LATERAL SPACING:	STAGGER:	LENGTH:	WIDTH:	LATERAL OFFSET:
RECEIVER	TYPE: <u>20 A</u>	PATTERN: <u>inlac</u>	NO. OF ELEMENTS: <u>12</u>	INLINE SPACING: <u>12</u>	LATERAL SPACING:	STAGGER:	LENGTH:	WIDTH:	LATERAL OFFSET:
SPREAD	CONNECTION: <u>Series-Parallel</u>	RESISTANCE: <u>50</u> ohms	SWEEP POSITION:	SWEEP START:	SWEEP END:	SWEEP LENGTH:	SWEEP TAPER:	PHASE COMP:	
	NO. OF GROUPS: <u>48</u>	GROUP INTERVAL: <u>220</u>	SHOTPOINT INTERVAL: <u>440</u>	FOLD: <u>6</u>	DIRECTION OF PROGRESSION: <u>Parallel</u>	OFFSET GROUP 1: <u>5170</u>	OFFSET GROUP 48/96: <u>5770</u>	LEADING GROUP: <u>110</u>	

DIAGRAMS/MISC. INFORMATION:

SHOTPOINT	TR. _____ to _____		TR. _____ to _____		SHOT				SPREAD			REMARKS:	CORR. STACK				
	REEL NO.	REC.	REEL NO.	REC.	SIZE	DEPTH	NO.	OFFSET	DIR.	CDP SWITCH	LINE GROUPS		SET UP	TR 1-48	TR 49-96	REC.	REC.
101	715	934	222		20	67	41			71	9541 - 10644	3					
102			223		20	67	42			27	9611 - 10714	4	Recorder @ 10712/10713				
103			224		20	67	43			31	9711 - 10814						
104			225		20	67	44			35	9811 - 10917						
105			226		20	67	45	440	5	39	9911 - 11017						
106			227		20	67	46			43	10011 - 11114						
107			228		20	67	47			47	10111 - 11214		Clock error in Cameras (off 2040 Sec)				
108			229		20	67	48			51	10211 - 11317						
109			230		20	67	49			55	10311 - 11417						
110			231		20	67	50			59	10411 - 11517						
111			232		20	67	51			63	10511 - 11620						
112			233		20	67	52			67	10611 - 11721						