



# LAND SEISMIC RECORDING LOG

CLIENT: <b>Husky</b>		PROSPECT: <b>NAR-A</b>		AREA: <b>Barron</b>		LINE NO: <b>682</b>					
PARTY NO: <b>1183</b>		INST. ENG: <b>Street</b>		DATE: <b>4</b>		MO: <b>4</b>		DAY: <b>30</b>		YEAR: <b>79</b>	
INSTRUMENT: <input type="checkbox"/> 1 SYSTEM <input type="checkbox"/> 2 SYSTEMS		<input type="checkbox"/> 1-24 & 25-48 <input type="checkbox"/> 1-48 & 49-96		TYPE: <input type="checkbox"/> DFS III <input type="checkbox"/> DFS IV <input type="checkbox"/> OTHER		<input type="checkbox"/> 1 TRACK <input type="checkbox"/> 2 TRACK		FORMAT: <b>B</b>		<input type="checkbox"/> GAPPED <input type="checkbox"/> UNGAPPED	
NO. BYTES IN HEADER REC:		NO. BYTES IN RECORD ID:		NO. BYTES PER SCAN: <b>134</b>		RECORD NUMBERS:		<input type="checkbox"/> DEC <input type="checkbox"/> OCT		GAIN CONSTANT: (1) (2) (3) (4) (5) (6)	
CONFIGURATION (MAG TAPE)		FIELD TRACE NOS.: <b>1-48</b>		DATA CHANNEL NOS.: <b>1-48</b>		AUXILIARY DATA:		AUXILIARY CHANNEL NOS.:		(ON MAG TAPE)	
PARAMETER		RECORD LENGTH: <b>6</b>		SAMPLE RATE: <input type="checkbox"/> 1 sec <input type="checkbox"/> 4 sec		GAIN MODE: <input type="checkbox"/> INITIAL <input type="checkbox"/> MANUAL <input type="checkbox"/> OPERATE		FILTERS:		LO CUT: <b>1X</b>	
DISPLAY		MODE: <input type="checkbox"/> FLOAT <input type="checkbox"/> AMPLIFIER <input type="checkbox"/> DIRECT		INITIAL GAIN: <b>12</b>		TRIP SENS: <b>0</b>		POLARITY CONVENTION:		PRESSURE INCREASE ON GEOPHONE:	
CFS I		TYPE STACK:		GATE LENGTH:		RECORD REJECTION:		NOISE REDUCTION:		NOISE THRESHOLD:	
SOURCE		TYPE: <input type="checkbox"/> DYNAMITE <input type="checkbox"/> VIBROSEIS <input type="checkbox"/> OTHER		PATTERN: <b>Inline - 1 hole</b>		NO. OF POSITIONS:		INLINE SPACING:		LATERAL SPACING:	
RECEIVER		TYPE: <b>20-0</b>		PATTERN: <b>inline</b>		NO. OF ELEMENTS: <b>12</b>		INLINE SPACING: <b>12</b>		LATERAL SPACING:	
SPREAD		CONNECTION: <b>Series-Parallel</b>		RESISTANCE: <b>500</b>		STAGGER:		LENGTH:		WIDTH:	
NO. OF GROUPS: <b>48</b>		GROUP INTERVAL: <b>220</b>		SHOTPOINT INTERVAL: <b>980</b>		FOLD: <b>6</b>		DIRECTION OF PROGRESSION: <b>South North</b>		LEADING GROUP: <b>48</b>	
TYPE OFFSET GROUP 1: <b>5170</b>		OFFSET GROUP 2: <b>110</b>		OFFSET GROUP 25: <b>110</b>		OFFSET GROUP 48/90: <b>5170</b>		PHASE COMP:		LATERAL OFFSET:	

DIAGRAMS/MISC. INFORMATION:

SHOTPOINT #	FR		TR		SHOT				SPREAD				REMARKS	CORR STACK		
	REEL NO.	SEC.	REEL NO.	SEC.	SIZE	DEPTH	NO.	OFFSET	DIR.	COR SWITCH	LINE GROUPS			HT.	HT.	HT.
121	71	17	45	316	20	167	21	11	53	17+1	-28+4	3	Stacked on 19			
122					20	167	22	11	45	18+1	-26+4		Stacked on 23 offset 220 S # 57 N.O.			
123					20	167	23	11	53	17+1	-28+4					
124					20	167	24	11	57	18+1	-28+4					
125					20	167	25	11	61	17+1	-30+4					
126					20	167	26	11	29	20+1	-21+4	4	Recorder @ SP-31			
127					20	167	27	11	33	21+1	-22+4					
128					20	167	28	11	37	22+1	-33+4					
129					20	167	29	11	41	23+1	-34+4					
130					20	167	30	11	45	24+1	-35+4					
131					20	167	31	11	49	25+1	-36+4		# 47-N.G.			
132					20	167	32	11	53	26+1	-37+4					
133					20	167	33	11	57	27+1	-38+4					
134					20	167	34	11	61	28+1	-39+4					
135					20	167	35	11	65	29+1	-40+4					
136					20	167	36	11	69	30+1	-41+4					
137					20	167	37	11	73	31+1	-42+4		# 54-N.G.			
138					20	167	38	11	29	32+1	-43+4	5	Recorder @ SP-43			
139					20	167	39	11	33	33+1	-44+4					
140					20	167	40	660	37	34+1	-45+4		# 59-N.G.			

# LAND SEISMIC RECORDING LOG

CLIENT: <u>Hush</u>		PROSPECT: <u>NPRA</u>		AREA: <u>Barrow</u>		LINE NO: <u>682</u>					
PARTY NO: <u>1182</u>		INST. ENG: <u>Stieff</u>		DATE: <u>4 OCT 30 1979</u>		MO: <u>4</u>		DAY: <u>30</u>		YEAR: <u>79</u>	
INSTRUMENT (9-TRACK)		<input type="checkbox"/> 1 SYSTEM <input checked="" type="checkbox"/> 2 SYSTEMS <input type="checkbox"/> 1-24 & 25-48 <input type="checkbox"/> 1-48 & 49-96		TYPE: <input type="checkbox"/> DFS III <input type="checkbox"/> DFS IV <input type="checkbox"/> OTHER		<input checked="" type="checkbox"/> 9 TRACK <input type="checkbox"/> 21 TRACK		FORMAT: <u>B</u> <input type="checkbox"/> GAPPED <input type="checkbox"/> UNGAPPED		BACKING DENSITY: (1) <u>110</u> (2) <u>354 BPI</u> (3) <u>400 BPI</u> (4) <u>712 BPI</u> (5) <u>LAGO BPI</u>	
NO. BYTES IN HEADER REC:		NO. BYTES IN RECORD ID:		NO. BYTES PER SCAN: <u>124</u>		RECORD NUMBERS: <u>DEC</u> <input type="checkbox"/> OCT		GAIN CONSTANT: <u>36</u> db		INPUT IMPEDANCE: <u>200</u> ohms	
CONFIGURATION (MAG TAPE)		FIELD TRACE NOS.:		DATA CHANNEL NOS.:		AUXILIARY DATA:		AUXILIARY CHANNEL NOS.:			
PARAMETER		RECORD LENGTH: <u>6</u> sec		SAMPLE RATE: <input type="checkbox"/> 1 sec <input type="checkbox"/> 4 ms		GAIN MODE: <input type="checkbox"/> INITIAL <input type="checkbox"/> MANUAL <input type="checkbox"/> OPERATE		FILTERS: FREQ: <u>8</u> LO CUT HZ SLOPE: <u>180</u> HI CUT HZ SLOPE: <u>70</u>		<input type="checkbox"/> IN FILTER <input type="checkbox"/> OUT FILTER	
DISPLAY		<input checked="" type="checkbox"/> ADC <input type="checkbox"/> FLOAT <input type="checkbox"/> DEFOAT <input type="checkbox"/> DIRECT		INITIAL GAIN: <u>12</u> db		TRIP SENS: <u>0</u> db		POLARITY CONVENTION: <input type="checkbox"/> NEGATIVE <input checked="" type="checkbox"/> POSITIVE		PRESSURE INCREASE ON GEOPHONE: <input type="checkbox"/> NEGATIVE <input checked="" type="checkbox"/> POSITIVE NUMBERS ON MAG. TAPE: <input type="checkbox"/> DOWNBREAK <input type="checkbox"/> UPBREAK ON DISPLAY: <input type="checkbox"/> DOWNBREAK <input type="checkbox"/> UPBREAK	
CFS I		TYPE STACK:		GATE LENGTH:		RECORD REJECTION:		NOISE REDUCTION:		NOISE THRESHOLD:	
SOURCE		TYPE: <input checked="" type="checkbox"/> DYNAMITE <input type="checkbox"/> VIBROSEIS <input type="checkbox"/> OTHER		PATTERN: <u>Inline-Hole</u>		NO. OF POSITIONS:		INLINE SPACING:		LATERAL SPACING:	
RECEIVER		TYPE: <u>20-R</u>		PATTERN: <u>Inline</u>		NO. OF ELEMENTS: <u>18</u>		INLINE SPACING: <u>12</u>		LATERAL SPACING:	
SPREAD		CONNECTION: <u>Series-Parallel</u>		RESISTANCE: <u>560</u> ohms		STAGGER:		LENGTH:		WIDTH:	
NO. OF GROUPS: <u>48</u>		GROUP INTERVAL: <u>320</u>		SHOTPOINT INTERVAL: <u>880</u>		FIELD: <u>6</u>		DIRECTION OF PROGRESSION: <u>NOR+L</u>		LEADING GROUP: <u>48</u>	
OFFSET GROUP 1: <u>5170</u>		GROUP 24: <u>110</u>		OFFSET GROUP 25: <u>110</u>		OFFSET GROUP 48/90: <u>5170</u>					

DIAGRAMS/MISC. INFORMATION:

Noisy traces across Bare tundra

SHOTPOINT	TR. NO.		TR. NO.		SHOT				SPREAD				REMARKS	CORE STACK			
	REEL NO.	REC.	REEL NO.	REC.	SIZE	DEPTH	NO.	OFFSET	DB.	CDP SWITCH	LINE GROUPS			TR. NO.	REC.	TR. NO.	REC.
41	751745	62			20	60	41			41	35+1	-46+4	5				
42		62			20	60	42			45	36+1	-47+4					
43		63			20	60	43			49	37+1	-48+4					
44		64			20	60	44			53	38+1	-49+4					
45		65			20	60	45			57	39+1	-50+4					
46		68			20	60	46			61	40+1	-51+4					
47		69			20	60	47			65	41+1	-52+4					
48		70			20	60	48			69	42+1	-53+4					
49		71			20	60	49			73	43+1	-54+4					
50		72			20	60	50			29	44+1	-55+4	6	Recorder @ SP-55			
51		73			20	60	51			33	45+1	-56+4		# 74 -> 78 - N.G.			
52		80			20	60	52			37	46+1	-57+4					
53		81			20	60	53			41	47+1	-58+4					
54		82			20	60	54			45	48+1	-59+4					
55		83			20	60	55	220	5	49	49+1	-60+4					
56		84			20	60	56			53	50+1	-61+4					
57		85			20	60	57			57	51+1	-62+4					
58		86			20	60	58			61	52+1	-63+4					
59		87			20	60	59			65	53+1	-64+4					
60		88			20	60	60	220	N	69	54+1	-65+4					





Recording Hrs. - 15

### LAND SEISMIC RECORDING LOG

CLIENT: <b>Husky</b>		PROSPECT: <b>NRA-A</b>		AREA: <b>Barrow</b>		LINE NO: <b>182</b>	
PARTY NO: <b>1182</b>		INST. ENG: <b>Stieff</b>		DATE: <b>MO-9 DAY-7 YR-79</b>			
INSTRUMENT: <input type="checkbox"/> 1 SYSTEM <input type="checkbox"/> 2 SYSTEMS		DOGS: <input type="checkbox"/> 1-24 & 25-48 <input type="checkbox"/> 1-48 & 49-96		TYPE: <input type="checkbox"/> DFS III <input type="checkbox"/> DFS X <input type="checkbox"/> DFS II		TRACKS: <input type="checkbox"/> 1 TRACK <input type="checkbox"/> 2 TRACKS	
NO. BYTES IN HEADER REC:		NO. BYTES IN RECORD ID1:		NO. BYTES PER SCAN: <b>134</b>		RECORD NUMBERS: <input type="checkbox"/> DEC <input type="checkbox"/> OCT	
FIELD TRACE NOS.: <b>1-48</b>		DATA CHANNEL NOS.: <b>1-48</b>		AUXILIARY DATA:		GAIN CONSTANT: <b>36</b> db	
PARAMETER: RECORD LENGTH: <b>1</b> sec		SAMPLE RATE: <input type="checkbox"/> 1 ms <input type="checkbox"/> 4 ms		GAIN MODE: <input type="checkbox"/> INITIAL <input type="checkbox"/> MANUAL <input type="checkbox"/> FINAL <input type="checkbox"/> OPERATE		FILTERS: FREQ: <b>8</b> LO CUT: <b>1.1</b> HI CUT: <b>108</b>	
DISPLAY: MODE: <input type="checkbox"/> TRACK <input type="checkbox"/> FLOAT <input type="checkbox"/> DEFLOAT <input type="checkbox"/> AMPLIFIER DIRECT		INITIAL GAIN: <b>72</b> db		TRIP SENS: <b>0</b> db		POLARITY CONVENTION: <input type="checkbox"/> NEGATIVE <input type="checkbox"/> POSITIVE	
SOURCE: TYPE: <input type="checkbox"/> DYNAMITE <input type="checkbox"/> VIBROSEIS <input type="checkbox"/> OTHER		PATTERN: <b>1-1/2 in - 1/2 in</b>		NO. OF POSITIONS: <b>18</b>		LATERAL SPACING: <b>12</b>	
RECEIVER: TYPE: <b>20-2</b>		PATTERN: <b>1-1/2 in</b>		NO. OF ELEMENTS: <b>18</b>		LATERAL SPACING: <b>12</b>	
CONNECTION: <b>Series-Parallel</b>		RESISTANCE: <b>560</b> ohms		STAGGER: <b>18</b>		LATERAL OFFSET: <b>48</b>	
SPREAD: NO. OF GROUPS: <b>48</b>		GROUP INTERVAL: <b>220</b>		SHOTPOINT INTERVAL: <b>880</b>		DIRECTION OF REGRESSION: <b>None</b>	
OFFSET GROUP 1: <b>5170</b>		OFFSET GROUP 2: <b>110</b>		OFFSET GROUP 25: <b>110</b>		LEADING GROUP: <b>48</b>	

DIAGRAMS/MISC. INFORMATION: **TAM1** **TAM47** **H122-122 tests** **H-133 test meters**

SHOTPOINT	TR. 10		TR. 20		SHOT		SPREAD		REMARKS	CORR STAGE	
	REEL NO.	REC.	REEL NO.	REC.	SIZE	DEPTH	NO. OFFSET	DIR.		LINE GROUPS	TR. 10
86	7151	7416	1134		120	167	1	29	70+1 - 91+4	1	Recorder @ SP-91
87		1135			120	167	2	33	81+1 - 92+4		
88		1137			120	167	3	37	82+1 - 93+4		H136-N.G.
89		1138			120	167	4	41	83+1 - 94+4		
90		1139			120	167	5	45	84+1 - 95+4		
91		1144			120	167	6	49	85+1 - 96+4		#140 → 141-N.G.
92		1145			120	167	7	53	86+1 - 97+4		
93		1146			120	167	8	57	87+1 - 98+4		
94		1147			120	167	9	61	88+1 - 99+4		
95		1148			120	167	10	65	89+1 - 100+4		
96		1149			120	167	11	69	90+1 - 101+4		
97		1150			120	167	12	75	91+1 - 102+4	2	Recorder @ SP-103
98		1154			120	167	13	29	92+1 - 103+4		#151-152-N.G.
99		1155			120	167	14	33	93+1 - 104+4		
100		1157			120	167	15	37	94+1 - 105+4		H156-N.G.
101		1158			120	167	16	41	95+1 - 106+4		
102		1160			120	167	17	45	96+1 - 107+4		#159-N.G.
103		1161			120	167	18	49	97+1 - 108+4		
104		1162			120	167	19	53	98+1 - 109+4		
105		1164			120	167	20	57	99+1 - 110+4		#163-N.G.

# LAND SEISMIC RECORDING LOG

CLIENT: <b>HUSKY</b>		PROSPECT: <b>NPR-A</b>		AREA: <b>Barrow</b>		LINE NO: <b>682</b>	
PARTY NO: <b>1112</b>		INST. ENG: <b>Stiff</b>		DATE: <b>MO 5 DAY 1 YR 79</b>			
INSTRUMENT (9-TRACK) <input type="checkbox"/> 1 SYSTEM <input type="checkbox"/> 2 SYSTEMS NO. BYTES IN HEADER REC: _____		TYPE: <input type="checkbox"/> DFS III <input type="checkbox"/> DFS II <input type="checkbox"/> DFS I NO. BYTES IN RECORD ID: _____		RECORD NUMBERS: _____		GAIN CONSTANT: <b>36</b> db	
CONFIGURATION (MAG TAPE) FIELD TRACE NOS.: <b>1-48</b> DATA CHANNEL NOS.: <b>1-48</b>		AUXILIARY DATA: AUXILIARY CHANNEL NOS.: _____		NOISE REDUCTION: _____		CORR SCALING: _____	
PARAMETER RECORD LENGTH: <b>6</b> sec MODE: <input type="checkbox"/> FLOAT <input type="checkbox"/> DEFLOAT AMPLIFIER: <input type="checkbox"/> DIRECT		SAMPLE RATE: <input type="checkbox"/> 1 ms <input type="checkbox"/> 2 ms <input type="checkbox"/> 4 ms INITIAL GAIN: <b>12</b> db		GAIN MODE: <input type="checkbox"/> INITIAL <input type="checkbox"/> FINAL TRIP SENS: <b>6</b> db		FILTERS: FREQ. <b>8</b> Hz LO CUT: <b>18</b> Hz HI CUT: <b>70</b> Hz NOISE FILTER: <input type="checkbox"/> IN <input type="checkbox"/> OUT	
SOURCE TYPE: <input type="checkbox"/> DYNAMITE <input type="checkbox"/> VIBROSEIS <input type="checkbox"/> OTHER		PATTERN: <b>inline-hole</b> CHG/ HOLE: <b>20</b> HOLE DEPTH: <b>75</b>		NO. OF POSITIONS: _____ SWEEP POSITION: _____		LATERAL SPACING: _____ SWEEP START: _____ SWEEP END: _____	
RECEIVER TYPE: <b>20-0</b> CONNECTION: <b>Series-Parallel</b>		PATTERN: <b>inline</b> RESISTANCE: <b>560</b> ohms		NO. OF ELEMENTS: <b>18</b> STAGGER: _____		INLINE SPACING: <b>12</b> LENGTH: _____ WIDTH: _____ LATERAL OFFSET: _____	
SPREAD NO. OF GROUPS: <b>48</b> OFFSET GROUP 1: <b>5170</b>		GROUP INTERVAL: <b>220</b> OFFSET GROUP 2: <b>110</b>		SHOTPOINT INTERVAL: <b>880</b> OFFSET GROUP 25: <b>110</b>		FOLD: <b>6</b> OFFSET GROUP 48/90: <b>5170</b> DIRECTION OF PROGRESSION: <b>North</b> LEADING GROUP: <b>48</b>	

DIAGRAMS/MISC. INFORMATION:

SHOTPOINT	TR. 10		TR. 11		SHOT				SPREAD		REMARKS	CORR. STAGE				
	REEL NO.	REC.	REEL NO.	REC.	SIZE	DEPTH	NO.	OFFSET	DB.	CDP SWITCH		LINE GROUPS	HT.	TR. 11	TR. 10	REC.
1111	75119146	1165			20	617	21			61	100+1 - 111+4	2				
1112		1166			20	617	22			65	101+1 - 112+4					
1113		1167			20	617	23			69	102+1 - 113+4					
1114		1168			20	617	24			73	103+1 - 114+4					
1115		1169			20	617	25			77	104+1 - 115+4	3				# 165-169-N.G.
1116		1170			20	617	26			81	105+1 - 116+4					Recorder @ 92-115
1117		1171			20	617	27			85	106+1 - 117+4					
1118		1172			20	617	28			89	107+1 - 118+4					
1119		1173			20	617	29			93	108+1 - 119+4					
1120		1174			20	617	30			97	109+1 - 120+4					
1121		1175			20	617	31			101	110+1 - 121+4					
1122		1176			20	617	32			105	111+1 - 122+4					
1123		1177			20	617	33			109	112+1 - 123+4					
1124		1178			20	617	34			113	113+1 - 124+4					
1125		1179			20	617	35			117	114+1 - 125+4					
1126		1180			20	617	36			121	115+1 - 126+4					
1127		1181			20	617	37			125	116+1 - 127+4	4				Recorder @ 128+2/128+3
1128		1182			20	617	38			129	117+1 - 128+4					
1129		1183			20	617	39			133	118+1 - 129+4					
1130		1184			20	617	40			137	119+1 - 130+4					

# LAND SEISMIC RECORDING LOG



CLIENT: <b>Husk</b>		PROSPECT: <b>NPR-A</b>		AREA: <b>BACCH</b>		LINE NO.: <b>682</b>													
PARTY NO.: <b>1182</b>		INST. ENG.: <b>Stioff</b>		DATE: <b>MO 5 DAY 1 YR 79</b>															
INSTRUMENT <input type="checkbox"/> 1 SYSTEM <input type="checkbox"/> 2 SYSTEMS		<input type="checkbox"/> 1-24 & 25-48 <input type="checkbox"/> 1-48 & 49-96		TYPE: <input type="checkbox"/> DFS III <input type="checkbox"/> DFS IV		<input type="checkbox"/> 9 TRACK <input type="checkbox"/> 21 TRACK		FORMAT: <input type="checkbox"/> GAPPED <input type="checkbox"/> UNGAPPED		PACKING DENSITY: (LO) <input type="checkbox"/> 350 BPI <input type="checkbox"/> 800 BPI		(HI) <input type="checkbox"/> 712 BPI <input type="checkbox"/> 1600 BPI							
NO. BYTES IN HEADER REC.		NO. BYTES IN RECORD ID		NO. BYTES PER SCAN:		RECORD NUMBERS:		DEC. 1 OCT		GAIN CONSTANT: (1) _____ (2) _____ (3) _____ (4) _____ (5) _____ (6) _____ (7) _____		INPUT IMPEDANCE: _____ ohms							
CONFIGURATION (MAG TAPE)		FIELD TRACE NOS.:		DATA CHANNEL NOS.:		AUXILIARY DATA:		AUXILIARY CHANNEL NOS.:											
PARAMETER		RECORD LENGTH: _____ sec.		SAMPLE RATE: <input type="checkbox"/> 1 sec. <input type="checkbox"/> 4 sec.		GAIN MODE: <input type="checkbox"/> INITIAL <input type="checkbox"/> MANUAL <input type="checkbox"/> FINAL <input type="checkbox"/> OPERATE		FILTERS: _____		LO CUT HZ SLOPE _____		HI CUT HZ SLOPE _____		NOISE FILTER: <input type="checkbox"/> IN <input type="checkbox"/> OUT					
DISPLAY		<input type="checkbox"/> MODE. <input type="checkbox"/> AGC <input type="checkbox"/> FLOAT <input type="checkbox"/> DEFOAT <input type="checkbox"/> AMPLIFIER <input type="checkbox"/> DIRECT		INITIAL GAIN: _____ db		TRIP SENS.: _____ db		POLARITY CONVENTION: _____		PRESSURE INCREASE ON GEOPHONE: _____		<input type="checkbox"/> NEGATIVE <input type="checkbox"/> POSITIVE		NUMBERS ON MAG. TAPE <input type="checkbox"/> DOWNBREAK <input type="checkbox"/> UPBREAK ON DISPLAY					
CFS I		TYPE STACK:		GATE LENGTH: _____		RECORD REJECTION: _____		NOISE REDUCTION: _____		NOISE THRESHOLD: _____		CORR. SCALING: _____		R.C.U. NORM/ALT SW.					
SOURCE		TYPE: <input type="checkbox"/> DYNAMITE <input type="checkbox"/> VIBROSEIS <input type="checkbox"/> OTHER		PATTERN: _____		NO. OF POSITIONS: _____		INLINE SPACING: _____		LATERAL SPACING: _____		STAGGER: _____		LENGTH: _____		WIDTH: _____		LATERAL OFFSET: _____	
RECEIVER		CONNECTION: _____		DISTANCE: _____		NO. OF ELEMENTS: _____		STAGGER: _____		INLINE SPACING: _____		LENGTH: _____		WIDTH: _____		LATERAL OFFSET: _____			
SPREAD		NO. OF GROUPS: <b>48</b>		GROUP INTERVAL: <b>220</b>		SHOTPOINT INTERVAL: <b>880</b>		FOLD: <b>6</b>		DIRECTION OF PROGRESSION: <b>N-11A</b>		LEADING GROUP: <b>48</b>							
OFFSET GROUP 1: <b>5170</b>		OFFSET GROUP 24: <b>110</b>		OFFSET GROUP 25: <b>110</b>		OFFSET GROUP 48/96: <b>5170</b>													

DIAGRAMS/MISC. INFORMATION:

SHOTPOINT	TR _____ to _____		TR _____ to _____		SHOT		SPREAD		REMARKS	CORR. STACK		
	REEL NO.	REC.	REEL NO.	REC.	SIZE	DEPTH	NO. OFFSET	DIR.		CDP SWITCH	LINE GROUPS	TR
1126	751946	1187			20	67	41		39	120+1 - 139+4		
1127		1188			20	67	42		43	121+1 - 132+4		
1128		1189			20	67	43		47	122+1 - 133+4	#187 -> 208 - N.G.	
1129		1190			20	67	44		51	123+1 - 134+4		
1130		1191			20	67	45		55	124+1 - 135+4		
1131		1192			20	67	46		59	125+1 - 136+4		
1132		1193			20	67	47		63	126+1 - 137+4		
1133		1194			20	67	48		67	127+1 - 138+4		
1134		1195			20	67	49		71	128+1 - 139+4		
1135		1196			20	67	50		27	129+1 - 140+4	5 Recorder @ 140+2/140+3 #216 - N.G.	
1136		1197			20	67	51		31	130+1 - 141+4		
1137		1198			20	67	52		35	131+1 - 142+4		
1138		1199			20	67	53		39	132+1 - 143+4		
1139		1200			20	67	54		43	133+1 - 144+4	#221 - N.G.	
1140		1201			20	67	55		47	134+1 - 145+4	#223, 224 - N.G.	
1141		1202			20	67	56		51	135+1 - 146+4		
1142		1203			20	67	57		55	136+1 - 147+4	#227 - N.G.	
1143		1204			20	67	58		59	137+1 - 148+4		
1144		1205			20	67	59		63	138+1 - 149+4		
1145		1206			20	67	60		67	139+1 - 150+4	#231 - N.G.	



# LAND SEISMIC RECORDING LOG

	CLIENT: <u>Husky</u>	PROSPECT: <u>NPA-A</u>	AREA: <u>Barrow</u>	LINE NO: <u>682</u>						
	PARTY NO: <u>1182</u>	INST. ENG: <u>Shiff</u>		DATE: <u>5</u> DAY: <u>1</u> TO <u>79</u>						
INSTRUMENT (9-TRACK)	<input type="checkbox"/> 1 SYSTEM <input type="checkbox"/> 2 SYSTEMS	<input type="checkbox"/> 1-24 & 25-48 <input type="checkbox"/> 1-48 & 49-96	EVENTS	TYPE: <input type="checkbox"/> DFS III <input type="checkbox"/> DFS IX	<input type="checkbox"/> 9 TRACK <input type="checkbox"/> 21 TRACK	FORMAT: _____	<input type="checkbox"/> GAPPED <input type="checkbox"/> UNGAPPED	PACKING DENSITY: (1) _____ (2) _____ (3) _____ (4) _____ (5) _____ (6) _____ (7) _____	(10) <input type="checkbox"/> 350 WPI <input type="checkbox"/> 500 WPI	(11) <input type="checkbox"/> 712 WPI <input type="checkbox"/> 1000 WPI
	NO. BYTES IN HEADER REC: _____	NO. BYTES IN RECORD ID: _____	NO. BYTES PER SCAN: _____	RECORD NUMBERS: _____	<input type="checkbox"/> DEC. <input type="checkbox"/> OCT	GAIN CONSTANT: _____ db	INPUT IMPEDANCE: _____ ohms			
CONFIGURATION (MAG TAPE)	FIELD TRACE NOS.: _____ DATA CHANNEL NOS.: _____			AUXILIARY DATA: _____ AUXILIARY CHANNEL NOS.: _____						
PARAMETER	RECORD LENGTH: _____ sec.	SAMPLE RATE: _____ Hz	<input type="checkbox"/> 4 in. <input type="checkbox"/> 4 in. <input type="checkbox"/> 4 in.	GAIN MODE: <input type="checkbox"/> INITIAL <input type="checkbox"/> FINAL	<input type="checkbox"/> MANUAL <input type="checkbox"/> OPERATE	FREQ. _____	LO CUT HZ SLOPE _____	H CUT HZ SLOPE _____	NOTCH FILTER: <input type="checkbox"/> IN <input type="checkbox"/> OUT	
DISPLAY	MODE: <input type="checkbox"/> AGC <input type="checkbox"/> FLOAT <input type="checkbox"/> AMPLIFIER <input type="checkbox"/> DIRECT	INITIAL GAIN: _____ db	TRIP SENS: _____ db	RECORD REJECTION: _____	NOISE REDUCTION: _____	POLARITY CONVENTION: <input type="checkbox"/> NEGATIVE <input type="checkbox"/> POSITIVE	PRESSURE INCREASE ON GEOPHONE: _____	NUMBERS ON MAG. TAPE: _____	DOWNBREAK UPBREAK: <input type="checkbox"/> ON DISPLAY	
CFS I	TYPE STACK: _____	GATE LENGTH: _____	RECORD REJECTION: _____	NOISE REDUCTION: _____	CORR. SCALING: _____	R.C.U. NORM/ALT SW: _____				
SOURCE	TYPE: <input type="checkbox"/> DYNAMIC <input type="checkbox"/> VIBROSEIS <input type="checkbox"/> OTHER	PATTERN: _____	NO. OF POSITIONS: _____	INLINE SPACING: _____	LATERAL SPACING: _____	STAGGER: _____	LENGTH: _____	WIDTH: _____	LATERAL OFFSET: _____	
RECEIVER	CONNECTION: _____	RESISTANCE: _____	NO. OF ELEMENTS: _____	STAGGER: _____	INLINE SPACING: _____	LENGTH: _____	WIDTH: _____	LATERAL OFFSET: _____		
SPREAD	NO. OF GROUPS: <u>48</u>	GROUP INTERVAL: <u>220</u>	SHOTPOINT INTERVAL: <u>890</u>	FOLD: <u>6</u>	DIRECTION OF PROGRESSION: <u>North</u>	LEADING GROUP: <u>48</u>				
	OFFSET GROUP 1: <u>5170</u>	GROUP 1: <u>118</u>	GROUP 2: <u>110</u>	OFFSET GROUP 2: <u>5170</u>						

DIAGRAMS/MISC. INFORMATION:

SHOTPOINT	TR. 10		TR. 20		SHOT			SPREAD			REMARKS	CORR. STACK		
	REEL NO.	REC.	REEL NO.	REC.	DEPTH	NO. OFFSET	DIR.	CDP SWITCH	LINE GROUPS	TR. 10		TR. 20	TR. 30	
1146	2516	146	271		120	167	61	71	140+1-151+4	5	#233-N.G			
1147		235			120	167	62	21	141+1-152+4	6	Recorder @ SP-154			
1148		236			120	167	63	25	142+1-153+4					
1149		237			120	167	64	29	143+1-154+4					
1150		238			120	167	65	33	144+1-155+4					
1151		239			120	167	66	37	145+1-156+4					
1152		240			120	167	67	41	146+1-157+4					
1153		241			120	167	68	45	147+1-158+4					
1154		242			120	167	69	49	148+1-159+4					
1155		243			120	167	70	53	149+1-160+4					
1156		245			120	167	71	57	150+1-161+4					
1157		246			120	167	72	61	151+1-162+4					
1158		247			120	167	73	65	152+1-163+4					
1159		248			120	167	74	69	153+1-164+4					
1160		249			120	167	75	73	154+1-165+4					
1161		250			120	167	76	77	155+1-166+4	7	Recorder @ SP-166			
1162		251			120	167	77	81	156+1-167+4					
1163		253			120	167	78	85	157+1-168+4		#252-N.G			
1164		254			120	167	79	89	158+1-169+4					
1165		255			120	167	80	93	159+1-170+4					

# LAND SEISMIC RECORDING LOG

	CLIENT: <u>Husky</u>	PROSPECT: <u>NPPA-A</u>	AREA: <u>Barron</u>
	PARTY NO: <u>1182</u>	INST. ENG: <u>Steff</u>	LINE NO: <u>672</u>
INSTRUMENT (P-TRACK)	<input type="checkbox"/> 1 SYSTEM <input type="checkbox"/> 2 SYSTEMS	<input type="checkbox"/> 1-24 & 25-48 <input type="checkbox"/> 1-48 & 49-96	DATE: <u>MO 5 DAY 1 YEAR 79</u>
	NO. BYTES IN HEADER REC.:	NO. BYTES IN RECORD ID:	NO. BYTES PER SCAN:
CONFIGURATION (MAG TAPE)	FIELD TRACE NOS.:	DATA CHANNEL NOS.:	AUXILIARY DATA:
PARAMETER	RECORD LENGTH:	SAMPLE RATE:	AUXILIARY CHANNEL NOS.:
DISPLAY	MODE: <input type="checkbox"/> AOC <input type="checkbox"/> DEFLOAT <input type="checkbox"/> DIRECT	INITIAL GAIN:	FILTERS:
CFS I	TYPE STACK:	GATE LENGTH:	FREQ.:
SOURCE	TYPE: <input type="checkbox"/> DYNAMITE <input type="checkbox"/> VIBROSEIS <input type="checkbox"/> OTHER	PATTERN:	TO CUT H2 SLOPE
RECEIVER	CONNECTION:	RESISTANCE:	HI CUT H2 SLOPE
SPREAD	NO. OF GROUPS: <u>48</u>	GROUP INTERVAL: <u>330</u>	NOISE REDUCTION:
DIAGRAMS/MISC. INFORMATION:			NOISE THRESHOLD:

SHOTPOINT	TR. 10		TR. 20		SHOT			SPREAD		REMARKS	CORR. SPACE			
	REEL NO.	REC.	REEL NO.	REC.	REEL	DEPTH	NO.	OFFSET	DIR.		CDP SWITCH	LINE GROUPS	TR. 10	TR. 20
1166	75	119146	125	16	120	167.81	11		49	160+1 - 1714	7			
1167		2157			120	167.82	11		53	161+1 - 1724				
1168		2158			120	167.83	11		57	162+1 - 174				
1169		2159			120	167.84	11		61	163+1 - 178				
1170		2160			120	167.85	11		65	164+1 - 1712				
1171		2161			120	167.86	11		69	165+1 - 1716				
1172		2163			120	167.87	11		73	166+1 - 1720				
1173		2164			120	167.88	220	5	77	167+1 - 1724				