

# LAND SEISMIC RECORDING LOG

16-Hours

	CLIENT: <u>Husky</u>	PROSPECT: <u>NPR-A</u>	AREA: <u>BARROW</u>	LINE NO: <u>7524</u>	
	PARTY NO: <u>1192</u>	INST. ENG: <u>STREFF</u>		DATE: <u>MO 6 DAY 7 YR 79</u>	

INSTRUMENT	<input type="checkbox"/> 1 SYSTEM <input type="checkbox"/> 2 SYSTEMS	<input type="checkbox"/> 1-24 & 25-48 <input type="checkbox"/> 1-48 & 49-96	DOOS EVENTS	TYPE: <input type="checkbox"/> DFS III <input type="checkbox"/> DFS IX	<input checked="" type="checkbox"/> TRACK <input type="checkbox"/> 21 TRACK	FORMAT: SEG <u>B</u>	<input type="checkbox"/> GAPPED <input type="checkbox"/> UNGAPPED	PACKING DENSITY:	(LQ) <input type="checkbox"/> 356 BPI <input type="checkbox"/> 800 BPI	(HI) <input type="checkbox"/> 712 BPI <input type="checkbox"/> 1600 BPI				
(9-TRACK)	NO. BYTES IN HEADER REC:	NO. BYTES IN RECORD ID:	NO. BYTES PER SCAN: <u>136</u>	RECORD NUMBERS:	<input checked="" type="checkbox"/> DEC <input type="checkbox"/> OCT	GAIN CONSTANT: <u>36</u> db	INPUT IMPEDANCE: <u>20,000</u> ohms	(1)	(2)	(3)	(4)	(5)	(6)	(7)
CONFIGURATION (MAG TAPE)	FIELD TRACE NOS.: <u>1-48</u>				AUXILIARY DATA: <u>YB</u> <u>UH</u>				AUXILIARY CHANNEL NOS.: <u>3</u> <u>4</u>					
PARAMETER	RECORD LENGTH: <u>6</u> sec.	SAMPLE RATE: <input type="checkbox"/> 1 ms <input type="checkbox"/> 4 ms	GAIN MODE: <input checked="" type="checkbox"/> INITIAL <input type="checkbox"/> MANUAL	FILTERS: FREQ. <u>8</u>	LO CUT HZ SLOPE <u>18</u>	FREQ. <u>120</u>	HI CUT HZ SLOPE <u>70</u>	NOTCH FILTER: <input type="checkbox"/> IN <input type="checkbox"/> OUT						
DISPLAY	MODE: <input type="checkbox"/> AGC <input type="checkbox"/> DEFLOAT <input type="checkbox"/> DIRECT	AMPLIFIER	INITIAL GAIN: <u>18</u> db	TRIP SENS.: <u>18</u> db	POLARITY CONVENTION:	PRESSURE INCREASE ON GEOPHONE:	<input type="checkbox"/> NEGATIVE <input type="checkbox"/> POSITIVE	NUMBERS ON MAG. TAPE		DOWNBREAK UPBREAK		ON DISPLAY		
CFS I	TYPE STACK:	GATE LENGTH:	RECORD REJECTION:	NOISE REDUCTION:	NOISE THRESHOLD:	CORR. SCALING:	B.C.U. NORM/ALT SW.							
SOURCE	TYPE: <input checked="" type="checkbox"/> DYNAMITE <input type="checkbox"/> VIBROSEIS <input type="checkbox"/> OTHER		PATTERN: <u>Single hole - InLine</u>		NO. OF POSITIONS:	INLINE SPACING:	LATERAL SPACING:	STAGGER:	LENGTH:	WIDTH:	LATERAL OFFSET:			
RECEIVER	TYPE: <u>GSC-20d</u>		PATTERN: <u>InLine</u>		NO. OF ELEMENTS: <u>18</u>	INLINE SPACING: <u>12'</u>	LATERAL SPACING:	STAGGER:	LENGTH:	WIDTH:	LATERAL OFFSET:			
SPREAD	NO. OF GROUPS: <u>48</u>		GROUP INTERVAL: <u>220'</u>		SHOTPOINT INTERVAL: <u>830'</u>	FOLD: <u>6</u>	DIRECTION OF PROGRESSION: <u>W → E (NW)</u>	OFFSET GROUP 1: <u>570'</u>		OFFSET GROUP 2: <u>110'</u>		LEADING GROUP: <u>48</u>		

DIAGRAMS/MISC. INFORMATION: TR-1 → 24-group 1st → TR-20 → 5th → TR-25 → TR-25 → TR-48 → SPG → File # 34 → 220' daily tests

SHOTPOINT	TR. 1 to 48		TR. 10		SHOT		SPREAD		REMARKS	CORR. STACK			
	REEL NO.	REC.	REEL NO.	REC.	SIZE	DEPTH	NO.	OFFSET		DIR.	CDP SWITCH	LINE GROUPS	TR 1-48
1	2318	2213			20	67	1	11	25	T-1	- 6+4		
2		2214			20	67	2	11	25	T-5	- 7+4		
3		2216			20	67	3	11	32	T-9	- 8+4		
4		2217			20	67	4	11	37	T-13	- 9+4		
5		2218			20	67	5	11	41	T-17	- 10+4		
6		2219			20	67	6	11	45	T-21	- 11+4		
7		2220			20	67	7	11	49	T+1	- 12+4		
8		2221			20	67	8	11	53	T+1	- 13+4		
9		2222			20	67	9	11	57	T+1	- 14+4		
10		2223			20	67	10	11	61	T+1	- 15+4		
11		2224			20	67	11	11	65	T+1	- 16+4		
12		2225			20	67	12	11	69	T+1	- 17+4		
13		2226			20	67	13	11	25	T+1	- 18+4	2	Recorder @ SP-19
14		2227			20	67	14	11	29	T+1	- 19+4		
15		2228			20	67	15	11	33	T+1	- 20+4		
16		2229			20	67	16	11	19	T+1	- 21+4	3	Recorder @ SP-23+2
17		2240			20	67	17	11	23	T+1	- 22+4		
18		2241			20	67	18	11	27	T+1	- 23+4		
19		2242			20	67	19	11	31	T+1	- 24+4		
20		2243			20	67	20	11	35	T+1	- 25+4		

# LAND SEISMIC RECORDING LOG

	CLIENT: <b>Haskey</b>	PROSPECT: <b>NPR-11</b>	AREA: <b>BARROW</b>	LINE NO: <b>75 KW</b>					
	PARTY NO: <b>1182</b>	INST. ENG: <b>Stroff-Windham</b>		DATE: <b>MO 4 DAY 7 YR 79</b>					
INSTRUMENT (9-TRACK)	<input type="checkbox"/> 1 SYSTEM <input type="checkbox"/> 2 SYSTEMS	<input type="checkbox"/> 24 & 25-48 <input type="checkbox"/> 1-48 & 49-96	ODDS <input type="checkbox"/> EVENS	TYPE: <input type="checkbox"/> DFS III <input type="checkbox"/> DFS IX <input type="checkbox"/> OTHER	<input type="checkbox"/> 9 TRACK <input type="checkbox"/> 21 TRACK	FORMAT: <b>R</b>	<input type="checkbox"/> GAPPED <input type="checkbox"/> UNGAPPED	PACKING DENSITY: (L) <input type="checkbox"/> 356 BPI <input type="checkbox"/> 800 BPI	(M) <input type="checkbox"/> 712 BPI <input type="checkbox"/> 1600 BPI
	NO. BYTES IN HEADER REC:	NO. BYTES IN RECORD ID:	NO. BYTES PER SCAN: <b>136</b>	RECORD NUMBERS: <input type="checkbox"/> DEC <input type="checkbox"/> OCT	GAIN CONSTANT: <b>36</b> db	INPUT IMPEDANCE: <b>20,000</b> ohms			
CONFIGURATION (MAG TAPE)	FIELD TRACE NOS.: <b>1-48</b>			AUXILIARY DATA: (1) <b>7B</b> (2) <b>4H</b> (3) (4) (5) (6) (7)					
	DATA CHANNEL NOS.: <b>1-48</b> (ON MAG TAPE)			AUXILIARY CHANNEL NOS.: <b>3 4</b>					
PARAMETER	RECORD LENGTH: <b>6</b> sec.	SAMPLE RATE: <input type="checkbox"/> 1 ms <input type="checkbox"/> 4 ms <input checked="" type="checkbox"/> 2 ms <input type="checkbox"/> ms	GAIN MODE: <input type="checkbox"/> INITIAL <input type="checkbox"/> MANUAL <input checked="" type="checkbox"/> ETFF <input type="checkbox"/> FINAL <input type="checkbox"/> OPERATE	FILTERS: FREQ: <b>8</b> LO CUT HZ SLOPE <b>18</b>		FREQ: <b>120</b> HI CUT HZ SLOPE <b>70</b>	NOTCH FILTER: <input type="checkbox"/> IN <input type="checkbox"/> OUT		
DISPLAY	MODE: <input type="checkbox"/> FLOAT <input type="checkbox"/> AMPLIFIER <input checked="" type="checkbox"/> DEFLOAT <input type="checkbox"/> DIRECT	INITIAL GAIN: <b>19</b> db	TRIP SENS: <b>18</b> db	POLARITY CONVENTION: <input type="checkbox"/> NEGATIVE <input type="checkbox"/> POSITIVE		PRESSURE INCREASE ON GEOPHONE: <input type="checkbox"/> NUMBERS ON MAG. TAPE		<input type="checkbox"/> DOWNBREAK <input type="checkbox"/> UPBREAK ON DISPLAY	
CFS I	TYPE STACK:	GATE LENGTH:	RECORD REJECTION:	NOISE REDUCTION:		NOISE THRESHOLD:	CORR. SCALING:	R.C.U. NORM/ALT SW.	
SOURCE	TYPE: <input checked="" type="checkbox"/> DYNAMITE <input type="checkbox"/> VIBROSEIS <input type="checkbox"/> OTHER	PATTERN: <b>Single hole - inline</b>	NO. OF POSITIONS:	INLINE SPACING:	LATERAL SPACING:	STAGGER:	LENGTH:	WIDTH:	LATERAL OFFSET:
		CMG/ HOLE: <b>23</b> HOLE DEPTH: <b>75'</b>	SWEEP POSITION:	SWEEP START:	SWEEP END:	SWEEP LENGTH:	SWEEP TAPER:	PHASE COMP.	
RECEIVER	TYPE: <b>RSC-20d</b>	PATTERN: <b>inline</b>	NO. OF ELEMENTS: <b>18</b>	INLINE SPACING: <b>12'</b>	LATERAL SPACING:	STAGGER:	LENGTH:	WIDTH:	LATERAL OFFSET:
	CONNECTION: <b>Series - Parallel</b>	RESISTANCE: <b>560</b> ohms							
SPREAD	NO. OF GROUPS: <b>48</b>	GROUP INTERVAL: <b>220'</b>	SHOTPOINT INTERVAL: <b>380'</b>	FOLD: <b>6</b>	DIRECTION OF PROGRESSION: <b>W → E (NW → SE)</b>		LEADING GROUP: <b>48</b>		
	OFFSET GROUP 1: <b>5170'</b>	OFFSET GROUP 24: <b>110'</b>	OFFSET GROUP 5: <b>110'</b>	OFFSET GROUP 48/98+: <b>5170</b>					

DIAGRAMS/MISC. INFORMATION:

SHOTPOINT	TR. 1 to 48		TR. 10 to		SHOT								SPREAD		REMARKS	CORR. STACK			
	REEL NO.	REC.	REEL NO.	REC.	SIZE	DEPTH	NO.	OFFSET	DIR.	COP SWITCH	LINE GROUPS		SP	TR 1-48		TR 48-96	TR 1-48	TR 48-96	
21	751092B	2144			20	67	21				39	15+1	-26+4	3					
22		2145			20	67	22				43	16+1	-27+4						
23		2146			20	67	23				47	17+1	-28+4						
24		2147			20	67	24				51	18+1	-29+4						
25		2148			20	67	25				55	19+1	-30+4						
26		2149			20	67	26	170	Right		59	20+1	-31+4	4	Recovered SP-21				
27		2150			20	67	27	170	Right		37	22+1	-33+4		Recovered SP-27				
28		2151			20	67	28				37	22+1	-33+4						
29		2152			20	67	29				41	23+1	-34+4						
30		2153			20	67	30				45	24+1	-35+4						
31		2154			20	67	31				49	25+1	-36+4						
32		2155			20	67	32				53	26+1	-37+4						
33		2156			20	67	33				57	27+1	-38+4						
34		2157			20	67	34				61	28+1	-39+4						
35		2158			20	67	35				29	29+1	-40+4	5	Recovered SP-40				
36		2159			20	67	36				33	30+1	-41+4						
37		2160			20	67	37				37	31+1	-42+4						
38		2161			20	67	38				41	32+1	-43+4						
39		2162			20	67	39				45	33+1	-44+4						
40		2163			20	67	40				49	34+1	-45+4						

# LAND SEISMIC RECORDING LOG

	CLIENT: <u>Husky</u>	PROSPECT: <u>NPR-A</u>	AREA: <u>BARROW</u>	LINE NO.: <u>75XW</u>					
	PARTY NO.: <u>1182</u>	INST. ENG.: <u>STACH - O. Williams</u>	DATE: <u>MO 4 DAY 7 YR 79</u>						
INSTRUMENT (9-TRACK)	<input checked="" type="checkbox"/> 1 SYSTEM <input type="checkbox"/> 2 SYSTEMS	<input type="checkbox"/> 1-24 & 25-48 <input type="checkbox"/> 1-48 & 49-96	ODDS EVENS: <input type="checkbox"/>	TYPE: <input type="checkbox"/> DFS III <input type="checkbox"/> DFS IV	<input type="checkbox"/> 9-TRACK <input type="checkbox"/> 21 TRACK	FORMAT: <u>SEG</u>	<input type="checkbox"/> GAPPED <input type="checkbox"/> UNGAPPED	PACKING DENSITY: (LO) <input type="checkbox"/> 356 BPI (HI) <input type="checkbox"/> 712 BPI <input type="checkbox"/> 800 BPI <input type="checkbox"/> 1600 BPI	
	NO. BYTES IN HEADER REC: <u>17</u>	NO. BYTES IN RECORD ID: <u>136</u>	NO. BYTES PER SCAN: <u>136</u>	RECORD NUMBERS: <input checked="" type="checkbox"/> DEC <input type="checkbox"/> OCT	GAIN CONSTANT: <u>76</u> db	INPUT IMPEDANCE: <u>20,000</u> ohms			
CONFIGURATION (MAG TAPE)	FIELD TRACE NOS.: <u>1-48</u>	AUXILIARY DATA: (1) <u>FB</u> (2) <u>UH</u> (3) (4) (5) (6) (7)							
	DATA CHANNEL NOS.: <u>1-48</u>	(ON MAG TAPE) AUXILIARY CHANNEL NOS.: <u>3</u> <u>4</u>							
PARAMETER	RECORD LENGTH: <u>6</u> sec	SAMPLE RATE: <input type="checkbox"/> 1 ms <input type="checkbox"/> 4 ms <input checked="" type="checkbox"/> 2 ms <input type="checkbox"/>	GAIN MODE: <input type="checkbox"/> INITIAL <input checked="" type="checkbox"/> TRIP	FILTERS: FREQ: <u>8</u> LO CUT HZ SLOPE: <u>18</u>	FREQ: <u>120</u> HI CUT HZ SLOPE: <u>70</u>	<input type="checkbox"/> NOTCH FILTER: <input type="checkbox"/> IN <input checked="" type="checkbox"/> OUT			
DISPLAY	MODE: <input checked="" type="checkbox"/> AGC <input type="checkbox"/> FLOAT <input type="checkbox"/> DEFOAT <input type="checkbox"/> AMPLIFIER <input type="checkbox"/> DIRECT	INITIAL GAIN: <u>18</u> db	TRIP SENS: <u>18</u> db	POLARITY CONVENTION: <input type="checkbox"/> PRESSURE INCREASE ON GEOPHONE: <input type="checkbox"/> NEGATIVE <input checked="" type="checkbox"/> POSITIVE	NUMBERS ON MAG. TAPE: <input type="checkbox"/> DOWNBREAK <input checked="" type="checkbox"/> UPBREAK	ON DISPLAY			
CFS I	TYPE STACK:	GATE LENGTH:	RECORD REJECTION:	NOISE REDUCTION:	NOISE THRESHOLD:	CORR. SCALING:	R.C.U. NORM/ALT SW.		
SOURCE	TYPE: <input checked="" type="checkbox"/> DYNAMITE <input type="checkbox"/> VIBROSEIS <input type="checkbox"/> OTHER	PATTERN: <u>Single hole - inline</u>	NO. OF POSITIONS:	INLINE SPACING:	LATERAL SPACING:	STAGGER:	LENGTH:	WIDTH:	LATERAL OFFSET:
	CHG/ HOLE: <u>2</u>	HOLE DEPTH: <u>75'</u>	SWEEP POSITION:	SWEEP START:	SWEEP END:	SWEEP LENGTH:	SWEEP TAPER:	PHASE COMP.	
RECEIVER	TYPE: <u>65C-20d</u>	PATTERN: <u>inline</u>	NO. OF ELEMENTS: <u>18</u>	INLINE SPACING: <u>12'</u>	LATERAL SPACING:	STAGGER:	LENGTH:	WIDTH:	LATERAL OFFSET:
	CONNECTION: <u>Series - Parallel</u>	RESISTANCE: <u>5.6</u> ohms							
SPREAD	NO. OF GROUPS: <u>48</u>	GROUP INTERVAL: <u>220'</u>	SHOTPOINT INTERVAL: <u>880'</u>	FOLD: <u>6</u>	DIRECTION OF PROGRESSION: <u>N → E</u>	OFFSET GROUP 1: <u>5170'</u>	OFFSET GROUP 48: <u>5170'</u>	LEADING GROUP: <u>48</u>	

DIAGRAMS/MISC. INFORMATION:

SHOTPOINT	TR 1 to 118		TR 17 to 223		SHOT		SPREAD			REMARKS	CORE STACK						
	REEL NO.	REC.	REEL NO.	REC.	SIZE	DEPTH	NO.	OFFSET	DIR.		CDP SWITCH	LINE GROUPS		SET UP	TR 1-16	TR 17-22	TR 23-28
411	751192B	2164			20	67411				53	35+1	-46+4	5				
412		2165			20	67412				57	36+1	-47+4					
413		2166			20	67413				61	37+1	-48+4					
414		2167			20	67414				23	38+1	-49+4	6	Recorder @ SP-502			
415		2168			20	67415				27	39+1	-50+4					
416		2169			20	67416				31	40+1	-51+4					
417		2170			20	67417				35	41+1	-52+4					
418		2171			20	67418				39	42+1	-53+4		File # 271 - misfire			
419		2172			20	67419				43	43+1	-54+4					
420		2173			20	67420				47	44+1	-55+4					
421		2174			20	67421				51	45+1	-56+4					
422		2175			20	67422				55	46+1	-57+4					
423		2176			20	67423				59	47+1	-58+4					
424		2177			20	67424				63	48+1	-59+4					
425		2178			20	67425				67	49+1	-60+4					
426		2179			20	67426				71	50+1	-61+4					
427		2180			20	67427				33	51+1	-62+4	7	Recorder @ SP-61			
428		2181			20	67428				37	52+1	-63+4					
429		2182			20	67429				41	53+1	-64+4					
430		2183			20	67430				45	54+1	-65+4					

# LAND SEISMIC RECORDING LOG

	CLIENT: Husky	PROSPECT: NPR-A	AREA: BARRROW	LINE NO: 75XW					
	PARTY NO: 1182	INST. ENG: STROTT - DINDHAM		DATE: MO 4 DAY 7 YR 79					
INSTRUMENT (9-TRACK)	<input checked="" type="checkbox"/> 1 SYSTEM <input checked="" type="checkbox"/> 2 SYSTEMS	<input checked="" type="checkbox"/> 24 & 25-48 <input checked="" type="checkbox"/> 48 & 49-96	ODDS EVENS	TYPE: <input type="checkbox"/> DFS III <input type="checkbox"/> DFS IV	<input type="checkbox"/> 9-TRACK <input type="checkbox"/> 21 TRACK	FORMAT: SEG B	<input type="checkbox"/> GAPPED <input type="checkbox"/> UNGAPPED	PACKING DENSITY: (L) <input type="checkbox"/> 358 BPI (M) <input type="checkbox"/> 400 BPI (H) <input type="checkbox"/> 712 BPI <input type="checkbox"/> 1600 BPI	
	NO. BYTES IN HEADER REC:	NO. BYTES IN RECORD ID:	NO. BYTES PER SCAN: 134	RECORD NUMBERS: <input checked="" type="checkbox"/> DEC <input type="checkbox"/> OCT	GAIN CONSTANT: 36 db	INPUT IMPEDANCE: 20,000 ohms			
CONFIGURATION (MAG TAPE)	FIELD TRACE NOS: 1-48	DATA CHANNEL NOS: 1-48 (ON MAG TAPE)			AUXILIARY DATA: (1) 1B (2) 2A (3) (4) (5) (6) (7)	AUXILIARY CHANNEL NOS: 3 4			
	PARAMETER	RECORD LENGTH: 8-11 sec	SAMPLE RATE: <input type="checkbox"/> 1 ms <input type="checkbox"/> 4 ms <input type="checkbox"/> 2 ms <input type="checkbox"/> 8 ms	GAIN MODE: <input type="checkbox"/> INITIAL <input type="checkbox"/> MANUAL <input checked="" type="checkbox"/> TRF <input type="checkbox"/> FINAL <input type="checkbox"/> OPERATE	FILTERS: FREQ 8	LO CUT HZ SLOPE 18	FREQ 128	H1 CUT HZ SLOPE 70	NOTCH FILTER: <input type="checkbox"/> IN <input checked="" type="checkbox"/> OUT
DISPLAY	MODE: <input checked="" type="checkbox"/> AGC <input type="checkbox"/> FLOAT <input type="checkbox"/> DEFOAT <input type="checkbox"/> AMPLIFIER DIRECT	INITIAL GAIN: 19 db	TRIP SENS: 18 db	POLARITY CONVENTION: <input type="checkbox"/> PRESSURE INCREASE ON GEOPHONE: <input type="checkbox"/> NEGATIVE <input checked="" type="checkbox"/> POSITIVE	NUMBERS ON MAG TAPE: <input type="checkbox"/> DOWNBREAK <input checked="" type="checkbox"/> UPBREAK	ON DISPLAY: <input type="checkbox"/> R.C.U. NORM/ALT SW.			
CFS I	TYPE STACK:	GATE LENGTH:	RECORD REJECTION:	NOISE REDUCTION:	NOISE THRESHOLD:	CORR. SCALING:			
SOURCE	TYPE: <input checked="" type="checkbox"/> DYNAMITE <input type="checkbox"/> VIBROSEIS <input type="checkbox"/> OTHER	PATTERN: Single hole - Inline	NO. OF POSITIONS: 19	INLINE SPACING:	LATERAL SPACING:	STAGGER:	LENGTH:	WIDTH:	LATERAL OFFSET:
	CHG/ HOLE: 20	HOLE DEPTH: 75'	SWEEP POSITION:	SWEEP START:	SWEEP END:	SWEEP LENGTH:	SWEEP TAPER:	PHASE COMP:	
RECEIVER	TYPE: RSC-20d	PATTERN: IN line	NO. OF ELEMENTS: 19	INLINE SPACING: 12'	LATERAL SPACING:	STAGGER:	LENGTH:	WIDTH:	LATERAL OFFSET:
	CONNECTION: Series Parallel	RESISTANCE: 560 ohms							
SPREAD	NO. OF GROUPS: 18	GROUP INTERVAL: 220'	SHOTPOINT INTERVAL: 880'	FOLD: 6	DIRECTION OF PROGRESSION: 41 → 9				
	OFFSET GROUP 1: 5170	OFFSET GROUP 18: 110	OFFSET GROUP 25: 110	OFFSET GROUP 48/96: 5170'	LEADING GROUP: 48				

DIAGRAMS/MISC. INFORMATION:

SHOTPOINT	TR 1 to 48		TR 17 to 22		TR 23 to 28		TR 29 to 34		TR 35 to 40		DIR.	CDP SWITCH	LINE GROUPS	REMARKS	CORR. STACK			
	REEL NO.	REC.	REEL NO.	REC.	SIZE	DEPTH	NO.	OFFSET	HT.	REC.					HT.	REC.		
61	751023	200			20	6761			49	55+1	-66+4	7						
62		200			20	6762			53	56+1	-67+4							
63		200			20	6763			57	57+1	-68+4							
64		200			20	6764			61	58+1	-69+4							
65		200			20	6765			23	59+1	-70+4	8						
66		200			20	6766			27	60+1	-71+4							
67		200			20	6767			31	61+1	-72+4							
68		200			20	6768			35	62+1	-73+4							
69		200			20	6769			39	63+1	-74+4							
70		200			20	6770			43	64+1	-75+4							
71		200			20	6771			47	65+1	-76+4							
72		200			20	6772			51	66+1	-77+4							
73		200			20	6773			55	67+1	-78+4							
74		200			20	6774			59	68+1	-79+4							
75		200			20	6775			63	69+1	-80+4							
76		200			20	6776			67	70+1	-81+4							
77		200			20	6777			29	71+1	-82+4	9						
78		200			20	6778			33	72+1	-83+4							
79		200			20	6779			37	73+1	-84+4							
80		200			20	6780			41	74+1	-85+4							



Note: Same RU as SP-63  
File # 238 - mist rec

Recorder @ SP-82



# LAND SEISMIC RECORDING LOG

16 Hours

	CLIENT: <u>Husky</u>	PROSPECT: <u>NPR-A</u>	AREA: <u>BARROW</u>	LINE NO: <u>75XW</u>					
	PARTY NO: <u>1182</u>	INST. ENG: <u>Streff-Windham</u>		DATE: <u>MO 4 DAY 9 YR 79</u>					
INSTRUMENT (9-TRACK)	<input checked="" type="checkbox"/> 1 SYSTEM <input type="checkbox"/> 2 SYSTEMS	<input checked="" type="checkbox"/> 24 & 25-48 <input type="checkbox"/> 1-48 & 49-96	<input type="checkbox"/> ODS <input type="checkbox"/> EVENTS	TYPE: <input type="checkbox"/> DFS III <input type="checkbox"/> DFS IV <input type="checkbox"/> OTHER	<input checked="" type="checkbox"/> TRACK <input type="checkbox"/> 2) TRACK	FORMAT: <u>B</u>	<input type="checkbox"/> BAPPED <input type="checkbox"/> UNGAPPED	PACKING DENSITY: (L) <input type="checkbox"/> 356 BPI (H) <input type="checkbox"/> 712 BPI <input type="checkbox"/> 800 BPI <input type="checkbox"/> 1600 BPI	
	NO. BYTES IN HEADER REC:	NO. BYTES IN RECORD ID:	NO. BYTES PER SCAN: <u>134</u>	RECORD NUMBERS: <input checked="" type="checkbox"/> DEC. <input type="checkbox"/> OCT.	GAIN CONSTANT: <u>36</u> db	INPUT IMPEDANCE: <u>2000</u> ohms.	(1) (2) (3) (4) (5) (6) (7)		
CONFIGURATION (MAG TAPE)	FIELD TRACE NOS.: <u>1-48</u>			AUXILIARY DATA: <u>TB WH</u>					
	DATA CHANNEL NOS.: <u>1-48</u> (ON MAG TAPE)			AUXILIARY CHANNEL NOS.: <u>3 4</u>					
PARAMETER	RECORD LENGTH: <u>6</u> sec.	SAMPLE RATE: <input type="checkbox"/> 1 ms. <input type="checkbox"/> 4 ms. <input checked="" type="checkbox"/> 1 ms.	GAIN MODE: <input type="checkbox"/> INITIAL <input type="checkbox"/> MANUAL <input checked="" type="checkbox"/> FINAL <input type="checkbox"/> OPERATE	FILTERS: FREQ. <u>8</u> LO CUT HZ SLOPE <u>18</u>	FREQ. <u>128</u> HI CUT HZ SLOPE <u>20</u>	NOYCH FILTER: <input type="checkbox"/> IN <input checked="" type="checkbox"/> OUT			
DISPLAY	MODE: <input checked="" type="checkbox"/> AGC <input type="checkbox"/> FLOAT <input type="checkbox"/> DEFLOAT <input type="checkbox"/> DIRECT	AMPLIFIER: <input type="checkbox"/> DIRECT	INITIAL GAIN: <u>18</u> db	TRIP SENS.: <u>18</u> db	POLARITY CONVENTION: <input type="checkbox"/> NEGATIVE <input checked="" type="checkbox"/> POSITIVE	PRESSURE INCREASE ON GEOPHONE: <input type="checkbox"/> NEGATIVE <input checked="" type="checkbox"/> POSITIVE	NUMBERS ON MAG TAPE: <input type="checkbox"/> ON <input checked="" type="checkbox"/> OFF	DOWNBREAK / UPBREAK: <input type="checkbox"/> ON <input checked="" type="checkbox"/> OFF	ON DISPLAY
CFS I	TYPE STACK:	GATE LENGTH:	RECORD REJECTION:	NOISE REDUCTION:	NOISE THRESHOLD:	CORR. SCALING:	R.C.U. NORM/ALT SW.		
SOURCE	TYPE: <input checked="" type="checkbox"/> DYNAMITE <input type="checkbox"/> VIBROSEIS <input type="checkbox"/> OTHER	PATTERN: <u>Single hole - INline</u>	NO. OF POSITIONS:	INLINE SPACING:	LATERAL SPACING:	STAGGER:	LENGTH:	WIDTH:	LATERAL OFFSET:
		CHG/ HOLE: <u>20</u>	HOLE DEPTH: <u>75'</u>	SWEEP POSITION:	SWEEP START:	SWEEP END:	SWEEP LENGTH:	SWEEP TAPER:	PHASE COMP:
RECEIVER	TYPE: <u>GSC-20d</u>	PATTERN: <u>INline</u>	NO. OF ELEMENTS: <u>18</u>	INLINE SPACING: <u>12'</u>	LATERAL SPACING:	STAGGER:	LENGTH:	WIDTH:	LATERAL OFFSET:
	CONNECTION: <u>Series-Parallel</u>	RESISTANCE: <u>560</u> ohms	STAGGER:	LENGTH:	WIDTH:	LATERAL OFFSET:			
SPREAD	NO. OF GROUPS: <u>48</u>	GROUP INTERVAL: <u>220'</u>	SHOTPOINT INTERVAL: <u>880'</u>	FOLD: <u>6</u>	DIRECTION OF PROGRESSION: <u>W → E (NW)</u>	LEADING GROUP: <u>48</u>			
	OFFSET GROUP 1: <u>5170'</u>	OFFSET GROUP 2: <u>110'</u>	OFFSET GROUP 25: <u>3110'</u>	OFFSET GROUP 48: <u>5170'</u>					

DIAGRAMS/MISC. INFORMATION

76
100
SP101
106
107
FILE # 328 →
DAILY TESTS

PPAA
PPPA
PPAA
PPAA
PPAA
PPAA

STR-1
TR-20
CIR-75
TR-48
File # 341 - TEST TB

SHOTPOINT	TR 1 to 48		TR 10 to 20		SHOT		SPREAD		REMARKS	CORR STACK		
	REEL NO.	REC.	REEL NO.	REC.	SIZE	DEPTH	NO.	OFFSET		CDP SWITCH	LINE GROUPS	TR 1-48
1011	751A	342			20	167	1	29	95+1	- 106+1		
1012		343			20	167	2	33	96+1	- 107+1		
1013		344			20	167	3	37	97+1	- 108+1		
1014		345			20	167	4	41	98+1	- 109+1		
1015		346			20	167	5	45	99+1	- T14		
1016		347			20	167	6	49	100+1	- T8		
1017		348			20	167	7	53	101+1	- T12		
1018		349			20	167	8	57	102+1	- T16		
1019		350			20	167	9	61	103+1	- T20		
1010		351			20	167	10	65	104+1	- T24		
E O L												

RECORDED @ SP-106