




# LAND SEISMIC RECORDING LOG

CLIENT: <b>Husky</b>	PROSPECT: <b>NPR-A</b>	AREA: <b>BARROW</b>	LINE NO: <b>D9211</b>
PARTY NO: <b>1182</b>	INST. ENG: <b>Windham</b>		DATE: <b>MO 2 DAY 20 YR 77</b>
<b>INSTRUMENT</b> (9-TRACK)	<input type="checkbox"/> 1 SYSTEM <input checked="" type="checkbox"/> 2 SYSTEMS	<input checked="" type="checkbox"/> 24 & 25-48 <input type="checkbox"/> 1-48 & 49-96	TYPE: <input type="checkbox"/> DFS III <input checked="" type="checkbox"/> DFS II <input type="checkbox"/> DFS I <input type="checkbox"/> OTHER
<b>CONFIGURATION</b> (MAG TAPE)	FIELD TRACE NOS.: <b>1-48</b>	DATA CHANNEL NOS.: <b>1-48</b>	(ON MAG TAPE)
<b>PARAMETER</b>	RECORD LENGTH: <b>6</b> sec	SAMPLE RATE: <input checked="" type="checkbox"/> 1 ms <input type="checkbox"/> 4 ms	GAIN MODE: <input type="checkbox"/> INITIAL <input type="checkbox"/> MANUAL <input checked="" type="checkbox"/> FINAL <input type="checkbox"/> OPERATE
<b>DISPLAY</b>	MODE: <input checked="" type="checkbox"/> MAGC <input type="checkbox"/> FLOAT <input type="checkbox"/> AMPLIFIER <input type="checkbox"/> DEFLOAT <input type="checkbox"/> DIRECT	INITIAL GAIN: <b>13</b> db	JRIP SENS: <b>24</b> db
<b>CFS</b>	TYPE STACK:	GATE LENGTH:	RECORD REJECTION:
<b>SOURCE</b>	TYPE: <input type="checkbox"/> DYNAMITE <input type="checkbox"/> VIBROSEIS <input type="checkbox"/> OTHER	PATTERN: <b>Single hole - Inline</b>	NO. OF POSITIONS: <b>18</b>
<b>RECEIVER</b>	TYPE: <b>GSC-22d</b>	PATTERN: <b>Inline</b>	NO. OF ELEMENTS: <b>18</b>
<b>SPREAD</b>	NO. OF GROUPS: <b>48</b>	GROUP INTERVAL: <b>330'</b>	SHOTPOINT INTERVAL: <b>1320'</b>

DIAGRAMS/MISC. INFORMATION:

SHOTPOINT	TR 1 to 48		TR ... to ...		SHOT			SPREAD		REMARKS	CORR. STACK			
	REEL NO.	REC.	REEL NO.	REC.	SIZE	DEPTH	NO. OFFSET	DIR.	COP SWITCH		LINE GROUPS	HT.	REC.	HT.
21	2818	2812			40	5921			49	15+1 - 26+4				
22		2813			40	5922			53	16+1 - 27+4				
23		2814			40	5923			57	17+1 - 28+4				
24		2815			40	5924			29	18+1 - 29+4	4			Recorder @ SP-29
25		2816			40	5925			33	19+1 - 30+4				
26		2817			40	5926			37	20+1 - 31+4				
27		2818			40	5927			41	21+1 - 32+4				
28		2819			40	5928			45	22+1 - 33+4				
29		2820			40	5929			49	23+1 - 34+4				
30		2821			40	5930			53	24+1 - 35+4				
31		2822			40	5931			57	25+1 - 36+4				
32		2823			40	5932			29	26+1 - 37+4	5			Recorder @ SP-37
33		2824			40	5933			33	27+1 - 38+4				
34		2825			40	5934			37	28+1 - 39+4				
35		2826			40	5935			41	29+1 - 40+4				
36		2827			40	5936			45	30+1 - 41+4				
37		2828			40	5937			49	31+1 - 42+4				
38		2829			40	5938			53	32+1 - 43+4	6			Recorder @ SP-39
39		2830			40	5939			57	33+1 - 44+4				
40		2831			40	5940			29	34+1 - 45+4	7			Recorder @ SP-45

# LAND SEISMIC RECORDING LOG

	CLIENT: <b>Husky</b>	PROSPECT: <b>NPR-A</b>	AREA: <b>Barrow</b>	LINE NO: <b>192N</b>					
	PARTY NO: <b>1192</b>	INST. ENG: <b>William</b>		DATE: <b>MO 0 DAY 22 TR 79</b>					
INSTRUMENT	<input checked="" type="checkbox"/> 1 SYSTEM <input checked="" type="checkbox"/> 2 SYSTEMS	<input checked="" type="checkbox"/> 1-24 & 25-48 <input checked="" type="checkbox"/> 1-48 & 49-96	<input type="checkbox"/> DDFS III <input type="checkbox"/> DDFS IV	<input type="checkbox"/> 9 TRACK <input type="checkbox"/> 21 TRACK	FORMAT: <b>B</b>	<input type="checkbox"/> GAPPED <input type="checkbox"/> UNGAPPED	PACKING DENSITY: (LO) <input type="checkbox"/> 356 BPI (HI) <input type="checkbox"/> 712 BPI <input type="checkbox"/> 800 BPI <input type="checkbox"/> 1600 BPI		
	NO. BYTES IN HEADER REC: <b>5717</b>	NO. BYTES IN RECORD ID: _____	NO. BYTES PER SCAN: <b>134</b>	RECORD NUMBERS: <input checked="" type="checkbox"/> DEC. <input type="checkbox"/> OCT.	GAIN CONSTANT: <b>56</b> db	INPUT IMPEDANCE: <b>20,000</b> ohms			
CONFIGURATION (MAG TAPE)	FIELD TRACE NOS.: <b>1-48</b>	DATA CHANNEL NOS.: <b>1-48</b>	AUXILIARY DATA: (1) <b>FB</b> (2) <b>CH</b> (3) _____ (4) _____ (5) _____ (6) _____ (7) _____						
PARAMETER	RECORD LENGTH: <b>6.51</b> sec	SAMPLE RATE: <input type="checkbox"/> 1 ms. <input type="checkbox"/> 4 ms. <input type="checkbox"/> 2 ms. <input type="checkbox"/> _____ ms.	GAIN MODE: <input type="checkbox"/> INITIAL <input type="checkbox"/> MANUAL <input type="checkbox"/> OPERATE	FILTERS: FREQ. <b>8</b>	LO CUT HZ SLOPE <b>18</b>	H CUT HZ SLOPE <b>70</b>	NOTCH FILTER: <input type="checkbox"/> IN <input type="checkbox"/> OUT		
DISPLAY	MODE: <input checked="" type="checkbox"/> AGC <input type="checkbox"/> FLOAT <input type="checkbox"/> AMPLIFIER <input type="checkbox"/> DIRECT	INITIAL GAIN: <b>18</b> db	TRIP SENS: <b>24</b> db	POLARITY CONVENTION: _____	PRESSURE INCREASE ON GEOPHONE: <input type="checkbox"/> NEGATIVE <input type="checkbox"/> POSITIVE	NUMBERS ON MAG TAPE: _____	DOWNBREAK <input type="checkbox"/> UPBREAK <input type="checkbox"/> ON DISPLAY		
CF5 I	TYPE STACK: _____	GATE LENGTH: _____	RECORD REJECTION: _____	NOISE REDUCTION: _____	NOISE THRESHOLD: _____	CORR. SCALING: _____	R.C.U. NORM/ALT SW: _____		
SOURCE	TYPE: <input type="checkbox"/> DYNAMITE <input type="checkbox"/> VIBROSEIS <input type="checkbox"/> OTHER	PATTERN: <b>Single hole - Inline</b>	NO. OF POSITIONS: _____	INLINE SPACING: _____	LATERAL SPACING: _____	STAGGER: _____	LENGTH: _____	WIDTH: _____	LATERAL OFFSET: _____
		CHG/HOLE: <b>40</b> HOLE DEPTH: <b>75</b>	SWEEP POSITION: _____	SWEEP START: _____	SWEEP END: _____	SWEEP LENGTH: _____	SWEEP TAPER: _____	PHASE COMP: _____	
RECEIVER	TYPE: <b>GSC-200</b>	PATTERN: <b>Inline</b>	NO. OF ELEMENTS: <b>18</b>	INLINE SPACING: <b>18'</b>	LATERAL SPACING: _____	STAGGER: _____	LENGTH: _____	WIDTH: _____	LATERAL OFFSET: _____
	CONNECTION: <b>Series-Parallel</b>	RESISTANCE: <b>560</b> ohms							
SPREAD	NO. OF GROUPS: <b>48</b>	GROUP INTERVAL: <b>330'</b>	SHOTPOINT INTERVAL: <b>1320'</b>	FOLD: <b>6</b>	DIRECTION OF PROGRESSION: <b>N → S</b>	OFFSET GROUP 1: <b>7755'</b>	OFFSET GROUP 25: <b>165'</b>	OFFSET GROUP 48: <b>7755'</b>	LEADING GROUP: <b>48</b>

DIAGRAMS/MISC. INFORMATION:

SHOTPOINT	TR. 1 to 48		TR. 17 to 22		SHOT					SPREAD		REMARKS	CORR. STACK			
	REEL NO.	REC.	REEL NO.	REC.	SIZE	DEPTH	NO.	OFFSET	DIR.	COP SWITCH	LINE GROUPS		TR 1-16	TR 17-22	TR 23-28	TR 29-34
41	751094	302			40	59	41			33	35+1 - 46+4					
42		303			40	59	42			37	36+1 - 47+4					
43		304			40	59	43			41	37+1 - 48+4					
44		305			40	59	44			45	38+1 - 49+4					
45		306			40	59	45			49	39+1 - 50+4					
46		307			40	59	46			53	40+1 - 51+4					
47		308			40	59	47			57	41+1 - 52+4					
48		309			40	59	48			61	42+1 - 53+4					
49		310			40	59	49			65	43+1 - 54+4					

# LAND SEISMIC RECORDING LOG

*11:5 Hours*

	CLIENT: <u>Husky</u>	PROSPECT: <u>NPR-A</u>	AREA: <u>BARRON</u>	LINE NO: <u>09X1</u>	
	PARTY NO: <u>1182</u>	INST. ENG: <u>Windham</u>		DATE: <u>MO 2 DAY 21 TR 79</u>	

INSTRUMENT (9-TRACK)	<input type="checkbox"/> 1 SYSTEM <input type="checkbox"/> 2 SYSTEMS	<input type="checkbox"/> 1-24 & 25-48 <input type="checkbox"/> 1-48 & 49-96	ODDS EVENS <input type="checkbox"/> ODDS <input type="checkbox"/> EVENS	TYPE: <input type="checkbox"/> DFS III <input type="checkbox"/> DFS IV <input type="checkbox"/> OTHER	<input type="checkbox"/> 9 TRACK <input type="checkbox"/> 21 TRACK	FORMAT: SEG <u>B</u> <input type="checkbox"/> GAPPED <input type="checkbox"/> UNGAPPED	PACKING DENSITY: (LO) <input type="checkbox"/> 356 BPI <input type="checkbox"/> 800 BPI (HI) <input type="checkbox"/> 712 BPI <input type="checkbox"/> 1600 BPI
	NO. BYTES IN HEADER REC:	NO. BYTES IN RECORD ID:	NO. BYTES PER SCAN: <u>136</u>	RECORD NUMBERS: <input type="checkbox"/> DEC <input type="checkbox"/> OCT	GAIN CONSTANT: <u>30</u> db	INPUT IMPEDANCE: _____ ohms	


CONFIGURATION (MAG TAPE)	FIELD TRACE NOS.: <u>1-48</u> DATA CHANNEL NOS.: <u>1-48</u> (ON MAG TAPE)	AUXILIARY DATA: (1) <u>TR</u> (2) <u>2H</u> (3) (4) (5) (6) (7) AUXILIARY CHANNEL NOS.: <u>3</u> <u>4</u>
-----------------------------	---	--

PARAMETER	RECORD LENGTH: <u>6</u> sec	SAMPLE RATE: <input type="checkbox"/> 1 ms. <input type="checkbox"/> 4 ms. <input type="checkbox"/> 2 ms. <input type="checkbox"/> _____ ms.	GAIN MODE: <input type="checkbox"/> INITIAL <input type="checkbox"/> MANUAL <input checked="" type="checkbox"/> TRF <input type="checkbox"/> FINAL <input type="checkbox"/> OPERATE	FILTERS: FREQ. <u>8</u> LO CUT HZ SLOPE <u>18</u>	HI CUT HZ SLOPE <u>70</u> NOTCH FILTER: <input type="checkbox"/> IN <input type="checkbox"/> OUT
DISPLAY	MODE: <input type="checkbox"/> FLOAT <input type="checkbox"/> AMPLIFIER <input checked="" type="checkbox"/> RGC <input type="checkbox"/> DEFLOAT <input type="checkbox"/> DIRECT	INITIAL GAIN: <u>18</u> db	JRIP SENS: <u>18</u> db	POLARITY CONVENTION: _____	PRESSURE INCREASE ON GEOPHONE: <input type="checkbox"/> NEGATIVE } NUMBERS ON MAG TAPE <input type="checkbox"/> POSITIVE } <input type="checkbox"/> DOWNBREAK } ON DISPLAY <input type="checkbox"/> UPBREAK }
CFS I	TYPE STACK: _____	GATE LENGTH: _____	RECORD REJECTION: _____	NOISE REDUCTION: _____	NOISE THRESHOLD: _____

SOURCE	TYPE: <input checked="" type="checkbox"/> DYNAMITE <input type="checkbox"/> VIBROSEIS <input type="checkbox"/> OTHER	PATTERN: <u>Single hole - inline</u>	NO. OF POSITIONS: _____	INLINE SPACING: _____	LATERAL SPACING: _____	STAGGER: _____	LENGTH: _____	WIDTH: _____	LATERAL OFFSET: _____
		CHG/ HOLE: <u>H8</u>	HOLE DEPTH: <u>75</u>	SWEEP POSITION: _____	SWEEP START: _____	SWEEP END: _____	SWEEP LENGTH: _____	SWEEP TAPER: _____	PHASE COMP: _____

RECEIVER	TYPE: <u>CSC-20d</u>	PATTERN: <u>IN line</u>	NO. OF ELEMENTS: <u>18</u>	INLINE SPACING: <u>18'</u>	LATERAL SPACING: _____	STAGGER: _____	LENGTH: _____	WIDTH: _____	LATERAL OFFSET: _____
	CONNECTION: <u>Series-Parallel</u>	RESISTANCE: <u>560</u> ohms							

SPREAD	NO. OF GROUPS: <u>48</u>	GROUP INTERVAL: <u>330'</u>	SHOTPOINT INTERVAL: <u>1320'</u>	FOLD: <u>6</u>	DIRECTION OF PROGRESSION: <u>N → S</u>
	OFFSET GROUP 1: <u>7755'</u>	OFFSET GROUP 24: <u>165'</u>	OFFSET GROUP 25: <u>165'</u>	OFFSET GROUP 48/90: <u>7755'</u>	LEADING GROUP: <u>48</u>



SHOTPOINT	TR. 1 to 18		TR. 19 to 36		SHOT		SPREAD		REMARKS	CORR. STACK									
	REEL NO.	REC.	REEL NO.	REC.	SIZE	DEPTH	NO.	OFFSET		DIR.	CDP SWITCH	LINE GROUPS							
50																			
51	25	1213	16	17	22	23	20	27	29	30	32	33	37						
52																			
53																			
54																			
55																			
56																			
57																			
58																			
59																			
60																			
61																			
62																			
63																			
64																			
65																			
66																			
67																			
68																			
69																			

Recorder @ SP 55

Recorder @ SP 59

64+3 Dead

Recorder @ SP 65

Recorder @ SP 70

# LAND SEISMIC RECORDING LOG

	CLIENT: <b>Husky</b>	PROSPECT: <b>NPP-A</b>	AREA: <b>Barron</b>	LINE NO: <b>179XN</b>					
	PARTY NO: <b>1182</b>	INST. ENG: <b>Windham</b>		DATE: <b>MO 2 DAY 21 YR 79</b>					
INSTRUMENT (P-TRACK)	<input type="checkbox"/> 1 SYSTEM <input type="checkbox"/> 2 SYSTEMS	<input checked="" type="checkbox"/> 1-24 & 25-48 <input type="checkbox"/> 1-48 & 49-96	ODDS EVENS	TYPE: <input type="checkbox"/> DFS III <input type="checkbox"/> DFS IX <input type="checkbox"/> OTHER	<input checked="" type="checkbox"/> 1 TRACK <input type="checkbox"/> 2 TRACK	FORMAT: <b>B</b>	<input checked="" type="checkbox"/> GAPPED <input type="checkbox"/> UNGAPPED	PACKING DENSITY: (L0) <input type="checkbox"/> 356 BPI (M1) <input type="checkbox"/> 712 BPI <input type="checkbox"/> 800 BPI <input type="checkbox"/> 1600 BPI	
	NO. BYTES IN HEADER REC:	NO. BYTES IN RECORD ID:	NO. BYTES PER SCAN: <b>134</b>	RECORD NUMBERS: <input checked="" type="checkbox"/> DEC. <input type="checkbox"/> OCT	GAIN CONSTANT: <b>36</b> db	INPUT IMPEDANCE: <b>20000</b> ohms.	(1) (2) (3) (4) (5) (6) (7)		
CONFIGURATION (MAG TAPE)	FIELD TRACE NOS. <b>1-48</b>	DATA CHANNEL NOS. <b>1-48</b>	(ON MAG TAPE)	AUXILIARY DATA: <b>FR 111</b>	AUXILIARY CHANNEL NOS.: <b>3 4</b>				
PARAMETER	RECORD LENGTH: <b>2000</b> sec	SAMPLE RATE: <input type="checkbox"/> 1 ms. <input type="checkbox"/> 4 ms. <input checked="" type="checkbox"/> 20 ms.	GAIN MODE: <input type="checkbox"/> INITIAL <input type="checkbox"/> MANUAL <input type="checkbox"/> OPERATE	FILTERS: FREQ. <b>8</b>	LO CUT HZ SLOPE: <b>18</b>	FREQ. <b>128</b> HI CUT HZ SLOPE: <b>72</b>	NOTCH FILTER: <input type="checkbox"/> IN <input checked="" type="checkbox"/> OUT		
DISPLAY	MODE: <input type="checkbox"/> FLOAT <input type="checkbox"/> AMPLIFIER <input type="checkbox"/> DIRECT	INITIAL GAIN: <b>18</b> db	TRIP SENS.: <b>18</b> db	POLARITY CONVENTION: <input type="checkbox"/> NEGATIVE <input checked="" type="checkbox"/> POSITIVE	PRESSURE INCREASE ON GEOPHONE: <input type="checkbox"/> NUMBERS ON MAG. TAPE	<input type="checkbox"/> DOWNBREAK <input type="checkbox"/> UPBREAK	ON DISPLAY		
CFS I	TYPE STACK: <b>1-2</b>	GATE LENGTH:	RECORD REJECTION:	NOISE REDUCTION:	NOISE THRESHOLD:	CORR. SCALING:	R.C.U. NORM / ALT SW.		
SOURCE	TYPE: <input checked="" type="checkbox"/> DYNAMITE <input type="checkbox"/> VIBROSEIS <input type="checkbox"/> OTHER	PATTERN: <b>SINGLE hole - inline</b>	NO. OF POSITIONS: <b>48</b>	INLINE SPACING: <b>18'</b>	LATERAL SPACING:	STAGGER: <b>18'</b>	LENGTH: <b>18'</b>	WIDTH: <b>18'</b>	LATERAL OFFSET:
RECEIVER	CONNECTION: <b>Series - Parallel</b>	RESISTANCE: <b>560</b> ohms	NO. OF ELEMENTS: <b>18</b>	INLINE SPACING: <b>18'</b>	LATERAL SPACING:	STAGGER: <b>18'</b>	LENGTH: <b>18'</b>	WIDTH: <b>18'</b>	LATERAL OFFSET:
SPREAD	NO. OF GROUPS: <b>48</b>	GROUP INTERVAL: <b>330'</b>	SHOTPOINT INTERVAL: <b>1320'</b>	FOLD: <b>6</b>	OFFSET GROUP 1: <b>7755'</b>	OFFSET GROUP 24: <b>165'</b>	OFFSET GROUP 48: <b>7755'</b>	DIRECTION OF PROGRESSION: <b>N → S</b>	LEADING GROUP: <b>48</b>

DIAGRAMS/MISC. INFORMATION:

SHOTPOINT	TR 1 to 48		TR 10 to 48		SHOT			SPREAD			REMARKS	CORR. STACK			
	REEL NO	REC.	REEL NO.	REC.	SIZE	DEPTH	NO.	OFFSET	DIR.	CDP SWITCH		LINE GROUPS	ST UP	TR 1-24 REC.	TR 25-48 REC.
770	7518194	342			40	59	21			49	64+1 - 75+4	4			
771		343			40	59	22			53	65+1 - 76+4				
772		344			40	59	23			57	66+1 - 77+4				
773		345			40	59	24			29	67+1 - 78+4	5			Recorder @ 5278
774		346			40	59	25			33	68+1 - 79+4				
775		347			40	59	26			37	69+1 - 80+4				
776		348			40	59	27			41	70+1 - 81+4				
777		349			40	59	28			45	71+1 - 82+4				
778		350			40	59	29			49	72+1 - 83+4				
779		351			40	59	30			53	73+1 - 84+4				
801		352			40	59	31			57	74+1 - 85+4				
811		353			40	59	32			29	75+1 - 86+4	6			Recorder @ 52-86
821		354			40	59	33			33	76+1 - 87+4				
831		355			40	59	34			37	77+1 - 88+4				
841		356			40	59	35			41	78+1 - 89+4				
851		357			40	59	36			45	79+1 - 90+4				
861		358			40	59	37			49	80+1 - 91+4				
871		359			40	59	38			53	81+1 - 92+4				
881		360			40	59	39			57	82+1 - 93+4				
891		361			40	59	40			61	83+1 - 94+4				

E. O. L.