



LAND SEISMIC RECORDING LOG

P. 1 of 2



	CLIENT:	PROSPECT:	AREA:	LINE NO: R-7XN						
	PARTY NO: 96	INST. ENG:		DATE: MO 1 DAY 27 YR 69						
INSTRUMENT (9-TRACK)	<input type="checkbox"/> 1 SYSTEM <input type="checkbox"/> 2 SYSTEMS	<input type="checkbox"/> 1-24 & 25-48 <input type="checkbox"/> 1-48 & 49-96	ODDS EVENS	TYPE: <input type="checkbox"/> DFS <input checked="" type="checkbox"/> DFS	<input type="checkbox"/> 1 TRACK <input type="checkbox"/> 2 TRACK	FORMAT: SEG	<input type="checkbox"/> GAPPED <input type="checkbox"/> UNGAPPED	PACKING DENSITY:	(L) <input type="checkbox"/> 356 BPI <input type="checkbox"/> 800 BPI	(H) <input type="checkbox"/> 712 BPI <input type="checkbox"/> 1600 BPI
	NO. BYTES IN HEADER REC: 179	NO. BYTES IN RECORD ID:		NO. BYTES PER SCAN: 254	RECORD NUMBERS:	<input type="checkbox"/> DEC. <input type="checkbox"/> OCT.	GAIN CONSTANT: 36	4b	INPUT IMPEDANCE: 70 ohms	
CONFIGURATION (MAG TAPE)	FIELD TRACE NOS.: 1-96				AUXILIARY DATA:					
	DATA CHANNEL NOS.: 1-96 (ON MAG TAPE)				AUXILIARY CHANNEL NOS.:					
PARAMETER	RECORD LENGTH: 3 sec.	SAMPLE RATE: <input type="checkbox"/> 1 ms. <input type="checkbox"/> 4 ms. <input type="checkbox"/> 2 ms. <input type="checkbox"/> 8 ms.	GAIN MODE: <input type="checkbox"/> INITIAL <input type="checkbox"/> MANUAL <input type="checkbox"/> FINAL	FILTERS: FREQ. 9	LO CUT HZ SLOPE 12	FREQ. 170	HI CUT HZ SLOPE 22	NOTCH FILTER: <input type="checkbox"/> IN <input type="checkbox"/> OUT		
DISPLAY	MODE: <input type="checkbox"/> AGC <input type="checkbox"/> FLOAT <input type="checkbox"/> AMPLIFIER <input type="checkbox"/> DIRECT	INITIAL GAIN: 4b	TRIP SENS: 4b	POLARITY CONVENTION: <input type="checkbox"/> PRESSURE INCREASE ON GEOPHONE <input type="checkbox"/> NEGATIVE <input type="checkbox"/> POSITIVE	NUMBERS ON MAG. TAPE		<input type="checkbox"/> DOWNBREAK <input type="checkbox"/> UPBREAK	ON DISPLAY		
CFS I	TYPE STACK:	GATE LENGTH:	RECORD REJECTION:	NOISE REDUCTION:	NOISE THRESHOLD:	CORR. SCALING:	R.C.U. NORM./ALT SW.			
SOURCE	TYPE: <input type="checkbox"/> DYNAMITE <input type="checkbox"/> VIBROSEIS <input type="checkbox"/> OTHER	PATTERN: 100 105	NO. OF POSITIONS:	INLINE SPACING:	LATERAL SPACING:	STAGGER:	LENGTH:	WIDTH:	LATERAL OFFSET:	
	CHG/HOLE: 100	HOLE DEPTH: 105	SWEEP POSITION:	SWEEP START:	SWEEP END:	SWEEP LENGTH:	SWEEP TAPER:	PHASE COMP.		
RECEIVER	TYPE: 204	PATTERN: 100 105	NO. OF ELEMENTS: 15	INLINE SPACING: 15	LATERAL SPACING:	STAGGER:	LENGTH:	WIDTH:	LATERAL OFFSET:	
SPREAD	NO. OF GROUPS: 20	GROUP INTERVAL: 220'	SHOTPOINT INTERVAL: 50'	FOLD: 100%	DIRECTION OF PROGRESSION: North-South		LEADING GROUP: V-			
OFFSET GROUP 1: 10450'		OFFSET GROUP 48 : 110'	OFFSET GROUP 49 : 110'	OFFSET GROUP 48/96 : 11450'						

DIAGRAMS/MISC. INFORMATION: **North #1 10340' *48 P 49 10.340 *96 South Complete layout of line R-7XN**

SHOTPOINT	TR	TR 10		TR 20		SHOT		SPREAD		REMARKS:	CORR. STACK							
		REEL NO.	REC.	REEL NO.	REC.	SIZE	DEPTH	NO.	OFFSET		DIR.	CDF SWITCH	LINE GROUPS	TR 1-20	TR 21-40			
650	1	722500	10	22	23	20	20	94	105	1	S	1	T-48	639.1	1	643.4	644.1	Foot.
649			11			94	105	2				5	T-44	639.1				Work on my April notes
648			12			94	105	3				9	T-40	636.1				" " " "
647			13			94	105	4				17	T-36	636.1				" " " "
646			14			94	105	5				19	T-32	634.1				" " " "
645			15			94	105	6				21	T-28	633.1				" " " "
644			16			100	105	7				25	T-24	633.1				" " " "
643			17			100	105	8				27	T-20	631.1				" " " "
642			18			100	105	9				29	T-16	629.1				" " " "
641			19			100	105	10				27	T-12	629.1				" " " "
640			20			100	105	11				41	T-8	629.1				" " " "
639			21			100	105	12				45	T-4	629.1				" " " "
638			22			100	105	13				1	T-0	629.1				" " " "
637			23			100	105	14						629.1				" " " "
636			24			100	105	15						629.1				" " " "
635			25			100	105	16						629.1				" " " "
634			26			100	105	17						629.1				" " " "
633			27			100	105	18						629.1				" " " "
632			28			100	105	19						629.1				" " " "
631			29			100	105	20						629.1				" " " "

LAND SEISMIC RECORDING LOG

107143

	CLIENT: <i>107143</i>	PROSPECT: <i>107143</i>	AREA: <i>107143</i>	LINE NO: <i>107143</i>			
	PARTY NO: <i>107143</i>	INST. ENG: <i>107143</i>	DATE: <i>10/1/73</i>				
INSTRUMENT (9-TRACK)	<input type="checkbox"/> 1 SYSTEM <input checked="" type="checkbox"/> 2 SYSTEMS	<input type="checkbox"/> 1-24 & 25-48 <input type="checkbox"/> 1-48 & 49-96	<input type="checkbox"/> ODDS <input type="checkbox"/> EVENS	TYPE: <input type="checkbox"/> DFS <input checked="" type="checkbox"/> DFS	<input type="checkbox"/> 9 TRACK <input checked="" type="checkbox"/> 21 TRACK	FORMAT: <input type="checkbox"/> GAPPED <input type="checkbox"/> UNGAPPED	PACKING DENSITY: (LO) <input type="checkbox"/> 356 BPI (HI) <input type="checkbox"/> 712 BPI <input type="checkbox"/> 1600 BPI
	NO. BYTES IN HEADER REC: <i>29</i>	NO. BYTES IN RECORD ID: <i>254</i>	NO. BYTES PER SCAN: <i>254</i>	RECORD NUMBERS: <input type="checkbox"/> DEC. <input type="checkbox"/> OCT.	GAIN CONSTANT: <i>36</i> db	INPUT IMPEDANCE: <i>2000</i> ohms	
CONFIGURATION (MAG TAPE)	FIELD TRACE NOS.: <i>1-96</i>			AUXILIARY DATA:			
	DATA CHANNEL NOS.: <i>1-96</i> (ON MAG TAPE)			AUXILIARY CHANNEL NOS.:			
PARAMETER	RECORD LENGTH: <i>1</i> sec.	SAMPLE RATE: <input type="checkbox"/> 1 ms. <input type="checkbox"/> 4 ms. <input type="checkbox"/> 2 ms. <input type="checkbox"/> ms.	GAIN MODE: <input type="checkbox"/> INITIAL <input type="checkbox"/> MANUAL <input type="checkbox"/> FINAL <input type="checkbox"/> OPERATE	FILTERS: <input type="checkbox"/> FREQ. <i>0</i> LO CUT HZ SLOPE <i>18</i> HI CUT HZ SLOPE <i>12</i>	NOTCH FILTER: <input type="checkbox"/> IN <input type="checkbox"/> OUT		
DISPLAY	MODE: <input type="checkbox"/> FLOAT <input type="checkbox"/> AMPLIFIER <input type="checkbox"/> DIRECT	INITIAL GAIN: <i>25</i> db	TRIP SENS: <i>25</i> db	POLARITY CONVENTION: <input type="checkbox"/> NEGATIVE <input type="checkbox"/> POSITIVE	PRESSURE INCREASE ON GEOPHONE: <input type="checkbox"/> NEGATIVE <input type="checkbox"/> POSITIVE		NUMBERS ON MAG TAPE: <input type="checkbox"/> DOWNBREAK <input type="checkbox"/> UPBREAK
CFS I	TYPE STACK:	GATE LENGTH:	RECORD REJECTION:	NOISE REDUCTION:	NOISE THRESHOLD:	CORR. SCALING:	E.C.U. NORM./ALT SW
SOURCE	TYPE: <input type="checkbox"/> DYNAMITE <input type="checkbox"/> VIBROSEIS <input type="checkbox"/> OTHER	PATTERN:	NO. OF POSITIONS:	INLINE SPACING:	LATERAL SPACING:	STAGGER:	LENGTH:
	CHG/HOLE:	HOLE DEPTH:	SWEEP POSITION:	SWEEP START:	SWEEP END:	SWEEP LENGTH:	SWEEP TAPER:
RECEIVER	CONNECTION: <i>107143</i>	RESISTANCE: <i>200</i> ohms	STAGGER:	LENGTH:	WIDTH:	LATERAL OFFSET:	
SPREAD	NO. OF GROUPS: <i>96</i>	GROUP INTERVAL: <i>120</i>	SHOTPOINT INTERVAL: <i>960</i>	FOLD: <i>1</i>	DIRECTION OF PROGRESSION: <i>North to South</i>		
	OFFSET GROUP 1: <i>1-360</i>	OFFSET GROUP <i>48</i>	OFFSET GROUP <i>1</i>	OFFSET GROUP <i>1</i>	LEADING GROUP: <i>36</i>		

DIAGRAMS/MISC. INFORMATION:
North #1 10.340 ^{SP} 49 10340 96 South

SHOTPOINT	TR. 10		TR. 10		SHOT		SPREAD		REMARKS	CORR. STACK							
	REEL NO.	REC.	REEL NO.	REC.	SIZE	DEPTH	NO.	OFFSET		DIR.	COP SWITCH	LINE GROUPS		HT	REC	HT	REC
614	7225711	55			100	105	1		3	1	625.4	602.1					
613		56			101	106	2			5	625.4	602.1					
612		57			102	107	3			9	625.4	602.1					
611		58			103	108	4			13	625.4	602.1					
610		59			104	109	5			17	625.4	602.1					
609		60			105	110	6			21	625.4	602.1					
608		61			106	111	7			25	625.4	602.1					
607		62			107	112	8			29	625.4	602.1					
606		63			108	113	9			33	625.4	602.1					
605		64			109	114	10			37	625.4	602.1					
604		65			110	115	11			41	625.4	602.1					
603		66			111	116	12			45	625.4	602.1					
602		67			112	117	13			49	625.4	602.1					
601		68			113	118	14			53	625.4	602.1					
600		69			114	119	15			57	625.4	602.1					
599		70			115	120	16			61	625.4	602.1					
598		71			116	121	17			65	625.4	602.1					
597		72			117	122	18			69	625.4	602.1					
596		73			118	123	19			73	625.4	602.1					
595		74			119	124	20			77	625.4	602.1					

LAND SEISMIC RECORDING LOG

	CLIENT: <u>Hess</u>	PROSPECT: <u>South Sea E 200</u>	AREA: <u>Block 200</u>	LINE NO: <u>1170</u>	
PARTY NO: <u>1170</u>		INST. ENG:		DATE: <u>NOV 19 1968</u>	

INSTRUMENT (9-TRACK)	<input type="checkbox"/> 1 SYSTEM <input type="checkbox"/> 2 SYSTEMS	<input type="checkbox"/> 1-24 & 25-48 <input type="checkbox"/> 1-48 & 49-96	ODDS EVENTS	TYPE: <input type="checkbox"/> DFS III <input type="checkbox"/> DFS IV <input type="checkbox"/> OTHER	<input type="checkbox"/> 9 TRACK <input type="checkbox"/> 21 TRACK	FORMAT: SEG	<input type="checkbox"/> GAPPED <input type="checkbox"/> UNGAPPED	PACKING DENSITY: (L) <input type="checkbox"/> 356 BPI (M) <input type="checkbox"/> 712 BPI (H) <input type="checkbox"/> 1400 BPI			
NO. BYTES IN HEADER REC.		NO. BYTES IN RECORD ID		NO. BYTES PER SCAN		RECORD NUMBERS: <input type="checkbox"/> DEC. <input type="checkbox"/> OCT.		GAIN CONSTANT: (1) (2) (3) (4) (5) (7)		INPUT IMPEDANCE: ohms	
CONFIGURATION (MAG TAPE)						AUXILIARY DATA:					
FIELD TRACE NOS.:						AUXILIARY CHANNEL NOS.:					
DATA CHANNEL NOS.:						[ON MAG TAPE]					
PARAMETER		RECORD LENGTH: sec.		SAMPLE RATE: <input type="checkbox"/> 1 ms. <input type="checkbox"/> 4 ms. <input type="checkbox"/> 2 ms. <input type="checkbox"/> ms.		GAIN MODE: <input type="checkbox"/> INITIAL <input type="checkbox"/> FINAL		<input type="checkbox"/> MANUAL <input type="checkbox"/> OPERATE		FILTERS: FREQ. LO CUT HZ SLOPE HI CUT HZ SLOPE	
DISPLAY		MODE: <input type="checkbox"/> AGC <input type="checkbox"/> FLOAT <input type="checkbox"/> DEFOAT <input type="checkbox"/> DIRECT		AMPLIFIER		INITIAL GAIN: db		Z/HP SENS: db		POLARITY CONVENTION: PRESSURE INCREASE ON GEOPHONE	
CFS I		TYPE STACK:		GATE LENGTH:		RECORD REJECTION:		NOISE REDUCTION:		CORR. SCALING: R.C.U. NORM./ALT SW.	
SOURCE		TYPE: <input type="checkbox"/> DYNAMITE <input type="checkbox"/> VIBROSEIS <input type="checkbox"/> OTHER		PATTERN:		NO. OF POSITIONS:		INLINE SPACING:		LATERAL SPACING:	
RECEIVER		TYPE:		PATTERN:		NO. OF ELEMENTS:		INLINE SPACING:		LATERAL SPACING:	
SPREAD		NO. OF GROUPS:		GROUP INTERVAL:		SHOTPOINT INTERVAL:		FOLO:		DIRECTION OF PROGRESSION:	
		OFFSET GROUP 1:		OFFSET GROUP:		OFFSET GROUP:		OFFSET GROUP 48/96:		LEADING GROUP:	

DIAGRAMS/MISC. INFORMATION:

SHOTPOINT	TR 1 to		TR 2 to		SHOT					SPREAD			REMARKS	CORR STACK			
	REEL NO.	REC.	REEL NO.	REC.	SIZE	DEPTH	NO.	OFFSET	DIR	COP SWITCH	LINE GROUPS			IN UP	TR 1-48	TR 49-96	TR 1-48
584	722571	75			100	105	21		5	33	6054	5801					
583		76			100	105	22			37	6054	5801					
582		77			100	105	23			41	6054	5801					
581		78			100	105	24			45	6054	5801					
580		79			100	105	25			1	6054	5801	2				
589		80			100	105	26			5	6054	5801					
588		81			100	105	27			9	6054	5801					
587		82			100	105	28			13	6054	5801					
586		83			100	105	29			17	6054	5801					
585		84			100	105	30			21	6054	5801					
584		85			100	105	31			25	6054	5801					
583		86			100	105	32			29	6054	5801					
582		87			100	105	33			33	6054	5801					
581		88			100	105	34			37	6054	5801					
580		89			100	105	35			41	6054	5801					
579		90			100	105	36			45	6054	5801					
578		91			100	105	37			1	6054	5801					
577	722572	92			100	105	38			5	6054	5801					
576		93			100	105	39			9	6054	5801					
575		94			100	105	40			13	6054	5801					

LAND SEISMIC RECORDING LOG

4743

	CLIENT: 4743	PROSPECT: H. P. P. P. P.	AREA: H. P. P. P.	LINE NO.:						
	PARTY NO: 474	INST. ENG.:		DATE:						
INSTRUMENT (9-TRACK)	<input type="checkbox"/> 1 SYSTEM	<input type="checkbox"/> 1-24 & 25-48	<input type="checkbox"/> ODDS	TYPE: <input type="checkbox"/> DFS III	<input type="checkbox"/> 9 TRACK	FORMAT: <input type="checkbox"/> SEG	<input type="checkbox"/> GAPPED	PACKING DENSITY:	(LO) <input type="checkbox"/> 356 BPI	(HI) <input type="checkbox"/> 712 BPI
	<input type="checkbox"/> 2 SYSTEMS	<input type="checkbox"/> 1-48 & 49-96	<input type="checkbox"/> EVENS	<input type="checkbox"/> DFS II	<input type="checkbox"/> 21 TRACK		<input type="checkbox"/> UNGAPPED		<input type="checkbox"/> 800 BPI	<input type="checkbox"/> 1600 BPI
	NO. BYTES IN HEADER REC.:	NO. BYTES IN RECORD ID.:	NO. BYTES PER SCAN:	RECORD NUMBERS:	<input type="checkbox"/> DEC.	<input type="checkbox"/> OCT.	GAIN CONSTANT:	INPUT IMPEDANCE:	ohms.	
CONFIGURATION (MAG TAPE)	FIELD TRACE NOS.:			AUXILIARY DATA:			AUXILIARY CHANNEL NOS.:			
	DATA CHANNEL NOS.:			(ON MAG TAPE)						
PARAMETER	RECORD LENGTH: _____ sec.	SAMPLE RATE: <input type="checkbox"/> 1 sec. <input type="checkbox"/> 2 sec. <input type="checkbox"/> 4 sec. <input type="checkbox"/> 8 sec.	GAIN MODE: <input type="checkbox"/> INITIAL <input type="checkbox"/> FINAL <input type="checkbox"/> MANUAL <input type="checkbox"/> OPERATE	FILTERS: _____	LO CUT HZ SLOPE	FREQ. _____	HI CUT HZ SLOPE	NOISE FILTER: <input type="checkbox"/> IN <input type="checkbox"/> OUT		
DISPLAY	MODE: <input type="checkbox"/> AGC <input type="checkbox"/> FLOAT <input type="checkbox"/> AMPLIFIER <input type="checkbox"/> DEFOAT <input type="checkbox"/> DIRECT	INITIAL GAIN: _____ db	TRIP SENS: _____ db	POLARITY CONVENTION: _____	PRESSURE INCREASE ON GEOPHONE: <input type="checkbox"/> NEGATIVE <input type="checkbox"/> POSITIVE	NUMBERS ON ON MAG TAPE	<input type="checkbox"/> DOWNBREAK <input type="checkbox"/> UPBREAK	ON DISPLAY		
CFS I	TYPE STACK:	GATE LENGTH: _____	RECORD REJECTION: _____	NOISE REDUCTION: _____	NOISE THRESHOLD: _____	CORR. SCALING: _____	R.C.U. NORM./ALT SW.			
SOURCE	TYPE: <input type="checkbox"/> DYNAMITE <input type="checkbox"/> VIBROREIS <input type="checkbox"/> OTHER	PATTERN: _____	NO. OF POSITIONS: _____	INLINE SPACING: _____	LATERAL SPACING: _____	STAGGER: _____	LENGTH: _____	WIDTH: _____	LATERAL OFFSET: _____	
	CHG/ HOLE: _____	HOLE DEPTH: _____	SWEEP POSITION: _____	SWEEP START: _____	SWEEP END: _____	SWEEP LENGTH: _____	SWEEP TAPER: _____	PHASE COMP: _____		
RECEIVER	TYPE: _____	PATTERN: _____	NO. OF ELEMENTS: _____	INLINE SPACING: _____	LATERAL SPACING: _____	STAGGER: _____	LENGTH: _____	WIDTH: _____	LATERAL OFFSET: _____	
	CONNECTION: _____	RESISTANCE: _____ ohms								
SPREAD	NO. OF GROUPS: _____	GROUP INTERVAL: _____	SHOTPOINT INTERVAL: _____	FOLD: _____	DIRECTION OF PROGRESSION: _____	OFFSET GROUP 1: _____	OFFSET GROUP 44/96: _____	LEADING GROUP: _____		

DIAGRAMS/MISC. INFORMATION:

SHOTPOINT	TR. _____ to _____		TR. _____ to _____		SHOT					SPREAD			REMARKS:	CORR. STACK				
	REEL NO.	REC.	REEL NO.	REC.	SIZE	DEPTH	NO.	OFFSET	DIR.	CDP SWITCH	LINE GROUPS			SET UP	TR. 44	TR. 48	TR. 96	TR. 96
															HY.	REC.	HY.	REC.
524	722570	97			100	105	41		5	10	585.4	562.1						
523		98			100	120	42			21	584.4	471.1						
522		99			100	105	43			25	575.0	471.1						
521		100			100	105	44			27	590.0	470.0						
520		101			100	105	45			23	571.0	470.0						
519		102			100	105	46			27	620.0	470.0						
518		103			100	105	47	200'		41	590.0	470.0						
517		104			100	105	48			45	578.4	555.1						

LAND SEISMIC RECORDING LOG



Page 1 of 3

	CLIENT: <u>Husky</u>	PROSPECT: <u>1-24 & 25-48</u>	AREA: <u>1-24 & 25-48</u>	LINE NO.: <u>1-24</u>										
	PARTY NO.: <u>1151</u>	INST. ENG.: <u>14m K. - D.R.P.</u>	DATE: <u>MO 1 DAY 27 YE 79</u>											
INSTRUMENT (9-TRACK)	<input type="checkbox"/> 1 SYSTEM <input type="checkbox"/> 2 SYSTEMS	<input type="checkbox"/> 1-24 & 25-48 <input type="checkbox"/> 1-48 & 49-96	ODDS EVENTS: <input type="checkbox"/>	TYPE: <input type="checkbox"/> OPS III <input type="checkbox"/> OPS IX	<input type="checkbox"/> 9 TRACK <input type="checkbox"/> 21 TRACK	FORMAT: <u>SEG A</u>	<input type="checkbox"/> GAPPED <input type="checkbox"/> UNGAPPED	PACKING DENSITY: (L) <input type="checkbox"/> 356 BPI (H) <input type="checkbox"/> 712 BPI <input type="checkbox"/> 1400 BPI	NO. BYTES IN HEADER REC: <u>179</u>	NO. BYTES IN RECORD ID: _____	NO. BYTES PER SCAN: <u>254</u>	RECORD NUMBERS: <input type="checkbox"/> DEC. <input type="checkbox"/> OCT.	GAIN CONSTANT: <u>36</u> db	INPUT IMPEDANCE: <u>70,000</u> ohms.
	CONFIGURATION (MAG TAPE)	FIELD TRACE NOS.: <u>1-96</u>				AUXILIARY DATA:				AUXILIARY CHANNEL NOS.: _____				
PARAMETER	RECORD LENGTH: <u>2</u> sec.	SAMPLE RATE: <input type="checkbox"/> 1 ms. <input type="checkbox"/> 4 ms. <input type="checkbox"/> 2 ms.	GAIN MODE: <input type="checkbox"/> INITIAL <input type="checkbox"/> MANUAL <input type="checkbox"/> OPERATE	FILTERS: FREQ. <u>9</u> LO CUT HZ SLOPE <u>19</u> HI CUT HZ SLOPE <u>22</u>				INCH FILTER: <input type="checkbox"/> IN <input type="checkbox"/> OUT						
DISPLAY	MODE: <input type="checkbox"/> ACC <input type="checkbox"/> FLOAT <input type="checkbox"/> AMPLIFIER <input type="checkbox"/> DIRECT	INITIAL GAIN: _____ db	TRIP SENS: _____ db	POLARITY CONVENTION: <input type="checkbox"/> NEGATIVE } NUMBERS ON MAG. TAPE <input type="checkbox"/> DOWNBREAK } ON DISPLAY <input type="checkbox"/> POSITIVE } UPBREAK }										
CFS I	TYPE STACK: _____	GATE LENGTH: _____	RECORD REJECTION: _____	NOISE REDUCTION: _____ NOISE THRESHOLD: _____				CORR. SCALING: _____ R.C.U. NORM./ALT SW. _____						
SOURCE	TYPE: <input type="checkbox"/> DYNAMITE <input type="checkbox"/> VIBROSEIS <input type="checkbox"/> OTHER	PATTERN: <u>T.N.H.E.</u>	NO. OF POSITIONS: _____	INLINE SPACING: _____	LATERAL SPACING: _____	STAGGER: _____	LENGTH: _____	WIDTH: _____	LATERAL OFFSET: _____					
RECEIVER	TYPE: <u>2-1/2</u>	PATTERN: <u>T.N.H.E.</u>	NO. OF ELEMENTS: <u>10</u>	INLINE SPACING: _____				LATERAL SPACING: _____						
SPREAD	NO. OF GROUPS: _____	GROUP INTERVAL: <u>320'</u>	SHOTPOINT INTERVAL: <u>980'</u>	FOLD: <u>12.5%</u>				DIRECTION OF PROGRESSION: _____						
DIAGRAMS/MISC. INFORMATION:														
#1 → 12340 48 P 49 10340 96														

SHOTPOINT	TR. NO. _____		TR. NO. _____		SHOT			SPREAD			REMARKS	CORE STACK		
	REEL NO.	REC.	REEL NO.	REC.	SIZE	DEPTH	NO.	OFFSET	DIR.	COP SWITCH		LINE GROUPS	TR 1-48	TR 48-96
566	722570	114			100	105	1		3	1	577.4 554.1			
565		115			100	105	2			5	577.4 554.1			
564		116			100	105	3			9	577.4 554.1			
563		117			100	105	4			9	577.4 554.1			
562		118			100	105	5			17	577.4 554.1			
561		119			100	105	6			31	577.4 554.1			
560		120			100	105	7			30	577.4 554.1			
559		121			100	105	8			37	577.4 554.1			
558		122			100	105	9			33	577.4 554.1			
557		123			100	105	10			39	577.4 554.1			
556		124			100	105	11			11	577.4 554.1			
555		125			100	105	12			25	577.4 554.1			
554		126			100	105	13			1	577.4 554.1			
553		128			100	105	14			5	577.4 554.1			
552		129			100	105	15			3	577.4 554.1			
551		130			100	105	16			13	577.4 554.1			
550		131			100	105	17			11	577.4 554.1			
549		132			100	105	18			31	577.4 554.1			
548		133			100	105	19			25	577.4 554.1			
547		134			100	105	20			79	538.4 535.1			

LAND SEISMIC RECORDING LOG

Page 24.3



	CLIENT: Husky	PROSPECT: Southern Foothills	AREA: NPR-A ALASKA	LINE NO.: R-7XN					
	PARTY NO.: 1196	INST. ENG.:		DATE: MO 1 DAY 27 YE 79					
INSTRUMENT (9-TRACK)	<input type="checkbox"/> 1 SYSTEM <input type="checkbox"/> 2 SYSTEMS	<input type="checkbox"/> 1-24 & 25-48 <input type="checkbox"/> 1-48 & 49-96	ODDS <input type="checkbox"/> EVENS	TYPE: <input type="checkbox"/> DFS III <input type="checkbox"/> DFS IX <input type="checkbox"/> OTHER	<input type="checkbox"/> 9 TRACK <input type="checkbox"/> 21 TRACK	FORMAT: _____ SEG _____	<input type="checkbox"/> GAPPED <input type="checkbox"/> UNGAPPED	PACKING DENSITY: (L) <input type="checkbox"/> 356 BPI <input type="checkbox"/> 800 BPI	(H) <input type="checkbox"/> 712 BPI <input type="checkbox"/> 1400 BPI
	NO. BYTES IN HEADER REC:	NO. BYTES IN RECORD ID:	NO. BYTES PER SCAN:	RECORD NUMBERS: <input type="checkbox"/> DEC. <input type="checkbox"/> OCT.	GAIN CONSTANT: _____ db	INPUT IMPEDANCE: _____ ohms			
CONFIGURATION (MAG TAPE)	FIELD TRACE NOS.: _____			AUXILIARY DATA: (1) _____ (2) _____ (3) _____ (4) _____ (5) _____ (7) _____					
	DATA CHANNEL NOS.: _____			AUXILIARY CHANNEL NOS.: _____					
PARAMETER	RECORD LENGTH: _____ sec.	SAMPLE RATE: <input type="checkbox"/> 1 ms. <input type="checkbox"/> 4 ms. <input type="checkbox"/> 2 ms. <input type="checkbox"/> _____ ms.	GAIN MODE: <input type="checkbox"/> INITIAL <input type="checkbox"/> IFF	<input type="checkbox"/> MANUAL <input type="checkbox"/> OPERATE	FILTERS: _____	LO CUT HZ SLOPE _____	FREQ. _____	HI CUT HZ SLOPE _____	NOTCH FILTER: <input type="checkbox"/> IN <input type="checkbox"/> OUT
DISPLAY	MODE: <input type="checkbox"/> AGC <input type="checkbox"/> FLOAT <input type="checkbox"/> DEFOAT <input type="checkbox"/> DIRECT	AMPLIFIER <input type="checkbox"/> DIRECT	INITIAL GAIN: _____ db	TRIP SENS: _____ db	POLARITY CONVENTION: _____	PRESSURE INCREASE ON GEOPHONE: <input type="checkbox"/> NEGATIVE <input type="checkbox"/> POSITIVE	NUMBERS ON MAG TAPE: _____	<input type="checkbox"/> DOWNBREAK <input type="checkbox"/> UPBREAK	ON DISPLAY
CFS I	TYPE STACK: _____	GATE LENGTH: _____	RECORD REJECTION: _____	NOISE REDUCTION: _____	NOISE THRESHOLD: _____	CORR. SCALING: _____	R.C.U. NORM/ACT SW.		
SOURCE	TYPE: <input type="checkbox"/> DYNAMITE <input type="checkbox"/> VIBROSEIS <input type="checkbox"/> OTHER	PATTERN: _____	NO. OF POSITIONS: _____	INLINE SPACING: _____	LATERAL SPACING: _____	STAGGER: _____	LENGTH: _____	WIDTH: _____	LATERAL OFFSET: _____
	CHG/ MOLE: _____	HOLE DEPTH: _____	SWEEP POSITION: _____	SWEEP START: _____	SWEEP END: _____	SWEEP LENGTH: _____	SWEEP TAPER: _____	PHASE COMP: _____	
RECEIVER	TYPE: _____	PATTERN: _____	NO. OF ELEMENTS: _____	INLINE SPACING: _____	LATERAL SPACING: _____	STAGGER: _____	LENGTH: _____	WIDTH: _____	LATERAL OFFSET: _____
	CONNECTION: _____	RESISTANCE: _____ ohms							
SPREAD	NO. OF GROUPS: _____	GROUP INTERVAL: _____	SHOTPOINT INTERVAL: _____	FOLD: _____	DIRECTION OF PROGRESSION: _____	LEADING GROUP: _____			
	OFFSET GROUP 1: _____	OFFSET GROUP _____	OFFSET GROUP _____	OFFSET GROUP 48/96: _____					

DIAGRAMS/MISC. INFORMATION:

SHOTPOINT	TR _____ TO _____		TR _____ TO _____		SHOT			DIR.	CDP SWITCH	SPREAD		REMARKS:	CORR. STACK	
	REEL NO.	REC.	REEL NO.	REC.	SIZE	DEPTH	NO.			OFFSET	LINE GROUPS		STAGGER	TR 1-48
546	722.572	135			100	105	21	5	33	557.4	534.1			
545		136			100	105	22		37	556.4	533.1			
544		137			100	105	23		41	555.4	532.1			
543		138			100	105	24		45	554.4	531.1			
542		139			100	105	25		1	553.4	530.1	3	636.1 + 535.4 Insl.	
541	722.573	141			100	105	26		5	552.4	529.1		Tape Change File #140 - IFF	
540		142			100	105	27		9	551.4	528.1			
539		143			100	105	28		13	550.4	527.1			
538		144			100	105	29		17	549.4	526.1			
537		145			100	105	30		21	548.4	525.1			
536		146			100	105	31		25	547.4	524.1		Trace 94 dead.	
535		147			100	105	32		29	546.4	523.1		" 90 "	
534		148			100	105	33		33	545.4	522.1		" 86 "	
533		149			100	105	34		37	544.4	521.1		82 "	
532		150			100	105	35		41	543.4	520.1		78 "	
531		151			100	105	36		45	542.4	519.1		74 "	
530		152			100	105	37		1	541.4	518.1	4	Insl. 524.1 + 523.4	
529		153			100	105	38		5	540.4	517.1			
528		154			100	105	39		9	539.4	516.1			
527		155			100	105	40		13	538.4	515.1			

LAND SEISMIC RECORDING LOG

Page 3 of 3



	CLIENT: <u>Husky</u>	PROSPECT: <u>Southern Foothills</u>	AREA: <u>NPR-A ALASKA</u>	LINE NO.: <u>R-7XN</u>							
	PARTY NO.: <u>1196</u>	INST. ENG.:		DATE: <u>L DAY 27 YR 79</u>							
INSTRUMENT (9-TRACK)	<input type="checkbox"/> 1 SYSTEM	<input type="checkbox"/> 1-24 & 25-48	<input type="checkbox"/> ODDS	TYPE: <input type="checkbox"/> DFS III	<input type="checkbox"/> DFS X	<input type="checkbox"/> 9-TRACK	FORMAT: <input type="checkbox"/> SEG	<input type="checkbox"/> GAPPED	PACKING DENSITY: (L) <input type="checkbox"/> 356 BPI	(H) <input type="checkbox"/> 712 BPI	<input type="checkbox"/> 1400 BPI
	<input type="checkbox"/> 2 SYSTEMS	<input type="checkbox"/> 1-48 & 49-96	<input type="checkbox"/> EVENS	<input type="checkbox"/> DFS III	<input type="checkbox"/> OTHER	<input type="checkbox"/> 2PTRACK		<input type="checkbox"/> UNGAPPED			
	NO. BYTES IN HEADER REC.:	NO. BYTES IN RECORD ID:	NO. BYTES PER SCAN:	RECORD NUMBERS:	<input type="checkbox"/> DEC.	<input type="checkbox"/> OCT.	GAIN CONSTANT: _____ db	INPUT IMPEDANCE: _____ ohms			
CONFIGURATION (MAG TAPE)	FIELD TRACE NOS.:		DATA CHANNEL NOS.:		AUXILIARY DATA:						
PARAMETER	RECORD LENGTH: _____ sec.	SAMPLE RATE: <input type="checkbox"/> 1 ms. <input type="checkbox"/> 4 ms.	GAIN MODE: <input type="checkbox"/> IFF		<input type="checkbox"/> INITIAL	<input type="checkbox"/> MANUAL	FILTERS: _____		LO CUT _____	HI CUT _____	NOTCH FILTER: <input type="checkbox"/> IN <input type="checkbox"/> OUT
DISPLAY	MODE: <input type="checkbox"/> AGC <input type="checkbox"/> FLOAT <input type="checkbox"/> AMPLIFIER <input type="checkbox"/> DEFLOAT <input type="checkbox"/> DIRECT	INITIAL GAIN: _____ db	TRIP SENS: _____ db		POLARITY CONVENTION: _____		PRESSURE INCREASE ON GEOPHONE: _____		<input type="checkbox"/> NEGATIVE <input type="checkbox"/> POSITIVE		<input type="checkbox"/> NUMBERS ON MAG. TAPE <input type="checkbox"/> DOWNBREAK <input type="checkbox"/> UPBREAK
CFS I	TYPE STACK:	GATE LENGTH:	RECORD REJECTION:		NOISE REDUCTION:		NOISE THRESHOLD:		CORR. SCALING: _____		
SOURCE	TYPE: <input type="checkbox"/> DYNAMITE <input type="checkbox"/> VIBROSEIS <input type="checkbox"/> OTHER	PATTERN:	NO. OF POSITIONS:	INLINE SPACING:	LATERAL SPACING:	STAGGER:	LENGTH:	WIDTH:	LATERAL OFFSET:		
RECEIVER	CONNECTION:	RESISTANCE: _____ ohms	STAGGER:	INLINE SPACING:	LATERAL SPACING:	LENGTH:	WIDTH:	LATERAL OFFSET:			
SPREAD	NO. OF GROUPS:	GROUP INTERVAL:	SHOTPOINT INTERVAL:	FOLD:	DIRECTION OF PROGRESSION:	OFFSET GROUP 1:	OFFSET GROUP 48/96:	LEADING GROUP:			

DIAGRAMS/MISC. INFORMATION:

SHOTPOINT	TR 10		TR 10		SHOT				SPREAD			REMARKS	CORE STACK				
	REEL NO.	REC.	REEL NO.	REC.	SIZE	DEPTH	NO.	OFFSET	DIR.	CDP SWITCH	LINE GROUPS		SET UP	TR 1-48	TR 48-96	TR 96-144	TR 144-192
526	722	513	156		100	105	41		S	17	537.4	514.1	4				
525		157			100	105	42			21	536.4	513.1					
524		158			100	105	43			25	535.4	512.1					
523		159			100	105	44			29	534.4	511.1					
522		160			100	105	45			33	533.4	510.1					
521		161			100	105	46			37	532.4	509.1					
520		162			100	105	47			41	531.4	508.1		TRACE 96 DEAD			
519		163			100	105	48			45	530.4	507.1		92			

LAND SEISMIC RECORDING LOG

Page 1 of 3



	CLIENT: <u>Husky</u>	PROSPECT: <u>Southern Foothills</u>	AREA: <u>NPR-A Alaska</u>	LINE NO: <u>R-7XN</u>	
PARTY NO: <u>1186</u>		INST. ENG: <u>LEAVE BASE 700</u>		DATE: <u>MO 1 DAY 28 YR 79</u>	
INSTRUMENT (9-TRACK)	<input type="checkbox"/> 1 SYSTEM <input type="checkbox"/> 2 SYSTEMS		<input type="checkbox"/> 1-24 & 25-48 <input type="checkbox"/> 1-48 & 49-96		<input type="checkbox"/> ODDS <input type="checkbox"/> EVENS
	NO. BYTES IN HEADER REC: <u>128</u>		NO. BYTES IN RECORD ID: _____		NO. BYTES PER SCAN: <u>254</u>
CONFIGURATION (MAG TAPE)	FIELD TRACE NOS.: <u>1-96</u>			AUXILIARY DATA:	
	DATA CHANNEL NOS.: <u>1-96</u> [ON MAG TAPE]			AUXILIARY CHANNEL NOS.: _____	
PARAMETER	RECORD LENGTH: <u>8</u> sec.	SAMPLE RATE: <input type="checkbox"/> 1 sec. <input type="checkbox"/> 4 sec.	GAIN MODE: <input type="checkbox"/> INITIAL <input type="checkbox"/> MANUAL <input type="checkbox"/> FINAL	FILTERS: FREQ. <u>18</u> LO CUT HZ SLOPE <u>18</u>	HI CUT HZ SLOPE <u>72</u>
DISPLAY	MODE: <input type="checkbox"/> AGC <input type="checkbox"/> DEFLOAT <input type="checkbox"/> DIRECT	INITIAL GAIN: _____ db	TRIP SENS: _____ db	POLARITY CONVENTION: _____	PRESSURE INCREASE ON GEOPHONE: <input type="checkbox"/> NEGATIVE <input type="checkbox"/> POSITIVE
CFS I	TYPE STACK: _____	GATE LENGTH: _____	RECORD REJECTION: _____	NOISE REDUCTION: _____	NOISE THRESHOLD: _____
SOURCE	TYPE: <input checked="" type="checkbox"/> DYNAMITE <input type="checkbox"/> VIBROSEIS <input type="checkbox"/> OTHER		PATTERN: <u>INLINE</u>	NO. OF POSITIONS: _____	INLINE SPACING: _____
	CHG/ HOLE: <u>100</u>	HOLE DEPTH: <u>105</u>	SWEEP POSITION: _____	SWEEP START: _____	SWEEP END: _____
RECEIVER	TYPE: <u>Hst 10Hz</u>	PATTERN: <u>INLINE</u>	NO. OF ELEMENTS: <u>18</u>	INLINE SPACING: _____	LATERAL SPACING: _____
	CONNECTION: <u>SERIES</u>	RESISTANCE: _____ ohms	STAGGER: _____	LENGTH: _____	WIDTH: _____
SPREAD	NO. OF GROUPS: <u>96</u>	GROUP INTERVAL: <u>220'</u>	SHOTPOINT INTERVAL: <u>980'</u>	FOLD: <u>1200%</u>	DIRECTION OF PROGRESSION: <u>North-South</u>
	OFFSET GROUP 1: <u>10,450</u>	OFFSET GROUP <u>49</u> : <u>110'</u>	OFFSET GROUP <u>49</u> : <u>110'</u>	OFFSET GROUP <u>48/96</u> : <u>10,450</u>	LEADING GROUP: <u>96</u>

DIAGRAMS/MISC. INFORMATION:

SHOTPOINT	TR. _____ to _____		TR. _____ to _____		SHOT				SPREAD			REMARKS:	CORR. STACK		
	REEL NO.	REC.	REEL NO.	REC.	SIZE	DEPTH	NO.	OFFSET	DIR.	CDP SWITCH	LINE GROUPS		TR 1-48	TR 49-96	
516	722	1573	1173		100	105	1		S	1	529.4 506.1	1	FILE #164-172 Daily Tests.		
517		1774			100	105	2			5	528.4 505.1		TR 94 DEAD		
514		1775			100	105	3			9	527.4 504.1				
515		1776			100	105	4			13	526.4 503.1				
514		1777			100	105	5			17	525.4 502.1				
513		1778			100	105	6			21	524.4 501.1				
512		1779			100	105	7			25	523.4 500.1				
511		1780			100	105	8			29	522.4 499.1				
510		1781			100	105	9			33	521.4 499.1		TRACE 94 dead		
509		1782			100	105	10			37	520.4 499.1				
508		1783			100	105	11			41	519.4 496.1				
507		1784			100	105	12			45	518.4 495.1				
506		1785			100	105	13			1	517.4 494.1	2	INST 500.1 + 499.4		
505	722	574	1786		100	105	14			5	516.4 493.1		Tape Change File #186 IFP		
504		1787			100	105	15			9	515.4 492.1				
503		1788			100	105	16	25 W		13	514.4 491.1				
502		1789			100	105	17			17	513.4 490.1		TR 1 BAD		
501		1790			100	105	18			21	512.4 489.1		TR 1 BAD		
500		1791			100	105	19			25	511.4 488.1				
499		1792			100	105	20			29	510.4 487.1				

LAND SEISMIC RECORDING LOG

Page 3 of 3

	CLIENT: <u>Husky</u>	PROSPECT: <u>Southern Foothills</u>	AREA: <u>NPR-A Alaska</u>	LINE NO.: <u>R-72N</u>								
	PARTY NO.: <u>1186</u>	INST. ENG.:		DATE: <u>MO 1 DAY 28 YR 99</u>								
INSTRUMENT (9-TRACK)	<input type="checkbox"/> 1 SYSTEM <input type="checkbox"/> 2 SYSTEMS	<input type="checkbox"/> 1-24 & 25-48 <input type="checkbox"/> 1-48 & 49-96	<input type="checkbox"/> ODDS <input type="checkbox"/> EVENS	TYPE: <input type="checkbox"/> DFS III <input type="checkbox"/> DFS IX	<input type="checkbox"/> DFS X <input type="checkbox"/> OTHER	<input type="checkbox"/> 9 TRACK <input type="checkbox"/> 21 TRACK	FORMAT: <input type="checkbox"/> SEG	<input type="checkbox"/> GAPPED <input type="checkbox"/> UNGAPPED	PACKING DENSITY: (LO) <input type="checkbox"/> 336 BPI <input type="checkbox"/> 800 BPI	(HI) <input type="checkbox"/> 712 BPI <input type="checkbox"/> 1600 BPI		
	NO. BYTES IN HEADER REC:	NO. BYTES IN RECORD ID:	NO. BYTES PER SCAN:	RECORD NUMBERS: <input type="checkbox"/> DEC. <input type="checkbox"/> OCT.	GAIN CONSTANT: _____ db	INPUT IMPEDANCE: _____ ohms						
CONFIGURATION (MAG TAPE)	FIELD TRACE NOS.:			AUXILIARY DATA:			AUXILIARY CHANNEL NOS.:					
PARAMETER	RECORD LENGTH: _____ sec.	SAMPLE RATE: <input type="checkbox"/> 1 ms. <input type="checkbox"/> 4 ms. <input type="checkbox"/> 2 ms. <input type="checkbox"/> _____ ms.	GAIN MODE: <input type="checkbox"/> INITIAL <input type="checkbox"/> MANUAL <input type="checkbox"/> IFP <input type="checkbox"/> FINAL <input type="checkbox"/> OPERATE	FILTERS: _____		LO CUT HZ SLOPE: _____	FREQ. _____	HI CUT HZ SLOPE: _____	NOYCH FILTER: <input type="checkbox"/> IN <input type="checkbox"/> OUT			
DISPLAY	MODE: <input type="checkbox"/> AGC <input type="checkbox"/> DEFOAT <input type="checkbox"/> AMPLIFIER <input type="checkbox"/> DIRECT	INITIAL GAIN: _____ db	TRIP SENS: _____ db	POLARITY CONVENTION: _____		PRESSURE INCREASE ON GEOPHONE: <input type="checkbox"/> NEGATIVE <input type="checkbox"/> POSITIVE	NUMBERS ON MAG. TAPE: _____	DOWNBREAK <input type="checkbox"/> UPBREAK <input type="checkbox"/>	ON DISPLAY			
CFS I	TYPE STACK:	GATE LENGTH: _____	RECORD REJECTION: _____	NOISE REDUCTION: _____		NOISE THRESHOLD: _____	CORR. SCALING: _____	R.C.U. NORM/ALT SW.				
SOURCE	TYPE: <input type="checkbox"/> DYNAMITE <input type="checkbox"/> VIBROSEIS <input type="checkbox"/> OTHER	PATTERN: _____	NO. OF POSITIONS: _____	INLINE SPACING: _____	LATERAL SPACING: _____	STAGGER: _____	LENGTH: _____	WIDTH: _____	LATERAL OFFSET: _____			
	CHG/ HOLE: _____	HOLE DEPTH: _____	SWEEP POSITION: _____	SWEEP START: _____	SWEEP END: _____	SWEEP LENGTH: _____	SWEEP TAPER: _____	PHASE COMP. _____				
RECEIVER	TYPE: _____	PATTERN: _____	NO. OF ELEMENTS: _____	INLINE SPACING: _____		LENGTH: _____		LATERAL SPACING: _____		LATERAL OFFSET: _____		
	CONNECTION: _____	RESISTANCE: _____ ohms										
SPREAD	NO. OF GROUPS: _____	GROUP INTERVAL: _____	SHOTPOINT INTERVAL: _____		FOLD: _____		DIRECTION OF PROGRESSION: _____					
	OFFSET GROUP 1: _____	OFFSET GROUP _____	OFFSET GROUP _____		OFFSET GROUP 48/96: _____		LEADING GROUP: _____					

DIAGRAMS/MISC. INFORMATION:

SHOTPOINT	TR. _____ to _____		TR. _____ to _____		SHOT				SPREAD			REMARKS	CORR. STACK				
	REEL NO.	REC.	REEL NO.	REC.	SIZE	DEPTH	NO.	OFFSET	DIR.	CDP SWITCH	LINE GROUPS		TR 1-48	TR 49-96	TR 1-48	TR 49-96	
478	2250H	215			100	105	41		S	17	489.4	466.1					
477		216			100	105	42			21	489.4	466.1					
476		217			100	105	43			25	487.4	467.1					
475		218			100	105	44			29	486.4	468.1					
474		219			100	105	45			33	485.4	469.1					
473		220			100	105	46			37	484.4	468.1					
472		221			100	105	47			41	483.4	460.1					
471		222			100	105	48			45	482.4	459.1					
470		223			100	105	49			1	481.4	458.1	5				
469		224			100	105	50			5	480.4	457.1					
468		225			100	105	51			9	479.4	456.1					
467		226			100	105	52			13	478.4	455.1					
466		227			100	105	53			17	477.4	454.1					
465	225.7H	229			100	105	54			21	476.4	453.1					
464		230			100	105	55			25	475.4	452.1					
463		231			100	105	56			29	474.4	451.1					
462		232			100	105	57			33	473.4	450.1					
461		233			100	105	58			37	472.4	449.1					
460		234			100	105	59			41	471.4	448.1					
459		235			100	105	60			45	470.4	447.1					



*214 file - misfire

INBT 464.1 + 463.4

Tape Change File # 229 IFP

LAND SEISMIC RECORDING LOG

Page # 1 of 2

	CLIENT: Husky	PROSPECT: Southern Foothills	AREA: NFR-A Alaska	LINE NO: R-7XN					
	PARTY NO: 1186	INST. ENG.: DeRette - Parks	LEAVE BASE: 9:00 a.m.	ARRIVE BASE: 9:00	DATE: MO 1 DAY 29 YE 79				
INSTRUMENT (9-TRACK)	<input type="checkbox"/> 1 SYSTEM <input checked="" type="checkbox"/> 2 SYSTEMS	<input type="checkbox"/> 1-24 & 25-48 <input checked="" type="checkbox"/> 1-48 & 49-96	<input type="checkbox"/> ODDS <input checked="" type="checkbox"/> EVENS	TYPE: <input type="checkbox"/> DFS I <input checked="" type="checkbox"/> DFS II <input type="checkbox"/> OTHER	<input type="checkbox"/> 9 TRACK <input checked="" type="checkbox"/> 21 TRACK	FORMAT: B	<input type="checkbox"/> GAPPED <input type="checkbox"/> UNGAPPED	PACKING DENSITY: (L) <input type="checkbox"/> 356 BPI (H) <input type="checkbox"/> 712 BPI <input type="checkbox"/> 1400 BPI	
	NO. BYTES IN HEADER REC: 126	NO. BYTES IN RECORD ID:	NO. BYTES PER SCAN: 254	RECORD NUMBERS: <input type="checkbox"/> DEC. <input type="checkbox"/> OCT.	GAIN CONSTANT: 36 db	INPUT IMPEDANCE: 2000 ohms			
CONFIGURATION (MAG TAPE)	FIELD TRACE NOS.: 1-96			AUXILIARY DATA: (1) (2) (3) (4) (5) (6) (7)					
	DATA CHANNEL NOS.: 1-96			AUXILIARY CHANNEL NOS.:					
PARAMETER	RECORD LENGTH: 3 sec.	SAMPLE RATE: <input type="checkbox"/> 1 ms. <input type="checkbox"/> 4 ms. <input checked="" type="checkbox"/> 2 ms.	GAIN MODE: <input type="checkbox"/> INITIAL <input type="checkbox"/> MANUAL <input checked="" type="checkbox"/> FINAL <input type="checkbox"/> OPERATE	FILTERS: FREQ. 8	LO CUT HZ SLOPE 18	FREQ. 128	HI CUT HZ SLOPE 72	NOISE FILTER: <input type="checkbox"/> IN <input checked="" type="checkbox"/> OUT	
DISPLAY	MODE: <input type="checkbox"/> FLOAT <input type="checkbox"/> AMPLIFIER <input type="checkbox"/> DIRECT <input checked="" type="checkbox"/> AGC <input type="checkbox"/> DEFLOAT	INITIAL GAIN: 48 db	TRIP SENS: 48 db	POLARITY CONVENTION: <input type="checkbox"/> NEGATIVE <input checked="" type="checkbox"/> POSITIVE	PRESSURE INCREASE ON GEOPHONE: <input type="checkbox"/> NUMBERS ON MAG. TAPE	<input type="checkbox"/> DOWNBREAK <input type="checkbox"/> UPBREAK	ON DISPLAY		
CFS I	TYPE STACK:	GATE LENGTH:	RECORD REJECTION:	NOISE REDUCTION:	NOISE THRESHOLD:	CORR. SCALING:	R.C.U. NORM/ALT SW.		
SOURCE	TYPE: <input checked="" type="checkbox"/> DYNAMITE <input type="checkbox"/> VIBROSEIS <input type="checkbox"/> OTHER	PATTERN: INLINE	NO. OF POSITIONS:	INLINE SPACING:	LATERAL SPACING:	STAGGER:	LENGTH:	WIDTH:	LATERAL OFFSET:
	CHG/ HOLE: 100	HOLE DEPTH: 105	SWEEP POSITION:	SWEEP START:	SWEEP END:	SWEEP LENGTH:	SWEEP TAPER:	PHASE COMP:	
RECEIVER	TYPE: Hst 1042	PATTERN: INLINE	NO. OF ELEMENTS: 18	INLINE SPACING:	LATERAL SPACING:	STAGGER:	LENGTH:	WIDTH:	LATERAL OFFSET:
	CONNECTION: SERIES	RESISTANCE:							
SPREAD	NO. OF GROUPS:	GROUP INTERVAL: 220'	SHOTPOINT INTERVAL: 880'	FOLD: 1700%	DIRECTION OF PROGRESSION: South				
	OFFSET GROUP: 10450	OFFSET GROUP: 48, 110'	OFFSET GROUP: 48, 110'	OFFSET GROUP: 48/96: 10,450	LEADING GROUP: 96				

DIAGRAMS/MISC. INFORMATION:

* 10.340 → 48 49 → 96

SHOTPOINT	TR. 1 to		TR. 2 to		SHOT				SPREAD		REMARKS	CORR. STACK		
	REEL NO.	REC.	REEL NO.	REC.	SIZE	DEPTH	NO.	OFFSET	DIR.	CDP SWITCH		LINE GROUPS	TR. 1-24	TR. 48-96
452	702575	247	2223	2022	100	105	1	35	S	1	469.4	446.1		
453		248			100	105	2			5	468.7	445.1		
456		249			100	105	13			9	467.9	444.1		
455		250			100	105	14			13	466.4	443.1		
454		251			100	105	5			17	465.4	442.1		
453		252			100	105	6			21	464.4	441.1		
452		254			100	105	7			25	463.4	440.1		
451		255			100	105	8			29	462.4	439.1		
450		256			100	105	9			33	461.4	438.1		
449		257			100	105	10			37	460.4	437.1		
448		258			100	105	11			41	459.4	436.1		
447		259			100	105	12			45	458.4	435.1		
446		260			100	105	13	30	S	1	457.4	434.1	2	
445		261			100	105	14			5	456.4	433.1		
444		262			100	105	15			9	455.4	432.1		
443		263			100	105	16			13	454.4	431.1		
442		264			100	105	17			17	453.4	430.1		
441		265			100	105	18			21	452.4	429.1		
440		266			100	105	19			25	451.4	428.1		
439		267			100	105	20			29	450.4	427.1		

File # 236-246 Daily Tests

Inst. 452.1 + 451.4

File # 253 - MISFILE N.R.

Trace 93 Noisy

Inst. 440.1 + 439.4 96 NOISY

TR 85 NOISY



TR 11, 13, 21, 29, 34 + 35 NOISY

25, 24, 40 NOISY

21, 25 NOISY

LAND SEISMIC RECORDING LOG

Page 2 of 2

	CLIENT: <u>Husky</u>	PROSPECT: <u>Southern Foothills</u>	AREA: <u>NPR-A ALASKA</u>	LINE NO.: <u>R-7XW</u>						
	PARTY NO.: <u>1186</u>	INST. ENG.:		DATE: <u>MO 1 DAY 29 YR 79</u>						
INSTRUMENT (9-TRACK)	<input type="checkbox"/> 1 SYSTEM <input type="checkbox"/> 2 SYSTEMS	<input type="checkbox"/> 1-24 & 25-48 <input type="checkbox"/> 1-48 & 49-96	ODDS EYENS	TYPE: <input type="checkbox"/> DFS III <input type="checkbox"/> DFS IV <input type="checkbox"/> OTHER	<input type="checkbox"/> 9 TRACK <input type="checkbox"/> 21 TRACK	FORMAT: SEG	<input type="checkbox"/> GAPPED <input type="checkbox"/> UNGAPPED	PACKING DENSITY:	(L0) <input type="checkbox"/> 356 BPI <input type="checkbox"/> 800 BPI	(H1) <input type="checkbox"/> 712 BPI <input type="checkbox"/> 1600 BPI
	NO. BYTES IN HEADER REC.:	NO. BYTES IN RECORD ID:	NO. BYTES PER SCAN:	RECORD NUMBERS:	<input type="checkbox"/> DEC. <input type="checkbox"/> OCT.	GAIN CONSTANT:	db	INPUT IMPEDANCE:	ohms.	(1) (2) (3) (4) (5) (6) (7)
CONFIGURATION (MAG TAPE)	FIELD TRACE NOS.:			DATA CHANNEL NOS.:			(ON MAG TAPE)			
PARAMETER	RECORD LENGTH: _____ sec.	SAMPLE RATE: <input type="checkbox"/> 1 ms. <input type="checkbox"/> 4 ms. <input type="checkbox"/> 2 ms. <input type="checkbox"/> _____ ms.	GAIN MODE: <input type="checkbox"/> INITIAL <input type="checkbox"/> IFF <input type="checkbox"/> FINAL <input type="checkbox"/> OPERATE	FILTERS:	LO CUT HZ SLOPE	FREQ.	HI CUT HZ SLOPE	NOTCH FILTER: <input type="checkbox"/> IN <input type="checkbox"/> OUT		
DISPLAY	MODE: <input type="checkbox"/> AGC <input type="checkbox"/> FLOAT <input type="checkbox"/> DEFLOAT <input type="checkbox"/> AMPLIFIER <input type="checkbox"/> DIRECT	INITIAL GAIN: _____ db	SEIP SENS: _____ db	POLARITY CONVENTION: <input type="checkbox"/> NEGATIVE <input type="checkbox"/> POSITIVE	PRESSURE INCREASE ON GEOPHONE:	NUMBERS ON ON MAG. TAPE	<input type="checkbox"/> DOWNBREAK <input type="checkbox"/> UPBREAK	ON DISPLAY		
CFS I	TYPE STACK:	GATE LENGTH:	RECORD REJECTION:	NOISE REDUCTION:	NOISE THRESHOLD:	CORR. SCALING:	R.C.U. NORM/ALT SW.			
SOURCE	TYPE: <input type="checkbox"/> DYNAMITE <input type="checkbox"/> VIBROSEIS <input type="checkbox"/> OTHER	PATTERN:	NO. OF POSITIONS:	INLINE SPACING:	LATERAL SPACING:	STAGGER:	LENGTH:	WIDTH:	LATERAL OFFSET:	
RECEIVER	CONNECTION:	RESISTANCE:	ohms	STAGGER:	LENGTH:	WIDTH:	LATERAL OFFSET:			
SPREAD	NO. OF GROUPS:	GROUP INTERVAL:	SHOTPOINT INTERVAL:	FOLD:	OFFSET GROUP 48/96:	DIRECTION OF PROGRESSION:	LEADING GROUP:			

DIAGRAMS/MISC. INFORMATION:

SHOTPOINT	TR. _____ to _____		TR. _____ to _____		SHOT				SPREAD		REMARKS:	CORR. STACK	
	REEL NO.	REC.	REEL NO.	REC.	SIZE	DEPTH	NO.	OFFSET	DIR.	CDP SWITCH		LINE GROUPS	TR 1-48
438	722575	268			100	105	21		S	33	449.4 426.1		
437		269			100	105	22			37	448.4 425.1		
436		270			100	105	23			41	447.4 424.1	TR 93 Noisy	
435		271			100	105	24			45	446.4 423.1	" 89 " * 28.27	
434		272			100	105	25			1	445.4 422.1	3 Inst. 428.1 + 427.4	
433		273			100	105	26			5	444.4 421.1		
432		274			100	105	27			9	443.4 420.1		
431		275			100	105	28			13	442.4 419.1		
430		276			100	105	29			17	441.4 418.1		
429	722576	278			100	105	30			21	440.4 417.1	TAPE CHANGE File # 277 IFF TR 92 NOISY	
428		279			100	105	31			25	439.4 416.1		
427		280			100	105	32			29	438.4 415.1	72, 73, 78 Traces dead	
426		281			100	105	33			33	437.4 414.1		
425		282			100	105	34			37	436.4 413.1		
424		283			100	105	35			41	435.4 412.1		
423		284			100	105	36			45	434.4 411.1	TR 12 17 NOISY	

LAND SEISMIC RECORDING LOG

P 1/2



CLIENT: Husky		PROSPECT: Southern Foothills		AREA: NPR A ALASKA		LINE NO.: R-7XN			
PARTY NO.: 1186		INST. ENG.: DEREDE - HANU		LEAVE BASE: 7:00 AM		ARRIVE BASE: 9:30 P.M.		DATE: MO 1 DAY 30 YR 79	
INSTRUMENT <input type="checkbox"/> 1 SYSTEM <input checked="" type="checkbox"/> 2 SYSTEMS		<input type="checkbox"/> 1-24 & 25-48 <input checked="" type="checkbox"/> 1-48 & 49-96		<input type="checkbox"/> ODDS EVENS		<input type="checkbox"/> DFS III <input checked="" type="checkbox"/> DFS III		<input type="checkbox"/> DFS IV <input checked="" type="checkbox"/> OTHER	
<input type="checkbox"/> 9 TRACK <input checked="" type="checkbox"/> 21 TRACK		<input type="checkbox"/> GAPPED <input checked="" type="checkbox"/> UNGAPPED		PACKING DENSITY: (L) <input type="checkbox"/> 356 BPI <input type="checkbox"/> 800 BPI		<input type="checkbox"/> (M) <input type="checkbox"/> 712 BPI <input checked="" type="checkbox"/> 1600 BPI		NO. BYTES IN HEADER REC.: 178	
NO. BYTES IN RECORD ID:		NO. BYTES PER SCAN: 2571		RECORD NUMBERS: <input type="checkbox"/> DEC. <input type="checkbox"/> OCT		GAIN CONSTANT: 36 db		INPUT IMPEDANCE: 20,000 ohms	
CONFIGURATION (MAG TAPE)		FIELD TRACE NOS.: 1-96		AUXILIARY DATA:		AUXILIARY CHANNEL NOS.:		NO. OF TRACKS: (1) (2) (3) (4) (5) (6) (7)	
PARAMETER		RECORD LENGTH: 8 sec		SAMPLE RATE: <input type="checkbox"/> 1 ml. <input type="checkbox"/> 4 ms.		GAIN MODE: <input type="checkbox"/> INITIAL <input type="checkbox"/> MANUAL		FILTERS: FREQ. 8 LO CUT HZ SLOPE 18	
DISPLAY		<input type="checkbox"/> MODE: <input type="checkbox"/> AGC <input type="checkbox"/> FLOAT <input type="checkbox"/> DEFLAT		<input type="checkbox"/> AMPLIFIER <input type="checkbox"/> DIRECT		<input type="checkbox"/> INITIAL GAIN: 46 db		<input type="checkbox"/> POLARITY CONVENTION: <input type="checkbox"/> NEGATIVE <input type="checkbox"/> POSITIVE	
CFS I		TYPE STACK:		GATE LENGTH:		RECORD REJECTION:		NOISE REDUCTION:	
SOURCE		<input checked="" type="checkbox"/> DYNAMITE <input type="checkbox"/> VIBROSEIS <input type="checkbox"/> OTHER		PATTERN: INLINE		NO. OF POSITIONS:		INLINE SPACING:	
RECEIVER		TYPE: HST 1.6 Hz		PATTERN: INLINE		NO. OF ELEMENTS: 15		INLINE SPACING:	
SPREAD		CONNECTION: SERIES		RESISTANCE: ohms		STAGGER:		LENGTH:	
NO. OF GROUPS:		GROUP INTERVAL: 220'		SHOTPOINT INTERVAL: 580'		FOLD: 15.00%		DIRECTION OF PROGRESSION: South	
OFFSET GROUP 1: 10,460		OFFSET GROUP 49: 110'		OFFSET GROUP 15: 410'		OFFSET GROUP 48/96: 10450		LEADING GROUP: 96	

DIAGRAMS/MISC. INFORMATION:
 North \rightarrow 10340 \rightarrow 45° A 49° \rightarrow 10340 \rightarrow 46° South

SHOTPOINT	TR. to		TR. to		SHOT				SPREAD				REMARKS	CORR. STACK			
	REEL NO.	REC.	REEL NO.	REC.	SIZE	DEPTH	NO.	OFFSET	DIR.	CDP SWITCH	LINE GROUPS			FT	TR. 1-48	TR. 49-96	
423	722	296			100	105	1		S	1	433.1	410.1	1	File # 285-294 Daily Tests Inst 416.1 + 415.4			
421		296			100	105	2			5	432.4	409.1					
420		297			100	105	3			9	431.4	408.1					
419		298			100	105	4			13	430.4	407.1			TR 94 DEAD		
418		299			100	105	5			17	429.4	406.1					
417		300			100	105	6			21	428.4	405.1					
416		301			100	105	7			25	427.4	404.1					
415		302			100	105	8			29	426.4	403.1					
414		303			100	105	9			33	425.4	402.1					
413		304			100	105	10			37	424.4	401.1					
412		305			100	105	11			41	423.4	400.1					
411		306			100	105	12			45	422.4	399.1					
410		307			100	105	13			1	421.4	398.1	2		Inst 404.1 + 403.4		
409		308			100	105	14			5	420.4	397.1					
408		309			100	105	15			9	419.4	396.1					
407		310			100	105	16			13	418.4	395.1					
406		311			100	105	17			17	417.4	394.1					
405		312			100	105	18			21	416.4	393.1					
404		NA			100	105	19			25	415.4	392.1		313 + 314 File # 315 SHOT FIRED	PRE MAJURE		
403		313			100	105	20			29	414.4	391.1		Rec # 316, 317, 2006			

LAND SEISMIC RECORDING LOG

P 2 OF 2

	CLIENT: <i>U.S. G.P.</i>	PROSPECT: <i>Southwest Alaska</i>	AREA: <i>WPA Alaska</i>	LINE NO: <i>1-71N</i>					
PARTY NO: <i>1191</i>		INST. ENG.:		DATE: <i>NO 1 DAY 25 YR 79</i>					
INSTRUMENT (9-TRACK)	<input type="checkbox"/> 1 SYSTEM <input type="checkbox"/> 2 SYSTEMS	<input type="checkbox"/> 1-24 & 25-48 <input type="checkbox"/> 1-48 & 49-96	ODDS & EVENS	TYPE: <input type="checkbox"/> DFS III <input type="checkbox"/> DFS IX <input type="checkbox"/> OTHER	<input type="checkbox"/> 9 TRACK <input type="checkbox"/> 21 TRACK	FORMAT: SEG	<input type="checkbox"/> GAPPED <input type="checkbox"/> UNGAPPED	PACKING DENSITY: (L) <input type="checkbox"/> 356 BPI (H) <input type="checkbox"/> 712 BPI <input type="checkbox"/> 800 BPI <input type="checkbox"/> 1600 BPI	
	NO. BYTES IN HEADER REC.	NO. BYTES IN RECORD ID:	NO. BYTES PER SCAN:	RECORD NUMBERS:	<input type="checkbox"/> DEC. <input type="checkbox"/> OCT.	GAIN CONSTANT: _____ db	INPUT IMPEDANCE: _____ ohms	(1) (2) (3) (4) (5) (6) (7)	
CONFIGURATION (MAG TAPE)	FIELD TRACE NOS.:			AUXILIARY DATA:			AUXILIARY CHANNEL NOS.:		
PARAMETER	RECORD LENGTH: _____ sec.	SAMPLE RATE: <input type="checkbox"/> 1 ms. <input type="checkbox"/> 4 ms. <input type="checkbox"/> 2 ms. _____ ms.	GAIN MODE: <input type="checkbox"/> INITIAL <input type="checkbox"/> IFF <input type="checkbox"/> FINAL	MANUAL OPERATE	FILTERS: FREQ.	LO CUT HZ SLOPE	HIGH CUT HZ SLOPE	NOTCH FILTER: <input type="checkbox"/> IN <input type="checkbox"/> OUT	
DISPLAY	MODE: <input type="checkbox"/> AGC <input type="checkbox"/> FLOAT <input type="checkbox"/> DEFLAT <input type="checkbox"/> AMPLIFIER <input type="checkbox"/> DIRECT	INITIAL GAIN: _____ db	TRIP SENS: _____ db	POLARITY CONVENTION: <input type="checkbox"/> NEGATIVE <input type="checkbox"/> POSITIVE	PRESSURE INCREASE ON GEOPHONE:	NUMBERS ON ON MAG. TAPE		<input type="checkbox"/> DOWNBREAK <input type="checkbox"/> UPBREAK ON DISPLAY	
CFS I	TYPE STACK:	GATE LENGTH:	RECORD REJECTION:	NOISE REDUCTION:	NOISE THRESHOLD:	CORR. SCALING:	E.C.U. NORM./ALT. SW.		
SOURCE	TYPE: <input type="checkbox"/> DYNAMITE <input type="checkbox"/> VIBROSEIS <input type="checkbox"/> OTHER	PATTERN:	NO. OF POSITIONS:	INLINE SPACING:	LATERAL SPACING:	STAGGER:	LENGTH:	WIDTH:	LATERAL OFFSET:
RECEIVER	CONNECTION:	PATTERN:	RESISTANCE: _____ ohms	NO. OF ELEMENTS:	STAGGER:	INLINE SPACING:	LENGTH:	WIDTH:	LATERAL OFFSET:
SPREAD	NO. OF GROUPS:	GROUP INTERVAL:	OFFSET GROUP _____	SHOTPOINT INTERVAL:	OFFSET GROUP _____	FOLD:	OFFSET GROUP 46/96: _____	DIRECTION OF PROGRESSION:	LEADING GROUP:

DIAGRAMS/MISC. INFORMATION:

SHOTPOINT	TR. _____ TO _____		TR. _____ TO _____		SHOT				SPREAD				REMARKS	CORR. STACK						
	REEL NO.	REC.	REEL NO.	REC.	SIZE	DEPTH	NO.	OFFSET	DIR.	CDP SWITCH	LINE GROUPS			SET UP	HT	REC	HT	REC		
630	72	1570	30	22	23	26	27	29	30	32	35	37	5	33	611.4	618.1				
629			31											37	610.4	617.1				
628			32											41	608.4	616.1				
627			33											45	607.4	615.1				
626			34											1	605.4	614.1	3			
625			35											5	604.4	613.1				
624			36											9	603.4	612.1				
623			37											13	602.4	611.1				
622			38											17	601.4	610.1				
621			39											21	600.4	609.1				
620			40											25	599.4	608.1				
619			41											29	598.4	607.1				
618			42											33	597.4	606.1				
617			43											37	596.4	605.1				
616			44											41	595.4	604.1				
615			45											45	594.4	603.1				