



LAND SEISMIC RECORDING LOG

Recording S. 10

1 of 2



	CLIENT: HUSKY	PROSPECT: NPRA	AREA: TUNALIH	LINE NO: 26XW					
PARTY NO: 1182		INST. ENG: STREFF		DATE: 1 DAY 15 YR 80					
INSTRUMENT (9-TRACK)	<input type="checkbox"/> 1 SYSTEM <input type="checkbox"/> 2 SYSTEMS	<input type="checkbox"/> T-24 & 25-48 <input type="checkbox"/> 1-48 & 49-96	<input type="checkbox"/> ODDS <input type="checkbox"/> EVENS	TYPE: <input type="checkbox"/> DFS III <input type="checkbox"/> DFS IV	<input type="checkbox"/> 9 TRACK <input type="checkbox"/> 21 TRACK	FOFPHAT. SEG: B	<input type="checkbox"/> DAPPED <input type="checkbox"/> UNGAPPED	PACKING DENSITY: (LO) <input type="checkbox"/> 356 BPI <input type="checkbox"/> 800 BPI	(HI) <input type="checkbox"/> 712 BPI <input type="checkbox"/> 1600 BPI
	NO. BYTES IN HEADER REC:	NO. BYTES IN RECORD ID:	NO. BYTES PER SCAN:	RECORD NUMBERS: <input type="checkbox"/> DEC. <input type="checkbox"/> OCT.	GAIN CONSTANT: 36 db	INPUT IMPEDANCE: 20K ohms.	FIELD TRACE NOS.: 1-48		
CONFIGURATION (MAG TAPE)	DATA CHANNEL NOS.: 1-48			AUXILIARY DATA: (1) (2) (3) (4) (5) (6) (7)					
PARAMETER	RECORD LENGTH: 6 sec.	SAMPLE RATE: <input type="checkbox"/> 1 ms. <input type="checkbox"/> 4 ms. <input type="checkbox"/> 2 ms. <input type="checkbox"/> 8 ms.	GAIN MODE: <input type="checkbox"/> INITIAL <input checked="" type="checkbox"/> OFF	<input type="checkbox"/> MANUAL <input type="checkbox"/> OPERATE	FILTERS: FREQ. 8	LO CUT HZ SLOPE 18	HIGH CUT HZ SLOPE 70	NOTCH FILTER: <input type="checkbox"/> IN <input type="checkbox"/> OUT	
DISPLAY	MODE: <input checked="" type="checkbox"/> ABC <input type="checkbox"/> FLOAT <input type="checkbox"/> DEFLOAT <input type="checkbox"/> AMPLIFIER <input type="checkbox"/> DIRECT	INITIAL GAIN: 24 db	JRIP SENS: 3 db	POLARITY CONVENTION: <input type="checkbox"/> NEGATIVE <input type="checkbox"/> POSITIVE	PRESSURE INCREASE ON GEOPHONE: <input type="checkbox"/> NEGATIVE <input type="checkbox"/> POSITIVE	NUMBERS ON MAG. TAPE: <input type="checkbox"/> DOWNBREAK <input type="checkbox"/> UPBREAK	ON DISPLAY: <input type="checkbox"/> DOWNBREAK <input type="checkbox"/> UPBREAK		
CFS I	TYPE STACK:	GATE LENGTH:	RECORD REJECTION:	NOISE REDUCTION:	NOISE THRESHOLD:	CORR. SCALING:	R.C.U. NORM/ALT SW.		
SOURCE	TYPE: <input checked="" type="checkbox"/> DYNAMITE <input type="checkbox"/> VIBROSEIS <input type="checkbox"/> OTHER	PATTERN: in line / hole	NO. OF POSITIONS:	INLINE SPACING:	LATERAL SPACING:	STAGGER:	LENGTH:	WIDTH:	LATERAL OFFSET:
RECEIVER	CONNECTION: 20-11 series	RESISTANCE: 580 ohms	NO. OF ELEMENTS: 12	STAGGER:	LENGTH:	WIDTH:	LATERAL OFFSET:	CHG/ HOLE: 50 HOLE DEPTH: 75	
SPREAD	NO. OF GROUPS: 48	GROUP INTERVAL: 330	SHOTPOINT INTERVAL: 1320	FOLD: 6	DIRECTION OF PROGRESSION: W	LEADING GROUP: 48			

DIAGRAMS/MISC. INFORMATION:
 T-1 X T-23 X T-1+2 X T-7+1 X
 TR#2 TR#29 SPI TR#25 #280-291 tests
 # 292 test TB

SHOTPOINT	TR. 1-48		TR. 49-96		SHOT		SPREAD		REMARKS	CORR. STACK			
	REEL NO.	REC.	REEL NO.	REC.	SIZE	DEPTH	NO.	OFFSET		DIR.	CDP SWITCH	LINE GROUPS	TR 1-48 REC.
1	293	293			50	67	1			40	T-1 - 7+1		
2		294			50	67	2			44	T-4 - 8+1		
3		295			50	67	3			48	T-8 - 9+1		
4		296			50	67	4			52	T-10 - 10+1		
5		297			50	67	5			56	T-18 - 11+1		
6		298			50	67	6			60	T-20 - 12+1		
7		299			50	67	7			64	T-24 - 13+1		
8		300			50	67	8			68	1+4 - 14+1		
9		301			50	67	9			72	2+4 - 15+1		
10		302			50	67	10			76	3+4 - 16+1		
11		303			50	67	11			80	4+4 - 17+1		
12		304			50	67	12			84	5+4 - 18+1		
13		305			50	67	13			88	6+4 - 19+1		
14		306			50	67	14			92	7+4 - 20+1		
15		307			50	67	15			96	8+4 - 21+1		
16		308			50	67	16			100	9+4 - 22+1		
17		309			50	67	17			104	10+4 - 23+1		
18		310			50	67	18			108	11+4 - 24+1		
19		311			50	67	19			112	12+4 - 25+1		
20		312			50	67	20			116	13+4 - 26+1		

LAND SEISMIC RECORDING LOG

2 of 2

	CLIENT: Husky	PROSPECT: NPR-A	AREA: TUNALIK	LINE NO.: 26XW									
	PARTY NO.: 1182	INST. ENG.: STREFF		DATE: MO 1 DAY 15 YR 80									
INSTRUMENT (9-TRACK)	<input checked="" type="checkbox"/> SYSTEM <input checked="" type="checkbox"/> 2 SYSTEMS	<input checked="" type="checkbox"/> 24 & 25-48 <input checked="" type="checkbox"/> 1-48 & 49-96	<input checked="" type="checkbox"/> ODDS <input checked="" type="checkbox"/> EVENS	TYPE: <input type="checkbox"/> DFS III <input type="checkbox"/> DFS IV	<input checked="" type="checkbox"/> TRACK <input type="checkbox"/> 21 TRACK	FORMAT: B	<input type="checkbox"/> GAPPED <input type="checkbox"/> UNGAPPED	PACKING DENSITY: (10) <input type="checkbox"/> 356 BPI 800 BPI (11) <input type="checkbox"/> 712 BPI 1400 BPI					
	NO. BYTES IN HEADER REC:	NO. BYTES IN RECORD ID:	NO. BYTES PER SCAN:	RECORD NUMBERS: <input checked="" type="checkbox"/> DEC. <input type="checkbox"/> OCT.	GAIN CONSTANT: 36 db	INPUT IMPEDANCE: 207 ohms							
CONFIGURATION (MAG TAPE)	FIELD TRACE NOS.: 1-48			AUXILIARY DATA:			(1)	(2)	(3)	(4)	(5)	(6)	(7)
	DATA CHANNEL NOS.: 1-48			AUXILIARY CHANNEL NOS.:									
PARAMETER	RECORD LENGTH: 6 sec.	SAMPLE RATE: <input type="checkbox"/> 1 ms. <input type="checkbox"/> 4 ms. <input checked="" type="checkbox"/> 2 ms.	GAIN MODE: <input type="checkbox"/> INITIAL <input checked="" type="checkbox"/> TRF	<input type="checkbox"/> MANUAL <input checked="" type="checkbox"/> OPERATE	FILTERS: FREQ. 8 LO CUT HZ SLOPE 18	FREQ. 128 HI CUT HZ SLOPE 70	NOTCH FILTER: <input type="checkbox"/> IN <input type="checkbox"/> OUT						
DISPLAY	MODE: <input checked="" type="checkbox"/> ACC <input type="checkbox"/> FLOAT <input type="checkbox"/> DEFLOAT	<input type="checkbox"/> AMPLIFIER <input type="checkbox"/> DIRECT	INITIAL GAIN: 0.4 db	TRIP SENS: 2 db	POLARITY CONVENTION: <input type="checkbox"/> NEGATIVE <input checked="" type="checkbox"/> POSITIVE	PRESSURE INCREASE ON GEOPHONE: <input type="checkbox"/> NEGATIVE <input checked="" type="checkbox"/> POSITIVE	NUMBERS ON MAG. TAPE: <input type="checkbox"/> DOWNBREAK <input type="checkbox"/> UPBREAK	ON DISPLAY: <input type="checkbox"/> ON <input type="checkbox"/> OFF					
CFS I	TYPE STACK:	GATE LENGTH:	RECORD REJECTION:	NOISE REDUCTION:	NOISE THRESHOLD:	CORR. SCALING:	R.C.U. NORM./ALT SW.						
SOURCE	TYPE: <input checked="" type="checkbox"/> DYNAMITE <input type="checkbox"/> VIBROSEIS <input type="checkbox"/> OTHER	PATTERN: Inline/Hole	NO. OF POSITIONS:	INLINE SPACING:	LATERAL SPACING:	STAGGER:	LENGTH:	WIDTH:	LATERAL OFFSET:				
	CHG/HOLE: 50	HOLE DEPTH: 75	SWEEP POSITION:	SWEEP START:	SWEEP END:	SWEEP LENGTH:	SWEEP TAPER:	PHASE COMP:					
RECEIVER	TYPE: 20-D	PATTERN: Inline	NO. OF ELEMENTS: 12	INLINE SPACING: 28	LATERAL SPACING:	STAGGER:	LENGTH: 330	WIDTH:	LATERAL OFFSET:				
	CONNECTION: Series Parallel	RESISTANCE: 580 ohms	STAGGER:										
SPREAD	NO. OF GROUPS: 48	GROUP INTERVAL: 330	SHOTPOINT INTERVAL: 1320	FOLD: 6	DIRECTION OF PROGRESSION: West								
	OFFSET GROUP 1: 8085	OFFSET GROUP 24: 495	OFFSET GROUP 25: 495	OFFSET GROUP 48/96: 8085	LEADING GROUP: 48								

DIAGRAMS/MISC. INFORMATION:

SHOTPOINT	TR. to		TR. to		SHOT										SPREAD		REMARKS:	CORR. STACK	
	REEL NO.	REC.	REEL NO.	REC.	SIZE	DEPTH	NO.	OFFSET	DIR.	CDP SWITCH	LINE GROUPS		SET UP	TR 1-48	TR 48-96				
														HY	REC	HY		REC	
1	9811065	3113			150	167	21				36	14+4-27+1	24						
2		3114			150	167	22				40	15+4-28+1							
3		3115			150	167	23	100	W		44	16+4-29+1							
4		3116			150	167	24				48	17+4-30+1							
5		3117			150	167	25				24	18+4-31+1	31						
6		3118			150	167	26				28	19+4-32+1							
7		3119			150	167	27				32	20+4-33+1							
8		320			150	167	28				36	21+4-34+1							
9		321			150	167	29				40	22+4-35+1							
10		322			150	167	30				44	23+4-36+1							
11		323			150	167	31				48	24+4-37+1							
12		324			150	167	32				28	25+4-38+1	37						
13		325			150	167	33				32	26+4-39+1							
14		326			150	167	34				36	27+4-40+1							
15		327			150	167	35				40	28+4-41+1							
16		328			150	167	36				44	29+4-42+1							
17		329			150	167	37				48	30+4-43+1							
18		330			150	167	38				52	31+4-44+1							
19		331			150	167	39				56	32+4-45+1							
40		332			150	167	40				60	33+4-46+1							

46+1 - dead

