

LAND SEISMIC RECORDING LOG 14 Rec Hours

PAGE 1 of 8



CLIENT: Husky	PROSPECT: NPR-A	AREA: TUNALIK	LINE NO: 702
PARTY NO: 1182	INST. ENG: TORGERSON		DATE: 2 DAY 2 YR 80

INSTRUMENT: (9-TRACK)	<input checked="" type="checkbox"/> 1 SYSTEM <input type="checkbox"/> 2 SYSTEMS	CHS: 24 & 25-48 <input type="checkbox"/> 1-48 & 49-96	ODDS <input checked="" type="checkbox"/> EVENS	TYPE: <input type="checkbox"/> DFS III <input type="checkbox"/> DFS II <input type="checkbox"/> OTHER	9 TRACK <input type="checkbox"/> 21 TRACK	FORMAT: B SEG	GAPPED <input type="checkbox"/> UNGAPPED	PACKING DENSITY: (LO) <input type="checkbox"/> 356 BPI (HI) <input type="checkbox"/> 712 BPI <input type="checkbox"/> 800 BPI <input type="checkbox"/> 1600 BPI	
NO. BYTES IN HEADER REC:	NO. BYTES IN RECORD ID:	NO. BYTES PER SCAN:	RECORD NUMBERS:	<input checked="" type="checkbox"/> DEC. <input type="checkbox"/> OCT.	GAIN CONSTANT:	INPUT IMPEDANCE:	ohms		
CONFIGURATION (MAG TAPE)	FIELD TRACE NOS.:	(ON MAG TAPE)			AUXILIARY DATA:	(1) TW (2) FN (3) RTB (4) RSPS (5) TB (6) SPS (7) GW			
PARAMETER	RECORD LENGTH: 6 sec.	SAMPLE RATE: <input type="checkbox"/> 1 ms. <input type="checkbox"/> 4 ms. <input checked="" type="checkbox"/> 8 ms.	GAIN MODE: <input type="checkbox"/> INITIAL <input type="checkbox"/> MANUAL <input type="checkbox"/> OPERATE	FILTERS:	LO CUT HZ SLOPE: 15	FREQ: 125	HI CUT HZ SLOPE: 72	NOTCH FILTER: <input type="checkbox"/> IN <input checked="" type="checkbox"/> OUT	
DISPLAY	MODE: <input checked="" type="checkbox"/> AGC <input type="checkbox"/> FLOAT <input type="checkbox"/> AMPLIFIER <input type="checkbox"/> DIRECT	INITIAL GAIN: VARIABLE db	TRIP SENS: db	POLARITY CONVENTION: <input type="checkbox"/> NEGATIVE <input type="checkbox"/> POSITIVE	PRESSURE INCREASE ON GEOPHONE: <input type="checkbox"/> NUMBERS ON MAG. TAPE	DOWNBREAK <input type="checkbox"/> UPBREAK <input type="checkbox"/> ON DISPLAY			
CFS I	TYPE STACK:	GATE LENGTH:	RECORD REJECTION:	NOISE REDUCTION:	NOISE THRESHOLD:	CORR. SCALING:	R.C.U. NORM/ALT SW.		
SOURCE	TYPE: <input checked="" type="checkbox"/> DYNAMITE <input type="checkbox"/> VIBROSEIS <input type="checkbox"/> OTHER	PATTERN:	NO. OF POSITIONS:	INLINE SPACING:	LATERAL SPACING:	STAGGER:	LENGTH:	WIDTH:	LATERAL OFFSET:
RECEIVER	TYPE: GSC-200	PATTERN: Inline	NO. OF ELEMENTS: 18	INLINE SPACING: 19.4	LATERAL SPACING:	STAGGER:	LENGTH: 330	WIDTH:	LATERAL OFFSET:
SPREAD	CONNECTION: SER-PAR	RESISTANCE: ohms	STAGGER:	LENGTH:	WIDTH:	LATERAL OFFSET:	DIRECTION OF PROGRESSION: NORTH		
	NO. OF GROUPS: 48	GROUP INTERVAL: 330	SHOTPOINT INTERVAL: 1320	FOLD: 6	LEADING GROUP: 48				
	OFFSET GROUP 1: 8085	OFFSET GROUP 2: 495	OFFSET GROUP 3: 445	OFFSET GROUP 4: 8085					

DIAGRAMS/MISC. INFORMATION: **T25 X** **T2 X** **T12 X** **T11 X** **sp1**

Daily Limits FN 645-662 FN 644 DUNNELL ROAD

FN 663 TT8

SHOTPOINT	TR. 1 to		TR. 2 to		SHOT		DIR.	COP SWITCH	SPREAD	REMARKS	CORR. STACK			
	REEL NO.	REC.	REEL NO.	REC.	SIZE	DEPTH					NO.	OFFSET	TR 1-28	TR 29-36
1	98101	16	17	22	50	60	11	16	T25 - 7+1	9				
2		16			50	60	12	20	T21 - 8+1					
3		16			50	60	13	24	T17 - 9+1					
4		16			50	60	14	28	T13 - 10+1					
5		16			50	60	15	32	T9 - 11+1					
6		16			50	60	16	36	T5 - 12+1					
7		16			50	60	17	40	T1 - 13+1					
8		16			50	60	18	44	1+4 - 14+1					
9		16			50	60	19	48	2+4 - 15+1					
10		16			50	60	20	52	3+4 - 16+1					
11		16			50	60	21	56	4+4 - 17+1					
12		16			50	60	22	60	5+4 - 18+1					
13		16			50	60	23	64	6+4 - 19+1					
14		16			50	60	24	24	7+4 - 20+1	20				
15		16			50	60	25	28	8+4 - 21+1					
16		16			50	60	26	32	9+4 - 22+1					
17		16			50	60	27	36	10+4 - 23+1					
18		16			50	60	28	40	11+4 - 24+1					
19		16			50	60	29	44	12+4 - 25+1					
20		16			50	60	30	48	13+4 - 26+1					

RECORD # 682 NG
PAR-TT

LAND SEISMIC RECORDING LOG

2012

	CLIENT: Husky	PROSPECT: NPR-4	AREA: TUNALIUK	LINE NO: 702	
PARTY NO: 1182		INST. ENG: TERG BRSON		DATE: 2 DAY 2 YR 80	

INSTRUMENT (9-TRACK)	<input type="checkbox"/> 1 SYSTEM <input type="checkbox"/> 2 SYSTEMS	<input type="checkbox"/> 1-24 & 25-48 <input type="checkbox"/> 1-48 & 49-96	ODDS & EVENS	TYPE: <input type="checkbox"/> DFS III <input type="checkbox"/> DFS IX	<input type="checkbox"/> DFS X <input type="checkbox"/> OTHER	<input type="checkbox"/> 9 TRACK <input type="checkbox"/> 21 TRACK	FORMAT: SEC	<input type="checkbox"/> GAPPED <input type="checkbox"/> UNGAPPED	PACKING DENSITY:	<input type="checkbox"/> (LO) 356 BPI <input type="checkbox"/> 800 BPI	<input type="checkbox"/> (HI) 712 BPI <input type="checkbox"/> 1600 BPI
NO. BYTES IN HEADER REC:		NO. BYTES IN RECORD ID:		NO. BYTES PER SCAN:		RECORD NUMBERS:		<input type="checkbox"/> DEC. <input type="checkbox"/> OCT.		GAIN CONSTANT: _____ db	
FIELD TRACE NOS.:						AUXILIARY DATA:					
DATA CHANNEL NOS.:						AUXILIARY CHANNEL NOS.:					
PARAMETER		RECORD LENGTH: _____ sec.		SAMPLE RATE: <input type="checkbox"/> 1 ms. <input type="checkbox"/> 4 ms. <input type="checkbox"/> 2 ms. <input type="checkbox"/> _____ ms.		GAIN MODE: <input type="checkbox"/> INITIAL <input type="checkbox"/> MANUAL <input type="checkbox"/> IFP <input type="checkbox"/> FINAL <input type="checkbox"/> OPERATE		FILTERS: _____		LO CUT HZ SLOPE: _____	
DISPLAY		MODE: <input type="checkbox"/> AGC <input type="checkbox"/> FLOAT <input type="checkbox"/> AMPLIFIER <input type="checkbox"/> DEFLOAT <input type="checkbox"/> DIRECT		INITIAL GAIN: _____ db		TRIP SENS: _____ db		POLARITY CONVENTION: _____		PRESSURE INCREASE ON GEOPHONE: _____	
CFS I		TYPE STACK:		GATE LENGTH:		RECORD REJECTION: _____		NOISE REDUCTION:		NOISE THRESHOLD: _____	
SOURCE		TYPE: <input type="checkbox"/> DYNAMITE <input type="checkbox"/> VIBROSEIS <input type="checkbox"/> OTHER		PATTERN:		NO. OF POSITIONS:		INLINE SPACING:		LATERAL SPACING:	
RECEIVER		CONNECTION:		RESISTANCE: _____ ohms		STAGGER:		INLINE SPACING:		LATERAL SPACING:	
SPREAD		NO. OF GROUPS:		GROUP INTERVAL:		SHOTPOINT INTERVAL:		FOLD:		DIRECTION OF PROGRESSION: NORTH	
		OFFSET GROUP 1:		OFFSET GROUP _____		OFFSET GROUP _____		OFFSET GROUP 48/96:		LEADING GROUP:	

DIAGRAMS/MISC. INFORMATION:

SHOTPOINT	TR _____ to _____		TR _____ to _____		SHOT				SPREAD				REMARKS	CORR. STACK			
	REEL NO.	REC.	REEL NO.	REC.	SIZE	DEPTH	NO.	OFFSET	DIR.	CDP SWITCH	LINE GROUPS			SEP	TR 1-24	TR 25-48	TR 49-96
21	1040	687			50	60	21			52	14+4	- 27+1	20				
22		686			50	60	22			56	15+4	- 28+1					
23		687			50	60	23			60	16+4	- 29+1					
24		688			50	60	24			68	17+4	- 30+1	34				
25		689			50	60	25			12	18+4	- 31+1					
26		690			50	60	26			16	19+4	- 32+1					
27		691			50	60	27			20	20+4	- 33+1					
28		692			50	60	28	300 W		24	21+4	- 34+1					
29		693			50	60	29	200 W		28	22+4	- 35+1					
30		694			50	60	30			32	23+4	- 36+1					
31		695			50	60	31			36	24+4	- 37+1					
32		696			50	60	32			40	25+4	- 38+1					
33		697			50	60	33	100 E		44	26+4	- 39+1					
34		698			50	60	34			48	27+4	- 40+1					
35		699			50	60	35			52	28+4	- 41+1					
36		700			50	60	36			56	29+4	- 42+1					
37		701			50	60	37			60	30+4	- 43+1					
38		702			50	60	38			64	31+4	- 44+1					
39		703			50	60	39			68	32+4	- 45+1					
40		704			50	60	40			72	33+4	- 46+1					

Part 1 Error

LAND SEISMIC RECORDING LOG

	CLIENT: Husky	PROSPECT: NPR-A	AREA: TUNALIK	LINE NO: 702					
	PARTY NO: 1182	INST. ENG: TORGERSON		DATE: 2 DAY 3 YR 80					
INSTRUMENT (9-TRACK)	<input checked="" type="checkbox"/> 1 SYSTEM <input checked="" type="checkbox"/> 2 SYSTEMS	<input checked="" type="checkbox"/> 1-24 & 25-48 <input checked="" type="checkbox"/> 1-48 & 49-96	ODDS EVENTS: <input checked="" type="checkbox"/>	TYPE: <input type="checkbox"/> DFS III <input type="checkbox"/> DFS II <input type="checkbox"/> OTHER	<input checked="" type="checkbox"/> 9 TRACK <input type="checkbox"/> 21 TRACK	FORMAT: B	<input checked="" type="checkbox"/> GAPPED <input type="checkbox"/> UNGAPPED	PACKING DENSITY: (LO) <input type="checkbox"/> 356 BPI <input type="checkbox"/> 800 BPI	(HI) <input type="checkbox"/> 712 BPI <input checked="" type="checkbox"/> 1000 BPI
	NO. BYTES IN HEADER REC: 132	NO. BYTES IN RECORD ID: 24	NO. BYTES PER SCAN: 134	RECORD NUMBERS: <input checked="" type="checkbox"/> DEC. <input type="checkbox"/> OCT.	GAIN CONSTANT: 36 db	INPUT IMPEDANCE: 2000 ohms.			
CONFIGURATION (MAG TAPE)	FIELD TRACE NOS.: 1-48				AUXILIARY DATA: TW 875 (3) (4) (5) (6) (7)				
	DATA CHANNEL NOS.: 5-52 (ON MAG TAPE)				AUXILIARY CHANNEL NOS.: 0 1				
PARAMETER	RECORD LENGTH: VARIABLE (L) sec.	SAMPLE RATE: <input type="checkbox"/> 1 ms. <input type="checkbox"/> 4 ms. <input checked="" type="checkbox"/> 2 ms. <input type="checkbox"/> ms.	GAIN MODE: <input type="checkbox"/> INITIAL <input type="checkbox"/> MANUAL <input type="checkbox"/> FINAL <input type="checkbox"/> OPERATE	FILTERS: FREQ. 8 LO CUT HZ SLOPE 15 HI CUT HZ SLOPE 20 NOTCH FILTER: <input checked="" type="checkbox"/> IN <input type="checkbox"/> OUT					
DISPLAY	MODE: <input type="checkbox"/> FLOAT <input type="checkbox"/> AMPLIFIER <input checked="" type="checkbox"/> AGC <input type="checkbox"/> DEFLOAT <input type="checkbox"/> DIRECT	INITIAL GAIN: VARIABLE db	TRIP SENS: VARIABLE db	POLARITY CONVENTION: POS		PRESSURE INCREASE ON GEOPHONE: <input checked="" type="checkbox"/> NEGATIVE <input type="checkbox"/> POSITIVE		NUMBERS ON MAG. TAPE <input checked="" type="checkbox"/> DOWNBREAK <input type="checkbox"/> UPBREAK	
CFS I	TYPE STACK:	GATE LENGTH:	RECORD REJECTION:	NOISE REDUCTION:		NOISE THRESHOLD:		CORR. SCALING: R.C.U. NORM./ALT SW.	
SOURCE	TYPE: <input checked="" type="checkbox"/> DYNAMITE <input type="checkbox"/> VIBROSEIS <input type="checkbox"/> OTHER	PATTERN: Inline	NO. OF POSITIONS:	INLINE SPACING:	LATERAL SPACING:	STAGGER:	LENGTH:	WIDTH:	LATERAL OFFSET:
	CHG/HOLE: 52 HOLE DEPTH: 75		SWEEP POSITION:	SWEEP START:	SWEEP END:	SWEEP LENGTH:	SWEEP TAPER:	PHASE COMP.	
RECEIVER	TYPE: GSC-200	PATTERN: Inline	NO. OF ELEMENTS: 18	INLINE SPACING: 19.4	LATERAL SPACING:	STAGGER:	LENGTH: 330	WIDTH:	LATERAL OFFSET:
	CONNECTION: SER-PHR	RESISTANCE: ohms	STAGGER:	LENGTH: 330	WIDTH:	LATERAL OFFSET:			
SPREAD	NO. OF GROUPS: 48	GROUP INTERVAL: 330	SHOTPOINT INTERVAL: 1320	FOLD: 6	DIRECTION OF PROGRESSION: NORTH				
	OFFSET GROUP 1: 8045	OFFSET GROUP 2: 495	OFFSET GROUP 25: 495	OFFSET GROUP 48/04: 8085	LEADING GROUP: 48				

DIAGRAMS/MISC. INFORMATION: **3414** **403** **412** **471**
X **X** **X**
401 **471**
401
DAILY TESTS FN 705-773
FILE # 724 TTB

SHOTPOINT	TR. 10		TR. 10		SHOT					SPREAD			REMARKS	CORR STACK				
	REEL NO.	REC.	REEL NO.	REC.	SIZE	DEPTH	NO.	OFFSET	DIR.	COP SWITCH	LINE GROUPS			SEP	TR 1-48	TR 48-96	TR 1-48	TR 48-96
41	781016	725			50	60	1			28	34+4	-	47+1	46				
42		726			50	60	2			32	35+4	-	48+1					
43		727			50	60	3			36	36+4	-	49+1					
44		728			50	60	4			40	37+4	-	50+1					
45		729			50	60	5			44	38+4	-	51+1					
46		730			50	60	6			48	39+4	-	52+1					
47		731			50	60	7			52	40+4	-	53+1					
48		732			50	60	8			56	41+4	-	54+1					
49		733			50	60	9			24	42+4	-	55+1	85				
50		734			50	60	10			28	43+4	-	56+1					
51		735			50	60	11			32	44+4	-	57+1					
52		736			50	60	12			36	45+4	-	58+1					
53		737			50	60	13			40	46+4	-	59+1					
54		738			50	60	14			44	47+4	-	T5					
55		739			50	60	15			48	48+4	-	T9					
56		740			50	60	16			52	49+4	-	T13					
57		741			50	60	17			56	50+4	-	T17					
58		742			50	60	18			60	51+4	-	T21					
59	781016	743			85	10	19	330	S	64	52+4	-	T25					

801