

LAND SEISMIC RECORDING LOG



| | | | |
|--------------------------|--------------------------------|--|------------------------|
| CLIENT: Husky | PROSPECT: NPR-A | AREA: TUNALIK | LINE NO: 703 |
| PARTY NO: 1182 | INST. ENG: TORBERSON | DATE: MO 2 DAY 6 YR 80 | |

| SHOTPOINT | TR. 10 | | TR. 10 | | SHOT | | | | SPREAD | | REMARKS | CORR. STACK | | | | | |
|-----------|----------|------|----------|------|------|-------|-----|--------|--------|------------|-------------|-------------|--|---------|-----|----------|-----|
| | REEL NO. | REC. | REEL NO. | REC. | SIZE | DEPTH | NO. | OFFSET | DIR. | COP SWITCH | | LINE GROUPS | | TR 1-28 | | TR 48-96 | |
| | | | | | | | | | | | | | | HT | REC | HT | REC |
| 21 | 1182 | 877 | | | 50 | 60 | 21 | | | 52 | 14+4 - 27+1 | 20 | | | | | |
| 22 | | 877 | | | 50 | 60 | 22 | | | 56 | 15+4 - 28+1 | | | | | | |
| 23 | | 876 | | | 50 | 60 | 23 | | | 60 | 16+4 - 29+1 | | | | | | |
| 24 | | 877 | | | 50 | 60 | 24 | | | 64 | 17+4 - 30+1 | | | | | | |
| 25 | | 878 | | | 50 | 60 | 25 | | | 68 | 18+4 - 31+1 | | | | | | |
| 26 | | 879 | | | 50 | 60 | 26 | | | 20 | 19+4 - 32+1 | 33 | | | | | |
| 27 | | 880 | | | 50 | 60 | 27 | | | 24 | 20+4 - 33+1 | | | | | | |
| 28 | | 881 | | | 50 | 60 | 28 | | | 28 | 21+4 - 34+1 | | | | | | |
| 29 | | 882 | | | 50 | 60 | 29 | | | 32 | 22+4 - 35+1 | | | | | | |
| 30 | | 883 | | | 50 | 60 | 30 | | | 36 | 23+4 - 36+1 | | | | | | |
| 31 | | 884 | | | 50 | 60 | 31 | | | 40 | 24+4 - 37+1 | | | | | | |
| 32 | | 885 | | | 50 | 60 | 32 | | | 44 | 25+4 - 38+1 | | | | | | |
| 33 | | 886 | | | 50 | 60 | 33 | | | 48 | 26+4 - 39+1 | | | | | | |
| 34 | | 887 | | | 50 | 60 | 34 | | | 52 | 27+4 - 40+1 | | | | | | |
| 35 | | 888 | | | 50 | 60 | 35 | | | 56 | 28+4 - 41+1 | | | | | | |
| 36 | | 889 | | | 50 | 60 | 36 | | | 60 | 29+4 - 42+1 | | | | | | |
| 37 | | 890 | | | 50 | 60 | 37 | | | 24 | 30+4 - 43+1 | 43 | | | | | |
| 38 | | 891 | | | 50 | 60 | 38 | | | 28 | 31+4 - 44+1 | | | | | | |
| 39 | | | | | 50 | 60 | 39 | | | | 32+4 - 45+1 | | | | | | |
| 40 | | | | | 50 | 60 | 40 | | | | 35+4 - 46+1 | | | | | | |

LAND SEISMIC RECORDING LOG

| | | | | | | | | | |
|--------------------------|---|--|---|---|---|--|---|---|-----------------|
| | CLIENT: Husky | PROSPECT: NPR-4 | AREA: TONALUIS | LINE NO: 703 | | | | | |
| | PARTY NO: 1182 | INST. ENG: TORGERSON | | DATE: 2 DAY 7 YE 82 | | | | | |
| INSTRUMENT (9-TRACK) | <input checked="" type="checkbox"/> 1 SYSTEM <input type="checkbox"/> 2 SYSTEMS | <input checked="" type="checkbox"/> 1-24 & 25-48 <input type="checkbox"/> 1-48 & 49-96 | ODDS EVENS <input checked="" type="checkbox"/> ODDS <input type="checkbox"/> EVENS | TYPE: <input type="checkbox"/> DFS III <input type="checkbox"/> DFS IV <input type="checkbox"/> OTHER | <input checked="" type="checkbox"/> 9 TRACK <input type="checkbox"/> 21 TRACK | FORMAT: <input type="checkbox"/> SEC <input type="checkbox"/> D | <input type="checkbox"/> GAPPED <input type="checkbox"/> UNGAPPED | PACKING DENSITY: (L) <input type="checkbox"/> 356 BPI <input type="checkbox"/> 800 BPI (H) <input type="checkbox"/> 712 BPI <input type="checkbox"/> 1600 BPI | |
| | NO. BYTES IN HEADER REC: 132 | NO. BYTES IN RECORD ID: 24 | NO. BYTES PER SCAN: 134 | RECORD NUMBERS: <input checked="" type="checkbox"/> DEC. <input type="checkbox"/> OCT | GAIN CONSTANT: 34 db | INPUT IMPEDANCE: 2000 ohms | | | |
| CONFIGURATION (MAG TAPE) | FIELD TRACE NOS.: 1-48 | DATA CHANNEL NOS.: 5-52 | (ON MAG TAPE) | AUXILIARY DATA: TW (1) 5ps (3) TVB (4) 0 (5) 0 (6) 0 | AUXILIARY CHANNEL NOS.: 0 1 2 3 4 | | | | |
| PARAMETER | RECORD LENGTH: VARIABLE (4) | SAMPLE RATE: <input checked="" type="checkbox"/> 1 ms. <input type="checkbox"/> 4 ms. <input type="checkbox"/> 2 ms. | GAIN MODE: <input checked="" type="checkbox"/> INITIAL <input type="checkbox"/> MANUAL <input type="checkbox"/> OPERATE | FILTERS: FREQ. 4 | LO CUT HZ SLOPE: 18 | H CUT HZ SLOPE: 20 | NOTCH FILTER: <input checked="" type="checkbox"/> IN <input type="checkbox"/> OUT | | |
| DISPLAY | MODE: <input checked="" type="checkbox"/> MAG <input type="checkbox"/> FLOAT <input type="checkbox"/> AMPLIFIER <input type="checkbox"/> DIRECT | INITIAL GAIN: VARIABLE db | TRIP SENS: VARIABLE db | POLARITY CONVENTION: POS | PRESSURE INCREASE ON GEOPHONE: <input type="checkbox"/> NEGATIVE <input checked="" type="checkbox"/> POSITIVE | NUMBERS ON MAG. TAPE: <input type="checkbox"/> DOWNBREAK <input checked="" type="checkbox"/> UPBREAK | ON DISPLAY | | |
| CFS I | TYPE STACK: | GATE LENGTH: | RECORD REJECTION: | NOISE REDUCTION: | NOISE THRESHOLD: | CORR. SCALING: | R.C.U. NORM./ALT SW. | | |
| SOURCE | TYPE: <input checked="" type="checkbox"/> DYNAMITE <input type="checkbox"/> VIBROSEIS <input type="checkbox"/> OTHER | PATTERN: In-line | NO. OF POSITIONS: | INLINE SPACING: | LATERAL SPACING: | STAGGER: | LENGTH: | WIDTH: | LATERAL OFFSET: |
| RECEIVER | TYPE: CSC-200 | PATTERN: In-line | NO. OF ELEMENTS: 14 | INLINE SPACING: 19.4 | LATERAL SPACING: | STAGGER: | LENGTH: 332 | WIDTH: | LATERAL OFFSET: |
| SPREAD | NO. OF GROUPS: 48 | GROUP INTERVAL: 330 | SHOTPOINT INTERVAL: 1320 | FOLD: 6 | DIRECTION OF PROGRESSION: EAST | OFFSET GROUP 1: 8085 | OFFSET GROUP 48: 8085 | LEADING GROUP: 48 | |

DIAGRAMS/MISC. INFORMATION: 32+4 X, 34+3 X, 34+2 X, 45+1 X, File # 892 - 907 Direct Traces, File # 908 TTB

| SHOTPOINT | TR. _____ to _____ | | TR. _____ to _____ | | SHOT | | SPREAD | | REMARKS | CORR. STACK | | | |
|-----------|--------------------|------|--------------------|------|------|-------|--------|--------|---------|-------------|-------------|-------------|---------|
| | REEL NO. | REC. | REEL NO. | REC. | SIZE | DEPTH | NO. | OFFSET | | DIR. | CDP SWITCH | LINE GROUPS | TR 1-48 |
| 31 | 481 | 918 | 901 | | 50 | 60 | 1 | | | 16 | 32+4 - 45+1 | 47 | |
| 32 | | | 912 | | 50 | 60 | 2 | | | 20 | 33+4 - 46+1 | | |
| 41 | | | 911 | | 50 | 60 | 3 | | | 24 | 34+4 - 47+1 | | |
| 42 | | | 913 | | 50 | 60 | 4 | | | 28 | 35+4 - 48+1 | | |
| 43 | | | 913 | | 50 | 60 | 5 | | | 32 | 36+4 - 49+1 | | |
| 44 | | | 914 | | 50 | 60 | 6 | | | 36 | 37+4 - 50+1 | | |
| 45 | | | 915 | | 50 | 60 | 7 | | | 40 | 38+4 - 51+1 | | |
| 46 | | | 916 | | 50 | 60 | 8 | | | 44 | 39+4 - 52+1 | | |
| 47 | | | 917 | | 50 | 60 | 9 | | | 48 | 40+4 - 53+1 | | |
| 48 | | | 918 | | 50 | 60 | 10 | | | 52 | 41+4 - 54+1 | | |
| 49 | | | 919 | | 50 | 60 | 11 | | | 56 | 42+4 - 55+1 | | |
| 50 | | | 920 | | 50 | 60 | 12 | | | 60 | 43+4 - 56+1 | | |
| 51 | | | 921 | | 50 | 60 | 13 | | | 64 | 44+4 - 57+1 | | |
| 52 | | | 922 | | 50 | 60 | 14 | | | 68 | 45+4 - 58+1 | | |
| 53 | | | 923 | | 50 | 60 | 15 | | | 48 | 46+4 - 59+1 | 64 | |
| 54 | | | 924 | | 50 | 60 | 16 | | | 8 | 47+4 - 60+1 | | |
| 55 | | | 925 | | 50 | 60 | 17 | | | 12 | 48+4 - 61+1 | | |
| 56 | | | 926 | | 50 | 60 | 18 | | | 16 | 49+4 - 62+1 | | |
| 57 | | | 927 | | 50 | 60 | 19 | | | 20 | 50+4 - 63+1 | | |
| 58 | | | 928 | | 50 | 60 | 20 | | | 24 | 51+4 - 64+1 | | |

LAND SEISMIC RECORDING LOG



| | | | | | | | |
|------------|-------|-------------|-----------|-------|---------|-----------|-------------------|
| CLIENT: | Husky | PROSPECT: | NPR-A | AREA: | TUNALIK | LINE NO.: | 703 |
| PARTY NO.: | 1182 | INST. ENG.: | TORGERSON | | | DATE: | MO. 2 DAY 2 YR 80 |

| SHOTPOINT | TR. 10 | | TR. 10 | | SHOT | | | | | SPREAD | | | REMARKS | CORR. STACK | | | | |
|-----------|----------|------|----------|------|------|-------|-----|--------|------|------------|-------------|-------------|---------|-------------|---------|------|----------|--|
| | REEL NO. | REC. | REEL NO. | REC. | SIZE | DEPTH | NO. | OFFSET | DIR. | CDP SWITCH | LINE GROUPS | | | SET UP | TR 1-48 | | TR 49-96 | |
| | | | | | | | | | | | HT. | REC. | | | HT. | REC. | | |
| 59 | 9811016 | 929 | | | | 50 | 60 | 21 | | | 28 | 52+4 - 65+1 | 64 | | | | | |
| 60 | | 930 | | | | 50 | 60 | 22 | | | 32 | 53+4 - 66+1 | | | | | | |
| 61 | | 931 | | | | 50 | 60 | 23 | | | 36 | 54+4 - 67+1 | | | | | | |
| 62 | | 932 | | | | 50 | 60 | 24 | | | 40 | 55+4 - 68+1 | | | | | | |
| 63 | | 933 | | | | 50 | 60 | 25 | | | 44 | 56+4 - 69+1 | | | | | | |
| 64 | | 934 | | | | 50 | 60 | 26 | | | 48 | 57+4 - 70+1 | | | | | | |
| 65 | | 935 | | | | 50 | 60 | 27 | | | 52 | 58+4 - 71+1 | | | | | | |
| 66 | | 936 | | | | 50 | 60 | 28 | | | 56 | 59+4 - 72+1 | | | | | | |
| 67 | | 937 | | | | 50 | 60 | 29 | | | 60 | 60+4 - 73+1 | 28 | | | | | |
| 68 | | 938 | | | | 50 | 60 | 30 | | | 8 | 61+4 - 74+1 | 28 | | | | | |
| 69 | | 939 | | | | 50 | 60 | 31 | | | 12 | 62+4 - 75+1 | | | | | | |
| 70 | | 940 | | | | 50 | 60 | 32 | | | 16 | 63+4 - 76+1 | | | | | | |
| 71 | | 941 | | | | 50 | 60 | 33 | | | 20 | 64+4 - 77+1 | | | | | | |
| 72 | | 942 | | | | 50 | 60 | 34 | | | 24 | 65+4 - 78+1 | | | | | | |
| 73 | | 943 | | | | 50 | 60 | 35 | | | 28 | 66+4 - 79+1 | | | | | | |
| 74 | | 944 | | | | 50 | 60 | 36 | | | 32 | 67+4 - 80+1 | | | | | | |
| 75 | | 945 | | | | 50 | 60 | 37 | | | 36 | 68+4 - 81+1 | | | | | | |
| 76 | | 946 | | | | 50 | 60 | 38 | | | 40 | 69+4 - 82+1 | | | | | | |
| 77 | | 947 | | | | 50 | 60 | 39 | | | 44 | 70+4 - 83+1 | | | | | | |
| 78 | | 948 | | | | 50 | 60 | 40 | | | 48 | 71+4 - 84+1 | | | | | | |
| 79 | | 949 | | | | 50 | 60 | 41 | | | 52 | 72+4 - 85+1 | | | | | | |
| 80 | | | | | | 50 | 60 | 42 | | | | 73+4 - 86+1 | | | | | | |
| | | | | | | | | 46 | | | | -90 | | | | | | |

LAND SEISMIC RECORDING LOG

| | | | | | | | | |
|-------------------------------------|--|---|---|--|--|--|--|---|
| | | CLIENT: Husky | PROSPECT: NPR-A | AREA: TUNALIK | LINE NO: 703 | | | |
| PARTY NO: 1187 | | INST. ENG: TARGERSON | | | DATE: 2 DAY 8 YR 80 | | | |
| INSTRUMENT (9-TRACK) | | <input checked="" type="checkbox"/> 1 SYSTEM <input checked="" type="checkbox"/> 2 SYSTEMS <input type="checkbox"/> 1-24 & 25-48 <input type="checkbox"/> 1-48 & 49-96 | | TYPE: <input type="checkbox"/> DFS III <input type="checkbox"/> DFS IV <input checked="" type="checkbox"/> OTHER | <input checked="" type="checkbox"/> 9 TRACK <input checked="" type="checkbox"/> 2 TRACK | FORMAT: B SEG | <input type="checkbox"/> GAPPED <input type="checkbox"/> UNGAPPED | PACKING DENSITY: (L) <input type="checkbox"/> 356 BPI <input type="checkbox"/> 800 BPI (H) <input type="checkbox"/> 712 BPI <input type="checkbox"/> 1600 BPI |
| NO. BYTES IN HEADER REC: 132 | | NO. BYTES IN RECORD ID: 24 | | NO. BYTES PER SCAN: 134 | | RECORD NUMBERS: <input checked="" type="checkbox"/> DEC. <input type="checkbox"/> OCT. | GAIN CONSTANT: 36 db | INPUT IMPEDANCE: 2000 ohms. |
| CONFIGURATION (MAG TAPE) | | FIELD TRACE NOS.: 1-48 | | | AUXILIARY DATA: (1) TW (2) SPS (3) TD (4) 6 (5) 8 (6) 10 (7) 11 | | | |
| DATA CHANNEL NOS.: 5-52 | | (ON MAG TAPE) | | | AUXILIARY CHANNEL NOS.: 0 1 2 3 4 | | | |
| PARAMETER | RECORD LENGTH: VARIABLE (6) sec. | SAMPLE RATE: <input type="checkbox"/> 1 ms. <input type="checkbox"/> 4 ms. <input checked="" type="checkbox"/> 2 ms. | GAIN MODE: <input type="checkbox"/> INITIAL <input type="checkbox"/> FINAL <input type="checkbox"/> MANUAL <input type="checkbox"/> OPERATE | FILTERS: FREQ. 8 LO CUT HZ SLOPE 18 HI CUT HZ SLOPE 70 NOTCH FILTER: <input type="checkbox"/> IN <input type="checkbox"/> OUT | | | | |
| DISPLAY | MODE: <input checked="" type="checkbox"/> AGC <input type="checkbox"/> FLOAT <input type="checkbox"/> AMPLIFIER <input type="checkbox"/> DEFLOAT <input type="checkbox"/> DIRECT | INITIAL GAIN: VARIABLE db | TRIP SENS: VARIABLE db | POLARITY CONVENTION: POS | PRESSURE INCREASE ON GEOPHONE: <input type="checkbox"/> NEGATIVE <input type="checkbox"/> POSITIVE } NUMBERS ON ON MAG. TAPE <input checked="" type="checkbox"/> DOWNBREAK <input type="checkbox"/> UPBREAK } ON DISPLAY | | | |
| CFS I | TYPE STACK: | GATE LENGTH: | RECORD REJECTION: | NOISE REDUCTION: | NOISE THRESHOLD: | CORR. SCALING: | R.C.U. NORM./ALT SW. <input checked="" type="checkbox"/> | |
| SOURCE | TYPE: <input checked="" type="checkbox"/> DYNAMITE <input type="checkbox"/> VIBROSEIS <input type="checkbox"/> OTHER | PATTERN: INLINE | NO. OF POSITIONS: | INLINE SPACING: | LATERAL SPACING: | STAGGER: | LENGTH: WIDTH: LATERAL OFFSET: | |
| RECEIVER | TYPE: GSC-200 10HZ | PATTERN: INLINE | NO. OF ELEMENTS: 19 | INLINE SPACING: 19.4 | LATERAL SPACING: | STAGGER: | LENGTH: 330 WIDTH: LATERAL OFFSET: | |
| SPREAD | CONNECTION: SBR-ARR | RESISTANCE: ohms | STAGGER: | LENGTH: 330 | WIDTH: LATERAL OFFSET: | | | |
| | NO. OF GROUPS: 48 | GROUP INTERVAL: 330 | SHOTPOINT INTERVAL: 1320 | FOLD: 6 | DIRECTION OF PROGRESSION: EAST | | | |
| | OFFSET GROUP 1: 8085 | OFFSET GROUP 2: 495 | OFFSET GROUP 3: 495 | OFFSET GROUP 4: 8085 | LEADING GROUP: 48 | | | |

DIAGRAMS/MISC. INFORMATION: **13+4 X** **794 X** **5012 X** **96+1 X** **580**

DAILY TESTS FN 950 - 965
TTB FN 966

| SHOTPOINT | TR. _____ TO _____ | | TR. _____ TO _____ | | SHOT | | | SPREAD | | | REMARKS | CORR. STACK | | | |
|-----------|--------------------|------|--------------------|------|------|-------|-----|--------|------|------------|--------------|-------------|-----|---------|----------|
| | REEL NO. | REC. | REEL NO. | REC. | SIZE | DEPTH | NO. | OFFSET | DIR. | CDP SWITCH | | LINE GROUPS | SET | YR 1-48 | YR 49-96 |
| 80 | 9710 | 967 | | | 50 | 143 | 1 | | | 16 | 73+4 - 86+1 | 38 | | | |
| 81 | | 968 | | | 50 | 140 | 2 | | | 20 | 74+4 - 87+1 | | | | |
| 82 | | 969 | | | 50 | 142 | 3 | | | 24 | 75+4 - 88+1 | | | | |
| 83 | | 970 | | | 50 | 142 | 4 | | | 28 | 76+4 - 89+1 | | | | |
| 84 | | 971 | | | 50 | 142 | 5 | | | 32 | 77+4 - 90+1 | | | | |
| 85 | | 972 | | | 50 | 142 | 6 | | | 36 | 78+4 - 91+1 | | | | |
| 86 | | 973 | | | 50 | 140 | 7 | | | 40 | 79+4 - 92+1 | | | | |
| 87 | | 974 | | | 50 | 140 | 8 | | | 44 | 80+4 - 93+1 | | | | |
| 88 | | 975 | | | 50 | 140 | 9 | | | 48 | 81+4 - 94+1 | | | | |
| 89 | | 976 | | | 50 | 140 | 10 | | | 12 | 82+4 - 95+1 | 98 | | | |
| 90 | | 977 | | | 50 | 140 | 11 | | | 16 | 83+4 - 96+1 | | | | |
| 91 | | 978 | | | 50 | 140 | 12 | | | 20 | 84+4 - 97+1 | | | | |
| 92 | | 979 | | | 50 | 140 | 13 | | | 24 | 85+4 - 98+1 | | | | |
| 93 | | 980 | | | 50 | 140 | 14 | | | 28 | 86+4 - 99+1 | | | | |
| 94 | | 981 | | | 50 | 140 | 15 | | | 32 | 87+4 - 100+1 | | | | |
| 95 | | 982 | | | 50 | 140 | 16 | 1320 E | | 36 | 88+4 - 101+1 | | | | |
| 96 | | 983 | | | 50 | 140 | 17 | | | 40 | 89+4 - 102+1 | | | | |
| 97 | | 984 | | | 50 | 140 | 18 | | | 44 | 90+4 - 103+1 | | | | |
| 98 | | 985 | | | 50 | 140 | 19 | | | 48 | 91+4 - 104+1 | | | | |
| 99 | | 986 | | | 50 | 140 | 20 | | | 52 | 92+4 - 105+1 | | | | |

LAND SEISMIC RECORDING LOG



| | | | | | | | |
|-----------|-------|------------|-----------|-------|---------|------------------|-----|
| CLIENT: | Husky | PROSPECT: | NPR | AREA: | TUNALIK | LINE NO: | 703 |
| PARTY NO: | 1182 | INST. ENG: | TORGERSON | | DATE: | MO 2 DAY 8 YR 80 | |

| SHOTPOINT | TR. _____ to _____ | | TR. _____ to _____ | | SHOT | | | | SPREAD | | | REMARKS | CORR. STACK | | | | |
|-----------|--------------------|------|--------------------|------|------|-------|-----|--------|--------|------------|---------------|---------|--|---------|------|----------|------|
| | REEL NO. | REC. | REEL NO. | REC. | SIZE | DEPTH | NO. | OFFSET | DIR. | COP SWITCH | LINE GROUPS | | SET | TR 1-48 | | TR 48-96 | |
| | HT. | REC. | HT. | REC. | | | | | | | | | | HT. | REC. | HT. | REC. |
| 1100 | 991 | 997 | | | 50 | 60 | 21 | 1320 | W | 56 | 93+4 - 106+1 | 94 | 100 offset to 99 | | | | |
| 1101 | 998 | | | | 50 | 60 | 22 | 990 | E | 60 | 94+4 - 107+1 | | 101 offset 990' toward 102 | | | | |
| 1102 | 999 | | | | 50 | 60 | 23 | | | 64 | 95+4 - 108+1 | | | | | | |
| 1103 | 990 | | | | 50 | 60 | 24 | | | 68 | 96+4 - 109+1 | | | | | | |
| 1104 | 991 | | | | 50 | 60 | 25 | | | 72 | 97+4 - 110+1 | 110 | | | | | |
| 1105 | 992 | | | | 50 | 60 | 26 | | | 76 | 98+4 - 111+1 | | | | | | |
| 1106 | 993 | | | | 50 | 60 | 27 | | | 80 | 99+4 - 112+1 | | | | | | |
| 1107 | 994 | | | | 50 | 60 | 28 | | | 84 | 100+4 - 113+1 | 116 | 6' 112+4 DEAD spacing BETWEEN 112+113 990' | | | | |
| 1108 | 995 | | | | 50 | 60 | 29 | | | 16 | 101+4 - 114+1 | | left 112+4 DEAD | | | | |
| 1109 | 996 | | | | 50 | 60 | 30 | | | 20 | 102+4 - 115+1 | | | | | | |
| 1110 | 997 | | | | 50 | 60 | 31 | | | 24 | 103+4 - 116+1 | | | | | | |
| 1111 | 998 | | | | 50 | 60 | 32 | | | 28 | 104+4 - 117+1 | | | | | | |
| 1112 | 999 | | | | 50 | 60 | 33 | | | 32 | 105+4 - 118+1 | | | | | | |
| 1113 | 1000 | | | | 50 | 60 | 34 | | | 36 | 106+4 - 119+1 | | | | | | |
| 1114 | 1001 | | | | 50 | 60 | 35 | | | 40 | 107+4 - 120+1 | | | | | | |
| 1115 | 1002 | | | | 50 | 60 | 36 | | | 44 | 108+4 - 121+1 | | | | | | |
| 1116 | 1003 | | | | 50 | 60 | 37 | | | 48 | 109+4 - 122+1 | | | | | | |
| 1117 | 1004 | | | | 50 | 60 | 38 | | | 52 | 110+4 - 123+1 | | | | | | |
| 1118 | 1005 | | | | 50 | 60 | 39 | | | 56 | 111+4 - 124+1 | | | | | | |
| 1119 | 1006 | | | | 50 | 60 | 40 | | | 60 | 112+4 - T1 | | | | | | |
| 1120 | 1007 | | | | 50 | 60 | 41 | | | 64 | 113+4 - T5 | | | | | | |
| 1121 | 1008 | | | | 50 | 60 | 42 | | | 68 | 114+4 - T9 | | | | | | |
| 1122 | 1009 | | | | 50 | 60 | 43 | | | 72 | 115+4 - T13 | | | | | | |
| 1123 | 1010 | | | | 50 | 60 | 44 | 330 | E | 76 | 116+4 - T17 | | 123 offset 330' toward 124 | | | | |
| 1124 | 1011 | | | | 50 | 60 | 45 | | | 80 | 117+4 - T21 | | | | | | |
| 1125 | 1012 | | | | 50 | 60 | 46 | | | 84 | 118+4 - T25 | | | | | | |
| EOL | | | | | | | | | | | | | | | | | |