

LAND SEISMIC RECORDING LOG 13.0 Recording Hours



	CLIENT: Husky	PROSPECT: NPR-A	AREA: TUNALIK	LINE NO: 706					
	PARTY NO: 1182	INST. ENG: TORBERSON		DATE: 1 DAY 26 YR 80					
INSTRUMENT (9-TRACK)	<input checked="" type="checkbox"/> 1 SYSTEM <input type="checkbox"/> 2 SYSTEMS	<input checked="" type="checkbox"/> 1-24 & 25-48 <input type="checkbox"/> 1-48 & 49-96	ODDS <input checked="" type="checkbox"/> EVENS	TYPE: <input type="checkbox"/> DFS III <input type="checkbox"/> DFS IX <input checked="" type="checkbox"/> DFS X <input type="checkbox"/> OTHER	<input checked="" type="checkbox"/> 9 TRACK <input type="checkbox"/> 21 TRACK	FORMAT: B	<input checked="" type="checkbox"/> GAPPED <input type="checkbox"/> UNGAPPED	PACKING DENSITY: (L) <input type="checkbox"/> 356 BPI <input type="checkbox"/> 800 BPI (H) <input type="checkbox"/> 712 BPI <input checked="" type="checkbox"/> 1600 BPI	
	NO. BYTES IN HEADER REC:	NO. BYTES IN RECORD ID:	NO. BYTES PER SCAN:	RECORD NUMBERS: DEC <input type="checkbox"/> OCT	GAIN CONSTANT: 36 db	INPUT IMPEDANCE: _____ ohms	(1) _____ (2) _____ (3) _____ (4) _____ (5) _____ (6) _____ (7) _____		
CONFIGURATION (MAG TAPE)	FIELD TRACE NOS.: _____ DATA CHANNEL NOS.: _____ (ON MAG TAPE)			AUXILIARY DATA: AUXILIARY CHANNEL NOS.: _____					
PARAMETER	RECORD LENGTH: 6 sec	SAMPLE RATE: <input type="checkbox"/> 1 ms. <input type="checkbox"/> 4 ms. <input type="checkbox"/> 2 ms. <input type="checkbox"/> _____ ms.	GAIN MODE: <input type="checkbox"/> INITIAL <input type="checkbox"/> MANUAL <input type="checkbox"/> IFF <input type="checkbox"/> FINAL <input type="checkbox"/> OPERATE	FILTERS: _____	LO CUT HZ SLOPE _____	HI CUT HZ SLOPE _____	NOTCH FILTER: <input type="checkbox"/> IN <input type="checkbox"/> OUT		
DISPLAY	MODE: <input checked="" type="checkbox"/> AOC <input type="checkbox"/> FLOAT <input type="checkbox"/> AMPLIFIER <input type="checkbox"/> DEFLOAT <input type="checkbox"/> DIRECT	INITIAL GAIN: _____ db	TRIP SENS: _____ db	POLARITY CONVENTION: _____	PRESSURE INCREASE ON GEOPHONE: <input type="checkbox"/> NEGATIVE <input type="checkbox"/> POSITIVE	NUMBERS ON MAG. TAPE <input type="checkbox"/> DOWNBREAK <input type="checkbox"/> UPBREAK	ON DISPLAY <input type="checkbox"/>		
CFS I	TYPE STACK: _____	GATE LENGTH: _____	RECORD REJECTION: _____	NOISE REDUCTION: _____	NOISE THRESHOLD: _____	CORR. SCALING: _____	R.C.U. NORM/ALT SW. _____		
SOURCE	TYPE: <input checked="" type="checkbox"/> DYNAMITE <input type="checkbox"/> VIBROSEIS <input type="checkbox"/> OTHER	PATTERN: Enline / 1 Hole	NO. OF POSITIONS: _____	INLINE SPACING: _____	LATERAL SPACING: _____	STAGGER: _____	LENGTH: _____	WIDTH: _____	LATERAL OFFSET: _____
RECEIVER	TYPE: GSC-200	PATTERN: Enline	NO. OF ELEMENTS: 18	INLINE SPACING: 17.4	LATERAL SPACING: _____	STAGGER: _____	LENGTH: 338	WIDTH: _____	LATERAL OFFSET: _____
SPREAD	CONNECTION: SBR-PAR	RESISTANCE: _____ ohms	SHOTPOINT INTERVAL: 1370'	FOLD: 6	DIRECTION OF PROGRESSION: NORTH	SWEEP LENGTH: _____	SWEEP TAPER: _____	PHASE COMP: _____	LEADING GROUP: 48
	NO. OF GROUPS: 48	GROUP INTERVAL: 330'	OFFSET GROUP: 25 495	OFFSET GROUP: 25 495	OFFSET GROUP: 25 495	SWEEP END: _____	SWEEP TAPER: _____	PHASE COMP: _____	LEADING GROUP: 48

DIAGRAMS/MISC. INFORMATION: T25 T2 T1
X X X
50'

SHOTPOINT	TR. to		TR. to		SHOT			SPREAD			REMARKS	CORR. STACK				
	REEL NO.	REC.	REEL NO.	REC.	SIZE	DEPTH	NO. OFFSET	DIR.	CDP SWITCH	LINE GROUPS		SET UP	TR 1-48	TR 49-96	REC.	REC.
1	98110112	285			50	67	1		20	T25 - 7+1	8					
2		283			50	67	2		24	T21 - 8+1						
3		284			50	67	3		28	T17 - 9+1						
4		285			50	67	4		32	T13 - 10+1						
5		286			50	67	5		36	T9 - 11+1						
6		287			50	67	6		40	T5 - 12+1						
7		288			50	67	7		44	T1 - 13+1						
8		289			50	67	8		48	1+1 - 14+1						
9		290			50	67	9		52	2+1 - 15+1						
10		291			50	67	10		56	3+1 - 16+1						
11		292			50	67	11		60	4+1 - 17+1						
12		293			50	67	12		64	5+1 - 18+1						
13		294			50	67	13		68	6+1 - 19+1						
14		295			50	67	14		72	7+1 - 20+1	20					
15		296			50	67	15		76	8+1 - 21+1						
16		297			50	67	16		80	9+1 - 22+1						
17		298			50	67	17		84	10+1 - 23+1						
18		299			50	67	18		88	11+1 - 24+1						
19		300			50	67	19		92	12+1 - 25+1						
20		301			50	67	20		96	13+1 - 26+1						

Rec. Mtr = 13.5

LAND SEISMIC RECORDING LOG

	CLIENT: Husky	PROSPECT: NPR-A	AREA: TUNALIK	LINE NO: 706																		
PARTY NO: 1182		INST. ENG: TORGERSON		DATE: 1 27 80																		
INSTRUMENT (9-TRACK)	<input checked="" type="checkbox"/> 1 SYSTEM <input type="checkbox"/> 2 SYSTEMS		<input checked="" type="checkbox"/> 7-24 & 25-48 <input type="checkbox"/> 1-48 & 49-96	ODDS & EVENS <input checked="" type="checkbox"/> ODDS <input type="checkbox"/> EVENS	TYPE: <input type="checkbox"/> DFS III <input type="checkbox"/> DFS II <input checked="" type="checkbox"/> DFS I <input type="checkbox"/> OTHER	<input checked="" type="checkbox"/> 9 TRACK <input type="checkbox"/> 21 TRACK	FOP/MAT: B SEG:	<input type="checkbox"/> GAPPED <input type="checkbox"/> UNGAPPED	PACKING DENSITY: (L) <input type="checkbox"/> 356 BPI <input type="checkbox"/> 800 BPI (H) <input type="checkbox"/> 712 BPI <input type="checkbox"/> 1600 BPI	NO. BYTES IN HEADER REC.: NO. BYTES IN RECORD ID: NO. BYTES PER SCAN:	RECORD NUMBERS: <input checked="" type="checkbox"/> DEC. <input type="checkbox"/> OCT.	GAIN CONSTANT: 36 db INPUT IMPEDANCE: ohms.										
	CONFIGURATION (MAG TAPE)	FIELD TRACE NOS.:		DATA CHANNEL NOS.:		(ON MAG TAPE)																
PARAMETER	RECORD LENGTH: 6 sec.	SAMPLE RATE: <input checked="" type="checkbox"/> 1 ms. <input type="checkbox"/> 4 ms. <input type="checkbox"/> 2 ms. <input type="checkbox"/> ms.	GAIN MODE: <input type="checkbox"/> INITIAL <input type="checkbox"/> MANUAL <input type="checkbox"/> OPERATE	FILTERS: FREQ. 8 LO CUT HZ SLOPE 18 HI CUT HZ SLOPE 70		NOTCH FILTER: <input type="checkbox"/> IN <input type="checkbox"/> OUT		POLARITY CONVENTION: <input type="checkbox"/> NEGATIVE <input type="checkbox"/> POSITIVE		PRESSURE INCREASE ON GEOPHONE: <input type="checkbox"/> NEGATIVE <input type="checkbox"/> POSITIVE		NUMBERS ON MAG. TAPE: <input type="checkbox"/> DOWNBREAK <input type="checkbox"/> UPBREAK		ON DISPLAY: <input type="checkbox"/> ON DISPLAY								
DISPLAY	MODE: <input checked="" type="checkbox"/> AGC <input type="checkbox"/> FLOAT <input type="checkbox"/> DEFLOAT <input type="checkbox"/> AMPLIFIER <input type="checkbox"/> DIRECT	INITIAL GAIN: db	TRIP SENS: db	RECORD REJECTION:		NOISE REDUCTION:		NOISE THRESHOLD:		CORR. SCALING:		R.C.U. NORM / ALT SW.										
CFS I	TYPE STACK:		GATE LENGTH:		PATTERN: Inline / 1 Hole		NO. OF POSITIONS:		INLINE SPACING:		LATERAL SPACING:		STAGGER:		LENGTH:		WIDTH:		LATERAL OFFSET:			
SOURCE	<input checked="" type="checkbox"/> DYNAMITE <input type="checkbox"/> VIBROSEIS <input type="checkbox"/> OTHER		CHG/ HOLE:		HOLE DEPTH:		SWEEP POSITION:		SWEEP START:		SWEEP END:		SWEEP LENGTH:		SWEEP TAPER:		PHASE COMP:					
RECEIVER	TYPE: GSC-700		PATTERN: Inline		NO. OF ELEMENTS: 18		INLINE SPACING: 19.4		LATERAL SPACING: 330		STAGGER:		LENGTH:		WIDTH:		LATERAL OFFSET:					
SPREAD	CONNECTION: SEP-PRR		RESISTANCE: ohms		FOLD: 6		DIRECTION OF PROGRESSION: NORTH		LEADING GROUP: 48		NO. OF GROUPS: 48		GROUP INTERVAL: 330		SHOTPOINT INTERVAL: 1320		OFFSET GROUP 1: 8085		OFFSET GROUP 2: 8085		OFFSET GROUP 3: 8085	

DIAGRAMS/MISC. INFORMATION: 1944 257 262 32+1 Daily Tests in 706 -



x 0 x

SPR

SHOTPOINT	TR. to		TR. to		SHOT				SPREAD				REMARKS:	CORR. STACK				
	REEL NO.	REC.	REEL NO.	REC.	SIZE	DEPTH	NO.	OFFSET	DIR.	CDP SWITCH	LINE GROUPS			SET	TR 1-48	TR 49-96	TR 1-48	TR 49-96
26	981012	326			50	67	1			36	19+4	-	32+1	32				
27		327			50	67	2			40	20+4	-	33+1					
28		328			50	67	3			44	21+4	-	34+1					
29		329			50	67	4			8	22+4	-	35+1	39				
30		330			50	67	5			12	23+4	-	36+1					
31		331			50	67	6			16	24+4	-	37+1					
32		332			50	67	7			20	25+4	-	38+1					
33		333			50	67	8			24	26+4	-	39+1					
34		334			50	67	9			28	27+4	-	40+1					
35		335			50	67	10			32	28+4	-	41+1					
36		336			50	67	11			36	29+4	-	42+1					
37		337			50	67	12			40	30+4	-	43+1					
38		338			50	67	13			44	31+4	-	44+1					
39		339			50	67	14			48	32+4	-	45+1					
40		340			50	67	15			52	33+4	-	46+1					
41		341			50	67	16			56	34+4	-	47+1					
42		342			50	67	17			60	35+4	-	48+1					
43		343			50	67	18			24	36+4	-	49+1	49				
44		344			50	67	19			28	37+4	-	50+1					
45		345			50	67	20			32	38+4	-	51+1					

LAND SEISMIC RECORDING LOG

Page 7 of 2

	CLIENT: Husky	PROSPECT: NPP-A	AREA: TOMALIK	LINE NO: 706					
PARTY NO: 1182		INST. ENG: TORBERSON		DATE: 1 DAY 27 YR 80					
INSTRUMENT (9-TRACK)	<input checked="" type="checkbox"/> 1 SYSTEM <input type="checkbox"/> 2 SYSTEMS	<input checked="" type="checkbox"/> 1-24 & 25-48 <input type="checkbox"/> 1-48 & 49-96	DODS & EVENS	TYPE: <input type="checkbox"/> DFS III <input type="checkbox"/> DFS IX <input type="checkbox"/> OTHER	<input checked="" type="checkbox"/> 1 TRACK <input type="checkbox"/> 2 TRACK	FORMAT: B	<input checked="" type="checkbox"/> GAPPED <input type="checkbox"/> UNGAPPED	PACKING DENSITY: (LO) <input type="checkbox"/> 356 BPI <input type="checkbox"/> 600 BPI	(HI) <input type="checkbox"/> 712 BPI <input type="checkbox"/> 1600 BPI
	NO. BYTES IN HEADER REC:	NO. BYTES IN RECORD ID:	NO. BYTES PER SCAN:	RECORD NUMBERS: <input checked="" type="checkbox"/> DEC. <input type="checkbox"/> OCT.	GAIN CONSTANT: 36 db	INPUT IMPEDANCE: _____ ohms.			
CONFIGURATION (MAG TAPE)	FIELD TRACE NOS.: _____			AUXILIARY DATA:					
	DATA CHANNEL NOS.: _____			AUXILIARY CHANNEL NOS.: _____					
PARAMETER	RECORD LENGTH: 6 sec.	SAMPLE RATE: <input type="checkbox"/> 1 ms. <input type="checkbox"/> 4 ms. <input checked="" type="checkbox"/> 2 ms. <input type="checkbox"/> _____ ms.	GAIN MODE: <input type="checkbox"/> INITIAL <input type="checkbox"/> MANUAL <input checked="" type="checkbox"/> OFF <input type="checkbox"/> FINAL <input type="checkbox"/> OPERATE	FILTERS: FREQ. 8 LO CUT 18 HI CUT _____		HZ SLOPE 20		NOTCH FILTER: <input checked="" type="checkbox"/> IN <input type="checkbox"/> OUT	
DISPLAY	MODE: <input checked="" type="checkbox"/> FLOAT <input type="checkbox"/> AMPLIFIER <input type="checkbox"/> DEFOAT <input type="checkbox"/> DIRECT	INITIAL GAIN: 18 db	TRIP SENS: _____ db	POLARITY CONVENTION: _____		PRESSURE INCREASE ON GEOPHONE: _____		<input type="checkbox"/> NEGATIVE } NUMBERS ON <input type="checkbox"/> POSITIVE } ON MAG. TAPE <input type="checkbox"/> DOWNBREAK } ON DISPLAY <input type="checkbox"/> UPBREAK }	
CFS I	TYPE STACK:	GATE LENGTH:	RECORD REJECTION:	NOISE REDUCTION:		NOISE THRESHOLD:		CORR. SCALING: _____ R.C.U. NORM/ALT SW.	
SOURCE	TYPE: <input checked="" type="checkbox"/> DYNAMITE <input type="checkbox"/> VIBROSEIS <input type="checkbox"/> OTHER	PATTERN: Inline	NO. OF POSITIONS:	INLINE SPACING:	LATERAL SPACING:	STAGGER:	LENGTH:	WIDTH:	LATERAL OFFSET:
	CHG/ HOLE:	DEPTH:	SWEEP POSITION:	SWEEP START:	SWEEP END:	SWEEP LENGTH:	SWEEP TAPER:	PHASE COMP:	
RECEIVER	TYPE: GSC-700	PATTERN: Inline	NO. OF ELEMENTS: 8	INLINE SPACING: 19.4	LATERAL SPACING:	STAGGER:	LENGTH: 3.30	WIDTH:	LATERAL OFFSET:
	CONNECTION: 682-PAR	RESISTANCE: _____ ohms	STAGGER:	LENGTH: 3.30	WIDTH:	LATERAL OFFSET:			
SPREAD	NO. OF GROUPS: 48	GROUP INTERVAL: 330	SHOTPOINT INTERVAL: 1320	FOLD: 6	DIRECTION OF PROGRESSION: North				
	OFFSET GROUP 1: 8085	OFFSET GROUP 24: 495	OFFSET GROUP 25: 495	OFFSET GROUP 48/96: 8085	LEADING GROUP: 48				


DIAGRAMS/MISC. INFORMATION:

SHOTPOINT	TR. _____ to _____	TR. _____ to _____		SHOT				SPREAD			REMARKS:	CORR. STACK							
		REEL NO.	REC.	REEL NO.	REC.	SIZE	DEPTH	NO.	OFFSET	DIR.		CDP SWITCH	LINE GROUPS		SET UP	TR 1-48		TR 49-96	
46		9811012	3416	17	22	23	26	27	29	30	32	35	37	36	39+4 - 52+1	49			
47			347				50	67	72					40	40+4 - 53+1				
48			348				50	67	73					44	41+4 - 54+1				
49			349				50	67	74					48	42+4 - 55+1				
50			350				50	67	75					52	43+4 - 56+1				
51															57				
52															58				
53															59				

Recording Hrs = 16.0

LAND SEISMIC RECORDING LOG

Page 1 of 2

	CLIENT: Husky	PROSPECT: NPR-A	AREA: TONALIK	LINE NO: 786							
	PARTY NO: 1182	INST. ENG: JORGESON		DATE: 1 DAY 28 YR 80							
INSTRUMENT (9-TRACK)	<input checked="" type="checkbox"/> 1 SYSTEM <input type="checkbox"/> 2 SYSTEMS	<input checked="" type="checkbox"/> 1-24 & 25-48 <input type="checkbox"/> 1-48 & 49-96	ODDS EVEN	TYPE: <input type="checkbox"/> DFS III <input type="checkbox"/> DFS IV <input checked="" type="checkbox"/> DFS V <input type="checkbox"/> OTHER	<input checked="" type="checkbox"/> 9 TRACK <input type="checkbox"/> 21 TRACK	FOFHAT: B	<input type="checkbox"/> GAPPED <input type="checkbox"/> UNGAPPED	PACKING DENSITY: (LO) <input type="checkbox"/> 356 BPI (HI) <input checked="" type="checkbox"/> 712 BPI <input type="checkbox"/> 1600 BPI	RECORD NUMBERS: <input checked="" type="checkbox"/> DEC. <input type="checkbox"/> OCT.	GAIN CONSTANT: 36 db	INPUT IMPEDANCE: _____ ohms.
	NO. BYTES IN HEADER REC: _____	NO. BYTES IN RECORD ID: _____	NO. BYTES PER SCAN: _____			(1) _____ (2) _____ (3) _____ (4) _____ (5) _____ (6) _____ (7) _____					
CONFIGURATION (MAG TAPE)	FIELD TRACE NOS.: _____		(ON MAG TAPE)		AUXILIARY DATA: _____						
	DATA CHANNEL NOS.: _____				AUXILIARY CHANNEL NOS.: _____						
PARAMETER	RECORD LENGTH: 6 sec.	SAMPLE RATE: <input type="checkbox"/> 1 ms. <input type="checkbox"/> 4 ms. <input checked="" type="checkbox"/> 2 ms. <input type="checkbox"/> _____ ms.	GAIN MODE: <input type="checkbox"/> INITIAL <input type="checkbox"/> MANUAL <input checked="" type="checkbox"/> OFF <input type="checkbox"/> FINAL <input type="checkbox"/> OPERATE	FILTERS: FREQ 8	LO CUT HZ SLOPE 18	HI CUT HZ SLOPE 70	NOTCH FILTER: <input type="checkbox"/> IN <input type="checkbox"/> OUT	PRESSURE INCREASE ON GEOPHONE: <input type="checkbox"/> NEGATIVE <input type="checkbox"/> POSITIVE		NUMBERS ON MAG. TAPE <input type="checkbox"/> DOWNBREAK <input type="checkbox"/> UPBREAK	ON DISPLAY
DISPLAY	MODE: <input type="checkbox"/> FLOAT <input type="checkbox"/> AMPLIFIER <input checked="" type="checkbox"/> AGC <input type="checkbox"/> DEFLOAT <input type="checkbox"/> DIRECT	INITIAL GAIN: 18 db	TRIP SENS: _____ db	POLARITY CONVENTION: _____	NOISE REDUCTION: _____		NOISE THRESHOLD: _____	CORR. SCALING: _____	R.C.U. NORM./ALT SW.		
CFS I	TYPE STACK: _____	GATE LENGTH: _____	RECORD REJECTION: _____								
SOURCE	TYPE: <input checked="" type="checkbox"/> DYNAMITE <input type="checkbox"/> VIBROSEIS <input type="checkbox"/> OTHER	PATTERN: Fullup	NO. OF POSITIONS: _____	INLINE SPACING: _____	LATERAL SPACING: _____	STAGGER: _____	LENGTH: _____	WIDTH: _____	LATERAL OFFSET: _____		
RECEIVER	TYPE: GSC-200	PATTERN: Fullup	NO. OF ELEMENTS: 16	INLINE SPACING: _____	LATERAL SPACING: _____	STAGGER: _____	LENGTH: 19.4	WIDTH: _____	LATERAL OFFSET: _____		
SPREAD	CONNECTION: SER-PAR	RESISTANCE: _____ ohms	STAGGER: _____	LENGTH: _____	WIDTH: _____	LATERAL OFFSET: _____					
	NO. OF GROUPS: 48	GROUP INTERVAL: 330	SHOTPOINT INTERVAL: 1320	FOLD: 1	6	DIRECTION OF PROGRESSION: NORTH	LEADING GROUP: 48				
	OFFSET GROUP 1: 8085	OFFSET GROUP 25: 495	OFFSET GROUP 25: 495	OFFSET GROUP 48/MET: 8085	DAILY TESTS FN 351 - 372						

DIAGRAMS/MISC. INFORMATION: 444 443 5012 5711

~~X~~ ~~X~~ ~~X~~ ~~X~~

FN

SHOTPOINT	TR _____ TO _____		TR _____ TO _____		SHOT			SPREAD			REMARKS	CORR. STACK				
	REEL NO.	REC.	REEL NO.	REC.	SIZE	DEPTH	NO.	OFFSET	DIR.	CDP SWITCH		LINE GROUPS	TR 1-24	TR 25-48	TR 49-96	TR 100-120
50	17	10	17	22	20	27	29	30	32	35	37					
51		10				50	67	1			24	44+4 - 57+1				
52		10				50	67	2			28	45+4 - 58+1				
53		10				50	67	3			32	46+4 - 59+1				
54		10				50	67	4			36	47+4 - 60+1				
55		10				50	67	5			40	48+4 - 61+1				
56		10				50	67	6			44	49+4 - 62+1				
57		10				50	67	7			48	50+4 - 63+1				
58		10				50	67	8			52	51+4 - 64+1				
59		10				50	67	9			28	52+4 - 65+1				
60		10				50	67	10			32	53+4 - 66+1				
61		10				50	67	11			36	54+4 - 67+1				
62		10				50	67	12	100	E	40	55+4 - 68+1				
63		10				50	67	13			44	56+4 - 69+1				
64		10				50	67	14			48	57+4 - 70+1				
65		10				50	67	15			52	58+4 - 71+1				
66		10				50	67	16			56	59+4 - 72+1				
67		10				50	67	17			40	60+4 - 73+1				
68		10				50	67	18			44	61+4 - 74+1				
69		10				50	67	19			48	62+4 - 75+1				
70		10				50	67	20			52	63+4 - 76+1				

