


Records Hrs - 14

LAND SEISMIC RECORDING LOG

	CLIENT: Husky	PROSPECT: NPR-A	AREA: TUNALIK	LINE NO: 710												
	PARTY NO: 1182	INST. ENG:		DATE: MO 1 DAY 00 YR 80												
INSTRUMENT (9-TRACK)	<input checked="" type="checkbox"/> 1 SYSTEM <input type="checkbox"/> 2 SYSTEMS	<input checked="" type="checkbox"/> 1-24 & 25-48 <input type="checkbox"/> 1-48 & 49-96	<input checked="" type="checkbox"/> ODDS <input type="checkbox"/> EVENS	TYPE: <input type="checkbox"/> DFS III <input type="checkbox"/> DFS IV	<input checked="" type="checkbox"/> TRACK <input type="checkbox"/> 21 TRACK	FORMAT: B	<input type="checkbox"/> GAPPED <input type="checkbox"/> UNGAPPED	PACKING DENSITY:	(L0) <input type="checkbox"/> 356 BPI <input type="checkbox"/> 800 BPI	(H1) <input type="checkbox"/> 712 BPI <input type="checkbox"/> 1000 BPI						
	NO. BYTES IN HEADER REC:	NO. BYTES IN RECORD ID:	NO. BYTES PER SCAN:	RECORD NUMBERS: <input type="checkbox"/> SEC. <input type="checkbox"/> OCT.	GAIN CONSTANT: 36	db	INPUT IMPEDANCE: 20k	ohms	(1)	(2)	(3)	(4)	(5)	(6)	(7)	
CONFIGURATION (MAG TAPE)	FIELD TRACE NOS.:				AUXILIARY DATA:				AUXILIARY CHANNEL NOS.:							
PARAMETER	RECORD LENGTH: 6 sec.	SAMPLE RATE: <input type="checkbox"/> 1 ms. <input type="checkbox"/> 4 ms.	GAIN MODE: <input type="checkbox"/> INITIAL <input type="checkbox"/> MANUAL <input type="checkbox"/> OPERATE	FILTERS: FREQ. 8	LO CUT HZ SLOPE 18	HI CUT HZ SLOPE 70	NOTCH FILTER: <input type="checkbox"/> IN <input type="checkbox"/> OUT									
DISPLAY	MODE: <input checked="" type="checkbox"/> AGC <input type="checkbox"/> FLOAT <input type="checkbox"/> DEFOAT <input type="checkbox"/> AMPLIFIER <input type="checkbox"/> DIRECT	INITIAL GAIN: 24 db	TRIP SENS: 3 db	POLARITY CONVENTION:	PRESSURE INCREASE ON GEOPHONE:	<input type="checkbox"/> NEGATIVE <input type="checkbox"/> POSITIVE	NUMBERS ON MAG TAPE	<input type="checkbox"/> DOWNBREAK <input type="checkbox"/> UPBREAK	ON DISPLAY							
CFS I	TYPE STACK:	GATE LENGTH:	RECORD REJECTION:	NOISE REDUCTION:	NOISE THRESHOLD:	CORR. SCALING:	R.C.U. NORM./ALT SW.									
SOURCE	TYPE: <input type="checkbox"/> DYNAMITE <input type="checkbox"/> VIBROSEIS <input type="checkbox"/> OTHER	PATTERN: Inline / hole	NO. OF POSITIONS:	NE ADJ.:	LATERAL SPACING:	STAGGER:	LENGTH:	WIDTH:	LATERAL OFFSET:							
RECEIVER	TYPE: 20-D	PATTERN: Inline	NO. ELEMENTS: 13	NE ADJ.:	LATERAL SPACING:	STAGGER:	LENGTH: 28	WIDTH:	LATERAL OFFSET:							
SPREAD	CONNECTION: Series-Parallel	RESISTANCE: 580 ohms	STAGGER:	NO. OF GROUPS: 48	GROUP INTERVAL: 330	SHOTPOINT INTERVAL: 1320	FOLD: 6	DIRECTION OF PROGRESSION: South	LEADING GROUP: 48							
DIAGRAMS/MISC. INFORMATION:	T-1 X				T-24 X				T-12 X				T-71 X			



SHOTPOINT	TR. 1 to		TR. 2 to		SHOT				SPREAD			REMARKS	CORR. STACK									
	REEL NO.	REC.	REEL NO.	REC.	SIZE	DEPTH	NO.	OFFSET	DIR.	COP SWITCH	LINE GROUPS		SET UP	TR 1-28		TR 48-96						
															RV	REC	RV	REC				
1	981007	13	17	22/23	26	27	29	30	32	33	37	330	S	40	T-1	-7+1	3	#3 misfire				
2		14												44	T-5	-8+1						
3		15												48	T-9	-9+1						
4		16												52	T-13	-10+1						
5		17												56	T-17	-11+1						
6		18												60	T-21	-12+1						
7		19												64	T-25	-13+1						
8		20												68	1+4	-14+1						
9		21												72	2+4	-15+1						
10		22												76	3+4	-16+1						
11		23												80	4+4	-17+1						
12		24												32	5+4	-18+1	16					
13		25												36	6+4	-19+1						
14		26												40	7+4	-20+1						
15		27												44	8+4	-21+1						
16		28												32	9+4	-22+1	20	COP ERROR (28-18+4-21+1)				
17		29												36	10+4	-23+1						
18		30												40	11+4	-24+1						
19		31												44	12+4	-25+1						
20		32												48	13+4	-26+1						

LAND SEISMIC RECORDING LOG



	CLIENT: HUSKY	PROSPECT: NPR-A	AREA: TUNALIK	LINE NO: 710		
	PARTY NO: 1172	INST. ENG: Streiff		DATE: 1 DAY 20th 80		
INSTRUMENT (9-TRACK)	<input checked="" type="checkbox"/> SYSTEM <input type="checkbox"/> 2 SYSTEMS	<input checked="" type="checkbox"/> 24 & 25-48 <input type="checkbox"/> 1-48 & 49-96	<input type="checkbox"/> DDFS <input type="checkbox"/> DDF	<input checked="" type="checkbox"/> TRACK <input type="checkbox"/> 21 TRACK	<input type="checkbox"/> GAPPED <input type="checkbox"/> UNGAPPED	PACKING DENSITY: (LQ) <input type="checkbox"/> 356 BPI (HI) <input type="checkbox"/> 712 BPI <input type="checkbox"/> 1408 BPI
	NO. BYTES IN HEADER REC:	NO. BYTES IN RECORD ID:	NO. BYTES PER SCAN:	RECORD NUMBERS:	GAIN CONSTANT: db	INPUT IMPEDANCE: ohms
CONFIGURATION (MAG TAPE)	FIELD TRACE NOS.: _____ DATA CHANNEL NOS.: _____ (ON MAG TAPE)			AUXILIARY DATA: AUXILIARY CHANNEL NOS.: _____		
PARAMETER	RECORD LENGTH: 6 sec.	SAMPLE RATE: <input type="checkbox"/> 1 ms. <input type="checkbox"/> 4 ms.	GAIN MODE: <input checked="" type="checkbox"/> INITIAL <input type="checkbox"/> MANUAL <input type="checkbox"/> FINAL <input type="checkbox"/> OPERATE	FILTERS: FREQ: 8 Hz	LO CUT HZ SLOPE: 17	HIGH CUT HZ SLOPE: 70
DISPLAY	MODE: <input checked="" type="checkbox"/> ASC <input type="checkbox"/> FLOAT <input type="checkbox"/> AMPLIFIER <input type="checkbox"/> DIRECT	INITIAL GAIN: 24 db	TRIP SENS: 7 db	POLARITY CONVENTION: <input type="checkbox"/> NEGATIVE <input type="checkbox"/> POSITIVE	PRESSURE INCREASE ON GEOPHONE: <input type="checkbox"/> NUMBERS ON MAG. TAPE: <input type="checkbox"/> DOWNBREAK <input type="checkbox"/> UPBREAK	NOTCH FILTER: <input checked="" type="checkbox"/> IN <input type="checkbox"/> OUT
CFS I	TYPE STACK:	GATE LENGTH:	RECORD REJECTION:	NOISE REDUCTION:	NOISE THRESHOLD:	CORR. SCALING: R.C.U. NORM/ALT SW.
SOURCE	TYPE: <input checked="" type="checkbox"/> DYNAMITE <input type="checkbox"/> VIBROSEIS <input type="checkbox"/> OTHER	PATTERN: inline/hole	NO. OF POSITIONS:	INLINE SPACING:	LATERAL SPACING:	STAGGER: _____ LENGTH: _____ WIDTH: _____ LATERAL OFFSET: _____
RECEIVER	TYPE: 20-D	PATTERN: inline	NO. OF ELEMENTS: 12	INLINE SPACING: 28	LATERAL SPACING: _____	STAGGER: _____ LENGTH: 330 WIDTH: _____ LATERAL OFFSET: _____
SPREAD	CONNECTION: series-parallel	RESISTANCE: 500 ohms	SHOTPOINT INTERVAL: 1320	FOLD: 6	DIRECTION OF PROGRESSION: South	LEADING GROUP: 48

DIAGRAMS/MISC. INFORMATION:

SHOTPOINT	FR. _____ TO _____		TR. _____ TO _____		SHOT				SPREAD			REMARKS	CORR. STACK			
	REEL NO.	REC.	REEL NO.	REC.	SIZE	DEPTH	NO.	OFFSET	DIR	CDP SWITCH	LINE GROUPS		KEY UP	TE 48-49	REC.	TE 48-49
21	98110017	24			50	160	21			52	14+4-27+1	20				
22		25			50	160	22			24	15+4-28+1	28				
23		26			50	160	23			28	16+4-29+1					
24		27			50	160	24			32	17+4-30+1					
25		28			50	160	25			36	18+4-31+1					
26		29			50	160	26			40	19+4-32+1					
27		30			50	160	27			44	20+4-33+1					
28		31			50	160	28			48	21+4-34+1					
29		32			50	160	29			52	22+4-35+1					
30		33			50	160	30			24	23+4-36+1	36				
31		34			50	160	31			28	24+4-37+1					
32		35			50	160	32			32	25+4-38+1					
33		36			50	160	33			36	26+4-39+1					
34		37			50	160	34			40	27+4-40+1					
35		38			50	160	35			44	28+4-41+1					
36		39			50	160	36			48	29+4-42+1					
37		40			50	160	37			52	30+4-43+1					
38		41			50	160	38			56	31+4-44+1					
39		42			50	160	39			60	32+4-45+1					
40		43			50	160	40			64	33+4-46+1					

Hole blew out

LAND SEISMIC RECORDING LOG

	CLIENT: Husky	PROSPECT: NPR-A	AREA: TUNALIK	LINE NO: 710					
PARTY NO: 1182		INST. ENG: Streiff		DATE: 1 MAY 21 1980					
INSTRUMENT (9-TRACK)	<input checked="" type="checkbox"/> 1 SYSTEM <input type="checkbox"/> 2 SYSTEMS	<input type="checkbox"/> 1-24 & 25-48 <input type="checkbox"/> 1-48 & 49-96	<input type="checkbox"/> ODDS <input type="checkbox"/> EVENS	TYPE: <input type="checkbox"/> DFS III <input type="checkbox"/> DFS IV <input type="checkbox"/> OTHER	<input checked="" type="checkbox"/> 1 TRACK <input type="checkbox"/> 21 TRACK	FORMAT: B SEG	<input type="checkbox"/> GAPPED <input type="checkbox"/> UNGAPPED	PACKING DENSITY: (L) <input type="checkbox"/> 356 SFI (M) <input type="checkbox"/> 712 SFI (H) <input type="checkbox"/> 1400 SFI	
	NO. BYTES IN HEADER REC:	NO. BYTES IN RECORD ID:	NO. BYTES PER SCAN:	RECORD NUMBERS: <input checked="" type="checkbox"/> DEC <input type="checkbox"/> OCT	GAIN CONSTANT: 36 db	INPUT IMPEDANCE: 20K ohms	(1) (2) (3) (4) (5) (6) (7)		
CONFIGURATION (MAG TAPE)	FIELD TRACE NOS.: 1-48			AUXILIARY DATA:					
	DATA CHANNEL NOS.: 1-48 (ON MAG TAPE)			AUXILIARY CHANNEL NOS.:					
PARAMETER	RECORD LENGTH: 6 sec	SAMPLE RATE: <input type="checkbox"/> 1 ms. <input type="checkbox"/> 4 ms. <input checked="" type="checkbox"/> 2 ms.	GAIN MODE: <input type="checkbox"/> INITIAL <input type="checkbox"/> MANUAL <input checked="" type="checkbox"/> TFP	FILTERS: FREQ 8	LO CUT HZ SLOPE 18	HI CUT HZ SLOPE 70	NOTCH FILTER: <input type="checkbox"/> IN <input checked="" type="checkbox"/> OUT		
DISPLAY	MODE: <input checked="" type="checkbox"/> AGC <input type="checkbox"/> FLOAT <input type="checkbox"/> DEFLOAT <input type="checkbox"/> AMPLIFIER DIRECT	INITIAL GAIN: 24 db	TRIP SENS: 3 db	POLARITY CONVENTION: <input type="checkbox"/> POSITIVE <input checked="" type="checkbox"/> NEGATIVE	PRESSURE INCREASE ON GEOPHONE: <input type="checkbox"/> POSITIVE <input checked="" type="checkbox"/> NEGATIVE	NUMBERS ON MAG. TAPE: <input type="checkbox"/> DOWNBREAK <input checked="" type="checkbox"/> UPBREAK	ON DISPLAY		
CFS I	TYPE STACK:	GATE LENGTH:	RECORD REJECTION:	NOISE REDUCTION:	NOISE THRESHOLD:	CORR. SCALING:	P.C.U. NORM./ALT SW.		
SOURCE	TYPE: <input checked="" type="checkbox"/> DYNAMITE <input type="checkbox"/> VISROSEIS <input type="checkbox"/> OTHER	PATTERN: inline/hole	NO. OF POSITIONS:	INLINE SPACING:	LATERAL SPACING:	STAGGER:	LENGTH:	WIDTH:	LATERAL OFFSET:
RECEIVER	TYPE: 20-D	PATTERN: inline	NO. OF ELEMENTS: 12	INLINE SPACING: 28	LATERAL SPACING:	STAGGER:	LENGTH: 330	WIDTH:	LATERAL OFFSET:
SPREAD	CONNECTION: Series-parallel	RESISTANCE: 580 ohms	STAGGER:	LENGTH: 330	WIDTH:	LATERAL OFFSET:	DIAGRAMS/MISC. INFORMATION:		
<p>NO. OF GROUPS: 48 GROUP INTERVAL: 330 SHOTPOINT INTERVAL: 1320 FOLD: 6 DIRECTION OF PROGRESSION: South</p> <p>OFFSET GROUP 1: 8085 OFFSET GROUP 24: 495 OFFSET GROUP 25: 495 OFFSET GROUP 48/96: 8085 LEADING GROUP: 48</p> <p>3414 4013 4112 4711 #55 test TB X X O X X TR#1 SP41 TR#48</p>									



SHOTPOINT	TR 1 to		TR 2 to		SHOT			SPREAD			REMARKS	CORR. STACK			
	REEL NO.	REC.	REEL NO.	REC.	SIZE	DEPTH	NO. OFFSET	DIR.	COP SWITCH	LINE GROUPS		TR 1-48	TR 48-96	TR 1-48	TR 48-96
41	7181007	58			150	60	11		28	34+4-47+46					
42		59			50	60	12		32	35+4-48+1					
43		60			50	60	13		36	36+4-49+1					
44		61			50	60	14		40	37+4-50+1					
45		62			50	60	15		44	38+4-51+1					
46		63			50	60	16		48	39+4-52+1					
47		64			50	60	17		52	40+4-53+1					
48		65			50	60	18		56	41+4-54+1					
49		66			50	60	19	75 E	60	42+4-55+1					
50		67			50	60	20		64	43+4-56+1					
51		68			50	60	21		68	44+4-57+1					
52		69			50	60	22		72	45+4-58+1					
53		70			50	60	23		76	46+4-59+1					
54		71			50	60	24		80	47+4-60+1					
55		72			50	60	25		36	48+4-61+1	58				
56		73			50	60	26		40	49+4-62+1					
57		74			50	60	27	330 S	44	50+4-63+1					
58		75			50	60	28		48	51+4-64+1					
59		76			50	60	29		52	52+4-65+1					
60		77			50	60	30		56	53+4-66+1					

Wind NOISE

SP-56 → 58 ICC

TR#1 dead
Hole Blew Out

LAND SEISMIC RECORDING LOG



	CLIENT: Husky	PROSPECT: NPR-A	AREA: JUNALIK	LINE NO: 710					
	PARTY NO: 1122	INST. ENG: Streiff		DATE: 1-21-80					
INSTRUMENT (9-TRACK)	<input type="checkbox"/> 1 SYSTEM <input type="checkbox"/> 2 SYSTEMS	<input type="checkbox"/> 24 & 25-48 <input type="checkbox"/> 1-48 & 49-96	TYPE: <input type="checkbox"/> DFS III <input type="checkbox"/> DFS IV	<input checked="" type="checkbox"/> TRACK <input type="checkbox"/> 21 TRACK	FOF/BAT: B	<input type="checkbox"/> GAPPED <input type="checkbox"/> UNGAPPED	PACKING DENSITY: (L) <input type="checkbox"/> 356 BPI (H) <input type="checkbox"/> 712 BPI <input type="checkbox"/> 1400 BPI		
	NO. BYTES IN HEADER REC:	NO. BYTES IN RECORD ID:	NO. BYTES PER SCAN:	RECORD NUMBERS: <input type="checkbox"/> DEC. <input type="checkbox"/> OCT.	GAIN CONSTANT: _____ db	INPUT IMPEDANCE: _____ ohms.			
CONFIGURATION (MAG TAPE)	FIELD TRACE NOS.: 1-48		AUXILIARY DATA: (1) _____ (2) _____ (3) _____ (4) _____ (5) _____ (6) _____ (7) _____		AUXILIARY CHANNEL NOS.: _____				
PARAMETER	RECORD LENGTH: 6 sec.	SAMPLE RATE: <input type="checkbox"/> 1 ms. <input type="checkbox"/> 4 ms. <input checked="" type="checkbox"/> 8 ms. <input type="checkbox"/> 16 ms.	GAIN MODE: <input type="checkbox"/> INITIAL <input type="checkbox"/> FINAL <input type="checkbox"/> MANUAL <input type="checkbox"/> OPERATE	FILTERS: FREQ. 8	LO CUT HZ SLOPE: 18	H1 CUT HZ SLOPE: 70	NOTCH FILTER: <input type="checkbox"/> IN <input type="checkbox"/> OUT		
DISPLAY	MODE: <input type="checkbox"/> FLOAT <input type="checkbox"/> AMPLIFIER <input type="checkbox"/> DIRECT	INITIAL GAIN: 24 db	TRIP SENS: 3 db	POLARITY CONVENTION: <input type="checkbox"/> NEGATIVE <input type="checkbox"/> POSITIVE	PRESSURE INCREASE ON GEOPHONE: <input type="checkbox"/> NEGATIVE <input type="checkbox"/> POSITIVE	NUMBERS ON MAG TAPE: <input type="checkbox"/> DOWNBREAK <input type="checkbox"/> UPBREAK	ON DISPLAY		
CFS I	TYPE STACK:	GATE LENGTH:	RECORD REJECTION:	NOISE REDUCTION:	NOISE THRESHOLD:	CORR. SCALING:	R.C.U. NORM./ALT SW.		
SOURCE	TYPE: <input checked="" type="checkbox"/> DYNAMITE <input type="checkbox"/> VIBROSEIS <input type="checkbox"/> OTHER	PATTERN: inline/hole	NO. OF POSITIONS:	INLINE SPACING:	LATERAL SPACING:	STAGGER:	LENGTH:	WIDTH:	LATERAL OFFSET:
RECEIVER	TYPE: 20-D	PATTERN: inline	NO. OF ELEMENTS: 12	INLINE SPACING: 28	LATERAL SPACING:	STAGGER:	LENGTH:	WIDTH:	LATERAL OFFSET:
SPREAD	CONNECTION: Series-Parallel	RESISTANCE: 580 ohms	STAGGER:	LENGTH:	WIDTH:	LATERAL OFFSET:			
	NO. OF GROUPS: 48	GROUP INTERVAL: 330	SHOTPOINT INTERVAL: 1320	FOLD: 6	DIRECTION OF PROGRESSION: South				
	OFFSET GROUP 1: 8085	OFFSET GROUP 24: 495	OFFSET GROUP 25: 495	OFFSET GROUP 48/96: 8085	LEADING GROUP: 48				

DIAGRAMS/MISC. INFORMATION:

SHOTPOINT NO.	TR. _____ to _____		TR. _____ to _____		SHOT					DIR.	CDP SWITCH	SPREAD LINE GROUPS	REMARKS	CORR. STACK			
	REEL NO.	REC.	REEL NO.	REC.	SIZE	DEPTH	NO.	OFFSET	HI					TE 48-96	REC.	REC.	
61	781007	78			50	160	21			60	54+4-67+1	58					
62		79			50	160	22			64	55+4-68+1						
63		80			50	160	23			24	56+4-69+1	69					
64		81			50	160	24			28	57+4-70+1						
65		83			50	160	25			32	58+4-71+1					# 82 mis fire	
66		84			50	160	26			36	59+4-72+1					TR#48 dead	
67		85			50	160	27			40	60+4-73+1						
68		86			50	160	28			44	61+4-74+1						
69		87			50	160	29			48	62+4-75+1						
70		88			50	160	30			24	63+4-76+1	76				INITIAL GAIN 30 db	
71		89			50	160	31			28	64+4-77+1						
72		90			50	160	32			32	65+4-78+1						
73		91			50	160	33			36	66+4-79+1						
74		92			50	160	34			40	67+4-80+1						
75		93			50	160	35			44	68+4-81+1						
76		94			50	160	36			48	69+4-82+1						
77		95			50	160	37			52	70+4-83+1						
78		96			50	160	38			24	71+4-84+1	84				TR#48 Noisy (layout crew)	
79		97			50	160	39			28	72+4-85+1						
80		98			50	160	40			32	73+4-86+1						

Rec. Nr. = 110

LAND SEISMIC RECORDING LOG

	CLIENT: Husky	PROSPECT: NPR-A	AREA: TUNALIK	LINE NO: 710					
	PARTY NO: 1182	INST. ENG:		DATE: NO 1 DAY 22 YR 80					
INSTRUMENT (9-TRACK)	<input type="checkbox"/> 1 SYSTEM <input type="checkbox"/> 2 SYSTEMS	<input type="checkbox"/> 1-24 & 25-48 <input type="checkbox"/> 1-48 & 49-96	<input checked="" type="checkbox"/> DPOS <input checked="" type="checkbox"/> EVENS	TYPE: <input type="checkbox"/> DFS III <input type="checkbox"/> DFS IV <input type="checkbox"/> OTHER	<input checked="" type="checkbox"/> 9 TRACK <input type="checkbox"/> 21 TRACK	FORMAT: B	<input type="checkbox"/> GAPPED <input type="checkbox"/> UNGAPPED	PACKING DENSITY: (L) <input type="checkbox"/> 356 BPI (H) <input type="checkbox"/> 712 BPI <input type="checkbox"/> 1000 BPI	
	NO. BYTES IN HEADER REC:	NO. BYTES IN RECORD ID:	NO. BYTES PER SCAN:	RECORD NUMBERS: <input checked="" type="checkbox"/> DEC <input type="checkbox"/> OCT	GAIN CONSTANT: 36 db	INPUT IMPEDANCE: 20K ohms.	(1) (2) (3) (4) (5) (6) (7)		
CONFIGURATION (MAG TAPE)	FIELD TRACE NOS.:			AUXILIARY DATA:					
	DATA CHANNEL NOS.:			AUXILIARY CHANNEL NOS.:					
PARAMETER	RECORD LENGTH: 6 sec.	SAMPLE RATE: <input type="checkbox"/> 1 ms. <input type="checkbox"/> 4 ms.	GAIN MODE: <input checked="" type="checkbox"/> INITIAL <input type="checkbox"/> FINAL	FILTERS: FREQ: 8	LO CUT HZ SLOPE: 18	HI CUT HZ SLOPE: 70	NOTCH FILTER: <input type="checkbox"/> IN <input type="checkbox"/> OUT		
DISPLAY	MODE: <input checked="" type="checkbox"/> AGC <input type="checkbox"/> FLOAT <input type="checkbox"/> AMPLIFIER <input type="checkbox"/> DEFLOAT <input type="checkbox"/> DIRECT	INITIAL GAIN: 24 db	TRIP SENS: 3 ds	POLARITY CONVENTION: <input type="checkbox"/> NEGATIVE <input checked="" type="checkbox"/> POSITIVE	PRESSURE INCREASE ON GEOPHONE: <input type="checkbox"/> NEGATIVE <input checked="" type="checkbox"/> POSITIVE	NUMBERS ON MAG. TAPE: <input type="checkbox"/> DOWNBREAK <input checked="" type="checkbox"/> UPBREAK	ON DISPLAY		
CFS I	TYPE STACK:	GATE LENGTH:	RECORD REJECTION:	NOISE REDUCTION:	NOISE THRESHOLD:	CORR. SCALING:	R.C.U. NORM./ALT SW.		
SOURCE	TYPE: <input checked="" type="checkbox"/> DYNAMITE <input type="checkbox"/> VIBROSEIS <input type="checkbox"/> OTHER	PATTERN: inline / hole	NO. OF POSITIONS:	INLINE SPACING:	LATERAL SPACING:	STAGGER:	LENGTH:	WIDTH:	LATERAL OFFSET:
	CHG/ HOLE: 50	MOLE DEPTH: 75	SWEEP POSITION:	SWEEP START:	SWEEP END:	SWEEP LENGTH:	SWEEP TAPER:	PHASE COMP.	
RECEIVER	TYPE: 20-0	PATTERN: inline	NO. OF ELEMENTS: 12	INLINE SPACING: 28	LATERAL SPACING:	STAGGER:	LENGTH: 330	WIDTH:	LATERAL OFFSET:
	CONNECTION: Series-Parallel	RESISTANCE: 580 ohms	STAGGER:	LENGTH:					
SPREAD	NO. OF GROUPS: 4.8	GROUP INTERVAL: 330	SHOTPOINT INTERVAL: 1320	FOLD: 6	DIRECTION OF PROGRESSION: South				
	OFFSET GROUP 1: 8085	OFFSET GROUP 2: 495	OFFSET GROUP 3: 495	OFFSET GROUP 4/96: 8085	LEADING GROUP: 48				

DIAGRAMS/MISC. INFORMATION: # 115-116-117 test TB
130 test TB

SHOTPOINT	TR. _____ to _____		TR. _____ to _____		SHOT			SPREAD			REMARKS:	CORR. STACK				
	REEL NO.	REC.	REEL NO.	REC.	SIZE	DEPTH	NO.	OFFSET	DIR.	CUP SWITCH		LINE GROUPS	SET	TR 1-24	TR 25-48	TR 49-96
85	981907	1118			50	60	11			24	78+4 - 91+1	91				
86		1119			50	60	12			28	79+4 - 92+1					
87		1120			50	60	13			32	80+4 - 93+1					
88	981008	1122			50	60	14			36	81+4 - 94+1					
89		1123			50	60	15			40	82+4 - 95+1					
90		1124			50	60	16			44	83+4 - 96+1					
91		1125			50	60	17			48	84+4 - 97+1					
92		1126			50	60	18			24	85+4 - 98+1	98				
93		1127			50	60	19			28	86+4 - 99+1					
94		1128			50	60	20			32	87+4 - 100+1					
95		1129			50	60	21			36	88+4 - T-1					
96		1131			50	60	22			40	89+4 - T-5					
97		1132			50	60	23			44	90+4 - T-9					
98		1133			50	60	24			48	91+4 - T-13					
99		1134			50	60	25			52	92+4 - T-17					
100		1135			50	60	26			56	93+4 - T-21					
101		1136			50	60	27			60	94+4 - T-25					