



Rec. HRS = 14.0

LAND SEISMIC RECORDING LOG

	CLIENT: HUSKY	PROSPECT: NPR-A	AREA: TUNALIK	LINE NO: 712	
	PARTY NO: 1172	INST. ENG: Streff		DATE: MO 1 DAY 17, YR 80	

INSTRUMENT (9-TRACK)	<input type="checkbox"/> 1 SYSTEM <input type="checkbox"/> 2 SYSTEMS	<input type="checkbox"/> 1-24 & 25-48 <input type="checkbox"/> 1-48 & 49-96	ODDS EVENS <input type="checkbox"/> ODDS <input type="checkbox"/> EVENS	TYPE: <input type="checkbox"/> DFS I <input type="checkbox"/> DFS II <input type="checkbox"/> DFS III <input type="checkbox"/> OTHER	<input type="checkbox"/> 2 TRACK <input type="checkbox"/> 21 TRACK	FORMAT: B SEG	<input type="checkbox"/> GAPPED <input type="checkbox"/> UNGAPPED	PACKING DENSITY: (L) <input type="checkbox"/> 356 BPM <input type="checkbox"/> 800 BPM	(H) <input type="checkbox"/> 712 BPM <input type="checkbox"/> 1800 BPM				
	NO. BYTES IN HEADER REC:	NO. BYTES IN RECORD 10:	NO. BYTES PER SCAN:	RECORD NUMBERS: <input checked="" type="checkbox"/> DEC <input type="checkbox"/> OCT	GAIN CONSTANT: 36 db	INPUT IMPEDANCE: 20K ohms	(1)	(2)	(3)	(4)	(5)	(6)	(7)
CONFIGURATION (MAG TAPE)	FIELD TRACE NOS.: 1-48				AUXILIARY DATA:				AUXILIARY CHANNEL NOS.:				
	DATA CHANNEL NOS.: 1-48 (ON MAG TAPE)												
PARAMETER	RECORD LENGTH: 6 sec.	SAMPLE RATE: <input type="checkbox"/> 1 ms <input type="checkbox"/> 4 ms	GAIN MODE: <input type="checkbox"/> INITIAL <input type="checkbox"/> MANUAL <input type="checkbox"/> OPERATE	FILTERS: FREQ: 8	LO CUT HZ SLOPE: 18	HIGH CUT HZ SLOPE: 70	NOTCH FILTER: <input type="checkbox"/> IN <input type="checkbox"/> OUT						
DISPLAY	MODE: <input checked="" type="checkbox"/> REC <input type="checkbox"/> FLOAT <input type="checkbox"/> AMPLIFIER <input type="checkbox"/> DIRECT	INITIAL GAIN: 24 db	TRIP SENS: 3 db	POLARITY CONVENTION: <input type="checkbox"/> PRESSURE INCREASE ON GEOPHONE <input type="checkbox"/> NEGATIVE <input type="checkbox"/> POSITIVE		NUMBERS ON MAG TAPE: <input type="checkbox"/> DOWNBREAK <input type="checkbox"/> UPBREAK		ON DISPLAY					
CFS I	TYPE STACK:	GATE LENGTH:	RECORD REJECTION:	NOISE REDUCTION:		NOISE THRESHOLD:	CORR. SCALING:	R.C.U. NORM/ALT SW.					
SOURCE	TYPE: <input type="checkbox"/> DYNAMITE <input type="checkbox"/> VIBROSEIS <input type="checkbox"/> OTHER	PATTERN: inline/hole	NO. OF POSITIONS:	INLINE SPACING:	LATERAL SPACING:	STAGGER:	LENGTH:	WIDTH:	LATERAL OFFSET:				
		CHG/HOLE: 50 HOLE DEPTH: 75	SWEEP POSITION:	SWEEP START:	SWEEP END:	SWEEP LENGTH:	SWEEP TAPER:	PHASE COMP.					
RECEIVER	TYPE: 20-D	PATTERN: inline	NO. OF ELEMENTS: 12	INLINE SPACING: 28	LATERAL SPACING:		LENGTH:	WIDTH:	LATERAL OFFSET:				
	CONNECTION: Series-Parallel	RESISTANCE: 580 ohms	STAGGER:										
SPREAD	NO. OF GROUPS: 48	GROUP INTERVAL: 330	SHOTPOINT INTERVAL: 1320	FOLD: 6	DIRECTION OF PROGRESSION: South		LEADING GROUP: 48						
	OFFSET GROUP 1: 8085	OFFSET GROUP 24: 495	OFFSET GROUP 24: 495	OFFSET GROUP 48/96: 8085									

DIAGRAMS/MISC. INFORMATION:

T-1-1
 X
 1 TR#2

T-33-1
 X
 1 SPI

T-112
 X
 7+1
 TR#48

SHOTPOINT	SR		TR		SHOT				SPREAD		REMARKS	CORR. STACK	
	REEL NO.	REC.	REEL NO.	REC.	SIZE	DEPTH	NO.	OFFSET	DIR.	CDP SWITCH		LINE GROUPS	TR 1-48
1	781006	49			50	60	19			24	7+1 - 7+1		
2		50			50	60	20			28	7-4 - 8+1		
3		51			50	60	21			32	7-8 - 9+1		
4		52			50	60	22			36	7-12 - 10+1		
5		53			50	60	23			40	7-16 - 11+1		
6		54			50	60	24			44	7-20 - 12+1		
7		55			50	60	25			48	7-24 - 13+1		
8		56			50	60	26			52	7+4 - 14+1		
9		57			50	60	27			56	2+4 - 15+1		
10		58			50	60	28			60	3+4 - 16+1		
11		59			50	60	29			24	4+4 - 17+1		
12		60			50	60	30			28	5+4 - 18+1		
13		61			50	60	31			32	6+4 - 19+1		
14		62			50	60	32			36	7+4 - 20+1		
15		63			50	60	33			40	8+4 - 21+1		
16		64			50	60	34			44	9+4 - 22+1		
17		65			50	60	35			48	10+4 - 23+1		
18		66			50	60	36			52	11+4 - 24+1		
19		67			50	60	37			56	12+4 - 25+1		
20		68			50	60	38			60	13+4 - 26+1		
21		69			50	60	39			64	14+4 - 27+1		
22		70			50	60	40			68	15+4 - 28+1		

NOISY TRACES
on Bare ICE

14+4 dead

wind noise

20+2 on bare ICE



LAND SEISMIC RECORDING LOG

	CLIENT: Husky	PROSPECT: NPR-A	AREA: LUNGLIN	LINE NO: 712 #2			
	PARTY NO: 1182	INST. ENG: Streff		DATE: 1 DAY 19 VR 80			
INSTRUMENT (9-TRACK)	<input type="checkbox"/> SYSTEM <input type="checkbox"/> 2 SYSTEMS	<input type="checkbox"/> 1-24 & 25-48 <input type="checkbox"/> 1-48 & 49-96	<input checked="" type="checkbox"/> DFS I <input type="checkbox"/> DFS II <input type="checkbox"/> DFS III <input type="checkbox"/> OTHER	<input type="checkbox"/> TRACK <input type="checkbox"/> 21 TRACK	FORMAT: B	<input type="checkbox"/> GAPPED <input type="checkbox"/> UNGAPPED	PACKING DENSITY: (LO) <input type="checkbox"/> 356 BPI (HI) <input type="checkbox"/> 712 BPI
	NO. BYTES IN HEADER REC:	NO. BYTES IN RECORD ID:	NO. BYTES PER SCAN:	RECORD NUMBERS: <input type="checkbox"/> DEC. <input type="checkbox"/> OCT	GAIN CONSTANT: _____ db	INPUT IMPEDANCE: _____ ohms	(1) (2) (3) (4) (5) (6) (7)
CONFIGURATION (MAG TAPE)	FIELD TRACE NOS.: 1-48			AUXILIARY DATA:			
	DATA CHANNEL NOS.: 1-48			AUXILIARY CHANNEL NOS.:			
PARAMETER	RECORD LENGTH: 6 sec	SAMPLE RATE: <input type="checkbox"/> 1 ms. <input type="checkbox"/> 4 ms.	GAIN MODE: <input checked="" type="checkbox"/> TRIP <input type="checkbox"/> INITIAL <input type="checkbox"/> FINAL <input type="checkbox"/> MANUAL <input type="checkbox"/> OPERATE	FILTERS: FREQ. 8	LO CUT HZ SLOPE 18	HI CUT SLOPE 70	NOTCH FILTER: <input type="checkbox"/> IN <input type="checkbox"/> OUT
DISPLAY	MODE: <input type="checkbox"/> AGC <input type="checkbox"/> FLOAT <input type="checkbox"/> DEFOAT <input type="checkbox"/> AMPLIFIER <input type="checkbox"/> DIRECT	INITIAL GAIN: 2.4 db	TRIP SENS: 3 db	POLARITY CONVENTION: <input type="checkbox"/> NEGATIVE <input type="checkbox"/> POSITIVE	PRESSURE INCREASE ON GEOPHONE: <input type="checkbox"/> NEGATIVE <input type="checkbox"/> POSITIVE	NUMBERS ON MAG TAPE: <input type="checkbox"/> DOWNBREAK <input type="checkbox"/> UPBREAK	ON DISPLAY: <input type="checkbox"/> ON DISPLAY
CFS I	TYPE STACK:	GATE LENGTH:	RECORD REJECTION:	NOISE REDUCTION:	NOISE THRESHOLD:	CORR. SCALING:	R.C.U. NORM. ALT SW.
SOURCE	TYPE: <input type="checkbox"/> DYNAMITE <input type="checkbox"/> V-BROSEIS <input type="checkbox"/> OTHER	PATTERN: inline/hole	NO. OF POSITIONS:	INLINE SPACING:	LATERAL SPACING:	STAGGER:	LENGTH: WIDTH: LATERAL OFFSET:
		CHG/ HOLE: 50 HOLE DEPTH: 75	SWEET POSITION:	SWEET START:	SWEET END:	SWEET LENGTH: SWEET TAPER:	PHASE COMP.
RECEIVER	TYPE: 20-0	PATTERN: inline	NO. OF ELEMENTS:	INLINE SPACING:	LATERAL SPACING:	STAGGER:	LENGTH: WIDTH: LATERAL OFFSET:
	CONNECTION: Series-Parallel	RESISTANCE: 580 ohms	STAGGER:	LENGTH:	WIDTH:	LATERAL OFFSET:	
SPREAD	NO. OF GROUPS: 48	GROUP INTERVAL: 330	SHOTPOINT INTERVAL: 1320	FOLD:	DIRECTION OF PROGRESSION:	LEADING GROUP:	
	OFFSET GROUP 1: 8095	OFFSET GROUP 24 495	OFFSET GROUP 25	OFFSET GROUP 48/96:			

DIAGRAMS/MISC. INFORMATION: #182 test TA

SHOTPOINT	TR 10		TR 10		SHOT					DIP	CDP SWITCH	SPREAD	REMARKS:	CORR STACK			
	REEL NO.	REC.	REEL NO.	REC.	SIZE	DEPTH	NO.	OFFSET	LINE GROUPS					TR 10	TR 20	TR 30	TR 40
23	981006	83			50	60	1		32	16+4-29+1	27						
24		84			50	60	2		36	17+4-30+1							
25		85			50	60	3		40	18+4-31+1							
26		86			50	60	4		40	19+4-32+1	28						
27		87			50	60	5		44	20+4-33+1							
28		88			50	60	6	250 E	48	21+4-34+1							
29		89			50	60	7		52	22+4-35+1							
30		90			50	60	8		56	23+4-36+1							
31		91			50	60	9		60	24+4-37+1							
32		92			50	60	10		64	25+4-38+1							
33		93			50	60	11		68	26+4-39+1							
34		94			50	60	12		70	27+4-40+1	41						
35		96			50	60	13		74	28+4-41+1							
36		97			50	60	14		78	29+4-42+1							
37		98			50	60	15		82	30+4-43+1							
38		99			50	60	16		86	31+4-44+1							
39		100			50	60	17	250 W	90	32+4-45+1							
40		101			50	60	18	250 W	94	33+4-46+1							
41		102			50	60	19	330 S	98	34+4-47+1							
42		103			50	60	20	250 W	102	35+4-48+1							

LAND SEISMIC RECORDING LOG

	CLIENT: HUSKY	PROSPECT: NPR-A	AREA: TUNALIK	LINE NO.: 712					
	PARTY NO.: 1182	INST. ENG.: Streff		DATE: 1 DAY 19 80					
INSTRUMENT (9-TRACK)	<input checked="" type="checkbox"/> SYSTEM <input type="checkbox"/> 2 SYSTEMS	<input type="checkbox"/> 1-24 & 25-48 <input type="checkbox"/> 1-48 & 49-96	ODDS EVENS	TYPE: <input type="checkbox"/> DFS III <input type="checkbox"/> DFS IV <input type="checkbox"/> DFS V <input type="checkbox"/> OTHER	<input type="checkbox"/> 9 TRACK <input type="checkbox"/> 21 TRACK	FORMAT: B	<input type="checkbox"/> GAPPED <input type="checkbox"/> UNGAPPED	PACKING DENSITY: (L) <input type="checkbox"/> 356 BPI <input type="checkbox"/> 800 BPI	(H) <input type="checkbox"/> 712 BPI <input type="checkbox"/> 1400 BPI
	NO. BYTES IN HEADER REC.	NO. BYTES IN RECORD ID:	NO. BYTES PER SCAN:	RECORD NUMBERS: <input type="checkbox"/> DEC <input type="checkbox"/> OCT	GAIN CONSTANT: _____ db	INPUT IMPEDANCE: _____ ohms			
CONFIGURATION (MAG TAPE)	FIELD TRACE NOS.: 1-48			AUXILIARY DATA: (1) _____ (2) _____ (3) _____ (4) _____ (5) _____ (6) _____ (7) _____					
	DATA CHANNEL NOS.: 1-48			AUXILIARY CHANNEL NOS.: _____					
PARAMETER	RECORD LENGTH: 6 sec.	SAMPLE RATE: <input type="checkbox"/> 1 ms <input type="checkbox"/> 4 ms	GAIN MODE: <input type="checkbox"/> INITIAL <input checked="" type="checkbox"/> TRIP	FILTERS: FREQ. 8 LO CUT HZ SLOPE 18 HI CUT HZ SLOPE 70			NOTCH FILTER: <input type="checkbox"/> IN <input type="checkbox"/> OUT		
DISPLAY	MODE: <input checked="" type="checkbox"/> AGC <input type="checkbox"/> FLOAT <input type="checkbox"/> AMPLIFIER <input type="checkbox"/> DEFLOAT <input type="checkbox"/> DIRECT	INITIAL GAIN: 24 db	TRIP SENS.: 3 db	POLARITY CONVENTION: <input type="checkbox"/> NEGATIVE <input type="checkbox"/> POSITIVE			NUMBERS ON ON MAC TAPE: <input type="checkbox"/> DOWNBREAK <input type="checkbox"/> UPBREAK ON DISPLAY		
CFS I	TYPE STACK:	GATE LENGTH:	RECORD REJECTION:	NOISE REDUCTION: _____ NOISE THRESHOLD: _____			CORR. SCALING: _____ R.C.U. NORM./ALT SW.		
SOURCE	TYPE: <input checked="" type="checkbox"/> DYNAMIC <input type="checkbox"/> VIBROSEIS <input type="checkbox"/> OTHER	PATTERN: inline/hole	NO. OF POSITIONS:	INLINE SPACING:	LATERAL SPACING:	STAGGER:	LENGTH:	WIDTH:	LATERAL OFFSET:
		CHG./HOLE: 50 HOLE DEPTH: 75	SWEET POSITION:	SWEET START:	SWEET END:	SWEET LENGTH:	SWEET TAPER:	PHASE COMP.	
RECEIVER	TYPE: 20-D	PATTERN: inline	NO. OF ELEMENTS: 12	INLINE SPACING: 28			LATERAL SPACING:		
	CONNECTION: Series-Parallel	RESISTANCE: 580 ohms	STAGGER:	LENGTH: 330			WIDTH:		
SPREAD	NO. OF GROUPS: 48	GROUP INTERVAL: 730	SHOTPOINT INTERVAL: 1320	HOLD: 6			DIRECTION OF PROGRESSION: South		
	OFFSET GROUP 1: 8085	OFFSET GROUP 2: 495	OFFSET GROUP 25: 495	OFFSET GROUP 48/96: 8085			LEADING GROUP: 48		

DIAGRAMS/MISC. INFORMATION:

SHOTPOINT	TR 10		TR 20		SHOT				SPREAD			REMARKS	CORR STACK				
	REEL NO.	REC.	REEL NO.	REC.	SIZE	DEPTH	NO.	OFFSET	DIP	CDP SWITCH	LINE GROUPS		1-48	19 80	1-48	19 80	
43	801006	104			50	6021				56	36+4 - 49+1		41				
44		105			50	6022				60	37+4 - 50+1						
45		106			50	6023				24	38+4 - 51+1		51				
46		107			50	6024				28	39+4 - 52+1						
47		108			50	6025	250	W		32	40+4 - T-1						
48		109			50	6026				36	41+4 - T-5						
49		110			50	6027				40	42+4 - T-9						
50		111			50	6028				44	43+4 - T-13						
51		112			50	6029				48	44+4 - T-17						
52		113			50	6030				52	45+4 - T-21						
53		114			50	6031				56	46+4 - T-24						
											E.O.L.						