

LAND SEISMIC RECORDING LOG

of 2

CLIENT: Husky	PROSPECT: NPR-A	AREA:	LINE NO: 713	
PARTY NO: 1182	INST. ENG: D. LUSTER, S. IPPUSCH		DATE: MO 4 DAY 20 YR 80	

INSTRUMENT (9-TRACK)	NO. BYTES IN HEADER REC: 228	NO. BYTES IN RECORD ID: 24	NO. BYTES PER SCAN: 254	RECORD NUMBERS: DEC	GAIN CONSTANT: 36	INPUT IMPEDANCE: 2K
-------------------------	--	--------------------------------------	-----------------------------------	-------------------------------	-----------------------------	-------------------------------

CONFIGURATION (MAG TAPE)	FIELD TRACE NOS.: 1-96	AUXILIARY DATA: TW 5AS 78	AUXILIARY CHANNEL NOS.: 0 1 2
--------------------------	----------------------------------	-------------------------------------	---


PARAMETER	RECORD LENGTH: 8	SAMPLE RATE: 2	GAIN MODE: IFP	FILTERS: FREQ. 8	LO CUT HZ SLOPE 18	HI CUT HZ SLOPE 20	NOTCH FILTER: IN
-----------	----------------------------	--------------------------	--------------------------	----------------------------	---------------------------	---------------------------	----------------------------

DISPLAY	MODE: AGC	INITIAL GAIN: 0	TRIP SENS: db	POLARITY CONVENTION: POS	PRESSURE INCREASE ON GEOPHONE: POSITIVE	CORR. SCALING:	R.C.U. NORM/ALT SW.
---------	---------------------	---------------------------	-------------------------	------------------------------------	---	----------------	---------------------

SOURCE	TYPE: DYNAMITE	PATTERN: INLINE	NO. OF POSITIONS: 1	INLINE SPACING:	LATERAL SPACING:	STAGGER:	LENGTH:	WIDTH:	LATERAL OFFSET:
--------	--------------------------	---------------------------	-------------------------------	-----------------	------------------	----------	---------	--------	-----------------

RECEIVER	TYPE: GSC-20 D	PATTERN: INLINE	NO. OF ELEMENTS: 18	INLINE SPACING: 5.6	LATERAL SPACING:	STAGGER:	LENGTH:	WIDTH:	LATERAL OFFSET:
----------	--------------------------	---------------------------	-------------------------------	-------------------------------	------------------	----------	---------	--------	-----------------

SPREAD	NO. OF GROUPS: 96	GROUP INTERVAL: 110'	SHOTPOINT INTERVAL: 880'	FOLD: 6	DIRECTION OF PROGRESSION: W
--------	-----------------------------	--------------------------------	------------------------------------	-------------------	---------------------------------------



DAILY TEST FILE 1343-1352
TEST TB FILE 1371

SHOTPOINT	TR. to		TR. to		SHOT		SPREAD		REMARKS	CORR. STACK				
	REEL NO.	REC.	REEL NO.	REC.	SIZE	DEPTH	NO. OFFSET	DIR.		CDP SWITCH	LINE GROUPS	TR. 1-24	TR. 25-48	TR. 49-72
100	98	1104	1372		110	90	11		17	96+1 - 107+8				
101		1373			110	90	2		17	97+1 - 107+8				
102		1374			110	90	3	E	17	98+1 - 107+8				
103		1375			110	90	4		25	97+1 - 108+8				
104		1376			110	90	5		33	98+1 - 108+8				
105		1377			110	90	6		41	99+1 - 110+8				
106		1378			110	90	7		49	100+1 - 111+8				
107		1379			110	90	8		9	101+1 - 112+8				
108		1380			110	90	9		17	102+1 - 113+8				
109		1381			110	90	10		25	103+1 - 114+8				
110		1382			110	90	11		33	104+1 - 115+8				
111		1383			110	90	12		41	105+1 - 116+8				
112		1384			110	90	13		49	106+1 - 117+8				
113		1385			110	90	14		9	107+1 - 118+8				T-1 dead
114		1386			110	90	15		17	108+1 - 119+8				
115		1387			110	90	16		25	109+1 - 120+8				
116		1388			110	90	17		33	110+1 - 121+8				T-12 dead
117		1389			110	90	18		41	111+1 - 122+8				
118		1390			110	90	19		49	112+1 - 123+8				
119		1391			110	90	20		9	113+1 - 124+8				T-14 dead

LAND SEISMIC RECORDING LOG



CLIENT: **Husky**
 PARTY NO.: **1182**

PROSPECT: **NPR-A**
 INST. ENG.: **D. Luster / S. Lipschit**

AREA:

LINE NO.: **713**
 DATE: **MO 4 DAY 20 YR 80**



SHOTPOINT	TR. 10		TR. 10		SHOT		SPREAD		REMARKS	CORR. STACK								
	REEL NO.	REC.	REEL NO.	REC.	SIZE	DEPTH	NO.	OFFSET		DIR.	CDP SWITCH	LINE GROUPS		TR 1-20		TR 20-35		
														HT.	REC.	HT.	REC.	
120	9811104	1392			110	9021				17	114+1	-	125+8					T-6 DEAD
121		1393			110	9022				25	115+1	-	126+8					
122		1394			110	9023				33	116+1	-	127+8					
123		1395			110	9024				41	117+1	-	128+8					
124		1396			110	9025				49	118+1	-	129+8					
125		1397			110	9026				9	119+1	-	130+8					T-1 DEAD
126		1398			110	9027				17	120+1	-	131+8					
127		1399			110	9028				25	121+1	-	132+8					T-10 DEAD
128		1400			110	9029				33	122+1	-	133+8					
129		1401			110	9030				41	123+1	-	134+8					
130					110	9031				49	124+1	-	135+8					

LAND SEISMIC RECORDING LOG

	CLIENT: Husky	PROSPECT: NPP-A	AREA: FORTRESS M.T., Colville River	LINE NO.: 713
	PARTY NO.: 1182	INST. ENG.: LUSTER - IPPISCH		DATE: MO 4 DAY 21 YR 80

INSTRUMENT	<input checked="" type="checkbox"/> 1 SYSTEM <input checked="" type="checkbox"/> 2 SYSTEMS	<input type="checkbox"/> 1-24 & 25-48 <input type="checkbox"/> 1-48 & 49-96	ODDS EVENS <input checked="" type="checkbox"/> ODDS <input type="checkbox"/> EVENS	TYPE: <input type="checkbox"/> DPS III <input type="checkbox"/> DPS III <input checked="" type="checkbox"/> DPS III <input type="checkbox"/> OTHER	<input checked="" type="checkbox"/> 9 TRACK <input type="checkbox"/> 21 TRACK	FORMAT: B SEG:	<input checked="" type="checkbox"/> GAPPED <input type="checkbox"/> UNGAPPED	PACKING DENSITY: (10) <input type="checkbox"/> 356 BPI (11) <input type="checkbox"/> 712 BPI (12) <input type="checkbox"/> 1000 BPI
(9-TRACK)	NO. BYTES IN HEADER REC.: 228	NO. BYTES IN RECORD ID.: 24	NO. BYTES PER SCAN.: 254	RECORD NUMBERS: <input checked="" type="checkbox"/> DEC. <input type="checkbox"/> OCT.	GAIN CONSTANT: 36 db	INPUT IMPEDANCE: 2K ohms		

CONFIGURATION (MAG TAPE)	FIELD TRACE NOS.: 1-96 DATA CHANNEL NOS.: 5-100 (ON MAG TAPE)	AUXILIARY DATA: FW SPS 7A AUXILIARY CHANNEL NOS.: 0 1 2
--------------------------	--	--

PARAMETER	RECORD LENGTH: 8 sec.	SAMPLE RATE: <input type="checkbox"/> 1 ms. <input type="checkbox"/> 4 ms. <input checked="" type="checkbox"/> 2 ms.	GAIN MODE: <input type="checkbox"/> INITIAL <input checked="" type="checkbox"/> FINAL <input type="checkbox"/> MANUAL <input type="checkbox"/> OPERATE	FILTERS: <input type="checkbox"/> LO CUT <input type="checkbox"/> HI CUT FREQ. 8 HZ SLOPE 18	FREQ. 128 HZ SLOPE 70 NOTCH FILTER: <input type="checkbox"/> IN <input type="checkbox"/> OUT
-----------	------------------------------	---	---	--	--


DISPLAY	MODE: <input type="checkbox"/> FLOAT <input checked="" type="checkbox"/> ACQ <input type="checkbox"/> DEFOAT <input type="checkbox"/> DIRECT	AMPLIFIER <input type="checkbox"/> DIRECT	INITIAL GAIN: 0 db TRIP SENS.: _____ db	POLARITY CONVENTION: POS PRESSURE INCREASE ON GEOPHONE: <input type="checkbox"/> NEGATIVE <input checked="" type="checkbox"/> POSITIVE	NUMBERS ON MAG. TAPE: <input type="checkbox"/> DOWNBREAK <input checked="" type="checkbox"/> UPBREAK	ON DISPLAY: <input type="checkbox"/> ON DISPLAY
---------	---	--	---	---	---	---

CFS I	TYPE: STAND ALONE DES	GATE LENGTH: _____	RECORD REJECTION: _____	NOISE REDUCTION: _____	NOISE THRESHOLD: _____	CORR. SCALING: _____	R.C.U. NORM./ALT SW.
-------	------------------------------	--------------------	-------------------------	------------------------	------------------------	----------------------	----------------------

SOURCE	TYPE: <input checked="" type="checkbox"/> DYNAMITE <input type="checkbox"/> VIBROSEIS <input type="checkbox"/> OTHER	PATTERN: INLINE	NO. OF POSITIONS: 1	INLINE SPACING: _____	LATERAL SPACING: _____	STAGGER: _____	LENGTH: _____	WIDTH: _____	LATERAL OFFSET: _____
		CHG/ HOLE: 110	HOLE DEPTH: 90	SWEEP POSITION: _____	SWEEP START: _____	SWEEP END: _____	SWEEP LENGTH: _____	SWEEP TAPER: _____	PHASE COMP.: _____

RECEIVER	TYPE: GSC 201D	PATTERN: INLINE	NO. OF ELEMENTS: 18	INLINE SPACING: 6.5 5.6	LATERAL SPACING: _____
	CONNECTION: SER/ PAR	RESISTANCE: 560 ohms	STAGGER: _____	LENGTH: _____	WIDTH: _____

SPREAD	NO. OF GROUPS: 96	GROUP INTERVAL: 110'	SHOTPOINT INTERVAL: 880	FOLD: 6	DIRECTION OF PROGRESSION: W
	OFFSET GROUP 1: 5225'	OFFSET GROUP 48: 55'	OFFSET GROUP 97: 55'	OFFSET GROUP 96: 5225'	LEADING GROUP: 96



SHOTPOINT	TR 10		TR 10		SHOT		SPREAD		REMARKS	CORR STACK			
	REEL NO.	REC.	REEL NO.	REC.	SIZE	DEPTH	NO.	OFFSET		DIR.	COP SWITCH	LINE GROUPS	TR 1-48
130	981105	1A1A			110	90	1			1	128+1 - 135+8		
131		1A15			110	90	9			9	125+1 - 136+8		
132		1A16			110	90	17	110 E		17	126+1 - 137+8		
133		1A17			110	90	25			25	127+1 - 138+8		
134		1A18			110	90	33			33	128+1 - 139+8		
135		1A19			110	90	41			41	129+1 - 140+8		
136		1A20			110	90	49			49	130+1 - 141+8		
137		1A21			110	90	9			9	131+1 - 142+8		
138		1A22			110	90	17			17	132+1 - 143+8		
139		1A23			110	90	25			25	133+1 - 144+8		
140		1A24			110	90	33			33	134+1 - 145+8		
141		1A25			110	90	41			41	135+1 - 146+8		
142		1A26			110	90	49			49	136+1 - 147+8		
143		1A27			110	90	9			9	137+1 - 148+8		
144		1A28			110	90	17			17	138+1 - 149+8		
145		1A29			110	90	25			25	139+1 - 150+8		
146		1A30			110	90	33	110 E		33	140+1 - 151+8		
147		1A31			110	90	41			41	141+1 - 152+8		
148		1A32			110	90	49			49	142+1 - 153+8		
149		1A33			110	90	9			9	143+1 - 154+8		

