

LAND SEISMIC RECORDING LOG

	CLIENT: Husky	PROSPECT: NPR-4	AREA: UMIAT
PARTY NO: 1186	INST. ENG: Streff	LINE NO: 720	DATE: MO 4 DAY 26 YR 80

INSTRUMENT (9-TRACK)	<input type="checkbox"/> 1 SYSTEM <input checked="" type="checkbox"/> 2 SYSTEMS	<input type="checkbox"/> 24 & 25-48 <input checked="" type="checkbox"/> 48 & 49-96	<input type="checkbox"/> ODDS <input type="checkbox"/> EVENS	TYPE: <input type="checkbox"/> DFS III <input type="checkbox"/> DFS IV <input type="checkbox"/> DFS V <input type="checkbox"/> OTHER	<input checked="" type="checkbox"/> 1 TRACK <input type="checkbox"/> 2 TRACK	FORMAT: 1 SEG B <input type="checkbox"/> UNGAPPED <input type="checkbox"/> GAPPED	PACKING DENSITY: (I) <input type="checkbox"/> 356 BPI <input type="checkbox"/> 800 BPI (II) <input type="checkbox"/> 712 BPI <input type="checkbox"/> 1000 BPI
NO. BYTES IN HEADER REC: 228	NO. BYTES IN RECORD ID: 24	NO. BYTES PER SCAN: 254	RECORD NUMBERS: <input checked="" type="checkbox"/> DEC <input type="checkbox"/> OCT	GAIN CONSTANT: 36	INPUT IMPEDANCE: 20000 ohms		

CONFIGURATION (MAG TAPE)	FIELD TRACE NOS.: 1-96 DATA CHANNEL NOS.: 5-100 (ON MAG TAPE)	AUXILIARY DATA: AUXILIARY CHANNEL NOS.: TW SPS TD
--------------------------	--	---

PARAMETER	RECORD LENGTH: Y sec	SAMPLE RATE: <input type="checkbox"/> 1 ms <input type="checkbox"/> 4 ms	GAIN MODE: <input type="checkbox"/> INITIAL <input type="checkbox"/> FINAL	FILTERS: <input type="checkbox"/> LO CUT <input type="checkbox"/> HI CUT	FREQ: 8 HZ SLOPE: 18 FREQ: 128 HZ SLOPE: 70	NOTCH FILTER: <input type="checkbox"/> IN <input checked="" type="checkbox"/> OUT POLARITY CONVENTION: POS
DISPLAY	<input type="checkbox"/> MODE <input type="checkbox"/> FLOAT <input type="checkbox"/> AMPLIFIER <input type="checkbox"/> DEFLOAT <input type="checkbox"/> DIRECT	INITIAL GAIN: 8 db	TRIP SENS: 0 db	NOISE REDUCTION: <input type="checkbox"/> NOISE THRESHOLD: <input type="checkbox"/> CORR. SCALING: <input type="checkbox"/>	PRESSURE INCREASE ON GEOPHONE: <input type="checkbox"/> NEGATIVE <input checked="" type="checkbox"/> POSITIVE NUMBERS ON MAG TAPE: <input type="checkbox"/> DOWNBREAK <input type="checkbox"/> UPBREAK	ON DISPLAY: <input type="checkbox"/> ON DISPLAY
CFS I	TYPE STACK:	GATE LENGTH:	RECORD REJECTION:	R.C.U. NORM. ALT SW.		

SOURCE	<input type="checkbox"/> DYNAMITE <input type="checkbox"/> VIBROSEIS <input type="checkbox"/> OTHER	PATTERN: inline-hole CHG/ HOLE: 110 HOLE DEPTH: 185	NO. OF POSITIONS: SWEEP POSITION:	INLINE SPACING: SWEEP START:	LATERAL SPACING: SWEEP END:	STAGGER: SWEEP LENGTH:	LENGTH: SWEEP TAPER:	WIDTH: PHASE COMP.	LATERAL OFFSET:
--------	---	---	--------------------------------------	---------------------------------	--------------------------------	---------------------------	-------------------------	-----------------------	-----------------

RECEIVER	TYPE: 70-D CONNECTION: Series-Parallel	PATTERN: inline RESISTANCE: 560 ohms	NO. OF ELEMENTS: 18 STAGGER:	INLINE SPACING: LENGTH: 110	LATERAL SPACING: WIDTH:	LATERAL OFFSET:
----------	---	---	--	---------------------------------------	----------------------------	-----------------

SPREAD	NO. OF GROUPS: 96 OFFSET GROUP 1: 5225	GROUP INTERVAL: 110 OFFSET GROUP 47: 55	SHOTPOINT INTERVAL: 880 OFFSET GROUP 48/96: 5225	FOLD: 6 DIRECTION OF PROGRESSION: North	LEADING GROUP: 96
--------	---	--	---	--	--------------------------



DIAGRAMS/MISC. INFORMATION:
 #128-137 tests
 #138 test TD
 T-1 T-8
 4 x x x x x x x x
 E TA#1
 SP-100
 North
 105
 1 x x x x x x x x
 TR#56


Note! 908 not shown in this log # 908 logs were not aligned in order with logs

SHOTPOINT	TR. 1 to		TR. 2 to		SHOT		SPREAD		REMARKS	CORR. STACK				
	REEL NO.	REC.	REEL NO.	REC.	SIZE	DEPTH	NO.	OFFSET		DIR.	CDP SWITCH	LINE GROUPS	SET UP	TR. 1-22
1100	9894	104			110	101.5	1			13	T-1 - 105+8	1	Recorder @ SP 104+4/15	
1101		1140					2			21	T-9 - 106+8			
1102		1141					3			29	T-17 - 107+8			
1103		1142					4			37	T-25 - 108+8			
1104		1143					5			45	T-33 - 109+8			
1105		1144					6			5	T-41 - 110+8	2	Recorder @ SP 109+4/15	
1106		1145					7			13	100+1 - 111+8			
1107		1146					8	440 N		21	101+1 - 112+8			
1108		1147					9	77.5 NE		29	102+1 - 113+8			
1109		1148					10			37	103+1 - 114+8			
1110		1149					11			45	104+1 - 115+8			
1111		1150					12			5	105+1 - 116+8	3	Recorder @ SP 113+4/15	
1112		1151					13			13	106+1 - 117+8		SP-116 → 117 - steep slope	
1113		1152					14			21	107+1 - 118+8			
1114		1153					15			29	108+1 - 119+8			
1115		1154					16			37	109+1 - 120+8			
1116		1155					17	18.5 S		45	110+1 - 121+8			
1117		1156					18	130 S		5	111+1 - 122+8	4	Recorder @ SP 119+4/15	
1118		1157					19	130 E		13	112+1 - 123+8			
1119		1158					20	25 E		21	113+1 - 124+8			
120		159					31			29	114+1 - 125+8			
121		160					32			37	115+1 - 126+8			
122		161					33			45	116+1 - 127+8			

LAND SEISMIC RECORDING LOG

Page 1 of 2

	CLIENT: Husky	PROSPECT: UM1AT	AREA: NPR-4	LINE NO.: 720			
	PARTY NO.: 1186	INST. ENG.: R. Scheel	DATE: MO 4 DAY 27 YE 80				
Daily Tests FN162-171; Test TB FN122; Noise FN124							
INSTRUMENT (9-TRACK)	<input type="checkbox"/> 1 SYSTEM <input type="checkbox"/> 2 SYSTEMS	<input type="checkbox"/> 1-24 & 25-48 <input type="checkbox"/> 1-48 & 49-96	NO. BYTES IN RECORD ID: 24	NO. BYTES PER SCAN: 254	RECORD NUMBERS: DEC <input type="checkbox"/> OCT <input type="checkbox"/>	GAIN CONSTANT: 36 db	INPUT IMPEDANCE: 20000 ohms
	CONFIGURATION (MAG TAPE)		FIELD TRACE NOS.: 1-96		AUXILIARY DATA: SW SPS TB EM 10		
PARAMETER	RECORD LENGTH: 8 sec.	SAMPLE RATE: <input type="checkbox"/> 1 ms <input type="checkbox"/> 4 ms	GAIN MODE: <input checked="" type="checkbox"/> INITIAL <input type="checkbox"/> MANUAL	FILTERS: FREQ. 8 LO CUT 18 HI CUT 70		NOTCH FILTER: <input type="checkbox"/> IN <input type="checkbox"/> OUT	
DISPLAY	MODE: <input checked="" type="checkbox"/> AGC <input type="checkbox"/> FLOAT <input type="checkbox"/> AMPLIFIER <input type="checkbox"/> DIRECT	INITIAL GAIN: 0 db	TRIP SENS.: 0 db	POLARITY CONVENTION: Pos.		PRESSURE INCREASE ON GEOPHONE: <input type="checkbox"/> NEGATIVE <input type="checkbox"/> POSITIVE	
CFS I	TYPE: Stand Alone II		RECORD REJECTION:	NOISE REDUCTION:	NOISE THRESHOLD:	CORR. SCALING:	E.C.U. NORM/ALT SW.
SOURCE	PATTERN: Single Hole		NO. OF POSITIONS:	INLINE SPACING:	LATERAL SPACING:	STAGGER:	LENGTH: WIDTH: LATERAL OFFSET:
RECEIVER	TYPE: 20-D	PATTERN: In line	NO. OF ELEMENTS: 18	INLINE SPACING: 6'	LATERAL SPACING:	STAGGER:	LENGTH: WIDTH: LATERAL OFFSET:
SPREAD	CONNECTION: Series/Parallel	RESISTANCE: 560 ohms	STAGGER:	LENGTH: 110'	WIDTH:	LATERAL OFFSET:	DIRECTION OF PROGRESSION: N
	NO. OF GROUPS: 96	GROUP INTERVAL: 110'	SHOTPOINT INTERVAL: 080	FOLD: 6	LEADING GROUP: 96		
	OFFSET GROUP 1: 5225'	OFFSET GROUP 48: 55'	OFFSET GROUP 96: 55'	OFFSET GROUP 48/96: 5225'			

DIAGRAMS/MISC. INFORMATION:


SHOTPOINT	TR _____ TO _____		TR _____ TO _____		SHOT		SPREAD		REMARKS:	CORR. STACK			
	REEL NO.	REC.	REEL NO.	REC.	SIZE	DEPTH	NO.	OFFSET		DIR.	CDP SWITCH	LINE GROUPS	TR 1-48
1123	984112	173	17	22	110	105	1			5	117+1 - 128+8		
1124		175					2			13	118+1 - 124+8		
1125		176					3	35 S		21	119+1 - 130+8		
1126		177					4	35 S		29	120+1 - 131+8		
1127		178					5			37	121+1 - 132+8		
1128		179					6			45	122+1 - 133+8		
1129		180					7			5	123+1 - 134+8	2	Recorder @ SP 131+4-5
1130		181					8	35 E		13	124+1 - 135+8		
1131		182					9			21	125+1 - 136+8		
1132		183					10			29	126+1 - 137+8		
1133		184					11			37	127+1 - 138+8		
1134	984112	185					12			45	128+1 - 139+8		
1135	984113	187					13	35 S		5	129+1 - 140+8	3	Recorder @ SP 137+4-5
1136		188					14			13	130+1 - 141+8		
1137		189					15	35 E		21	131+1 - 142+8		
1138		190					16	30 N		29	132+1 - 143+8		
1139		191					17			37	133+1 - 144+8		
1140		192					18			45	134+1 - 145+8		
1141		193					19	30 E		5	135+1 - 146+8	4	Recorder @ SP 143+4-5
1142		194					20	35 NE		13	136+1 - 147+8		

(SEE DUMP) 189 shot record

Groups @ 137+8, 138+3, 139+4, 140+2, 3, 6 replanted
Occasional high wind gusts

LAND SEISMIC RECORDING LOG



CLIENT: Husky	PROSPECT: NPR-4	AREA: UMIAT	LINE NO: 720
PARTY NO: 1186	INST. ENG: R. Scheel		DATE: 4 DAY 27 80

SHOTPOINT	TR. to		TR. to		SHOT				SPREAD		REMARKS	CORR. STACK			
	REEL NO.	REC.	REEL NO.	REC.	SIZE	DEPTH	NO.	OFFSET	DIR.	CDP SWITCH		LINE GROUPS	TR 1-48	TR 49-96	TR 97-144
1467	196	196			110	105	21	146	W	21	137+1 - 148+8				
1468	196	196					29			29	138+1 - 149+8				
1469	197	197					37			37	139+1 - 150+8				
1470	198	198					45			45	140+1 - 151+8				
1471	199	199					5			5	141+1 - 152+8	5			
1472	200	200					13	40 E		13	142+1 - 153+8				
1473	201	201					21	30 S		21	143+1 - 154+8				
1474	202	202					29	25 E		29	144+1 - 155+8				
1475	203	203					37	50 E		37	145+1 - 156+8				
1476	204	204					45	26 S		45	146+1 - 157+8				
1477	205	205					5			5	147+1 - 158+8	6			
1478	206	206					13	35 E		13	148+1 - 159+8				
1479	207	207					21	35 E		21	149+1 - 160+8				
1480	208	208					29	30 E		29	150+1 - 161+8				
1481	209	209					37	46 E		37	151+1 - 162+8				
1482	210	210					45	40 E		45	152+1 - 163+8				
1483	211	211					5	40 E		5	153+1 - 164+8	7			
1484	212	212					13	40 E		13	154+1 - 165+8				
1485	213	213					21	50 NE		21	155+1 - 166+8				
1486	214	214					29			29	156+1 - 167+8				
1487	215	215					37			37	157+1 - 168+8				
1488	216	216					45			45	158+1 - 169+8				

SHORT RECORD (SEE DUMP)

Recorder @ 149+4-5

Recorder @ 155+4-5

F. NO. 9 NG; TR 94 dead for SP 157 (F. NO. 10)

Recorder @ 161+4-5

LAND SEISMIC RECORDING LOG

	CLIENT: <u>Husky</u>	PROSPECT: <u>NPR-4</u>	AREA: <u>UM1A7</u>	LINE NO: <u>720</u>	
PARTY NO: <u>1186</u>	INST ENG: <u>Streff</u>			DATE: <u>4 DAY 28 80</u>	

INSTRUMENT (9-TRACK)	<input checked="" type="checkbox"/> 1 SYSTEM <input checked="" type="checkbox"/> 2 SYSTEMS	<input type="checkbox"/> 1-24 & 25-48 <input type="checkbox"/> 1-48 & 49-96	TYPE: <input type="checkbox"/> DFS III <input type="checkbox"/> DFS IV	<input type="checkbox"/> DFS V <input type="checkbox"/> OTHER	<input checked="" type="checkbox"/> TRACK <input type="checkbox"/> 21 TRACK	FOPMAT: <u>B</u> SEG	<input type="checkbox"/> GAPPED <input type="checkbox"/> UNGAPPED	PACKING DENSITY: (LO) <input type="checkbox"/> 356 BPI <input type="checkbox"/> 800 BPI	(HI) <input type="checkbox"/> 712 BPI <input type="checkbox"/> 1400 BPI
NO. BYTES IN HEADER REC: <u>228</u>	NO. BYTES IN RECORD ID: <u>24</u>	NO. BYTES PER SCAN: <u>254</u>	RECORD NUMBERS: <input checked="" type="checkbox"/> DEC <input type="checkbox"/> OCT	GAIN CONSTANT: <u>36</u> db	INPUT IMPEDANCE: <u>20,000</u> ohms				

CONFIGURATION (MAG TAPE)	FIELD TRACE NOS.: <u>1-96</u>	AUXILIARY DATA: <u>TR 125 13 14 15</u>
PARAMETER	DATA CHANNEL NOS.: <u>5-100</u> (ON MAG TAPE)	AUXILIARY CHANNEL NOS.: <u>0 1 2 3 4</u>
DISPLAY	RECORD LENGTH: <u>8</u> sec	SAMPLE RATE: <input type="checkbox"/> 1 ms <input type="checkbox"/> 4 ms
CFS I	MODE: <input checked="" type="checkbox"/> AGC <input type="checkbox"/> FLOAT <input type="checkbox"/> AMPLIFIER <input type="checkbox"/> DIRECT	INITIAL GAIN: <u>0</u> db
	GATE LENGTH:	TRIP SENS: <u>0</u> db
		RECORD REJECTION:
		FILTERS: FREQ: <u>8</u> LO CUT: <u>18</u> HI CUT: <u>20</u> NOTCH: <input type="checkbox"/> IN <input type="checkbox"/> OUT
		POLARITY CONVENTION: <u>POS</u> PRESSURE INCREASE ON GEOPHONE: <input type="checkbox"/> NEGATIVE <input type="checkbox"/> POSITIVE
		NOISE REDUCTION: NOISE THRESHOLD: CORR SCALING: R.C.U. NORM/ALT SW

SOURCE	TYPE: <input type="checkbox"/> DYNAMITE <input type="checkbox"/> VIBROSEIS <input type="checkbox"/> OTHER	PATTERN: <u>Single Hole</u>	NO. OF POSITIONS:	INLINE SPACING:	LATERAL SPACING:	STAGGER:	LENGTH:	WIDTH:	LATERAL OFFSET:
RECEIVER	TYPE: <u>20-D</u>	PATTERN: <u>In line</u>	NO. OF ELEMENTS: <u>18</u>	INLINE SPACING: <u>6'</u>	LATERAL SPACING: <u>110'</u>	STAGGER:	LENGTH:	WIDTH:	LATERAL OFFSET:
SPREAD	CONNECTION: <u>Series/Parallel</u>	RESISTANCE: <u>560</u> ohms	STAGGER:	LENGTH:	WIDTH:	LATERAL OFFSET:			

SPREAD	NO. OF GROUPS: <u>96</u>	GROUP INTERVAL: <u>110'</u>	SHOTPOINT INTERVAL: <u>880'</u>	FOLD: <u>6</u>	DIRECTION OF PROGRESSION: <u>N</u>
	OFFSET GROUP 1: <u>5225'</u>	OFFSET GROUP <u>48</u> : <u>55'</u>	OFFSET GROUP <u>49</u> : <u>55'</u>	OFFSET GROUP <u>49/96</u> : <u>5225'</u>	LEADING GROUP: <u>96</u>

DIAGRAMS/MISC. INFORMATION:
 #218 - 227 tests
 #224 - test 70
 SP159 TR48 → SP165 TR49 SP171
 P ← → P → → P → → P → → TR96
 → → N

SHOTPOINT	TR 10		TR 10		SHOT		SPREAD		REMARKS	CORR STACK						
	REEL NO.	REC.	REEL NO.	REC.	SIZE	DEPTH	NO.	OFFSET		DIR	CDP SWITCH	LINE GROUPS	TR 1-48	TR 49-96		
165	984	113	230		110	105	1			5	159+1 - 17048	1				
166		231					2			13	160+1 - 17148					
167		232					3			21	161+1 - 17248					
168		233					4			29	162+1 - 17348					
169		234					5			37	163+1 - 17448					
170		235					6			45	164+1 - 17548					
171	984	114	237				7			5	165+1 - 17648	2				
172		238					8	175	S	13	166+1 - 17748					
173		239					9			21	167+1 - 17848					
174		240					10			29	168+1 - 17948					
175		241					11			37	169+1 - 18048					
176		242					12	200	S	45	170+1 - 18148					
177		243					13	320	N	5	171+1 - 18248	3				
178		244					14	215	W	5	172+1 - 18348					
179		245					15			21	173+1 - 18448					
180		247					16			29	174+1 - 18548					
181		248					17	170	N	37	175+1 - 18648					
182		249					18			45	176+1 - 18748					
183		250					19	20	E	5	177+1 - 18848	4				
184		251					110	105	20	13	178+1 - 18948					

LAND SEISMIC RECORDING LOG



CLIENT: **Husky**
PARTY NO: **1186**

PROSPECT: **NPR-A**

AREA: **UMIAT**

LINE NO: **720**

INST. ENG: **Staff**

DATE: **MO 4 DAY 28 YR 80**



SHOTPOINT	TR		TR		SHOT		SPREAD		REMARKS	CORR STACK					
	REEL NO.	REC.	REEL NO.	REC.	SIZE	DEPTH	NO.	OFFSET		DIR.	CDP SWITCH	LINE GROUPS	HT	REC.	HT
1185	984114	252			110	105	21			21	179+1 - 170+8				
1186		253					22			29	180+1 - 171+8				
1187		254					23	1515	NW	37	181+1 - 182+8				
1188		255					24	215	S	45	182+1 - 193+8				
1189		256					25			5	183+1 - 194+8	5	Recorder @ SP 191+4/15		
1190		257					26	110	N	13	184+1 - 195+8				
1191		258					27	171	N	21	185+1 - 196+8				
1192		259					28			29	186+1 - 197+8				
1193		260					29			37	187+1 - 198+8				
1194		261					30			45	188+1 - 199+8				
1195		262					31			5	189+1 - 200+8	6	Recorder @ SP-177+4/15		
1196		263					32			13	190+1 - 201+8				
1197		264					33			21	191+1 - 202+8				
1198		265					34			29	192+1 - 203+8				
1199		266					35			37	193+1 - 204+8				
1200		267					36			45	194+1 - 205+8				
1201		268					37			5	195+1 - 206+8	7	Recorder @ SP-203+4/15		
1202		269					38			13	196+1 - 207+8				
1203		270					39	1515	S	21	197+1 - 208+8				
1204		271					40	410	SE	37	198+1 - 209+8				
1205		272			190	100	41	350	N	37	199+1 - 210+8				
1206		273			190	100	42	350	S	45	200+1 - 211+8				
1207	984115	274					43	350	N	5	201+1 - 212+8	8	Recorder @ SP-209+4/15		
1208		275					44	550	SW	13	202+1 - 213+8				
1209		276					45			21	203+1 - 214+8				
1210		277					46			29	204+1 - 215+8				
1211		278					47			37	205+1 - T-8				
1212		279					48			45	206+1 - T-16				
1213		280					49			17	207+1 - T-24	9	Recorder @ SP-114		
1214		281					50			25	208+1 - T-32				
1215		282					51			33	209+1 - T-40				
1216	984115	283			110	105	52			41	210+1 - T-48				
											EOL				