

LAND SEISMIC RECORDING LOG


REC Hrs. 15.0

	CLIENT: Husky	PROSPECT: XXXXXXXXXX NPR-A	AREA: Larross Mtns	LINE NO: 728	
	PARTY NO: 1182	INST. ENG:		DATE: 3 DAY 14 80	

INSTRUMENT	<input checked="" type="checkbox"/> 1 SYSTEM <input type="checkbox"/> 2 SYSTEMS	<input type="checkbox"/> 1-24 & 25-48 <input checked="" type="checkbox"/> 1-48 & 49-96	ODDS EVENS <input checked="" type="checkbox"/> ODDS <input type="checkbox"/> EVENS	TYPE: <input type="checkbox"/> DFS III <input type="checkbox"/> DFS II <input type="checkbox"/> OTHER	<input checked="" type="checkbox"/> 9 TRACK <input type="checkbox"/> 2 TRACK	FORMAT: SEG B <input checked="" type="checkbox"/> GAPPED <input type="checkbox"/> UNGAPPED	PACKING DENSITY: (L) <input type="checkbox"/> 350 BPI (M) <input type="checkbox"/> 712 BPI <input type="checkbox"/> 800 BPI <input type="checkbox"/> 1400 BPI
(9-TRACK)	NO. BYTES IN HEADER REC: 228	NO. BYTES IN RECORD ID: 24	NO. BYTES PER SCAN: 254	RECORD NUMBERS: <input checked="" type="checkbox"/> DEC <input type="checkbox"/> OCT	GAIN CONSTANT: 36 db	INPUT IMPEDANCE: 2K ohms	(4) (5) (6) (7)

CONFIGURATION (MAG TAPE)	FIELD TRACE NOS.: 1-96 DATA CHANNEL NOS.: 5-100 [ON MAG TAPE]	AUXILIARY DATA: TW SPS 1/2 AUXILIARY CHANNEL NOS.: 0 1 2
PARAMETER	RECORD LENGTH: 8 sec. SAMPLE RATE: <input type="checkbox"/> 1 mc. <input type="checkbox"/> 4 ms. <input checked="" type="checkbox"/> 8 ms.	GAIN MODE: <input checked="" type="checkbox"/> INITIAL <input type="checkbox"/> MANUAL <input type="checkbox"/> OPERATE <input type="checkbox"/> TRIP SENS.
DISPLAY	MODE: <input type="checkbox"/> FLOAT <input type="checkbox"/> AMPLIFIER <input type="checkbox"/> DIRECT <input checked="" type="checkbox"/> AGC <input type="checkbox"/> DEFOAT	POLARITY CONVENTION: POS PRESSURE INCREASE ON GEOPHONE: <input type="checkbox"/> NEGATIVE <input checked="" type="checkbox"/> POSITIVE
CFS I	TYPE STACK: STAIR ALONG DEFS GATE LENGTH:	NOISE REDUCTION: <input type="checkbox"/> NOISE THRESHOLD: <input type="checkbox"/> CORR. SCALING: <input type="checkbox"/> E.C.U. NORM/ALT SW.

SOURCE	TYPE: <input checked="" type="checkbox"/> DYNAMIC <input type="checkbox"/> VIBROSEIS <input type="checkbox"/> OTHER	PATTERN: INLINE CHG/NOLE: 110 HOLE DEPTH: 90	NO. OF POSITIONS: 1 SWEEP POSITION:	INLINE SPACING: 6.5' SWEEP START: SWEEP END:	LATERAL SPACING: 6.5' SWEEP LENGTH: SWEEP FAPER:	STAGGER: 18 SWEEP LENGTH: SWEEP FAPER:	LENGTH: WIDTH: LATERAL OFFSET:
RECEIVER	TYPE: GSC-200 CONNECTION: S/P	PATTERN: INLINE RESISTANCE: 562 ohms	NO. OF ELEMENTS: 18 STAGGER:	INLINE SPACING: 6.5' LENGTH:	LATERAL SPACING: 5 WIDTH: LATERAL OFFSET:		
SPREAD	NO. OF GROUPS: 96 OFFSET GROUP 1: 5225	GROUP INTERVAL: 110' OFFSET GROUP 48: 55'	SHOTPOINT INTERVAL: 880' OFFSET GROUP 49: 55'	FOLD: 6 OFFSET GROUP 48/96: 5225'	DIRECTION OF PROGRESSION: S LEADING GROUP: 96		



SHOTPOINT	TR. 10		TR. 20		SHOT		SPREAD		REMARKS	CORR. STACK			
	REEL NO.	REC.	REEL NO.	REC.	SIZE	DEPTH	NO.	OFFSET		DIR.	CDP SWITCH	LINE GROUPS	TR 1-24
100	984067	587			110	90	1			1	94+1 - 105+8	TR 31 NO154	
101		590			110	90	9			9	95+1 - 106+9	TR 23,26 "	
102		591			110	90	17			17	96+1 - 107+10	TR 15,18 "	
103		592			110	90	25			25	97+1 - 108+11	TR 7 "	
104		593			110	90	33			33	98+1 - 109+12	TR 2 "	
105		594			110	90	41			41	99+1 - 110+13		
106		595			110	90	49			49	100+1 - 111+14		
107		596			110	90	9			9	101+1 - 112+15	TR 43 NO154	
108		597			110	90	17			17	102+1 - 113+16	TR 49 "	
109		598			110	90	25			25	103+1 - 114+17		
110		599			110	90	33			33	104+1 - 115+18		
111		600			110	90	41			41	105+1 - 116+19		
112		601			110	90	49			49	106+1 - 117+20	TR 42 NO154	

LAND SEISMIC RECORDING LOG

Rec 10 10

	CLIENT: HUSKY	PROSPECT: NPR-A	AREA: FORTRESS MTN	LINE NO.: 728
	PARTY NO: 1182	INST. ENG:		DATE: MO 3 DAY 16 YR 80


INSTRUMENT (9-TRACK)	<input checked="" type="checkbox"/> 1 SYSTEM <input checked="" type="checkbox"/> 2 SYSTEMS NO. BYTES IN HEADER REC: 224	<input type="checkbox"/> 1-24 & 25-48 <input type="checkbox"/> 1-48 & 49-96 NO. BYTES IN RECORD ID: 24	TYPE: <input type="checkbox"/> DFS III <input checked="" type="checkbox"/> DFS II <input type="checkbox"/> OTHER NO. BYTES PER SCAN: 254	<input checked="" type="checkbox"/> 9 TRACK <input checked="" type="checkbox"/> 21 TRACK RECORD NUMBERS: <input checked="" type="checkbox"/> DEC <input type="checkbox"/> OCT	FORMAT: SEG B <input checked="" type="checkbox"/> GAPPED <input type="checkbox"/> UNGAPPED PACKING DENSITY: (L) <input type="checkbox"/> 336 BPI (M) <input checked="" type="checkbox"/> 712 BPI (H) <input type="checkbox"/> 1800 BPI
CONFIGURATION (MAG TAPE)	FIELD TRACE NOS.: 1-96		AUXILIARY DATA: TW SPS 78		INPUT IMPEDANCE: ZK ohms
	DATA CHANNEL NOS.: 5-100		AUXILIARY CHANNEL NOS.: 0 1 2		

PARAMETER	RECORD LENGTH: 8 sec.	SAMPLE RATE: <input checked="" type="checkbox"/> 2 sec. <input type="checkbox"/> 4 sec.	GAIN MODE: <input checked="" type="checkbox"/> INITIAL <input type="checkbox"/> FINAL <input type="checkbox"/> MANUAL <input type="checkbox"/> OPERATE	FILTERS: FREQ. 8	LO CUT HZ SLOPE: 18
DISPLAY	MODE: <input type="checkbox"/> FLOAT <input type="checkbox"/> AMPLIFIER <input type="checkbox"/> DEFLOAT <input type="checkbox"/> DIRECT	INITIAL GAIN: db	TRIP SENS: db	POLARITY CONVENTION: <input type="checkbox"/> NEGATIVE <input checked="" type="checkbox"/> POSITIVE	HI CUT HZ SLOPE: 70
CFS I	TYPE STACK: STAND ALONE DFS	GATE LENGTH:	RECORD REJECTION:	NOISE REDUCTION:	NOISE THRESHOLD:

SOURCE	TYPE: <input checked="" type="checkbox"/> DYNAMITE <input type="checkbox"/> VIBROSEIS <input type="checkbox"/> OTHER	PATTERN: INLINE	NO. OF POSITIONS: 1	INLINE SPACING:	LATERAL SPACING:
	CHG7 HOLE: 110	HOLE DEPTH: 90	SWEEP POSITION:	SWEEP START:	SWEEP END:

RECEIVER	TYPE: GSC 200	PATTERN: INLINE	NO. OF ELEMENTS: 18	INLINE SPACING: 6.5'	LATERAL SPACING:
	CONNECTION: SERIES/PARALLEL	RESISTANCE: 562 ohms	STAGGER:	LENGTH:	WIDTH:

SPREAD	NO. OF GROUPS: 96	GROUP INTERVAL: 110'	SHOTPOINT INTERVAL: 880'	FOLD: 6	DIRECTION OF PROGRESSION: S
	OFFSET GROUP 1: 5225'	OFFSET GROUP 49: 55'	OFFSET GROUP 49: 55'	OFFSET GROUP 48/96: 5225'	LEADING GROUP: 96



SHOTPOINT	TR. TO		TR. TO		SHOT			DIR	CDF SWITCH	LINE GROUPS	REMARKS	CORR. STACK				
	REEL NO	REC.	REEL NO	REC.	SIZE	DEPTH	NO.					OFFSET	TR 1-24	TR 25-48	TR 49-72	TR 73-96
113	981067	624			110	90	1		9	107+1 - 118+8	115	6				
114		625			110	90	2		17	108+1 - 119+8						
115		626			110	90	3		25	109+1 - 120+8						
116		627			110	90	4		33	110+1 - 121+8						
117		628			110	90	5		41	111+1 - 122+8						
118		629			110	90	6		49	112+1 - 123+8						
119		631			110	90	7		9	113+1 - 124+8	121					
120		632			110	90	8		17	114+1 - 125+8						
121		633			110	90	9		25	115+1 - 126+8						
122		634			110	90	10		33	116+1 - 127+8						
123		635			110	90	11		41	117+1 - 128+8						
124		636			110	90	12		49	118+1 - 129+8						
125		637			110	90	13		9	119+1 - 130+8	127					
126		638			110	90	14		17	120+1 - 131+8						
127		639			110	90	15		25	121+1 - 132+8						
128		640			110	90	16		33	122+1 - 133+8						
129		641			110	90	17		41	123+1 - 134+8						
130		642			110	90	18		49	124+1 - 135+8						
131		643			110	90	19		9	125+1 - 136+8	135					
132		644			110	90	20		17	126+1 - 137+8						

#+90 dead

~~TR 40 NOISE (SP, ST)~~

LAND SEISMIC RECORDING LOG

PAGE 1 of 1

	CLIENT: Husky		PROSPECT: NPR-A		AREA: FORTRESS MTN PLATE AREA		LINE NO: 728									
	PARTY NO: 1182		INST. ENG: TORGERSON				DATE: MO 3 DAY 17 YE 80									
INSTRUMENT (9-TRACK)	<input checked="" type="checkbox"/> 1 SYSTEM <input type="checkbox"/> 2 SYSTEMS		<input checked="" type="checkbox"/> 1-24 & 25-48 <input type="checkbox"/> 1-48 & 49-96		TYPE: <input type="checkbox"/> DFS III <input type="checkbox"/> DFS III <input type="checkbox"/> OTHER		<input checked="" type="checkbox"/> 9 TRACK <input type="checkbox"/> 21 TRACK		FORMAT: B		<input checked="" type="checkbox"/> GAPPED <input type="checkbox"/> UNGAPPED		PACKING DENSITY: (L) <input type="checkbox"/> 356 BPI (M) <input type="checkbox"/> 712 BPI			
	NO. BYTES IN HEADER REC: 878		NO. BYTES IN RECORD ID: 24		NO. BYTES PER SCAN: 256		RECORD NUMBERS: <input checked="" type="checkbox"/> DEC. <input type="checkbox"/> OCT.		GAIN CONSTANT: 36 db		INPUT IMPEDANCE: 2000 ohms					
CONFIGURATION (MAG TAPE)	FIELD TRACE NOS.: 1-96				AUXILIARY DATA: FW SPS (3) FB (4) (5) (6)											
	DATA CHANNEL NOS.: 5-106 (ON MAG TAPE)				AUXILIARY CHANNEL NOS.: 0 1 2 3 4											
PARAMETER	RECORD LENGTH: Var (S) sec.		SAMPLE RATE: <input type="checkbox"/> 1 ms <input type="checkbox"/> 4 ms <input checked="" type="checkbox"/> 8 ms <input type="checkbox"/> 16 ms		GAIN MODE: <input type="checkbox"/> INITIAL <input type="checkbox"/> MANUAL <input checked="" type="checkbox"/> TRIP <input type="checkbox"/> FINAL <input type="checkbox"/> OPERATE		FILTERS: FREQ. 8 LO CUT HZ SLOPE 18		HI CUT HZ SLOPE 26		NOTCH FILTER: <input type="checkbox"/> IN <input type="checkbox"/> OUT					
DISPLAY	MODE: <input type="checkbox"/> FLOAT <input type="checkbox"/> AMPLIFIER <input checked="" type="checkbox"/> LOG <input type="checkbox"/> DEFLOAT <input type="checkbox"/> DIRECT		INITIAL GAIN: Var db		TRIP SENS: Var db		POLARITY CONVENTION: POS		PRESSURE INCREASE ON GEOPHONE: <input type="checkbox"/> NEGATIVE <input checked="" type="checkbox"/> POSITIVE		NUMBERS ON MAG TAPE: <input type="checkbox"/> DOWNBREAK <input type="checkbox"/> UPBREAK		ON DISPLAY			
CFS I	TYPE STACK:		GATE LENGTH:		RECORD REJECTION:		NOISE REDUCTION:		NOISE THRESHOLD:		CORR SCALING:		R.C.U. NORM/ALT SW.			
SOURCE	TYPE: <input checked="" type="checkbox"/> DYNAMITE <input type="checkbox"/> VIBROSEIS <input type="checkbox"/> OTHER		PATTERN: Inline		NO. OF POSITIONS:		INLINE SPACING:		LATERAL SPACING:		STAGGER:		LENGTH:		WIDTH:	
	CHG/ HOLE: 110		HOLE DEPTH: 105		SWEEP POSITION:		SWEEP START:		SWEEP END:		SWEEP LENGTH:		SWEEP TAPER:		PHASE COMP.	
RECEIVER	TYPE: GSC-700		PATTERN: Inline		NO. OF ELEMENTS: 18		INLINE SPACING: 6.5		LATERAL SPACING:		STAGGER:		LENGTH: 110'		WIDTH:	
	CONNECTION: SER-PAR		RESISTANCE:		STAGGER:		LENGTH:		FOLD: 6		DIRECTION OF PROGRESSION: N → S		LEADING GROUP: 96			
SPREAD	NO. OF GROUPS: 96		GROUP INTERVAL: 110		SHOTPOINT INTERVAL: 880		FOLD: 6		DIRECTION OF PROGRESSION: N → S		LEADING GROUP: 96					
	OFFSET GROUP 1: 5225		OFFSET GROUP 44: 55		OFFSET GROUP 47: 55		OFFSET GROUP 49/96: 5225									

DIAGRAMS/MISC. INFORMATION:



SHOTPOINT	TR 10		TR 10		SHOT		SPREAD		REMARKS	CORR. STACK		
	REEL NO.	REC.	REEL NO.	REC.	SIZE	DEPTH	NO.	OFFSET		CDP SWITCH	LINE GROUPS	TR 10
137	981068	660			110	90	1		9	131+1 - 142+8	139	
138		667			110	90	2		17	132+1 - 143+8		
139		668			110	90	3		25	133+1 - 144+8		
140		669			110	90	4		33	134+1 - 145+8		
141		670			110	90	5		41	135+1 - 146+8		
142		671			110	90	6		13	136+1 - 147+8		
143		672			110	90	7		21	137+1 - 148+8		
144		673			110	90	8		29	138+1 - 149+8		
145		674			110	90	9		37	139+1 - 150+8		
146		675			110	90	10		45	140+1 - 151+8		
147		676			110	90	11		5	141+1 - 152+8	149+4	
148		677			110	90	12		13	142+1 - 153+8		
149		678			110	90	13		21	143+1 - 154+8		
150		680			110	90	14		29	144+1 - 155+8		
151		681			110	90	15		37	145+1 - 156+8		
152		682			110	90	16		45	146+1 - 157+8		
153		683			110	90	17		5	147+1 - 158+8	55+4	
154		684			110	90	18		13	148+1 - 159+8		
155		685			110	90	19		21	149+1 - 160+8		
156		686			110	90	20		29	150+1 - 161+8		

LAND SEISMIC RECORDING LOG



CLIENT: Husky	PROSPECT: NPR-A	AREA: FORTRESS MTN PLAT AREA	LINE NO. 728
PARTY NO. 1K2	INST. ENG. Torgerson		DATE: 3 DAY 17 YR 80

SHOTPOINT	TR NO		TR NO		SHOT				DIR	COP SWITCH	SPREAD LINE GROUPS	REMARKS	CORR. STACK			
	REEL NO.	REC.	REEL NO.	REC.	SIZE	DEPTH	NO.	OFFSET					TR 1-48		TR 49-96	
													HT	REC	HT	REC
157	981068	687			11.0	90	21			37	151+1 - 162+8	155+4 TR 92 NOISY				
158		688			11.0	90	22			45	152+1 - 163+8	TR 84, 88 NOISY				
159		689			11.0	90	23			17	153+1 - 164+8	160 Omit Rec # 689 TR 76, 82 NOISY				
160		691			11.0	90	24			25	154+1 - 165+8	TR 68, 74 NOISY				
161		692			11.0	90	25			33	155+1 - 166+8	TR 54 "				
162		693			11.0	90	26			41	156+1 - 167+8	TR 58 "				
163		694			11.0	90	27			1	157+1 - 168+8	166				
164		695			11.0	90	28			9	158+1 - 169+8	TR 34, 38 NOISY + 97.				
165	981069	696			11.0	90	29			17	159+1 - 170+8	TR 72, 86 NOISY				
166	981069	698			11.0	90	30			25	160+1 - 171+8	REC # 697 Dummy Rec TR 26, 69, 76 NOISY				
167		699			11.0	90	31			33	161+1 - 172+8	TR 18, 24, 30, 36 NOISY (92 REV. 96 DEAD)				
168		700			11.0	90	32			41	162+1 - 173+8	TR 62 NOISY (84 REV.)				
169		701			11.0	90	33			49	163+1 - 174+8	TR 22, 27, NOISY 76 REV.				
170		702			11.0	90	34			9	164+1 - 175+8	172 TR 85 PHASE? 68 "				
171		703			11.0	90	35			17	165+1 - 176+8	177 " 83 (60) "				
172		704			11.0	90	36			25	166+1 - 177+8	172+4 P. WIPED - GK TR 18, 24, 30, 36 REV				
173		705			11.0	90	37	220 N	31	31	167+1 - 178+8	Line offset 920' NORTH TR 18, 24, 30, 36 REV				
174		706			11.0	90	38			41	168+1 - 179+8	TR 42, 48 NOISY				
175		707			11.0	90	39			49	169+1 - 180+8	TR 84, 85 "				

LAND SEISMIC RECORDING LOG

Page 1 of 1

	CLIENT: Husky	PROSPECT: NPR-A	AREA: Fortress with PLAT A-9	LINE NO: 728					
	PARTY NO: 1187	INST. ENG: TORJERSON		DATE: 3 DAY 18 YR 80					
INSTRUMENT (9-TRACK)	<input checked="" type="checkbox"/> 1 SYSTEM <input type="checkbox"/> 2 SYSTEMS	<input type="checkbox"/> 1-24 & 25-48 <input checked="" type="checkbox"/> 1-48 & 49-96	ODDS EVENS	TYPE: <input type="checkbox"/> DFS III <input type="checkbox"/> DFS III <input type="checkbox"/> OTHER	<input checked="" type="checkbox"/> 1 TRACK <input type="checkbox"/> 2 TRACK	FORMAT: B	<input checked="" type="checkbox"/> GAPPED <input type="checkbox"/> UNGAPPED	PACKING DENSITY: (L) <input type="checkbox"/> 356 BPI (H) <input type="checkbox"/> 712 BPI <input type="checkbox"/> 800 BPI <input type="checkbox"/> 1600 BPI	
	NO. BYTES IN HEADER REC: 228	NO. BYTES IN RECORD ID: 24	NO. BYTES PER SCAN: 256	RECORD NUMBERS: <input type="checkbox"/> DEC. <input type="checkbox"/> OCT.	GAIN CONSTANT: 46	INPUT IMPEDANCE: ohms			
CONFIGURATION (MAG TAPE)	FIELD TRACE NOS.: 1-96			AUXILIARY DATA: 11 TW (2) 13 14 15 16 17			AUXILIARY CHANNEL NOS.: 6 1 2 3 4		
	DATA CHANNEL NOS.: 5-100 (ON MAG TAPE)			FILTERS: 8 LO CUT 18 HZ SLOPE 18 FREQ. 128 HI CUT 70 HZ SLOPE 70			NOTCH FILTER: <input type="checkbox"/> IN <input type="checkbox"/> OUT		
PARAMETER	RECORD LENGTH: VAR (8) sec.	SAMPLE RATE: <input type="checkbox"/> 1 ms. <input type="checkbox"/> 4 ms. <input checked="" type="checkbox"/> 2 ms.	GAIN MODE: <input type="checkbox"/> INITIAL <input type="checkbox"/> MANUAL <input checked="" type="checkbox"/> OPERATE	POLARITY CONVENTION: POS			PRESSURE INCREASE ON GEOPHONE: <input type="checkbox"/> NEGATIVE <input checked="" type="checkbox"/> POSITIVE		
DISPLAY	MODE: <input checked="" type="checkbox"/> MAGC <input type="checkbox"/> FLOAT <input type="checkbox"/> AMPLIFIER <input type="checkbox"/> DE FLOAT <input type="checkbox"/> DIRECT	INITIAL GAIN: VAR db	TRIP SENS: VAR db	NOISE REDUCTION: <input type="checkbox"/> NOISE THRESHOLD: <input type="checkbox"/> COR. SCALING: <input type="checkbox"/>			R.C.U. NORM/ALT SW. <input type="checkbox"/>		
CFS I	TYPE STACK:	GATE LENGTH:	RECORD REJECTION:						
SOURCE	TYPE: <input checked="" type="checkbox"/> DYNAMITE <input type="checkbox"/> VIBROSEIS <input type="checkbox"/> OTHER	PATTERN: Inline	NO. OF POSITIONS:	INLINE SPACING:	LATERAL SPACING:	STAGGER:	LENGTH:	WIDTH:	LATERAL OFFSET:
	CHG/ HOLE: 10	HOLE DEPTH: 105	SWEEP POSITION:	SWEEP START:	SWEEP END:	SWEEP LENGTH:	SWEEP TAPER:	PHASE COMP.	
RECEIVER	TYPE: GSC-200	PATTERN: Inline	NO. OF ELEMENTS: K	INLINE SPACING: 6.5	LATERAL SPACING:	STAGGER:	LENGTH: 116	WIDTH:	LATERAL OFFSET:
	CONNECTION: SQR PHR	RESISTANCE: ohms	STAGGER:	LENGTH: 116	WIDTH:	LATERAL OFFSET:			
SPREAD	NO. OF GROUPS:	GROUP INTERVAL: 110'	SHOTPOINT INTERVAL: 540'	FOLD: 6	DIRECTION OF PROGRESSION: N → S				
	OFFSET GROUP 1: 5225	OFFSET GROUP K : 55	OFFSET GROUP 41 : 55	OFFSET GROUP 116 : 5225	LEADING GROUP: 96				



SHOTPOINT	TR 1		TR 2		SHOT		SPREAD		REMARKS	CORR. STACK					
	REEL NO.	REC.	REEL NO.	REC.	SIZE	DEPTH	NO.	OFFSET		DIR.	CDP SWITCH	LINE GROUPS	TR 1	TR 2	TR 3
176	1610	167	744		110	90	1			9	170+1 - 181+8				
177		745			110	90	2			17	171+1 - 182+8				
178		746			110	90	3			25	172+1 - 183+8				
179		747			110	90	4			33	173+1 - 184+8				
180		748			110	90	5			41	174+1 - 185+8				
181		749			110	90	6			1	175+1 - 186+8				
182		750			110	90	7			9	176+1 - 187+8				
183		751			110	90	8			17	177+1 - 188+8				
184		752			110	90	9			25	178+1 - 189+8				
185		753			110	90	10			33	179+1 - 190+8				
186		754			110	90	11			41	180+1 - 191+8				
187		755			110	90	12			1	181+1 - 192+8				
188		756			110	90	13			9	182+1 - 193+8				
189		757			110	90	14			17	183+1 - 194+8				
190		758			110	90	15			25	184+1 - 195+8				
191		759			110	90	16			33	185+1 - 196+8				
192		760			110	90	17			41	186+1 - 197+8				
193		761			110	90	18			49	187+1 - 198+8				

EOL