

LAND SEISMIC RECORDING LOG

KBC Hours 12.2 HRS

Page 1 of 1





CLIENT: Husky	PROSPECT: NPR-A	AREA: FORTRESS MTN PLAY AREA	LINE NO: 736
PARTY NO: 1182	INST. ENG: D TORGERSON		DATE: MO 2 DAY 27 YR 80

INSTRUMENT (9-TRACK)	<input checked="" type="checkbox"/> 1 SYSTEM <input type="checkbox"/> 2 SYSTEMS	<input type="checkbox"/> 1-24 & 25-48 <input checked="" type="checkbox"/> 1-48 & 49-96	ODDS EVENS <input checked="" type="checkbox"/> ODDS <input type="checkbox"/> EVENS	TYPE: <input type="checkbox"/> DFS III <input type="checkbox"/> DFS II <input type="checkbox"/> OTHER	<input checked="" type="checkbox"/> 9 TRACK <input type="checkbox"/> 21 TRACK	FOPMAT: B SEG:	<input type="checkbox"/> GAPPED <input type="checkbox"/> UNGAPPED	PACKING DENSITY: (L) <input type="checkbox"/> 356 BPI <input type="checkbox"/> 800 BPI	(H) <input type="checkbox"/> 712 BPI <input type="checkbox"/> 1400 BPI
	NO. BYTES IN HEADER REC: 228	NO. BYTES IN RECORD ID: 24	NO. BYTES PER SCAN: 256	RECORD NUMBERS: RDEC <input type="checkbox"/> OCT	GAIN CONSTANT: 36 db	INPUT IMPEDANCE: 2000 ohms			
CONFIGURATION (MAG TAPE)	FIELD TRACE NOS.: 1-96				AUXILIARY DATA: (1) TW (2) TB (3) SPS (4) 0 (5) 0 (6) 407 (7) 474				
	DATA CHANNEL NOS.: 5-100 (ON MAG TAPE)				AUXILIARY CHANNEL NOS.: 0 1 2 3 4				
PARAMETER	RECORD LENGTH: VARIABLE (9) sec	SAMPLE RATE: <input type="checkbox"/> 1 ms. <input type="checkbox"/> 4 ms. <input checked="" type="checkbox"/> 2 ms.	GAIN MODE: <input type="checkbox"/> INITIAL <input type="checkbox"/> MANUAL <input checked="" type="checkbox"/> OPERATE	FILTERS: <input type="checkbox"/> LO CUT <input type="checkbox"/> HI CUT	FREQ: 8 HZ SLOPE 18		FREQ: 128 HZ SLOPE 72		NOTCH FILTER: <input type="checkbox"/> IN <input checked="" type="checkbox"/> OUT
DISPLAY	MODE: <input checked="" type="checkbox"/> MAG <input type="checkbox"/> FLOAT <input type="checkbox"/> AMPLIFIER <input type="checkbox"/> DIRECT	INITIAL GAIN: VAR db	TRIP SENS: VAR db	POLARITY CONVENTION: <input type="checkbox"/> PRESSURE INCREASE ON GEOPHONE <input type="checkbox"/> NEGATIVE <input checked="" type="checkbox"/> POSITIVE		NUMBERS ON MAG TAPE <input type="checkbox"/> DOWNBREAK <input type="checkbox"/> UPBREAK		ON DISPLAY	
CFS I	TYPE STACK:	GATE LENGTH:	RECORD REJECTION:	NOISE REDUCTION:	NOISE THRESHOLD:	CORR. SCALING:	R.C.U. NORM./ALT SW.		
SOURCE	TYPE: <input checked="" type="checkbox"/> DYNAMITE <input type="checkbox"/> VIBROSEIS <input type="checkbox"/> OTHER	PATTERN: Inline	NO. OF POSITIONS:	INLINE SPACING:	LATERAL SPACING:	STAGGER:	LENGTH:	WIDTH:	LATERAL OFFSET:
		CHG/ HOLE: 110	HOLE DEPTH: 105	SWEEP POSITION:	SWEEP START:	SWEEP END:	SWEEP LENGTH:	SWEEP TAPER:	PHASE COMP:
RECEIVER	TYPE: GSC-200	PATTERN: INLINE	NO. OF ELEMENTS: 18	INLINE SPACING: 6.5'	LATERAL SPACING:	STAGGER:	LENGTH: 110'	WIDTH:	LATERAL OFFSET:
	CONNECTION: SER-PAR	RESISTANCE:	STAGGER:	LENGTH: 110'	WIDTH:	LATERAL OFFSET:			
SPREAD	NO. OF GROUPS: 96	GROUP INTERVAL: 110'	SHOTPOINT INTERVAL: 880	FOLD: 6	DIRECTION OF PROGRESSION: NORTH				
	OFFSET GROUP 1: 5170	OFFSET GROUP 2: 55'	OFFSET GROUP 3: 55'	OFFSET GROUP 4: 5170	LEADING GROUP: 96				

DIAGRAMS/MISC. INFORMATION:
 No gap x 48 x 17 96 DAILY Tests FN 628 - 643
T94H TK18 200 100+ 105+
TTB FN 644-646

SHOTPOINT	TR 1 to 36		TR 37 to 72		SHOT		DIR.	COP SWITCH	SPREAD	REMARKS:	CORR STACK			
	REEL NO.	REC.	REEL NO.	REC.	SIZE	DEPTH					NO.	OFFSET	TR 1-48	TR 49-96
100	98104H	647			110	90	1		T94+1 - 105+8	109				
101		648			110	90	2		T95+1 - 106+8					
102		649			110	90	3	1150 N	T96+1 - 107+8		INLINE offset			
103		650			110	90	4	1110 N	T97+1 - 108+8		Inline offset			
104		651			110	90	5		T98+1 - 109+8					
105		652			120	90	6		T99+1 - 110+8					
106		653			110	90	7		100+1 - 111+8					
107		654			110	90	8		101+1 - 112+8	109				
108		655			110	90	9		102+1 - 113+8					
109		656			110	90	10		103+1 - 114+8					
110		657			110	90	11		104+1 - 115+8					
111		658			110	90	12		105+1 - 116+8					
112		659			110	90	13		106+1 - 117+8	115				
113		660			110	90	14		107+1 - 118+8					
114	78104H	661			110	90	15		108+1 - 119+8					
115	88104H	663			110	90	16		109+1 - 120+8		FN 662 dummy Rec			
116		664			110	90	17		110+1 - 121+8					
117		665			110	90	18		111+1 - 122+8					
118		666			110	90	19	700 S	112+1 - 123+8	124	Inline offset 770 south			
119		667			110	90	20		113+1 - 124+8					

LAND SEISMIC RECORDING LOG

	CLIENT: Husky	PROSPECT: NPR-A	AREA: FORTRESS MTN PLATEAU AREA	LINE NO: 736					
	PARTY NO: 1182	INST. ENG: D TORGERSON		DATE: NO 2 DAY 24 YR 80					
INSTRUMENT (9-TRACK)	<input checked="" type="checkbox"/> 1 SYSTEM <input type="checkbox"/> 2 SYSTEMS	<input type="checkbox"/> 1-24 & 25-48 <input checked="" type="checkbox"/> 1-48 & 49-96	TYPE: <input type="checkbox"/> DFS III <input type="checkbox"/> DFS III <input checked="" type="checkbox"/> OTHER	<input checked="" type="checkbox"/> TRACK <input type="checkbox"/> 21 TRACK	FORMAT: B	<input checked="" type="checkbox"/> GAPPED <input type="checkbox"/> UNGAPPED	PACKING DENSITY: (L) <input type="checkbox"/> 350 BPI <input type="checkbox"/> 500 BPI	(H) <input type="checkbox"/> 712 BPI <input type="checkbox"/> 1600 BPI	
	NO. BYTES IN HEADER REC: 278	NO. BYTES IN RECORD ID: 24	NO. BYTES PER SCAN: 254	RECORD NUMBERS: <input checked="" type="checkbox"/> DEC. <input type="checkbox"/> OCT	GAIN CONSTANT: 36 db	INPUT IMPEDANCE: 2000 ohms			
CONFIGURATION (MAG TAPE)	FIELD TRACE NOS.: 1-96			AUXILIARY DATA: (1) 74 (2) 703 (3) 283 (4) 2 (5) 8 (6) 44 (7) 171					
	DATA CHANNEL NOS.: 5-100 (ON MAG TAPE)			AUXILIARY CHANNEL NOS.: 6 1 2 3 4					
PARAMETER	RECORD LENGTH: VARIABLE (8) sec	SAMPLE RATE: <input type="checkbox"/> 1 ms. <input type="checkbox"/> 4 ms. <input checked="" type="checkbox"/> 2 ms.	GAIN MODE: <input type="checkbox"/> INITIAL <input type="checkbox"/> MANUAL <input checked="" type="checkbox"/> OPERATE	FILTERS: FREQ. 5 LO CUT HZ SLOPE 18 HI CUT HZ SLOPE 125 NOTCH FILTER: <input type="checkbox"/> IN <input checked="" type="checkbox"/> OUT					
DISPLAY	MODE: <input checked="" type="checkbox"/> MAGC <input type="checkbox"/> FLOAT <input type="checkbox"/> AMPLIFIER <input type="checkbox"/> DIRECT	INITIAL GAIN: VARIABLE db	TRIP SENS: VARIABLE db	POLARITY CONVENTION: P2S PRESSURE INCREASE ON GEOPHONE: <input type="checkbox"/> NEGATIVE <input checked="" type="checkbox"/> POSITIVE	NUMBERS ON MAG TAPE: <input type="checkbox"/> DOWNBREAK <input type="checkbox"/> UPBREAK		ON DISPLAY		
CFS I	TYPE STACK: DPS I STAIR	GATE: ALWAYS	RECORD REJECTION:	NOISE REDUCTION:	NOISE THRESHOLD:	CORR. SCALING:	R.C.U. NORM./ALT SW.		
SOURCE	TYPE: <input checked="" type="checkbox"/> DYNAMITE <input type="checkbox"/> VIBROSEIS <input type="checkbox"/> OTHER	PATTERN: Inline	NO. OF POSITIONS:	INLINE SPACING:	LATERAL SPACING:	STAGGER:	LENGTH:	WIDTH:	LATERAL OFFSET:
		CHG/HOLE:	HOLE DEPTH:	SWEEP POSITION:	SWEEP START:	SWEEP END:	SWEEP LENGTH:	SWEEP TAPER:	PHASE COMP:
RECEIVER	TYPE: GSC-200	PATTERN: INLINE	NO. OF ELEMENTS: 18	INLINE SPACING: 65	LATERAL SPACING:	STAGGER:	LENGTH: 110	WIDTH:	LATERAL OFFSET:
	CONNECTION: SER-PAR	RESISTANCE: ohms							
SPREAD	NO. OF GROUPS: 96	GROUP INTERVAL: 110	SHOTPOINT INTERVAL: 880	FOLD: 6	DIRECTION OF PROGRESSION: NORTH				
	OFFSET GROUP 1: 5170	OFFSET GROUP 48: 55	OFFSET GROUP 96: 55	OFFSET GROUP 96: 5170	LEADING GROUP: 96				

DIAGRAMS/MISC. INFORMATION:

481045 DAILY Tests FN 680 - 695
TTB FN 696

SHOTPOINT	TR. 10		TR. 10		SHOT			DIR.	CDP SWITCH	SPREAD	REMARKS	CORR STACK			
	REEL NO.	REC.	REEL NO.	REC.	SIZE	DEPTH	NO. OFFSET					TR 1-41	REC	TR 42-96	REC
130	781046	697	22	23	110	90	1		1	124+1 - 135+8	133				
131		698			110	90	2		9	125+1 - 136+8					
132		699			110	90	3		17	126+1 - 137+8					
133		700			110	90	4		25	127+1 - 138+8					
134		701			110	90	5		33	128+1 - 139+8					
135		702			110	90	6		41	129+1 - 140+8					
136		703			110	90	7		49	130+1 - 141+8					
137		704			110	90	8		7	131+1 - 142+8	139				
138		705			110	90	9		17	132+1 - 143+8					
139		706			110	90	10		25	133+1 - 144+8					
140		707			110	90	11		33	134+1 - 145+8					
141		708			110	90	12		41	135+1 - 146+8					
142		709			110	90	13		49	136+1 - 147+8					
143		710			110	90	14	20.0 W	9	137+1 - 148+8	145				
144		711			110	90	15		17	138+1 - 149+8					
145		712			110	90	16		25	139+1 - 150+8					
146	981046	713			110	90	17		33	140+1 - 151+8					
147	981047	714			110	90	18		41	141+1 - 152+8					
148		715			110	90	19		49	142+1 - 153+8	151				
149		716			110	90	20		9	143+1 - 154+8					

LAND SEISMIC RECORDING LOG



CLIENT: **Husky**
 PARTY NO: **1182**

PROSPECT: **NPR-A**
 INST. ENG: **D. TARGERSAIX**



AREA: **FORTRESS Mtn PLATE AREA**

LINE NO: **736**
 DATE: **7 28 80**

SHOTPOINT	TR. No		TR. No		SHOT			CDP SWITCH	SPREAD	REMARKS	CORR. STACK			
	REEL NO.	REC.	REEL NO.	REC.	SIZE	DEPTH	NO.				LINE GROUPS	IN 1-48	IN 25-96	REC.
150	1182	727			110	90	27	17	1441 - 155+8	151				
151		727			110	90	27	25	1451 - 156+8					
152		728			110	90	27	33	1461 - 157+8					
153		728			110	90	27	41	1471 - 158+8					
154		729			110	90	25	1	1481 - 159+8	157				
155		727			110	90	26	9	1491 - 160+8		LONGER offset			
156		728			110	90	27	17	1501 - 161+8					
157		729			110	90	28	25	1511 - 162+8					
158		730			110	90	29	33	1521 - 163+8					
159		731			110	90	30	41	1531 - 164+8					
160		732			110	90	31	49	1541 - 165+8					

LAND SEISMIC RECORDING LOG

PAGE 1 OF 1


	CLIENT: Husky	PROSPECT: NPR-A	AREA: FOOTRESS Mtn PLAY AREA	LINE NO: 736	
PARTY NO: 1182		INST. ENG: D. TARGERSON		DATE: 2 29 80	

INSTRUMENT	<input checked="" type="checkbox"/> 1 SYSTEM <input type="checkbox"/> 2 SYSTEMS	<input type="checkbox"/> 1-24 & 25-48 <input type="checkbox"/> 41-48 & 49-96	ODDS EVENS	TYPE: <input type="checkbox"/> DFS I <input type="checkbox"/> DFS II <input checked="" type="checkbox"/> DFS III <input type="checkbox"/> OTHER	9 TRACK 21 TRACK	FORMAT: B SEG	GAPPED UNGAPPED	PACKING DENSITY: (L) <input type="checkbox"/> 356 BPI <input type="checkbox"/> 800 BPI	(M) <input type="checkbox"/> 712 BPI <input type="checkbox"/> 1800 BPI	
(9-TRACK)	NO. BYTES IN HEADER REC: 278	NO. BYTES IN RECORD ID: 24	NO. BYTES PER SCAN: 257	RECORD NUMBERS: <input checked="" type="checkbox"/> DEC. <input type="checkbox"/> OCT.	GAIN CONSTANT: 36 db	INPUT IMPEDANCE: 2000 ohms				

CONFIGURATION (MAG TAPE)	FIELD TRACE NOS.: 1-96	DATA CHANNEL NOS.: 5-100 (ON MAG TAPE)	AUXILIARY DATA: 111 121 131 141 151 161
PARAMETER	RECORD LENGTH: VARIABLE (5) sec.	SAMPLE RATE: <input checked="" type="checkbox"/> 1 ms. <input type="checkbox"/> 4 ms.	GAIN MODE: <input type="checkbox"/> INITIAL <input type="checkbox"/> MANUAL <input type="checkbox"/> OPERATE <input checked="" type="checkbox"/> STEP <input type="checkbox"/> FINAL
DISPLAY	MODE: <input checked="" type="checkbox"/> MAGC <input type="checkbox"/> FLOAT <input type="checkbox"/> AMPLIFIER <input type="checkbox"/> DEFLOAT <input type="checkbox"/> DIRECT	INITIAL GAIN: 60 db	TRIP SENS.: 100 db
CFS I	TYPE STACK:	GATE LENGTH:	RECORD REJECTION:

SOURCE	TYPE: <input checked="" type="checkbox"/> DYNAMITE <input type="checkbox"/> VIBROSEIS <input type="checkbox"/> OTHER	PATTERN: Inline	NO. OF POSITIONS:	INLINE SPACING:	LATERAL SPACING:	STAGGER:	LENGTH:	WIDTH:	LATERAL OFFSET:
RECEIVER	TYPE: CSG-700	PATTERN: Inline	NO. OF ELEMENTS: 18	INLINE SPACING: 6.5	LATERAL SPACING: 110	STAGGER:	LENGTH:	WIDTH:	LATERAL OFFSET:



SPREAD	NO. OF GROUPS: 96	GROUP INTERVAL: 110'	SHOTPOINT INTERVAL: 88'	FOLD: 6	DIRECTION OF PROGRESSION: NORTH
	OFFSET GROUP 1: 5170	OFFSET GROUP 2: 55	OFFSET GROUP 3: 55'	OFFSET GROUP 4: 5170	LEADING GROUP: 96



SHOTPOINT	TR 1		TR 2		SHOT		DIR	CDP SWITCH	SPREAD	REMARKS	CORR STACK			
	REEL NO.	REC.	REEL NO.	REC.	SIZE	DEPTH					NO.	OFFSET	TR 1-48	TR 48-96
1161	5511	2223	2627	2930	110	90	1	9	155+1 - 166+8	FN 733-741 LINE TESTS				
										FN 743 NG TEST HOLE				

LAND SEISMIC RECORDING LOG

PAGE 1 OF

	CLIENT: Husky	PROSPECT: NPR-A	AREA: Fortress Mtn Play Area	LINE NO.: 736	
	PARTY NO.: 1192	INST. ENG.: LEE CURTIS	- STEVE IPPISCH		DATE: 3 DAY 1 YR 80

INSTRUMENT	<input checked="" type="checkbox"/> 1 SYSTEM <input type="checkbox"/> 2 SYSTEMS	<input type="checkbox"/> 1-24 & 25-48 <input type="checkbox"/> 1-48 & 49-96	ODDS <input type="checkbox"/> EVENS	TYPE: <input type="checkbox"/> DFS III	<input checked="" type="checkbox"/> DFS IV <input type="checkbox"/> OTHER	<input checked="" type="checkbox"/> 1 TRACK <input type="checkbox"/> 2 TRACK	FOPMAT: B SEG	<input checked="" type="checkbox"/> GAPPED <input type="checkbox"/> UNGAPPED	PACKING DENSITY: (L) <input type="checkbox"/> 256 BPI <input type="checkbox"/> 800 BPI	(M) <input type="checkbox"/> 712 BPI <input type="checkbox"/> 1600 BPI	
(9-TRACK)	NO. BYTES IN HEADER REC: 225	NO. BYTES IN RECORD ID: 24	NO. BYTES PER SCAN: 254	RECORD NUMBERS: <input checked="" type="checkbox"/> DEC. <input type="checkbox"/> OCT	GAIN CONSTANT: 36 db	INPUT IMPEDANCE: 2000 ohms.					
CONFIGURATION (MAG TAPE)	FIELD TRACE NOS.: 1-96					AUXILIARY DATA: TW 78 383 141 1 1 1 1					
	DATA CHANNEL NOS.: 5-100 (ON MAG TAPE)					AUXILIARY CHANNEL NOS.: 0 1 2 3 4					
PARAMETER	RECORD LENGTH: VARIABLE (S) sec.	SAMPLE RATE: <input type="checkbox"/> 1 ms. <input type="checkbox"/> 4 ms.	GAIN MODE: <input type="checkbox"/> INITIAL <input type="checkbox"/> MANUAL	FILTERS: FREQ: 8 Hz		LO CUT HZ SLOPE: 18		FREQ: 128 Hz		HIGH CUT HZ SLOPE: 72	NOTCH FILTER: <input type="checkbox"/> IN <input checked="" type="checkbox"/> OUT
DISPLAY	MODE: <input type="checkbox"/> FLOAT <input type="checkbox"/> AMPLIFIER <input type="checkbox"/> DIRECT	INITIAL GAIN: VAR db	TRIP SENS.: VAR db	POLARITY CONVENTION: POS		PRESSURE INCREASE ON GEOPHONE: <input type="checkbox"/> NEGATIVE <input checked="" type="checkbox"/> POSITIVE		NUMBERS ON MAG. TAPE: <input type="checkbox"/> DOWNBREAK <input type="checkbox"/> UPBREAK		ON DISPLAY: <input type="checkbox"/> ON DISPLAY	
CFS I	TYPE: <input checked="" type="checkbox"/> PS II <input type="checkbox"/> STANCO	RECORD LENGTH: ALONE	RECORD REJECTION:	NOISE REDUCTION:		NOISE THRESHOLD:		CORR. SCALING:		R.C.U. NORM./ALT SW.	

SOURCE	TYPE: <input checked="" type="checkbox"/> DYNAMITE	PATTERN:	NO. OF POSITIONS:	INLINE SPACING:	LATERAL SPACING:	STAGGER:	LENGTH:	WIDTH:	LATERAL OFFSET:	
	<input type="checkbox"/> VIBROSEIS									
	<input type="checkbox"/> OTHER									
RECEIVER	TYPE: GSC-200	PATTERN: Fulcrum	NO. OF ELEMENTS: 18	INLINE SPACING: 6.5'	LATERAL SPACING:	STAGGER:	LENGTH: 110'	WIDTH:	LATERAL OFFSET:	
	CONNECTION: SEP-PNR	RESISTANCE: _____ ohms	STAGGER:	LENGTH: 110'	WIDTH:	LATERAL OFFSET:				
SPREAD	NO. OF GROUPS: 96	GROUP INTERVAL: 110'	SHOTPOINT INTERVAL: 850'	FOLD: 6	DIRECTION OF PROGRESSION: NORTH					
	OFFSET GROUP 1: 5170	OFFSET GROUP 45: 55'	OFFSET GROUP 49: 55	OFFSET GROUP 96: 5170	LEADING GROUP: 96					

DIAGRAMS/MISC. INFORMATION: **No GRP** * **X** **X** **X** **56**
58 **56** **56**

DAILY TESTS FN -
TTB FN

SHOTPOINT	TR. 1 to 96			TR. 10 to 100			SHOT		SPREAD				REMARKS:	CORR STACK				
	REEL NO.	REC.	REEL NO.	REC.	SIZE	DEPTH	NO.	OFFSET	DIR	COP SWITCH	LINE GROUPS			TR 1-49	TR 49-96			
															HI	REC	HI	REC
162		783			11.0	90					17	156-1	→	167B	168			
163		784			11.0	90					25	157-1	→	168B				
164		785			11.0	90					33	158-1	→	169B				
165		786			11.0	90					41	159-1	→	170B				
166	981049	787			11.0	90					49	160-1	→	171B				
167		788			11.0	90					9	161-1	→	172B	169			
168		790			11.0	90					17	162-1	→	173B				
169		791			11.0	90					25	163-1	→	174B				
170		792			11.0	90					33	164-1	→	175B				
171		793			11.0	90					41	165-1	→	176B				
172		794			11.0	90					49	166-1	→	177B				
173		795			11.0	90					9	167-1	→	178B	175			
174		796			11.0	90					17	168-1	→	179B				
175		797			11.0	90					25	169-1	→	180B				
176		798			11.0	90					33	170-1	→	181B				
177		799			11.0	90					41	171-1	→	182B				
178		800			11.0	90					49	172-1	→	183B				
179		801			11.0	90					9	173-1	→	184B	181			
180		802			11.0	90					17	174-1	→	185B				
181		803			11.0	90					25	175-1	→	186B				

LAND SEISMIC RECORDING LOG



CLIENT: **HUSKY**

PROSPECT: **NPR-A**

AREA: **FORTRESS MTN PLAY AREA**

LINE NO: **736**

PARTY NO: **1102**

INST. ENG: **LEE CURTIS + STEVE IPPISH**

DATE: **MO 3 DAY 2 YE 80**

SHOTPOINT	TR 1 to 70		TR 10		SHOT				SPREAD			REMARKS	FOUR STACK					
	REEL NO.	REC.	REEL NO.	REC.	SIZE	DEPTH	NO.	OFFSET	DIR.	CDP SWITCH	LINE GROUPS		HT.	TR 1-40	REC.	HT.	TR 40-96	REC.
182		804			110	90				33	176-1 → 187-8	181						
183		805			110	90		330	N	41	177-1 → 188-8							
184		806			110	90				49	178-1 → 181-8							
185	RELEASE	807			110	90				9	179-1 → 190-8	187						
186		808			110	90				17	180-1 → 191-8							
187		809			110	90				25	181-1 → 192-8							
188		810			110	90				33	182-1 → 193-8							
189		811			110	90				41	183-1 → 194-8							
190		812			110	90				49	184-1 → 195-8							
191		813			110	90				9	185-1 → 196-8	193						
192		814			110	90				17	186-1 → 197-8							
193		815			110	90				25	187-1 → 198-8							
194		816			110	90				33	188-1 → 199-8							
195		817			110	90				41	189-1 → 200-8							
196		818			110	90				49	190-1 → 201-8							

(NOTE OFFSET)

187 TAPE CHANGE *

1-24 SLASHED

TRACKS 93, 96 (200-S + 200-E) DEAD

LAND SEISMIC RECORDING LOG



CLIENT: **Husky** PROSPECT: **NPR-A** AREA: **Fortress Mtn. Play Area** LINE NO.: **736**
 PARTY NO.: **1182** INST. ENG.: _____ DATE: **MO 3 DAY 3 YE 80**

INSTRUMENT: 1 SYSTEM 2 SYSTEMS 1-24 & 25-48 1-48 & 49-96 ODDS EVENS TYPE: DFS III DFS II OTHER _____
 (9-TRACK) NO. BYTES IN HEADER REC: _____ NO. BYTES IN RECORD ID: _____ NO. BYTES PER SCAN: _____
 RECORD NUMBERS: DEC OCT GAIN CONSTANT: **36** db INPUT IMPEDANCE: **20,000** ohms.
 PACKING DENSITY: (LO) 356 BPI (HI) 712 BPI 1000 BPI
 FILTERS: 9 TRACK 21 TRACK FORMAT: SEG **B** GAPPED UNGAPPED
 (1) (2) (3) (4) (5) (6) (7)

CONFIGURATION (MAG TAPE) FIELD TRACE NOS.: **1-96** AUXILIARY DATA: _____
 DATA CHANNEL NOS.: **1-96** (ON MAG TAPE) AUXILIARY CHANNEL NOS.: _____
 PARAMETER RECORD LENGTH: **8** sec. SAMPLE RATE: 1 ms. 2 ms. 4 ms. GAIN MODE: INITIAL FINAL MANUAL OPERATE
 DISPLAY MODE: AGC FLOAT DEFLOAT AMPLIFIER DIRECT INITIAL GAIN: **0** db TRIP SENS.: _____ db
 CFS I TYPE STACK: _____ GATE LENGTH: _____ RECORD REJECTION: _____ NOISE REDUCTION: _____ NOISE THRESHOLD: _____ CORR. SCALING: _____ R.C.U. NORM./ALT SW. _____

SOURCE TYPE: DYNAMITE VIBROSEIS OTHER _____ PATTERN: **SINGLE HOLE INLINE** NO. OF POSITIONS: _____ INLINE SPACING: _____ LATERAL SPACING: _____ STAGGER: _____ LENGTH: _____ WIDTH: _____ LATERAL OFFSET: _____
 CHG. HOLE: **110** HOLE DEPTH: **90** SWEEP POSITION: _____ SWEEP START: _____ SWEEP END: _____ SWEEP LENGTH: _____ SWEEP TAPER: _____ PHASE COMP: _____

RECEIVER TYPE: **ESC 2.0D** PATTERN: **INLINE** NO. OF ELEMENTS: **18** INLINE SPACING: **6.5'** LATERAL SPACING: _____ CONNECTION: **SERIES/PARALLEL** RESISTANCE: _____ STAGGER: _____ LENGTH: **110'** WIDTH: _____ LATERAL OFFSET: _____

SPREAD NO. OF GROUPS: **96** GROUP INTERVAL: **110'** SHOTPOINT INTERVAL: **660'** FOLD: **6** DIRECTION OF PROGRESSION: **N**
 OFFSET GROUP 1: **5225** OFFSET GROUP 48: **55'** OFFSET GROUP 49: **55'** OFFSET GROUP 96: **5225** LEADING GROUP: **98**

DIAGRAMS/MISC. INFORMATION: **194 195 196 197 198 199 Sp200 201 202 203 204 205 Sp206**
TR 1 194+1 **TR 98 205+8**

SHOTPOINT	TR _____ to _____		TR _____ to _____		SHOT		SPREAD		REMARKS	CORR. STACK			
	REEL NO.	REC.	REEL NO.	REC.	SIZE	DEPTH	NO.	OFFSET		DIR.	CDP SWITCH	LINE GROUPS	TR 1-48
197	9810510	832			110	90	11		9	191+1	-202+8	199	
198		833			110	90	2		17	192+1	-203+8		
199		834			110	90	3		25	193+1	-204+8		
200	9810511	835			110	90	4		33	194+1	-205+8		TAPE CHANGE
201		836			110	90	5		41	195+1	-206+8		
202		837			110	90	6		13	196+1	-207+8	209+4	TR 39 DEAD
203		838			110	90	7		21	197+1	-208+8		TR 17 WEAK
204		839			110	90	8		29	198+1	-209+8		TR 40 NOISY
205		840			110	90	9		37	199+1	-210+8		TR 32 "
206		841			110	90	10		45	200+1	-211+8		TR 24+27 NOISY
207		842			110	90	11		5	201+1	-212+8	209+4	TR 19+23 WRAX TR 87 NOISY
208		843			110	90	12		13	202+1	-213+8		68 NOISY
209		844			110	90	13		21	203+1	-214+8		TR 1,2,3+4 DEAD JUG GREW.
210		845			110	90	14		29	204+1	-215+8		
211		846			110	90	15		37	205+1	-216+8		
212		847			110	90	16		945	206+1	-217+8	214	
213		848			110	90	17		17	207+1	-218+8		1-48 SLASHED
214		849			110	90	18		25	208+1	-219+8		
215		851			110	90	19		33	209+1	-220+8		FILE # 850 No FIRE
216		852			110	90	20		41	210+1	-221+8		

LAND SEISMIC RECORDING LOG



CLIENT: Husky	PROSPECT: NPR-A	AREA: FORTRESS MTN. PLAY AREA	LINE NO: 736
PARTY NO: 1182	INST. ENG:		DATE: MO 3 DAY 3 YR 87

SHOTPOINT	TR		TR		SHOT								SPREAD		REMARKS	CORR. STACK			
	REEL NO.	REC.	REEL NO.	REC.	SIZE	DEPTH	NO.	OFFSET	DIR.	CDP SWITCH	LINE GROUPS		TR 1-48			TR 49-96			
	HT.	REC.	HT.	REC.									HT.	REC.		HT.	REC.		
2117	9811251	18573			110	19021					49	211+1 - 222+8							
2118		18555			110	19022					33	212+1 - 223+8		FILE # 854	NO FIRE				
2119	9811252	18516			110	19023					4	213+1 - 224+8		TAPE CHANGE					
220		18517			110	19024	110	S			49	214+1 - 225+8		E.O.L.					

E.O.L.