



LAND SEISMIC RECORDING LOG

Recording Hrs 14.5
10 of 3 3 DRIVE



	CLIENT: Husky	PROSPECT: NPA-4	AREA: Meat Mtn	LINE NO: 756	
PARTY NO: 1186		INST. ENG: Streff		DATE: NO. 3 DAY 8 YR 80	
INSTRUMENT (9-TRACK)	<input checked="" type="checkbox"/> SYSTEM <input type="checkbox"/> 2 SYSTEMS	<input type="checkbox"/> 1-24 & 25-48 <input checked="" type="checkbox"/> 24 & 49-96	<input type="checkbox"/> DFS III <input checked="" type="checkbox"/> DFS III	<input type="checkbox"/> TRACK <input checked="" type="checkbox"/> 2 TRACK	FORMAT: B
	NO. BYTES IN HEAD REC: 228	NO. BYTES IN RECORD ID: 24	NO. BYTES PER SCAN: 254	RECORD NUMBERS: <input type="checkbox"/> DEC. <input type="checkbox"/> OCT.	GAIN CONSTANT: 36 db
CONFIGURATION (MAG TAPE)	FIELD TRACE NOS.: 1-48	DATA CHANNEL NOS.: 5-10	AUXILIARY DATA: AUXILIARY CHANNEL NOS.: TW SPS TO EM 0		
PARAMETER	RECORD LENGTH: 8 sec.	SAMPLE RATE: <input type="checkbox"/> 1 ms. <input checked="" type="checkbox"/> 4 ms.	GAIN MODE: <input checked="" type="checkbox"/> INITIAL <input type="checkbox"/> MANUAL <input type="checkbox"/> OPERATE	FILTERS: FREQ. 8	LO CUT HZ SLOPE 18
DISPLAY	MODE: <input type="checkbox"/> FLOAT <input type="checkbox"/> AMPLIFIER <input type="checkbox"/> DIRECT	INITIAL GAIN: 0 db	TRIP SENS.: 0 db	POLARITY CONVENTION: POS	PRESSURE INCREASE ON GEOPHONE: <input type="checkbox"/> NEGATIVE <input checked="" type="checkbox"/> POSITIVE
CFS I	TYPE STACK: STAND ALONE	GATE LENGTH:	RECORD REJECTION:	NOISE THRESHOLD:	CORR. SCALING:
SOURCE	TYPE: <input checked="" type="checkbox"/> DYNAMITE <input type="checkbox"/> VIBROSEIS <input type="checkbox"/> OTHER	PATTERN: Inline - hole	NO. OF POSITIONS:	INLINE SPACING:	LATERAL SPACING:
RECEIVER	TYPE: 20-0	PATTERN: 111111	NO. OF ELEMENTS: 18	INLINE SPACING: 6	LATERAL SPACING:
SPREAD	CONNECTION: Series-Parallel	RESISTANCE: 560 ohms	STAGGER:	LENGTH: 110	WIDTH: 96
NO. OF GROUPS: 96		GROUP INTERVAL: 110	SHOTPOINT INTERVAL: 440	FOLD: 12	DIRECTION OF PROGRESSION: SE N→S
OFFSET GROUP 1: 5225		OFFSET GROUP 2: 38	OFFSET GROUP 3: 55	OFFSET GROUP 48/96: 5225	LEADING GROUP: 96

DIAGRAMS/MISC. INFORMATION:
TR#15 SE → TR#96 #1154-1157 test TD
#1143-1153 tests

SHOTPOINT	TR 10		TR 20		SHOT		SPREAD		REMARKS	CORR STACK					
	REEL NO.	REC.	REEL NO.	REC.	SIZE	DEPTH	NO.	OFFSET		DIR.	CDP SWITCH	LINE GROUPS			
1100	784063	1158			110	105	1	1158	SW	1069	102+1 - 125+4	1	WALKING SHOOTER THROUGH CABLE		
1102		1159			110	105	2				" - "		Recorder @ SP-120 (S.P. 102) = 100'		
1104		1160			110	105	3				" - "		SP-102 - SP120 - NO SNOW		
1105		1161			110	105	4	45W			" - "		JUMBLED ROCKS & SOLID ROCK		
1106		1162			110	105	5				" - "		SOME traces noisy from BAR COUPLING		
1107		1163			110	105	6				" - "		SP 102 - 105 Very high on mountain - High winds		
1108		1164			110	105	7				" - "				
1109		1165			110	105	8				" - "				
1110		1166			110	105	9				" - "				
1111		1167			110	105	10				" - "				
1112		1168			110	105	11				" - "				
1113		1169			110	105	12				" - "				
1114		1170			110	105	13				" - "				
1115		1171			110	105	14				" - "				
1116		1172			110	105	15				" - "				
1117		1173			110	105	16				" - "				
1118		1174			110	105	17				" - "				
1119		1175			110	105	18				" - "				
1120		1176			110	105	19				" - "				
1121		1177			110	105	20				" - "				
											102+1 - 125+4		SHOOTING NORMAL SPLIT		
											103+1 - 126+4		Even numbered SP's from		
											104+1 - 127+4		SP 116 - 134 loaded with		
											105+1 - 128+4		100 lbs stick GEL. ALL		
											106+1 - 129+4		others loaded normally.		
											107+1 - 130+4				
											108+1 - 131+4				
											109+1 - 132+4				

LAND SEISMIC RECORDING LOG

2 of 3

	CLIENT: HUSHY	PROSPECT: NPR-4	AREA: meat mtn	LINE NO: 756												
PARTY NO: 1186		INST. ENG: STREFF		DATE: MO 3 DAY 8 YR 80												
INSTRUMENT (9-TRACK)	<input type="checkbox"/> 1 SYSTEM <input type="checkbox"/> 2 SYSTEMS	<input type="checkbox"/> 1-24 & 25-48 <input type="checkbox"/> 1-48 & 49-96	ODDS & EVENS	TYPE: <input type="checkbox"/> DFS III <input type="checkbox"/> DFS II <input type="checkbox"/> OTHER	<input type="checkbox"/> 9 TRACK <input type="checkbox"/> 21 TRACK	FORMAT: SEG	<input type="checkbox"/> GAPPED <input type="checkbox"/> UNGAPPED	PACKING DENSITY: (LD) <input type="checkbox"/> 356 BPI (MI) <input type="checkbox"/> 800 BPI (HI) <input type="checkbox"/> 712 BPI <input type="checkbox"/> 1000 BPI	NO. BYTES IN HEADER REC: _____		NO. BYTES IN RECORD ID: _____	NO. BYTES PER SCAN: _____	RECORD NUMBERS: <input type="checkbox"/> DEC <input type="checkbox"/> OCT	GAIN CONSTANT: _____ db	INPUT IMPEDANCE: _____ ohms	
	CONFIGURATION (MAG TAPE)	FIELD TRACE NOS.: _____			AUXILIARY DATA: _____			AUXILIARY CHANNEL NOS.: _____			GAIN CONSTANT: (1) _____ (2) _____ (3) _____ (4) _____ (5) _____ (6) _____ (7) _____					
PARAMETER	RECORD LENGTH: _____ sec.	SAMPLE RATE: <input type="checkbox"/> 1 ms. <input type="checkbox"/> 4 ms. <input type="checkbox"/> 2 ms. <input type="checkbox"/> _____ ms.	GAIN MODE: <input type="checkbox"/> INITIAL <input type="checkbox"/> IFF	<input type="checkbox"/> MANUAL <input type="checkbox"/> OPERATE	FILTERS: _____	LO CUT HZ SLOPE _____	FREQ _____	HI CUT HZ SLOPE _____	NOTCH FILTER: <input type="checkbox"/> IN <input type="checkbox"/> OUT	MODE: <input type="checkbox"/> FLOAT <input type="checkbox"/> AMPLIFIER <input type="checkbox"/> AGC <input type="checkbox"/> DEFLOAT <input type="checkbox"/> DIRECT	INITIAL GAIN: _____ db	TRIP SENS: _____ db	POLARITY CONVENTION _____	PRESSURE INCREASE ON GEOPHONE: <input type="checkbox"/> NEGATIVE <input type="checkbox"/> POSITIVE	NUMBERS ON MAG. TAPE <input type="checkbox"/> DOWNBREAK <input type="checkbox"/> UPBREAK	ON DISPLAY
DISPLAY	CFS I	TYPE STACK: _____	GATE LENGTH: _____	RECORD REJECTION: _____	NOISE REDUCTION: _____	NOISE THRESHOLD: _____	CORR. SCALING: _____	R.C.U. NORM./ALT SW. _____								
SOURCE	TYPE: <input type="checkbox"/> DYNAMITE <input type="checkbox"/> VIBROSEIS <input type="checkbox"/> OTHER	PATTERN: _____	NO. OF POSITIONS: _____	INLINE SPACING: _____	LATERAL SPACING: _____	STAGGER: _____	LENGTH: _____	WIDTH: _____	LATERAL OFFSET: _____							
RECEIVER	CONNECTION: _____	PATTERN: _____	RESISTANCE: _____ ohms	STAGGER: _____	INLINE SPACING: _____	LENGTH: _____	WIDTH: _____	LATERAL OFFSET: _____								
SPREAD	NO. OF GROUPS: _____	GROUP INTERVAL: _____	SHOTPOINT INTERVAL: _____	FOLD: _____	DIRECTION OF PROGRESSION: _____	LEADING GROUP: _____										



DIAGRAMS/MISC. INFORMATION: _____

SPIKES - TRACES 1-48 - OLD HOLES

SHOTPOINT	TR _____ to _____		TR _____ to _____		SHOT				SPREAD			REMARKS:	CORR. STACK									
	REEL NO.	REC.	REEL NO.	REC.	SIZE	DEPTH	NO.	OFFSET	DIR.	CDP SWITCH	LINE GROUPS		SET UP	TR 1-48	TR 49-96	TR 1-48	TR 49-96					
1120	784063	1178	17	2223	26	27	29	30	32	35	37	90	N	33	110+1-133+4	1	SP 132 - 135	CREEK - noisy				
1123		1179			110	105	22							37	111+1-134+4							
1124		1180			100	105	23		25	E				41	112+1-135+4							
1125		1181			110	105	24							45	113+1-136+4							
1126		1182			100	105	25							49	114+1-137+4							
1127		1183			110	105	26							5	115+1-138+4	2	Recorder @ SP-132					
1128		1184			100	105	27							9	116+1-139+4		132+1 dead					
1129		1185			110	105	28							13	117+1-140+4		132+1 dead					
1130		1186			100	105	29							17	118+1-141+4		SP-141 → 147 - no snow	rocks	noisy			
1131		1187			110	105	30							21	119+1-142+4							
1132		1188			100	105	31							25	120+1-143+4							
1133		1189			110	105	32							29	121+1-144+4							
1134		1190			100	105	33	60	SW	RD				33	122+1-145+4		L					
1135		1191			100	105	34	60	NW	RD				37	123+1-146+4							
1136		1192			110	105	35							41	124+1-147+4							
1137		1193			110	105	36							45	125+1-148+4		#1194 all ones #1195 NG					
1138	784064	1194			110	105	37							49	126+1-149+4		TAPE CHANGE					
1139		1197			110	105	38							5	127+1-150+4	3	Recorder @ SP144					
1140		1198			110	105	39	95	W					9	128+1-151+4							
1141		1199			110	105	40							13	129+1-152+4							

LAND SEISMIC RECORDING LOG

3 of 3



	CLIENT: Husky	PROSPECT: NPR-4	AREA: Meat Mtn	LINE NO: 756					
	PARTY NO: 1186	INST. ENG: Street		DATE: 3 DAY 8 80					
INSTRUMENT (9-TRACK)	<input type="checkbox"/> 1 SYSTEM <input type="checkbox"/> 2 SYSTEMS	<input type="checkbox"/> 1-24 & 25-48 <input type="checkbox"/> 1-48 & 49-96	<input type="checkbox"/> ODDS & EVENS	TYPE: <input type="checkbox"/> DFS III <input type="checkbox"/> DFS IV <input type="checkbox"/> OTHER	<input type="checkbox"/> 9 TRACK <input type="checkbox"/> 21 TRACK	FORMAT: <input type="checkbox"/> SEG	<input type="checkbox"/> GAPPED <input type="checkbox"/> UNGAPPED	PACKING DENSITY: (L) <input type="checkbox"/> 356 BPI <input type="checkbox"/> 800 BPI	(H) <input type="checkbox"/> 712 BPI <input type="checkbox"/> 1600 BPI
	NO. BYTES IN HEADER REC:	NO. BYTES IN RECORD ID:	NO. BYTES PER SCAN:	RECORD NUMBERS:	<input type="checkbox"/> DEC. <input type="checkbox"/> OCT.	GAIN CONSTANT: _____ db	INPUT IMPEDANCE: _____ ohms.	(1) _____ (2) _____ (3) _____ (4) _____ (5) _____ (6) _____ (7) _____	
CONFIGURATION [MAG TAPE]	FIELD TRACE NOS. _____				AUXILIARY DATA: _____				
	DATA CHANNEL NOS. _____ (ON MAG TAPE)				AUXILIARY CHANNEL NOS. _____				
PARAMETER	RECORD LENGTH: _____ sec.	SAMPLE RATE: <input type="checkbox"/> 1 ms. <input type="checkbox"/> 4 ms. <input type="checkbox"/> 2 ms. <input type="checkbox"/> _____ ms.	GAIN MODE: <input type="checkbox"/> INITIAL <input type="checkbox"/> MANUAL <input type="checkbox"/> 1FP <input type="checkbox"/> FINAL <input type="checkbox"/> OPERATE	FILTERS: _____	LO CUT HZ SLOPE _____	FREQ. _____	HI CUT HZ SLOPE _____	NOTCH FILTER: <input type="checkbox"/> IN <input type="checkbox"/> OUT	
DISPLAY	MODE: <input type="checkbox"/> FLOAT <input type="checkbox"/> AMPLIFIER <input type="checkbox"/> AGC <input type="checkbox"/> DEFLOAT <input type="checkbox"/> DIRECT	INITIAL GAIN: _____ db	TRIP SENS: _____ db	POLARITY CONVENTION: _____	PRESSURE INCREASE ON GEOPHONE: <input type="checkbox"/> NEGATIVE <input type="checkbox"/> POSITIVE	NUMBERS ON ON MAG TAPE	<input type="checkbox"/> DOWNBREAK <input type="checkbox"/> UPBREAK	ON DISPLAY	
CFS I	TYPE STACK: _____	GATE LENGTH: _____	RECORD REJECTION: _____	NOISE REDUCTION: _____	NOISE THRESHOLD: _____	CORR. SCALING: _____	E.C.U. NORM./ALT SW.		
SOURCE	TYPE: <input type="checkbox"/> DYNAMITE <input type="checkbox"/> VIBROSEIS <input type="checkbox"/> OTHER	PATTERN: _____	NO. OF POSITIONS: _____	INLINE SPACING: _____	LATERAL SPACING: _____	STAGGER: _____	LENGTH: _____	WIDTH: _____	LATERAL OFFSET: _____
	CHG/ HOLE: _____	HOLE DEPTH: _____	SWEEP POSITION: _____	SWEEP START: _____	SWEEP END: _____	SWEEP LENGTH: _____	SWEEP TAPER: _____	PHASE COMP: _____	
RECEIVER	TYPE: _____	PATTERN: _____	NO. OF ELEMENTS: _____	INLINE SPACING: _____	LATERAL SPACING: _____	STAGGER: _____	LENGTH: _____	WIDTH: _____	LATERAL OFFSET: _____
	CONNECTION: _____	RESISTANCE: _____ ohms							
SPREAD	NO. OF GROUPS: _____	GROUP INTERVAL: _____	SHOTPOINT INTERVAL: _____	FOLD: _____	DIRECTION OF PROGRESSION: _____				
	OFFSET GROUP 1: _____	OFFSET GROUP _____	OFFSET GROUP _____	OFFSET GROUP 48/96: _____	LEADING GROUP: _____				


DIAGRAMS/MISC. INFORMATION:

SHOTPOINT	TR. _____ to _____		TR. _____ to _____		SHOT			SPREAD			REMARKS:	CORR. STACK			
	REEL NO.	REC.	REEL NO.	REC.	SIZE	DEPTH	NO. OFFSET	DIR.	CDP SWITCH	LINE GROUPS		TR 1-48	TR 48-96	TR 1-48	TR 48-96
141	7890	1200			110	105	41		17	130+1 - 153+4					
142		1201			110	105	42		21	131+1 - 154+4					
144		1202			110	105	43		25	132+1 - 155+4					
145		1203			110	105	44		29	133+1 - 156+4	SP 155 → SP-159	900' Vertical	TR 1-48	TR 48-96	
146		1204			110	105	45		33	134+1 - 157+4					
147		1205			110	105	46		37	135+1 - 158+4					
148		1206			110	105	47		41	136+1 - 159+4					
149		1207			110	105	48		45	137+1 - 160+4	TR# 94 dead				
150		1208			110	105	49		49	138+1 - 161+4					
151		1209			110	105	50		13	139+1 - 162+4	4	recorder @ SP 153			
152		1210			110	105	51		21	140+1 - 163+4					
153		1211			110	105	52		25	141+1 - 164+4					
154		1212			110	105	53		29	142+1 - 165+4					
155		1213			110	105	54	130 N	33	143+1 - 166+4					
156		1214			110	105	55	130 N	41	145+1 - 168+4	STACHED ON SP-155				
157		1215			110	105	56	130 N	49	147+1 - 169+4	STACHED ON SP-155				

LAND SEISMIC RECORDING LOG

10f3

	CLIENT: Husky	PROSPECT: NPR-4	AREA: Meat Mtn	LINE NO: 756													
	PARTY NO: 1186	INST. ENG: Stieff		DATE: 3 DAY 9 YR 80													
INSTRUMENT	<input checked="" type="checkbox"/> 1 SYSTEM <input type="checkbox"/> 2 SYSTEMS	<input type="checkbox"/> 1-24 & 25-48 <input checked="" type="checkbox"/> 1-48 & 49-96	EVENTS: <input checked="" type="checkbox"/> ODDS <input type="checkbox"/> EVENS	TYPE: <input type="checkbox"/> ODS III <input type="checkbox"/> ODS III <input type="checkbox"/> ODS IV <input type="checkbox"/> OTHER	<input type="checkbox"/> TRACK <input type="checkbox"/> 21 TRACK	FORMAT: B	<input type="checkbox"/> GAPPED <input type="checkbox"/> UNGAPPED	PACKING DENSITY: (L) <input type="checkbox"/> 356 BPI (H) <input type="checkbox"/> 712 BPI <input type="checkbox"/> 1000 BPI	NO. BYTES IN HEADER REC: 228	NO. BYTES IN RECORD ID: 24	NO. BYTES PER SCAN: 254	RECORD NUMBERS: <input type="checkbox"/> DEC <input type="checkbox"/> OCT	GAIN CONSTANT: 36 db	INPUT IMPEDANCE: 2000 ohms			
CONFIGURATION (MAG TAPE)	FIELD TRACE NOS.: 1-96			AUXILIARY DATA: (1) 0 (2) 1 (3) 2 (4) 3 (5) 0 (6) 0 (7) 0			AUXILIARY CHANNEL NOS.: TW SPS TB EM 0			(ON MAG TAPE)							
PARAMETER	RECORD LENGTH: 8 sec	SAMPLE RATE: <input type="checkbox"/> 1 ms. <input type="checkbox"/> 4 ms. <input checked="" type="checkbox"/> 2 ms.	GAIN MODE: <input type="checkbox"/> INITIAL <input type="checkbox"/> MANUAL <input type="checkbox"/> OPERATE	FILTERS: FREQ: 8 LO CUT HZ SLOPE 18 HI CUT HZ SLOPE 20	NOTCH FILTER: <input type="checkbox"/> IN <input type="checkbox"/> OUT												
DISPLAY	MODE: <input checked="" type="checkbox"/> FLAGG <input type="checkbox"/> FLOAT <input type="checkbox"/> AMPLIFIER <input type="checkbox"/> DIRECT	INITIAL GAIN: 0 db	TRIP SENS: 0 db	POLARITY CONVENTION: POS	PRESSURE INCREASE ON GEOPHONE: <input type="checkbox"/> NEGATIVE <input checked="" type="checkbox"/> POSITIVE		NUMBERS ON MAG. TAPE: <input type="checkbox"/> DOWNBREAK <input type="checkbox"/> UPBREAK			ON DISPLAY			R.C.U. NORM./ALT SW.				
CFS I	TYPE STACK: standalone II	GATE LENGTH:	RECORD REJECTION:	NOISE REDUCTION:	NOISE THRESHOLD:	CORR. SCALING:											
SOURCE	TYPE: <input checked="" type="checkbox"/> DYNAMITE <input type="checkbox"/> VIBROSEIS <input type="checkbox"/> OTHER	PATTERN: inline	NO. OF POSITIONS:	INLINE SPACING:	LATERAL SPACING:	STAGGER:	LENGTH:	WIDTH:	LATERAL OFFSET:	CHG/ HOLE: 110	HOLE DEPTH: 105	SWEEP POSITION:	SWEEP START:	SWEEP END:	SWEEP LENGTH:	SWEEP TAPER:	PHASE COMP:
RECEIVER	TYPE: 20-P	PATTERN: inline	NO. OF ELEMENTS: 18	INLINE SPACING: 6	LATERAL SPACING:	STAGGER:	LENGTH: 1:0	WIDTH:	LATERAL OFFSET:	CONNECTION: Series-parallel	RESISTANCE: 560 ohms	STAGGER:	LENGTH:	WIDTH:	LATERAL OFFSET:		
SPREAD	NO. OF GROUPS: 96	GROUP INTERVAL: 110	SHOTPOINT INTERVAL: 440	FOLD: 12	DIRECTION OF PROGRESSION: SE	LEADING GROUP: 96											
OFFSET GROUP 1: 5225		OFFSET GROUP 48: 55		OFFSET GROUP 49: 55		OFFSET GROUP 48/96: 5225											



SHOTPOINT	TR. 10		TR. 10		SHOT		SPREAD		REMARKS	CORR. STACK						
	REEL NO.	REC.	REEL NO.	REC.	SIZE	DEPTH	NO.	OFFSET		DIR.	CDP SWITCH	LINE GROUPS	HT.	REC.	HT.	REC.
1158	98406	1231			110	105	1250	5	17	165+1 - 168+4						
1159		1232					2250	5	25	148+1 - 170+4						
1160		1233							29	148+1 - 171+4						
1161		1234							33	149+1 - 172+4						
1162		1235							37	150+1 - 173+4						
1163		1237							41	151+1 - 174+4						
1164		1238							45	152+1 - 175+4						
1165		1239							49	153+1 - 176+4						
1166		1240							5	154+1 - 177+4						
1167		1241							9	155+1 - 178+4						
1168		1242							13	156+1 - 179+4						
1169		1243							17	157+1 - 180+4						
1170		1244							21	158+1 - 181+4						
1171		1245							25	159+1 - 182+4						
1172	98406	1247			105	15			29	160+1 - 183+4						
1173		1248			95	16			33	161+1 - 184+4						
1174		1249			105	17			37	162+1 - 185+4						
1175		1250				18			41	163+1 - 186+4						
1176		1251				19	60 SW		45	164+1 - 187+4						
1177		1252			110	105	20		49	165+1 - 188+4						

1229-1230 - NG.

Recorder @ SP-159 - STAGED on SP-159

TR#94 dead

1236 - N.G. TR#94 dead

CDP-41 → 151+1 - 175+4

TAPE CHANGE # 1246 allows



184+2 dead

SP-184 - 186 200 foot vertical drop

17
28
67

LAND SEISMIC RECORDING LOG

2 of 3

	CLIENT: Husky	PROSPECT: NPR-4	AREA: Meat mtn	LINE NO: 756					
	PARTY NO: 1186	INST. ENG: Stieff		DATE: 3 DAY 8 YR 80					
INSTRUMENT	<input type="checkbox"/> 1 SYSTEM <input type="checkbox"/> 2 SYSTEMS	<input type="checkbox"/> 1-24 & 25-48 <input type="checkbox"/> 1-48 & 49-96	<input type="checkbox"/> ODDS <input type="checkbox"/> EVENS	TYPE: <input type="checkbox"/> DFS III <input type="checkbox"/> DFS IV <input type="checkbox"/> OTHER	<input type="checkbox"/> 9 TRACK <input type="checkbox"/> 21 TRACK	FORMAT: _____ SEG _____	<input type="checkbox"/> GAPPED <input type="checkbox"/> UNGAPPED	PACKING DENSITY: (L) <input type="checkbox"/> 356 BPI <input type="checkbox"/> 800 BPI	(H) <input type="checkbox"/> 712 BPI <input type="checkbox"/> 1600 BPI
[9-TRACK]	NO. BYTES IN HEADER REC: _____	NO. BYTES IN RECORD ID: _____	NO. BYTES PER SCAN: _____	RECORD NUMBERS: _____	<input type="checkbox"/> DEC. <input type="checkbox"/> OCT	GAIN CONSTANT: _____ db	INPUT IMPEDANCE: _____ ohms.	(1) _____ (2) _____ (3) _____ (4) _____ (5) _____ (6) _____ (7) _____	
CONFIGURATION (MAG TAPE)	FIELD TRACE NOS.: _____				AUXILIARY DATA: _____				
	DATA CHANNEL NOS.: _____ (ON MAG TAPE)				AUXILIARY CHANNEL NOS.: _____				
PARAMETER	RECORD LENGTH: _____ sec.	SAMPLE RATE: <input type="checkbox"/> 1 ms. <input type="checkbox"/> 4 ms. <input type="checkbox"/> 2 ms. <input type="checkbox"/> _____ ms.	GAIN MODE: <input type="checkbox"/> INITIAL <input type="checkbox"/> IFF <input type="checkbox"/> FINAL <input type="checkbox"/> OPERATE	FILTERS: _____	LO CUT HZ SLOPE _____	FREQ. _____	HI CUT HZ SLOPE _____	NOTCH FILTER: <input type="checkbox"/> IN <input type="checkbox"/> OUT	
DISPLAY	MODE: <input type="checkbox"/> FLOAT <input type="checkbox"/> AMPLIFIER <input type="checkbox"/> AGC <input type="checkbox"/> DEFLOAT <input type="checkbox"/> DIRECT	INITIAL GAIN: _____ db	TRIP SENS: _____ db	POLARITY CONVENTION: _____	PRESSURE INCREASE ON GEOPHONE: <input type="checkbox"/> NEGATIVE <input type="checkbox"/> POSITIVE	NUMBERS ON MAG. TAPE _____	DOWNBREAK <input type="checkbox"/> ON DISPLAY UPBREAK <input type="checkbox"/> ON DISPLAY		
CFS I	TYPE STACK: _____	GATE LENGTH: _____	RECORD REJECTION: _____	NOISE REDUCTION: _____	NOISE THRESHOLD: _____	CORR. SCALING: _____	R.C.U. NORM/ALT SW: _____		
SOURCE	TYPE: <input type="checkbox"/> DYNAMITE <input type="checkbox"/> VIBROSEIS <input type="checkbox"/> OTHER	PATTERN: _____	NO. OF POSITIONS: _____	INLINE SPACING: _____	LATERAL SPACING: _____	STAGGER: _____	LENGTH: _____	WIDTH: _____	LATERAL OFFSET: _____
	CHG/ HOLE: _____	HOLE DEPTH: _____	SWEEP POSITION: _____	SWEEP START: _____	SWEEP END: _____	SWEEP LENGTH: _____	SWEEP TAPER: _____	PHASE COMP: _____	
RECEIVER	TYPE: _____	PATTERN: _____	NO. OF ELEMENTS: _____	INLINE SPACING: _____	LATERAL SPACING: _____	STAGGER: _____	LENGTH: _____	WIDTH: _____	LATERAL OFFSET: _____
	CONNECTION: _____	RESISTANCE: _____ ohms	STAGGER: _____	LENGTH: _____	WIDTH: _____	LATERAL OFFSET: _____			
SPREAD	NO. OF GROUPS: _____	GROUP INTERVAL: _____	SHOTPOINT INTERVAL: _____	FOLD: _____	DIRECTION OF PROGRESSION: _____	OFFSET GROUP 1: _____	OFFSET GROUP 48/96: _____	LEADING GROUP: _____	

DIAGRAMS/MISC. INFORMATION: _____

SHOTPOINT	TR. _____ to _____		TR. _____ to _____		SHOT				SPREAD			REMARKS	CORR. STACK				
	REEL NO	REC.	REEL NO	REC.	SIZE	DEPTH	NO.	OFFSET	DIR.	COP SWITCH	LINE GROUPS		STY	TR 1-48	TR 48-96	REC.	REC.
1178	9840	1253			10	10	5				166+1-189+4	3					
1179		1254					22				167+1-190+4	9					
1180		1255					23				168+1-191+4	13					
1181		1256					24	60	NW	47	169+1-192+4	17					
1182		1257					25				170+1-193+4	21					
1183		1258					26				171+1-194+4	25					
1184		1259					27	60	N	5	172+1-195+4	4					
1185		1260					28	90	S	9	173+1-196+4	9					
1186		1261					29				174+1-197+4	13					
1187		1262					30				175+1-198+4	17					
1188		1263					31				176+1-199+4	21					
1189		1264					32				177+1-200+4	25					
1190		1265					33				178+1-201+4	29					
1191		1266					34				179+1-T-4	33					
1192		1267					35				180+1-T-8	37					
1193		1268					36				181+1-T-12	41					
1194		1269					37				182+1-T-16	45					
1195		1270					38				183+1-T-20	49					
1196		1271					39				184+1-T-24	5					
1197		1272					40	65	W	21	185+1-T-28	21					

LAND SEISMIC RECORDING LOG

3 of 3



CLIENT: Husky	PROSPECT: NPR-4	AREA: Meat mth	LINE NO: 756
PARTY NO: 1186	INST. ENG: Streff	DATE: MO 3 DAY 8 YR 90	

INSTRUMENT	<input type="checkbox"/> 1 SYSTEM <input type="checkbox"/> 2 SYSTEMS	<input type="checkbox"/> 1-24 & 25-48 <input type="checkbox"/> 1-48 & 49-96	ODDS <input type="checkbox"/> EVENS	TYPE:	<input type="checkbox"/> DFS III <input type="checkbox"/> DFS IV <input type="checkbox"/> OTHER	<input type="checkbox"/> 9 TRACK <input type="checkbox"/> 21 TRACK	FOPMAT: SEG	<input type="checkbox"/> GAPPED <input type="checkbox"/> UNGAPPED	PACKING DENSITY: (LO)	<input type="checkbox"/> 350 BPI <input type="checkbox"/> 800 BPI	(M)	<input type="checkbox"/> 712 BPI <input type="checkbox"/> 1000 BPI		
(9-TRACK)	NO. BYTES IN HEADER REC:	NO. BYTES IN RECORD ID:	NO. BYTES PER SCAN:	RECORD NUMBERS:	<input type="checkbox"/> DEC. <input type="checkbox"/> OCT	GAIN CONSTANT: _____ db	INPUT IMPEDANCE: _____ ohms	(1)	(2)	(3)	(4)	(5)	(6)	(7)
CONFIGURATION (MAG TAPE)	FIELD TRACE NOS.:					AUXILIARY DATA:					AUXILIARY CHANNEL NOS.:			
PARAMETER	RECORD LENGTH: _____ sec.	SAMPLE RATE: <input type="checkbox"/> 1 ms. <input type="checkbox"/> 4 ms. <input type="checkbox"/> 2 ms. <input type="checkbox"/> _____ ms.	GAIN MODE: <input type="checkbox"/> INITIAL <input type="checkbox"/> MANUAL <input type="checkbox"/> OPERATE	TRIP SENS: _____ db		FILTERS: FREQ. _____	LO CUT HZ SLOPE	HI CUT HZ SLOPE	NOTCH FILTER: <input type="checkbox"/> IN <input type="checkbox"/> OUT					
DISPLAY	MODE: <input type="checkbox"/> FLOAT <input type="checkbox"/> AMPLIFIER <input type="checkbox"/> DIRECT	INITIAL GAIN: _____ db	POLARITY CONVENTION: <input type="checkbox"/> NEGATIVE <input type="checkbox"/> POSITIVE		PRESSURE INCREASE ON GEOPHONE: <input type="checkbox"/> NUMBERS ON MAG TAPE		DOWNBREAK <input type="checkbox"/> UPBREAK		ON DISPLAY					
CFS I	TYPE STACK:	GATE LENGTH:	RECORD REJECTION:	NOISE REDUCTION:	NOISE THRESHOLD:	CORR. SCALING:	R.C.U. NORM./ALT SW.							
SOURCE	TYPE: <input type="checkbox"/> DYNAMITE <input type="checkbox"/> VIBROSEIS <input type="checkbox"/> OTHER	PATTERN:	NO. OF POSITIONS:	INLINE SPACING:	LATERAL SPACING:	STAGGER:	LENGTH:	WIDTH:	LATERAL OFFSET:					
RECEIVER	CONNECTION:	PATTERN:	RESISTANCE: _____ ohms	STAGGER:	LENGTH:	WIDTH:	LATERAL OFFSET:							
SPREAD	NO. OF GROUPS:	GROUP INTERVAL:	SHOTPOINT INTERVAL:	FOLD:	DIRECTION OF PROGRESSION:		LEADING GROUP:							
	OFFSET GROUP 1:	OFFSET GROUP _____	OFFSET GROUP _____	OFFSET GROUP _____	OFFSET GROUP 48/96:									

DIAGRAMS/MISC. INFORMATION:

SHOTPOINT	TR. _____ to _____		TR. _____ to _____		SHOT				SPREAD			REMARKS	CORR. STACK			
	REEL NO.	REC.	REEL NO.	REC.	SIZE	DEPTH	NO.	OFFSET	DIR	CDP SWITCH	LINE GROUPS		TR 1-48	TR 48-96	TR 1-48	TR 48-96
198	184	1273			110	10.5	41			25	186+1-T 32					
199		1274					42			29	187+1-T 36					
200		1275					43			33	188+1-T 40					
201		1276					44	30W		37	189+1-T 44					
202		1277			110	10.5	45			41	190+1-T 48					
											F.O.L.					