

LAND SEISMIC RECORDING LOG

	CLIENT: Husky	PROSPECT: NPR-4	AREA: Meat Mtn.	LINE NO.: 758	
PARTY NO.: 1186	INS. ENG.: R. Schoel	FN 1278 All ones; FN 1279-1289 Daily Tests; FN 1290 NG		DATE: 3 DAY 10 YR 80	

INSTRUMENT (9-TRACK)	<input checked="" type="checkbox"/> 1 SYSTEM <input type="checkbox"/> 2 SYSTEMS	<input type="checkbox"/> 1-24 & 25-48 <input type="checkbox"/> 1-48 & 49-96	TYPE: <input type="checkbox"/> DFS III <input type="checkbox"/> DFS II <input type="checkbox"/> OTHER	<input checked="" type="checkbox"/> TRACK <input type="checkbox"/> 21 TRACK	FORMAT: B SEG:	<input type="checkbox"/> GAPPED <input type="checkbox"/> UNGAPPED	PACKING DENSITY: (LO) <input type="checkbox"/> 356 BPI (HI) <input type="checkbox"/> 712 BPI <input type="checkbox"/> 800 BPI <input type="checkbox"/> 1600 BPI
NO. BYTES IN HEADER REC: 228	NO. BYTES IN RECORD ID: 24	NO. BYTES PER SCAN: 254	RECORD NUMBERS: <input type="checkbox"/> DEC <input type="checkbox"/> OCT	GAIN CONSTANT: 26 db	INPUT IMPEDANCE: 20,000 ohms		


CONFIGURATION (MAG TAPE)	FIELD TRACE NOS.: 1-96	AUXILIARY DATA: TW SPS TR EM 0
	DATA CHANNEL NOS.: 5-100 (ON MAG TAPE)	AUXILIARY CHANNEL NOS.: 0 1 2 3 4

PARAMETER	RECORD LENGTH: 8 sec	SAMPLE RATE: <input type="checkbox"/> 1 ms <input type="checkbox"/> 4 ms <input type="checkbox"/> 16 ms	GAIN MODE: <input checked="" type="checkbox"/> TFF <input type="checkbox"/> INITIAL <input type="checkbox"/> FINAL <input type="checkbox"/> OPERATE	FILTERS: FREQ. 8 LO CUT HZ SLOPE 18	HI CUT HZ SLOPE 70	NOTCH FILTER: <input type="checkbox"/> IN <input type="checkbox"/> OUT
DISPLAY	MODE: <input checked="" type="checkbox"/> GGC <input type="checkbox"/> FLOAT <input type="checkbox"/> AMPLIFIER <input type="checkbox"/> DEFOAT <input type="checkbox"/> DIRECT	INITIAL GAIN: 0 db	TRIP SENS: 0 db	POLARITY CONVENTION: Pos.	PRESSURE INCREASE ON GEOPHONE: <input type="checkbox"/> NEGATIVE <input type="checkbox"/> POSITIVE	NUMBERS ON MAG TAPE: <input type="checkbox"/> DOWNBREAK <input type="checkbox"/> UPBREAK <input type="checkbox"/> ON DISPLAY

SOURCE	TYPE: Standard Alone	PATTERN: Single Hole	NO. OF POSITIONS:	INLINE SPACING:	LATERAL SPACING:	STAGGER:	LENGTH:	WIDTH:	LATERAL OFFSET:
	<input type="checkbox"/> DYNAMITE <input type="checkbox"/> VIBROSEIS <input type="checkbox"/> OTHER	CHG/HOLE: 110	HOLE DEPTH: 105	SWEEP POSITION:	SWEEP START:	SWEEP END:	SWEEP LENGTH:	SWEEP TAPER:	PHASE COMP:

RECEIVER	TYPE: 2.0D	PATTERN: In Line	NO. OF ELEMENTS: 18	INLINE SPACING: 6'	LATERAL SPACING:
	CONNECTION: Series/Parallel	RESISTANCE: 560 ohms	STAGGER:	LENGTH: 110'	WIDTH: 96



SPREAD	NO. OF GROUPS: 96	GROUP INTERVAL: 110'	SHOTPOINT INTERVAL: 440'	FOLD: 12	DIRECTION OF PROGRESSION: N
	OFFSET GROUP 1: 5225'	OFFSET GROUP 48: 55'	OFFSET GROUP 49: 55'	OFFSET GROUP 96: 5225'	LEADING GROUP: 96



SHOTPOINT	TR 10		TR 10		SHOT				SPREAD		REMARKS	CORR STACK			
	REEL NO.	REC.	REEL NO.	REC.	SIZE	DEPTH	NO.	OFFSET	DIR.	CDP SWITCH		LINE GROUPS	TR 1-48	TR 48-96	TR 1-48
100	984066	1292			110	105	1				T48 - 1144				
101		1293					2				5 T44 - 1124				
102		1294					3				9 T40 - 1134				
103		1295					4				13 T36 - 1144				
104		1296					5				17 T32 - 1154				
105		1297					6	125 SE			21 T28 - 1164				
106		1298					7				25 T24 - 1174				
107		1299					8				29 T20 - 1184				
108		1300					9	40 S			33 T16 - 1194				
109		1301					10				37 T12 - 1204				
110		1302					11				41 T8 - 1214				
111		1303					12				45 T4 - 1224				
112		1304					13				49 100+1 - 1234				
113		1305					14				5 101+1 - 1244				
114		1306					15				9 102+1 - 1254				
115		1307					16				13 103+1 - 1264				
116		1308					17				17 104+1 - 1274				
117		1309					18				21 105+1 - 1284				
118		1310					19				25 106+1 - 1294				
119		1311					20	10520			29 107+1 - 1304				

LAND SEISMIC RECORDING LOG

Page 2 of 3

	CLIENT: Husky	PROSPECT: NPR-4	AREA: Meat Mtn	LINE NO: 758	
	PARTY NO: 1186	INST. ENG: R. Scheel		DATE: MO 3 DAY 10 YR 80	

INSTRUMENT (9-TRACK)	<input type="checkbox"/> 1 SYSTEM <input type="checkbox"/> 2 SYSTEMS	<input type="checkbox"/> 1-24 & 25-48 <input type="checkbox"/> 1-48 & 49-96	ODDS <input type="checkbox"/> EVENS	TYPE: <input type="checkbox"/> DFS III <input type="checkbox"/> DFS IV <input type="checkbox"/> OTHER	<input type="checkbox"/> 9 TRACK <input type="checkbox"/> 21 TRACK	FOPMAT: _____ SEG: _____	<input type="checkbox"/> GAPPED <input type="checkbox"/> UNGAPPED	PACKING DENSITY: (LO) <input type="checkbox"/> 356 BPI <input type="checkbox"/> 800 BPI	(HI) <input type="checkbox"/> 712 BPI <input type="checkbox"/> 1600 BPI	
CONFIGURATION (MAG TAPE)	FIELD TRACE NOS.:				AUXILIARY DATA:				(1) (2) (3) (4) (5) (6) (7)	
PARAMETER	RECORD LENGTH: _____ sec.	SAMPLE RATE: <input type="checkbox"/> 1 ms. <input type="checkbox"/> 4 ms. <input type="checkbox"/> 2 ms. _____ ms.	GAIN MODE: <input type="checkbox"/> INITIAL <input type="checkbox"/> MANUAL <input type="checkbox"/> OPERATE	FILTERS: _____		LO CUT HZ SLOPE: _____	HI CUT HZ SLOPE: _____	NOTCH FILTER: <input type="checkbox"/> IN <input type="checkbox"/> OUT		
DISPLAY	MODE: <input type="checkbox"/> FLOAT <input type="checkbox"/> AMPLIFIER <input type="checkbox"/> DIRECT	INITIAL GAIN: _____ db	TRIP SENS: _____ db	POLARITY CONVENTION: _____		PRESSURE INCREASE ON GEOPHONE: <input type="checkbox"/> NEGATIVE <input type="checkbox"/> POSITIVE	NUMBERS ON MAG. TAPE: _____		<input type="checkbox"/> DOWNBREAK <input type="checkbox"/> UPBREAK	
CFS I	TYPE STACK: _____	GATE LENGTH: _____	RECORD REJECTION: _____	NOISE REDUCTION: _____		NOISE THRESHOLD: _____	CORR. SCALING: _____	R.C.U. NORM/ALT SW.		
SOURCE	TYPE: <input type="checkbox"/> DYNAMITE <input type="checkbox"/> VIBROSEIS <input type="checkbox"/> OTHER	PATTERN: _____	NO. OF POSITIONS: _____	INLINE SPACING: _____	LATERAL SPACING: _____	STAGGER: _____	LENGTH: _____	WIDTH: _____	LATERAL OFFSET: _____	
RECEIVER	CONNECTION: _____	PATTERN: _____	RESISTANCE: _____ ohms	NO. OF ELEMENTS: _____	STAGGER: _____	INLINE SPACING: _____	LENGTH: _____	WIDTH: _____	LATERAL OFFSET: _____	
SPREAD	NO. OF GROUPS: _____	GROUP INTERVAL: _____	SHOTPOINT INTERVAL: _____	FOLD: _____		DIRECTION OF PROGRESSION: _____		LEADING GROUP: _____		

DIAGRAMS/MISC. INFORMATION:

SHOTPOINT	TR. _____ to _____		TR. _____ to _____		SHOT				SPREAD				REMARKS	CORR STACK			
	REEL NO.	REC.	REEL NO.	REC.	SIZE	DEPTH	NO.	OFFSET	DIP	CDP SWITCH	LINE GROUPS			SET UP	TR 1-48	TR 49-96	
120	984067	1312			110	105	21			33	108+1	-	131+4	2			
121		1313					22			37	109+1	-	132+4				
122		1314					23	40 W		41	110+1	-	133+4				
123		1315					24			45	111+1	-	134+4				
124		1316					25	65 NE		49	112+1	-	135+4				
125		1317					26			5	113+1	-	136+4	3			
126		1318					27			9	114+1	-	137+4				
127		1319					28			13	115+1	-	138+4				
128		1320					29			17	116+1	-	139+4				
129		1321					30	30 W		21	117+1	-	140+4				
130		1322					31			25	118+1	-	141+4				
131		1323					32			29	119+1	-	142+4				
132		1324					33			33	120+1	-	143+4				
133		1325					34			37	121+1	-	144+4				
134		1326					35			41	122+1	-	145+4				
135		1327					36	250 S		45	123+1	-	146+4				
136	984066	1328					37			49	124+1	-	147+4				
137	984067	1330					38	185 N		5	125+1	-	148+4	4			
138		1331					39			9	126+1	-	149+4				
139		1332					40			13	127+1	-	150+4				



SP128+33/4 steep drop-off
SP132-134 on top of ridge

Recorder @ SP130

Recorder @ SP142; RN 1329 All Ones

LAND SEISMIC RECORDING LOG

Page 3 of 3

	CLIENT: Husky	PROSPECT: NPR-4	AREA: Meat Mtn.	LINE NO: 758								
	PARTY NO: 1186	INST. TAG: R. School		DATE: MO. 3 DAY 10 YE 80								
INSTRUMENT (9-TRACK)	<input type="checkbox"/> 1 SYSTEM <input type="checkbox"/> 2 SYSTEMS	<input type="checkbox"/> 1-24 & 25-48 <input type="checkbox"/> 1-48 & 49-96	ODDS & EVENS <input type="checkbox"/>	TYPE: <input type="checkbox"/> DFS III <input type="checkbox"/> DFS IV <input type="checkbox"/> OTHER	<input type="checkbox"/> 9 TRACK <input type="checkbox"/> 21 TRACK	FORMAT: _____	<input type="checkbox"/> GAPPED <input type="checkbox"/> UNGAPPED	PACKING DENSITY: (L) <input type="checkbox"/> 356 BPI <input type="checkbox"/> 800 BPI (H) <input type="checkbox"/> 712 BPI <input type="checkbox"/> 1600 BPI				
	NO. BYTES IN HEADER REC: _____	NO. BYTES IN RECORD ID: _____	NO. BYTES PER SCAN: _____	RECORD NUMBERS: <input type="checkbox"/> DEC <input type="checkbox"/> OCT	GAIN CONSTANT: _____ db	INPUT IMPEDANCE: _____ ohms	(1)	(2)	(3)	(4)	(5)	(6)
CONFIGURATION (MAG TAPE)	FIELD TRACE NOS: _____				AUXILIARY DATA: _____				AUXILIARY CHANNEL NOS: _____			
PARAMETER	RECORD LENGTH: _____ sec	SAMPLE RATE: <input type="checkbox"/> 1 ms <input type="checkbox"/> 4 ms <input type="checkbox"/> 2 ms <input type="checkbox"/> _____ ms	GAIN MODE: <input type="checkbox"/> INITIAL <input type="checkbox"/> MANUAL <input type="checkbox"/> IFF <input type="checkbox"/> FINAL <input type="checkbox"/> OPERATE	FILTERS: _____	LO CUT _____	HI CUT _____	NOTCH FILTER: <input type="checkbox"/> IN <input type="checkbox"/> OUT					
DISPLAY	MODE: <input type="checkbox"/> AGC <input type="checkbox"/> DEFOAT <input type="checkbox"/> DIRECT	AMPLIFIER <input type="checkbox"/>	INITIAL GAIN: _____ db	TRIP SENS: _____ db	POLARITY CONVENTION: _____	PRESSURE INCREASE ON GEOPHONE: <input type="checkbox"/> NEGATIVE <input type="checkbox"/> POSITIVE	NUMBERS ON MAG. TAPE: <input type="checkbox"/>	DOWNBREAK <input type="checkbox"/>	UPBREAK <input type="checkbox"/>	ON DISPLAY		
CFS I	TYPE STACK: _____	GATE LENGTH: _____	RECORD REJECTION: _____	NOISE REDUCTION: _____	NOISE THRESHOLD: _____	CORR. SCALING: _____	R.C.U. NORM./ALT SW: _____					
SOURCE	TYPE: <input type="checkbox"/> DYNAMITE <input type="checkbox"/> VIBROSEIS <input type="checkbox"/> OTHER	PATTERN: _____	NO. OF POSITIONS: _____	INLINE SPACING: _____	LATERAL SPACING: _____	STAGGER: _____	LENGTH: _____	WIDTH: _____	LATERAL OFFSET: _____			
RECEIVER	CONNECTION: _____	PATTERN: _____	RESISTANCE: _____ ohms	STAGGER: _____	INLINE SPACING: _____	LENGTH: _____	WIDTH: _____	LATERAL OFFSET: _____				
SPREAD	NO. OF GROUPS: _____	GROUP INTERVAL: _____	SHOTPOINT INTERVAL: _____	OFFSET GROUP: _____	OFFSET GROUP 48/96: _____	FOLD: _____	DIRECTION OF PROGRESSION: _____					

DIAGRAMS/MISC. INFORMATION:

SHOTPOINT	TR _____ to _____		TR _____ to _____		SHOT				SPREAD				REMARKS:	CORR. STACK			
	REEL NO.	REC.	REEL NO.	REC.	SIZE	DEPTH	NO.	OFFSET	DIR	CDP SWITCH	LINE GROUPS			SET	TR 1-48	TR 48-96	
1140	99406	1338	17	2223	202	2930	30	33	37	5	17	128+1	-	151+4	4		
1141		1335								N	21	129+1	-	152+4			
1142		1336									25	130+1	-	153+4			
1143		1337									29	131+1	-	154+4			
1144		1338									33	132+1	-	155+4			
1145		1339									37	133+1	-	156+4			
1146		1340									41	134+1	-	157+4			
1147		1341									45	135+1	-	158+4			
1148		1342									49	136+1	-	159+4			
1149		1343									5	137+1	-	160+4	5		Recorder @ SP 154
1150		1344									9	138+1	-	161+4			
1151		1345									13	139+1	-	162+4			
1152		1346									17	140+1	-	163+4			
1153		1347									21	141+1	-	164+4			
1154		1348									25	142+1	-	165+4			
1155		1349									29	143+1	-	166+4			
1156		1350									33	144+1	-	167+4			
1157		1351									37	145+1	-	168+4			
1158		1352									41	146+1	-	169+4			
1159		1353									45	147+1	-	170+4			
160		1354									49	148+1	-	171+4			

Strong Winds

FN133 NG

SP155 in Creek bottom

SP167+3 replotted

(Bare rock & steep slope)
from SP1160 to 175

LAND SEISMIC RECORDING LOG

1 of 1

	CLIENT: Husky	PROSPECT: NPR-4	AREA: Meg Mth	LINE NO: -758	
	PARTY NO: 1186	INST. ENG: Streff		DATE: MO 3 DAY 11 YE 80	

INSTRUMENT (9-TRACK)	<input checked="" type="checkbox"/> SYSTEM SYSTEMS <input type="checkbox"/> 1-24 & 25-48 <input type="checkbox"/> 48 & 49-96	<input checked="" type="checkbox"/> ODDS EVENTS <input type="checkbox"/> 1-24 <input type="checkbox"/> 25-48 <input type="checkbox"/> 49-96	TYPE: <input type="checkbox"/> DFS III <input type="checkbox"/> DFS III <input type="checkbox"/> DFS III <input type="checkbox"/> OTHER	<input checked="" type="checkbox"/> TRACK <input type="checkbox"/> 21 TRACK	FORMAT: SEG A <input type="checkbox"/> TRACK <input type="checkbox"/> TRACK	<input type="checkbox"/> GAPPED <input type="checkbox"/> UNGAPPED	PACKING DENSITY: (L) <input type="checkbox"/> 356 BPI <input type="checkbox"/> 800 BPI (H) <input type="checkbox"/> 712 BPI <input type="checkbox"/> 1600 BPI
	NO. BYTES IN HEADER REC: 228	NO. BYTES IN RECORD ID: 24	NO. BYTES PER SCAN: 254	RECORD NUMBERS: <input checked="" type="checkbox"/> DEC <input type="checkbox"/> OCT	GAIN CONSTANT: 36 db	INPUT IMPEDANCE: 20000 ohms	

CONFIGURATION (MAG TAPE)	FIELD TRACE NOS.: 1-96 DATA CHANNEL NOS.: 5-100 (ON MAG TAPE)	AUXILIARY DATA: (1) 2 (2) 1 (3) 2 (4) 3 (5) 4 (6) 0 (7) 0 AUXILIARY CHANNEL NOS.: TW SPS TO EM 0	
PARAMETER	RECORD LENGTH: 8 sec SAMPLE RATE: <input type="checkbox"/> 1 ms <input type="checkbox"/> 4 ms <input type="checkbox"/> 2 ms <input type="checkbox"/> 8 ms	GAIN MODE: <input type="checkbox"/> INITIAL <input type="checkbox"/> MANUAL <input type="checkbox"/> FINAL <input type="checkbox"/> OPERATE	FILTERS: FREQ. 8 LO CUT HZ SLOPE 18 HI CUT HZ SLOPE 70 NOTCH FILTER: <input type="checkbox"/> IN <input type="checkbox"/> OUT
DISPLAY	MODE: <input type="checkbox"/> FLOAT <input type="checkbox"/> AMPLIFIER <input checked="" type="checkbox"/> LOG <input type="checkbox"/> DEFLAT <input type="checkbox"/> DIRECT	INITIAL GAIN: 0 db TRIP SENS: 0 db	POLARITY CONVENTION: PAS PRESSURE INCREASE ON GEOPHONE: <input type="checkbox"/> NEGATIVE <input checked="" type="checkbox"/> POSITIVE
CFS I	TYPE STACK: STAND ALONE II	RECORD REJECTION:	NOISE REDUCTION: NOISE THRESHOLD: CORR. SCALING: R.C.U. NORM/ALT SW.

SOURCE	TYPE: <input checked="" type="checkbox"/> DYNAMITE <input type="checkbox"/> VIBROSEIS <input type="checkbox"/> OTHER	PATTERN: inline - hole CHG/ HOLE: 110 HOLE DEPTH: 105	NO. OF POSITIONS: SWEEP POSITION:	INLINE SPACING: SWEEP START:	LATERAL SPACING: SWEEP END:	STAGGER: SWEEP LENGTH:	LENGTH: SWEEP TAPER:	WIDTH: PHASE COMP:	LATERAL OFFSET:
--------	--	---	--------------------------------------	---------------------------------	--------------------------------	---------------------------	-------------------------	-----------------------	-----------------

RECEIVER	TYPE: 20-0 CONNECTION: Series-Parallel	PATTERN: inline RESISTANCE: 560 ohms	NO. OF ELEMENTS: 18 STAGGER:	INLINE SPACING: 6' LENGTH: 110'	LATERAL SPACING: WIDTH:	LATERAL OFFSET:
----------	---	---	--	--	----------------------------	-----------------

SPREAD	NO. OF GROUPS: 96 OFFSET GROUP 1: 5225	GROUP INTERVAL: 110 OFFSET GROUP: 48 55	SHOTPOINT INTERVAL: 440 OFFSET GROUP: 49 55	FOLD: 12 OFFSET GROUP 48/96: 5225	DIRECTION OF PROGRESSION: North LEADING GROUP: 96
--------	---	--	--	--	--

DIAGRAMS/MISC. INFORMATION:
 TR#1 ¹¹⁹ 9xxxx9 ¹⁵⁰ ^{SP 161} ¹⁷² 9xxxx9 ¹⁷³
 #1355 - #1365 + 595
 #1366 - 1367 + 570

SHOTPOINT	TR 1 to		TR 2 to		SHOT		SPREAD		REMARKS	CORR. STACK			
	REEL NO.	REC.	REEL NO.	REC.	SIZE	DEPTH	NO.	OFFSET		DIR.	CDP SWITCH	LINE GROUPS	TR 1-16
1161	984067	1368			110	105	1			5	149+1 - 172+4		
1162		1369			110	105	2			9	150+1 - 173+4		
1163		1370			110	105	3	50 SW		13	151+1 - 174+4		
1164		1371			110	105	4	30 E		5	152+1 - 175+4		
1165		1372			110	105	5	60 NE		9	153+1 - 176+4		
1166		1373			110	105	6	35 N		13	154+1 - 177+4		
1167		1374			110	105	7			17	155+1 - 178+4		
1168		1375			110	105	8			21	156+1 - 179+4		
1169		1376			110	105	9	75 N		25	157+1 - 180+4		
1170		1377			110	105	10	40 W		29	158+1 - 181+4		
1171		1378			110	105	11	80 W		37	160+1 - 183+4		
1172		1380			110	105	12	80 E		45	162+1 - 185+4		
1173	984068	1382			110	105	13	50 W		9	159+1 - 182+4		
1174		1383			110	105	14	30 SW		17	160+1 - 184+4		
1175		1384			110	105	15	50 NW		25	163+1 - 186+4		
1176		1385			110	105	16			29	164+1 - 187+4		
1177		1386			110	105	17	45 W		33	165+1 - 188+4		
1178		1388			110	105	18			37	166+1 - 189+4		
1179		1389			110	105	19	35 E		41	167+1 - 190+4		
1180		1390			110	105	20	90 S		45	168+1 - 191+4		

REMARKS: High wind on ridges
 Recorder @ SP-169
 Noisy GROUPS on loose rock, steep slope SP160-SP175
 Recorder @ SP-169
 STACKED ON 170 #1379 N.G.
 STACKED ON SP170
 TAPECHANGE #1381 ALL ONES
 STACKED ON SP-175
 #1387 - N.G.

LAND SEISMIC RECORDING LOG

20 of 2

	CLIENT: HUSKY	PROSPECT: NPR-4	AREA: Meat mtn	LINE NO: 758	
PARTY NO: 1186		INST. ENG: Stroff		DATE: MO 3 DAY 11 YR 80	

INSTRUMENT (9-TRACK)	<input type="checkbox"/> 1 SYSTEM <input type="checkbox"/> 2 SYSTEMS	<input type="checkbox"/> 1-24 & 25-48 <input type="checkbox"/> 1-48 & 49-96	CODES EVENTS	TYPE: <input type="checkbox"/> DFS III <input type="checkbox"/> DFS IV <input type="checkbox"/> DFS V <input type="checkbox"/> OTHER	<input type="checkbox"/> 9 TRACK <input type="checkbox"/> 21 TRACK	FORMAT: SEG	<input type="checkbox"/> GAPPED <input type="checkbox"/> UNGAPPED	PACKING DENSITY:	(LO) <input type="checkbox"/> 356 BPI <input type="checkbox"/> 800 BPI	(HI) <input type="checkbox"/> 732 BPI <input type="checkbox"/> 1400 BPI	
NO. BYTES IN HEADER REC:		NO. BYTES IN RECORD ID:		NO. BYTES PER SCAN:		RECORD NUMBERS: <input type="checkbox"/> DEC. <input type="checkbox"/> OCT.		GAIN CONSTANT: _____ db		INPUT IMPEDANCE: _____ ohms	
CONFIGURATION (MAG TAPE)						AUXILIARY DATA:					
FIELD TRACE NOS.:						AUXILIARY CHANNEL NOS.:					
DATA CHANNEL NOS.:						(ON MAG TAPE)					
PARAMETER		RECORD LENGTH: _____ sec.		SAMPLE RATE: <input type="checkbox"/> 1 ms. <input type="checkbox"/> 4 ms. <input type="checkbox"/> 2 ms. <input type="checkbox"/> _____ ms.		GAIN MODE: <input type="checkbox"/> INITIAL <input type="checkbox"/> MANUAL <input type="checkbox"/> OPERATE <input type="checkbox"/> IFP <input type="checkbox"/> FINAL		FILTERS: FREQ. _____		LO CUT HZ SLOPE _____	
DISPLAY		MODE: <input type="checkbox"/> FLOAT <input type="checkbox"/> AMPLIFIER <input type="checkbox"/> AGC <input type="checkbox"/> DEFOAT <input type="checkbox"/> DIRECT		INITIAL GAIN: _____ db		JRP SENS: _____ db		POLARITY CONVENTION: _____		PRESSURE INCREASE ON GEOPHONE: <input type="checkbox"/> NEGATIVE <input type="checkbox"/> POSITIVE	
CFS I		TYPE STACK:		GATE LENGTH:		RECORD REJECTION:		NOISE REDUCTION:		CORR. SCALING: _____	
SOURCE		TYPE: <input type="checkbox"/> DYNAMITE <input type="checkbox"/> VIBROSEIS <input type="checkbox"/> OTHER		PATTERN:		NO. OF POSITIONS:		INLINE SPACING:		LATERAL SPACING:	
RECEIVER		CONNECTION:		RESISTANCE: _____ ohms		STAGGER:		INLINE SPACING:		LATERAL SPACING:	
SPREAD		NO. OF GROUPS:		GROUP INTERVAL:		SHOTPOINT INTERVAL:		FOLD:		DIRECTION OF PROGRESSION:	
		OFFSET GROUP 1:		OFFSET GROUP _____		OFFSET GROUP _____		OFFSET GROUP 48/96:		LEADING GROUP:	

DIAGRAMS/MISC. INFORMATION:

SHOTPOINT	TR _____ to _____		TR _____ to _____		SHOT					SPREAD			REMARKS	CORR. STACK		
	REEL NO.	REC.	REEL NO.	REC.	SIZE	DEPTH	NO.	OFFSET	DIR.	CDP SWITCH	LINE GROUPS			ST	TR 1-48	TR 48-96
181	98406	1391	17	22	110	105	21	40	S	5	170+1-193+4	4	STACKED ON SP-180			
182		1392			110	105	22	110	S	5	170+1-193+4	4	Recorder @ SP 187			
183		1393			110	105	23			9	171+1-194+4					
184		1394			110	105	24			13	172+1-195+4					
185		1395			110	105	25			17	173+1-196+4					
186		1396			110	105	26	30	N	21	174+1 - T-4					
187		1397			110	105	27	185	N	25	175+1 - T-8					
188		1398			110	105	28			29	176+1 - T-12					
189		1399			110	105	29			33	177+1 - T-16					
190		1400			110	105	30			37	178+1 - T-20					
191		1401			110	105	31			41	179+1 - T-24					
192		1402			110	105	32			45	180+1 - T-28					
193		1403			110	105	33			49	181+1 - T-32					
194		1404			110	105	34			29	182+1 - T-36	5	Recorder @ SP-193			
195		1405			110	105	35			33	183+1 - T-40					
196		1406			110	105	36			37	184+1 - T-44					
197		1407			110	105	37			41	185+1 - T-48					