



LAND SEISMIC RECORDING LOG

	CLIENT: Husky	PROSPECT: NPR-4	AREA: Foothills Thrust	LINE NO: 760							
PARTY NO: 1186		INST. ENG: R. Scheel		DATE: MO 2 DAY 14 YR 80							
INSTRUMENT (9-TRACK)	<input type="checkbox"/> 1 SYSTEM <input type="checkbox"/> 2 SYSTEMS	<input type="checkbox"/> 1-24 & 25-48 <input type="checkbox"/> 1-48 & 49-96	ODDS & EVENS	TYPE: <input type="checkbox"/> DFS III <input type="checkbox"/> DFS IX	<input type="checkbox"/> DFS X <input type="checkbox"/> OTHER	<input type="checkbox"/> 9 TRACK <input type="checkbox"/> 21 TRACK	FORMAT: _____ SEG	<input type="checkbox"/> GAPPED <input type="checkbox"/> UNGAPPED	PACKING DENSITY:	(LO) <input type="checkbox"/> 356 BPI <input type="checkbox"/> 800 BPI	(HI) <input type="checkbox"/> 712 BPI <input type="checkbox"/> 1600 BPI
	NO. BYTES IN HEADER REC: _____	NO. BYTES IN RECORD ID: _____	NO. BYTES PER SCAN: _____	RECORD NUMBERS: _____	<input type="checkbox"/> DEC. <input type="checkbox"/> OCT	GAIN CONSTANT: _____ db	INPUT IMPEDANCE: _____ ohms				
CONFIGURATION (MAG TAPE)	FIELD TRACE NOS: _____					AUXILIARY DATA: _____					
	DATA CHANNEL NOS: _____ (ON MAG TAPE)					AUXILIARY CHANNEL NOS: _____					
PARAMETER	RECORD LENGTH: _____ sec.	SAMPLE RATE: <input type="checkbox"/> 1 ms. <input type="checkbox"/> 4 ms. <input type="checkbox"/> 2 ms. <input type="checkbox"/> _____ ms.	GAIN MODE: <input type="checkbox"/> INITIAL <input type="checkbox"/> IFP	<input type="checkbox"/> MANUAL <input type="checkbox"/> OPERATE	FILTERS: _____	LO CUT HZ SLOPE	FREQ. _____	HI CUT HZ SLOPE	NOTCH FILTER: <input type="checkbox"/> IN <input type="checkbox"/> OUT		
DISPLAY	MODE: <input type="checkbox"/> FLOAT <input type="checkbox"/> AMPLIFIER <input type="checkbox"/> AGC <input type="checkbox"/> DELOAD <input type="checkbox"/> DIRECT	INITIAL GAIN: _____ db	TRIP SENS: _____ db	RECORD REJECTION: _____	POLARITY CONVENTION: _____	PRESSURE INCREASE ON GEOPHONE: _____	<input type="checkbox"/> NEGATIVE <input type="checkbox"/> POSITIVE	NUMBERS ON ON MAG TAPE	<input type="checkbox"/> DOWNBREAK <input type="checkbox"/> UPBREAK	ON DISPLAY	
CFS I	TYPE STACK: _____	GATE LENGTH: _____	NOISE REDUCTION: _____	NOISE THRESHOLD: _____	CORR. SCALING: _____	R.C.U. NORM/ALT SW.					
SOURCE	<input type="checkbox"/> DYNAMITE <input type="checkbox"/> VIBROSEIS <input type="checkbox"/> OTHER	PATTERN: _____	NO. OF POSITIONS: _____	INLINE SPACING: _____	LATERAL SPACING: _____	STAGGER: _____	LENGTH: _____	WIDTH: _____	LATERAL OFFSET: _____		
	CHG/HOLE: _____	HOLE DEPTH: _____	SWEEP POSITION: _____	SWEEP START: _____	SWEEP END: _____	SWEEP LENGTH: _____	SWEEP TAPER: _____	PHASE COMP. _____			
RECEIVER	TYPE: _____	PATTERN: _____	NO. OF ELEMENTS: _____	INLINE SPACING: _____	LATERAL SPACING: _____	STAGGER: _____	LENGTH: _____	WIDTH: _____	LATERAL OFFSET: _____		
	CONNECTION: _____	RESISTANCE: _____ ohms	STAGGER: _____	LENGTH: _____	WIDTH: _____	LATERAL OFFSET: _____					
SPREAD	NO. OF GROUPS: _____	GROUP INTERVAL: _____	SHOTPOINT INTERVAL: _____	FOLD: _____	DIRECTION OF PROGRESSION: _____						
	OFFSET GROUP 1: _____	OFFSET GROUP _____	OFFSET GROUP _____	OFFSET GROUP 48/96: _____	LEADING GROUP: _____						

DIAGRAMS/MISC. INFORMATION:

SHOTPOINT	TR _____ to _____		TR _____ to _____		SHOT				SPREAD				REMARKS:	CORR. STACK					
	REEL NO.	REC.	REEL NO.	REC.	SIZE	DEPTH	NO.	OFFSET	DIR.	CDP SWITCH	LINE GROUPS			SET	TR 1-24	TR 48-96	TR 1-24	TR 48-96	
															HY	REC	HY	REC	
120	994036	34	2223	26	110	105	21	35	37		33	108H	-	1344	2				
121		35			110	105	22				37	109H	-	1324					
122		36			110	105	23				41	110H	-	1334					
123		37			110	105	24				45	111H	-	1344					
124		38			110	105	25				49	112H	-	1354					
125					110	105	26				5	113H	-	1364	3	Recorder @ SP 30			
126					110	105	27					114H	-	1374					
127					110	105	28					115H	-	1384					
128					110	105	29					116H	-	1394					
129					110	105	30					117H	-	1404					

LAND SEISMIC RECORDING LOG

1 of 5

	CLIENT: Husky	PROSPECT: NPR-4	AREA: Foot hills Thrust	LINE NO: 760											
PARTY NO: 1186		INST. ENG.: Streiff		DATE: MO 2 DAY 15 YR 80											
INSTRUMENT (9-TRACK)	<input checked="" type="checkbox"/> SYSTEM <input type="checkbox"/> 2 SYSTEMS	<input checked="" type="checkbox"/> 1-24 & 25-48 <input checked="" type="checkbox"/> 48 & 49-96	ODDS EVENS	TYPE: <input type="checkbox"/> DFS III <input type="checkbox"/> DFS IV	<input checked="" type="checkbox"/> TRACK <input type="checkbox"/> 21 TRACK	FORMAT: SEG B3	<input type="checkbox"/> GAPPED <input type="checkbox"/> UNGAPPED	PACKING DENSITY: (L0) <input type="checkbox"/> 356 BPI (H1) <input type="checkbox"/> 712 BPI (L) <input type="checkbox"/> 3000 BPI	NO. BYTES IN RECORD ID: 24		NO. BYTES PER SCAN: 254	RECORD NUMBERS: <input type="checkbox"/> DEC <input type="checkbox"/> OCT	GAIN CONSTANT: 3.6 db	INPUT IMPEDANCE: 2000 ohms	
	NO. BYTES IN HEADER REC: 288	FIELD TRACE NOS: 1-96		AUXILIARY DATA: (1) 0 (2) 1 (3) 2 (4) 3 (5) 4 (6) 0 (7) 0		AUXILIARY CHANNEL NOS: TW SPS TB EM 0									
CONFIGURATION (MAG TAPE)	DATA CHANNEL NOS.: 5-100		(ON MAG TAPE)												
PARAMETER	RECORD LENGTH: 8 sec	SAMPLE RATE: <input type="checkbox"/> 1 ms <input type="checkbox"/> 4 ms	GAIN MODE: <input type="checkbox"/> INITIAL <input type="checkbox"/> MANUAL <input type="checkbox"/> OPERATE		FILTERS: FREQ. 8 LO CUT 18 HZ SLOPE 18		FREQ. 128 HI CUT 70 HZ SLOPE 70		NOTCH FILTER: <input type="checkbox"/> IN <input type="checkbox"/> OUT						
DISPLAY	MODE: <input type="checkbox"/> FLOAT <input type="checkbox"/> AMPLIFIER <input checked="" type="checkbox"/> TRACE <input type="checkbox"/> DEFOAT <input type="checkbox"/> DIRECT	INITIAL GAIN: 0 db	TRIP SENS: 0 db		POLARITY CONVENTION: POS		PRESSURE INCREASE ON GEOPHONE: <input type="checkbox"/> NEGATIVE <input checked="" type="checkbox"/> POSITIVE		NUMBERS ON MAG TAPE: <input type="checkbox"/> DOWNBREAK <input type="checkbox"/> UPBREAK		ON DISPLAY				
CPSI	STACK: STANDALONE		GATE LENGTH:		NOISE REDUCTION:		NOISE THRESHOLD:		CORR SCALING:		R.C.U. NORM./ALT SW.				
SOURCE	TYPE: <input type="checkbox"/> DYNAMITE <input type="checkbox"/> VIBROSEIS <input type="checkbox"/> OTHER		PATTERN: inline/hole		NO. OF POSITIONS:		INLINE SPACING:		LATERAL SPACING:		STAGGER:		LENGTH:		
RECEIVER	TYPE: 30-D		PATTERN: inline		NO. OF ELEMENTS: 18		INLINE SPACING: 6		LATERAL SPACING:		STAGGER:		LENGTH: 110		
SPREAD	NO. OF GROUPS: 96		GROUP INTERVAL: 110		SHOTPOINT INTERVAL: 440		FOLD: 12		DIRECTION OF PROGRESSION: South		LEADING GROUP: 96				
DIAGRAMS/MISC. INFORMATION:		SP113 4 x x x x		SP114 4		SP135 4		SP135 4 x x x x		SP136 #59 - 50 + 5 x 5		SP136 #51 test TB			

SHOTPOINT	TR 10		TR 10		SHOT		SPREAD		REMARKS	CORR STACK				
	REEL NO.	REC.	REEL NO.	REC.	SIZE	DEPTH	NO.	OFFSET		DIR	CDP SWITCH	LINE GROUPS	SET UP	YET TO REC.
1125	98401316	152			110	105	1	135	S	5	130+1 - 136+4	1		
1126		153			110	105	2	120	S	9	114+1 - 137+4			
1127		154			110	105	3	115	S	13	115+1 - 138+4			
1128		155			110	105	4	135	S	17	116+1 - 139+4			
1129		156			110	105	5	215	S	21	117+1 - 140+4			
1130		157			110	105	6	11	S	25	118+1 - 141+4			
1131		158			110	105	7	11	S	29	119+1 - 142+4			
1132	98401317	160			110	105	8	11	S	33	120+1 - 143+4			
1133		161			110	105	9	135	N	37	121+1 - 144+4			
1134		162			110	105	10	120	SW	41	122+1 - 145+4			
1135		163			110	105	11	245	S	45	123+1 - 146+4			
1136		164			110	105	12	11	S	49	124+1 - 147+4			
1137		165			110	105	13	11	S	5	125+1 - 148+4	2		
1138		166			110	105	14	11	S	9	126+1 - 149+4			
1139		167			110	105	15	85	N	13	127+1 - 150+4			
1140		168			110	105	16	165	N	17	128+1 - 151+4			
1141		169			110	105	17	175	S	21	129+1 - 152+4			
1142		170			110	105	18	11	S	25	130+1 - 153+4			
1143		171			110	105	19	75	S	29	131+1 - 154+4			
1144		172			110	105	20	125	E	33	132+1 - 155+4			

Recorder @ SP 130

TR# 2,3,4 dead - Backcrew picking up early

TR#1 dead

#59 allones tape change

Recorder @ SP-142

TR#14 noisy

G.P-153 +4 96 Reversed for 24 shots

SP 142 → 16.5 92"

OB H 1-48 SLASH

LAND SEISMIC RECORDING LOG

2 of 5



CLIENT: Husky	PROSPECT: NPR-4	AREA: Foot hills Thrust	LINE NO.: 760
PARTY NO.: 1186	INST. ENG.: Streff		DATE: NO 2 DAY 15 TR 80

INSTRUMENT	<input type="checkbox"/> 1 SYSTEM <input type="checkbox"/> 2 SYSTEMS	<input type="checkbox"/> 1-24 & 25-48 <input type="checkbox"/> 1-48 & 49-96	ODDS & EVENS	TYPE: <input type="checkbox"/> DFS III <input type="checkbox"/> DFS II	<input type="checkbox"/> 9 TRACK <input type="checkbox"/> 21 TRACK	FORMAT: SEG	<input type="checkbox"/> GAPPED <input type="checkbox"/> UNGAPPED	PACKING DENSITY: (L0) <input type="checkbox"/> 356 BPI (H1) <input type="checkbox"/> 712 BPI <input type="checkbox"/> 800 BPI <input type="checkbox"/> 1600 BPI	
(9-TRACK)	NO. BYTES IN HEADER REC:	NO. BYTES IN RECORD ID:	NO. BYTES PER SCAN:	RECORD NUMBERS: <input type="checkbox"/> DEC. <input type="checkbox"/> OCT	GAIN CONSTANT: _____ db	INPUT IMPEDANCE: _____ ohms.	(1) _____ (2) _____ (3) _____ (4) _____ (5) _____ (6) _____ (7) _____	AUXILIARY DATA:	
CONFIGURATION (MAG TAPE)	FIELD TRACE NOS.:			DATA CHANNEL NOS.:			(ON MAG TAPE)		
PARAMETER	RECORD LENGTH: _____ sec	SAMPLE RATE: <input type="checkbox"/> 1 ms. <input type="checkbox"/> 4 ms. <input type="checkbox"/> 2 ms. <input type="checkbox"/> _____ ms.	GAIN MODE: <input type="checkbox"/> INITIAL <input type="checkbox"/> MANUAL <input type="checkbox"/> IFP <input type="checkbox"/> FINAL <input type="checkbox"/> OPERATE	FILTERS: _____	LO CUT HZ SLOPE: _____	FREQ. _____	HI CUT HZ SLOPE: _____	NOTCH FILTER: <input type="checkbox"/> IN <input type="checkbox"/> OUT	
DISPLAY	MODE: <input type="checkbox"/> AGC <input type="checkbox"/> FLOAT <input type="checkbox"/> AMPLIFIER <input type="checkbox"/> DEFLOAT <input type="checkbox"/> DIRECT	INITIAL GAIN: _____ db	TRIP SENS: _____ db	POLARITY CONVENTION: _____	PRESSURE INCREASE ON GEOPHONE: _____	<input type="checkbox"/> NEGATIVE <input type="checkbox"/> POSITIVE	NUMBERS ON ON MAG TAPE	<input type="checkbox"/> DOWNBREAK <input type="checkbox"/> UPBREAK ON DISPLAY	
CFS I	TYPE STACK:	GATE LENGTH:	RECORD REJECTION:	NOISE REDUCTION:	NOISE THRESHOLD:	CORR. SCALING:	R.C.U. NORM/ALT SW.		
SOURCE	TYPE: <input type="checkbox"/> DYNAMITE <input type="checkbox"/> VIBROSEIS <input type="checkbox"/> OTHER	PATTERN:	NO. OF POSITIONS:	INLINE SPACING:	LATERAL SPACING:	STAGGER:	LENGTH:	WIDTH:	LATERAL OFFSET:
RECEIVER	CONNECTION:	RESISTANCE: _____ ohms	STAGGER:	LENGTH:	WIDTH:	LATERAL OFFSET:			
SPREAD	NO. OF GROUPS:	GROUP INTERVAL:	SHOTPOINT INTERVAL:	FOLD:	DIRECTION OF PROGRESSION:				
	OFFSET GROUP 1:	OFFSET GROUP _____	OFFSET GROUP _____	OFFSET GROUP 48/96:	LEADING GROUP:				

DIAGRAMS/MISC. INFORMATION:

SHOTPOINT	TR. _____ to _____		TR. _____ to _____		SHOT				SPREAD			REMARKS:	CORR. STACK			
	REEL NO.	REC.	REEL NO.	REC.	SIZE	DEPTH	NO.	OFFSET	DIR.	CDP SWITCH	LINE GROUPS		SET UP	TR 1-48	TR 48-96	TR 96-144
1145	784037	73			110	105	24			37	133+1 - 156+4	2				
1146		74			110	105	22			41	134+1 - 157+4					
1147		75			110	105	23			45	135+1 - 158+4					
1148		77			110	105	24			49	136+1 - 159+4					
1149		78			110	105	25			5	137+1 - 160+4	3	# 76 NG.			
1150		79			110	105	26			9	138+1 - 161+4		Recorder @ SP154			
1151		80			110	105	27			13	139+1 - 162+4		49-96 SLASH			
1152		81			110	105	27			17	140+1 - 163+4		" 56 "			
1153		82			110	105	29	30	E	21	141+1 - 164+4		49-96 SLASH			
1154		83			110	105	30			25	142+1 - 165+4		" 48 "			
1155		84			110	105	30			29	143+1 - 166+4		49-96 "			
1156		85			110	105	32	126	W	33	144+1 - 167+4		" 40 "			
1157		86			110	105	33	150	SE	37	145+1 - 168+4		" 36 "			
1158		87			110	105	34	25	N	41	146+1 - 169+4		" 32 "			
1159		88			110	105	35	25	S	45	147+1 - 170+4		" 28 "			
1160		89			160	105	36	2	HOLE 8	49	148+1 - 171+4		" 24 "			
1161		90			110	105	37			5	149+1 - 172+4	#	Recorder @ SP166			
1162		91			110	105	38			9	150+1 - 173+4		# 37 noisy ✓			
1163		92			110	105	39			13	151+1 - 174+4		# 33 noisy ✓			
1164		93			110	105	40			17	152+1 - 175+4		TR 29 "			

LAND SEISMIC RECORDING LOG

3 of 5



CLIENT: Husky PROSPECT: NPR-4 AREA: _____
 PARTY NO.: 1186 INST. ENG.: Streff LINE NO.: 760
 DATE: MO 2 DAY 15 YR 80

INSTRUMENT (9-TRACK)	<input type="checkbox"/> 1 SYSTEM <input type="checkbox"/> 2 SYSTEMS	<input type="checkbox"/> 1-24 & 25-48 <input type="checkbox"/> 1-48 & 49-96	<input type="checkbox"/> ODDS <input type="checkbox"/> EVENS	TYPE: <input type="checkbox"/> DFS III <input type="checkbox"/> DFS IV <input type="checkbox"/> OTHER	<input type="checkbox"/> 9 TRACK <input type="checkbox"/> 21 TRACK	FOPMAT: SEG	<input type="checkbox"/> GAPPED <input type="checkbox"/> UNGAPPED	PACKING DENSITY: (L0) <input type="checkbox"/> 356 BPI (H1) <input type="checkbox"/> 712 BPI (H2) <input type="checkbox"/> 1424 BPI	
CONFIGURATION (MAG TAPE)	FIELD TRACE NOS.: _____ DATA CHANNEL NOS.: _____				RECORD NUMBERS: <input type="checkbox"/> DEC. <input type="checkbox"/> OCT.				
PARAMETER	RECORD LENGTH: _____ sec	SAMPLE RATE: <input type="checkbox"/> 1 ms. <input type="checkbox"/> 4 ms. <input type="checkbox"/> 2 ms. <input type="checkbox"/> _____ ms.	GAIN MODE: <input type="checkbox"/> INITIAL <input type="checkbox"/> MANUAL <input type="checkbox"/> IFF <input type="checkbox"/> OPERATE		AUXILIARY DATA: (1) _____ (2) _____ (3) _____ (4) _____ (5) _____ (6) _____ (7) _____				
DISPLAY	MODE: <input type="checkbox"/> AGC <input type="checkbox"/> FLOAT <input type="checkbox"/> AMPLIFIER <input type="checkbox"/> DEFOAT <input type="checkbox"/> DIRECT	INITIAL GAIN: _____ db	TRIP SENS: _____ db		AUXILIARY CHANNEL NOS.: _____				
CFS I	TYPE STACK: _____	GATE LENGTH: _____	RECORD REJECTION: _____		FILTERS: _____ LO CUT _____ HZ SLOPE _____ HI CUT _____ HZ SLOPE _____ PRESSURE INCREASE ON GEOPHONE: <input type="checkbox"/> NEGATIVE <input type="checkbox"/> POSITIVE } NUMBERS ON MAG. TAPE <input type="checkbox"/> DOWNBREAK <input type="checkbox"/> UPBREAK } ON DISPLAY NOISE REDUCTION: _____ NOISE THRESHOLD: _____ CORR. SCALING: _____ R.C.U. NORM./ALT SW: _____				
SOURCE	TYPE: <input type="checkbox"/> DYNAMITE <input type="checkbox"/> VIBROSEIS <input type="checkbox"/> OTHER	PATTERN: _____	NO. OF POSITIONS: _____	INLINE SPACING: _____	LATERAL SPACING: _____	STAGGER: _____	LENGTH: _____	WIDTH: _____	LATERAL OFFSET: _____
RECEIVER	TYPE: _____	PATTERN: _____	RESISTANCE: _____ ohms	STAGGER: _____	LENGTH: _____	WIDTH: _____	LATERAL OFFSET: _____		
SPREAD	NO. OF GROUPS: _____	GROUP INTERVAL: _____	SHOTPOINT INTERVAL: _____	FOLD: _____	DIRECTION OF PROGRESSION: _____				

DIAGRAMS/MISC. INFORMATION: _____

SHOTPOINT	TR _____ to _____		TR _____ to _____		SHOT				DIR.	CDP SWITCH	SPREAD LINE GROUPS	SET UP	REMARKS:	CORR. STACK			
	REEL NO.	REC.	REEL NO.	REC.	SIZE	DEPTH	NO.	OFFSET						TR 1-24	TR 25-48	TR 49-96	REC.
166	981037	94			110	105	41			21	153+1 - 176+4	4	49-96 started after 6 sec TR 4 REV TR 25 NOISY				
166		95			110	105	42			25	154+1 - 177+4		TR 21 NOISY				
167		96			110	105	43			29	155+1 - 178+4		" 17 "				
168		97			110	105	44			33	156+1 - 179+4						
169		98			110	105	45	35 N		37	157+1 - 180+4						
170		99			110	105	46	30 W		41	158+1 - 181+4						
171		100			110	105	47	30 W		45	159+1 - 182+4						
172	984037	101			110	105	48	50 SE		49	160+1 - 183+4						
173	984038	103			110	105	49			5	161+1 - 184+4	5	Recorder @ SP-178				
174		104			110	105	50	110 S		9	162+1 - 185+4		File #102 All ONES				
175		105			110	105	51	35 W		13	163+1 - 186+4						
176		106			110	105	52			17	164+1 - 187+4						
177		107			110	105	53			21	165+1 - 188+4						
178		108			110	105	54	30 E		25	166+1 - 189+4						
179		109			110	105	55			29	167+1 - 190+4						
180		110			110	105	56	100 S		33	168+1 - 191+4						
181		111			110	105	57			37	169+1 - 192+4		TR 96 Noisy (42+4) (on bare rock)				
182		112			110	105	58	30 N		41	170+1 - 193+4		92 "				
183		113			110	105	59			45	171+1 - 194+4		88 "				
184		114			110	105	60			49	172+1 - 195+4		84 "				

LAND SEISMIC RECORDING LOG

Page 4 of 5

	CLIENT: Husky	PROSPECT: NPR-4	AREA: Foothills Thrust	LINE NO: 760	
	PARTY NO: 1186	INST. ENG: R. Scheel		DATE: MO 2 DAY 15 YR 80	


INSTRUMENT	<input type="checkbox"/> 1 SYSTEM <input type="checkbox"/> 2 SYSTEMS	<input type="checkbox"/> 1-24 & 25-48 <input type="checkbox"/> 1-48 & 49-96	ODDS EVENS	TYPE: <input type="checkbox"/> DPS III <input type="checkbox"/> DPS IX	<input type="checkbox"/> DPS X <input type="checkbox"/> OTHER	<input type="checkbox"/> 9 TRACK <input type="checkbox"/> 21 TRACK	FOPMAT: _____ SEG: _____	<input type="checkbox"/> GAPPED <input type="checkbox"/> UNGAPPED	PACKING DENSITY: (LO) <input type="checkbox"/> 356 BPI <input type="checkbox"/> 800 BPI	(HI) <input type="checkbox"/> 712 BPI <input type="checkbox"/> 1600 BPI				
(9-TRACK)	NO. BYTES IN HEADER REC:	NO. BYTES IN RECORD ID:	NO. BYTES PER SCAN:	RECORD NUMBERS:	<input type="checkbox"/> DEC. <input type="checkbox"/> OCT.	GAIN CONSTANT: _____ db	INPUT IMPEDANCE: _____ ohms	(1)	(2)	(3)	(4)	(5)	(6)	(7)
CONFIGURATION (MAG TAPE)	FIELD TRACE NOS.:				AUXILIARY DATA:				AUXILIARY CHANNEL NOS.:					
PARAMETER	RECORD LENGTH: _____ sec	SAMPLE RATE: <input type="checkbox"/> 1 ms. <input type="checkbox"/> 4 ms. <input type="checkbox"/> 2 ms. <input type="checkbox"/> _____ ms.	GAIN MODE: <input type="checkbox"/> INITIAL <input type="checkbox"/> MANUAL <input type="checkbox"/> IFP <input type="checkbox"/> FINAL <input type="checkbox"/> OPERATE	FILTERS: _____		LO CUT HZ SLOPE: _____	FREQ: _____	HI CUT HZ SLOPE: _____	NOTCH FILTER: <input type="checkbox"/> IN <input type="checkbox"/> OUT					
DISPLAY	<input type="checkbox"/> MODE: <input type="checkbox"/> FLOAT <input type="checkbox"/> AMPLIFIER <input type="checkbox"/> AGC <input type="checkbox"/> DEFLOAT <input type="checkbox"/> DIRECT	INITIAL GAIN: _____ db	TRIP SENS: _____ db	POLARITY CONVENTION: _____		PRESSURE INCREASE ON GEOPHONE: <input type="checkbox"/>	<input type="checkbox"/> NEGATIVE <input type="checkbox"/> POSITIVE	NUMBERS ON MAG. TAPE: <input type="checkbox"/>	<input type="checkbox"/> DOWNBREAK <input type="checkbox"/> UPBREAK	ON DISPLAY				
CFS I	TYPE STACK: _____	GATE LENGTH: _____	RECORD REJECTION: _____	NOISE REDUCTION: _____		NOISE THRESHOLD: _____	CORR. SCALING: _____	P.C.U. NORM./ALT SW.						
SOURCE	<input type="checkbox"/> DYNAMITE <input type="checkbox"/> VIBROSEIS <input type="checkbox"/> OTHER	PATTERN: _____	NO. OF POSITIONS: _____	INLINE SPACING: _____	LATERAL SPACING: _____	STAGGER: _____	LENGTH: _____	WIDTH: _____	LATERAL OFFSET: _____					
RECEIVER	TYPE: _____	PATTERN: _____	NO. OF ELEMENTS: _____	INLINE SPACING: _____	LATERAL SPACING: _____	STAGGER: _____	LENGTH: _____	WIDTH: _____	LATERAL OFFSET: _____					
SPREAD	NO. OF GROUPS: _____	GROUP INTERVAL: _____	SHOTPOINT INTERVAL: _____	FOLD: _____	DIRECTION OF PROGRESSION: _____					LEADING GROUP: _____				

DIAGRAMS/MISC. INFORMATION:

SHOTPOINT	TR _____ to _____		TR _____ to _____		SHOT									SPREAD		REMARKS:	CORR. STACK				
	REEL NO.	REC.	REEL NO.	REC.	SIZE	DEPTH	NO.	OFFSET	DIR.	CDP SWITCH	LINE GROUPS		STAGGER	TR 1-48	TR 49-96		REC	TR 1-48	TR 49-96	REC	
1185	884038	1115			119	105	61				5	173+1	-	196+4	6	Recorder @ SP 190 TR 80 NOISY					TRI DEAD
1186		1116			119	105	62				9	174+1	-	197+4		" 76 "					
1187		1117			119	105	63				23	175+1	-	198+4		" 72 "					
1188		1118			105	64	90 NW	123			17	176+1	-	199+4		" 68 "					
1189		1119			105	65	175 SE	124			21	177+1	-	200+4		" 64 "					
1190		1120			105	66	50 S	25			25	178+1	-	201+4		" 60 "					
1191		1121			105	67	60 S	29			29	179+1	-	202+4		" 56 "					TRI Dead
1192		1122			105	68	175 SE	33			33	180+1	-	203+4		" 52 "					
1193		1123			105	69	30 N	37			37	181+1	-	204+4		" 48 "					
1194		1124			105	70	65 S	41			41	182+1	-	205+4		" 44 "					
1195		1125			105	71	110 NW	45			45	183+1	-	206+4		" 40 "					
1196		1126			105	72		49			49	184+1	-	207+4		" 36 "					
1197		1127			105	73	180 S	5			5	185+1	-	208+4	7	Recorder @ SP 202 32 NOISY					
1198		1128			105	74	30 W	9			9	186+1	-	209+4		49-96 SLASH " 28 "					
1199		1129			105	75		13			13	187+1	-	210+4		" 24 "					
1200					105	76		17			17	188+1	-	211+4		FN 130NG; BOTH CAPS BAD. TOBE RE-DRILLED + SHOT 7/16					
1201		1131			105	77		21			21	189+1	-	212+4		" 16 NOISY					
1202		1132			105	78		25			25	190+1	-	213+4							
1203		1133			105	79		29			29	191+1	-	214+4							
1204		1134			110	105	80	30 E			33	192+1	-	215+4							

LAND SEISMIC RECORDING LOG



CLIENT: Husky		PROSPECT: NPR-4		AREA: FootHills Thrust		LINE NO: 760					
PARTY NO: 1186		INST. ENG: R. Scheel		DATE: MO 2 DAY 16 YR 80		FILE: 139 All ones; Files 140-1 NG; Files 142-152 Daily Tests					
INSTRUMENT (9-TRACK): <input checked="" type="checkbox"/> 1 SYSTEM <input type="checkbox"/> 1-24 & 25-48 <input type="checkbox"/> 2 SYSTEMS <input checked="" type="checkbox"/> 48 & 49-96 <input type="checkbox"/> ODD EVENTS		TYPE: <input type="checkbox"/> DFS III <input type="checkbox"/> DFS IV <input type="checkbox"/> OTHER		<input checked="" type="checkbox"/> TRACK <input type="checkbox"/> 21 TRACK <input type="checkbox"/> FOPMAT: SEG		<input type="checkbox"/> GAPPED <input type="checkbox"/> UNGAPPED PACKING DENSITY: (LO) <input type="checkbox"/> 356 BPI (HI) <input type="checkbox"/> 712 BPI <input type="checkbox"/> 1400 BPI		NO. BYTES IN HEADER REC: 228 NO. BYTES IN RECORD ID: 24 NO. BYTES PER SCAN: 254		RECORD NUMBERS: <input type="checkbox"/> DEC <input type="checkbox"/> OCT GAIN CONSTANT: 36 db INPUT IMPEDANCE: 20,000 ohms.	
CONFIGURATION (MAG TAPE): FIELD TRACE NOS.: 1-96		DATA CHANNEL NOS.: 5-100 (ON MAG TAPE)		AUXILIARY DATA: TW SPS TB EM 15		AUXILIARY CHANNEL NOS.: 0 1 2 3 4		(6) (17)		(1) (17)	
PARAMETER: RECORD LENGTH: 8 sec. SAMPLE RATE: <input type="checkbox"/> 1 ms. <input type="checkbox"/> 4 ms. GAIN MODE: <input type="checkbox"/> INITIAL <input type="checkbox"/> MANUAL <input type="checkbox"/> OPERATE		FILTERS: FREQ: 8 LO CUT: 12 HI CUT: 70 NOTCH FILTER: <input type="checkbox"/> IN <input checked="" type="checkbox"/> OUT		DISPLAY: MODE: <input type="checkbox"/> FLOAT <input type="checkbox"/> AMPLIFIER <input type="checkbox"/> DEFLOAT <input type="checkbox"/> DIRECT INITIAL GAIN: 0 db		POLARITY CONVENTION: Pos PRESSURE INCREASE ON GEOPHONE: <input type="checkbox"/> NEGATIVE <input checked="" type="checkbox"/> POSITIVE NUMBERS ON MAG TAPE: <input type="checkbox"/> SWTBREAK <input type="checkbox"/> UPBREAK ON DISPLAY		CFS I: TYPE STACK: Stand-Alone RECORD REJECTION: NOISE REDUCTION: NOISE THRESHOLD: CORR. SCALING: R.C.U. NORM/ALT SW.			
SOURCE: <input checked="" type="checkbox"/> DYNAMITE <input type="checkbox"/> VIBROSEIS <input type="checkbox"/> OTHER		PATTERN: Single Hole		NO. OF POSITIONS: INLINE SPACING: LATERAL SPACING:		STAGGER: LENGTH: WIDTH: LATERAL OFFSET:		CHG/HOLE: 110 HOLE DEPTH: 105 SWEEP POSITION: SWEEP START: SWEEP END:		SWEEP LENGTH: SWEEP TAPER: PHASE COMP.	
RECEIVER: TYPE: 20D		PATTERN: In-line		NO. OF ELEMENTS: 18		INLINE SPACING: 6'		LATERAL SPACING:		STAGGER: LENGTH: WIDTH: LATERAL OFFSET:	
CONNECTION: Series/Parallel		RESISTANCE: 560 ohms		STAGGER:		LENGTH: 110'		WIDTH:		LATERAL OFFSET:	
SPREAD: NO. OF GROUPS: 96		GROUP INTERVAL: 110'		SHOTPOINT INTERVAL: 440'		FOLD: 12		DIRECTION OF PROGRESSION: S		LEADING GROUP: 96	
OFFSET GROUP 1: 5225'		OFFSET GROUP 48: 55'		OFFSET GROUP 49: 55'		OFFSET GROUP 96: 5225'					



SHOTPOINT	TR 1 to		TR 17 to		SHOT				SPREAD		REMARKS	CORR STACK			
	REEL NO	REC.	REEL NO	REC.	SIZE	DEPTH	NO.	OFFSET	DIR	CDP SWITCH		LINE GROUPS	HT.	TR 1-48 REC.	TR 49-96 REC.
200	184039	154	17	2225	110		1			17	182+1 - 211+4	1			
209		158					2			5	192+1 - 220+4	2			
210		157					3	150 S		9	198+1 - 221+4				
211		158					4	30 E		13	199+1 - 222+4				
212		159					5			17	200+1 - 223+4				
213		160					6	75 NW	49	21	201+1 - 224+4				
214		161					7	40 N	25	202+1 - 225+4					
215		162					8		29	203+1 - 226+4					
216		163					9		33	204+1 - 227+4					
217		164					10		37	205+1 - 228+4					
218		165					11	25 S	41	206+1 - 229+4					
219		166					12		45	207+1 - 230+4					
220		167					13	130 W	49	208+1 - 231+4					
221		168					14	110 N	5	209+1 - 232+4	3				
222		169					15	60 W	9	210+1 - 233+4					
223		170					16	75 NW	13	211+1 - 234+4					
224		171					17	75 NW	17	212+1 - 235+4					
225		172					18		21	213+1 - 236+4					
226		173					19	40 E	25	214+1 - 237+4					
228		174					20	250 N	29	215+1 - 238+4					

LAND SEISMIC RECORDING LOG

Page 2 of 2

	CLIENT: Husky	PROSPECT: NPR-4	AREA: Foothills Thrust	DATE: MO 2 DAY 16 YR 80									
PARTY NO: 1186		INST. ENG: R. Scheel		LOG NO: 760									
INSTRUMENT (9-TRACK)	<input type="checkbox"/> 1 SYSTEM <input type="checkbox"/> 2 SYSTEMS	<input type="checkbox"/> 1-24 & 25-48 <input type="checkbox"/> 1-48 & 49-96	<input type="checkbox"/> ODDS <input type="checkbox"/> EVENS	TYPE: <input type="checkbox"/> DFS III <input type="checkbox"/> DFS IV <input type="checkbox"/> OTHER	<input type="checkbox"/> 9 TRACK <input type="checkbox"/> 21 TRACK	FORMAT: <input type="checkbox"/> SEG	<input type="checkbox"/> GAPPED <input type="checkbox"/> UNGAPPED	PACKING DENSITY:	(LO) <input type="checkbox"/> 356 BPI <input type="checkbox"/> 800 BPI	(HI) <input type="checkbox"/> 712 BPI <input type="checkbox"/> 1600 BPI			
	NO. BYTES IN HEADER REC:	NO. BYTES IN RECORD ID:	NO. BYTES PER SCAN:	RECORD NUMBERS: <input type="checkbox"/> DEC. <input type="checkbox"/> OCT	GAIN CONSTANT: _____ db	INPUT IMPEDANCE: _____ ohms	(1)	(2)	(3)	(4)	(5)	(6)	(7)
CONFIGURATION (MAG TAPE)	FIELD TRACE NOS: _____			AUXILIARY DATA:			AUXILIARY CHANNEL NOS.:						
PARAMETER	RECORD LENGTH: _____ sec.	SAMPLE RATE: <input type="checkbox"/> 1 ms. <input type="checkbox"/> 4 ms. <input type="checkbox"/> 2 ms. <input type="checkbox"/> _____ ms.	GAIN MODE: <input type="checkbox"/> INITIAL <input type="checkbox"/> IFF	FILTERS: _____		LO CUT HZ SLOPE	FREQ. _____	HI CUT HZ SLOPE	NOTCH FILTER: <input type="checkbox"/> IN <input type="checkbox"/> OUT				
DISPLAY	MODE: <input type="checkbox"/> FLOAT <input type="checkbox"/> AMPLIFIER <input type="checkbox"/> ACC <input type="checkbox"/> DEFLOAT <input type="checkbox"/> DIRECT	INITIAL GAIN: _____ db	TRIP SENS: _____ db	POLARITY CONVENTION: _____		PRESSURE INCREASE ON GEOPHONE: _____	<input type="checkbox"/> NEGATIVE <input type="checkbox"/> POSITIVE	NUMBERS ON MAG TAPE	<input type="checkbox"/> DOWNBREAK <input type="checkbox"/> UPBREAK	ON DISPLAY			
CFS I	TYPE STACK:	GATE LENGTH:	RECORD REJECTION:	NOISE REDUCTION:	NOISE THRESHOLD:	CORR. SCALING:	R.C.U. NORM./ALT SW.						
SOURCE	TYPE: <input type="checkbox"/> DYNAMITE <input type="checkbox"/> VIBROSEIS <input type="checkbox"/> OTHER	PATTERN:	NO. OF POSITIONS:	INLINE SPACING:	LATERAL SPACING:	STAGGER:	LENGTH:	WIDTH:	LATERAL OFFSET:				
RECEIVER	CONNECTION:	RESISTANCE: _____ ohms	STAGGER:	LENGTH:	WIDTH:	LATERAL OFFSET:							
SPREAD	NO. OF GROUPS:	GROUP INTERVAL:	SHOTPOINT INTERVAL:	OFFSET GROUP:	OFFSET GROUP:	FOLD:	OFFSET GROUP 48/96:	DIRECTION OF PROGRESSION:					

DIAGRAMS/MISC. INFORMATION:

SHOTPOINT	TR _____ to _____		TR _____ to _____		SHOT								SPREAD		REMARKS:	CORR STACK			
	REEL NO.	REC.	REEL NO.	REC.	SIZE	DEPTH	NO.	OFFSET	DIR.	CDP SWITCH	LINE GROUPS		SET	HI		TR 1-28	REC.	TR 48-96	REC.
228	984039	175			110		21	150	SE	106	33	216+1	-T16	3	SP 228-230 over bare rock				
229		176					22	150	S		37	212+1	-T20						
230		177					23	150	SW		41	218+1	-T24						
231		178					24	150	SW	35	45	219+1	-T28						
232		179					25	110	N		49	220+1	-T32						
233		180					26	85	W		29	221+1	-T36	4	Recorder @ SP 232				
234		181					27	40	W		33	222+1	-T40						
235		182					28	25	W		37	223+1	-T44						
236		183					29	100	SW	71	41	224+1	-T48						