

LAND SEISMIC RECORDING LOG

| | | | | | |
|--|------------------------|---------------------------|----------------------|-----------------------------|--|
| | CLIENT: Husky | PROSPECT: NPR-A | AREA: TUNALIK | LINE NO.: D4XW | |
| | PARTY NO.: 1182 | INST. ENG.: Stieff | | DATE: 1 DAY 16 YR 80 | |


| | | | | | | | | |
|----------------------|---|---|---------------------|--|---|------------------------------|--|---|
| INSTRUMENT (9-TRACK) | <input type="checkbox"/> 1 SYSTEM <input type="checkbox"/> 2 SYSTEMS | <input checked="" type="checkbox"/> 24 & 25-48 <input type="checkbox"/> 1-48 & 49-96 | ODDS EVENS | TYPE: <input type="checkbox"/> DFS III <input type="checkbox"/> DFS IV <input type="checkbox"/> DFS V <input type="checkbox"/> OTHER | <input type="checkbox"/> TRACK <input type="checkbox"/> 21 TRACK | FORMAT: B | <input type="checkbox"/> GAPPED <input type="checkbox"/> UNGAPPED | PACKING DENSITY: (LO) <input type="checkbox"/> 356 BPI <input type="checkbox"/> 800 BPI (HI) <input type="checkbox"/> 712 BPI <input type="checkbox"/> 1400 BPI |
| | NO. BYTES IN HEADER REC: | NO. BYTES IN RECORD ID: | NO. BYTES PER SCAN: | RECORD NUMBERS: <input type="checkbox"/> DEC. <input type="checkbox"/> OCT. | GAIN CONSTANT: (1) (2) (3) (4) (5) (6) (7) | INPUT IMPEDANCE: _____ ohms. | | |

| | | |
|--------------------------|--|---|
| CONFIGURATION (MAG TAPE) | FIELD TRACE NOS.: 1-48 | AUXILIARY DATA: |
| | DATA CHANNEL NOS.: 1-48 (ON MAG TAPE) | AUXILIARY CHANNEL NOS.: |
| PARAMETER | RECORD LENGTH: 6 sec. | SAMPLE RATE: <input type="checkbox"/> 1 ms. <input type="checkbox"/> 4 ms. <input type="checkbox"/> 8 ms. |
| DISPLAY | MODE: <input type="checkbox"/> FLOAT <input type="checkbox"/> AMPLIFIER <input type="checkbox"/> DEFLOAT <input type="checkbox"/> DIRECT | INITIAL GAIN: 24 db |
| CFS I | TYPE STACK: | GATE LENGTH: |

| | | | | | | | | | |
|--------|---|-----------------------------|-----------------------|-----------------|------------------|------------|---------------|--------------|-----------------|
| SOURCE | TYPE: <input type="checkbox"/> DYNAMITE <input type="checkbox"/> VIBROSEIS <input type="checkbox"/> OTHER | PATTERN: inline/hole | NO. OF POSITIONS: | INLINE SPACING: | LATERAL SPACING: | STAGGER: | LENGTH: | WIDTH: | LATERAL OFFSET: |
| | | CHG/ HOLE: 50 | HOLE DEPTH: 75 | SWEEP POSITION: | SWEEP START: | SWEEP END: | SWEEP LENGTH: | SWEEP TAPER: | PHASE COMP: |



| | | | | | | | | | |
|----------|------------------------------------|-----------------------------|----------------------------|---------------------------|------------------|-----------------|---------|--------|-----------------|
| RECEIVER | TYPE: 20-D | PATTERN: inline | NO. OF ELEMENTS: 12 | INLINE SPACING: 28 | LATERAL SPACING: | STAGGER: | LENGTH: | WIDTH: | LATERAL OFFSET: |
| | CONNECTION: Series-Parallel | RESISTANCE: 580 ohms | STAGGER: | LENGTH: | WIDTH: | LATERAL OFFSET: | | | |

| | | | | | |
|--------|-----------------------------|-----------------------------|---------------------------------|---------------------------------|---------------------------------------|
| SPREAD | NO. OF GROUPS: 48 | GROUP INTERVAL: 330 | SHOTPOINT INTERVAL: 1320 | FOLD: 6 | DIRECTION OF PROGRESSION: West |
| | OFFSET GROUP 1: 8085 | OFFSET GROUP 24: 495 | OFFSET GROUP 25: 495 | OFFSET GROUP 48/96: 8085 | LEADING GROUP: 48 |



| SHOTPOINT | TR _____ to _____ | | TR _____ to _____ | | SHOT | | | SPREAD | | | REMARKS: | CORR. STACK | | |
|-----------|-------------------|------|-------------------|------|------|-------|-----|--------|------|------------|-------------|-------------|--------|---------|
| | REEL NO. | REC. | REEL NO. | REC. | SIZE | DEPTH | NO. | OFFSET | DIR. | CDP SWITCH | | LINE GROUPS | SET UP | TR 1-48 |
| 1 | 981006 | 2 | 22 | 23 | 50 | 60 | 12 | | | 40 | T-1 - 7+1 | 3 | | |
| 2 | | 3 | | | 50 | 60 | 13 | | | 44 | T-4 - 8+1 | | | |
| 3 | | 4 | | | 50 | 60 | 14 | | | 48 | T-8 - 9+1 | | | |
| 4 | | 5 | | | 50 | 60 | 15 | | | 52 | T-12 - 10+1 | | | |
| 5 | | 6 | | | 50 | 60 | 16 | | | 56 | T-16 - 11+1 | | | |
| 6 | | 7 | | | 50 | 60 | 17 | | | 60 | T-20 - 12+1 | | | |
| 7 | | 8 | | | 50 | 60 | 18 | | | 64 | T-24 - 13+1 | | | |
| 8 | | 9 | | | 50 | 60 | 19 | | | 68 | 1+4 - 14+1 | | | |
| 9 | | 10 | | | 50 | 60 | 20 | | | 72 | 2+4 - 15+1 | 15 | | |
| 10 | | 11 | | | 50 | 60 | 21 | | | 76 | 3+4 - 16+1 | | | |
| 11 | | 12 | | | 50 | 60 | 22 | 330 W | | 80 | 4+4 - 17+1 | | | |
| 12 | | 13 | | | 50 | 60 | 23 | | | 84 | 5+4 - 18+1 | | | |
| 13 | | 14 | | | 50 | 60 | 24 | | | 88 | 6+4 - 19+1 | | | |
| 14 | | 15 | | | 50 | 60 | 25 | | | 92 | 7+4 - 20+1 | | | |
| 15 | | 16 | | | 50 | 60 | 26 | | | 96 | 8+4 - 21+1 | | | |
| 16 | | 17 | | | 50 | 60 | 27 | | | 100 | 9+4 - 22+1 | | | |
| 17 | | 18 | | | 50 | 60 | 28 | | | 104 | 10+4 - 23+1 | | | |
| | | | | | | | 29 | | | | | | | |
| | | | | | | | 30 | | | | | | | |
| | | | | | | | 31 | | | | | | | |

LAND SEISMIC RECORDING LOG

| | | | | | |
|--|----------------------|--------------------------|----------------------|--------------------------------|---|
|  | CLIENT: HUSKY | PROSPECT: NPR-A | AREA: TUNALIK | LINE NO: D4XW |  |
| PARTY NO: 1182 | | INST. ENG: Streff | | DATE: MO 1 DAY 17 YR 80 | |

| | | | | | | | | | | | |
|--------------------------|---|---|---|---|-------------------------|---|---|-------------------------|--|-----------------------------|--|
| INSTRUMENT (9-TRACK) | <input checked="" type="checkbox"/> SYSTEM <input checked="" type="checkbox"/> 2 SYSTEMS <input type="checkbox"/> 24 & 25-48 <input type="checkbox"/> 1-48 & 49-96 | <input type="checkbox"/> ODDS <input type="checkbox"/> EVENS | TYPE: <input type="checkbox"/> DFS III <input type="checkbox"/> DFS IV <input type="checkbox"/> OTHER | <input type="checkbox"/> TRACK <input type="checkbox"/> 21 TRACK | FOPMAT: B SEG | <input type="checkbox"/> GAPPED <input type="checkbox"/> UNGAPPED | PACKING DENSITY: (LO) <input type="checkbox"/> 356 BPI <input type="checkbox"/> 800 BPI (HI) <input type="checkbox"/> 712 BPI <input type="checkbox"/> 1600 BPI | | | | |
| NO. BYTES IN HEADER REC: | | NO. BYTES IN RECORD ID: | | NO. BYTES PER SCAN: | | RECORD NUMBERS: <input type="checkbox"/> DEC. <input type="checkbox"/> OCT. | | GAIN CONSTANT: _____ db | | INPUT IMPEDANCE: _____ ohms | |

| | | |
|-----------------------------|--------------------------------|-------------------------|
| CONFIGURATION (MAG TAPE) | FIELD TRACE NOS.: 1-48 | AUXILIARY DATA: |
| | DATA CHANNEL NOS.: 1-48 | AUXILIARY CHANNEL NOS.: |

| | | | | |
|-----------|---|--|---|--|
| PARAMETER | RECORD LENGTH: 6 sec. | SAMPLE RATE: <input type="checkbox"/> 1 ms. <input type="checkbox"/> 4 ms. <input type="checkbox"/> 1/2 ms. <input type="checkbox"/> ms. | GAIN MODE: <input checked="" type="checkbox"/> OFF <input type="checkbox"/> INITIAL <input type="checkbox"/> FINAL <input type="checkbox"/> MANUAL <input type="checkbox"/> OPERATE | FILTERS: FREQ. 80 HZ SLOPE 18 LO CUT HZ SLOPE 70 HI CUT HZ SLOPE 70 NOTCH FILTER: <input type="checkbox"/> IN <input type="checkbox"/> OUT |
| DISPLAY | MODE: <input checked="" type="checkbox"/> MAGC <input type="checkbox"/> FLOAT <input type="checkbox"/> DEFLOAT <input type="checkbox"/> AMPLIFIER <input type="checkbox"/> DIRECT | INITIAL GAIN: 24 db | TRIP SENS: 3 db | POLARITY CONVENTION: <input checked="" type="checkbox"/> POSITIVE <input type="checkbox"/> NEGATIVE } NUMBERS ON ON MAG. TAPE <input type="checkbox"/> DOWNBREAK <input type="checkbox"/> UPBREAK } ON DISPLAY |
| CFS I | TYPE STACK: | GATE LENGTH: | RECORD REJECTION: | NOISE REDUCTION: NOISE THRESHOLD: CORR. SCALING: R.C.U. NORM./ALT SW. |

| | | | | | | | | | |
|--------|--|-------------------------------|-------------------|-----------------|------------------|---------------|--------------|-------------|-----------------|
| SOURCE | TYPE: <input checked="" type="checkbox"/> DYNAMITE <input type="checkbox"/> VIBROSEIS <input type="checkbox"/> OTHER | PATTERN: 1/4 line/hole | NO. OF POSITIONS: | INLINE SPACING: | LATERAL SPACING: | STAGGER: | LENGTH: | WIDTH: | LATERAL OFFSET: |
| | CHG/HOLE: 50 | HOLE DEPTH: 75 | SWEEP POSITION: | SWEEP START: | SWEEP END: | SWEEP LENGTH: | SWEEP TAPER: | PHASE COMP: | |

| | | | | | |
|----------|------------------------------------|-----------------------------|------------------|-----------------|------------------------|
| RECEIVER | TYPE: 20-0 | PATTERN: inline | NO. OF ELEMENTS: | INLINE SPACING: | LATERAL SPACING: |
| | CONNECTION: Series-Parallel | RESISTANCE: 580 ohms | STAGGER: | LENGTH: | WIDTH: LATERAL OFFSET: |

| | | | | | |
|--------|-----------------------------|----------------------------|---------------------------------|---------------------------------|---------------------------------------|
| SPREAD | NO. OF GROUPS: 48 | GROUP INTERVAL: 330 | SHOTPOINT INTERVAL: 1320 | FOLD: 6 | DIRECTION OF PROGRESSION: West |
| | OFFSET GROUP 1: 8085 | OFFSET GROUP 2: 495 | OFFSET GROUP 25: 495 | OFFSET GROUP 48/96: 8085 | LEADING GROUP: 48 |

DIAGRAMS/MISC. INFORMATION:
 11+4 X $\frac{17+3}{X0}$ $\frac{18+2}{0}$ $\frac{24+1}{X}$ #30 test TD
 TR#1 SP-18 TR#48

| SHOTPOINT | TR _____ to _____ | | TR _____ to _____ | | SHOT | | | | | | | | | | SPREAD | | REMARKS | CORR. STACK | | | |
|------------|-------------------|------|-------------------|------|------|-------|-----|--------|------|------------|-------------|--|--------|---------|----------|---------|---------|------------------|--|--|--|
| | REEL NO. | REC. | REEL NO. | REC. | SIZE | DEPTH | NO. | OFFSET | DIR. | CDP SWITCH | LINE GROUPS | | SET UP | TR 1-48 | TR 48-96 | TR 1-48 | | TR 48-96 | | | |
| 18 | 981006 | 131 | | | 50 | 60 | 1 | | | 24 | 11+4 - 24+1 | | 24 | | | | | | | | |
| 19 | | 132 | | | 50 | 60 | 2 | | | 28 | 12+4 - 25+1 | | | | | | | | | | |
| 20 | | 133 | | | 50 | 60 | 3 | 660 W | | 32 | 13+4 - 26+1 | | | | | | | | | | |
| 21 | | 134 | | | 50 | 60 | 4 | | | 36 | 14+4 - 27+1 | | | | | | | | | | |
| 22 | | 135 | | | 50 | 60 | 5 | | | 40 | 15+4 - 28+1 | | | | | | | | | | |
| 23 | | 136 | | | 50 | 60 | 6 | | | 44 | 16+4 - 29+1 | | | | | | | | | | |
| 24 | | 137 | | | 50 | 60 | 7 | | | 48 | 17+4 - 30+1 | | | | | | | | | | |
| 25 | | 138 | | | 50 | 60 | 8 | | | 52 | 18+4 - 31+1 | | | | | | | | | | |
| 26 | | 139 | | | 50 | 60 | 9 | | | 24 | 19+4 - 32+1 | | 32 | | | | | | | | |
| 27 | | 140 | | | 50 | 60 | 10 | | | 28 | 20+4 - 33+1 | | | | | | | | | | |
| 28 | | 141 | | | 50 | 60 | 11 | | | 32 | 21+4 - 34+1 | | | | | | | | | | |
| 29 | | 142 | | | 50 | 60 | 12 | | | 36 | 22+4 - T-1 | | | | | | | | | | |
| 30 | | 143 | | | 50 | 60 | 13 | | | 40 | 23+4 - T-5 | | | | | | | | | | |
| 31 | | 144 | | | 50 | 60 | 14 | | | 44 | 24+4 - T-9 | | | | | | | | | | |
| 32 | | 145 | | | 50 | 60 | 15 | | | 48 | 25+4 - T-13 | | | | | | | | | | |
| 33 | | 146 | | | 50 | 60 | 16 | 165 W | | 52 | 26+4 - T-17 | | | | | | | | | | |
| 34 | | 147 | | | 50 | 60 | 17 | | | 56 | 27+4 - T-21 | | | | | | | | | | |
| 35 | | 148 | | | 50 | 60 | 18 | | | 60 | 28+4 - T-24 | | | | | | | TR# 45 + 48 dead | | | |
| END | | | | | | | | | | | | | | | | | | | | | |