

ORE \_\_\_\_\_  
 MIN. \_\_\_\_\_  
 BARREN

FAV. \_\_\_\_\_  
 UNFAV. \_\_\_\_\_

U.S.A.E.C.

HOLE NO. <sup>NC</sup> 105

PROJECT Delta #3

LOCALITY N. Chuska Mtn CLAIM \_\_\_\_\_

COLLAR ELEV. 7870.47 DEPTH \_\_\_\_\_

COORDINATES N 96573 E 2048.31

DATE COMPLETED 6-20-52

LOGGED BY R.L.R. DATE 6-21-52

$\frac{116.4}{125}$

RECOVERY 92.9 %

RECOVERY	GEOLOGIC COLUMN	COLOR	BEDDING	TEXTURE	GRAIN COATINGS	CARBON	ORE MINERALS	MISCELLANEOUS	DEPTH
								Scint KX10	
								0-100' Plug Bit No Core 100-285' N Core	
160									
170		Br		VF.					
175		Br		F					
180		Br		Sop					
185		R		F					
190				IF					
195		Gr		Sop				Ms Spt	
200		Br							
205								Rec SW Contact	
210								R46n Ms Spts each	
215		Br		F					
220		Br		Sop					
225									
230		R		F					
235		Br		Sop					
240									
245		Br		F					
250									
255		Br		Sop					
260									
265		Br		F					
270									
275		Br		Sop					
280									
285		Br		F					
290									
295		Br		Sop					
300									
305		Br		F					
310									
315		Br		Sop					
320									
325		Br		F					
330									
335		Br		Sop					
340									
345		Br		F					
350									
355		Br		Sop					
360									
365		Br		F					
370									
375		Br		Sop					
380									
385		Br		F					
390									
395		Br		Sop					
400									
405		Br		F					
410									
415		Br		Sop					
420									
425		Br		F					
430									
435		Br		Sop					
440									
445		Br		F					
450									
455		Br		Sop					
460									
465		Br		F					
470									
475		Br		Sop					
480									
485		Br		F					
490									
495		Br		Sop					
500									
505		Br		F					
510									
515		Br		Sop					
520									
525		Br		F					
530									
535		Br		Sop					
540									
545		Br		F					
550									
555		Br		Sop					
560									
565		Br		F					
570									
575		Br		Sop					
580									
585		Br		F					
590									
595		Br		Sop					
600									
605		Br		F					
610									
615		Br		Sop					
620									
625		Br		F					
630									
635		Br		Sop					
640									
645		Br		F					
650									
655		Br		Sop					
660									
665		Br		F					
670									
675		Br		Sop					
680									
685		Br		F					
690									
695		Br		Sop					
700									
705		Br		F					
710									
715		Br		Sop					
720									
725		Br		F					
730									
735		Br		Sop					
740									
745		Br		F					
750									
755		Br		Sop					
760									
765		Br		F					
770									
775		Br		Sop					
780									
785		Br		F					
790									
795		Br		Sop					
800									
805		Br		F					
810									
815		Br		Sop					
820									
825		Br		F					
830									
835		Br		Sop					
840									
845		Br		F					
850									
855		Br		Sop					
860									
865		Br		F					
870									
875		Br		Sop					
880									
885		Br		F					
890									
895		Br		Sop					
900									
905		Br		F					
910									
915		Br		Sop					
920									
925		Br		F					
930									
935		Br		Sop					
940									
945		Br		F					
950									
955		Br		Sop					
960									
965		Br		F					
970									
975		Br		Sop					
980									
985		Br		F					
990									
995		Br		Sop					
1000									

Hole Bottomed  
 Approx. Bluff 285' 287'