

ORE MIN. BARREN

FAV. UNFAV.

U.S.A.E.C.

HOLE NO. NC-382-A

PROJECT LuKe #3

LOCALITY N. Chuska Mtns CLAIM

COLLAR ELEV. 7944.5 DEPTH 240'

COORDINATES N. 96, 130 E. 202, 161

DATE COMPLETED 5-19-53

LOGGED BY D. M. DATE 5-20-53

51.8 RECOVERY 94.1%
55

RECOVERY	GEOLOGIC COLUMN	COLOR	BEDDING	TEXTURE	GRAIN COATINGS	CARBON	ORE MINERALS	MISCELLANEOUS	DEPTH
110									
120									
130									
140									
150									
160									
170									
180									
185									
190									
198									
200									
205									
210									
215									
220									
225									
230									
235	xxxxx								
240	xxxxx								
245	0000								
250	0000								
255	0000								
260	0000								
265	0000								
270	0000								
275	0000								
280	0000								
285	0000								
290	0000								
295	0000								
300	0000								
305	0000								
310	0000								
315	0000								
320	0000								
325	0000								
330	0000								
335	0000								
340	0000								
345	0000								
350	0000								
355	0000								
360	0000								
365	0000								
370	0000								
375	0000								
380	0000								
385	0000								
390	0000								
395	0000								
400	0000								
405	0000								
410	0000								
415	0000								
420	0000								
425	0000								
430	0000								
435	0000								
440	0000								
445	0000								
450	0000								
455	0000								
460	0000								
465	0000								
470	0000								
475	0000								
480	0000								
485	0000								
490	0000								
495	0000								
500	0000								
505	0000								
510	0000								
515	0000								
520	0000								
525	0000								
530	0000								
535	0000								
540	0000								
545	0000								
550	0000								
555	0000								
560	0000								
565	0000								
570	0000								
575	0000								
580	0000								
585	0000								
590	0000								
595	0000								
600	0000								
605	0000								
610	0000								
615	0000								
620	0000								
625	0000								
630	0000								
635	0000								
640	0000								
645	0000								
650	0000								
655	0000								
660	0000								
665	0000								
670	0000								
675	0000								
680	0000								
685	0000								
690	0000								
695	0000								
700	0000								
705	0000								
710	0000								
715	0000								
720	0000								
725	0000								
730	0000								
735	0000								
740	0000								
745	0000								
750	0000								
755	0000								
760	0000								
765	0000								
770	0000								
775	0000								
780	0000								
785	0000								
790	0000								
795	0000								
800	0000								
805	0000								
810	0000								
815	0000								
820	0000								
825	0000								
830	0000								
835	0000								
840	0000								
845	0000								
850	0000								
855	0000								
860	0000								
865	0000								
870	0000								
875	0000								
880	0000								
885	0000								
890	0000								
895	0000								
900	0000								
905	0000								
910	0000								
915	0000								
920	0000								
925	0000								
930	0000								
935	0000								
940	0000								
945	0000								
950	0000								
955	0000								
960	0000								
965	0000								
970	0000								
975	0000								
980	0000								
985	0000								
990	0000								
995	0000								
1000	0000								

Plug Bit 0-185' No Core

Approx Bluff = 7639 ↓ 6' down

382-A